Interrogating Paradigms in Self-supervised Graph Representation Learning

Abstract

Graph contrastive learning (GCL) is a newly popular paradigm for self-supervised graph representation learning and offers an alternative to reconstruction-based methods. However, it is not well understood what conditions a task must satisfy such that a given paradigm is better suited. In this paper, we investigate the role of dataset properties and augmentation strategies on the success of GCL and reconstruction-based approaches. Using the recent population augmentation graph-based analysis of self-supervised learning, we show theoretically that the success of GCL with popular augmentations is bounded by the graph edit distance between different classes. Next, we introduce a synthetic data generation process that systematically controls the amount of style vs. content in each sample- i.e. information that is irrelevant vs. relevant to the downstream task- to elucidate how graph representation learning methods perform under different dataset conditions. We empirically show that reconstruction approaches perform better when the style vs. content ratio is low and GCL with popular augmentations benefits from moderate style. Our results provide a general, systematic framework for analyzing different graph representation learning methods and demonstrate when a given approach is expected to perform well.

1 Introduction

Analyzing graph-structured data is essential for many real-world applications and graph neural networks (GNNs) have emerged as a popular solution for challenging prediction tasks. However, these tasks often have limited labeled data due to prohibitive procuration costs and require models to possess strong generalization abilities to be practically useful. For example, in molecular property prediction, obtaining training labels requires expensive wet lab experiments and, at test time, models must predict properties for novel candidate molecules (Hwang et al., 2020; Duvenaud et al., 2015; Zitnik et al., 2018). Unsupervised graph representation learning is a natural paradigm in such cases, where graph contrastive learning (GCL) is a promising approach over using pre-training tasks (Hu et al., 2020).

While recent findings (Arora et al., 2019; HaoChen et al., 2021; Tian et al., 2020; von Kügelgen et al., 2021; Zimmermann et al., 2021; Wang & Isola, 2020; Purushwalkam & Gupta, 2020) have investigated what makes for successful *visual* contrastive learning, a similar understanding remains lacking for GCL. Furthermore, in computer vision, reconstruction-based approaches using an autoencoder framework (Kingma & Welling, 2014), updated with modern encoder architectures and data augmentation, are emerging as an alternative paradigm that avoids negative sampling or large batch sizes (Falcon et al., 2021). Reconstruction-based approaches (Kipf & Welling, 2016) have not yet been similarly revisited with improved GNN architecture designs or augmentations for self-supervised graph representation learning. Moreover, due to complications arising from the discrete, non-Euclidean nature of graph datasets, analysis from visual contrastive learning (VCL) cannot be straightforwardly extended to a graph setting. Therefore, it remains unclear under what circumstances a reconstruction or CL-based approach is expected to perform well on a given task.

In this paper, we investigate, theoretically and empirically, the conditions that enable a given unsupervised learning approach to perform well. Specifically, we first show theoretically that the success of GCL with generic graph augmentations (GGA) introduced by GraphCL (You et al., 2020a) is dependent on the graph edit distance between classes. Next, we address the elephant in the room:

that *untrained* GNNs have enough inductive bias to nullify the benefits of unsupervised pre-training on benchmark graph classification datasets. Therefore, we introduce a carefully designed synthetic dataset and conduct an extensive evaluation to better understand the behavior of both reconstruction and CL approaches. Here, we demonstrate that the effectiveness of different unsupervised approaches over strong untrained baselines can be understood through a style vs. content decomposition: the proportion of relevant information for a task (content) and irrelevant information (style) that each example in a dataset contains.

Our contributions are as follows:

- We provide theoretical analysis of when contrastive learning is expected to work well, showing that this depends on the graph edit distance of samples within and across classes.

- We systematically evaluate reconstruction as an alternative unsupervised paradigm to contrastive learning for graphs, including introducing augmentation-augmented graph autoencoders (AAGAE). Further, we empirically show to what extent untrained GNN models are a competitive baseline in terms of accuracy, invariance, and sample complexity.

- We identify a style vs. content trade-off in graphs and introduce an extensive benchmark setup that can carefully control this trade-off. Using our benchmark, we show how not only the ratio of style vs. content but also how generic versus content-aware augmentation impacts different learning paradigms.

2 BACKGROUND: UNSUPERVISED REPRESENTATION LEARNING FOR GNNS

While the general approach of pre-training can be either supervised (Hu et al., 2020)) or unsupervised, we focus on the latter. In this section, we formalize unsupervised representation learning for graphs and discuss two widely adopted approaches, namely graph contrastive learning and reconstruction-based learning. Appendix A.4 contains additional related work on self-supervised learning and data augmentation for graphs.

Graph Contrastive Learning. Contrastive learning (CL) frameworks learn representations by maximizing similarity between positive or augmented examples, and at the same time minimizing similarity between negative or uncorrelated examples. Formally, let $\overline{\mathcal{X}} = \{\overline{x}_1, \ldots, \overline{x}_n\}$ denote a dataset consisting of un-augmented (clean) samples, where each $\overline{x}_i = (G_i, F_i)$ corresponds to a tuple containing the adjacency matrix $G_i \in [0, 1]^{n \times n}$ and node feature matrix F_i. Let $\mathcal{A}$ represent a set of augmentations over $\overline{\mathcal{X}}$; namely the generic graph augmentations (GGA) introduced by (You et al., 2020a): (i) node dropping, (ii) edge perturbation, (iii) attribute masking and (iv) sub-graph sampling. Furthermore, let $\mathcal{X}$ be the set of all augmented samples given $\overline{\mathcal{X}}$, and $\{x_i = \mathcal{A}(\overline{x}_i), x_j = \mathcal{A}(\overline{x}_i)\}$ be considered a positive pair.

GraphCL parallels SimCLR (Chen et al., 2020a) and uses the normalized temperature scaled cross entropy (NT-XENT) loss to learn representations by contrasting the representations of positive pairs and negative samples. Specifically, let f be a graph feature learner, such that $f(x_i) = z_i \in \mathbb{R}^d$, e.g., a GNN with a global `READOUT` layer, *i.e.*, `READOUT` $: \mathbb{R}^{n \times d} \to \mathbb{R}^d$. Given batch size B, similarity function, sim$: (\mathbb{R}^d, \mathbb{R}^d) \to [0, 1]$, temperature parameter, τ, and positive pair, $\{x_i, x_j\}$, the NT-XENT loss is defined as:

$$\ell_{i,j} = -\log \frac{\exp\left(\text{sim}\left(z_i, z_j\right)/\tau\right)}{\sum_{k=1}^{2B} \mathbb{1}_{[k \neq i]} \exp\left(\text{sim}\left(z_i, z_k\right)/\tau\right)}. \tag{1}$$

Here, the numerator encourages the representations for x_i, x_j to have high similarity, while the denominator encourages representations of negative pairs ($k \neq i$) to have low similarity. By maximizing similarity between positive samples, we expect the representations to become invariant to the properties modified by augmentations. Correspondingly, models learn to perform instance discrimination where each sample defines its own class and the augmented samples also belong to this class. Other recent GCL frameworks follow this general formulation but differ in the choice of the objective function and the augmentation strategy. For example, InfoGraph (Sun et al., 2020) maximizes the mutual information between sampled subgraphs (local) and pooled graph (global) representations. MVGRL (Hassani & Ahmadi, 2020) contrasts representations of graphs augmented through diffusion processes at node and graph scales. While this work focuses on GraphCL, other formula-

tions including InfoGraph, DGI (Hjelm et al., 2019), and GMI (Peng et al., 2020), can be derived as instances of this general framework.

Reconstruction-Based Approaches. In computer vision, auto-encoding frameworks enriched with sophisticated model architectures and strong data augmentations (Falcon et al., 2021) are currently being revisited as an alternative unsupervised learning paradigm that is less dependent on large batch-sizes (Chen et al., 2020a) and negative sampling strategies (Kalantidis et al., 2020) when compared to CL. Given that graph datasets are often significantly smaller than vision datasets and negative sampling strategies may be difficult to design, such approaches are particularly relevant to self-supervised graph representation learning and bear revisiting in light of stronger GNN architectures and augmentations.

Formally, let $g\colon (G_i, F_i) \to \mathbb{R}^{n \times d}$ be an encoder that outputs node representations, $h : \mathbb{R}^{n \times d} \to [0, 1]^{n \times n}$ be a decoder that predicts the edges of G_i given node representations, and READOUT $: \mathbb{R}^{n \times d} \to \mathbb{R}^d$ provide graph representations given node representations. Then, a vanilla graph auto-encoder minimizes: $||h(g(x_i) - G_i||_2^2$, where h is often defined as $\sigma\left(g(x_i)g(x_i)^T\right)$ and the aggregated graph representation $\boldsymbol{z}_i = \text{READOUT}(g(G_i, F_i))$ is used to perform downstream tasks. Given that graphs are generally sparse, standard implementations sample an equivalent number of positive and negative edges to ensure stable training. Variational graph auto-encoders (Kipf & Welling, 2016) reparameterize node representations and add a KL divergence term to the reconstruction loss similar to (Kingma & Welling, 2014). As we will argue in this paper, reconstruction-based approaches enhanced with suitable augmentations can be an effective alternative for GCL, under specific conditions. We choose to focus on reconstruction tasks as it is more general than task-specific pretraining tasks and more amenable to theoretical analysis (Khemakhem et al., 2020). In subsequent sections, we seek to understand when and why a given method performs well, beginning by analyzing the role of GGA in graph contrastive learning.

3 SUCCESS CONDITIONS FOR GRAPH CONTRASTIVE LEARNING

Recent attempts to analyze theoretically the performance of contrastive learning often assumes that sample views are independent, a condition clearly violated by data augmentation (Arora et al., 2019; Tosh et al., 2021). To avoid this assumption, HaoChen et al. (2021) recently introduced the notion of a *population augmentation graph*, which represents augmented samples as nodes and edges as the likelihood of generating a given pair of augmented samples from the same clean sample. HaoChen et al. (2021) also provably showed that well-designed augmentations will lead to tight subgraphs (partitions) in the population graph that correspond with downstream class labels. They show that true class labels can be recovered, up to some error, by performing spectral decomposition on this graph and propose a matrix factorization based objective function to perform the decomposition.

In this section, we leverage population augmentation graphs (PAGs) for analyzing contrastive learning with graph data, and show that employing generic graph augmentations from (You et al., 2020a) will lead to subgraphs in the PAG that are dependent on the graph edit distance (GED) between samples of different classes: that is, the minimum number of graph edit operators (operations such as node dropping or edge perturbation that also form the basis for the augmentations commonly used in contrastive learning) needed to transform one sample into another. This implies that performing spectral decomposition on this graph will not align with true class labels if the average GED of samples between two different classes is smaller than the average GED of samples between the same class. Equivalently, generic graph augmentation (GGA) can be interpreted as imposing GED as the implicit metric for representation similarity, and the success of GCL with GGA is dependent on how appropriate GED is for a given task.

More specifically, our analysis is comprised of the following steps: (i) defining the population augmentation graph; (ii) showing that GGA can be decomposed in graph edit operators; (iii) describing graph characteristics of the PAG; and finally (iv) showing that the resulting subgraphs of the PAG are determined by GED, which may not necessarily align with downstream class labels. We follow the notation in (HaoChen et al., 2021).

3.1 CONSTRUCTING THE PAG WITH GENERIC GRAPH AUGMENTATIONS

Given a natural dataset $\overline{\mathcal{X}}$, let $\mathcal{A}(\cdot|\overline{\boldsymbol{x}}_i)$ be the distribution of augmentations given a natural sample $\overline{x}$, or, intuitively, as the probability of generating a particular augmented sample from the large

but finite set of all possible augmented versions of $\overline{x}$. Then, $\mathcal{X} := \cup_{\overline{x} \in \overline{\mathcal{X}}} \mathcal{A}(\cdot|\overline{x})$. Note, the tuple $(\boldsymbol{x} = \mathcal{A}(\overline{x}), \boldsymbol{x}' = \mathcal{A}(\overline{x}))$ is considered a positive pair.

Population Augmentation Graph HaoChen et al. (2021): Let $\mathcal{G}^p$ be the population graph, where all N samples in augmented set $\mathcal{X}$ form the nodes and $W \in \mathbb{R}^{N \times N}$ is the corresponding adjacency matrix. The edge weight between two nodes x and x' is defined as

$$w_{x,x'} := \mathbb{E}_{\overline{x} \in \mathcal{P}_{\overline{\mathcal{X}}}}[\mathcal{A}(x|\overline{x})\mathcal{A}(x'|\overline{x})].$$

Intuitively, if $w_{x,x'}$ is larger, it is relatively easier to generate the augmented pair from the same natural sample.

We first observe that augmentations defined by GraphCL (such as node dropping, edge perturbation, and sub-graph sampling) can be directly decomposed using standard graph edit operators (node dropping, node addition, edge dropping, and edge addition). For example, an edge perturbation augmentation can be represented as a set of edge drops and edge additions between $\{x, \mathcal{A}(x)\}$. Further, note that GraphCL assumes that constraining augmentations to a fraction, γ, of the overall graph size will preserve task-relevant information, and only one augmentation may be applied to a graph at a time. Then, for a single sample, $\overline{x}_i = (G_i, F_i)$, the maximum edit distance of an augmented sample $x' = \mathcal{A}(\overline{x})$ is:

$$\max\{\gamma|\mathcal{E}_i|, \gamma|\mathcal{V}_i|\},$$

where $\mathcal{E}_i, \mathcal{V}_i$ are the edge/node sets. Now, since graphs are discrete, the augmentation severity is restricted and only one edit can be applied at a time, we can completely delineate the set of allowable augmentations given $\overline{x}_i$, $\tilde{\mathcal{A}}_i$, and can determine the size of this set.

For example, consider the node dropping augmentation and let $\gamma_{\mathcal{V}_i} \in \mathbb{Z}^+$ be the number of allowable node drops for G_i. Then, there are

$$ND_i := \sum_{j=1}^{\gamma_{\mathcal{V}_i}} \frac{|\mathcal{V}_i|!}{(|\mathcal{V}_i| - j)!j!}$$

allowable augmented samples. Further, note that augmentations are applied randomly, so any sample in the augmentation set is equally likely, up to node permutation. This means, we can exactly define $\mathcal{A}(x|\overline{x})$, as $\frac{1}{|\tilde{\mathcal{A}}_i|}$. A similar analysis can be used for other augmentations. For ease of exposition, we focus on one augmentation here.

Then, we observe

$$\mathcal{A}(x|\overline{x}) \neq 0 \iff x \in \tilde{A}_{\overline{x}} \tag{2}$$
$$GED(x, \overline{x}) \leq \gamma_{\overline{x}}. \tag{3}$$

Intuitively, x must exist in the augmentation set of $\overline{x}$ to have non-zero probability and the augmentation set is defined by all graphs within $\gamma_{\overline{x}}$ edits. This implies $w_{x,x'}$ will be large when x, x' jointly appear in the augmentation set of many different natural samples. As such, we have defined all possible nodes in $\mathcal{G}^p$ as well as how the edges are defined and can discuss implications of the structure of the population graph induced by GGA.

3.2 ANALYZING POPULATION AUGMENTATION GRAPH STRUCTURE

HaoChen et al. (2021) show that performing spectral decomposition on the augmentation graph provably recovers underlying classes if the partitions or subgraphs in the augmentation graph can be aligned to downstream classes. We now show how these partitions are related to GED and how the structure of these partitions relates to task performance.

To define a min-cut partition, the number of edges crossing a subset of nodes should be minimized while the number of edges within a subset should be high. Clearly, for strong downstream performance, partitions must contain more samples from the same class than of different classes.

Recall Eq. 2 and Eq. 3 define when a given edge will exist between samples. Now, clearly, determining how many edges will cross between ground-truth classes can be determined by measuring the edit distance between samples of different classes. Formally, consider a simple binary task, where $\Psi := \{(GED(\overline{x}_i, \overline{x}_j) \leq \gamma_i + \gamma_j \ni y(\overline{x}_i) \neq y(\overline{x}_j)\}$ corresponds to a set of edges across classes and $\Phi := \{(GED(\overline{x}_i, \overline{x}_j) \leq \gamma_i + \gamma_j \ni y(\overline{x}_i) = y(\overline{x}_j)\}$ is the set of edges within classes. Then, if $|\Psi| > |\Phi|$, it is not possible to learn well-aligned partitions because partitions will contain a mix

of classes. Therefore, if spectral contrastive learning is performed using GGA, there is some fixed error, ϵ, that is directly determined by the average GED between classes, as shown.

While our analysis leverages PAG and the spectral contrastive loss, HaoChen et al. (2021) show that their proposed loss function can be extended to other popular contrastive loss functions and also empirically performs well. Therefore, our results suggest generally that the success of graph contrastive learning with GGA is dependent on the GED between classes. The augmentation set of a given sample is determined by its graph size, and thus it should be more difficult to achieve invariance to GGA augmentations for larger graphs. Third, the above analysis may offer a path to deriving bounds on the generalization to certain distribution shifts, for example graph size shifts.

4 COMPARING (NON-)LEARNING PARADIGMS

To the best of our knowledge, our analysis using PAG is the first attempt to understand theoretically the role of augmentations in GCL and to identify conditions (on dataset and augmentation) that influence the success of GCL with GGA. However, GED has exponential time complexity and heuristic approximations vary in speed and give few quality guarantees (Zeng et al., 2009), making it impractical to compute on most graphs. Moreoever, our above analysis is not applicable to other learning paradigms, for example, reconstruction. Therefore, we systematically evaluate the quality of representations via the downstream task performance, and benchmark not only GCL and reconstruction-based approaches but also the unreasonable effectiveness of untrained baselines.

4.1 REPRESENTATION LEARNING STRATEGIES

We consider three flavors of unsupervised representation learning: (i) *Graph contrastive learning*: For a representative GCL approach, we select GraphCL with GGA as it is a popular and effective method for graph classification. Following You et al. (2020a), we use random node-dropping or subgraph sampling at 20% of the graph size as the augmentation strategy; (ii) *Reconstruction-based*: In addition to standard graph autoencoders (GAEs), we extend AAVAE (Falcon et al., 2021) to the graph domain and introduce augmentation-augmented graph autoencoders (AAGAE). While GAE minimizes the reconstruction loss with respect to the original sample, AAGAE minimizes the reconstruction loss between the original and the reconstruction for an augmented sample to learn representations that are consistent with respect to augmentations: $||G_i - h(g(A(G_i, X_i)))||_2^2$. We use the same augmentations and encoder architecture as GraphCL for fair comparison and include a straight-through estimator in the decoder for better training (Jang et al., 2017); and finally (iii) *Untrained representations*: We include untrained GNNs as an important baseline and find that representations from randomly initialized models often perform comparably to unsupervised approaches.

There is some folk wisdom that untrained GNNs can be surprisingly competitive with trained models. Early GNN works noted that even an untrained model may have strong inductive bias suitable for node-level tasks (Kipf & Welling, 2017). For graph-level transfer learning, Xu et al. (2021) consider an untrained GIN model as a baseline, finding it obtains competitive although generally inferior results. A recent blog post performs a limited exploratory analysis of graph classification using untrained embeddings obtained from a simple GCN model (Safronov, 2021). Our analysis here (extended to consider different architectures in Appendix A.2-A.3) is far more comprehensive, showing precisely in what ways untrained models may be competitive and what training can hope to offer over them.

Table 1: **Inductive Bias on Benchmark Datasets.** We report the performance of *un*trained N-layer GIN encoders against 3-layer encoders trained through GraphCL (You et al., 2020a) or reconstruction approaches (GAE/AAGAE). Results for GraphCL are taken from the paper and we follow the same evaluation protocol. Best results are indicated in bold; results within standard deviation are underlined.

Dataset	Untrained (3)	Untrained(4)	Untrained (5)	GraphCL	GAE	AAGAE
MUTAG (188)	85.76 ± 7.38	86.36 ± 6.51	86.73 ± 10.33	86.80 ± 1.34	87.76 ± 3.00	$\mathbf{88.23 \pm 0.98}$
PROTEINS (1113)	$\underline{73.64 \pm 5.464}$	$\underline{74.46 \pm 4.09}$	$\underline{74.22 \pm 2.85}$	$\underline{74.39 \pm 0.45}$	$\mathbf{75.36 \pm 0.4}$	$\underline{74.77 \pm 0.43}$
NCI1 (4060)	70.65 ± 1.99	70.36 ± 3.11	70.49 ± 2.42	77.81 ± 0.41	$\underline{79.48 \pm 0.44}$	$\mathbf{79.75 \pm 1.25}$
DD (1187)	73.23 ± 8.25	72.15 ± 7.25	$\underline{77.08 \pm 4.18}$	$\mathbf{78.62 \pm 0.40}$	$\underline{78.24 \pm 0.67}$	77.59 ± 0.64
RDT-B (2000)	72.34 ± 6.64	64.57 ± 8.03	67.32 ± 7.41	$\mathbf{89.53 \pm 0.84}$	79.75 ± 1.25	79.95 ± 4.39
IMDB-B (1000)	67.22 ± 7.77	61.26 ± 7.01	60.43 ± 5.92	$\underline{71.14 \pm 0.44}$	$\mathbf{71.70 \pm 0.36}$	$\underline{71.26 \pm 0.305}$

| (a) | (b) |

Figure 1: (a) **Invariance vs. Acc on TUDatasets.** While trained models do see an improvement in both accuracy and invariance, we see that this improvement in often minimal over an untrained model, suggesting that GGA augmentations introduce invariance that is not always useful to the downstream tasks; (b) **Sample Complexity on TU Datasets.** We perform semi-supervised learning on TU Datasets with various amounts of labeled data. For REDDIT-BINARY, pretraining does not improve sample complexity. GAE/AAGAE have slightly better complexity than the supervised baseline on IMDB-BINARY. On PROTEINS, pretraining also does not have clear benefits.

4.2 EVALUATION METRICS

While prediction accuracy on the downstream task is an important criterion for choosing a representation learner, we consider two other metrics to empirically illustrate the benefits of these methods, or lack thereof, over the untrained representations. Specifically, we quantify how training with unsupervised methods affects the invariance of representations with respect to augmentations, and sample complexity. These metrics are selected because they are well-aligned with the objectives of potential applications. For example, in molecular property prediction, it is desirable to have models that are invariant to small measurement discrepancies and can quickly generalize to new distributions. We define these measures and describe how they are computed as follows.

Invariance: When training with NT-XENT, as GraphCL does, the representation similarity between augmented pairs is maximized and models learn invariances to augmentations. AAGAE also enforces consistency to natural and augmented samples. However, it is unclear if (i) models are actually learning invariant representations and (ii) if this property is valuable to downstream task performance. To measure this property, for a given sample $\overline{x}_i$, we generate 300 randomly augmented samples $\{x_i^1 \ldots x_i^{300}\}$ compute the average cosine similarity between $\overline{x}_i, x_i^j$. Note, using cosine similarity as a proxy for the invariance property is well-motivated by NX-ENT.

Sample Complexity: If unsupervised learning is used as the pre-training step, then it is expected that the pre-trained model will have improved sample complexity. We consider if this holds true for GraphCL, GAE and AAGAE. Specifically, after unsupervised training, we include a linear classifier layer to the backbone or encoder. Then, we train the model, end-to-end, in a supervised fashion, where we vary the size of the labeled dataset, extending the setup of (You et al., 2020a).

GGA introduces invariance that has limited improvements in performance. Fig. 1a plots the invariance of GraphCL, GAE, AAGAE, and untrained models on benchmark TU datasets. As noted in Tab. 1, untrained models often perform comparably to trained ones ($\leq 5\%$ difference). However, we see that training with GCL or reconstruction leads to improved invariance. This suggests that the learning invariance was not necessary for downstream task performance. While designing better augmentations is a difficult but obvious solution (Zhao et al., 2020; Kong et al., 2020), in Sec. 5, we find that even optimal augmentations are often unable to surpass supervised performance and discuss implications of this result.

Pretraining has limited benefits on sample complexity. Given that GCL or reconstruction did not lead to considerable improvements in accuracy over a untrained baseline or introduce meaningful invariance, we investigate if pretraining leads to better sample complexity. As shown in Fig. 1b, we find there is no clear benefit to pretraining. On REDDIT-BINARY, the fully supervised model has better accuracy across all label ratios. For IMDB-BINARY, reconstruction based approaches offers a slight improvement. The results are mixed for PROTEINS. We note that the supervised model did not see consistent improvements as the labeled ratio increased and suspect this is related to the random data-splits (Dwivedi et al., 2020).

Figure 2: **Synthetic Dataset Generation.** We create a six class, graph classification dataset by first, selecting one of six unique motifs and then injecting 1-3x copies into a randomly generated tree. Here, the motifs completely determine the class, and are considered "content" (shown in red). To vary the amount of style, the size of the background tree graph (shown in blue) is ratio of the number of "content" nodes. Above are examples of varying style ratios. Our dataset goes beyond binary, benchmark datasets and allows for content-aware augmentations, a critical component to understanding the maximal performance GCL frameworks.

5 GRAPH STYLE VS. CONTENT

While the above analysis identifies untrained networks as a strong baseline for unsupervised graph representation learning, it remains unclear how to improve different components of GCL and reconstruction-based approaches such that the additional expense of pretraining is justified. Given that existing augmentations are far from optimal (see Sec. 3), one avenue of improvement is through better augmentation design. However, graph data augmentation is known to be difficult (Kong et al., 2020; Zhao et al., 2020) and it is unclear if the different paradigms will benefit equally from improved augmentations. Therefore, in this section, we attempt to systematically understand the benefits of graph augmentations on different unsupervised learning paradigms. To that end, we first take the perspective that graph samples can be decomposed into style (*ir*relevant information) vs. content (task relevant information). We then introduce a synthetic data generation process that controls the amount of style vs. content in dataset samples (see Fig. 2), and allows for oracle, content-aware augmentations (CAA). Using this dataset, we validate the effectiveness of augmentations and introduce a valuable benchmark to the community.

Recent theoretical works in VCL also build upon a similar style vs. content perspective. For example, von Kügelgen et al. (2021) introduced a latent variable model to show that self-supervised training with data augmentations is able to recover a style vs. content partition in the latent representation and Zimmermann et al. (2021) showed that is possible to invert the data generating process using contrastive learning and augmentations. Our work differs in that our data generation process operates directly in the observed domain, instead of latent variables as in (von Kügelgen et al., 2021), and we leverage oracle augmentations to better understand the performance of different frameworks.

Synthetic Data Generation: The proposed data generation process consists of three components: a set of C motifs, $\mathcal{M}$, that uniquely determine C classes, a random graph generator, $RBG(n)$, parameterized by the number of nodes (we can also equivalently define this based on number of edges), and ρ, the style multiplier, which controls how much irrelevant information is included in a sample. To generate a sample, we attach a randomly generated background graph (*i.e.*, style component) to a motif (*i.e.*, content) in accordance to the style multiplier. While this process is simple, it addresses several limitations often encountered in GCL evaluation. Specifically, this process (i) allows for varying levels of content-aware augmentation (*i.e.*, edges that can be perturbed directly in the background graph without harming the motif); (ii) is easily extended beyond binary classification; (iii) contains relatively large number of samples and (iv) offers a natural test bed for GNN size generalization or transfer learning.

Experimental-Setup: We let $C = 6$ and define $RBG(n)$ through a random tree generator, where n is $\rho\%$ of the nodes belonging the motif. To make the task more challenging, we randomly insert between 1-3 motif copies into each sample. We explore two different augmentation strategies, namely *random* edge dropping and *content preserving* edge dropping, where only edges in the background graph are dropped. We parameterize these augmentations by the number of edges in the total entire and background graphs, respectively. We do not consider any additional node features, though that extension would be straightforward. We use a 5-layer GIN-based encoder for both our GraphCL backbone and GAE/AAGAE encoders and the models are evaluated using a linear probing protocol (Chen et al., 2020a). See appendix A.1 for more details.

Figure 3: **Effect of Style vs. Content Ratio on Different Paradigms:** We evaluate the performance of contrastive and reconstruction approaches with content preserving and random augmentations as the ratio of style vs. content changes. As expected, reconstruction methods perform best in low style regimes. While we see that content aware augmentations improve performance, especially for GCL, in high style regimes, it remains difficult to match the supervised performance.

5.1 BALANCING STYLE VS. CONTENT

Many real graph datasets can be understood through the aforementioned partitioning of relevant vs. irrelevant information. For example, molecules can be split into functional groups (content) and carbon rings (style). A natural question is whether a reconstruction-based approach or contrastive learning approach is preferable if there is some intuition on the ratio of style vs. content (*i.e.*, many carbon rings vs. a few). We make the following observations from Fig. 3.

Reconstruction-based approaches perform well in low style regimes. Note that as the amount of style increases, the problem inherently becomes harder. However, in regimes where there is little style content (irrelevant information), reconstruction-based approaches should perform well in particular as the model will only learn to recover the relevant information. Conversely, GCL with GGA risks corrupting content, and generating false positives or out of distribution samples. Thus, we expect the accuracy of reconstruction-based approaches to fall more sharply as the amount of style increases, which indeed we do see in Fig. 3. We also find that that CAA helps GCL perform considerably better than with GGA, and that less severe generic augmentations are better; this supports the hypothesis that GCL succeeds when, whether by augmentation design or simply the composition of the data, there is less risk of the augmentations corrupting content.

Content-aware augmentations are not a silver bullet. Optimal augmentations generate views that only share task-relevant information and minimize other task-irrelevant information (Tian et al., 2020). For the proposed dataset, this would correspond to removing the entire background graph. We restrict augmentations to removing 60% of the style portions and find even with strong content-preserving augmentations, unsupervised approaches significantly under-perform when compared to fully supervised models. This is in stark contrast to VCL where strong data augmentation is a critical component to surpassing performance of supervised models on a variety of vision tasks (Chen et al., 2020a). Our analysis suggests that other framework components, such as more expressive architectures (Chen et al., 2020b; Xu et al., 2019; Velickovic et al., 2018; Corso et al., 2020; Hamilton et al., 2017) and sampling strategies (Kalantidis et al., 2020; Grill et al., 2020; Chen & He, 2020), must also be developed before GCL sees the same success. Furthermore, we note that the gain from CAA in high-style regimes is much less pronounced for reconstruction approaches than for GCL. This may partially be attributed to increased difficulty in reconstructing larger graphs. More sophisticated decoders and algorithms may help improve performance.

5.2 EVALUATION

Our invariance and sample complexity analysis for the synthetic benchmark further highlights some use but also limitations of augmentations.

Invariance: Invariance to random edge dropping at 20% of the graph after performing unsupervised training when $\rho = 0.5$ is shown in Fig. 4a. Almost all methods improve on the untrained baselines in

(a)   (b)

Figure 4: (a) **Invariance vs. Accuracy on Synthetic Datasets.** We measure the invariance to random augmentations, when $\rho = 0.5$; (b) **Sample Complexity on Synthetic Dataset.** We perform semi-supervised learning when $\rho = 1.0$ with various amounts of labeled data. GraphCL has considerably better performance than reconstruction-based methods. Content-aware augmentations are useful for both paradigms.

accuracy and invariance. We find that all reconstruction-based methods have high invariance in this low style regime. In contrast, GCL models that are more invariant tend to be more accurate, which may suggest that for this learning paradigm, learning to be invariant to augmentations can improve accuracy. Interestingly, supervised training is the most accurate but the least invariant–this reminds us the pursuit of expressive GNN models that most successfully map distinct graphs to distinct representations Xu et al. (2019) is helpful in supervised settings, though without the guidance of task supervision, unsupervised learning may benefit from greater representation invariance.

Sample Complexity: We measure the performance of different methods when $\rho = 1$ and at different labeling ratios in a semi-supervised setting. While CAA improves the sample efficiency of reconstruction-based methods with respect to GGA, we see that (i) GAE outperforms AAGAE across all labeling rates, and (ii) all considered reconstruction-based methods are not able to match the performance of GCL or supervised performance. This suggests that AAGAE may converge to a more unstable loss landscape, but also highlights our observation at the end of Sec. 5.1 that augmentations are limited in what they can accomplish, and may require technical advances such as more sophisticated decoders to come into their own to the extent they have in computer vision.

Overall, we demonstrate that decomposing samples into style and content is a useful framework for understanding the performance of unsupervised learning algorithms on graph data.

6 CONCLUSION

In this paper, we seek to understand the behavior of GCL and reconstruction-based approaches when performing unsupervised graph representation learning. We show theoretically that the success of GCL with popular, generic graph augmentations is directly dependent on the average graph edit distance between classes. Our empirical study shows in detail the competitiveness of untrained GNNs on benchmark datasets to help the community understand what benefits to expect from training. We demonstrate for both GCL and reconstruction-based methods, which we consider in greater detail for unsupervised graph representation learning including with a new method AAGAE, that generic graph augmentation does not introduce meaningful invariance or reliably improve model sample complexity on these benchmarks. Thus, we introduce a synthetic benchmark with a controlled style vs. content decomposition to understand how much can be gained from optimal (content-aware) augmentations and better compare the GCL and reconstruction paradigms. Our work provides useful frameworks and evaluation tools to better understand the performance of unsupervised graph representation learning, contributions we expect to be of great interest to this burgeoning field.

7 REPRODUCIBILITY STATEMENT

For reproducibility, we provide details about data generation in appendix A.1. For baselines, we build off the code provided by the authors and follow the authors' guidelines to set the hyperparameters. We will also release code at this link: https://anonymous.4open.science/r/GCLRecon-5DF6/

REFERENCES

Sanjeev Arora, Hrishikesh Khandeparkar, Mikhail Khodak, Orestis Plevrakis, and Nikunj Saunshi. A theoretical analysis of contrastive unsupervised representation learning. *CoRR*, 2019.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey E. Hinton. A simple framework for contrastive learning of visual representations. In *ICML*, 2020a.

Ting Chen, Simon Kornblith, Kevin Swersky, Mohammad Norouzi, and Geoffrey E. Hinton. Big self-supervised models are strong semi-supervised learners. In *NeurIPS 2020*, 2020b.

Xinlei Chen and Kaiming He. Exploring simple siamese representation learning. *CoRR*, abs/2011.10566, 2020.

Gabriele Corso, Luca Cavalleri, Dominique Beaini, Pietro Liò, and Petar Velickovic. Principal neighbourhood aggregation for graph nets. In *NeurIPS*, 2020.

David Duvenaud, Dougal Maclaurin, Jorge Aguilera-Iparraguirre, Rafael Gómez-Bombarelli, Timothy Hirzel, Alán Aspuru-Guzik, and Ryan P. Adams. Convolutional networks on graphs for learning molecular fingerprints. In *NeurIPS*, 2015.

Vijay Prakash Dwivedi, Chaitanya K. Joshi, Thomas Laurent, Yoshua Bengio, and Xavier Bresson. Benchmarking graph neural networks. *CoRR*, 2020.

William Falcon, Ananya Harsh Jha, Teddy Koker, and Kyunghyun Cho. AAVAE: augmentation-augmented variational autoencoders. *CoRR*, 2021.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre H. Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Ávila Pires, Zhaohan Guo, Mohammad Gheshlaghi Azar, Bilal Piot, Koray Kavukcuoglu, Rémi Munos, and Michal Valko. Bootstrap your own latent - A new approach to self-supervised learning. In *NeurIPS*, 2020.

William L. Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. In *NeurIPS*, 2017.

Jeff Z. HaoChen, Colin Wei, Adrien Gaidon, and Tengyu Ma. Provable guarantees for self-supervised deep learning with spectral contrastive loss. *CoRR*, 2021.

Kaveh Hassani and Amir Hosein Khas Ahmadi. Contrastive multi-view representation learning on graphs. In *ICML*, 2020.

R. Devon Hjelm, Alex Fedorov, Samuel Lavoie-Marchildon, Karan Grewal, Philip Bachman, Adam Trischler, and Yoshua Bengio. Learning deep representations by mutual information estimation and maximization. In *ICLR*, 2019.

Weihua Hu, Bowen Liu, Joseph Gomes, Marinka Zitnik, Percy Liang, Vijay S. Pande, and Jure Leskovec. Strategies for pre-training graph neural networks. In *ICLR*, 2020.

Doyeong Hwang, Soojung Yang, Yongchan Kwon, Kyung-Hoon Lee, Grace Lee, Hanseok Jo, Seyeol Yoon, and Seongok Ryu. Comprehensive study on molecular supervised learning with graph neural networks. *J. Chem. Inf. Model.*, 2020.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with gumbel-softmax. In *ICLR*, 2017.

Y. Kalantidis, M. Bülent Sariyildiz, N. Pion, P. Weinzaepfel, and D. Larlus. Hard negative mixing for contrastive learning. In *NeurIPS*, 2020.

Zekarias T. Kefato and Sarunas Girdzijauskas. Self-supervised graph neural networks without explicit negative sampling. *CoRR*, 2021.

Ilyes Khemakhem, Diederik P. Kingma, Ricardo Pio Monti, and Aapo Hyvärinen. Variational autoencoders and nonlinear ICA: A unifying framework. In *AISTATS*, 2020.

Diederik P. Kingma and Max Welling. Auto-encoding variational bayes. In *ICLR*, 2014.

Thomas N. Kipf and Max Welling. Variational graph auto-encoders. *CoRR*, 2016.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *ICLR*, 2017.

Kezhi Kong, Guohao Li, Mucong Ding, Zuxuan Wu, Chen Zhu, Bernard Ghanem, Gavin Taylor, and Tom Goldstein. FLAG: adversarial data augmentation for graph neural networks. *CoRR*, 2020.

Yixin Liu, Shirui Pan, Ming Jin, Chuan Zhou, Feng Xia, and Philip S. Yu. Graph self-supervised learning: A survey. *CoRR*, abs/2103.00111, 2021. URL https://arxiv.org/abs/2103.00111.

Zhen Peng, Wenbing Huang, Minnan Luo, Qinghua Zheng, Yu Rong, Tingyang Xu, and Junzhou Huang. Graph representation learning via graphical mutual information maximization. In *Proceedings of The Web Conference 2020*, pp. 259–270, 2020.

Senthil Purushwalkam and Abhinav Gupta. Demystifying contrastive self-supervised learning: Invariances, augmentations and dataset biases, 2020.

Jiezhong Qiu, Qibin Chen, Yuxiao Dong, Jing Zhang, Hongxia Yang, Ming Ding, Kuansan Wang, and Jie Tang. GCC: graph contrastive coding for graph neural network pre-training. In *SIGKDD*. ACM, 2020.

Vadeem Safronov. Almost free inductive embeddings out-perform trained graph neural networks in graph classification in a range of benchmarks. https://towardsdatascience.com/almost-free-inductive-embeddings-out-perform-trained-graph-neural-networks-in-graph-classification-651ace368bc1, 2021. Accessed: 2021-10-05.

Ali Shafahi, Mahyar Najibi, Amin Ghiasi, Zheng Xu, John P. Dickerson, Christoph Studer, Larry S. Davis, Gavin Taylor, and Tom Goldstein. Adversarial training for free! In *NeurIPS*, 2019.

Fan-Yun Sun, Jordan Hoffmann, Vikas Verma, and Jian Tang. Infograph: Unsupervised and semi-supervised graph-level representation learning via mutual information maximization. In *ICLR*, 2020.

Shantanu Thakoor, Corentin Tallec, Mohammad Gheshlaghi Azar, Rémi Munos, Petar Velickovic, and Michal Valko. Bootstrapped representation learning on graphs. *CoRR*, abs/2102.06514, 2021. URL https://arxiv.org/abs/2102.06514.

Yonglong Tian, Chen Sun, Ben Poole, Dilip Krishnan, Cordelia Schmid, and Phillip Isola. What makes for good views for contrastive learning? In *NeurIPS*, 2020.

Christopher Tosh, Akshay Krishnamurthy, and Daniel Hsu. Contrastive learning, multi-view redundancy, and linear models. In Vitaly Feldman, Katrina Ligett, and Sivan Sabato (eds.), *Algorithmic Learning Theory, 16-19 March 2021, Virtual Conference, Worldwide*, volume 132 of *Proceedings of Machine Learning Research*, pp. 1179–1206. PMLR, 2021. URL http://proceedings.mlr.press/v132/tosh21a.html.

Aäron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *CoRR*, 2018.

Petar Velickovic, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph attention networks. In *ICLR*, 2018.

Petar Velickovic, William Fedus, William L. Hamilton, Pietro Liò, Yoshua Bengio, and R. Devon Hjelm. Deep graph infomax. In *ICLR*, 2019.

Julius von Kügelgen, Yash Sharma, Luigi Gresele, Wieland Brendel, Bernhard Schölkopf, Michel Besserve, and Francesco Locatello. Self-supervised learning with data augmentations provably isolates content from style. *CoRR*, abs/2106.04619, 2021.

Tongzhou Wang and Phillip Isola. Understanding contrastive representation learning through alignment and uniformity on the hypersphere. In *ICML*, 2020.

Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? In *ICLR*, 2019.

Minghao Xu, Hang Wang, Bingbing Ni, Hongyu Guo, and Jian Tang. Self-supervised graph-level representation learning with local and global structure. In *ICML*, 2021.

Yuning You, Tianlong Chen, Yongduo Sui, Ting Chen, Zhangyang Wang, and Yang Shen. Graph contrastive learning with augmentations. In *NeurIPS*, 2020a.

Yuning You, Tianlong Chen, Zhangyang Wang, and Yang Shen. When does self-supervision help graph convolutional networks? *CoRR*, abs/2006.09136, 2020b. URL https://arxiv.org/abs/2006.09136.

Jiahui Yu, Zhe Lin, Jimei Yang, Xiaohui Shen, Xin Lu, and Thomas S. Huang. Generative image inpainting with contextual attention. *CoRR*, abs/1801.07892, 2018. URL http://arxiv.org/abs/1801.07892.

Zhiping Zeng, Anthony KH Tung, Jianyong Wang, Jianhua Feng, and Lizhu Zhou. Comparing stars: On approximating graph edit distance. *Proceedings of the VLDB Endowment*, 2(1):25–36, 2009.

Tong Zhao, Yozen Liu, Leonardo Neves, Oliver J. Woodford, Meng Jiang, and Neil Shah. Data augmentation for graph neural networks. *CoRR*, 2020.

Yanqiao Zhu, Yichen Xu, Feng Yu, Qiang Liu, Shu Wu, and Liang Wang. Graph contrastive learning with adaptive augmentation. *WWW*, 2020.

Roland S. Zimmermann, Yash Sharma, Steffen Schneider, Matthias Bethge, and Wieland Brendel. Contrastive learning inverts the data generating process. In *ICML*, 2021.

Marinka Zitnik, Rok Sosič, and Jure Leskovec. Prioritizing network communities. *Nature Communications*, 2018.

A APPENDIX

A.1 DATASET GENERATION AND EXPERIMENTAL DETAILS

Figure 5: **Motifs used to determine class labels.**

We use the motifs shown in Fig. A.1 to define a 6 class graph classification task. It is important to ensure that the motifs are not isomorphic, as many GNNs are less expressive than the 1-Weisfeiler Lehman's test for isomorphism (Xu et al. (2019)). For each class, 1000 random samples are generated as follows: (i) We randomly select between 1-3 motifs to be in each sample. At this time, motifs all belong to the same class, though this condition could easily be changed for a more difficult task. (ii) We define the number of content nodes, C_n, as the size of the selected motif, scaled by the number of motifs in the sample. (iii) For a given style ratio, we determine the number of possible style nodes as $S_n = \rho C_n$ (iv) We define $RBG(n)$ using networkx's [1] random tree generator: `networkx.generators.trees.random_tree`. We note that other random graph generators would also be well suited for this task. (v) For additional randomness, we create background graphs using $S_n \pm 2$, and also randomly perturb up-to 10% of edges in sample. We repeat this set-up with $\rho \in \{0.5, 1.0, 1.5, 2.0, 2.5, 3.0\}$ to generate the datasets used in Sec 5.

---

[1]https://networkx.org/documentation/stable/

Experimental Set-up: We follow You et al. (2020a) for TUDataset experiments. We use a 5-layer GIN model with sum pooling for all synthetic experiments. Models are pretrained for 100 epochs and then fine-tuned for 200 epochs with 1 learning rate drop when the loss plateaus. The hidden layer dimension is 32. We concatenate hidden representations for a representation dimension of 160. All models are trained with Adam, lr = 0.001. For the sample complexity experiment, we allow for end to end training. For all other experiments, we freeze the backbone and only train the linear prediction head.

A.2 INDUCTIVE BIAS, ADDITIONAL RESULTS

To further demonstrate the effectiveness of untrained models on popular benchmarks, we include results from different GNN architectures: GraphSage (Hamilton et al. (2017)), PNA (Corso et al. (2020)), GCN (Kipf & Welling (2017)) and GAT (Velickovic et al. (2018)). We note that while it has been informally discussed that untrained GNNs have a strong inductive bias, our intention is to formalize why these untrained models *must* be included when evaluating unsupervised graph representation learning. Moreover, in Tab. A.3, we include a variant of untrained models, where we initialize BatchNorm statistics without computing any gradients by iterating over the dataset once. For several datasets and baselines, we see that this Warmup step makes the untrained baseline even stronger. We believe that future work should also consider this simple baseline when evaluating the performance of their models.

Table 2: Inductive Bias.

GraphSAGE	3 Layer	4 Layer	5 Layer	GraphCL	InfoGraph
MUTAG	0.85 ± 0.005	0.85 ± 0.006	0.85 ± 0.005	0.82 ± 0.040	0.85 ± 0.005
PROTEINS	0.73 ± 0.004	0.73 ± 0.003	0.74 ± 0.005	0.75 ± 0.002	0.74 ± 0.008
NCI1	0.74 ± 0.003	0.75 ± 0.006	0.73 ± 0.011	0.78 ± 0.000	0.79 ± 0.002
DD	0.77 ± 0.006	0.78 ± 0.002	0.78 ± 0.005	0.80 ± 0.008	0.77 ± 0.010
REDDIT-B	0.85 ± 0.014	0.83 ± 0.016	0.83 ± 0.005	–	0.66 ± 0.137
IMDB-B	0.66 ± 0.012	0.81 ± 0.008	0.81 ± 0.008	–	–

PNA	3 Layer	4 Layer	5 Layer	GraphCL	InfoGraph
MUTAG	0.88 ± 0.011	0.88 ± 0.010	0.89 ± 0.009	0.86 ± 0.023	0.90 ± 0.014
PROTEINS	0.74 ± 0.003	0.74 ± 0.012	0.74 ± 0.005	0.74 ± 0.007	0.74 ± 0.003
NCI1	0.67 ± 0.008	0.68 ± 0.011	0.68 ± 0.010	0.78 ± 0.008	0.77 ± 0.019
DD	0.76 ± 0.014	0.76 ± 0.002	0.76 ± 0.008	0.80 ± 0.008	0.76 ± 0.006
REDDIT-B	0.90 ± 0.003	0.88 ± 0.014	0.89 ± 0.010	0.92 ± 0.006	0.92 ± 0.006
IMDB-B	0.72 ± 0.007	0.68 ± 0.011	0.68 ± 0.010	0.71 ± 0.009	0.71 ± 0.009

GCN	3 Layer	4 Layer	5 Layer	GraphCL	InfoGraph
MUTAG	0.85 ± 0.003	0.85 ± 0.004	0.85 ± 0.005	0.82 ± 0.013	0.85 ± 0.003
PROTEINS	0.74 ± 0.003	0.73 ± 0.007	0.74 ± 0.004	0.75 ± 0.004	0.75 ± 0.003
NCI1	0.76 ± 0.004	0.75 ± 0.001	0.75 ± 0.002	0.78 ± 0.008	0.79 ± 0.007
DD	0.78 ± 0.002	0.77 ± 0.012	0.78 ± 0.003	0.79 ± 0.007	0.76 ± 0.003
REDDIT-B	0.52 ± 0.005	0.51 ± 0.003	0.52 ± 0.005	0.92 ± 0.002	0.80 ± 0.062
IMDB-B	0.54 ± 0.001	0.57 ± 0.016	0.58 ± 0.008	0.71 ± 0.011	0.62 ± 0.070

GAT	3 Layer	4 Layer	5 Layer	GraphCL	InfoGraph
MUTAG	0.84 ± 0.003	0.85 ± 0.009	0.84 ± 0.003	0.81 ± 0.032	0.85 ± 0.013
PROTEINS	0.74 ± 0.002	0.74 ± 0.005	0.74 ± 0.006	0.74 ± 0.007	0.74 ± 0.005
NCI1	0.76 ± 0.009	0.75 ± 0.004	0.76 ± 0.002	0.78 ± 0.004	0.70 ± 0.040
DD	0.78 ± 0.005	0.77 ± 0.006	0.79 ± 0.001	0.79 ± 0.003	0.76 ± 0.005
REDDIT-B	0.52 ± 0.005	0.53 ± 0.004	0.52 ± 0.012	0.75 ± 0.004	–
IMDB-B	0.51 ± 0.004	0.51 ± 0.009	0.50 ± 0.005	0.51 ± 0.007	–

A.3 INVARIANCE, ADDITIONAL RESULTS

We extend our representation invariance results on standard benchmarks to different architectures below in Tab. A.3. As in our main results, we use random subgraph sampling and node dropping as our augmentations, following You et al. (2020a), when computing invariance. We find that similar trends hold: while training with GCL does improve performance and invariance somewhat, untrained models perform comparably without the same levels of invariance.

Table 3: Invariance Table.

	RandGAT	(Acc)	WarmupGAT	(Acc)	GAT (GraphCL)	(Acc)
MUTAG	0.993	0.843	0.364	0.793	0.608	0.807
PROTEINS	0.987	0.737	0.819	0.738	0.554	0.744
NCI1	0.993	0.761	0.543	0.771	0.669	0.781
DD	0.970	0.779	0.381	0.778	0.361	0.793
REDDIT-B	1.000	0.517	0.850	0.724	0.982	0.747
IMDB-B	1.000	0.512	0.979	0.670	0.994	0.512
	RandGIN	(Acc)	WarmupGIN	(Acc)	GIN (GraphCL)	(Acc)
MUTAG	0.921	0.867	0.208	0.866	0.852	0.868
PROTEINS	0.910	0.745	0.495	0.750	0.547	0.744
NCI1	0.921	0.707	0.281	0.769	0.768	0.778
DD	0.907	0.732	0.071	0.760	0.638	0.786
REDDIT-B	0.906	0.723	0.242	0.768	0.286	0.895
IMDB-B	0.914	0.672	0.791	0.700	0.468	0.711
	RandGCN	(Acc)	WarmupGCN		GCN (GraphCL)	(Acc)
MUTAG	0.996	0.847	0.491	0.807	0.561	0.821
PROTEINS	0.980	0.739	0.886	0.750	0.765	0.749
NCI1	0.991	0.756	0.480	0.767	0.664	0.780
DD	0.968	0.779	0.440	0.772	0.367	0.789
REDDIT-B	0.999	0.519	0.129	0.833	0.678	0.919
IMDB-B	0.914	0.540	0.539	0.833	0.994	0.709
	RandSAGE	(Acc)	WarmupSAGE	(Acc)	SAGE (GraphCL)	(Acc)
MUTAG	0.910	0.846	0.273	0.801	0.303	0.823
PROTEINS	0.907	0.732	0.582	0.747	0.507	0.749
NCI1	0.912	0.737	0.412	0.771	0.579	0.779
DD	0.590	0.771	0.590	0.781	0.727	0.801
REDDIT-B	0.833	0.849	0.225	0.740	–	–
IMDB-B	0.223	0.663	0.223	0.497	–	–

Table 4: **Selected Graph Contrastive Learning Frameworks.** Brief description of augmentations used by selected frameworks is provided. Most frameworks use random corruptive, sampling, or diffusion-based approaches to generate augmentations.

Method	Augmentations
GraphCL (You et al. (2020a))	Node Dropping, Edge Adding/Dropping, Attr. Masking, Subgraph Extraction
GCC (Qiu et al. (2020))	RWR Subgraph Extraction of Ego Network
MVGRL (Hassani & Ahmadi (2020))	PPR Diffusion + Sampling
GCA (Zhu et al. (2020))	Edge Dropping, Attr. Masking (both weighted by centrality)
BGRL (Thakoor et al. (2021))	Edge Dropping, Attr. Masking
SelfGNN (Kefato & Girdzijauskas (2021))	Attr. Splitting, Attr. Standardization + Scaling, Local Degree Profile, Paste + Local Degree Profile

A.4 RELATED WORK

Graph Data Augmentation: Augmentations for graphs are difficult to define due to their discrete, non-euclidean nature. Furthermore, unlike images or natural language where there is an intuitive understanding of what changes will preserve task-relevant information, no such understanding exists for graphs. Indeed, a single edge change can completely change the properties of a molecular graph. Therefore, only a few works consider graph data augmentation. Zhao et al. (2020) note that a node classification task can be perfectly solved if edges only exist between same class samples. They train a neural edge predictor to increase homophily by adding edges between nodes expected to be of the same class and break edges between nodes of expected dissimilar classes. However, this approach is expensive and not applicable to graph classification. Kong et al. (2020) argue that information preserving topological transformations are difficult for the aforementioned reasons and instead focus on feature augmentations. Throughout training, they add an adversarial perturbation to node features to improve generalization. To avoid incurring the large expense of adversarial training, they leverage Shafahi et al. (2019) and compute the gradient of the model weights while computing

the gradients of the adversarial perturbation. This approach is not directly applicable to contrastive learning, where label information cannot be used to generate the adversarial perturbation.

Graph Self-Supervised Learning: Several paradigms for self-supervised learning in graphs have been recently explored, including the use of pre-text tasks, multi-tasks, and unsupervised learning. See Liu et al. (2021) for an up-to-date survey. Graph pre-text tasks are often reminiscent of image in-painting tasks Yu et al. (2018), and seek to complete masked graphs and/or node features (You et al. (2020b); Hu et al. (2020)). Other successful approaches include predicting graph level or property level properties during pre-training or part of regular training to prevent over-fitting (Hu et al. (2020)). These tasks often must be carefully selected to avoid negative transfer between tasks. Many unsupervised approaches have also been proposed. Sun et al. (2020); Velickovic et al. (2019) draw inspiration from Hjelm et al. (2019) and maximize the mutual information between global and local representations. MVGRL (Hassani & Ahmadi (2020)) contrasts different views at multiple granularities similar to van den Oord et al. (2018). You et al. (2020a); Qiu et al. (2020); Zhu et al. (2020); Thakoor et al. (2021); Kefato & Girdzijauskas (2021) use augmentations to generate views for contrastive learning. See Table A.4 for a summary of the augmentations used. We note that random corruption, sampling or diffusion based approaches often do not preserve task relevant information or introduce meaningful invariances.