Towards Robust Bisimulation Metric Learning

Abstract

Learned representations in deep reinforcement learning (DRL) have to extract task-relevant information from complex observations, balancing between robustness to distraction and informativeness to the policy. Such stable and rich representations, often learned via modern function approximation techniques, can enable practical application of the policy iteration theorem, even in high-dimensional continuous state-action spaces. Therefore, learning informative state representations efficiently is an important challenge, which has seen growing attention with recent advances in DRL. Bisimulation metrics offer one solution to this problem, by collapsing functionally similar states together in representation space, which promotes invariance to noise and distractors. In this work, we show that on-policy bisimulation metrics suffer from common issues in metric learning: embedding collapse and explosion. We identify the root cause of these issues theoretically, finding that they stem from an underconstrained dynamics model and an unstable dependence of the embedding norm on the reward signal. Further, we propose a set of practical remedies: (i) a norm constraint on the representation space, and (ii) an extension of prior approaches with intrinsic rewards and latent space regularization. Finally, we provide evidence that the resulting method is not only more robust to sparse reward functions, but also able to solve challenging continuous control tasks with observational distractions, where prior methods fail.

1 Introduction

Complex reinforcement learning (RL) problems require the agent to infer a useful representation of the world state from observations. The utility of this representation can be measured by how readily it can be used to learn and enact a policy that solves a specific task. As an example, consider a robot using visual perception to pour a cup of coffee. The clutter on the counter and the colour of the walls have little effect on the correct action; even more pertinent aspects, such as two mugs with slightly different patterns and shapes, should be treated nearly the same by the policy. In other words, many states are *equivalent* for a given task, with their differences being task-irrelevant distractors. Thus, a natural approach to generalization across environmental changes is constructing a representation that is invariant to such nuisance variables – effectively "grouping" such equivalent states together.

One method of obtaining such a representation uses the notion of a *bisimulation metric* (BSM) [10, 11]. The goal is to abstract the states into a new metric space, which groups "behaviourally" similar states in a task-dependent manner. In particular, bisimilar states (i.e., in this case, those close under the BSM) should yield similar stochastic reward sequences, given the same action sequence. In a recursive sense, this requires bisimilar states to have similar (i) immediate rewards and (ii) transition distributions in the BSM space (e.g., see Eq. 1). Thus, ideally, the resulting representation space contains the information necessary to help the policy maximize return and little else.

Recently, the Deep Bisimulation for Control (DBC) algorithm [36] showed how to map observations into a learned space that follows a policy-dependent (or on-policy) BSM (PBSM) for a given task

[8], resulting in a powerful ability to ignore distractors within high-dimensional observation spaces. Using a learned dynamics model, DBC trains an encoder to abstract states to follow the estimated PBSM, using the aforementioned recursive formulation for metric learning.

However, this method can suffer from issues of robustness under certain circumstances. Conceptually, differentiating state encodings requires trajectories with different rewards. In other words, two states that only differ in rewards far in the future should still not be bisimilar. Yet, in practice, the encoder and policy are learned simultaneously as the agent explores; hence, in the case of *uninformative* (e.g., sparse or near-constant) rewards, it may incorrectly surmise that two states are bisimilar, as most trajectories will look very similar. This leads to a premature *collapse* of the embedding space, grouping states that should not be grouped. On the other hand, we can show that the formulation of the metric learning loss is susceptible to embedding *explosion* if the representation space is left unconstrained. In our work, we build upon the DBC model in an attempt to tackle both problems: (1) we address embedding explosion by stabilizing the state representation space via a norm constraint and (2) we prevent embedding collapse by altering the encoder training method.

Contributions We (i) generalize theoretical value function approximation bounds to a broader family of BSMs, with learned dynamics; (ii) analyze the BSM loss formulation and identify sources of potential embedding pathologies (explosion and collapse); (iii) show how to constrain representation space to obtain better embedding quality guarantees; (iv) devise theoretically-motivated training modifications based on intrinsic motivation and inverse dynamics regularization; and (v) show on a variety of tasks that our method is more robust to both sparsity and distractors in the environment.

2 Related Work

Our work builds on two major aspects of DRL: representation learning, particularly task-specific encodings following the BSM, and methods for sparse reward environments, (e.g., intrinsic motivation).

Representation Learning for Control In the context of RL, there is a spectrum of representations from task-agnostic to task-specialized. One task-agnostic approach to learning latent representation spaces uses a reconstruction loss. In particular, some methods utilize this approach for model-based planning [20, 37, 19], while others do so for model-free RL [24, 13, 22]. Such approaches often utilize generative models, which have shown use for learning via simulation, in addition to representation learning [16]. Instead of fully reconstructing an input, other approaches use self-supervised representation learning methods, especially contrastive learning algorithms [25, 21, 32].

While task-agnostic reconstruction allows for reusability and transfer, it tends to store unnecessary details that can hamper performance on a given task. Thus, some methods try to focus on representations that can ignore irrelevant information. For instance, actionable representations [14] assign inter-state distances via the expected difference between policy distributions attempting to reach those states. Other methods use inverse dynamics prediction (i.e., predicting actions given state transitions) to encourage the latent representation to hold information relevant to what the agent can control [27].

In our work, we build on the use of task-specific *bisimulation relations*, which define equivalence classes of states based on a notion of behavioural similarity [12]. However, obtaining equivalence classes based on rewards and transition probabilities is brittle, as our estimates will be inexact; further, it will not aggregate states that are ε-close. Hence, Ferns et al. [10, 11] instead turn to a *metric* between states, which can vary smoothly as the rewards and transition probabilities change. More recently, Zhang et al. [36] devised Deep Bisimulation for Control (DBC), which applies a metric learning approach to enforce its representation to approximately follow bisimulation-derived state aggregation. While DeepMDP [13] proves that its representation provides an upper bound on the bisimulation distance, DBC [36] directly imposes the bisimulation metric structure on the latent space. Herein, we extend prior analysis and methods for representation learning using PBSMs, with the goal of improving robustness and general performance. In particular, we focus on preventing embedding pathologies, in the context of uninformative reward signals and distraction.

Reinforcement Learning under Uninformative Rewards Many real-world tasks suffer from uninformative rewards, meaning that the agent receives sparse (mostly zero) or static (largely constant) rewards throughout its trajectories. For example, games like Montezuma's Revenge only provide reward signals after a large number of steps – and the agent is likely not to receive one at all, in most cases. Thus, while common, this situation significantly increases the difficulty of the RL task, as the

agent receives little signal about its progress. To deal with such situations, a common tactic is to encourage the agent to explore in the absence of an extrinsic reward signal. This is often done by providing *intrinsic motivation* via a self-derived reward, resulting in "curiosity-driven" behaviour [6, 3]. Such approaches include surprise [1, 4] (where experiencing unexpected dynamics is rewarded), and empowerment [29, 15] (where the agent prefers states in which it has more control).

In this work, we specifically target the case of uninformative rewards, showing that the DBC model is especially susceptible to instability or collapse for such tasks, and consider ways to ameliorate this issue. In particular, we utilize the forward prediction error as an intrinsic reward [27, 6, 31], thus augmenting the sparse extrinsic rewards and encouraging exploration. We also regularize the latent space by learning an inverse dynamics model on top of it, which does not rely on the extrinsic reward signal and has previously been used for distraction-robust representation learning in DRL [2, 27].

3 Technical Approach

In this section, we first describe our notation and problem setting, and review prior definitions of bisimulation metrics and relevant metric learning objectives. Then, we consider theoretical connections to value functions and convergence properties, and show that these formulations may be susceptible to (i) instabilities in optimization due to embedding explosion (i.e., large norms), and (ii) convergence to trivial solutions where all states are represented as a single point (embedding collapse). Based on our analysis, we propose an extension of deep bisimulation metric learning, with theoretically-motivated constraints on the optimization objective, including alterations to the forward dynamics model, intrinsic motivation, and inverse dynamics regularization.

3.1 Preliminaries

In this work, we consider a discounted Markov Decision Process (MDP) given by a tuple, $\langle \mathcal{S}, \mathcal{A}, \mathcal{P}, R, \rho_0 \rangle$. At the beginning of each episode, an initial state, $\mathbf{s}_0 \in \mathcal{S}$, is sampled from the initial-state distribution ρ_0 over the state space $\mathcal{S}$. Then, at each discrete time-step $t \geq 0$, an agent takes an action, $\mathbf{a}_t \in \mathcal{A}$, according to a policy $\pi(\mathbf{a}_t|\mathbf{s}_t)$. As a result, the MDP transitions to the next state according to a transition distribution $\mathcal{P}(\mathbf{s}_{t+1}|\mathbf{s}_t, \mathbf{a}_t)$. The agent collects a scalar reward, $r_t = R(\mathbf{s}_t, \mathbf{a}_t)$, from the environment according to a bounded reward function, $R : \mathcal{S} \times \mathcal{A} \to [R_{\min}, R_{\max}]$. In infinite- and long-horizon settings, a discount factor, $\gamma \in [0, 1)$, is used to calculate the agent's discounted return in a given episode, $G = \sum_{t \geq 0} \gamma^t r_t$. RL algorithms aim to find an optimal policy, $\pi^* := \operatorname{argmax}_{\pi \in \Pi} \mathbb{E}[G]$, for a class of stationary policies Π. In high-dimensional, continuous state (or observation) spaces, this learning problem is rendered tractable via a state encoder (e.g., a neural network), $\phi : \mathcal{S} \to \mathbb{R}^d$, which is used to learn a policy of the form $\pi(\mathbf{a}|\phi(\mathbf{s}))$.

The following (pseudo[1])-metric, based on the Wasserstein metric (see Appendix A for a review), is of particular relevance to this work. Distances are assigned to state pairs, $(\mathbf{s}_i, \mathbf{s}_j) \in \mathcal{S} \times \mathcal{S}$, according to a pessimistic measure [7] of how much the rewards collected in each state and the respective transition distributions differ. A distance of zero for a pair implies state aggregation, or *bisimilarity*.

Definition 1 (Bisimulation metric for continuous MDPs, Thm. 3.12 of [11]). *The following metric exists and is unique, given $R : \mathcal{S} \times \mathcal{A} \to [0, 1]$ and $c \in (0, 1)$ for continuous MDPs:*

$$d(\mathbf{s}_i, \mathbf{s}_j) = \max_{\mathbf{a} \in \mathcal{A}}(1 - c)|R(\mathbf{s}_i, \mathbf{a}) - R(\mathbf{s}_j, \mathbf{a})| + cW_1(d)(\mathcal{P}(\cdot|\mathbf{s}_i, \mathbf{a}), \mathcal{P}(\cdot|\mathbf{s}_j, \mathbf{a})). \tag{1}$$

An earlier version of this metric for finite MDPs used separate weighting constants $c_R, c_T \geq 0$ for the first and second terms respectively, and required that $c_R + c_T \leq 1$ [10]. Here, when the weighting constant c_T of the $W_1(d)$ term is in $[0, 1)$, the RHS is a contraction mapping, $\mathcal{F}(d) : \mathfrak{met} \to \mathfrak{met}$, in the space of metrics. Then, the Banach fixed-point theorem can be applied to ensure the existence of a unique metric via fixed-point iteration. For more details, we refer the reader to [10, 11]. More recently, an *on-policy* bisimulation metric was proposed [8].

Definition 2 (On-policy bisimulation metric [8]). *Given a fixed policy π, the following on-policy bisimulation metric exists and is unique:*

$$d_\pi(\mathbf{s}_i, \mathbf{s}_j) := |r_i^\pi - r_j^\pi| + \gamma W_1(d_\pi)(\mathcal{P}^\pi(\cdot|\mathbf{s}_i), \mathcal{P}^\pi(\cdot|\mathbf{s}_j)), \tag{2}$$

---

[1]Pseudo-metrics are a generalization of metrics that allow distinct points to have zero distance. For simplicity, we broadly use the term "metric" in the remainder of this paper at the cost of imprecision.

138 *where $r_i^\pi \coloneqq \mathbb{E}_{a \sim \pi}[R(\mathbf{s}_i, \mathbf{a})]$ and $\mathcal{P}^\pi(\cdot|\mathbf{s}_i) \coloneqq \mathbb{E}_{\mathbf{a} \sim \pi}[\mathcal{P}(\cdot|\mathbf{s}_i, \mathbf{a})]$.*

139 Zhang et al. [36] proposed to learn a similar on-policy bisimulation metric directly in the embedding
140 space via an MSE objective. They proposed an algorithm for jointly learning a policy $\pi(\mathbf{a}|\phi(\mathbf{s}))$ with
141 an on-policy bisimulation metric. Below, we define a generalized variant of their objective:

$$J(\phi) \coloneqq \frac{1}{2}\mathbb{E}\left[\left(\widehat{d}_{\pi,\phi}(\mathbf{s}_i, \mathbf{s}_j) - |r_i^\pi - r_j^\pi| - \gamma W_2(\|\cdot\|_{q_1})(\widehat{\mathcal{P}}^\pi(\cdot|\phi(\mathbf{s}_i)), \widehat{\mathcal{P}}^\pi(\cdot|\phi(\mathbf{s}_j)))\right)^2\right], \quad (3)$$

142 where $\widehat{d}_{\pi,\phi}(\mathbf{s}_i, \mathbf{s}_j) \coloneqq \|\phi(\mathbf{s}_i) - \phi(\mathbf{s}_j)\|_{q_2}$ and they used ($q_1 = 2, q_2 = 1$). Notice that the recursion
143 induced by this objective is different from prior metrics in three ways; (i) a W_2 metric was used
144 instead of a W_1 metric since W_2 has a convenient closed form for Gaussian distributions when
145 $q_1 = 2$, (ii) the distance function used for the bisimulation metric and the Wasserstein metric are
146 different (L_1 and L_2 respectively), and (iii) a forward dynamics model is used instead of the ground
147 truth dynamics. While they may introduce practical benefits, these differences violate the conditions
148 under which the existence of a unique bisimulation metric has been proven [8, 10, 11, 12]. Thus,
149 we will (i) assume a unique metric exists for all Wasserstein metrics W_p (see Assumption 1), (ii)
150 study losses that use a matching metric, i.e., $q_1 = q_2 = q$, and (iii) introduce a constraint on forward
151 models in Sec. 3.2.2.

152 Next, we note that they recommend the use of stop gradients for the W_2 term. The resulting gradient
153 updates may be considered as approximate fixed-point iteration in the space of metrics:

$$\widehat{\mathcal{F}}(\widehat{d}_\pi(\phi_n, \widehat{\mathcal{P}}))(\mathbf{s}_i, \mathbf{s}_j) \coloneqq \widehat{d}_\pi(\mathbf{s}_i, \mathbf{s}_j; \phi_n + \alpha_n \nabla_\phi J(\phi_n), \widehat{\mathcal{P}}), \quad (4)$$

154 where α_n is a learning rate. However, in practice, π and $\widehat{\mathcal{P}}$ may also be updated in training, which is
155 of particular relevance when they have form $\pi(\mathbf{a}|\phi(\mathbf{s}))$ and $\widehat{\mathcal{P}}(\phi(\mathbf{s}')|\phi(\mathbf{s}), \mathbf{a})$ as in [36]. In the next
156 section, we will discuss conditions under which joint updates to a policy π and a metric defined by
157 state encodings ϕ may or may not converge in practical settings:

$$\lim_{n \to \infty} \mathcal{F}^{(n)}(\pi, \widehat{d}_{\pi,\phi}) \overset{?}{=} d_{\pi^*}, \quad (5)$$

158 where d_{π^*} is the on-policy bisimulation metric for the optimal policy π^*.

3.2 Theoretical Analysis

160 In this section, we generalize prior value function bounds for bisimulation metrics to cases where
161 arbitrary weighting constants c_R, c_T are used, and further derive a value function approximation
162 (VFA) bound for V^π rather than V^* unlike prior work [10, 11, 36]. We then describe constraints on
163 forward dynamics models for convergence to a unique metric in joint training, and derive VFA bounds
164 as a function of forward dynamics modelling error. Then, we discuss potential pitfalls in on-policy
165 bisimulation metric learning, which lead us to connecting its weaknesses with sparse rewards. Our
166 findings motivate our proposed remedies to the issues we identify in on-policy bisimulation; we
167 recommend a particular norm constraint on the latent space, and motivate the use of inverse dynamics
168 and intrinsic motivation outlined in Sec. 3.3. All proofs are provided in Appendix B.

3.2.1 Value Function Bounds

170 An important feature of bisimulation metrics is their relation to value functions since a provably
171 tight connection implies guarantees in VFA. Similarly to previous bounds for policy-independent
172 bisimulation metrics [10, 11], Castro [8] showed that given any two states $(\mathbf{s}_i, \mathbf{s}_j)$, the following
173 bound holds for on-policy bisimulation metrics (see Definition 2): $|V(\mathbf{s}_i) - V(\mathbf{s}_j)| \leq d_\pi(\mathbf{s}_i, \mathbf{s}_j)$.
174 As discussed earlier, differently from previous approaches, Zhang et al. [36] used a 2-Wasserstein
175 metric due to practical reasons. Here, we assume the existence of a unique bisimulation metric for
176 p-Wasserstein metrics and generalize previous value function bounds.

177 **Assumption 1** (p-Wasserstein bisimulation metric). *For a given $c_T \in [0, 1)$, $c_R \in [0, \infty)$ and $p \geq 1$,*
178 *the following bisimulation metric exists and is unique:*

$$d_\pi(\mathbf{s}_i, \mathbf{s}_j) \coloneqq c_R|r_i^\pi - r_j^\pi| + c_T W_p(d_\pi)(\mathcal{P}^\pi(\cdot|\mathbf{s}_i), \mathcal{P}^\pi(\cdot|\mathbf{s}_j)). \quad (6)$$

179 **Remark 1.** *If $p = 1$, or both the environment and policy are deterministic, Assumption 1 holds.*

Figure 1: Theoretical properties under the SparseCartpole task. (**Left**) Embedding explosion occurs for DBC [36] for the sparse 2D-Cartpole task, while our constraints discussed in Sec. 3.2.2 keep the model stable ($\mathrm{diam}(\mathcal{S}) \leq 100$). Our approach achieves maximum returns at evaluation, while DBC diverges. (**Right**) Given $c_T = 0.5$, Eq. (16) correctly predicts the ratio $\mu_{bd}^\pi/\mu_{rd}^\pi$ between bisimulation distance and difference of rewards at convergence. Dashed lines indicate analytically calculated targets, while solid lines correspond to mini-batch estimates of the ratio during training.

Theorem 1 (Generalized value difference bound). *Let the reward function be bounded as $R \in [0, 1]$. For an on-policy bisimulation metric given by Eq. (6), for any $c_T \in [0, 1)$ and $p \geq 1$, the bisimulation distance between a pair of states upper-bounds the difference in their values:*

$$c_R|V^\pi(\mathbf{s}_i) - V^\pi(\mathbf{s}_j)| \ \leq \ d_\pi(\mathbf{s}_i, \mathbf{s}_j) + \max\left(0, \frac{2c_R(\gamma - c_T)}{(1-\gamma)(1-c_T)}\right), \ \forall(\mathbf{s}_i, \mathbf{s}_j) \in \mathcal{S} \times \mathcal{S}. \quad (7)$$

Note that Thm. 3 of [8] is a special case with $c_R = p = 1$ and $c_T = \gamma$. Suppose $c_T \geq \gamma$; we observe that for a degenerate metric $d_\pi = 0$, the corresponding value function is a constant $V^\pi(\mathbf{s}) = c$. We will discuss the dangers posed by this relation in Section 3.2.3.

Theorem 2 (Generalized VFA bound). *Let rewards be bounded as $R \in [0, 1]$ and $\Phi : \mathcal{S} \to \widetilde{\mathcal{S}}$ be a function mapping states to a finite partitioning $\widetilde{\mathcal{S}}$ such that $\Phi(\mathbf{s}_i) = \Phi(\mathbf{s}_j) \Rightarrow d_\pi(\mathbf{s}_i, \mathbf{s}_j) \leq 2\epsilon$, which produces an aggregated MDP $\langle \widetilde{\mathcal{S}}, \mathcal{A}, \widetilde{\mathcal{P}}, \widetilde{R}, \widetilde{\rho}_0 \rangle$. For any $c_T \in [0, 1)$:*

$$|V^\pi(\mathbf{s}_i) - \widetilde{V}^\pi(\Phi(\mathbf{s}_i))| \ \leq \ \frac{2\epsilon}{c_R(1 - \min(c_T, \gamma))} + \max\left(0, \frac{\gamma - c_T}{(1-\gamma)(1-c_T)}\right), \ \forall \mathbf{s}_i \in \mathcal{S}. \quad (8)$$

The last two theorems highlight the possibility that while $c_T \geq \gamma$ provides a tighter VFA bound, other choices may also be acceptable for learning useful metrics. We further show in the next section that $c_T < \gamma$ may be desirable when approximate forward models are used (see Thm. 4). Indeed, we empirically investigate the use of $c_T < \gamma$ in Appendix C and find surprisingly strong results. We also speculate that with sufficient modelling capacity and a critic $V(\phi)$ being trained based on γ, the metric space may hold information about the environment regarding both timescales γ and c_T, while enjoying lower variance for specific choices of c_T (see Appendix C).

3.2.2 Bisimulation Metrics with Approximate Forward Dynamics

We next examine theoretical properties of the on-policy bisimulation distance, which turn out to constrain properties of the approximate transition model. This motivates an additional architectural constraint, resulting in empirical improvements over prior work.

Metrics prior to [36] were defined based on ground-truth dynamics, which enabled the application of the Banach fixed-point theorem to show the existence of a unique metric. However, the Banach fixed-point theorem requires that a contraction mapping is applied on complete metric spaces. For that reason, when bisimulation metrics were generalized from finite to continuous MDPs, a compact state space was assumed [11]. In practice, when using an approximate forward dynamics model $\widehat{\mathcal{P}} : \mathcal{S} \times \mathcal{A} \to \mathcal{M}(\mathcal{S}')$[2], if compactness is not guaranteed, the same convergence guarantees do not apply. Thus, ideally, $\mathcal{S}'$ is a compact subset of $\mathcal{S}$. Here, we formalize these restrictions on latent

---

[2]$\mathcal{M}(\mathcal{X})$ denotes the space of all probability distributions over $\mathcal{X}$.

representations and the forward dynamics model to guarantee convergence to a unique metric. The following states a constraint on the BSM solution space given approximate dynamics.

Lemma 1 (Diameter of $\mathcal{S}$ is bounded). *Let $d : \mathcal{S} \times \mathcal{S} \to [0, \infty)$ be any bisimulation metric:*

$$\text{diam}(\mathcal{S}; d) = \sup_{\mathbf{s}_i, \mathbf{s}_j \in \mathcal{S} \times \mathcal{S}} d(\mathbf{s}_i, \mathbf{s}_j) \leq \frac{c_R}{1 - c_T}(R_{\max} - R_{\min}). \tag{9}$$

Next, we provide a sufficient condition for the existence of a unique metric $\widehat{d}_\pi$, which, when satisfied, shrinks the solution space of metrics being searched to a set known to contain d_π due to Lemma 1.

Theorem 3 (Boundedness condition for convergence). *Assume $\mathcal{S}$ is compact. Given a forward dynamics model $\widehat{\mathcal{P}}$, for all $c_T \in [0, 1)$ and $p = 1$, if the support of $\widehat{\mathcal{P}}$ is a closed subset of $\mathcal{S}$, then there exists a unique on-policy bisimulation metric $\widehat{d}_\pi$ of the form Eq. (6), and this metric is bounded:*

$$\text{supp}(\widehat{\mathcal{P}}) \subseteq \mathcal{S} \Rightarrow \text{diam}(\mathcal{S}; \widehat{d}_\pi) \leq \frac{c_R}{1 - c_T}(R_{\max} - R_{\min}). \tag{10}$$

If this condition is not satisfied at any point during training, the system may diverge. Indeed, we confirm empirically in Sec. 4 that the absence of a norm constraint on the forward dynamics model may result in embedding explosion with practical consequences (see Fig. 1). Luckily, the condition can be satisfied with ease, e.g., by projecting larger vectors onto the surface of a closed ball with diameter given in Lemma 1, such that the following are true:

$$\phi(\mathbf{s}) \in \mathbb{B}_c = \{\mathbf{x} \in \mathbb{R}^d \mid d(\mathbf{x}, \mathbf{0}) \leq \frac{c_R(R_{\max} - R_{\min})}{2(1 - c_T)}\}, \ \forall \mathbf{s} \in \mathcal{S} \tag{11}$$

$$\widehat{\mathcal{P}}(\cdot | \phi(\mathbf{s}), \mathbf{a}) \in \mathcal{M}(\mathbb{B}_c), \ \forall (\mathbf{s}, \mathbf{a}) \in \mathcal{S} \times \mathcal{A}. \tag{12}$$

We find that the constraint applied here is mild yet effective, as evidenced by significantly improved performance and stability when the constraints are active (see Fig. 1).

Clearly, a necessary condition for $\widehat{d}_\pi \to d_\pi$ is an error-free dynamics model. A natural question that arises from this view concerns the degree to which modelling errors affect VFA bounds.

Theorem 4 (VFA bound in terms of model error). *Consider the same conditions as in Theorem 2, except that $c_T \in [\gamma, 1)$, $p = 1$, and $\Phi(\mathbf{s}_i) = \Phi(\mathbf{s}_j) \Rightarrow \widehat{d}_{\pi,\phi}(\mathbf{s}_i, \mathbf{s}_j) \leq 2\widehat{\epsilon}$. Then:*

$$|V^\pi(\mathbf{s}) - \widetilde{V}^\pi(\Phi(\mathbf{s}))| \leq \frac{1}{c_R(1 - \gamma)} \left(2\widehat{\epsilon} + \mathcal{E}_\phi + \frac{2c_R}{1 - c_T}\mathcal{E}_r + \frac{2c_T}{1 - c_T}\mathcal{E}_\mathcal{P} \right). \tag{13}$$

where $\mathcal{E}_\phi := \|\widehat{d}_{\pi,\phi} - \widehat{d}_\pi\|_\infty$ is the metric learning error, $\mathcal{E}_r := \|\widehat{r}^\pi - r^\pi\|_\infty$ is the reward approximation error, and $\mathcal{E}_\mathcal{P} := \sup_{\mathbf{s} \in \mathcal{S}} W_1(d_\pi)(\mathcal{P}^\pi(\cdot|\mathbf{s}), \widehat{\mathcal{P}}^\pi(\cdot|\mathbf{s}))$ is the state transition model error.

See Appendix D for details. Consider an ideal case where ground-truth rewards r^π are available and the metric is learned perfectly (i.e., $\mathcal{E}_\phi = \mathcal{E}_r = 0$). Then, we observe that the choice of c_T defines a trade-off between VFA error due to (a) forward model error $\mathcal{E}_\mathcal{P}$, and (b) "myopic" bisimulation (see Thm. 2, $c_T < \gamma$), where the BSM timescale is shorter than that of the discounted return.

3.2.3 On the Dangers of On-policy Bisimulation

Suppose that at training time, $|r_i^\pi - r_j^\pi| = 0$ for all pairs of states, e.g., during early training in a sparse reward setting. Then, unlike the policy-independent bisimulation metric, the on-policy formulation has a degenerate solution at $\text{diam}(\mathcal{S}; d_\pi) = 0$, regardless of the structure of the underlying MDP.

Lemma 2 (A reason for caution in on-policy bisimulation). *On-policy bisimulation metrics of the form Eq. (6) have an upper bound determined by their policy:*

$$\text{diam}(\mathcal{S}; d_\pi) \leq \frac{c_R}{1 - c_T} \sup |r_i^\pi - r_j^\pi|. \tag{14}$$

Due to policy-dependence, the target metric d_π changes with each policy update during joint training. As a result of this difficulty, convergence to a unique fixed point (i.e., a unique metric) for a learning algorithm was previously guaranteed with a strong assumption: "a policy that is continuously

241 improving", as in Thm. 1 of [36]. Informally, if the policy is assumed to be continuously improving,
242 in the worst case, the metric will have a fixed point d_{π^*} after the policy itself reaches a fixed point,
243 namely, the optimal policy π^*. However, this assumption may be too strong to guarantee convergence
244 especially for continuous MDPs, as the policy learning process depends heavily on the encoder.

245 Specifically, to prove their Thm. 1, Zhang et al. [36] relied on the policy improvement theorem. For
246 continuous MDPs, in practice, a policy $\pi(\mathbf{a}|\phi(\mathbf{s}))$ is learned via non-convex optimization (e.g., policy
247 gradients, VFA), rather than the vanilla policy improvement algorithm. Thus, if the bisimulation
248 metric is degenerate, a continuously improving policy cannot be guaranteed (see Eq. (23)). As we
249 will show, on-policy bisimulation metrics can in fact obstruct policy search in some cases (e.g., sparse
250 rewards, low dispersion rewards) by yielding a collapsed or exploded metric space, which is unable
251 to approximate the value function. Specifically, we can define and relate measures of (i) collapse in
252 the embedding space, and (ii) statistical dispersion of rewards under the current policy.

Definition 3 (Measuring collapse and sparse rewards). *Let ρ^π denote the stationary distribution over
states, and ν^π the distribution over pairs of states, $(\mathbf{s}_i, \mathbf{s}_j)$ sampled independently from ρ^π. Then;*

$$\mu_{bd}^\pi := \mathbb{E}_{(\mathbf{s}_i, \mathbf{s}_j) \sim \nu^\pi}[d^\pi(\mathbf{s}_i, \mathbf{s}_j)] \qquad\qquad \mu_{rd}^\pi := \mathbb{E}_{(\mathbf{s}_i, \mathbf{s}_j) \sim \nu^\pi}[|r_i^\pi - r_j^\pi|]. \tag{15}$$

255 In the low dispersion case, $\mu_{rd}^\pi \approx 0$, meaning the current reward signal under π is uninformative.
256 However, this can have dire consequences for our embedding, as shown in the lemma below.

Lemma 3 (Relating collapse and low-dispersion rewards). *Assume deterministic transitions and the
existence of a stationary distribution ρ_π over states. Given a bisimulation metric of the form Eq. (6):*

$$\mu_{bd}^\pi = \frac{c_R}{1 - c_T} \mu_{rd}^\pi. \tag{16}$$

259 Clearly, a collapsed state encoder, $\phi^*(\mathbf{s}_i) = \phi_0$, loses all information about the state ($\mathcal{H}_{\rho^\pi}(\phi(\mathbf{s})) = 0$).
260 These observations motivate us to extend the method with inverse dynamics-based regularization and
261 intrinsic rewards based on forward prediction errors (see Sec 3.3), since they promote $\mu_{bd}^\pi, \mu_{rd}^\pi > 0$
262 respectively. For empirical evidence of the relation in Lemma 3 at training-time, see Figure 1.
263 Relationships between variances are also discussed in Appendix C.

3.3 Intrinsic Rewards and Inverse Dynamics

265 The core principle of DBC is to construct a representation such that a given $\phi(\mathbf{s})$ relates to other latent
266 states via the PBSM, thus providing robustness to distractors, but also ensuring the latent state holds
267 sufficient information to maximize return. As already discussed, however, uninformative rewards can
268 induce metric learning issues for DBC, causing the embedding to hold insufficient information to
269 solve the task. We consider two approaches to improving upon this representational deficiency: (1)
270 using intrinsic rewards (IR), and (2) regularizing the latent space with inverse dynamics (ID) learning.

Curiosity-Driven Intrinsic Rewards One technique for encouraging exploration in sparse-reward
272 environments uses intrinsic motivation via self-generated rewards, based on a notion of curiosity
273 [6, 3]. In such cases, the agent rewards itself for entering unpredictable areas of the environ-
274 ment: in particular, at every time step t, we redefine the reward signal to be $r_t = r_{I,t} + r_{E,t}$,
275 where $r_{E,t}$ is the extrinsic reward (i.e., the original environmental reward) and $r_{I,t}$ is the IR.
276 Following prior work [6, 27, 31], we use the forward model error in the latent space for the
277 latter: $\widetilde{r}_{I,t} := \frac{\eta_r}{2d}||\widehat{\phi}_\mu(\mathbf{s}_t, \mathbf{a}_t) - \phi(\mathbf{s}_{t+1})||_2^2$, where $\widehat{\phi}_\mu(\mathbf{s}_t, \mathbf{a}_t) = \mathbb{E}_{\phi(\mathbf{s}_{t+1}) \sim \widehat{\mathcal{P}}(\cdot|\phi(\mathbf{s}_t), \mathbf{a}_t)}[\phi(\mathbf{s}_{t+1})]$ is
278 the mean of the predicted distribution from the forward dynamics model and $\eta_r > 0$ is a hyper-
279 parameter controlling the intrinsic reward scale. We finally clamp to a fixed maximum $R_{\max, I}$, so
280 that $r_{I,t} = \min(R_{\max, I}, \widetilde{r}_{I,t})$. We already train $\widehat{\mathcal{P}}$ for the DBC loss, so the additional computational
281 cost is limited. Finally, note that IRs cause the reward signal to become non-stationary, resulting in
282 the target of the BSM learning changing as well; however, as the agent explores and can better predict
283 its environment over time, the IR (and thus its influence on the metric learning process) should fade.

Latent Inverse Dynamics Prior We also consider regularizing the learned latent state space, by
285 having it learn to predict the inverse dynamics of the world, following prior work [2, 27]. Let
286 $g_I : \mathbb{R}^d \times \mathbb{R}^d \to \mathcal{A}$ be an inverse model, which predicts the action $\mathbf{a}_t \in \mathcal{A}$ that changed $\mathbf{s}_t$ to $\mathbf{s}_{t+1}$
287 using the learned latent space: $\widehat{\mathbf{a}}_t := g_I(\phi(\mathbf{s}_t), \phi(\mathbf{s}_{t+1}))$. This can be trained from observed transitions
288 $(\mathbf{s}_t, \mathbf{a}_t, \mathbf{s}_{t+1})$, via $J_d(\phi, g_I; \eta_d) := \frac{\eta_d}{d_a}||\mathbf{a}_t - \widehat{\mathbf{a}}_t||_1$, where $\eta_d > 0$ weighs the ID loss importance, and

Figure 2: Results on the *modified* Gym tasks: Cartpole (**top row**) and Mountain Car (**bottom row**). The left, middle, and right columns have 0, d, and $2d$ distractor noise dimensions respectively. We show the Soft Actor-Critic (*SAC*) and Deep Bisimulation for Control (*DBC*) baselines, along with our modifications using embedding normalization (*normed*), intrinsic rewards (*IR*), and inverse dynamics (*ID*). DBC struggles under all conditions of sparsity; while SAC handles it better (top-left), it cannot deal with high distraction (top-right) or more extreme sparsity (bottom row). However, latent normalization immediately improves performance (top row). Further, combining it with IR or IR+ID obtains superior performance on all tasks. Shading shows standard error over 10 seeds.

$\mathcal{A} = [-1, 1]^{d_a}$ for continuous control tasks. This loss prevents removal of information that pertains to the agent's ability to control the environment, but it is balanced against the loss driving ϕ to mimic the BSM. In this sense, we are placing a regularizing prior on ϕ via an auxiliary task, such that it adheres to the BSM requirement when possible, but still transmits useful information in the sparse reward case instead of collapsing. Yet, since only *actions* need be predicted, distractor aspects of the observation that the agent cannot influence are naturally ignored. Hence, we expect less disruption to the BSM encoding than other auxiliary tasks (e.g., reconstruction).

Summary In this section, we (1) provided generalized bounds connecting the value function to the on-policy BSM (Sec. 3.2.1); (2) showed that the BSM satisfies a fixed latent diameter, and devised a normalization for enforcing this property during learning (Sec. 3.2.2), which not only prevents embedding explosion but improves performance (Fig. 1); and (3) found the PBSM is susceptible to embedding collapse with sparse rewards, and suggested IR and ID to mitigate it (Sec. 3.2.3, 3.3).

4 Experiments

In this section, we seek answers to the following questions concerning our main hypotheses:

1. Do the embedding collapse and explosion issues predicted theoretically occur in practice?
2. Do our contributions address these problems?
3. Does our proposed approach preserve the noise-invariance property of bisimulation?
4. How do our proposed improvements interact with each other?
5. How does our method perform compared to prior work, particularly with sparse rewards?

To that end, we experiment on several altered classic control tasks from OpenAI Gym [5] by (i) sparsifying the reward signal, and (ii) augmenting the environment state with noisy dimensions, to simulate distractions. We also perform larger scale experiments on two challenging vision-based 3D robotics benchmarks from the DeepMind Control Suite [33].

Sparse Noisy Cartpole First, we modified the `Cartpole-v0` task, in which an agent tries to keep a pole upright. To increase sparsity, we shrank the angular extent in which the pole must be to earn rewards to 1% of its standard value. Then, to mimic distractors, we concatenate an $N_m d$-dimensional vector sampled from an isotropic Gaussian to the d-dimensional state vector. (See Appendix E.1.1

Figure 3: Performance on 3D robotics tasks from DMC [33]. (**Left**) Our method significantly improves upon DBC [36] and is on par with SAC [17]. (**Right**) DBC struggles under sparse rewards, while our approach remains robust (5 random seeds).

for more details.) The performance of the respective models, as well as other baselines are shown in Fig. 2, top row. While DBC struggles on this task due to the sparsity, the Soft Actor-Critic (SAC, [17]) baseline, which does not use BSMs, is able to solve the problem (top-left inset). Our proposed modifications address the embedding explosion problem and perform on-par with the SAC baseline, both when combined and separately. Furthermore, when distractors are introduced (top-middle and top-right insets), SAC also fails, while our approach combining intrinsic rewards (IR) and robust metric learning still solves the task. See also Appendix E.1.4 for results with $N_m = 3$.

Noisy Mountain Car We also consider the classic `MountainCarContinuous-v0` task [23], in its continuous control form (see Appendix E.1.2 for details). Since the task was already highly sparse, we modified only the distraction aspect, as in the Cartpole scenario. As shown in Fig. 2, all methods without IR are unable to solve the task and are stuck with rewards close to zero. However, DBC with IR is unstable and unable to solve the task either. Only using the normalization allows the agent to succeed; furthermore, the inverse dynamics (ID) regularization improves convergence speed and stability. This trend continues at even higher distraction levels as well (see Appendix E.1.4).

Sparse Noisy Pendulum We also modified the continuous `Pendulum-v0` task to have a higher degree of sparsity and distraction. Due to space constraints, we relegate details to Appendix E.1.3. We find that our method performs on par with DBC, but outperforms SAC in the presence of distractions.

DeepMind Control Suite We also include results on two simulated 3D robotics tasks [33], namely, `cheetah-run` and `cartpole-swingup-sparse`, shown in Figure 3. The former is a common benchmark where Zhang et al. [36] showed that their method performed sub-par in the *absence* of distractors. The latter is a task we select due to reward sparsity. With these experiments, we verify that our improvements carry over to larger-scale tasks where learning is over raw-pixels.

5 Conclusion

Limitations and Impact One shortcoming of our approach is the lack of a principled way to set hyper-parameters for IR and ID, which was done empirically. Indeed, our use of forward model error and ID regularization itself may not be optimal. Sometimes, we observe that the embeddings all attain norms close to the maximum allowed value, suggesting alternative approaches to normalization may be helpful. Finally, IR and ID incur an additional computational cost to training. In terms of broader impact, while our work is foundational RL, it focuses on removing distractions from internal representations. However, this culling can remove information that the agent deems unrelated to the task, potentially leading to unsafe decisions in unseen scenarios (e.g., for mission critical systems).

Discussion In this work, we investigated the behavior of on-policy deep bisimulation metric learning approaches, which construct efficient neural representations that are invariant to noise and distractors, without reconstructing the raw input [8, 36]. We identified embedding collapse and explosion as potential failure modes of this method via theoretical analysis, and highlighted that it may be especially susceptible to failure in sparse reward settings. Our experiments confirmed the dangers of these failure modes and showed that our proposed remedies address the issue. In particular, we enforced a norm constraint on state representations, and incorporated intrinsic motivation and latent regularization in our technique. The resulting approach preserves the noise-invariance property of bisimulation metrics while comparing favorably against strong baselines [17, 36] on altered versions of classic control tasks, which we rendered more challenging by sparsifying the rewards and synthesizing distractors, as well as harder tasks with visual observations. Future work could include more realistic 3D robotics benchmarks, with sparse reward structures and heavy distraction.

References

[1] Joshua Achiam and Shankar Sastry. Surprise-based intrinsic motivation for deep reinforcement learning. *arXiv preprint arXiv:1703.01732*, 2017.

[2] Pulkit Agrawal, Ashvin Nair, Pieter Abbeel, Jitendra Malik, and Sergey Levine. Learning to poke by poking: experiential learning of intuitive physics. *arXiv preprint arXiv:1606.07419*, 2016.

[3] Arthur Aubret, Laetitia Matignon, and Salima Hassas. A survey on intrinsic motivation in reinforcement learning. *arXiv preprint arXiv:1908.06976*, 2019.

[4] Marc G Bellemare, Sriram Srinivasan, Georg Ostrovski, Tom Schaul, David Saxton, and Remi Munos. Unifying count-based exploration and intrinsic motivation. *arXiv preprint arXiv:1606.01868*, 2016.

[5] Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. OpenAI gym. *arXiv preprint arXiv:1606.01540*, 2016.

[6] Yuri Burda, Harri Edwards, Deepak Pathak, Amos Storkey, Trevor Darrell, and Alexei A Efros. Large-scale study of curiosity-driven learning. *arXiv preprint arXiv:1808.04355*, 2018.

[7] Pablo Castro and Doina Precup. Using bisimulation for policy transfer in mdps. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 24, 2010.

[8] Pablo Samuel Castro. Scalable methods for computing state similarity in deterministic Markov decision processes. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 10069–10076, 2020.

[9] Philippe Clement and Wolfgang Desch. An elementary proof of the triangle inequality for the Wasserstein metric. *Proceedings of the American Mathematical Society*, 136(1):333–339, 2008.

[10] Norm Ferns, Prakash Panangaden, and Doina Precup. Metrics for finite Markov decision processes. In *Proceedings of the 20th Conference on Uncertainty in Artificial Intelligence*, UAI '04, page 162–169, Arlington, Virginia, USA, 2004. AUAI Press.

[11] Norm Ferns, Prakash Panangaden, and Doina Precup. Bisimulation metrics for continuous Markov decision processes. *SIAM J. Comput.*, 40(6):1662–1714, December 2011.

[12] Norm Ferns and Doina Precup. Bisimulation metrics are optimal value functions. In *Proceedings of the Thirtieth Conference on Uncertainty in Artificial Intelligence*, UAI'14, page 210–219, Arlington, Virginia, USA, 2014. AUAI Press.

[13] Carles Gelada, Saurabh Kumar, Jacob Buckman, Ofir Nachum, and Marc G Bellemare. Deep-MDP: Learning continuous latent space models for representation learning. In *International Conference on Machine Learning*, pages 2170–2179. PMLR, 2019.

[14] Dibya Ghosh, Abhishek Gupta, and Sergey Levine. Learning actionable representations with goal-conditioned policies. *arXiv preprint arXiv:1811.07819*, 2018.

[15] Karol Gregor, Danilo Jimenez Rezende, and Daan Wierstra. Variational intrinsic control. *arXiv preprint arXiv:1611.07507*, 2016.

[16] David Ha and Jürgen Schmidhuber. World models. *arXiv preprint arXiv:1803.10122*, 2018.

[17] Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International Conference on Machine Learning*, pages 1861–1870. PMLR, 2018.

[18] Tuomas Haarnoja, Aurick Zhou, Kristian Hartikainen, George Tucker, Sehoon Ha, Jie Tan, Vikash Kumar, Henry Zhu, Abhishek Gupta, Pieter Abbeel, et al. Soft actor-critic algorithms and applications. *arXiv preprint arXiv:1812.05905*, 2018.

[19] Danijar Hafner, Timothy Lillicrap, Ian Fischer, Ruben Villegas, David Ha, Honglak Lee, and James Davidson. Learning latent dynamics for planning from pixels. In *International Conference on Machine Learning*, pages 2555–2565. PMLR, 2019.

[20] Thanard Kurutach, Aviv Tamar, Ge Yang, Stuart Russell, and Pieter Abbeel. Learning plannable representations with causal InfoGAN. *arXiv preprint arXiv:1807.09341*, 2018.

[21] Michael Laskin, Aravind Srinivas, and Pieter Abbeel. Curl: Contrastive unsupervised representations for reinforcement learning. In *International Conference on Machine Learning*, pages 5639–5650. PMLR, 2020.

[22] Alex X Lee, Anusha Nagabandi, Pieter Abbeel, and Sergey Levine. Stochastic latent actor-critic: Deep reinforcement learning with a latent variable model. *arXiv preprint arXiv:1907.00953*, 2019.

[23] Andrew William Moore. Efficient memory-based learning for robot control. 1990.

[24] Ashvin Nair, Vitchyr Pong, Murtaza Dalal, Shikhar Bahl, Steven Lin, and Sergey Levine. Visual reinforcement learning with imagined goals. *arXiv preprint arXiv:1807.04742*, 2018.

[25] Masashi Okada and Tadahiro Taniguchi. Dreaming: Model-based reinforcement learning by latent imagination without reconstruction. *arXiv preprint arXiv:2007.14535*, 2020.

[26] Ingram Olkin and Friedrich Pukelsheim. The distance between two random vectors with given dispersion matrices. *Linear Algebra and its Applications*, 48:257–263, 1982.

[27] Deepak Pathak, Pulkit Agrawal, Alexei A Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *International Conference on Machine Learning*, pages 2778–2787. PMLR, 2017.

[28] Marek Petrik and Bruno Scherrer. Biasing approximate dynamic programming with a lower discount factor. In D. Koller, D. Schuurmans, Y. Bengio, and L. Bottou, editors, *Advances in Neural Information Processing Systems*, volume 21. Curran Associates, Inc., 2009.

[29] Christoph Salge, Cornelius Glackin, and Daniel Polani. Empowerment–an introduction. In *Guided Self-Organization: Inception*, pages 67–114. Springer, 2014.

[30] Filippo Santambrogio. Optimal transport for applied mathematicians. *Birkäuser, NY*, 55(58-63):94, 2015.

[31] Bradly C Stadie, Sergey Levine, and Pieter Abbeel. Incentivizing exploration in reinforcement learning with deep predictive models. *arXiv preprint arXiv:1507.00814*, 2015.

[32] Adam Stooke, Kimin Lee, Pieter Abbeel, and Michael Laskin. Decoupling representation learning from reinforcement learning. *arXiv preprint arXiv:2009.08319*, 2020.

[33] Yuval Tassa, Yotam Doron, Alistair Muldal, Tom Erez, Yazhe Li, Diego de Las Casas, David Budden, Abbas Abdolmaleki, Josh Merel, Andrew Lefrancq, et al. DeepMind control suite. *arXiv preprint arXiv:1801.00690*, 2018.

[34] Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pages 5026–5033. IEEE, 2012.

[35] Cédric Villani. *Optimal transport: old and new*, volume 338. Springer Science & Business Media, 2008.

[36] Amy Zhang, Rowan Thomas McAllister, Roberto Calandra, Yarin Gal, and Sergey Levine. Invariant representations for reinforcement learning without reconstruction. In *International Conference on Learning Representations*, 2021.

[37] Marvin Zhang, Sharad Vikram, Laura Smith, Pieter Abbeel, Matthew Johnson, and Sergey Levine. Solar: Deep structured representations for model-based reinforcement learning. In *International Conference on Machine Learning*, pages 7444–7453. PMLR, 2019.

[38] Brian D Ziebart. Modeling purposeful adaptive behavior with the principle of maximum causal entropy. 2010.