How Do Medical MLLMs Fail? A Study on Visual Grounding in Medical Images

Guimeng Liu [* 1] **Tianze Yu** [* 1] **Somayeh Ebrahimkhani** [* 1] **Lin Zhi Zheng Shawn** [2 3] **Kok Pin Ng** [2 3]
Ngai-Man Cheung [1]

Abstract

Generalist multimodal large language models (MLLMs) have achieved impressive performance across a wide range of vision-language tasks. However, their performance on medical tasks—particularly in zero-shot settings where generalization is critical—remains suboptimal. A key research gap is the limited understanding of why medical MLLMs underperform in medical image interpretation. **In this work**, we present a pioneering systematic investigation into the visual grounding capabilities of state-of-the-art medical MLLMs. To disentangle *visual grounding* from *semantic grounding*, we design VGMED, a novel evaluation dataset developed with expert clinical guidance, explicitly assessing the visual grounding capability of medical MLLMs. We introduce new quantitative metrics and conduct detailed qualitative analyses. Our study across **eight** state-of-the-art (SOTA) medical MLLMs validates that they often fail to ground their predictions in clinically relevant image regions. We note that this finding is specific to medical image analysis; in contrast, prior work has shown that MLLMs are capable of grounding their predictions in the correct image regions when applied to natural scene images. Motivated by these findings, we propose VGRefine, a simple yet effective inference-time method that refines attention distribution to improve visual grounding in medical settings. Our approach achieves SOTA performance across 6 diverse Med-VQA benchmarks (over 110K VQA sam-

ples from 8 imaging modalities) without requiring additional training or external expert models. Overall, our work, for the first time, systematically validates inadequate visual grounding as one of the key contributing factors for medical MLLMs' under-performance. Additional details and experiments are included in the Supp.

1. Introduction

Generalist multimodal large language models (MLLMs) have demonstrated strong performance across diverse vision-language tasks (Wang et al., 2024; Dai et al., 2023; Liu et al., 2023; Chen et al., 2024b; Liu et al., 2024b; Li et al., 2023b; Wu et al., 2024; Liu et al., 2024d; Zhuang et al., 2025; Shi et al., 2024), motivating their adaptation into medical MLLMs for clinical image understanding and decision support. Li et al. (2023a) build LLaVA-Med by fine-tuning LLaVA on biomedical figure-caption data from PubMed Central, but its zero-shot performance remains suboptimal and reliant on dataset-specific fine-tuning. Other recent systems leverage GPT-4V annotations or external medical expert models to strengthen medical image understanding. Xie et al. (2025) introduce MedTrinity-25M, a dataset comprising 25 million medical images, and propose LLaVA-Tri to improve regional focus in medical images. (See Supp. for detailed related work.)

Despite these advances, many medical MLLMs still rely on training or fine-tuning with downstream samples. They continue to underperform on medical VQA tasks in the zero-shot setting—where no downstream task samples are seen during training or fine-tuning—falling short of truly generalist medical MLLMs. This raises a key question: *Why do medical MLLMs struggle with medical image interpretation, despite their success in general-domain tasks?*

Research Gap. There remains a lack of analysis into the causes of medical MLLMs' suboptimal zero-shot performance, especially in terms of *how* and *where* predictions are derived from visual inputs. Without such analysis, it remains unclear whether limitations stem from weak clinical task understanding (semantic grounding) or from an inabil-

---

[*]Equal contribution . Ngai-Man Cheung is project lead. [1]Singapore University of Technology and Design, Singapore [2]Department of Neurology, National Neuroscience Institute, Singapore [3]Duke-NUS Medical School, Singapore. Correspondence to: Ngai-Man Cheung <ngaiman_cheung@sutd.edu.sg>, Kok Pin Ng <ng.kok.pin@singhealth.com.sg>.

Proceedings of the ICML 2026 3rd Workshop on Multi-modal Foundation Models and Large Language Models for Life Sciences, Seoul, Korea. 2026. Copyright 2026 by the author(s).

Figure 1. **Visual grounding issues in state-of-the-art medical MLLMs.** (a) Column 1 shows input medical images with expert-annotated ground-truth regions (red boxes). Columns 2–5 display attention distributions from representative medical MLLMs. (b) Column 1 shows natural scene images with annotated ground-truth bounding boxes, and column 2 shows attention distributions from LLaVA-v1.5. For the first time, we systematically validate that state-of-the-art medical MLLMs often suffer from *inadequate visual grounding*—they fail to accurately localize and interpret image regions that are clinically relevant to the question. We note that, in contrast, when applied to natural images, MLLMs are capable of grounding their predictions in the correct image regions (Zhang et al., 2025a). Attention maps are taken from the LLM layers identified as most relevant to visual grounding (see Sec. 2 for details).

ity to localize and interpret relevant image regions (visual grounding). Understanding these failure modes is essential for robust generalist medical MLLMs.

Our work underscores the importance of distinguishing between *semantic grounding* (Lu et al., 2024; Lyre, 2024) and *visual grounding* (Xiao et al., 2024) in medical tasks. This distinction is critical for Med-VQA, which—unlike general-domain VQA—often requires deep domain-specific reasoning. For example, answering "What diseases are included in the image?" requires reasoning about anatomical structures and visual features relevant to specific pathologies. A model may fail in *semantic grounding* if it lacks the medical knowledge to determine *what* to look for, or fail in *visual grounding* if it cannot accurately *localize and interpret* the relevant regions, even when it knows what to look for. As medical MLLMs increasingly incorporate large-scale biomedical knowledge to enhance semantic grounding, we argue that visual grounding may emerge as the primary bottleneck limiting further progress, yet it remains underexplored in current evaluations.

Our Contribution. In this work, we present a pioneering systematic investigation of failure modes and visual grounding capabilities in medical MLLMs (Fig. 1). To disentangle visual grounding from semantic grounding, we co-create VGMED with 3 clinicians, a dataset for Visual Grounding analysis of MEDical MLLMs. VGMED enables focused evaluation of whether MLLMs can accurately localize and interpret relevant regions in medical images. We introduce visual-grounding metrics, including AR, KL, and JS, together with qualitative analyses to assess whether model predictions are grounded in clinically relevant visual evidence (Sec. 2.2). *Critically, using VGMED to evaluate **eight SOTA medical MLLMs**, we reveal for the first time that even advanced models frequently rely on spurious or irrelevant regions, highlighting inadequate visual grounding as a pervasive failure mode.* This finding is specific to medical image analysis; prior work shows that MLLMs can ground predictions in correct image regions on natural images (Zhang et al., 2025a).

To address this, we propose VGRefine, a simple inference-time method that improves visual grounding by refining

internal attention distributions without additional training. Across 6 diverse Med-VQA benchmarks, comprising over 110K VQA samples from 8 imaging modalities, VGRefine consistently achieves improved and SOTA performance. Overall, our work offers new insights into medical MLLM failure modes and establishes visual grounding analysis as a diagnostic tool for advancing medical MLLMs.

2. Investigation of Visual Grounding in Medical MLLMs

Despite recent advances, medical MLLMs continue to underperform on complex medical image reasoning tasks, particularly in medical VQA (Hu et al., 2024; Jeong et al., 2024). In this work, we conduct a systematic study to validate that a key limitation lies in inaccurate visual grounding. As a starting point, we analyze attention maps from the model layers most relevant to visual grounding. As shown in Fig. 1, for medical images, MLLMs' attentions often fail to align with clinically relevant regions.

2.1. A New Dataset for Visual Grounding Analysis

Existing medical VQA datasets are ill-suited for visual grounding analysis. To rigorously evaluate medical MLLMs' visual grounding, we aim to systematically assess the extent to which their outputs are supported by clinically relevant regions of the image (e.g., organs, tissues, or lesions essential for answering a given question). However, existing medical VQA datasets are ill-suited for this purpose: many questions can be answered without referencing specific image regions, while abnormality- or knowledge-based questions require substantial medical knowledge to determine what to look for. These patterns may depend on clinical interpretation, making it difficult to determine whether model failures stem from inadequate semantic grounding or from visual grounding alone.

VGMED: A new dataset for Visual Grounding analysis of MEDical MLLMs co-created with clinicians. To address this gap, we build VGMED, an evaluation dataset focusing on visual grounding analysis. VGMED was co-created with three certified medical doctors and constructed from over 40 publicly available medical image segmentation datasets by converting segmentation masks into bounding boxes. To ensure diversity across imaging modalities and anatomical regions, we filter 13,962 samples, each consisting of a medical image paired with a ground-truth bounding box.

For each image-bbox pair, we construct clinically meaningful questions that target specific anatomical or pathological regions, guided by input from clinical experts. The questions are first generated using GPT-4 and subsequently reviewed and validated by medical professionals. They fall into two categories: *localization* and *attribute* questions; in total, VGMED contains approximately 28K image-bbox-question triplets. As the reference point, we randomly draw the same number of samples from MS COCO (Lin et al., 2014), using the same question generation pipeline for natural scene images. Fig. 2 summarizes the curation pipeline; additional construction, validation, prompt, and scale details are provided in Supp. B.

2.2. Quantifying MLLMs' Visual Grounding with Attention Maps

Measuring MLLMs' visual grounding. To evaluate how multimodal large language models (MLLMs) ground their predictions in visual evidence, we analyze internal attention maps that indicate which image regions the model attends to. Attention maps are widely used in recent studies to evaluate visual grounding in general-domain MLLMs (Zhang et al., 2025a; Kang et al., 2025; Kaduri et al., 2024); this enables us to directly compare visual grounding in medical images and natural scene images. We quantify alignment using Attention Ratio (AR), which measures how much attention mass falls inside the ground-truth box. Since AR does not capture how attention is distributed within the clinically relevant region, we further introduce KL and JS divergence to compare the normalized attention distribution with the annotated region; higher AR and lower KL/JS indicate better visual grounding. Full extraction details, formulas, and alternative grounding indicators are provided in Supp. B.3.

2.3. Experimental Setups

We conduct our analysis on 8 SOTA medical MLLMs, including LLaVA-Med (Li et al., 2023a), LLaVA-Tri (Xie et al., 2025), HuatuoGPT-Vision-7B/34B (Chen et al., 2024a), VILA-M3-8B/13B (Nath et al., 2024), MedRegA (Wang et al., 2025), and HuatuoGPT-V-Bio. We also include LLaVA-v1.5-7B (Liu et al., 2024a) on both medical and natural scene images as a general-domain reference. Additional setup details, including attention-map normalization and the BiomedCLIP variant, are provided in Supp. B.4 and Supp. H.

2.4. Empirical Analysis

Medical MLLMs exhibit inadequate visual grounding on medical images. Our layer-wise AR, KL, and JS analysis shows that all evaluated medical MLLMs align less with ground-truth regions on medical images than on natural images, with lower AR and higher KL/JS across most layers and both question types. In the reverse-domain comparison, LLaVA-v1.5 also fails to ground predictions in clinically relevant regions on medical images, whereas medical-domain models can ground predictions on natural images.

Figure 2. **Co-creation of VGMED with clinicians for visual grounding assessment.** Existing Med-VQA datasets often include questions about image modality or plane, which can be answered without referencing specific image regions. They also contain many abnormality- or knowledge-based questions that require substantial medical expertise to determine what to look for. As a result, existing datasets are not well-suited for analyzing visual grounding. In contrast, our dataset leverages LLM prompting and clinical expert guidance to generate clinically meaningful localization and attribute questions that are explicitly grounded in annotated image regions, enabling rigorous assessment of the visual grounding capabilities of medical MLLMs. **Best viewed in color and with zoom.**

Comprehensive qualitative analysis is provided in Supp. J.

> *Finding:* Medical MLLMs show weaker attention-region alignment on medical images than on natural images; reverse-domain evidence indicates a medical-domain-specific grounding failure.

3. Visual Grounding Refinement

Our analysis in Sec. 2 suggests that current medical MLLMs attend to both clinically relevant and irrelevant regions. We propose Visual Grounding Refinement (VGRefine), a training-free inference-time method that enhances visual grounding by suppressing attention to clinically irrelevant visual regions. VGRefine consists of two steps: Attention Triage and Attention Knockout.

Step I: Attention Triage — selecting high-confidence visual evidence. Medical MLLM attention maps are often noisy: they include clinically relevant regions but also substantial attention to irrelevant areas. VGRefine therefore selects the top K attention heads ranked by attention-region alignment on a reference set, aggregates their attention maps, and suppresses activations below percentile threshold $p\%$ by attention magnitude. The remaining high-confidence image-token regions are converted into a binary visual mask $\mathcal{M}$.

Step II: Attention Knockout — suppressing irrelevant visual input. VGRefine applies $\mathcal{M}$ to question-to-image attention during the forward pass, reducing information

flow from irrelevant visual tokens. This encourages the model to focus on clinically meaningful regions without additional training or model-parameter updates. The method figure, head-selection analysis, mask construction, and attention-knockout notation are provided in Supp. C.

4. Experiments

4.1. Evaluation Settings

Baselines. We compare VGRefine with open-source medical MLLMs, including Med-Flamingo (Moor et al., 2023), RadFM (Wu et al., 2023), LLaVA-Med-7B (Li et al., 2023a), LLaVA-Tri (Xie et al., 2025), MedPLIB (Huang et al., 2025), VILA-M3 (Nath et al., 2024), and HuatuoGPT-V (Chen et al., 2024a), as well as general-domain MLLMs LLaVA-v1.6-7B (Liu et al., 2024a) and Qwen-VL-Chat (Bai et al., 2023).

Benchmarks. We follow the evaluation protocol of Chen et al. (2024a) on six biomedical VQA benchmarks: VQA-RAD (Lau et al., 2018), SLAKE (Liu et al., 2021a), PathVQA (He et al., 2020), PMC-VQA (Zhang et al., 2023b), OmniMedVQA (Hu et al., 2024), and MMMU (Health & Medicine track) (Yue et al., 2024). All evaluations are zero-shot; detailed prompts, protocol details, and moved results are provided in Supp. D.

VGRefine. We apply VGRefine to HuatuoGPT-V (Chen et al., 2024a). Implementation details, including the COCO-based top-head selection, percentile filtering, and layer choice, are provided in Supp. D.

Figure 3. **Medical MLLMs demonstrate suboptimal visual grounding when applied to medical images.** Layer-wise AR, KL, and JS analysis shows weaker attention-region alignment on medical images than on natural scene images; the LLaVA-v1.5 comparison further supports this as a medical-domain-specific grounding failure. **Best viewed in color and with zoom.**

4.2. Experimental Results

Medical VQA Benchmarks. Table 1 reports closed-ended accuracy on four standard medical VQA datasets. VGRefine improves HuatuoGPT-V from 65.3% to 68.4% on average, with notable gains of +5.6% on VQA-RAD and +11.3% on PathVQA, outperforming all baselines. These results underscore that enhanced visual grounding contributes to better performance on medical VQA tasks. **Additional experiments, including MMMU, OmniMed-VQA, ablation studies, and clinician evaluation, are provided in Supp. D.**

5. Conclusion

In this work, we presented the first systematic analysis of visual grounding in medical MLLMs. Using VGMED and attention-based metrics, we showed that 8 SOTA medical MLLMs frequently fail to ground predictions in clinically relevant regions, helping explain their zero-shot underperformance. We further proposed VGRefine, a training-

Table 1. Accuracy on medical VQA datasets. To align with the evaluation protocol with HuatuoGPT-V (Chen et al., 2024a), we specifically used the closed-ended subset for evaluation. Evaluation on other subsets in Supp.

Model	VQA-RAD	SLAKE	PathVQA	PMC-VQA	Avg.
Qwen-VL-Chat	47.0	56.0	55.1	36.6	48.9
LLaVA-v1.6-7B	52.6	57.9	47.9	35.5	48.5
Med-Flamingo	45.4	43.5	54.7	23.3	41.7
RadFM	50.6	34.6	38.7	25.9	37.5
LLaVA-Med-7B	51.4	48.6	56.8	24.7	45.4
LLaVA-Tri	59.8	43.4	59.0	-	-
HuatuoGPT-V-7B	67.4	76.5	60.7	53.9	65.3
VGRefine (Ours)	**71.2**	**76.9**	**67.6**	**56.2**	**68.4**

free inference-time method that improves visual grounding. Across 6 Med-VQA benchmarks comprising over 110K VQA samples from 8 imaging modalities, VGRefine achieves SOTA performance, supporting visual grounding as a performance-relevant bottleneck. Overall, VGMED diagnoses inadequate visual grounding, while VGRefine shows that grounding-aware refinement can improve reliability and generalization. **Additional experiments, limitations, and ethical considerations are included in Supp.**

Acknowledgment

This research is supported by the National Research Foundation, Singapore under its AI Singapore Programmes (AISG Award No.: AISG2-TC-2022-007); The Agency for Science, Technology and Research (A*STAR) under its MTC Programmatic Funds (Grant No. M23L7b0021). This research is supported by the National Research Foundation, Singapore and Infocomm Media Development Authority under its Trust Tech Funding Initiative. Any opinions, findings and conclusions or recommendations expressed in this material are those of the author(s) and do not reflect the views of National Research Foundation, Singapore and Infocomm Media Development Authority. The work is sponsored by the SUTD Decentralised Gap Funding Grant.

References

Al-Dhabyani, W., Gomaa, M., Khaled, H., and Fahmy, A. Dataset of breast ultrasound images. *Data in Brief*, 28:104863, February 2020. doi: 10.1016/j.dib.2019. 104863. Retrieved: September 25, 2025.

Antonelli, M., Reinke, A., Bakas, S., Farahani, K., Kopp-Schneider, A., Landman, B. A., Litjens, G., Menze, B., Ronneberger, O., Summers, R. M., et al. The medical segmentation decathlon. *Nature communications*, 13(1): 4128, 2022.

Bai, J., Bai, S., Yang, S., Wang, S., Tan, S., Wang, P., Lin, J., Zhou, C., and Zhou, J. Qwen-vl: A versatile vision-language model for understanding, localization, text reading, and beyond. *arXiv preprint arXiv:2308.12966*, 2023.

Baid, U., Ghodasara, S., Mohan, S., Bilello, M., Calabrese, E., Colak, E., Farahani, K., Kalpathy-Cramer, J., Kitamura, F. C., Pati, S., Prevedello, L. M., Rudie, J. D., Sako, C., Shinohara, R. T., Bergquist, T., Chai, R., Eddy, J., Elliott, J., Reade, W., Schaffter, T., Yu, T., Zheng, J., Moawad, A. W., Coelho, L. O., McDonnell, O., Miller, E., Moron, F. E., Oswood, M. C., Shih, R. Y., Siakallis, L., Bronstein, Y., Mason, J. R., Miller, A. F., Choudhary, G., Agarwal, A., Besada, C. H., Derakhshan, J. J., Diogo, M. C., Do-Dai, D. D., Farage, L., Go, J. L., Hadi, M., Hill, V. B., Iv, M., Joyner, D., Lincoln, C., Lotan, E., Miyakoshi, A., Sanchez-Montano, M., Nath, J., Nguyen, X. V., Nicolas-Jilwan, M., Jimenez, J. O., Ozturk, K., Petrovic, B. D., Shah, C., Shah, L. M., Sharma, M., Simsek, O., Singh, A. K., Soman, S., Statsevych, V., Weinberg, B. D., Young, R. J., Ikuta, I., Agarwal, A. K., Cambron, S. C., Silbergleit, R., Dusoi, A., Postma, A. A., Letourneau-Guillon, L., Perez-Carrillo, G. J. G., Saha, A., Soni, N., Zaharchuk, G., Zohrabian, V. M., Chen, Y.,

Cekic, M. M., Rahman, A., Small, J. E., Sethi, V., Davatzikos, C., Mongan, J., Hess, C., Cha, S., Villanueva-Meyer, J., Freymann, J. B., Kirby, J. S., Wiestler, B., Crivellaro, P., Colen, R. R., Kotrotsou, A., Marcus, D., Milchenko, M., Nazeri, A., Fathallah-Shaykh, H., Wiest, R., Jakab, A., Weber, M.-A., Mahajan, A., Menze, B., Flanders, A. E., and Bakas, S. The rsna-asnr-miccai brats 2021 benchmark on brain tumor segmentation and radiogenomic classification, 2021. URL https://arxiv.org/abs/2107.02314.

Bakas, S., Akbari, H., Sotiras, A., Bilello, M., Rozycki, M., Kirby, J. S., Freymann, J. B., Farahani, K., and Davatzikos, C. Advancing the cancer genome atlas glioma mri collections with expert segmentation labels and radiomic features. *Scientific data*, 4(1):1–13, 2017.

Bernal, J., Sánchez, F. J., Fernández-Esparrach, G., Gil, D., Rodríguez, C., and Vilariño, F. Wm-dova maps for accurate polyp highlighting in colonoscopy: Validation vs. saliency maps from physicians. *Computerized medical imaging and graphics*, 43:99–111, 2015.

Bharatha, A., Hirose, M., Hata, N., Warfield, S. K., Ferrant, M., Zou, K. H., Suarez-Santana, E., Ruiz-Alzola, J., D'Amico, A., Cormack, R. A., Kikinis, R., Jolesz, F. A., and Tempany, C. M. C. Evaluation of three-dimensional finite element-based deformable registration of pre- and intraoperative prostate imaging. *Medical Physics*, 28 (12):2551–2560, 2001. doi: https://doi.org/10.1118/1. 1414009. URL https://aapm.onlinelibrary.wiley.com/doi/abs/10.1118/1.1414009.

Chen, J., Gui, C., Ouyang, R., Gao, A., Chen, S., Chen, G. H., Wang, X., Cai, Z., Ji, K., Wan, X., and Wang, B. Towards injecting medical visual knowledge into multimodal LLMs at scale. In Al-Onaizan, Y., Bansal, M., and Chen, Y.-N. (eds.), *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 7346–7370, Miami, Florida, USA, November 2024a. Association for Computational Linguistics. doi: 10.18653/v1/2024. emnlp-main.418. URL https://aclanthology.org/2024.emnlp-main.418/.

Chen, L., Zhao, H., Liu, T., Bai, S., Lin, J., Zhou, C., and Chang, B. An image is worth 1/2 tokens after layer 2: Plug-and-play inference acceleration for large vision-language models. In Leonardis, A., Ricci, E., Roth, S., Russakovsky, O., Sattler, T., and Varol, G. (eds.), *Computer Vision – ECCV 2024*, pp. 19–35, Cham, 2025a. Springer Nature Switzerland. ISBN 978-3-031-73004-7.

Chen, S., Zhu, T., Zhou, R., Zhang, J., Gao, S., Niebles, J. C., Geva, M., He, J., Wu, J., and Li, M. Why is spatial

reasoning hard for vlms? an attention mechanism perspective on focus areas. In *Forty-second International Conference on Machine Learning*, 2025b.

Chen, Z., Wu, J., Wang, W., Su, W., Chen, G., Xing, S., Zhong, M., Zhang, Q., Zhu, X., Lu, L., et al. Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 24185–24198, 2024b.

Codella, N., Rotemberg, V., Tschandl, P., Celebi, M. E., Dusza, S., Gutman, D., Helba, B., Kalloo, A., Liopyris, K., Marchetti, M., Kittler, H., and Halpern, A. Skin lesion analysis toward melanoma detection 2018: A challenge hosted by the international skin imaging collaboration (isic), 2019. URL https://arxiv.org/abs/1902.03368.

Codella, N. C. F., Gutman, D., Celebi, M. E., Helba, B., Marchetti, M. A., Dusza, S. W., Kalloo, A., Liopyris, K., Mishra, N., Kittler, H., and Halpern, A. Skin lesion analysis toward melanoma detection: A challenge at the 2017 international symposium on biomedical imaging (isbi), hosted by the international skin imaging collaboration (isic). In *2018 IEEE 15th International Symposium on Biomedical Imaging (ISBI 2018)*, pp. 168–172, 2018a. doi: 10.1109/ISBI.2018.8363547.

Codella, N. C. F., Gutman, D., Celebi, M. E., Helba, B., Marchetti, M. A., Dusza, S. W., Kalloo, A., Liopyris, K., Mishra, N., Kittler, H., and Halpern, A. Skin lesion analysis toward melanoma detection: A challenge at the 2017 international symposium on biomedical imaging (isbi), hosted by the international skin imaging collaboration (isic). In *2018 IEEE 15th International Symposium on Biomedical Imaging (ISBI 2018)*, pp. 168–172, 2018b. doi: 10.1109/ISBI.2018.8363547.

Cui, H., Mao, L., Liang, X., Zhang, J., Ren, H., Li, Q., Li, X., and Yang, C. Biomedical visual instruction tuning with clinician preference alignment. *Advances in neural information processing systems*, 37:96449–96467, 2024.

Dai, W., Li, J., Li, D., Tiong, A., Zhao, J., Wang, W., Li, B., Fung, P., and Hoi, S. InstructBLIP: Towards general-purpose vision-language models with instruction tuning. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=vvoWPYqZJA.

et al., O. Gpt-4 technical report, 2024. URL https://arxiv.org/abs/2303.08774.

Fang, H., Li, F., Fu, H., Sun, X., Cao, X., Lin, F., Son, J., Kim, S., Quellec, G., Matta, S., Shankaranarayana,

S. M., Chen, Y.-T., Wang, C.-H., Shah, N. A., Lee, C.-Y., Hsu, C.-C., Xie, H., Lei, B., Baid, U., Innani, S., Dang, K., Shi, W., Kamble, R., Singhal, N., Wang, C.-W., Lo, S.-C., Orlando, J. I., Bogunović, H., Zhang, X., and Xu, Y. Adam challenge: Detecting age-related macular degeneration from fundus images. *IEEE Transactions on Medical Imaging*, 41(10):2828–2847, 2022. doi: 10.1109/TMI.2022.3172773.

Fong, R. C. and Vedaldi, A. Interpretable explanations of black boxes by meaningful perturbation. In *Proceedings of the IEEE international conference on computer vision*, pp. 3429–3437, 2017.

Fu, H., Li, F., Orlando, J. I., Bogunovic, H., Sun, X., Liao, J., Xu, Y., Zhang, S., and Zhang, X. ichallenge-palm: Pathologic myopia challenge, 07 2019. URL https://cir.nii.ac.jp/crid/1880020692683121792.

Gandelsman, Y., Efros, A. A., and Steinhardt, J. Interpreting clip's image representation via text-based decomposition. In *The Twelfth International Conference on Learning Representations*, 2024.

Gatidis, S., Hepp, T., Früh, M., La Fougère, C., Nikolaou, K., Pfannenberg, C., Schölkopf, B., Küstner, T., Cyran, C., and Rubin, D. A whole-body fdg-pet/ct dataset with manually annotated tumor lesions. *Scientific Data*, 9(1):601, 2022.

Golovanevsky, M., Rudman, W., Palit, V., Singh, R., and Eickhoff, C. What do vlms notice? a mechanistic interpretability pipeline for noise-free text-image corruption and evaluation. *CoRR*, abs/2406.16320, 2024. URL https://doi.org/10.48550/arXiv.2406.16320.

He, X., Zhang, Y., Mou, L., Xing, E., and Xie, P. Pathvqa: 30000+ questions for medical visual question answering, 2020. URL https://arxiv.org/abs/2003.10286.

Heller, N., Sathianathen, N., Kalapara, A., Walczak, E., Moore, K., Kaluzniak, H., Rosenberg, J., Blake, P., Rengel, Z., Oestreich, M., Dean, J., Tradewell, M., Shah, A., Tejpaul, R., Edgerton, Z., Peterson, M., Raza, S., Regmi, S., Papanikolopoulos, N., and Weight, C. The kits19 challenge data: 300 kidney tumor cases with clinical context, ct semantic segmentations, and surgical outcomes, 2020. URL https://arxiv.org/abs/1904.00445.

Hooker, S., Erhan, D., Kindermans, P.-J., and Kim, B. A benchmark for interpretability methods in deep neural networks. *Advances in neural information processing systems*, 32, 2019.

Hu, Y., Li, T., Lu, Q., Shao, W., He, J., Qiao, Y., and Luo, P. Omnimedvqa: A new large-scale comprehensive evaluation benchmark for medical lvlm. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 22170–22183, June 2024.

Huang, R., Chen, Z., Chen, Y., Li, H., et al. Struct-Seg2019 Grand Challenge Dataset. https://structseg2019.grand-challenge.org/Dataset/, 2019. Retrieved: September 25, 2025.

Huang, X., Shen, L., Liu, J., Shang, F., Li, H., Huang, H., and Yang, Y. Towards a multimodal large language model with pixel-level insight for biomedicine. *Proceedings of the AAAI Conference on Artificial Intelligence*, 39(4):3779–3787, Apr. 2025. doi: 10.1609/aaai.v39i4.32394. URL https://ojs.aaai.org/index.php/AAAI/article/view/32394.

Igelsias, J., Styner, M., Langerak, T., Landman, B., Xu, Z., and Klein, A. Miccai multi-atlas labeling beyond the cranial vault–workshop and challenge. In *Proc. MICCAI Multi-Atlas Labeling Beyond Cranial Vault—Workshop Challenge*, 2015.

Ismail, A. A., Corrada Bravo, H., and Feizi, S. Improving deep learning interpretability by saliency guided training. *Advances in Neural Information Processing Systems*, 34:26726–26739, 2021.

Jeong, D. P., Garg, S., Lipton, Z. C., and Oberst, M. Medical adaptation of large language and vision-language models: Are we making progress? In Al-Onaizan, Y., Bansal, M., and Chen, Y.-N. (eds.), *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 12143–12170, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-main.677. URL https://aclanthology.org/2024.emnlp-main.677/.

Jha, D., Smedsrud, P. H., Riegler, M. A., Halvorsen, P., De Lange, T., Johansen, D., and Johansen, H. D. Kvasir-seg: A segmented polyp dataset. In *International conference on multimedia modeling*, pp. 451–462. Springer, 2019.

Jha, D., Tomar, N. K., Sharma, V., Trinh, Q.-H., Biswas, K., Pan, H., Jha, R. K., Durak, G., Hann, A., Varkey, J., Dao, H. V., Dao, L. V., Nguyen, B. P., Papachrysos, N., Rieders, B., Schmidt, P. T., Geissler, E., Berzin, T., Halvorsen, P., Riegler, M. A., de Lange, T., and Bagci, U. Polypdb: A curated multi-center dataset for development of ai algorithms in colonoscopy, 2025. URL https://arxiv.org/abs/2409.00045.

Ji, Y., Bai, H., GE, C., Yang, J., Zhu, Y., Zhang, R., Li, Z., Zhanng, L., Ma, W., Wan, X., and Luo, P. Amos: A large-scale abdominal multi-organ benchmark for versatile medical image segmentation. In Koyejo, S., Mohamed, S., Agarwal, A., Belgrave, D., Cho, K., and Oh, A. (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 36722–36732. Curran Associates, Inc., 2022. URL https://proceedings.neurips.cc/paper_files/paper/2022/file/ee604e1bedbd069d9fc9328b7b9584be-Paper-Datasets_and_Benchmarks.pdf.

Jiang, Z., Chen, J., Zhu, B., Luo, T., Shen, Y., and Yang, X. Devils in middle layers of large vision-language models: Interpreting, detecting and mitigating object hallucinations via attention lens. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 25004–25014, June 2025.

Kaduri, O., Bagon, S., and Dekel, T. What's in the image? a deep-dive into the vision of vision language models, 2024. URL https://arxiv.org/abs/2411.17491.

Kang, S., Kim, J., Kim, J., and Hwang, S. J. Your large vision-language model only needs a few attention heads for visual grounding, 2025. URL https://arxiv.org/abs/2503.06287.

Kavur, A. E., Gezer, N. S., Barış, M., Aslan, S., Conze, P.-H., Groza, V., Pham, D. D., Chatterjee, S., Ernst, P., Özkan, S., Baydar, B., Lachinov, D., Han, S., Pauli, J., Isensee, F., Perkonigg, M., Sathish, R., Rajan, R., Sheet, D., Dovletov, G., Speck, O., Nürnberger, A., Maier-Hein, K. H., Bozdağı Akar, G., Ünal, G., Dicle, O., and Selver, M. A. Chaos challenge - combined (ct-mr) healthy abdominal organ segmentation. *Medical Image Analysis*, 69:101950, 2021. ISSN 1361-8415. doi: https://doi.org/10.1016/j.media.2020.101950. URL https://www.sciencedirect.com/science/article/pii/S1361841520303145.

Lau, J. J., Gayen, S., Abacha, A. B., and Demner-Fushman, D. A dataset of clinically generated visual questions and answers about radiology images. *Scientific Data*, 5:1–10, 11 2018.

Li, C., Wong, C., Zhang, S., Usuyama, N., Liu, H., Yang, J., Naumann, T., Poon, H., and Gao, J. Llavamed: Training a large language-and-vision assistant for biomedicine in one day. In Oh, A., Naumann, T., Globerson, A., Saenko, K., Hardt, M., and Levine, S. (eds.), *Advances in Neural Information Processing Systems*, volume 36, pp. 28541–28564. Curran Associates, Inc., 2023a. URL https://proceedings.neurips.

cc/paper_files/paper/2023/file/
5abcdf8ecdcacba028c6662789194572-Paper-Datasets_
and_Benchmarks.pdf.

Li, J., Li, D., Savarese, S., and Hoi, S. BLIP-2: Boot-strapping language-image pre-training with frozen image encoders and large language models. In Krause, A., Brunskill, E., Cho, K., Engelhardt, B., Sabato, S., and Scarlett, J. (eds.), *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pp. 19730–19742. PMLR, 23–29 Jul 2023b. URL https://proceedings.mlr.press/v202/li23q.html.

Lin, T.-Y., Maire, M., Belongie, S., Hays, J., Perona, P., Ramanan, D., Dollár, P., and Zitnick, C. L. Microsoft coco: Common objects in context. In Fleet, D., Pajdla, T., Schiele, B., and Tuytelaars, T. (eds.), *Computer Vision – ECCV 2014*, pp. 740–755, Cham, 2014. Springer International Publishing. ISBN 978-3-319-10602-1.

Litjens, G., Toth, R., van de Ven, W., Hoeks, C., Kerkstra, S., van Ginneken, B., Vincent, G., Guillard, G., Birbeck, N., Zhang, J., Strand, R., Malmberg, F., Ou, Y., Davatzikos, C., Kirschner, M., Jung, F., Yuan, J., Qiu, W., Gao, Q., Edwards, P. Maan, B., van der Heijden, F., Ghose, S., Mitra, J., Dowling, J., Barratt, D., Huisman, H., and Madabhushi, A. Evaluation of prostate segmentation algorithms for mri: The promise12 challenge. *Medical Image Analysis*, 18(2):359–373, 2014. ISSN 1361-8415. doi: https://doi.org/10.1016/j.media.2013.12.002. URL https://www.sciencedirect.com/science/article/pii/S1361841513001734.

Liu, B., Zhan, L.-M., Xu, L., Ma, L., Yang, Y., and Wu, X.-M. Slake: A semantically-labeled knowledge-enhanced dataset for medical visual question answering. In *2021 IEEE 18th International Symposium on Biomedical Imaging (ISBI)*, pp. 1650–1654, 2021a. doi: 10.1109/ISBI48211.2021.9434010.

Liu, H., Li, C., Wu, Q., and Lee, Y. J. Visual instruction tuning. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=w0H2xGHlkw.

Liu, H., Li, C., Li, Y., and Lee, Y. J. Improved baselines with visual instruction tuning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 26296–26306, June 2024a.

Liu, H., Li, C., Li, Y., Li, B., Zhang, Y., Shen, S., and Lee, Y. J. Llava-next: Improved reasoning, ocr, and world knowledge, January 2024b. URL https://llava-vl.github.io/blog/2024-01-30-llava-next/.

Liu, P., Han, H., Du, Y., Zhu, H., Li, Y., Gu, F., Xiao, H., Li, J., Zhao, C., Xiao, L., et al. Deep learning to segment pelvic bones: large-scale ct datasets and baseline models. *International Journal of Computer Assisted Radiology and Surgery*, 16(5):749–756, 2021b.

Liu, S., Zheng, K., and Chen, W. Paying more attention to image: A training-free method for alleviating hallucination in lvlms. In *European Conference on Computer Vision*, pp. 125–140. Springer, 2024c.

Liu, W., Pan, Q., Zhang, Y., Liu, Z., Wu, J., Zhou, J., Zhou, A., Chen, Q., Jiang, B., and He, L. Cmm-math: A chinese multimodal math dataset to evaluate and enhance the mathematics reasoning of large multimodal models. *CoRR*, abs/2409.02834, 2024d. URL https://doi.org/10.48550/arXiv.2409.02834.

Lu, J., Rao, J., Chen, K., Guo, X., Zhang, Y., Sun, B., Yang, C., and Yang, J. Evaluation and enhancement of semantic grounding in large vision-language models. In *AAAI-24 Workshop on Responsible Language Models*, 2024. URL https://arxiv.org/abs/2309.04041.

Luo, X., Liao, W., Xiao, J., Chen, J., Song, T., Zhang, X., Li, K., Metaxas, D. N., Wang, G., and Zhang, S. Word: A large scale dataset, benchmark and clinical applicable study for abdominal organ segmentation from ct image. *Medical Image Analysis*, 82:102642, 2022. ISSN 1361-8415. doi: https://doi.org/10.1016/j.media.2022.102642. URL https://www.sciencedirect.com/science/article/pii/S1361841522002705.

Lyre, H. Understanding ai: Semantic grounding in large language models, 2024. URL https://arxiv.org/abs/2402.10992.

Ma, J., Zhang, Y., Gu, S., An, X., Wang, Z., Ge, C., Wang, C., Zhang, F., Wang, Y., Xu, Y., Gou, S., Thaler, F., Payer, C., Štern, D., Henderson, E. G., McSweeney, D. M., Green, A., Jackson, P., McIntosh, L., Nguyen, Q.-C., Qayyum, A., Conze, P.-H., Huang, Z., Zhou, Z., Fan, D.-P., Xiong, H., Dong, G., Zhu, Q., He, J., and Yang, X. Fast and low-gpu-memory abdomen ct organ segmentation: The flare challenge. *Medical Image Analysis*, 82:102616, 2022a. ISSN 1361-8415. doi: https://doi.org/10.1016/j.media.2022.102616. URL https://www.sciencedirect.com/science/article/pii/S1361841522002444.

Ma, J., Zhang, Y., Gu, S., Zhu, C., Ge, C., Zhang, Y., An, X., Wang, C., Wang, Q., Liu, X., Cao, S., Zhang, Q., Liu, S., Wang, Y., Li, Y., He, J., and Yang, X. Abdomenct-1k: Is abdominal organ segmentation a solved problem? *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 44(10):6695–6714, 2022b. doi: 10.1109/TPAMI.2021.3100536.

Ma, J., Zhang, Y., Gu, S., Ge, C., Mae, S., Young, A., Zhu, C., Yang, X., Meng, K., Huang, Z., et al. Unleashing the strengths of unlabelled data in deep learning-assisted pan-cancer abdominal organ quantification: the flare22 challenge. *The Lancet Digital Health*, 6(11):e815–e826, 2024.

Maier, O., Menze, B. H., von der Gablentz, J., Häni, L., Heinrich, M. P., Liebrand, M., Winzeck, S., Basit, A., Bentley, P., Chen, L., Christiaens, D., Dutil, F., Egger, K., Feng, C., Glocker, B., Götz, M., Haeck, T., Halme, H.-L., Havaei, M., Iftekharuddin, K. M., Jodoin, P.-M., Kamnitsas, K., Kellner, E., Korvenoja, A., Larochelle, H., Ledig, C., Lee, J.-H., Maes, F., Mahmood, Q., Maier-Hein, K. H., McKinley, R., Muschelli, J., Pal, C., Pei, L., Rangarajan, J. R., Reza, S. M., Robben, D., Rueckert, D., Salli, E., Suetens, P., Wang, C.-W., Wilms, M., Kirschke, J. S., Krämer, U. M., Münte, T. F., Schramm, P., Wiest, R., Handels, H., and Reyes, M. Isles 2015 - a public evaluation benchmark for ischemic stroke lesion segmentation from multispectral mri. *Medical Image Analysis*, 35:250–269, 2017. ISSN 1361-8415. doi: https://doi.org/10.1016/j.media.2016.07.009. URL https://www.sciencedirect.com/science/article/pii/S1361841516301268.

Menze, B. H., Jakab, A., Bauer, S., Kalpathy-Cramer, J., Farahani, K., Kirby, J., Burren, Y., Porz, N., Slotboom, J., Wiest, R., Lanczi, L., Gerstner, E., Weber, M.-A., Arbel, T., Avants, B. B., Ayache, N., Buendia, P., Collins, D. L., Cordier, N., Corso, J. J., Criminisi, A., Das, T., Delingette, H., Demiralp, , Durst, C. R., Dojat, M., Doyle, S., Festa, J., Forbes, F., Geremia, E., Glocker, B., Golland, P., Guo, X., Hamamci, A., Iftekharuddin, K. M., Jena, R., John, N. M., Konukoglu, E., Lashkari, D., Mariz, J. A., Meier, R., Pereira, S., Precup, D., Price, S. J., Raviv, T. R., Reza, S. M. S., Ryan, M., Sarikaya, D., Schwartz, L., Shin, H.-C., Shotton, J., Silva, C. A., Sousa, N., Subbanna, N. K., Szekely, G., Taylor, T. J., Thomas, O. M., Tustison, N. J., Unal, G., Vasseur, F., Wintermark, M., Ye, D. H., Zhao, L., Zhao, B., Zikic, D., Prastawa, M., Reyes, M., and Van Leemput, K. The multimodal brain tumor image segmentation benchmark (brats). *IEEE Transactions on Medical Imaging*, 34(10): 1993–2024, 2015. doi: 10.1109/TMI.2014.2377694.

Montoya, A., Hasnin, kaggle446, shirzad, Cukierski, W., and yffud. Ultrasound Nerve Segmentation. https://kaggle.com/competitions/ultrasound-nerve-segmentation, 2016. Retrieved: September 25, 2025.

Moor, M., Huang, Q., Wu, S., Yasunaga, M., Dalmia, Y., Leskovec, J., Zakka, C., Reis, E. P., and Rajpurkar, P. Med-flamingo: a multimodal medical few-shot learner. In Hegselmann, S., Parziale, A., Shanmugam, D., Tang,

S., Asiedu, M. N., Chang, S., Hartvigsen, T., and Singh, H. (eds.), *Proceedings of the 3rd Machine Learning for Health Symposium*, volume 225 of *Proceedings of Machine Learning Research*, pp. 353–367. PMLR, 10 Dec 2023. URL https://proceedings.mlr.press/v225/moor23a.html.

Nath, V., Li, W., Yang, D., Myronenko, A., Zheng, M., Lu, Y., Liu, Z., Yin, H., Law, Y. M., Tang, Y., et al. Vila-m3: Enhancing vision-language models with medical expert knowledge. *arXiv preprint arXiv:2411.12915*, 2024.

Olsson, C., Elhage, N., Nanda, N., Joseph, N., DasSarma, N., Henighan, T., Mann, B., Askell, A., Bai, Y., Chen, A., et al. In-context learning and induction heads. *arXiv preprint arXiv:2209.11895*, 2022.

Pace, D. F., Dalca, A. V., Geva, T., Powell, A. J., Moghari, M. H., and Golland, P. Interactive whole-heart segmentation in congenital heart disease. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pp. 80–88. Springer, 2015.

Palit, V., Pandey, R., Arora, A., and Liang, P. P. Towards vision-language mechanistic interpretability: A causal tracing tool for blip. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV) Workshops*, pp. 2856–2861, October 2023.

Selvaraju, R. R., Cogswell, M., Das, A., Vedantam, R., Parikh, D., and Batra, D. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE international conference on computer vision*, pp. 618–626, 2017.

Setio, A. A. A., Traverso, A., de Bel, T., Berens, M. S., van den Bogaard, C., Cerello, P., Chen, H., Dou, Q., Fantacci, M. E., Geurts, B., van der Gugten, R., Heng, P. A., Jansen, B., de Kaste, M. M., Kotov, V., Lin, J. Y.-H., Manders, J. T., Sóñora-Mengana, A., García-Naranjo, J. C., Papavasileiou, E., Prokop, M., Saletta, M., Schaefer-Prokop, C. M., Scholten, E. T., Scholten, L., Snoeren, M. M., Torres, E. L., Vandemeulebroucke, J., Walasek, N., Zuidhof, G. C., van Ginneken, B., and Jacobs, C. Validation, comparison, and combination of algorithms for automatic detection of pulmonary nodules in computed tomography images: The luna16 challenge. *Medical Image Analysis*, 42:1–13, 2017. ISSN 1361-8415. doi: https://doi.org/10.1016/j.media.2017.06.015. URL https://www.sciencedirect.com/science/article/pii/S1361841517301020.

Shi, W., Hu, Z., Bin, Y., Liu, J., Yang, Y., Ng, S.-K., Bing, L., and Lee, R. K.-W. Math-llava: Bootstrapping mathematical reasoning for multimodal large language models. *CoRR*, abs/2406.17294, 2024. URL https://doi.org/10.48550/arXiv.2406.17294.

Tianchi, A. Chest image dataset for pneumothorax segmentation. https://tianchi.aliyun.com/dataset/83075, 2020. Accessed: September 25, 2025.

Voita, E., Talbot, D., Moiseev, F., Sennrich, R., and Titov, I. Analyzing multi-head self-attention: Specialized heads do the heavy lifting, the rest can be pruned. *arXiv preprint arXiv:1905.09418*, 2019.

Wang, L., Wang, H., Yang, H., Mao, J., Yang, Z., Shen, J., and Li, X. Interpretable bilingual multimodal large language model for diverse biomedical tasks. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=YuHQTo6G9S.

Wang, P., Bai, S., Tan, S., Wang, S., Fan, Z., Bai, J., Chen, K., Liu, X., Wang, J., Ge, W., Fan, Y., Dang, K., Du, M., Ren, X., Men, R., Liu, D., Zhou, C., Zhou, J., and Lin, J. Qwen2-vl: Enhancing vision-language model's perception of the world at any resolution, 2024. URL https://arxiv.org/abs/2409.12191.

Wasserthal, J., Breit, H.-C., Meyer, M. T., Pradella, M., Hinck, D., Sauter, A. W., Heye, T., Boll, D. T., Cyriac, J., Yang, S., Bach, M., and Segeroth, M. Totalsegmentator: Robust segmentation of 104 anatomic structures in ct images. *Radiology: Artificial Intelligence*, 5(5):e230024, 2023. doi: 10.1148/ryai.230024. URL https://doi.org/10.1148/ryai.230024.

Wu, C., Zhang, X., Zhang, Y., Wang, Y., and Xie, W. Towards generalist foundation model for radiology. *CoRR*, abs/2308.02463, 2023. URL https://doi.org/10.48550/arXiv.2308.02463.

Wu, S., Fei, H., Qu, L., Ji, W., and Chua, T.-S. NExT-GPT: Any-to-any multimodal LLM. In *Proceedings of the International Conference on Machine Learning*, pp. 53366–53397, 2024.

Xiao, L., Yang, X., Lan, X., Wang, Y., and Xu, C. Towards visual grounding: A survey, 2024. URL https://arxiv.org/abs/2412.20206.

Xie, Y., Zhou, C., Gao, L., Wu, J., Li, X., Zhou, H.-Y., Liu, S., Xing, L., Zou, J., Xie, C., and Zhou, Y. Medtrinity-25m: A large-scale multimodal dataset with multigranular annotations for medicine. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=IwgmgidYPS.

Yang, T., Li, Z., Cao, J., and Xu, C. Mitigating hallucination in large vision-language models via modular attribution and intervention. In *Adaptive Foundation Models: Evolving AI for Personalized and Efficient Learning*, 2025.

Yu, Q., Merullo, J., and Pavlick, E. Characterizing mechanisms for factual recall in language models. In *The Conference on Empirical Methods in Natural Language Processing*, 2023.

Yu, Z. and Ananiadou, S. Understanding multimodal llms: the mechanistic interpretability of llava in visual question answering, 2025. URL https://arxiv.org/abs/2411.10950.

Yue, X., Ni, Y., Zhang, K., Zheng, T., Liu, R., Zhang, G., Stevens, S., Jiang, D., Ren, W., Sun, Y., Wei, C., Yu, B., Yuan, R., Sun, R., Yin, M., Zheng, B., Yang, Z., Liu, Y., Huang, W., Sun, H., Su, Y., and Chen, W. Mmmu: A massive multi-discipline multimodal understanding and reasoning benchmark for expert agi. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 9556–9567, June 2024.

Zawacki, A., Wu, C., Shih, G., Elliott, J., Fomitchev, M., Hussain, M., Lakhani, P., Culliton, P., and Bao, S. Siim-acr pneumothorax segmentation. https://kaggle.com/competitions/siim-acr-pneumothorax-segmentation, 2019. Kaggle.

Zhang, J., Khayatkhoei, M., Chhikara, P., and Ilievski, F. Mllms know where to look: Training-free perception of small visual details with multimodal llms. In *The Thirteenth International Conference on Learning Representations*, 2025a. URL https://openreview.net/forum?id=DgaY5mDdmThttps://github.com/saccharomycetes/mllms_know.

Zhang, M., Wu, Y., Zhang, H., Qin, Y., Zheng, H., Tang, W., Arnold, C., Pei, C., Yu, P., Nan, Y., Yang, G., Walsh, S., Marshall, D. C., Komorowski, M., Wang, P., Guo, D., Jin, D., Wu, Y., Zhao, S., Chang, R., Zhang, B., Lu, X., Qayyum, A., Mazher, M., Su, Q., Wu, Y., Liu, Y., Zhu, Y., Yang, J., Pakzad, A., Rangelov, B., Estepar, R. S. J., Espinosa, C. C., Sun, J., Yang, G.-Z., and Gu, Y. Multi-site, multi-domain airway tree modeling. *Medical Image Analysis*, 90:102957, 2023a. ISSN 1361-8415. doi: https://doi.org/10.1016/j.media.2023.102957. URL https://www.sciencedirect.com/science/article/pii/S1361841523002177.

Zhang, S., Xu, Y., Usuyama, N., Xu, H., Bagga, J., Tinn, R., Preston, S., Rao, R., Wei, M., Valluri, N., Wong, C., Tupini, A., Wang, Y., Mazzola, M., Shukla, S., Liden, L., Gao, J., Crabtree, A., Piening, B., Bifulco, C., Lungren, M. P., Naumann, T., Wang, S., and Poon, H. A multimodal biomedical foundation model trained from fifteen million image–text

pairs. *NEJM AI*, 2(1):AIoa2400640, 2025b. doi: 10. 1056/AIoa2400640. URL https://ai.nejm.org/doi/full/10.1056/AIoa2400640.

Zhang, X., Wu, C., Zhao, Z., Lin, W., Zhang, Y., Wang, Y., and Xie, W. Pmc-vqa: Visual instruction tuning for medical visual question answering. *CoRR*, abs/2305.10415, 2023b. URL https://doi.org/10.48550/arXiv.2305.10415.

Zhang, Z., Yadav, S., Han, F., and Shutova, E. Cross-modal information flow in multimodal large language models. *arXiv preprint arXiv:2411.18620*, 2024.

Zhao, Z., Chen, H., and Wang, L. A coarse-to-fine framework for the 2021 kidney and kidney tumor segmentation challenge. In *Kidney and Kidney Tumor Segmentation: MICCAI 2021 Challenge, KiTS 2021, Held in Conjunction with MICCAI 2021, Strasbourg, France, September 27, 2021, Proceedings*, pp. 53–58, Berlin, Heidelberg, 2021. Springer-Verlag. ISBN 978-3-030-98384-0. doi: 10.1007/978-3-030-98385-7_8. URL https://doi.org/10.1007/978-3-030-98385-7_8.

Zhuang, W., Huang, X., Zhang, X., and Zeng, J. Mathpuma: Progressive upward multimodal alignment to enhance mathematical reasoning. *Proceedings of the AAAI Conference on Artificial Intelligence*, 39(24): 26183–26191, Apr. 2025. doi: 10.1609/aaai.v39i24. 34815. URL https://ojs.aaai.org/index.php/AAAI/article/view/34815.

Appendix Overview

In this supplementary material, we provide additional experiments, ablation studies, and reproducibility details to support our findings. These sections are not included in the main paper due to space constraints.

Figure A.1: Our proposed inference-time method VGRefine achieve state-of-the-art performance on OmniMedVQA (Hu et al., 2024) and MMMU (Health & Medicine track) (Yue et al., 2024). Many existing medical MLLMs remain to underperform on medical VQA tasks in the zero-shot setting as shown in this figure, but there is a lack of systematic study to understand the reasons. Compared to existing medical MLLMs, our proposed VGRefine demonstrates consistently stronger zero-shot performance across all modalities and sub-domains, highlighting its effectiveness in mitigating the issue of inadequate visual grounding as revealed in our study.

A. More Discussion on Related Work

Medical Multimodal Large Language Models (MLLMs). Recent advances in medical multimodal large language models (MLLMs) have focused on leveraging image-text pairs from sources like PubMed central (Zhang et al., 2023b; Moor et al., 2023; Chen et al., 2024a; Li et al., 2023a) and medical textbooks (Moor et al., 2023) to enable generative VQA and medical reasoning. Models such as LLaVA-Med (Li et al., 2023a), MedVInT (Zhang et al., 2023b), Med-Flamingo (Moor et al., 2023), HuatuoGPT-Vision (Chen et al., 2024a), and BioMed-VITAL (Cui et al., 2024) introduce GPT-4 (et al., 2024) generated instruction-following datasets and expert-validated responses to improve medical VQA performance. More recent studies have begun to explore different ideas to improve region awareness in biomedical MLLMs: explicit fine-tuning with additional supervision, such as annotated bounding boxes (Wang et al., 2025; Xie et al., 2025) or segmentation masks (Jeong et al., 2024), along with architectural modifications to support spatial reasoning. For instance, models like MedRegA (Wang et al., 2025) and LLaVA-Tri (Xie et al., 2025) rely on additional datasets. Other recent models focus on scale or domain expertise. VILA-M3 (Nath et al., 2024), for instance, incorporates domain-specific expert models during training, arguing that generic Vision–Language Models (VLMs) lack the fine-grained expertise needed for healthcare. Given their dependence on task-specific fine-tuning (Nath et al., 2024; Xie et al., 2025) and sub-optimal generalization in zero-shot settings (Li et al., 2023a), *it remains unclear whether current medical MLLMs ground their predictions in meaningful visual evidence within medical images.* To our knowledge, no prior work has conducted a comprehensive analysis of visual grounding of medical MLLMs.

Visual Grounding Analysis in General Domain MLLMs. Some recent studies have investigated the internal attention mechanisms of general-domain MLLMs, revealing their potential for implicit visual grounding. Zhang et al. (2025a) demonstrated that MLLMs can identify the correct spatial regions relevant to a given query, even without explicit grounding supervision. They introduce a training-free intervention method (e.g., cropping guided by attention or gradient maps) that enhances performance on general-domain VQA tasks. Broader research into MLLM interpretability has studied how visual information is fused into language representations. Techniques such as causal intervention and cross-modal attention visualization have been employed to offer insights into how vision and language tokens interact through attention mechanisms (Golovanevsky et al., 2024; Zhang et al., 2024; Yu & Ananiadou, 2025; Palit et al., 2023). These studies suggest that middle layers are especially crucial for integrating object-level visual cues with textual context, and that cross-modal attention patterns can encode meaningful spatial alignment signals. However, all of these insights have been drawn from general-domain visual data, such as natural scene images and standard VQA benchmarks. *In contrast, to our knowledge, no prior work has performed visual grounding analysis of medical MLLMs.*

B. Additional Details for Section 2

B.1. VGMED Dataset Details

B.1.1. PUBLIC SEGMENTATION DATASETS USED IN VGMED

The original segmentation masks from public medical image segmentation datasets are converted into bounding boxes to support visual grounding analysis. Table B.1 summarizes the dataset sources used to construct VGMED.

B.1.2. VGMED SCALE COMPARISON

VGMED comprises approximately 28K image-bbox-question triplets, including 14K samples for localization questions and another 14K for attribute questions. The scale of VGMED is larger than or comparable to the number of samples used in the closely related RGB-domain visual grounding (Zhang et al., 2025a; Kang et al., 2025; Kaduri et al., 2024) / attention analysis work (Yang et al., 2025; Jiang et al., 2025; Chen et al., 2025a) (see Table B.2). Unlike RGB datasets that can be constructed by non-experts, our medical datasets require clinical expertise.

B.2. Clinical Validation During VGMED Curation

As part of the VGMED curation process, clinicians reviewed each sample to verify that (i) the question is properly focused on visual grounding, (ii) it does not require deep or diagnostic-level semantic medical reasoning, and (iii) it remains clinically appropriate and meaningful. An example of the rating interface used during the curation process is shown in Fig. B.1.

Clinical Relevance

- **1:** Irrelevant or misleading; the question is clinically inappropriate or nonsensical in this context.

- **2:** Marginally relevant; the question has limited medical value or loosely pertains to the case.

- **3:** Acceptable; the question is reasonable in clinical significance.

- **4:** Clinically useful; the question is clearly relevant and meaningful to medical interpretation.

- **5:** Highly relevant and valid; the question is well-phrased, accurate, and directly supports clinical reasoning.

Visual Grounding

- **1:** It refers to other anatomy or ignores the boxed area entirely; ignores the region.

- **2:** The question has only a weak or incidental connection to the boxed region; the area is largely irrelevant to the text.

- **3:** It reasonably overlaps or implies the boxed region.

- **4:** Clear reference to the boxed region.

- **5:** Perfectly aligned, the question precisely refers to the boxed region.

Minimum Semantic Grounding

- **1:** Very deep semantic grounding; requires advanced, multi-step clinical reasoning, such as staging, prognosis, mechanisms, or treatment decisions.

  Examples:

  "What is the appropriate treatment for this condition?"

  "How does this imaging pattern affect the patient's prognosis?"

- **2:** High semantic grounding; requires reasoning about specific diseases or well-defined diagnostic entities. Substantial medical knowledge is needed.

  Example:

  "What diseases are included in the image?"

- **3:** Moderate semantic grounding; requires linking features to broad categories of pathology, such as distinguishing between growth, inflammation, or degeneration.

  Example:

  "Do the changes suggest a long-standing damage?"

- **4:** Low-moderate semantic grounding; requires recognition of more specific medical descriptors, but does not involve broad pathology categories or diagnostic reasoning.

  Examples:

  "Does the structure appear to be pushing against or displacing nearby tissues?"

  "Is there a region that appears more diffuse rather than well-demarcated?"

- **5:** Low semantic grounding requires only basic clinical or anatomical recognition (e.g., body parts, organs, simple structures, fractures, nodules).

  Examples:

  "Does the bone show a visible fracture line?"

  "Is there a nodule in this region?"

Figure B.1. Example of the clinician rating interface used during VGMED curation.

Therefore, a rating of 3 represents acceptable threshold across all three dimensions: the sample is clinically relevant, visually grounded, and does not require deep semantic knowledge.

During the benchmark curation process, all samples receiving any score below 3 were discarded. Consequently, every VGMED sample satisfies 3 or above on all criteria. This ensured that retained samples genuinely test visual grounding rather than medical reasoning.

Furthermore, as summarized in Tab. B.3, the vast majority of clinician ratings are in the upper categories (4–5), with only a minor proportion of samples receiving a rating of 3 across any axis.

B.3. Attention Metrics Details

Alternative grounding indicators. Alternative grounding indicators, such as gradient-based saliency and causal perturbation, are in principle applicable but are considerably more expensive at scale. Gradient-based saliency methods (Selvaraju et al., 2017; Ismail et al., 2021) require backpropagation for each input, making them substantially more computation-intensive than directly using attention maps from the forward pass. Causal perturbation techniques (Fong & Vedaldi, 2017; Hooker et al., 2019) demand a new forward pass for each perturbed input (e.g., region masking or token removal), which may quickly become prohibitive for large-scale medical grounding analysis.

Attention map notation. We extract cross-attention weights from the last input text token to each of the N^2 im-

age tokens across all L layers and H attention heads of the LLM (Zhang et al., 2024; Kang et al., 2025). For each layer ℓ and head h, we denote the attention vector as $\alpha^{\ell,h} \in \mathbb{R}^{N^2}$, and compute the average across heads to obtain a per-layer attention map $A^\ell = \frac{1}{H}\sum_{h=1}^{H} \alpha^{\ell,h}$. Then we reshape A^ℓ into a spatial attention map of size $N \times N$.

Attention Ratio (AR). Let $A \in \mathbb{R}^{N \times N}$ denote the attention map over image patch tokens, and let $M \in \{0,1\}^{N \times N}$ represent the binary ground-truth mask indicating the annotated region (e.g., bounding box), where $M_{ij} = 1$ if patch (i,j) is inside the region, and 0 otherwise. Formally, AR is defined as

$$\text{AR} = \frac{\sum_{i=1}^{N}\sum_{j=1}^{N} A_{ij} \cdot M_{ij}}{\frac{\|A\|_1}{N^2} \cdot \|M\|_1},$$

where $\|A\|_1 = \sum_{i=1}^{N}\sum_{j=1}^{N} A_{ij}$ and similarly for $\|M\|_1$.

Kullback–Leibler (KL) divergence. We compute the KL divergence between the normalized ground-truth mask $\hat{M}$ and the normalized attention map $\hat{A}$ as

$$D_{\text{KL}}(\hat{M} \parallel \hat{A}) = \sum_{i=1}^{N}\sum_{j=1}^{N} \hat{M}_{ij} \log\left(\frac{\hat{M}_{ij}}{\hat{A}_{ij}}\right),$$

where $\hat{A}_{ij} = A_{ij}/\|A\|_1$ and $\hat{M}_{ij} = M_{ij}/\|M\|_1$.

Jensen–Shannon (JS) divergence. To obtain a symmetric and bounded divergence metric, we compute the JS divergence as

$$D_{\text{JS}}(\hat{M} \parallel \hat{A}) = \frac{1}{2} D_{\text{KL}}(\hat{M} \parallel \hat{R}) \frac{1}{2} D_{\text{KL}}(\hat{A} \parallel \hat{R}),$$
$$\hat{R}_{ij} = \frac{1}{2}\left(\hat{M}_{ij} + \hat{A}_{ij}\right).$$

The KL and JS divergences allow us to quantify not only whether the model attends to the correct region, but also how its attention is distributed within that region. A lower divergence indicates better alignment and more consistent attention over clinically relevant areas, offering a complementary perspective to AR.

B.4. Experimental Setup Details

To analyze attention behavior, we compute the mean attention map across all heads in each LLM layer. Inspired by Zhang et al. (2025a), we normalize the attention map using a reference attention map obtained from the generic prompt: *"Write a general description of the image."*. This normalization helps highlight regions relevant to the specific question.

We include LLaVA-v1.5-7B (Liu et al., 2024a) results on both medical and natural scene images. As a general-domain MLLM, LLaVA demonstrates strong performance

and exhibits good visual grounding, with attention distributions that align closely with ground-truth regions (Zhang et al., 2025a; Kang et al., 2025). This serves as a useful reference point for interpreting attention ratios, KL and JS divergence associated with effective visual grounding.

B.5. Grounding Analysis Details

Figure 3 provides the layer-wise AR, KL, and JS analysis supporting the main-text finding. Across evaluated medical MLLMs, attention distributions align less strongly with ground-truth annotations on medical images than on natural scene images. The setup and normalization details above provide the implementation context for this analysis.

Table B.1. Detailed information about the 44 datasets incorporated into VGMED. In the "Dataset" column, names such as "Struct-Seg2019 (Task 1)" represent specific task-based subsets. In the "Anatomical Structures" column, "Others" signifies datasets lacking detailed anatomical data from their original sources.

Dataset	Modality	Anatomical Structures
AMOS2022 (Ji et al., 2022)	CT, MR	Abdomen, Thorax, Pelvic
ATM2022 (Zhang et al., 2023a)	CT	Thorax
AbdomenomenCT-1K (Ma et al., 2022b)	CT	Abdomen
BTCV (Igelsias et al., 2015)	CT	Thorax, Abdomen, Pelvic
BraTS2013 (Menze et al., 2015)	MR	Head & neck
BraTS2015 (Menze et al., 2015)	MR	Head & neck
BraTS2018 (Menze et al., 2015)	MR	Head & neck
BraTS2019 (Menze et al., 2015)	MR	Head & neck
BraTS2020 (Menze et al., 2015)	MR	Head & neck
BraTS2021 (Bakas et al., 2017; Baid et al., 2021)	MR	Head & neck
CHAOS (Task 4) (Kavur et al., 2021)	MR	Abdomen
CTPelvic1k (Liu et al., 2021b)	CT	Pelvic
CVC-ClinicDB (Bernal et al., 2015)	Endoscopy	Others
Chest_Image_Pneum (Tianchi, 2020)	X-ray	Thorax
FLARE21 (Ma et al., 2022a)	CT	Abdomen
FLARE22 (Ma et al., 2024)	CT	Abdomen, Thorax
HVSMR2016 (Pace et al., 2015)	MR	Thorax
ADAM (Task 2) (Fang et al., 2022)	Fundus	Head & neck
PALM19 (Fu et al., 2019)	Fundus	Head & neck
ISLES (Maier et al., 2017)	MR	Head & neck
KiTS2019 (Heller et al., 2020)	CT	Abdomen
KiTS2021 (Zhao et al., 2021)	CT	Abdomen
LUNA16 (Setio et al., 2017)	CT	Thorax
MSD-BrainTumor (Antonelli et al., 2022)	MR	Head & neck
MSD-Liver (Antonelli et al., 2022)	CT	Abdomen
MSD-Pancreas (Antonelli et al., 2022)	CT	Abdomen
MSD-Spleen (Antonelli et al., 2022)	CT	Abdomen
CT-ORG (Antonelli et al., 2022)	CT	Head & neck, Thorax, Abdomen
PROMISE09 (Bharatha et al., 2001)	MR	Pelvic
PROMISE12 (Litjens et al., 2014)	MR	Pelvic
SIIM-ACR Pneumothorax (Zawacki et al., 2019)	X-ray	Thorax
StructSeg2019 (Task 1) (Huang et al., 2019)	CT	Head & neck
StructSeg2019 (Task 2) (Huang et al., 2019)	CT	Thorax, Abdomen
TotalSegmentator (Wasserthal et al., 2023)	CT	Head & neck, Thorax, Abdomen, Pelvic
Ultrasound Nerve Segmentation (Montoya et al., 2016)	Ultrasound	Others
WORD (Luo et al., 2022)	CT	Thorax, Abdomen
autoPET (Gatidis et al., 2022)	PET	Pelvic
BUSI (Al-Dhabyani et al., 2020)	Ultrasound	Thorax
Kvasir-SEG (Jha et al., 2019)	Endoscopy	Others
ISIC18 (Task 1) (Codella et al., 2019)	Dermoscopy	Skin
ISIC17 (Task 1) (Codella et al., 2018b)	Dermoscopy	Skin
ISIC16 (Task 1) (Codella et al., 2018a)	Dermoscopy	Skin
SLAKE (Liu et al., 2021a)	CT, MR, X-ray	Head & neck, Abdomen, Thorax
PolypDB (Jha et al., 2025)	Endoscopy	Others

Table B.2. Number of samples used in related works.

Related works	No. of Samples	Data Source
MLLMs Know (Zhang et al., 2025a)	4,370	Text-VQA
Your LVLM (Kang et al., 2025)	1,000	RefCOCO
What's in the Image (Kaduri et al., 2024)	81	COCO
Hallucination Attribution (Yang et al., 2025)	1,500	COCO
Devils in LVLM (Jiang et al., 2025)	2,000	COCO
FastV (Chen et al., 2025a)	1,000	4 VL Tasks

Table B.3. Percentage distribution of clinician ratings (3–5) across all axes for Attribute and Localization questions.

Type	Category	Rating 3 (%)	Rating 4 (%)	Rating 5 (%)
Attribute	Clinical Relevance	3.31	4.11	92.58
	Min. Semantic Grounding	0.37	10.38	89.25
	Visual Grounding	4.04	12.18	83.77
Localization	Clinical Relevance	0.02	0.52	99.46
	Min. Semantic Grounding	0.05	5.76	94.19
	Visual Grounding	3.96	11.79	84.25

C. Additional Details for Proposed VGRefine Method

C.1. VGRefine Method Overview

C.2. Head-Level Visual Sensitivity Analysis

We explore attention distributions from different attention heads across all layers, as prior work suggests that individual attention heads in transformers specialize in capturing distinct types of information (Voita et al., 2019; Olsson et al., 2022; Gandelsman et al., 2024; Yu et al., 2023; Yang et al., 2025). This motivates us to examine attention at finer granularity to obtain attention that focuses more on clinically relevant regions.

Following the same evaluation setup of Sec. 2.3 of the main paper, we assess relevancy to visual grounding of each attention head in HuatuoGPT-V by measuring the alignment between its attention distribution and ground-truth annotations. We perform this analysis using both natural scene images from MS COCO and medical images from VGMED. The alignment is measured by our proposed KL Divergence metric ($\downarrow$).

As shown in Fig. C.3, the visual relevancy patterns are consistent across domains: heads that are relevant to visual grounding in natural scenes also show relative relevancy in medical images, despite exhibiting inadequate visual grounding on medical images compared to natural images (as discussed in Sec. 2.4). Based on this analysis, we select the top K heads with the highest visual grounding relevancy (lowest KL) on natural images and average their attention maps to obtain a refined attention map. This map is used in Step II to guide the model's improved focus on clinically meaningful areas.

C.3. Implementation Details

Attention Triage. We select the top $K = 20$ attention heads ranked by alignment with visually relevant regions. Their attention maps are averaged to produce a filtered attention map. We then suppress low-activation regions using percentile threshold $p = 50\%$, since low activations are more likely to represent noisy or irrelevant attention. The filtered attention map is converted into a binary mask $\mathcal{M} \in \{0,1\}^{N^2}$ by setting all non-zero entries to 1 and keeping zeros unchanged.

Attention Knockout. We apply the binary mask $\mathcal{M}$ to the attention weights $\alpha_q^{\ell,h}$, where $\alpha_q^{\ell,h}$ denotes the cross-attention from the qth question token to all visual tokens at layer ℓ and head h. The masked attention is computed as

$$\hat{\alpha}_q^{\ell,h} = \alpha_q^{\ell,h} \odot \mathcal{M},$$

where $\odot$ denotes element-wise multiplication. We use $\hat{\alpha}_q^{\ell,h}$ for the subsequent attention computation in the model's forward pass. This restricts question tokens from receiving information from irrelevant visual regions at the selected layer, encouraging the model to attend selectively to meaningful regions.

Figure C.2. **Illustration of the proposed VGRefine method**: a two-step inference-time method to improve visual grounding in medical MLLMs. In **Step I (Attention Triage)**, we aggregate attention from the model's most visually sensitive heads and suppress low-confident attention, obtaining a binary mask. In **Step II (Attention Knockout)**, we use this mask to refine the model's attention distribution, improving its focus on relevant regions during inference. In the lower triangular attention matrix, each row represents the attention score of a query token to all key tokens.

Figure C.3. We conduct an experiment to analyze the alignment between attention distributions from different attention heads and layers and the ground truth annotations in the images. This follows the evaluation setup described in Section 2.3 of the main paper. The medical MLLM evaluated is HuatuoGPT-V-7B. Each cell in the above figures reflects the degree of alignment, measured using our proposed KL Divergence metric (lower is better). *This analysis helps identify the specific heads and layers that are most relevant to visual grounding.* COCO is used for natural scene image analysis, and our dataset VGMED is used for medical image analysis. Interestingly, we find that the attention heads most relevant to visual grounding in natural scene images are often also the most relevant for medical images. However, despite this overlap, the overall visual grounding performance on medical images remains lower than on natural scenes, consistent with the layer-wise grounding analysis in Supp. B.5. Based on this analysis, we identify the top K attention heads with the strongest alignment (i.e., lowest KL divergence) and aggregate their attention distributions to compute a refined attention map. *Notably, we select the top K heads using randomly sampled natural scene images from COCO dataset, to avoid data leakage from medical evaluation benchmarks.* This setup also demonstrates that our method generalizes effectively from natural images to the biomedical domain.

D. Additional Details for Experiments

D.1. Evaluation and VGRefine Settings

Baselines. We compared two types of open-source models: (1) medical MLLMs, including Med-Flamingo (Moor et al., 2023), RadFM (Wu et al., 2023), LLaVA-Med-7B (Li et al., 2023a), LLaVA-Tri (Xie et al., 2025), MedPLIB (Huang et al., 2025), VILA-M3 (Nath et al., 2024), and HuatuoGPT-V (Chen et al., 2024a); and (2) general-domain MLLMs, including LLaVA-v1.6-7B (Liu et al., 2024a) and Qwen-VL-Chat (Bai et al., 2023).

Benchmarks and protocol. We follow the exact evaluation protocol of Chen et al. (2024a). Specifically, we adopt six benchmarks designed for biomedical MLLM evaluation: VQA-RAD (Lau et al., 2018), SLAKE (Liu et al., 2021a), PathVQA (He et al., 2020), PMC-VQA (Zhang et al., 2023b), OmniMedVQA (Hu et al., 2024) (open-access split), and MMMU (Health & Medicine track) (Yue et al., 2024). All evaluations were conducted in a zero-shot setting using question templates provided by LLaVA; prompt details are provided in Supp. I.

VGRefine. We applied VGRefine to HuatuoGPT-V (Chen et al., 2024a). All experiments are conducted using the same hyperparameters across benchmarks. For Step I, we aggregate the attention maps from the top $K = 20$ heads with the highest alignment to visually relevant regions, as measured by KL divergence on our curated evaluation set built using COCO images. This setup prevents data leakage from medical evaluation benchmarks and demonstrates that our method generalizes from natural images to biomedical domains. Low-activation regions are suppressed based on percentile threshold $p = 50\%$ over attention magnitude. For Step II, we apply attention knockout only at layer $\ell = 16$, which demonstrates the most relevancy to visual grounding among the layers.

Reporting details. We follow the evaluation setup of HuatuoGPT-V (Chen et al., 2024a) to ensure consistency across benchmarks. Since the original papers of HuatuoGPT-V-7B (Chen et al., 2024a) and VILA-M3-8B (Nath et al., 2024) do not report results on certain benchmarks, we re-evaluate both models under the same zero-shot setting. For models with complete benchmark results available in their original publications, such as Med-PLIB (Huang et al., 2025) and LLaVA-Tri (Xie et al., 2025), we directly report the official numbers. For all other baselines, we use the results provided in the HuatuoGPT-V paper, as it adopts the same evaluation protocol.

Some models include benchmark training sets during pre-training, making zero-shot evaluation unfair. Specifically, VILA-M3 (Nath et al., 2024) and MedPLIB (Huang et al., 2025) incorporate training data from VQA-RAD, SLAKE, PathVQA, and PMC-VQA, and thus are excluded from our zero-shot comparison on those datasets.

D.2. MMMU Health and Medicine Results

VGRefine achieves the highest accuracy across all five MMMU Health and Medicine sub-domains, increasing the overall average from 45.8% to 47.2%. This demonstrates that enhancing visual grounding at inference time also improves complex multimodal medical reasoning.

D.3. OmniMedVQA Results

VGRefine improves performance across all eight imaging modalities, with significant boosts on CT (+7.5%), MRI (+6.4%), and X-Ray (+8.1%) on the OmniMedVQA benchmark. Overall, our method raises average accuracy from 71.3% to 74.4%, demonstrating robustness and generalizability across a wide range of modalities.

D.4. Human Evaluation

We conducted a blinded study with five experienced clinicians using 20 medical VQA cases from VGMED. Each case presented two attention maps: one from the baseline model and one from the same model after applying VGRefine. The source of each attention map was not disclosed, and their order was randomized. Clinicians were asked which map appeared more clinically reasonable and trustworthy. VGRefine was preferred in 76% of cases, with feedback noting improved focus and reduced noise. These results suggest that VGRefine enhances clinician trust by producing more interpretable visual evidence. Additional human-evaluation details and the interface example are provided in Supp. J.1.

Table D.4. Accuracy on MMMU Health & Medicine benchmark. **BMS**, **CM**, **DLM**, **P**, **PH** denote Basic Medical Science, Clinical Medicine, Diagnostics & Laboratory Medicine, Pharmacy, Public Health respectively.

Model	BMS	CM	DLM	P	PH	Avg.
Qwen-VL-Chat	36.5	31.7	32.7	28.4	34.6	32.7
LLaVA-v1.6-7B	40.5	36.9	32.1	32.3	26.9	33.1
Med-Flamingo	29.6	28.1	24.8	25.3	31.2	28.3
RadFM	27.5	26.8	25.8	24.7	29.1	27.0
LLaVA-Med-7B	39.9	39.1	34.6	37.4	34.0	36.9
LLaVA-Tri	37.1	-	27.8	-	-	-
VILA-M3-8B	39.3	39.7	34.0	32.1	28.7	34.0
HuatuoGPT-V-7B	58.9	57.2	43.8	37.2	38.3	45.8
VGRefine (Ours)	**59.5**	**59.1**	**45.7**	**38.6**	**39.3**	**47.2**

Table D.5. The accuracy of OmniMedVQA within different modalities. Specifically, **FP** denotes *Fundus Photography*, **MRI** denotes *Magnetic Resonance Imaging*, **OCT** denotes *Optical Coherence Tomography*, **Der** denotes *Dermoscopy*, **Mic** denotes *Microscopy Images*, **US** denotes *Ultrasound*.

Model	CT	FP	MRI	OCT	Der	Mic	X-Ray	US	Avg.
Qwen-VL-Chat (Bai et al., 2023)	51.5	45.4	43.9	54.0	55.4	49.5	63.1	33.5	49.5
LLaVA-v1.6-7B (Liu et al., 2024a)	40.1	39.5	54.8	58.4	54.0	48.8	53.3	47.9	49.6
Med-Flamingo (Moor et al., 2023)	34.6	33.3	27.5	26.0	28.3	28.1	30.1	33.2	30.2
RadFM (Wu et al., 2023)	33.3	35.0	22.0	31.3	36.3	28.0	31.5	26.1	30.5
LLaVA-Med-7B (Li et al., 2023a)	25.3	48.4	35.9	42.1	45.2	44.0	31.7	34.4	35.8
VILA-M3-8B (Nath et al., 2024)	60.2	35.7	51.5	56.9	51.5	51.7	65.4	46.1	53.0
MedPLIB (Huang et al., 2025)	62.7	65.0	67.0	75.1	51.5	64.4	60.3	38.8	60.6
HuatuoGPT-V-7B (Chen et al., 2024a)	62.6	80.3	67.7	86.2	**71.7**	74.2	74.2	**79.7**	71.3
VGRefine (Ours)	**67.3**	**82.4**	**72.0**	**86.9**	**71.7**	**74.9**	**80.2**	79.5	**74.4**

D.5. Ablation Studies

Table D.6 presents ablations on the number of top attention heads K and the percentile threshold p used for magnitude-based filtering. Performance improves consistently as K increases, with the best average accuracy (68.42%) achieved at $K = 20$, indicating that aggregating more heads helps capture richer grounding signals. For the percentile p, the model remains stable across values, with optimal performance also at $p = 50\%$, confirming the effectiveness of moderate filtering in removing noisy regions without discarding relevant information.

E. Experiments on Open-ended Medical VQA

We present additional experimental results on the open-ended questions from the Medical VQA benchmarks. Specifically, we evaluate on VQA-RAD (Lau et al., 2018), SLAKE (Liu et al., 2021a), and PathVQA (He et al., 2020), which include open-ended formats. As shown in Table E.7, our inference-time method consistently achieve better performance across all datasets, demonstrating its effectiveness in enhancing open-ended medical VQA.

F. Comparison with Other Attention-based Methods

We conducted an additional experiment comparing VGRefine with three very recent attention-based methods for medical MLLMs. Specifically, PAI (Liu et al., 2024c) and AdaptVis (Chen et al., 2025b) aim to refine/manipulate attention maps over visual tokens, while ViCrop (Zhang et al., 2025a) uses attention maps to enhance visual perception.

For a fair comparison, we implemented all methods on HuatuoGPT-V-7B, following their official code and hyperparameter settings. The experimental results, shown in Tab. F.8, indicate that VGRefine consistently outperforms all other methods.

G. More Experiments on Larger Models

In this section, we provide more experimental results on larger models (with parameters > 10B). We show comparison on all six benchmarks that are designed for biomedical MLLM evaluation, including VQA-RAD (Lau et al.,

Table D.6. Ablation study on the choice of top K heads and p percentile of magnitude-based filtering.

K	VQA-RAD	SLAKE	PathVQA	PMC-VQA	Avg.	p (%)	VQA-RAD	SLAKE	PathVQA	PMC-VQA	Avg.
1	68.62	75.81	64.85	53.65	68.28	30	70.78	76.84	67.55	55.70	68.22
2	69.78	76.63	63.58	53.90	68.21	40	70.70	76.66	67.28	56.00	68.12
5	70.09	76.56	66.52	54.30	68.08	50	**71.24**	**76.88**	67.61	**56.20**	**68.42**
8	70.70	76.52	66.64	55.60	68.12	60	70.70	76.66	67.28	55.65	68.05
10	70.86	76.81	**67.67**	56.05	68.34	70	70.47	76.66	67.61	55.80	68.17
15	70.78	76.84	67.43	55.40	68.11	80	70.78	76.73	67.55	55.80	68.21
20	**71.24**	**76.88**	67.61	**56.20**	**68.42**	90	70.55	76.34	**68.11**	55.50	68.20

Table E.7. Performance comparison on full medical VQA datasets for open-ended medical VQA. We evaluate all models under the zero-shot setting. These results underscore that enhanced visual grounding with our inference-time method VGRefine contributes to better performance on medical VQA tasks. It is important to note that VILA-M3 (Nath et al., 2024), MedPLIB (Huang et al., 2025) and LLaVA-Tri (Xie et al., 2025) incorporate training data from VQA-RAD, SLAKE, and PathVQA, and thus making zero-shot evaluation unfair, and are excluded from our zero-shot comparison.

Model	VQA-RAD				SLAKE				PathVQA			
Metric	BLEU-1	BERT	OpenRecall	Avg.	BLEU-1	BERT	OpenRecall	Avg.	BLEU-1	BERT	OpenRecall	Avg.
Qwen-VL-Chat	28.6	63.4	27.0	39.7	28.9	52.0	33.6	38.2	18.7	45.1	9.9	24.6
LLaVA-v1.6-7B	22.1	58.0	21.9	34.0	30.8	52.7	36.4	40.0	22.8	47.7	11.2	27.2
Med-Flamingo	27.4	61.9	12.7	34.0	11.8	40.2	21.1	24.4	24.3	50.4	2.4	25.7
RadFM	30.5	64.1	41.6	45.4	38.6	61.0	44.2	47.9	24.8	51.4	10.1	29.8
LLaVA-Med-7B	21.6	40.5	28.2	30.1	37.0	58.4	39.2	44.9	28.5	60.1	12.3	33.6
HuatuoGPT-V-7B	49.7	75.0	50.7	58.5	55.0	78.9	55.6	63.2	34.2	65.8	**36.5**	45.5
VGRefine-7B (Ours)	**51.2**	**76.3**	**52.3**	**59.9**	**56.5**	**80.0**	**56.7**	**64.4**	**36.1**	**68.1**	**36.5**	**46.9**

2018), SLAKE (Liu et al., 2021a), PathVQA (He et al., 2020), PMC-VQA (Zhang et al., 2023b), OmniMedVQA (Hu et al., 2024) (open-access split), and MMMU (Health & Medicine track) (Yue et al., 2024). All evaluations were conducted in a zero-shot setting using question templates provided by LLaVA (see Sec. I).

All experiments are conducted using the same hyperparameters across benchmarks. Specifically, for Step I, we aggregate the attention maps from the top $K = 20$ heads with the highest alignment to visual relevant regions, as measured by KL divergence on our curated evaluation set built using COCO images. This setup prevents data leakage from medical evaluation benchmarks and demonstrates that our method generalizes from natural images to biomedical domains. Low-activation regions are suppressed based on a percentile threshold $p = 50\%$ over attention magnitude. For Step II we apply the attention knockout only at $\ell = 34, 35, 36$ layer, which, according to our analysis in Fig. 3 demonstrates the most relevancy to visual grounding among all the layers. We applied our inference-time method VGRefine-34B on HuatuoGPT-V-34B (Chen et al., 2024a). The hyperparameters K and p are kept consistent with the VGRefine-7B setting. In Step II, we apply attention knockout to more layers, as the 34B model has twice as many layers as the 7B variant and requires deeper intervention to achieve significant improvements.

Results in Tab. G.9 demonstrate that our proposed method consistently achieves good performance across all 6 bench-

marks, demonstrating its effectiveness in enhancing all types of medical VQA.

Table F.8. Accuracy on closed-ended medical VQA datasets.

Model	VQA-RAD	SLAKE	PathVQA	PMC-VQA	Avg.
HuatuoGPT-V-7B (Baseline)	67.4	76.5	60.7	53.9	65.3
PAI(Liu et al., 2024c)	43.7	24.48	20.8	52.8	33.3
AdaptVis(Chen et al., 2025b)	68.6	75.1	**67.6**	52.9	66.7
ViCrop (Zhang et al., 2025a)	68.9	70.9	66.7	54.6	65.5
VGRefine (Ours)	**71.2**	**76.9**	67.6	**56.2**	**68.4**

Table G.9. Experiment results of larger models (more than 10B parameters). We evaluate all models under the zero-shot setting. Our inference-time method VGRefine outperforms other state-of-the-art medical MLLMs in most cases. These results underscore that enhanced visual grounding contributes to better performance on medical VQA tasks. It is important to note that VILA-M3 (Nath et al., 2024), MedRegA (Wang et al., 2025) incorporate training data from VQA-RAD (Lau et al., 2018), SLAKE (Liu et al., 2021a), PathVQA (He et al., 2020), and PMC-VQA (Zhang et al., 2023b), thus making zero-shot evaluation unfair, and are excluded from our zero-shot comparison of these benchmarks.

Benchmarks	Subset	Metric	LLaVA-v1.6-34B	VILA-M3-13B	MedRegA-34B	HuatuoGPT-V-34B	VGRefine-34B (Ours)
VQA-RAD	-	CloseAcc	58.6	-	-	68.1	**72.9**
		BLEU-1	44.5	-	-	50.5	**52.6**
		BERT	69.2	-	-	**74.8**	**74.8**
		OpenRecall	43.6	-	-	51.7	**52.8**
SLAKE	-	CloseAcc	67.3	-	-	76.9	**79.1**
		BLEU-1	48.6	-	-	56.3	**57.2**
		BERT	51.8	-	-	77.6	**79.5**
		OpenRecall	54.2	-	-	57.5	**58.5**
PathVQA	-	CloseAcc	59.1	-	-	63.5	**69.7**
		BLEU-1	28.1	-	-	36.6	**37.6**
		BERT	57.7	-	-	65.6	**65.9**
		OpenRecall	29.3	-	-	36.9	**37.1**
PathVQA	-	CloseAcc	44.4	-	-	58.2	**58.7**
Avg. on Med-VQAs	-	CloseAcc	57.4	-	-	67.0	**70.7**
MMMU	BMS	CloseAcc	56.4	36.8	54.3	64.3	**66.0**
	CM		52.8	38.8	53.5	56.5	**58.2**
	DLM		42.6	29.0	37.7	45.1	**45.4**
	P		41.6	29.3	38.4	43.7	**44.0**
	PH		38.4	32.2	40.7	43.8	**44.8**
	Avg.		45.6	33.3	44.7	50.1	**51.3**
OmniMedVQA	CT	CloseAcc	50.6	56.9	62.5	69.7	**71.7**
	FP		63.4	50.1	80.4	**84.6**	84.4
	MRI		60.9	52.9	72.7	69.7	**73.9**
	OCT		68.4	41.5	86.2	**87.8**	87.6
	Der		65.7	45.1	**79.9**	70.2	70.9
	Mic		62.8	50.6	71.3	71.1	**71.4**
	X-Ray		74.7	62.5	78.7	83.8	**84.7**
	US		44.5	47.1	49.4	81.7	**83.1**
	Avg.		61.4	52.3	70.3	74.4	**76.6**

H. HuatuoGPT-Vision-Bio with BiomedCLIP Vision Encoder

Model Setup. To evaluate the effect of domain-specific visual encoders, we modified the original HuatuoGPT-Vision architecture by replacing its CLIP-based vision encoder with BioMedCLIP (Zhang et al., 2025b), a biomedical foundation model pretrained on 15 million scientific image–text pairs. All other components of the model (including the Qwen2 language model, the cross-modal connector module, and the training protocol) remain identical to the original configuration. *This substitution allows us to isolate the impact of specialized medical image representations on visual grounding performance.*

Training Details. Since the original training code for HuatuoGPT-Vision was not publicly available, we replicated the training pipeline using the LLaVA-NeXT (Liu et al., 2024b) codebase. We follow a two-stage training protocol on the same pretraining and instruction-tuning datasets used in HuatuoGPT-Vision, including LLaVA and PubMedVision. In Stage I, we freeze both the BioMedCLIP vision encoder and the Qwen2 language model, training only the connector to align visual and textual representations. In Stage II, we fine-tune both the connector and the language model while keeping the vision encoder frozen. The model is trained for 1 epoch. BioMedCLIP processes images at a fixed resolution of 224×224 with a patch size of 16, which differs from the resolution and tokenization settings used in the original CLIP-based HuatuoGPT-Vision.

Analysis Results. As shown in Fig. 1 and Supp. B.5, *the issue of suboptimal visual grounding on medical images cannot be solved by using BiomedCLIP vision encoder.*

I. Prompts for VGMED and QA evaluation

I.1. Prompts for constructing VGMED

I.2. Prompts for Zero-shot Evaluation

We used the LLaVA prompt template during the evaluation for open, closed-ended, and multiple-choice questions.

Localization Question Set

- Is there a {label} in the image?

- Can you see a {label} in the image?

- Does the image contain a {label}?

- Is a {label} present in this image?

- Do you see a {label} in the picture?

- Is the {label} visible in the image?

- Is there any sign of a {label} in the image?

- Can a {label} be found in this image?

- Does this image show a {label}?

- Is a {label} shown in the picture?

Figure I.4. The question from a predefined question set is sampled for generating localization questions in both the COCO and VGMED datasets. {label} represents the object (in COCO) or organ/lesion (in VGMED) identified by a bounding box in the corresponding image.

Prompt for VGMED Attribute Questions (MRI)

Your task is to generate clinically meaningful questions for an evaluation dataset to assess visual grounding capability in medical reasoning, without requiring deep semantic grounding.

- Semantic Grounding: Anchors linguistic representations to domain-specific medical knowledge to inform what to look for, ensuring accurate reasoning about diseases or anatomical concepts.

- Visual Grounding: Localizes and interprets specific regions in medical images based on relevant features, enabling spatial alignment of language queries to visual elements for accurate analysis.

We will provide the label of a medical structure (organ, lesion, or tissue) in a {modality} image, derived from a bounding box annotation. Your need to generate three clinically relevant questions about visual attributes of this structure.

Guidelines for the question:

- Focus on visual grounding, without requiring deep medical semantic grounding.

- Ensure clinical relevance.

- Require attention to the entire annotated bounding box.

- Address only observable visual characteristics (e.g., size, shape, density, enhancement, homogeneity).

- Avoid referencing other body parts or surrounding structures.

- Do not include position, modality, or plane.

- Exclude diagnoses or treatments requiring deep semantic grounding.

- Avoid compound or multi-condition questions.

- Ensure variety across the three questions.

Example questions:

- "Is the lesion hyper or hypointense?"

- "Is the lesion enhancing?"

- "What does the area of necrosis look like?"

- "What pattern of enhancement does the lesion show?"

Now, generate three questions based on the label. Return exactly three questions without any additional text or formatting.

Label: {label}

Figure I.5. For attribute questions in VGMED, we use a specific prompt for each modality. In the prompt, {modality} denotes the modality of the image. {label} denotes the organ or lesion labeled by a bounding box in the image.

Prompt for VGMED Attribute Questions (CT)

Your task is to generate clinically meaningful questions for an evaluation
dataset to assess visual grounding capability in medical reasoning, without
requiring deep semantic grounding.

- Semantic Grounding: Anchors linguistic representations to
  domain-specific medical knowledge to inform what to look for, ensuring
  accurate reasoning about diseases or anatomical concepts.

- Visual Grounding: Localizes and interprets specific regions in medical
  images based on relevant features, enabling spatial alignment of language
  queries to visual elements for accurate analysis.

We will provide the label of a medical structure (organ, lesion, or tissue)
in a {modality} image, derived from a bounding box annotation. Your need to
generate three clinically relevant questions about visual attributes of this
structure.
Guidelines for the question:

- Focus on visual grounding, without requiring deep medical semantic
  grounding.

- Ensure clinical relevance.

- Require attention to the entire annotated bounding box.

- Address only observable visual characteristics (e.g., size, shape,
  density, enhancement, homogeneity).

- Avoid referencing other body parts or surrounding structures.

- Do not include position, modality, or plane.

- Exclude diagnoses or treatments requiring deep semantic grounding.

- Avoid compound or multi-condition questions.

- Ensure variety across the three questions.

Example questions:

- "Are there ground glass opacities within the lung?"

- "Is the kidney enlarged?"

- "What is the size of the necrosis?"

Now, generate three questions based on the label. Return exactly three
questions without any additional text or formatting.

Label: {label}

Figure I.6. For attribute questions in VGMED, we use a specific prompt for each modality. In the prompt, {modality} denotes the modality of the image. {label} denotes the organ or lesion labeled by a bounding box in the image.

Prompt for VGMED Attribute Questions (Ultrasound)

Your task is to generate clinically meaningful questions for an evaluation dataset to assess visual grounding capability in medical reasoning, without requiring deep semantic grounding.

- Semantic Grounding: Anchors linguistic representations to domain-specific medical knowledge to inform what to look for, ensuring accurate reasoning about diseases or anatomical concepts.

- Visual Grounding: Localizes and interprets specific regions in medical images based on relevant features, enabling spatial alignment of language queries to visual elements for accurate analysis.

We will provide the label of a medical structure (organ, lesion, or tissue) in a {modality} image, derived from a bounding box annotation. Your need to generate three clinically relevant questions about visual attributes of this structure.

Guidelines for the question:

- Focus on visual grounding, without requiring deep medical semantic grounding.

- Ensure clinical relevance.

- Require attention to the entire annotated bounding box.

- Address only observable visual characteristics (e.g., size, shape, density, enhancement, homogeneity).

- Avoid referencing other body parts or surrounding structures.

- Do not include position, modality, or plane.

- Exclude diagnoses or treatments requiring deep semantic grounding.

- Avoid compound or multi-condition questions.

- Ensure variety across the three questions.

Example questions:

- "Does the thyroid nodule have irregular or microlobulated margins?"

- "Does the thyroid nodule have marked hypoechogenicity?"

- "Does the thyroid nodule have multiple microcalcifications?"

- "Is the breast lesion homogeneous or heterogeneous?"

- "Does the breast lesion appear solid or cystic on ultrasound?"

Now, generate three questions based on the label. Return exactly three questions without any additional text or formatting.

Label: {label}

Figure I.7. For attribute questions in VGMED, we use a specific prompt for each modality. In the prompt, {modality} denotes the modality of the image. {label} denotes the organ or lesion labeled by a bounding box in the image.

Prompt for VGMED Attribute Questions (X-ray)

Your task is to generate clinically meaningful questions for an evaluation
dataset to assess visual grounding capability in medical reasoning, without
requiring deep semantic grounding.

- Semantic Grounding: Anchors linguistic representations to
  domain-specific medical knowledge to inform what to look for, ensuring
  accurate reasoning about diseases or anatomical concepts.

- Visual Grounding: Localizes and interprets specific regions in medical
  images based on relevant features, enabling spatial alignment of language
  queries to visual elements for accurate analysis.

We will provide the label of a medical structure (organ, lesion, or tissue)
in a {modality} image, derived from a bounding box annotation. Your need to
generate three clinically relevant questions about visual attributes of this
structure.
Guidelines for the question:

- Focus on visual grounding, without requiring deep medical semantic
  grounding.

- Ensure clinical relevance.

- Require attention to the entire annotated bounding box.

- Address only observable visual characteristics (e.g., size, shape,
  density, enhancement, homogeneity).

- Avoid referencing other body parts or surrounding structures.

- Do not include position, modality, or plane.

- Exclude diagnoses or treatments requiring deep semantic grounding.

- Avoid compound or multi-condition questions.

- Ensure variety across the three questions.

Example questions:

- "What is the size of the pneumothorax?"

- "Where is the pneumothorax?"

- "Does the lung field appear more opaque or translucent in the annotated
  region?"

Now, generate three questions based on the label. Return exactly three
questions without any additional text or formatting.

Label: {label}

Figure I.8. For attribute questions in VGMED, we use a specific prompt for each modality. In the prompt, {modality} denotes the modality of the image. {label} denotes the organ or lesion labeled by a bounding box in the image.

Prompt for VGMED Attribute Questions (Fundus Photography)

```
Your task is to generate clinically meaningful questions for an evaluation
dataset to assess visual grounding capability in medical reasoning, without
requiring deep semantic grounding.
```

- ```
  Semantic Grounding:  Anchors linguistic representations to
  domain-specific medical knowledge to inform what to look for, ensuring
  accurate reasoning about diseases or anatomical concepts.
  ```

- ```
  Visual Grounding:  Localizes and interprets specific regions in medical
  images based on relevant features, enabling spatial alignment of language
  queries to visual elements for accurate analysis.
  ```

```
We will provide the label of a medical structure (organ, lesion, or tissue)
in a {modality} image, derived from a bounding box annotation.  Your need to
generate three clinically relevant questions about visual attributes of this
structure.
```
Guidelines for the question:

- ```
  Focus on visual grounding, without requiring deep medical semantic
  grounding.
  ```

- Ensure clinical relevance.

- Require attention to the entire annotated bounding box.

- ```
  Address only observable visual characteristics (e.g., size, shape,
  density, enhancement, homogeneity).
  ```

- Avoid referencing other body parts or surrounding structures.

- Do not include position, modality, or plane.

- Exclude diagnoses or treatments requiring deep semantic grounding.

- Avoid compound or multi-condition questions.

- Ensure variety across the three questions.

Example questions:

- "Is there any pallor observed in the optic disc?"

- "Does the optic disc appear swollen or elevated?"

- "Is there any evidence of swelling or pallor in the optic disc?"

```
Now, generate three questions based on the label.  Return exactly three
questions without any additional text or formatting.
```

Label: {label}

Figure I.9. For attribute questions in VGMED, we use a specific prompt for each modality. In the prompt, {modality} denotes the modality of the image. {label} denotes the organ or lesion labeled by a bounding box in the image.

Prompt for VGMED Attribute Questions (Endoscopy)

Your task is to generate clinically meaningful questions for an evaluation dataset to assess visual grounding capability in medical reasoning, without requiring deep semantic grounding.

- Semantic Grounding: Anchors linguistic representations to domain-specific medical knowledge to inform what to look for, ensuring accurate reasoning about diseases or anatomical concepts.

- Visual Grounding: Localizes and interprets specific regions in medical images based on relevant features, enabling spatial alignment of language queries to visual elements for accurate analysis.

We will provide the label of a medical structure (organ, lesion, or tissue) in a {modality} image, derived from a bounding box annotation. Your need to generate three clinically relevant questions about visual attributes of this structure.

Guidelines for the question:

- Focus on visual grounding, without requiring deep medical semantic grounding.

- Ensure clinical relevance.

- Require attention to the entire annotated bounding box.

- Address only observable visual characteristics (e.g., size, shape, density, enhancement, homogeneity).

- Avoid referencing other body parts or surrounding structures.

- Do not include position, modality, or plane.

- Exclude diagnoses or treatments requiring deep semantic grounding.

- Avoid compound or multi-condition questions.

- Ensure variety across the three questions.

Example questions:

- "What is the size of the polyp?"

- "Does the colorectal polyp have a smooth or lobulated surface appearance?"

- "What is the mobility of the polyp?"

Now, generate three questions based on the label. Return exactly three questions without any additional text or formatting.

Label: {label}

Figure I.10. For attribute questions in VGMED, we use a specific prompt for each modality. In the prompt, {modality} denotes the modality of the image. {label} denotes the organ or lesion labeled by a bounding box in the image.

Prompt for VGMED Attribute Questions (PET)

```
Your task is to generate clinically meaningful questions for an evaluation
dataset to assess visual grounding capability in medical reasoning, without
requiring deep semantic grounding.
```

- `Semantic Grounding:  Anchors linguistic representations to`
  `domain-specific medical knowledge to inform what to look for, ensuring`
  `accurate reasoning about diseases or anatomical concepts.`

- `Visual Grounding:  Localizes and interprets specific regions in medical`
  `images based on relevant features, enabling spatial alignment of language`
  `queries to visual elements for accurate analysis.`

```
We will provide the label of a medical structure (organ, lesion, or tissue)
in a {modality} image, derived from a bounding box annotation.  Your need to
generate three clinically relevant questions about visual attributes of this
structure.
```
Guidelines for the question:

- `Focus on visual grounding, without requiring deep medical semantic`
  `grounding.`

- `Ensure clinical relevance.`

- `Require attention to the entire annotated bounding box.`

- `Address only observable visual characteristics (e.g., size, shape,`
  `density, enhancement, homogeneity).`

- `Avoid referencing other body parts or surrounding structures.`

- `Do not include position, modality, or plane.`

- `Exclude diagnoses or treatments requiring deep semantic grounding.`

- `Avoid compound or multi-condition questions.`

- `Ensure variety across the three questions.`

Example questions:

- `"Does the lesion show increased radiotracer uptake on the PET scan?"`

- `"Is the lesion hypo- or hyper-metabolic?"`

- `"What is the Standardized Uptake Value (SUV) of the lesion?"`

```
Now, generate three questions based on the label.  Return exactly three
questions without any additional text or formatting.
```

Label: {label}

Figure I.11. For attribute questions in VGMED, we use a specific prompt for each modality. In the prompt, {modality} denotes the modality of the image. {label} denotes the organ or lesion labeled by a bounding box in the image.

Prompt for VGMED Attribute Questions (Dermoscopy)

Your task is to generate clinically meaningful questions for an evaluation dataset to assess visual grounding capability in medical reasoning, without requiring deep semantic grounding.

- Semantic Grounding: Anchors linguistic representations to domain-specific medical knowledge to inform what to look for, ensuring accurate reasoning about diseases or anatomical concepts.

- Visual Grounding: Localizes and interprets specific regions in medical images based on relevant features, enabling spatial alignment of language queries to visual elements for accurate analysis.

We will provide the label of a medical structure (organ, lesion, or tissue) in a {modality} image, derived from a bounding box annotation. Your need to generate three clinically relevant questions about visual attributes of this structure.

Guidelines for the question:

- Focus on visual grounding, without requiring deep medical semantic grounding.

- Ensure clinical relevance.

- Require attention to the entire annotated bounding box.

- Address only observable visual characteristics (e.g., size, shape, density, enhancement, homogeneity).

- Avoid referencing other body parts or surrounding structures.

- Do not include position, modality, or plane.

- Exclude diagnoses or treatments requiring deep semantic grounding.

- Avoid compound or multi-condition questions.

- Ensure variety across the three questions.

Example questions:

- "What is the size of the lesion?"

- "Is the lesion hypo- or hyper pigmented?"

- "Does the lesion have peripheral black dots or clods?"

- "Does the skin lesion have thick lines (reticular or branched)?"

- "Does the lesion have Polymorphous vessels?"

Now, generate three questions based on the label. Return exactly three questions without any additional text or formatting.

Label: {label}

Figure I.12. For attribute questions in VGMED, we use a specific prompt for each modality. In the prompt, {modality} denotes the modality of the image. {label} denotes the organ or lesion labeled by a bounding box in the image.

Prompt for COCO Attribute Questions

Your task is to generate one simple and meaningful question about a visual attribute of an object identified in an image.

We will provide the label of the object, which comes from a bounding box annotation in an image from the COCO dataset.

Guidelines for the question:

• Ensure variety in the questions generated.

• Focus only on the visual characteristics (e.g., color, size, material, etc.) of the given object.

• Do not reference other parts of the image.

• Do not ask questions about the position of the object or the surrounding structure.

• Avoid compound or multi-condition questions.

Now, generate one question based on the following label:
Label: {label}

Figure I.13. In order to compare the results between our VGMED datasets and natural scene images, we have also generated the attribute questions for COCO examples. {label} refers to the object label from the image's bounding boxes.

Short Answer (e.g., VQA-RAD, SLAKE, PathVQA)

```
<question>
Answer the question using a single word or phrase.
```

Figure I.14. Prompt for evaluating the open and closed-ended questions in VQA-RAD, SLAKE, and PathVQA benchmarks.

Option-only for multiple-choice (e.g., PMC-VQA, OmniMedVQA, and MMMU)

```
<question>

 A. <option_1>

 B. <option_2>

 C. <option_3>

 D. <option_4>

Answer with the option's letter from the given choices directly.
```

Figure I.15. Prompt for evaluating the multiple-choice VQA benchmarks.

J. Additional Qualitative Evaluation

J.1. Human Evaluation

We conducted a blinded human evaluation involving five experienced clinicians (4 of them have over 10 years of clinical practice). The study was based on a 20-case questionnaire. For each case, clinicians were shown a medical image with a VQA question and two corresponding attention maps: (1) from the baseline model and (2) from the same model after applying VGRefine. The source of each attention map was not disclosed, and their order was randomized. Clinicians were asked: "*Which model's attention visualization (shown as heatmap) appears more clinically reasonable and trustworthy?*".

* Which model's highlighted region appears more clinically reasonable and trustworthy?

  ☐ Model A

  ☑ Model B

Please share any comments on what influenced your choice (optional):
appears to have less noise

Figure J.16. Example of a blinded human evaluation case, showing a medical image with a VQA question, baseline attention map, and VGRefine attention map, assessed by an experienced clinician for clinical reasonableness. Clinician feedback highlighted that VGRefine attention maps were less noisy, better localized, and more aligned with expected clinical focus points.

J.2. Additional Qualitative Analysis on Medical MLLM's Attention Maps

Figure J.17. **Qualitative evaluation.** We visualize attention maps across different layers, including those with the lowest KL divergence (highlighted with an orange boundary), which are indicative of layers most relevant to visual grounding in MLLMs. For medical images, the attention maps of medical MLLMs show limited alignment with the ground-truth annotated regions. In contrast, a general-domain MLLM LLaVA-v1.5 applied to natural images exhibits strong alignment with relevant regions, consistent with other study of general-domain MLLMs (Zhang et al., 2025a). This highlights a gap in MLLM's visual grounding performance between the medical and natural image domains. Best viewed in color and with zoom. **Additional results in Supp J.2**.

Figure J.18. **Qualitative** evaluation of (i) medical MLLMs HuatuoGPT-V, LLaVA-Tri and MedRegA on COCO, and (ii) LLaVA-v1.5 on VGMED. We visualize attention maps across different layers, including those with the lowest KL divergence (highlighted with an orange boundary), which are indicative of layers most relevant to visual grounding in MLLMs. We observe that LLaVA-v1.5 fails to ground predictions in clinically relevant regions when operating on medical images and medical VQA tasks. Furthermore, medical-domain models can ground their predictions when applied to natural images. This is consistent with our quantitative analysis in Supp. B.5. Together, they show that medical MLLMs possess good visual grounding capabilities in general-domain settings. **Overall, this confirms that the grounding failure is not due to model weakness, but is fundamentally specific to the medical domain, consistent with our central findings. Inadequate visual grounding is a medical-domain failure mode.**

Figure J.19. **Qualitative evaluation.** We visualize attention maps across different layers, including those with the lowest KL divergence (highlighted with an orange boundary), which are indicative of layers most relevant to visual grounding in MLLMs. For medical images, the attention maps of medical MLLMs show limited alignment with the ground-truth annotated regions. In contrast, a general-domain MLLM LLaVA-v1.5 applied to natural images exhibits strong alignment with relevant regions, consistent with other study of general-domain MLLMs (Zhang et al., 2025a). This highlights a gap in MLLM's visual grounding performance between the medical and natural image domains.

Figure J.20. **Qualitative evaluation.** We visualize attention maps across different layers, including those with the lowest KL divergence (highlighted with an orange boundary), which are indicative of layers most relevant to visual grounding in MLLMs. For medical images, the attention maps of medical MLLMs show limited alignment with the ground-truth annotated regions. In contrast, a general-domain MLLM LLaVA-v1.5 applied to natural images exhibits strong alignment with relevant regions, consistent with other study of general-domain MLLMs (Zhang et al., 2025a). This highlights a gap in MLLM's visual grounding performance between the medical and natural image domains.

Figure J.21. **Qualitative evaluation.** We visualize attention maps across different layers, including those with the lowest KL divergence (highlighted with an orange boundary), which are indicative of layers most relevant to visual grounding in MLLMs. For medical images, the attention maps of HuatuoGPT-V-Bio with a specialized vision encoder (BiomedCLIP) show limited alignment with the ground-truth annotated regions. In contrast, a general-domain MLLM LLaVA-v1.5 applied to natural images exhibits strong alignment with relevant regions, consistent with other study of general-domain MLLMs (Zhang et al., 2025a).

Figure J.22. **Qualitative evaluation.** We visualize attention maps across different layers, including those with the lowest KL divergence (highlighted with an orange boundary), which are indicative of layers most relevant to visual grounding in MLLMs. For medical images, the attention maps of medical MLLMs show limited alignment with the ground-truth annotated regions. In contrast, a general-domain MLLM LLaVA-v1.5 applied to natural images exhibits strong alignment with relevant regions, consistent with other study of general-domain MLLMs (Zhang et al., 2025a). This highlights a gap in MLLM's visual grounding performance between the medical and natural image domains.

Figure J.23. **Qualitative evaluation.** We visualize attention maps across different layers, including those with the lowest KL divergence (highlighted with an orange boundary), which are indicative of layers most relevant to visual grounding in MLLMs. For medical images, the attention maps of medical MLLMs show limited alignment with the ground-truth annotated regions. In contrast, a general-domain MLLM LLaVA-v1.5 applied to natural images exhibits strong alignment with relevant regions, consistent with other study of general-domain MLLMs (Zhang et al., 2025a). This highlights a gap in MLLM's visual grounding performance between the medical and natural image domains.

Figure J.24. **Qualitative evaluation.** We visualize attention maps across different layers, including those with the lowest KL divergence (highlighted with an orange boundary), which are indicative of layers most relevant to visual grounding in MLLMs. For medical images, the attention maps of medical MLLMs show limited alignment with the ground-truth annotated regions. In contrast, a general-domain MLLM LLaVA-v1.5 applied to natural images exhibits strong alignment with relevant regions, consistent with other study of general-domain MLLMs (Zhang et al., 2025a). This highlights a gap in MLLM's visual grounding performance between the medical and natural image domains.

Figure J.25. **Qualitative evaluation.** We visualize attention maps across different layers, including those with the lowest KL divergence (highlighted with an orange boundary), which are indicative of layers most relevant to visual grounding in MLLMs. For medical images, the attention maps of medical MLLMs show limited alignment with the ground-truth annotated regions. In contrast, a general-domain MLLM LLaVA-v1.5 applied to natural images exhibits strong alignment with relevant regions, consistent with other study of general-domain MLLMs (Zhang et al., 2025a). This highlights a gap in MLLM's visual grounding performance between the medical and natural image domains.

Figure J.26. **Qualitative evaluation.** We visualize attention maps across different layers, including those with the lowest KL divergence (highlighted with an orange boundary), which are indicative of layers most relevant to visual grounding in MLLMs. For medical images, the attention maps of medical MLLMs show limited alignment with the ground-truth annotated regions. In contrast, a general-domain MLLM LLaVA-v1.5 applied to natural images exhibits strong alignment with relevant regions, consistent with other study of general-domain MLLMs (Zhang et al., 2025a). This highlights a gap in MLLM's visual grounding performance between the medical and natural image domains.

K. Additional Evaluation of Latest General MLLMs

Figure K.27. (a) **Quantitative** and (b) **qualitative** evaluation of InternVL3-8B and Qwen2.5-VL-7B on VGMED and COCO. We observe that the visual grounding deficiency in medical domain persists even in these latest general-purpose models.

L. Attention Maps Derived from Different Text Tokens

Figure L.28. **Comparison of visual grounding when using *all input tokens*, *question-only tokens*, or the *last token* to derive attention maps.** Using two representative MLLMs (HuatuoGPT-V-7B and LLaVA-v1.5), we evaluate how different token-selection strategies affect attention alignment on VGMED and COCO. Across all metrics and layers, attention maps computed from the *last token* achieves equal or better alignment with ground-truth regions compared to the alternative options.

M. Representative Failure Cases

Figure M.29. **Representative failure cases of HuatuoGPT-Vision on medical benchmarks.** (a) The model correctly interprets the question but attends to the wrong anatomical region, leading to an incorrect answer. After applying VGRefine, the model's attention shifts toward more clinically relevant region, resulting the correct prediction. (b) The model misunderstand the question, resulting in both semantic and visual grounding failure. (c) Additionally, we include examples from LLaVA-v1.5 on natural images as a reference of accurate visual grounding. While multiple factors contribute to poor generalization, weak visual grounding consistently emerges as a major and measurable issue, though not the sole cause.

N. Limitations

While our work provides a systematic and detailed investigation into visual grounding as a key failure mode in medical MLLMs, it focuses exclusively on this aspect. We do not examine other potential sources of failure, such as deficiencies in semantic grounding or reasoning capabilities. In practice, failures may also arise from an inability to recognize what clinical concepts are relevant or to integrate multimodal information effectively. Additionally, our proposed method, VGRefine, is designed to improve visual grounding at inference time but does not address other underlying limitations, such as dataset biases or insufficient domain-specific knowledge. Future work will explore complementary methods to assess and improve semantic grounding and extend our analysis framework to uncover other failure modes.

O. Experimental Setting/Details and Computing Resources

For both VGRefine-7B and VGRefine-34B, we select the top 20 attention heads—ranked by alignment with visually relevant regions—and average their outputs to obtain the filtered attention map. A percentile threshold of 50% is used to suppress low-activation regions during attention knockout. For VGRefine-7B, the attention knockout is applied at layer $l = 16$, while for VGRefine-34B, it is applied at layers $l = 34, 35, 36$, identified through our quantitative analysis as most relevant to visual grounding. We follow a zero-shot evaluation protocol across six biomedical VQA benchmarks: VQA-RAD, SLAKE, PathVQA, PMC-VQA, OmniMedVQA, and MMMU (Health & Medicine track). The full set of prompts used for zero-shot evaluation is provided in Section F.2. All experiments are conducted on a server with 8×NVIDIA A100 80GB GPUs.

P. Broader Impacts and Ethical Considerations

This work involves the analysis of medical MLLMs using publicly available datasets that are de-identified. No private or sensitive patient data is used. We acknowledge that the deployment of medical MLLMs carries potential risks, including misinterpretation of clinical images, over-reliance on automated outputs by clinicians, and disparities in performance across patient populations. Our work aims to mitigate such risks by improving the reliability of model predictions through better visual grounding. To promote transparency and reproducibility, we provide open access to code, evaluation metrics, and the VGMED dataset. This enables the broader research community to scrutinize and build upon our work responsibly.

Q. Safeguards

Our study does not involve training or releasing a new foundation model, but rather evaluates and analyzes existing medical MLLMs in terms of their visual grounding behavior. While our proposed inference-time refinement method improves grounding performance, it is designed for research use only and does not replace expert validation. We do not claim clinical applicability, and no components of our work should be used for medical diagnosis or decision-making without extensive clinical evaluation.

If any models or code are released, access will be gated under a research-use license, and accompanied by usage guidelines clearly stating that they are intended solely for non-commercial, academic use. The evaluation dataset we construct contains only de-identified medical images drawn from publicly available datasets, and all visual content has been reviewed to ensure it does not pose safety, privacy, or dual-use risks.

R. Licenses

All datasets and models used in this work are publicly available and cited appropriately in the main paper. We do not scrape any new data from the web or repackage any existing datasets; all visual assets have been used in accordance with their licenses.

S. Use of Large Language Models (LLMs)

LLMs were used solely as a writing aid to improve clarity, grammar, and style. They were not involved in generating research ideas, designing methodology, analyzing data, or drawing conclusions.