Even your Teacher Needs Guidance: Ground-Truth Targets Dampen Regularization Imposed by Self-Distillation

Abstract

Knowledge distillation is classically a procedure where a neural network is trained on the output of another network along with the original targets in order to transfer knowledge between the architectures. The special case of self-distillation, where the network architectures are identical, has been observed to improve generalization accuracy. In this paper, we consider an iterative variant of self-distillation in a kernel regression setting, in which successive steps incorporate both model outputs and the ground-truth targets. This allows us to provide the first theoretical results on the importance of using the weighted ground-truth targets in self-distillation. Our focus is on fitting nonlinear functions to training data with a weighted mean square error objective function suitable for distillation, subject to ℓ_2 regularization of the model parameters. We show that any such function obtained with self-distillation can be calculated directly as a function of the initial fit, and that infinite distillation steps yields the same optimization problem as the original with amplified regularization. Furthermore, we provide a closed form solution for the optimal choice of weighting parameter at each step, and show how to efficiently estimate this weighting parameter for deep learning and significantly reduce the computational requirements compared to a grid search.

1 Introduction

Knowledge distillation, most commonly known from Hinton et al. (2015), is a procedure to transfer *knowledge* from one neural network (teacher) to another neural network (student).[1] Often the student has fewer parameters than the teacher, and the procedure can be seen as a model compression technique. Originally, the distillation procedure achieves the knowledge transfer by training the student network using the original training targets, denoted as ground-truth targets, as well as a softened distribution of logits from the (already trained and fixed) teacher network.[2] Since the popularization of knowledge distillation by Hinton et al. (2015), the idea of knowledge distillation has been extended to a variety of settings.[3] This paper will focus on the special case where the teacher and student are of identical architecture, called self-distillation, and where the aim is to improve predictive performance, rather than compressing the model.

The idea of self-distillation is to use outputs from a trained model together with the original targets as new targets for retraining the same model from scratch. We refer to this as one step of self-distillation, and one can iterate this procedure for multiple distillation steps (see Figure 1). Empirically, it has been shown that this procedure often generalizes better than the model trained merely on the

---

[1] Often knowledge distillation is also referred to under the name *Teacher-Student learning*.
[2] We will refer to the weighted outputs of the penultimate layer, i.e. pre-activation of the last layer, as logits.
[3] See Section 2 for a brief overview, or see Wang and Yoon (2020) for a more exhaustive survey

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

original targets, and achieves higher predictive performance on validation data, despite no additional information being provided during training (Furlanello et al., 2018; Ahn et al., 2019; Yang et al., 2018).

Figure 1: Illustration of self-distillation for two steps after the initial training, where we use the notation $f^{(\tau)} = f(\cdot, \hat{\boldsymbol{\beta}}^{(\tau)})$. See Section 3 for details.

Modern deep neural networks are often trained in the over-parameterized regime, where the amount of trainable parameters highly exceed the amount of training samples. Under simple first-order methods such as gradient descent, such large networks can fit any target, but in order to generalize well, such overfitting is usually undesirable (Zhang et al., 2017; Nakkiran et al., 2020). Thus, some type of regularization is typically imposed during training, in order to avoid overfitting. A common choice is to add an ℓ_2-regularization[4] term to our objective function, which has been shown to perform comparably to early-stopping gradient descent training (Yao et al., 2007). However, in the theoretical study of the over-parameterized regime, regularization is often overlooked, but recent results have shown a connection between wide neural networks and kernel ridge regression through the Neural Tangent Kernel (NTK) (Lee et al., 2019, 2020; Hu et al., 2019). We briefly elaborate on this connection in Section C, which motivates our problem setup and connection to deep learning in Section 5.

2 Related Work

The idea of knowledge distillation dates back to Bucila et al. (2006), and was later brought to the deep learning setting by Ba and Caruana (2014) and more recently popularized by Hinton et al. (2015) in the context of compressing neural networks. Since the original formulation, various extensions have been proposed. Some approaches focus on matching the teacher and student models on statistics other than the distribution of the logits, such as intermediate representations (Romero et al., 2015), spacial attention maps (Zagoruyko and Komodakis, 2019), Jacobians (Srinivas and Fleuret, 2018), Gram matrices (Yim et al., 2017), or relational information between teacher outputs (Park et al., 2019). Other extensions focus on developing the transfer procedure, such as self-distillation (Furlanello et al., 2018), data-free distillation (Lopes et al., 2017; Nayak et al., 2019; Micaelli and Storkey, 2019; Chen et al., 2019; Fang et al., 2019), data distillation (Radosavovic et al., 2018), residual knowledge distillation (Gao et al., 2020), online distillation (Anil et al., 2018) or contrastive distillation (Ahn et al., 2019; Tian et al., 2020a).

The practical benefits of knowledge distillation have been proven countless of times in a variety of settings, but the theoretical justification for knowledge distillation is still highly absent. Hinton et al. (2015) conjecture that the success of knowledge distillation should be attributed to the transfer of *dark knowledge* (e.g. inter-class relationships revealed in the soft labels). Müller et al. (2019); Tang et al. (2020) support this conjecture, and argue that knowledge distillation is similar to performing adaptive label smoothing weighted by the teacher's confidence in the predictions. Dong et al. (2019) show the importance of early stopping when training over-parameterized neural networks for distillation purposes by arguing that neural networks tend to fit informative and simple patterns faster than noisy signals, and knowledge distillation utilizes these simple patterns for knowledge transfer. Abnar et al. (2020) empirically investigate how knowledge distillation can transfer inductive biases between student and teacher models, and Gotmare et al. (2019) empirically shows how the dark knowledge shared by the teacher mainly is disbursed to some of the deepest layers of the teacher.

To the best of our knowledge, few papers investigate knowledge distillation from a rigorous theoretical point of view, and those that do, do so with strong assumptions on the setting. Phuong and Lampert (2019) ignore the ground-truth targets during distillation and furthermore assume linear models.

---

[4]With slight differences, ℓ_2 regularization is often referred to as weight decay and ridge regularization in deep learning and statistical learning literature, respectively.

Mobahi et al. (2020) investigate self-distillation in a Hilbert space setting with kernel ridge regression models where the teacher is trained on the ground-truth targets, and the student (and subsequent iterations) is only trained on the predictions from the teacher without access to the ground-truth targets. They show that self-distillation progressively limits the number of basis functions used to represent the solutions, thus eventually causing the solutions to underfit. In this paper, we build on the theoretical results of Mobahi et al. (2020), but we include the weighted ground-truth targets in the self-distillation procedure, where we allow the weight to depend on the self-distillation step, and show how this drastically affects the behavior and effect of self-distillation.[5]

Our Contributions   Through a theoretical analysis we show that

- the solution at any distillation step can easily be calculated as a function of the initial fit, and infinitely many steps of self-distillation (with fixed distillation weight) correspond to solving the usual kernel ridge regression problem with a specific amplified regularization parameter for non-zero weights,

- for fixed distillation weights, self-distillation amplifies the regularization at each distillation step, and the ground-truth targets dampen the sparsification and regularization of the self-distilled solutions, ensuring non-zero solutions for any number of distillation steps,

- the optimal distillation weight has a closed form solution for kernel ridge regression, and can be estimated efficiently for neural networks compared to grid search.

The proofs of all our results can be found in Supplementary Material A, and code to reproduce our example in Section 4.5 and results in Section B will be made publicly available after review.

Notation   Vectors and matrices are denoted by bold-faced letters; vectors are column vectors by default, and for a vector $\mathbf{a}$ let $[\mathbf{a}]_i$ be the i-th entry and for a matrix $\mathbf{A}$ let $[\mathbf{A}]_{i,j}$ be the (i,j)-th entry. Let $\mathbf{I}_n$ denote the identity matrix of dimension n, $[k] = \{1, 2, \ldots, k\}$, and let $\|\cdot\|_2$ and $\|\cdot\|_F$ denote the ℓ_2-norm and the Frobenius norm, respectively. Finally, for a function $h : \mathbb{R}^n \to \mathbb{R}^d$ and $\mathbf{X} \in \mathbb{R}^{m \times n}$, we denote by $h(\mathbf{X})$ the $\mathbb{R}^{m \times d}$ matrix of outcomes, where the i'th row of $h(\mathbf{X})$ is the function applied to the i'th row of $\mathbf{X}$, i.e. $[h(\mathbf{X})]_{i,\cdot} = h(\mathbf{x}_i)$.

3   Problem Setup

Consider the training dataset $\mathcal{D} \subseteq \mathbb{R}^d \times \mathbb{R}$, and let $\mathcal{X} = \{\mathbf{x} \mid (\mathbf{x}, y) \in \mathcal{D}\}$ and $\mathcal{Y} = \{y \mid (\mathbf{x}, y) \in \mathcal{D}\}$ denote the inputs and targets, respectively. Let $\mathbf{X} = [\mathbf{x}_i]_{i \in [n]} \in \mathbb{R}^{n \times d}$ be the matrix of inputs, $\mathbf{y} = [y_i]_{i \in [n]}$ the vector of targets, and $\tilde{\mathbf{X}} \in \mathbb{R}^{m \times d}, \tilde{\mathbf{y}} \in \mathbb{R}^m$ be the matrix and vector of validation inputs and targets, respectively. Given a feature map $\varphi : \mathbb{R}^d \to \mathcal{V}$, where $\mathcal{V}$ has dimension D, we denote by $\mathbf{K} = \kappa(\mathbf{X}, \mathbf{X}) = [\kappa(\mathbf{x}_i, \mathbf{x}_j)]_{i,j=1}^n \in \mathbb{R}^{n \times n}$, where $\kappa(\mathbf{x}_i, \mathbf{x}_j) = \langle \varphi(\mathbf{x}_i), \varphi(\mathbf{x}_j) \rangle$, the symmetric kernel (Gram) matrix associated with the feature map φ.[6]

3.1   Self-Distillation of Kernel Ridge Regressions

In order to avoid overfitting our training data, we will impose a regularization term on our weights, and thus investigate the kernel ridge regression functions $f \in \mathcal{F}$ mapping $f : \mathcal{X} \to \mathcal{Y}$, to construct a solution which best approximates the true underlying data generating map and generalize well to new unseen data from this underlying map. We consider self-distillation in the kernel ridge regression setup; i.e. consider the (self-distillation) objective function

$$\mathcal{L}^{\text{distill}}(f(\mathbf{X}, \boldsymbol{\beta}), \mathbf{y}_1, \mathbf{y}_2) = \frac{\alpha}{2} \|f(\mathbf{X}, \boldsymbol{\beta}) - \mathbf{y}_1\|_2^2 + \frac{1 - \alpha}{2} \|f(\mathbf{X}, \boldsymbol{\beta}) - \mathbf{y}_2\|_2^2 + \frac{\lambda}{2} \|\boldsymbol{\beta}\|_2^2, \quad (1)$$

where $\alpha \in [0, 1], \lambda > 0, \mathbf{y}_1, \mathbf{y}_2 \in \mathbb{R}^n$ and $f(\mathbf{X}, \boldsymbol{\beta}) = \varphi(\mathbf{X})\boldsymbol{\beta}$. The objective in (1) is a weighted sum of two Mean Square Error (MSE) objective functions with different targets[7] and an ℓ_2-regularization

---

[5]In Supplementary Material D we relate our problem setup to Mobahi et al. (2020) and extend some of our results to a constrained optimization setting with a regularization functional in Hilbert space.

[6]Since the kernel trick makes the predictions depend only on inner products in the feature space, it is not a restriction if D is infinite. However, for ease of exposition we assume D is finite.

[7]It is easy to verify that minimizing (1) and the classic MSE objective with a weighted target, i.e. $\tilde{\mathcal{L}}^{\text{distill}}(f(\mathbf{X}, \boldsymbol{\beta}), \mathbf{y}_1, \mathbf{y}_2) = \frac{1}{2} \|f(\mathbf{X}, \boldsymbol{\beta}) - (\alpha\mathbf{y}_1 + (1 - \alpha)\mathbf{y}_2)\|_2^2 + \frac{\lambda}{2} \|\boldsymbol{\beta}\|_2^2$, are equivalent and that the objective functions are equal up to the additive constant $\alpha(\alpha - 1) \|\mathbf{y}_1 - \mathbf{y}_2\|_2^2$.

on the model weights. Minimization of (1) w.r.t. $\boldsymbol{\beta}$ is straightforward and yields the minimizer

$$\hat{\boldsymbol{\beta}} \stackrel{\text{def}}{=} \underset{\beta}{\arg\min}\, \mathcal{L}^{\text{distill}}(f(\mathbf{X}, \boldsymbol{\beta}), \mathbf{y}_1, \mathbf{y}_2) = \varphi(\mathbf{X})^\intercal \left(\mathbf{K} + \lambda \mathbf{I}_n\right)^{-1} (\alpha \mathbf{y}_1 + (1-\alpha)\mathbf{y}_2) \qquad (2)$$

by Woodbury's matrix identity and definition of $\mathbf{K}$. This solution can also be seen as a direct application of the Representer Theorem (Schölkopf et al., 2001). Let $\mathbf{y}^{(0)} \stackrel{\text{def}}{=} \mathbf{y}$, i.e. the original targets, and recursively define for the steps $\tau \geq 1$,

$$\hat{\boldsymbol{\beta}}^{(\tau)} \stackrel{\text{def}}{=} \underset{\boldsymbol{\beta}}{\arg\min}\, \mathcal{L}^{\text{distill}}(\boldsymbol{\beta}, \mathbf{y}, \mathbf{y}^{(\tau-1)}) \qquad (3)$$

$$= \varphi(\mathbf{X})^\intercal \left(\mathbf{K} + \lambda \mathbf{I}_n\right)^{-1} \left(\alpha^{(\tau)}\mathbf{y} + (1-\alpha^{(\tau)})\mathbf{y}^{(\tau-1)}\right),$$

$$f(\mathbf{x}, \hat{\boldsymbol{\beta}}^{(\tau)}) \stackrel{\text{def}}{=} \varphi(\mathbf{x})^\intercal \hat{\boldsymbol{\beta}}^{(\tau)} \qquad (4)$$

$$= \kappa(\mathbf{x}, \mathbf{X})^\intercal \left(\mathbf{K} + \lambda \mathbf{I}_n\right)^{-1} \left(\alpha^{(\tau)}\mathbf{y} + (1-\alpha^{(\tau)})\mathbf{y}^{(\tau-1)}\right),$$

$$\mathbf{y}^{(\tau)} \stackrel{\text{def}}{=} f(\mathbf{X}, \hat{\boldsymbol{\beta}}^{(\tau)}), \qquad (5)$$

for fixed $\alpha^{(\tau)} \in [0, 1]$. Notice, the initial step ($\tau = 1$) corresponds to standard training by definition and as such is independent of $\alpha^{(1)}$. Self-distillation treats the weighted average of the predictions, $\mathbf{y}^{(1)}$, from this initial model on $\mathbf{X}$, and the ground-truth targets, $\mathbf{y}$ as targets. This procedure is repeated as defined in (3)-(5) and we obtain the self-distillation procedure as illustrated in Figure 1. Note, the special cases $\alpha^{(\tau)} = 0$ and $\alpha^{(\tau)} = 1$ correspond to merely training on the predictions from the previous step, and only training on the original targets, respectively. Thus, $\alpha^{(\tau)} = 1$ is usually not of interest, as the solution is equal to a classical kernel ridge regression, and self-distillation plays no role in this scenario. We will often consider the special case of equal weights, $\alpha^{(2)} = \cdots = \alpha^{(\tau)} = \alpha$, and if $\alpha = 0$ this corresponds to the setting investigated in Mobahi et al. (2020) in a slightly different setup. Thus, some of the following results can be seen as a generalization of Mobahi et al. (2020) to step-wise and non-zero α.

4 Main Results

In this section we present our main results for finitely and infinitely many distillation steps along with a closed form solution for the optimal $\alpha^{(\tau)}$ as well as an illustrative example highlighting the effect of the chosen sequence of $(\alpha^{(t)})$ on the solutions.

4.1 Finite Self-Distillation Steps

Our first result, which follows from straightforward computations, states that the predictions obtained after any finite number of distillation steps can be expressed directly as a function of $\mathbf{y}$ and the kernel matrix $\mathbf{K}$ calculated at the initial fit ($\tau = 1$).

Theorem 4.1. *Let $\mathbf{y}^{(\tau)}, \hat{\boldsymbol{\beta}}^{(\tau)}$, and $f(\cdot, \hat{\boldsymbol{\beta}}^{(\tau)})$ be defined as above. Fix $\alpha^{(2)}, \ldots, \alpha^{(\tau)} \in [0, 1)$, and let $\eta(i, \tau) \stackrel{\text{def}}{=} \prod_{j=i}^{\tau} \left(1 - \alpha^{(j)}\right)$, then for $\tau \geq 1$, we have that*

$$\mathbf{y}^{(\tau)} = \left(\sum_{i=2}^{\tau} \alpha^{(i)} \eta(i+1, \tau) \left(\mathbf{K}\left(\mathbf{K} + \lambda \mathbf{I}_n\right)^{-1}\right)^{\tau-i+1} + \eta(2, \tau) \left(\mathbf{K}\left(\mathbf{K} + \lambda \mathbf{I}_n\right)^{-1}\right)^{\tau}\right) \mathbf{y}, \quad (6)$$

$$f(\mathbf{x}, \hat{\boldsymbol{\beta}}^{(\tau)}) = \alpha^{(\tau)} f(\mathbf{x}, \hat{\boldsymbol{\beta}}^{(1)}) + (1 - \alpha^{(\tau)}) f(\mathbf{x}, \hat{\boldsymbol{\beta}}^{(\tau)}_{\alpha=0}) \qquad (7)$$

for any $\mathbf{x} \in \mathbb{R}^d$, where $\hat{\boldsymbol{\beta}}^{(\tau)}_{\alpha=0}$ is the minimizer in (3) with $\alpha^{(\tau)} = 0$.

Since (6) and (7) are expressed only in terms of $\mathbf{K}$, $(\mathbf{K} + \lambda \mathbf{I}_n)^{-1}$, and $\kappa(\mathbf{x}, \mathbf{X})$ we are able to calculate the predictions for the training data as well as for any $\mathbf{x} \in \mathbb{R}^d$ based merely on the initial fit ($\tau = 1$) without the need for any additional fits. Hence, despite the calculations of $\mathbf{K}$, $\kappa(\mathbf{x}, \mathbf{X})$, and especially $(\mathbf{K} + \lambda \mathbf{I}_n)^{-1}$ being (potentially) highly computationally demanding, when obtained, we can calculate any distillation step directly by the equations in Theorem 4.1. Furthermore, predictions at step τ can be seen as a weighted combination of two classical ridge regression solutions, based on the original targets and the predicted targets from step $\tau - 1$, respectively. However, choosing appropriate $\alpha^{(t)}$ for $t = 2, \ldots, \tau$ is non-trivial. We explore these dynamics in Section 4.3 and 4.4. First, we use Theorem 4.1 to analyse the regularization that self-distillation progressively impose on the solutions.

 ## 4.2 Effective Sparsification of Self-Distillation Solutions

We now show that we can represent the solutions as a weighted sum of basis functions, and that this basis sparsifies when we increase τ, but also that the amount of sparsification depends on the choice of α. A similar sparsification result for the special case of fixed $\alpha^{(\tau)} = 0$ for $\tau \geq 1$ was proved in Mobahi et al. (2020), and in particular, our (13) generalizes equation (47) in their paper.

Using the spectral decomposition of the symmetric matrix $\mathbf{K}$ we write $\mathbf{K} = \mathbf{V}\mathbf{D}\mathbf{V}^\intercal$, where $\mathbf{V} \in \mathbb{R}^{n \times n}$ is an orthogonal matrix with the eigenvectors of $\mathbf{K}$ as rows and $\mathbf{D} \in \mathbb{R}^{n \times n}$ is a non-negative diagonal matrix with the associated eigenvalues in the diagonal. Inserting the diagonalization yields

$$\mathbf{K}(\mathbf{K} + \lambda\mathbf{I}_n)^{-1} = \mathbf{V}\mathbf{D}\mathbf{V}^\intercal(\mathbf{V}\mathbf{D}\mathbf{V}^\intercal + \lambda\mathbf{I}_n)^{-1} \tag{8}$$

$$= \mathbf{V}\mathbf{D}(\mathbf{D} + \lambda\mathbf{I}_n)^{-1}\mathbf{V}^\intercal, \tag{9}$$

where $\lambda > 0$. By straightforward calculations using (6) and (9) we have

$$\mathbf{y}^{(\tau)} = \mathbf{V}\mathbf{B}^{(\tau)}\mathbf{V}^\intercal\mathbf{y}, \quad \text{where} \tag{10}$$

$$\mathbf{B}^{(\tau)} \stackrel{\text{def}}{=} \sum_{i=2}^{\tau} \alpha^{(i)}\eta(i+1,\tau)\mathbf{A}^{\tau-i+1} + \eta(2,\tau)\mathbf{A}^\tau, \quad \text{and} \quad \mathbf{A} \stackrel{\text{def}}{=} \mathbf{D}(\mathbf{D} + \lambda\mathbf{I}_n)^{-1}, \tag{11}$$

and $\mathbf{A}, \mathbf{B}^{(\tau)} \in \mathbb{R}^{n \times n}$ are diagonal matrices for any τ. Furthermore, by (10) the only part of the solution depending on τ is the diagonal matrix, $\mathbf{B}^{(\tau)}$, and in the following we show how $\mathbf{B}^{(\tau)}$ determines the effective sparsification of the solution $f(\cdot, \hat{\boldsymbol{\beta}}^{(\tau)})$.

Lemma 4.2. *Let $\mathbf{B}^{(\tau)}$, and $\mathbf{A}$ be defined as above, and let $\mathbf{B}^{(0)} \stackrel{\text{def}}{=} \mathbf{I}_n$. Then we can express $\mathbf{B}^{(\tau)}$ recursively as*

$$\mathbf{B}^{(\tau)} = \mathbf{A}\left((1 - \alpha^{(\tau)})\mathbf{B}^{(\tau-1)} + \alpha^{(\tau)}\mathbf{I}_n\right), \tag{12}$$

and $[\mathbf{B}^{(\tau)}]_{k,k} \in [0,1]$ is (strictly) decreasing in τ for all $k \in [n]$ and $\tau \geq 1$ if $\alpha^{(2)} = \cdots = \alpha^{(\tau)} = \alpha$.

Similarly to (10), if we use Lemma 4.2 and Theorem 4.1, we can show that for any $\mathbf{x} \in \mathbb{R}^p$

$$f(\mathbf{x}, \hat{\boldsymbol{\beta}}^{(\tau)}) = \kappa(\mathbf{x}, \mathbf{X})^\intercal\mathbf{V}\mathbf{D}^{-1}\mathbf{B}^{(\tau)}\mathbf{V}^\intercal\mathbf{y}$$

$$= \mathbf{p}(\mathbf{x})^\intercal\mathbf{B}^{(\tau)}\mathbf{z}, \quad \text{where} \tag{13}$$

$$\mathbf{p}(\mathbf{x}) \stackrel{\text{def}}{=} \mathbf{D}^{-1}\mathbf{V}^\intercal\kappa(\mathbf{x}, \mathbf{X}), \quad \text{and} \quad \mathbf{z} \stackrel{\text{def}}{=} \mathbf{V}^\intercal\mathbf{y}.$$

Thus, the solution $f(\cdot, \hat{\boldsymbol{\beta}}^{(\tau)})$ can be represented as a weighted sum of some basis functions, where the basis functions are the components of the orthogonally transformed and scaled basis $\mathbf{p}(\mathbf{x})$, and $\mathbf{z}$ is an orthogonally transformed vector of targets.

Now assume $\alpha^{(2)} = \cdots = \alpha^{(\tau)} = \alpha$ for any $\tau \geq 2$ for the remaining of this section. In the following we show how $\mathbf{B}^{(\tau)}$ effectively sparsifies with each distillation step when $\alpha < 1$, and thus also effectively sparsifies the solution $f(\cdot, \hat{\boldsymbol{\beta}}^{(\tau)})$. Lemma 4.2 not only provides a recursive formula for $\mathbf{B}^{(\tau)}$, but also shows that each diagonal element of $\mathbf{B}^{(\tau)}$ is in $[0,1]$ and is strictly decreasing in τ, which in turn implies that the self-distillation procedure progressively shrinks the coefficients of the basis functions. Using Lemma 4.2 we can now show, that not only does $\mathbf{B}^{(\tau)}$ decrease in τ, smaller elements of $\mathbf{B}^{(\tau)}$ shrink faster than larger elements, as we elaborate on below the theorem.

Theorem 4.3. *For any pair of diagonals of $\mathbf{D}$, i.e. d_k and d_j, where $d_k > d_j$, we have for all $\tau \geq 1$,*

$$\frac{[\mathbf{B}^{(\tau)}]_{k,k}}{[\mathbf{B}^{(\tau)}]_{j,j}} = \begin{cases} \frac{1 + \frac{\lambda}{d_j}}{1 + \frac{\lambda}{d_k}}, & \text{for } \alpha = 1, \\ \left(\frac{1 + \frac{\lambda}{d_j}}{1 + \frac{\lambda}{d_k}}\right)^\tau, & \text{for } \alpha = 0, \end{cases} \tag{14}$$

and if we let $\text{sgn}(\cdot)$ denote the sign function[8], then for $\alpha \in (0,1)$ we have that

$$
\text{sgn}\left(\frac{[\mathbf{B}^{(\tau)}]_{k,k}}{[\mathbf{B}^{(\tau)}]_{j,j}} - \frac{[\mathbf{B}^{(\tau-1)}]_{k,k}}{[\mathbf{B}^{(\tau-1)}]_{j,j}} \right)
$$
$$
= \text{sgn}\left(\left(\left(\frac{[\mathbf{B}^{(\tau-1)}]_{k,k}}{[\mathbf{B}^{(\tau-1)}]_{j,j}} - \frac{[\mathbf{A}]_{k,k}}{[\mathbf{A}]_{j,j}} \right) \frac{[\mathbf{A}]_{j,j}}{[\mathbf{B}^{(\tau-1)}]_{k,k}([\mathbf{A}]_{k,k} - [\mathbf{A}]_{j,j})} + 1 \right)^{-1} - \alpha \right). \qquad (15)
$$

If we consider a pair of diagonals of $\mathbf{D}$, where $d_k > d_j$, then for $\alpha = 0$, the fraction $\frac{[\mathbf{B}^{(\tau)}]_{k,k}}{[\mathbf{B}^{(\tau)}]_{j,j}}$ is strictly increasing in τ, due to the r.h.s. of (14) inside the parenthesis being strictly larger than 1. Hence, the diagonals corresponding to smaller eigenvalues shrink faster than the larger ones as τ increases. However, for $\alpha \in (0,1)$ we can not ensure this behaviour, but at step τ we are able to predict the behaviour at step $\tau + 1$, by using (15). Thus, when we include the ground-truth targets in our distillation procedure we do not consistently increase the regularization with each distillation step, but can potentially obtain a solution which does not sparsify any further. We now turn our attention to the question of how to pick the $\alpha^{(\tau)}$'s in an optimal manner, and find that it can be done if we relax the condition that the weights are restricted to the interval $[0,1]$.

4.3 Closed Form Optimal Weighting Parameter

Recall, $\tilde{\mathbf{X}} \in \mathbb{R}^{m \times d}$ is the matrix of validation inputs and $\tilde{\mathbf{y}} \in \mathbb{R}^m$ the vector of validation targets. If we allow $\alpha^{(\tau)} \in \mathbb{R}$, we can find an *optimal* $\alpha^{(\tau)}$ (which is a non-trivial function of λ) at each step τ, denoted by $\alpha^{\star(\tau)}$.[9] Here, *optimal* denotes the value for which the validation MSE is minimized.

Theorem 4.4. *Fix $\tau \geq 2$, $\lambda > 0$ and $\alpha^{(2)}, \ldots, \alpha^{(\tau-1)} \in \mathbb{R}$, then*

$$
\alpha^{\star(\tau)} = \underset{\alpha^{(\tau)} \in \mathbb{R}}{\text{argmin}} \left\| \tilde{\mathbf{y}} - f(\tilde{\mathbf{X}}, \hat{\boldsymbol{\beta}}^{(\tau)}) \right\|_2^2 = 1 - \frac{\left(\tilde{\mathbf{y}}_{\alpha=0}^{(\tau)} - \tilde{\mathbf{y}}^{(1)} \right)^{\mathsf{T}} \left(\tilde{\mathbf{y}} - \tilde{\mathbf{y}}^{(1)} \right)}{\left\| \tilde{\mathbf{y}}_{\alpha=0}^{(\tau)} - \tilde{\mathbf{y}}^{(1)} \right\|_2^2} \qquad (16)
$$

where $\tilde{\mathbf{y}}^{(1)} = f(\tilde{\mathbf{X}}, \hat{\boldsymbol{\beta}}^{(1)})$, and $\tilde{\mathbf{y}}_{\alpha=0}^{(\tau)} = f(\tilde{\mathbf{X}}, \hat{\boldsymbol{\beta}}_{\alpha=0}^{(\tau)})$.

Since neither $\tilde{\mathbf{y}}^{(1)}$ nor $\tilde{\mathbf{y}}_{\alpha=0}^{(\tau)}$ depend on the choice of $\alpha^{(\tau)}$, we can calculate $\alpha^{\star(\tau)}$ recursively as presented in Algorithm 1, where $\alpha^{\star(\tau)}$ has the closed form in (16). In combination with the diagonalization results of Section 4.2 we can efficiently calculate the solutions. This should be compared to performing grid-search for α with g equidistant values on $[0,1]$ in order to approximate the optimal α, which requires $g(\tau - 1) + 1$ model fits if one uses the same α for each sequence of $\tau \geq 2$ steps ($g^{(\tau-1)}$ if α is not fixed across distillation steps). However, by Algorithm 1 it is sufficient to perform $2(\tau - 1) + 1$ model fits, and obtain the exact optimal value instead of an approximated value. In Section 5 we apply Algorithm 1 to approximate $\alpha^{\star(\tau)}$ in a deep learning setting.

4.4 Infinite Number of Self-Distillation Steps

We now prove that if we were to perform an infinite number of distillations steps ($\tau \to \infty$) with a fixed α (i.e. $\alpha^{(2)} = \cdots = \alpha^{(\tau)} = \alpha$) the solution would solve the classical kernel ridge regression problem, with an amplified regularization parameter (by α^{-1}) if $\alpha > 0$. Observe that, when $\alpha = 0$ and $\tau \to \infty$, (6) and (7) yield that the predictions $\mathbf{y}^{(\infty)}$ and $f(\mathbf{x}, \hat{\boldsymbol{\beta}}^{(\infty)})$ collapse to the zero-solution for any $\mathbf{x} \in \mathbb{R}^p$ as expected from Mobahi et al. (2020).

Theorem 4.5. *Let $\mathbf{y}^{(\tau)}, \hat{\boldsymbol{\beta}}^{(\tau)}$, and $f(\cdot, \hat{\boldsymbol{\beta}}^{(\tau)})$ be defined as above, and $\alpha \in (0,1]$, then the following limits hold*

$$
\mathbf{y}^{(\infty)} \overset{\text{def}}{=} \lim_{\tau \to \infty} \mathbf{y}^{(\tau)} = \mathbf{K} \left(\mathbf{K} + \frac{\lambda}{\alpha} \mathbf{I}_n \right)^{-1} \mathbf{y} \qquad (17)
$$

$$
f(\mathbf{x}, \hat{\boldsymbol{\beta}}^{(\infty)}) \overset{\text{def}}{=} \lim_{\tau \to \infty} f(\mathbf{x}, \hat{\boldsymbol{\beta}}^{(\tau)}) = \alpha f(\mathbf{x}, \hat{\boldsymbol{\beta}}^{(1)}) + (1 - \alpha) f(\mathbf{x}, \hat{\boldsymbol{\gamma}}^{(\infty)})
$$

---

[8]Note, we use the definition of $\text{sgn}(\cdot)$ where $\text{sgn}(0) \overset{\text{def}}{=} 0$.

[9]If $\alpha^{\star(\tau)} \notin [0,1]$, the sign of either the first or second term of (1) becomes negative, indicating either too strong or weak regularization of the previous distillation step, and one might fear this affects distillation performance. However, simply clipping of $\alpha^{\star(\tau)}$ to be in $[0,1]$ alleviates this, at the cost of requiring a larger τ.

212 *where (17) corresponds to* classical *kernel ridge regression with amplified regularization parameter*
213 $\frac{\lambda}{\alpha}$, *and we let* $\hat{\gamma}^{(\infty)}$ *denote the kernel ridge regression parameter associated with solving another*
214 *kernel ridge regression on the targets* $\mathbf{y}^{(\infty)}$ *with regularization parameter* λ. *Furthermore, the*
215 *convergence* $\lim_{\tau \to \infty} \mathbf{y}^{(\tau)}$ *is of linear rate.*

216 If $\alpha > 0$, then by (9) and The-
217 orem 4.5, we have that $\mathbf{y}^{(\infty)} =$
218 $\sum_{j=1}^{p} \mathbf{v}_j \frac{d_j}{d_j + \frac{\lambda}{\alpha}} \mathbf{v}_j^\mathsf{T} \mathbf{y}$ and we shrink
219 the eigenvectors with smallest eigen-
220 values, corresponding to the direc-
221 tions with least variance, the most.
222 Furthermore, if $\alpha > 0$ the lim-
223 iting solution is a non-zero ker-
224 nel ridge regression with regulariza-
225 tion parameter $\lambda/\alpha \geq \lambda$, causing
226 the eigenvectors associated with the
227 smallest eigenvalues to shrink even
228 more than in the original solution.

Algorithm 1: Calculate $\hat{\boldsymbol{\beta}}^{(\tau)}$ and $\alpha^{\star(\tau)}$ for $\tau \geq 2$.

Calculate $\hat{\boldsymbol{\beta}}^{(1)}$ from (3) (with any $\alpha^{(1)}$);
Calculate $\tilde{\mathbf{y}}^{(1)} = f(\tilde{\mathbf{X}}, \hat{\boldsymbol{\beta}}^{(1)})$;
for $t = 2$ **to** τ **do**
    Calculate $\hat{\boldsymbol{\beta}}_{\alpha=0}^{(t)}$ from (3) and $\tilde{\mathbf{y}}_{\alpha=0}^{(t)} = f(\tilde{\mathbf{X}}, \hat{\boldsymbol{\beta}}_{\alpha=0}^{(t)})$;
    Solve:
$$\alpha^{\star(t)} = \underset{\alpha \in \mathbb{R}}{\operatorname{argmin}} \left\| \tilde{\mathbf{y}} - \left(\alpha \tilde{\mathbf{y}}^{(1)} + (1-\alpha) \tilde{\mathbf{y}}_{\alpha=0}^{(t)} \right) \right\|_2^2 ;$$
    Calculate $\hat{\boldsymbol{\beta}}^{(t)}$ from (3) with $\alpha^{\star(t)}$;
end

---

229 Our results gives a theoretical explanation for why one should treat $\alpha^{(\tau)}$ as an adjustable hyperparam-
230 eter to fine-tune the amount of regularization that self-distillation impose for a particular problem, and
231 that it can be chosen in an optimal way for kernel ridge regression. In the following we provide an
232 illustrative example, and in Section 5 we estimate the optimal weighting parameter for deep learning
233 using an adaptation of Algorithm 1.

234 **4.5 Illustrative example**

235 Consider the training dataset $\mathcal{D}$ where $\mathcal{X} = \{0, 0.1, \dots, 0.9, 1\}$ and $\mathcal{Y} = \{\sin(2\pi x) + \varepsilon \mid x \in \mathcal{X}\}$,
236 and ε is sampled from a zero-mean Gaussian random variable with standard deviation 0.5. Let φ be
237 the Radial Basis Function kernel, i.e. $\kappa(\mathbf{x}_i, \mathbf{x}_j) = e^{-\gamma \|\mathbf{x}_i - \mathbf{x}_j\|_2^2}$, where we choose $\gamma = \frac{1}{80}$, and let
238 $\lambda = 0.2$ and consider the three cases; (*a*) $\alpha = 0$, (*b*) $\alpha = 0.25$, and (*c*) step-wise optimal $\alpha^{\star(\tau)}$.

(a) $\alpha = 0$ (b) $\alpha = 0.25$ (c) $\alpha^{\star(\tau)}$

Figure 2: Six steps of self-distillation with (a) zero limiting solution (dashed), (b) non-zero limiting
solution (dashed), and (c) optimal step-wise $\alpha^{\star(\tau)}$. Training examples are represented with $\times$.

239 As illustrated in Figure 2a for case (*a*), the regularization imposed by self-distillation initially improves
240 the quality of the solution, but eventually overregularize and the solutions underfit the data, and
241 will eventually converge to the zero-solution. Using $\alpha > 0$ (see Figure 2b), and more specifically
242 $\alpha = 0.25$, reduce the imposed regularization and increases the stability of the distillation procedure;
243 i.e. the solutions differ much less between each distillation step. This allows for a more dense
244 exploration of solutions during iterated distillation steps, where increasing α reduces the difference
245 between solutions from two consecutive steps, but also reduces the space of possible solutions as
246 the limit, $f(\cdot, \hat{\boldsymbol{\beta}}^{(\infty)})$, approaches the initial solution $f(\cdot, \hat{\boldsymbol{\beta}}^{(1)})$ quickly.[10] However, choosing the
247 step-wise optimal $\alpha^{\star(\tau)}$ yields minuscule changes to the solution for $\tau > 2$, and a single step of
248 distillation is effectively enough. Furthermore, for $\tau \geq 3$, all $\alpha^{\star(\tau)}$ are approximately equal, and the
249 distillation procedure has reached an equilibrium.[11]

---

[10]As expected by Theorem 4.5, we experience a fast convergence to the limit; usually less than 10 iterations
are sufficient to converge

[11]If we clip $\alpha^{\star(\tau)}$ to be in $[0, 1]$, the $\alpha^{\star(\tau)}$ converges at $\tau = 4$ rather than $\tau = 3$.

As expected from Lemma 4.2 and Theorem 4.3, Figure 3 verifies that both in case (*a*) and (*b*), the diagonal of $\mathbf{B}^{(\tau)}$ is decreasing in τ and the diagonal coordinates corresponding to smaller eigenvalues shrink faster than those corresponding to larger eigenvalues. Without loss of generality we can assume $d_1 < d_2 < \cdots < d_n$, and for $k = 1, \ldots n - 1$ and any $\tau \geq 1$ define $R_k^{(\tau)} \stackrel{\text{def}}{=} \frac{[\mathbf{B}^{(\tau)}]_{k+1,k+1}}{[\mathbf{B}^{(\tau)}]_{k,k}}$. We expect $R_k^{(\tau)}$ to be strictly increasing in τ for all k in case (*a*), but for case (*b*) we can make no such guarantee. Both of these properties are verified in Figure 4.

(a) $\alpha = 0$ (b) $\alpha = 0.25$ (c) $\alpha^{\star(\tau)}$

Figure 3: Diagonal of $\mathbf{B}^{(\tau)}$ for $\tau = 1, \ldots, 6$ associated with Figure 2. Note, the plots are overlaid, but since the diagonal of $\mathbf{B}^{(\tau)}$ decrease in τ, all values until convergence are visible. In (a) we expect and observe strictly decreasing values in τ for all indices, until collapsing at 0, but in (b) and (c) the values converge to a non-zero limit.

Finally, we observe that in case (*a*), the values of $\mathbf{B}^{(\tau)}$ shrink much faster than in case (*b*), and eventually collapse to all zeros, whereas the latter is nearly converged after six iterations. Furthermore, case (*a*) appear to obtain a more sparsified solution, as the smallest coordinates effectively diminishes, which is not true for case (*b*). Furthermore, when directly comparing solutions from both cases with similar quality of fit, the solutions obtained with $\alpha = 0$ usually has smaller coordinates in $\mathbf{B}^{(\tau)}$ than those obtained with larger values of α.

(a) $\alpha = 0$ (b) $\alpha = 0.25$ (c) $\alpha^{\star(\tau)}$

Figure 4: Ratios, $R_k^{(\tau)}$ of the ordered diagonal of $\mathbf{B}^{(\tau)}$ for all τ. In (a) we expect and observe strictly increasing values in τ for all k, but have no such guarantee in (b) or (c). The x-axis corresponds to indices $k = 1, \ldots, n - 1$.

5   Approximate Optimal Weighting Parameter for Deep Learning

The following experiment aim at empirically evaluating the theoretical analysis above in a simple deep learning setting. In (16) we find $\alpha^{\star(\tau)}$ on closed form when $f(\cdot, \hat{\boldsymbol{\beta}}^{(\tau)})$ is a (self-distilled) kernel ridge regression. No closed form solution can be found for neural networks, but recent results show that (very) wide neural networks can be seen as kernel ridge regression solutions with the neural tangent kernel (Jacot et al., 2018; Arora et al., 2019; Lee et al., 2019, 2020).

Thus, inspired by (7) we propose to estimate $\alpha^{\star(t)}$ for $t = 2, \ldots, \tau$, denoted by $\hat{\alpha}^{(t)}$, for a neural network trained with self-distillation using an adapted Algorithm 1. Let $f_{\text{nn}}(\cdot, \boldsymbol{\theta}) \in \mathbb{R}^p$ be a neural network with vector of weights $\boldsymbol{\theta}$, and recursively for $\tau \geq 1$ let $\hat{\boldsymbol{\theta}}^{(\tau)}$ be the weights solving

$$\underset{\theta}{\operatorname{argmin}} \frac{\alpha^{(\tau)}}{2} \left\| f_{\text{nn}}(\mathbf{X}, \boldsymbol{\theta}) - \mathbf{Y}^{(1)} \right\|_F^2 + \frac{1 - \alpha^{(\tau)}}{2} \left\| f_{\text{nn}}(\mathbf{X}, \boldsymbol{\theta}) - \mathbf{Y}^{(\tau-1)} \right\|_F^2 + \frac{\lambda}{2} \|\boldsymbol{\theta}\|_2^2, \quad (18)$$

271 with $\alpha^{(\tau)} = \hat{\alpha}^{(\tau)}$ and where $\mathbf{Y}^{(\tau)} \in \mathbb{R}^{n \times p}$.[12] Furthermore, let $\hat{\boldsymbol{\theta}}_{\alpha=0}^{(\tau)}$ be the weights associated with
272 minimizing (18) with $\alpha^{(\tau)} = 0$, and $\tilde{\mathbf{Y}}_{\alpha=0}^{(\tau)} \overset{\mathsf{def}}{=} f_{\mathrm{nn}}(\tilde{\mathbf{X}}, \hat{\boldsymbol{\theta}}_{\alpha=0}^{(\tau)})$ as well as $\tilde{\mathbf{Y}}^{(\tau)} \overset{\mathsf{def}}{=} f_{\mathrm{nn}}(\tilde{\mathbf{X}}, \hat{\boldsymbol{\theta}}^{(\tau)})$ be the
273 predictions on the validation input $\tilde{\mathbf{X}}$. Then, following Algorithm 1 with $\|\cdot\|_2$ replaced by $\|\cdot\|_F$, and
274 (18) rather than (1) we can calculate the estimates $\hat{\alpha}^{(t)}$. These estimates yield comparable predictive
275 performance to the best fixed $\alpha^{(\tau)}$ (found with time-consuming grid search), but only require one
276 additional model fit per distillation step; i.e. $2(\tau - 1) + 1$ fits compared to $g(\tau - 1) + 1$ for a grid
277 search over g values. See Figure 5 for results and supplementary material for experimental details.

5.1 Experiment

279 We perform self-distillation with ResNet-50 (He et al., 2016) networks on CIFAR-10 (Krizhevsky
280 and Hinton, 2009), with minor pre-processing and augmentations. The model is initialized randomly
281 at each step[13] and trained according to the above with either estimated optimal parameters, $\hat{\alpha}^{(\tau)}$, or
282 fixed α for all steps. We use the network weights from the last iteration of training at each distillation
283 step for the next step, irrespective of whether a better model occurred earlier in the training. Our
284 models are trained for a fixed 75 epochs and each experiment is repeated with 4 different random
285 seeds over 11 chains of distillation steps, corresponding to $\alpha \in \{0.0, 0.1, \ldots, 0.9\}$ and $\hat{\alpha}^{(\tau)}$, with
286 the first model initialized identically across all chains. The accuracy reported at the τ'th step is based
287 on comparing the training and validation predictions, $\mathbf{Y}^{(\tau)}$ and $f(\tilde{\mathbf{X}}, \hat{\boldsymbol{\beta}}^{(\tau)})$ with the original training
288 and validation targets; $\mathbf{Y}$ and $\tilde{\mathbf{Y}}$.

Figure 5: Training and validation accuracy for five distillation steps with ResNet-50 models on CIFAR-10. Comparing fixed $\alpha^{(t)}$ for $t = 2 \ldots, \tau$ and estimating optimal weight with $\hat{\alpha}^{(t)}$ at each step. The experiment is repeated four times and the mean (and max/min in shaded) is reported.

6 Conclusion

290 In this paper, we provided theoretical arguments for the importance of weighting the teacher outputs
291 with the ground-truth targets when performing self-distillation with kernel ridge regressions along
292 with a closed form solution for the optimal weighting parameter. We proved how the solution at any
293 (possibly infinite) distillation step can be calculated directly from the initial distillation step, and
294 that self-distillation for an infinite number of steps corresponds to a classical kernel ridge regression
295 solution with amplified regularization parameter. We showed both empirically and theoretically that
296 the weighting parameter α determines the amount of regularization imposed by self-distillation, and
297 empirically supported our results in a simple deep learning setting.

6.1 Future Research Directions

299 Interesting directions of future research are on rigorously connecting neural networks and kernel
300 methods in a knowledge distillation setting, extend to other objective functions than MSE as well as
301 including intermediate model statistics in the distillation procedure. Finally, a larger empirical study
302 of the connection between the choice of α and the degree of overfitting is interesting as well.

---

[12]We treat class labels as p-dimensional one-hot encoded vectors and use norm of the difference between the predicted class probabilities and the one-hot vectors.

[13]Note, we initialize the models equally across all α for one experiment, but alter the seed for initialization between experiments.

References

Abnar, S., Dehghani, M., and Zuidema, W. (2020). Transferring Inductive Biases through Knowledge Distillation. *arXiv preprint arXiv:2006.00555*.

Ahn, S., Hu, S. X., Damianou, A., Lawrence, N. D., and Dai, Z. (2019). Variational information distillation for knowledge transfer. *Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, 2019-June:9155–9163.

Anil, R., Pereyra, G., Passos, A., Ormandi, R., Dahl, G. E., and Hinton, G. E. (2018). Large scale distributed neural network training through online distillation. *6th International Conference on Learning Representations, ICLR 2018 - Conference Track Proceedings*, pages 1–12.

Arora, S., Du, S. S., Hu, W., Li, Z., Salakhutdinov, R., and Wang, R. (2019). On exact computation with an infinitely wide neural net. *Advances in Neural Information Processing Systems*, 32(NeurIPS).

Ba, L. J. and Caruana, R. (2014). Do Deep Nets Really Need to be Deep? *Advances in Neural Information Processing Systems*, 3(January):2654–2662.

Bucila, C., Caruana, R., and Niculescu-Mizil, A. (2006). Model Compression. In *Proceedings of the 12th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '06, pages 535–541, New York, NY, USA. ACM.

Chen, H., Wang, Y., Xu, C. C. C., Yang, Z., Liu, C., Shi, B., and Tian, Q. (2019). Data-free learning of student networks. In *Proceedings of the IEEE International Conference on Computer Vision*.

Dong, B., Hou, J., Lu, Y., and Zhang, Z. (2019). Distillation approximately early stopping? harvesting dark knowledge utilizing anisotropic information retrieval for overparameterized neural network.

Falcon, W. (2019). PyTorch Lightning.

Fang, G., Song, J., Shen, C., Wang, X., Chen, D., and Song, M. (2019). Data-Free Adversarial Distillation. *arXiv preprint arXiv:1912.11006*.

Furlanello, T., Lipton, Z. C., Tschannen, M., Itti, L., and Anandkumar, A. (2018). Born Again Neural Networks. In Dy, J. and Krause, A., editors, *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 1607–1616, Stockholmsmässan, Stockholm Sweden. PMLR.

Gao, M., Shen, Y., Li, Q., and Loy, C. C. (2020). Residual Knowledge Distillation. *arXiv preprint arXiv:2002.09168*.

Gotmare, A., Shirish Keskar, N., Xiong, C., and Socher, R. (2019). A closer look at deep learning heuristics: Learning rate restarts, warmup and distillation. In *7th International Conference on Learning Representations, ICLR 2019*.

He, K., Zhang, X., Ren, S., and Sun, J. (2016). Deep residual learning for image recognition. *Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, 2016-Decem:770–778.

Hinton, G., Vinyals, O., and Dean, J. (2015). Distilling the Knowledge in a Neural Network. *arXiv preprint arXiv:1503.02531*.

Hu, W., Li, Z., and Yu, D. (2019). Simple and Effective Regularization Methods for Training on Noisily Labeled Data with Generalization Guarantee. *8th International Conference on Learning Representations, ICLR 2020*.

Jacot, A., Gabriel, F., and Hongler, C. (2018). Neural tangent kernel: Convergence and generalization in neural networks. *Advances in Neural Information Processing Systems*, 2018-Decem(5):8571–8580.

Krizhevsky, A. and Hinton, G. (2009). Learning multiple layers of features from tiny images.

Lee, J., Xiao, L., Schoenholz, S. S., Novak, Y. B. R., Sohl-Dickstein, J., Pennington, J., Bahri, Y., Dec, M. L., and Brain, G. (2019). Wide Neural Networks of Any Depth Evolve as Linear Models Under Gradient Descent. *Advances in Neural Information Processing Systems*.

Lee, J. D., Shen, R., Song, Z., Wang, M., and Yu, Z. (2020). Generalized Leverage Score Sampling for Neural Networks. *arXiv preprint arXiv:2009.09829*.

Lopes, R. G., Fenu, S., and Starner, T. (2017). Data-Free Knowledge Distillation for Deep Neural Networks. *arXiv preprint arXiv:1710.07535*.

Micaelli, P. and Storkey, A. J. (2019). Zero-shot Knowledge Transfer via Adversarial Belief Matching. In Wallach, H., Larochelle, H., Beygelzimer, A., d\textquotesingle Alché-Buc, F., Fox, E., and Garnett, R., editors, *Advances in Neural Information Processing Systems*, volume 32, pages 9551–9561. Curran Associates, Inc.

Mobahi, H., Farajtabar, M., and Bartlett, P. L. (2020). Self-Distillation Amplifies Regularization in Hilbert Space. *Advances in Neural Information Processing Systems*.

Müller, R., Kornblith, S., and Hinton, G. (2019). When Does Label Smoothing Help? In *Advances in Neural Information Processing Systems*.

Nakkiran, P., Barak, B., Kaplun, G., Sutskever, I., Bansal, Y., Yang, T., Barak, B., and Sutskever, I. (2020). Deep Double Descent: Where Bigger Models and More Data Hurt. In *International Conference on Learning Representations*.

Nayak, G. K., Mopuri, K. R., Shaj, V., Babu, R. V., Chakraborty, A., Venkatesh Babu, R., and Chakraborty, A. (2019). Zero-shot knowledge distillation in deep networks. *36th International Conference on Machine Learning, ICML 2019*, 2019-June:8317–8325.

Park, W., Kim, D., Lu, Y., and Cho, M. (2019). Relational Knowledge Distillation. In *Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition*.

Phuong, M. and Lampert, C. H. (2019). Towards understanding knowledge distillation. *36th International Conference on Machine Learning, ICML 2019*, 2019-June(2014):8993–9007.

Radosavovic, I., Dollár, P., Girshick, R., Gkioxari, G., He, K., Dollar, P., Girshick, R., Gkioxari, G., and He, K. (2018). Data Distillation: Towards Omni-Supervised Learning. *Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, pages 4119–4128.

Romero, A., Ballas, N., Kahou, S. E., Chassang, A., Gatta, C., and Bengio, Y. (2015). FitNets: Hints for thin deep nets. *3rd International Conference on Learning Representations, ICLR 2015 - Conference Track Proceedings*, pages 1–13.

Schölkopf, B., Herbrich, R., and Smola, A. J. (2001). A generalized representer theorem. In *International conference on computational learning theory*, volume 2111, pages 416–426. Springer.

Srinivas, S. and Fleuret, F. F. (2018). Knowledge transfer with jacobian matching. *35th International Conference on Machine Learning, ICML 2018*, 11:7515–7523.

Tang, J., Shivanna, R., Zhao, Z., Lin, D., Singh, A., Chi, E. H., and Jain, S. (2020). Understanding and Improving Knowledge Distillation. *arXiv preprint arXiv:2002.03532*.

Tian, Y., Krishnan, D., and Isola, P. (2020a). Contrastive Representation Distillation. In *International Conference on Learning Representations*, pages 1–19.

Tian, Y., Wang, Y., Krishnan, D., Tenenbaum, J. B., and Isola, P. (2020b). Rethinking Few-Shot Image Classification: a Good Embedding Is All You Need?

Wang, L. and Yoon, K.-J. (2020). Knowledge Distillation and Student-Teacher Learning for Visual Intelligence: A Review and New Outlooks. *arXiv preprint arXiv:2004.05937*.

Yang, C., Xie, L., Qiao, S., and Yuille, A. (2018). Knowledge Distillation in Generations: More Tolerant Teachers Educate Better Students. *arXiv preprint arXiv:1805.05551*.

Yao, Y., Rosasco, L., and Caponnetto, A. (2007). On Early Stopping in Gradient Descent Learning. *Constructive Approximation*, 26(2):289–315.

Yim, J., Joo, D., Bae, J., and Kim, J. (2017). A Gift from Knowledge Distillation: Fast Optimization, Network Minimization and Transfer Learning. In *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 7130–7138.

Zagoruyko, S. and Komodakis, N. (2019). Paying more attention to attention: Improving the performance of convolutional neural networks via attention transfer. *5th International Conference on Learning Representations, ICLR 2017 - Conference Track Proceedings*, pages 1–13.

Zhang, C., Recht, B., Bengio, S., Hardt, M., and Vinyals, O. (2017). Understanding deep learning requires rethinking generalization. *5th International Conference on Learning Representations, ICLR 2017 - Conference Track Proceedings*.