IMAGE GANS MEET DIFFERENTIABLE RENDERING FOR INVERSE GRAPHICS AND INTERPRETABLE 3D NEURAL RENDERING

ABSTRACT

Differentiable rendering has paved the way to training neural networks to perform "inverse graphics" tasks such as predicting 3D geometry from monocular photographs. To train high performing models, most of the current approaches rely on multi-view imagery which are not readily available in practice. Recent Generative Adversarial Networks (GANs) that synthesize images, in contrast, seem to acquire 3D knowledge implicitly during training: object viewpoints can be manipulated by simply manipulating the latent codes. However, these latent codes often lack further physical interpretation and thus GANs cannot easily be inverted to perform explicit 3D reasoning. In this paper, we aim to extract and disentangle 3D knowledge learned by generative models by utilizing differentiable renderers. Key to our approach is to exploit GANs as a multi-view data generator to train an inverse graphics network using an off-the-shelf differentiable renderer, and the trained inverse graphics network as a teacher to disentangle the GAN's latent code into interpretable 3D properties. The entire architecture is trained iteratively using cycle consistency losses. We show that our approach significantly outperforms state-of-the-art inverse graphics networks trained on existing datasets, both quantitatively and via user studies. We further showcase the disentangled GAN as a controllable 3D "neural renderer", complementing traditional graphics renderers.

1 INTRODUCTION

The ability to infer 3D properties such as geometry, texture, material, and light from photographs is key in many domains such as AR/VR, robotics, architecture, and computer vision. Interest in this problem has been explosive, particularly in the past few years, as evidenced by a large body of published works and several released 3D libraries (TensorflowGraphics Valentin et al. (2019), Kaolin J. et al. (2019), PyTorch3D Ravi et al. (2020)).

The process of going from images to 3D is often called "inverse graphics", since the problem is inverse to the process of rendering in graphics in which a 3D scene is projected onto an image by taking into account the geometry and material properties of objects, and light sources present in the scene. Most work on inverse graphics assumes that 3D labels are available during training (Wang et al., 2018; Mescheder et al., 2019; Groueix et al., 2018; Wang et al., 2019; Choy et al., 2016), and trains a neural network to predict these labels. To ensure high quality 3D ground-truth, synthetic datasets such as ShapeNet (Chang et al., 2015) are typically used. However, models trained on synthetic datasets often struggle on real photographs due to the domain gap with synthetic imagery.

To circumvent these issues, recent work has explored an alternative way to train inverse graphics networks that sidesteps the need for 3D ground-truth during training. The main idea is to make graphics renderers differentiable which allows one to infer 3D properties directly from images using gradient based optimization, Kato et al. (2018); Liu et al. (2019b); Li et al. (2018); Chen et al. (2019). These methods employ a neural network to predict geometry, texture and light from images, by minimizing the difference between the input image with the image rendered from these properties. While impressive results have been obtained in Liu et al. (2019b); Sitzmann et al. (2019); Liu et al. (2019a); Henderson & Ferrari (2018); Chen et al. (2019); Yao et al. (2018); Kanazawa et al. (2018), most of these works still require some form of implicit 3D supervision such as multi-view images of the same object with known cameras. Thus, most results have been reported on the syn-

Figure 1: We employ two "renderers": a GAN (StyleGAN in our work), and a differentiable graphics renderer (DIB-R in our work). We exploit StyleGAN as a synthetic data generator, and we label this data extremely efficiently. This "dataset" is used to train an inverse graphics network that predicts 3D properties from images. We use this network to disentangle StyleGAN's latent code through a carefully designed mapping network.

thetic ShapeNet dataset, or the large-scale CUB (Welinder et al., 2010) bird dataset annotated with keypoints from which cameras can be accurately computed using structure-from-motion techniques.

On the other hand, generative models of images appear to learn 3D information implicitly, where several works have shown that manipulating the latent code can produce images of the same scene from a different viewpoint (Karras et al., 2019a). However, the learned latent space typically lacks physical interpretation and is usually not disentangled, where properties such as the 3D shape and color of the object often cannot be manipulated independently.

In this paper, we aim to extract and disentangle 3D knowledge learned by generative models by utilizing differentiable graphics renderers. We exploit a GAN, specifically StyleGAN (Karras et al., 2019a), as a generator of multi-view imagery to train an inverse graphics neural network using a differentiable renderer. In turn, we use the inverse graphics network to inform StyleGAN about the image formation process through the knowledge from graphics, effectively disentangling the GAN's latent space. We connect StyleGAN and the inverse graphics network into a single architecture which we iteratively train using cycle-consistency losses. We demonstrate our approach to significantly outperform inverse graphics networks on existing datasets, and showcase controllable 3D generation and manipulation of imagery using the disentangled generative model.

2 RELATED WORK

3D from 2D: Reconstructing 3D objects from 2D images is one of the mainstream problems in 3D computer vision. We here focus our review to single-image 3D reconstruction which is the domain of our work. Most of the existing approaches train neural networks to predict 3D shapes from images by utilizing 3D labels during training, Wang et al. (2018); Mescheder et al. (2019); Choy et al. (2016); Park et al. (2019). However, the need for 3D training data limits these methods to the use of synthetic datasets. When tested on real imagery there is a noticeable performance gap.

Newer works propose to differentiate through the traditional rendering process in the training loop of neural networks, Loper & Black (2014); Kato et al. (2018); Liu et al. (2019b); Chen et al. (2019); Petersen et al. (2019). Differentiable renderers allow one to infer 3D from 2D images without requiring 3D ground-truth. However, in order to make these methods work in practice, several additional losses are utilized in learning, such as the multi-view consistency loss whereby the cameras are assumed known. Impressive reconstruction results have been obtained on the synthetic ShapeNet dataset. While CMR by Kanazawa et al. (2018) and DIB-R by Chen et al. (2019) show real-image 3D reconstructions on CUB and Pascal3D (Xiang et al., 2014) datasets, they rely on manually annotated keypoints, while still failing to produce accurate results.

A few recent works, Wu et al. (2020); Li et al. (2020); Goel et al. (2020); Kato & Harada (2019), explore 3D reconstruction from 2D images in a completely unsupervised fashion. They recover both 3D shapes and camera viewpoints from 2D images by minimizing the difference between original and re-projected images with additional unsupervised constraints, e.g., semantic information (Li et al. (2020)), symmetry (Wu et al. (2020)), GAN loss (Kato & Harada (2019)) or viewpoint distribution (Goel et al. (2020)). Their reconstruction is typically limited to 2.5D (Wu et al. (2020)), and produces lower quality results than when additional supervision is used (Goel et al. (2020); Li et al. (2020); Kato & Harada (2019)). In contrast, we utilize GANs to generate multi-view realistic datasets that can be annotated *extremely efficiently*, which leads to accurate 3D results. Furthermore, our model achieves disentanglement in GANs and turns them into interpretable 3D neural renderers.

Neural Rendering with GANs: GANs (Goodfellow et al., 2014; Karras et al., 2019a) can be regarded as neural renderers, as they take a latent code as input and "render" an image. However, the latent code is sampled from a predefined prior and lacks interpretability. Several works generate images with conditions: a semantic mask (Zhu et al., 2017), scene layout Karacan et al. (2016), or a

Figure 2: We show examples of cars (first two rows) synthesized in chosen viewpoints (columns). To get these, we fix the latent code w_v^* that controls the viewpoint (one code per column) and randomly sample the remaining dimensions of (Style)GAN's latent code (to get rows). Notice how well aligned the two cars are in each column. In the third row we show the same approach applied to horse and bird StyleGAN.

caption (Reed et al., 2016), and manipulate the generated images by modifying the input condition. Despite tremendous progress in this direction, there is little work on generating images through an interpretable 3D physics process. Dosovitskiy et al. (2016) synthesizes images conditioned on object style, viewpoint, and color. Most relevant work to ours is Zhu et al. (2018), which utilizes a learnt 3D geometry prior and generates images with a given viewpoint and texture code. We differ in three important ways. First, we do not require a 3D dataset to train the 3D prior. Second, the texture in our model has 3D physical meaning, while Zhu et al. (2018) still samples from a prior. We further control background while Zhu et al. (2018) synthesizes objects onto white background.

Disentangling GANs: Learning disentangled representations has been widely explored, Lee et al. (2020); Lin et al. (2019); Perarnau et al. (2016). Representative work is InfoGAN Chen et al. (2016), which tries to maximize the mutual information between the prior and the generated image distribution. However, the disentangled code often still lacks physical interpretability. Tewari et al. (2020) transfers face rigging information from an existing model to control face attribute disentanglement in the StyleGAN latent space. Shen et al. (2020) aims to find the latent space vectors that correspond to meaningful edits, while Härkönen et al. (2020) exploits PCA to disentangle the latent space. In our work, we disentangle the latent space with knowledge from graphics.

3 OUR APPROACH

We start by providing an overview of our approach (Fig. 1), and describe the individual components in more detail in the following sections. Our approach marries two types of renderers: a GAN-based neural "renderer" and a differentiable graphics renderer. Specifically, we leverage the fact that the recent state-of-the-art GAN architecture StyleGAN by Karras et al. (2019a;b) learns to produce highly realistic images of objects, and allows for a reliable control over the camera. We manually select a few camera views with a rough viewpoint annotation, and use StyleGAN to generate a large number of examples per view, which we explain in Sec. 3.1. In Sec. 3.2, we exploit this dataset to train an inverse graphics network utilizing the state-of-the-art differentiable renderer, DIB-R by Chen et al. (2019) in our work, with a small modification that allows it to deal with noisy cameras during training. In Sec. 3.3, we employ the trained inverse graphics network to disentangle StyleGAN's latent code and turn StyleGAN into a 3D neural renderer, allowing for control over explicit 3D properties. We fine-tune the entire architecture, leading to significantly improved results.

3.1 STYLEGAN AS SYNTHETIC DATA GENERATOR

We first aim to utilize StyleGAN to generate multi-view imagery. StyleGAN is a 16 layer convolutional neural network that maps a latent code $z \in Z$ drawn from a normal distribution into a realistic image. The code z is first mapped to an intermediate latent code $w \in W$ which is transformed to $w^* = (w_1^*, w_2^*, ..., w_{16}^*) \in W^*$ through 16 learned affine transformations. We call W^* the transformed latent space to differentiate it from the intermediate latent space W. Transformed latent codes w^* are then injected as the style information to the StyleGAN Synthesis network.

Different layers control different image attributes. As observed in Karras et al. (2019a), styles in early layers adjust the camera viewpoint while styles in the intermediate and higher layers influence shape, texture and background. We provide a careful analysis of all layers in Appendix. We empirically find that the latent code $w_v^* := (w_1^*, w_2^*, w_3^*, w_4^*)$ in the first 4 layers controls camera viewpoints. That is, if we sample a new code w_v^* but keep the remaining dimensions of w^* fixed (which we call the conten code), we generate images of the same object depicted in a different viewpoint. Examples are shown in Fig. 2.

We further observe that a sampled code w_v^* in fact represents a fixed camera viewpoint. That is, if we keep w_v^* fixed but sample the remaining dimensions of w^*, StyleGAN produces imagery of different objects in the same camera viewpoint. This is shown in columns in Fig. 2. Notice how aligned the objects are in each of the viewpoints. This makes StyleGAN a *multi-view* data generator!

"StyleGAN" multi-view dataset: We manually select several views, which cover all the common viewpoints of an object ranging from 0-360 in azimuth and roughly 0-30 in elevation. We pay attention to choosing viewpoints in which the objects look most consistent. Since inverse graphics works require camera pose information, we annotate the chosen viewpoint codes with a rough absolute camera pose. To be specific, we classify each viewpoint code into one of 12 azimuth angles, uniformly sampled along $360 \deg$. We assign each code a fixed elevation ($0°$) and camera distance. These camera poses provide a very coarse annotation of the actual pose – the annotation serves as the initialization of the camera which we will optimize during training. This allows us to annotate all views (and thus the entire dataset) in **only 1 minute** – making annotation effort neglible. For each viewpoint, we sample a large number of content codes to synthesize different objects in these views. Fig. 2 shows 2 cars, and a horse and a bird. Appendix provides more examples.

Since DIB-R also utilizes segmentation masks during training, we further apply MaskRCNN by He et al. (2017) to get instance segmentation in our generated dataset. As StyleGAN sometimes generates unrealistic images or images with multiple objects, we filter out "bad" images which have more than one instance, or small masks (less than 10% of the whole image area).

3.2 TRAINING AN INVERSE GRAPHICS NEURAL NETWORK

Following CMR by Kanazawa et al. (2018), and DIB-R by Chen et al. (2019), we aim to train a 3D prediction network f, parameterized by θ, to infer 3D shapes (represented as meshes) along with textures from images. Let I_V denote an image in viewpoint V from our StyleGAN dataset, and M its corresponding object mask. The inverse graphics network makes a prediction as follows: $\{S, T\} = f_\theta(I_V)$, where S denotes the predicted shape, and T a texture map. Shape S is deformed from a sphere as in Chen et al. (2019). While DIB-R also supports prediction of lighting, we empirically found its performance is weak for realistic imagery and we thus omit lighting estimation in our work.

To train the network, we adopt DIB-R as the differentiable graphics renderer that takes $\{S, T\}$ and V as input and produces a rendered image $I'_V = r(S, T, V)$ along with a rendered mask M'. Following DIB-R, the loss function then takes the following form:

$$
\begin{aligned}
L(I, S, T, V; \theta) = & \lambda_{\text{col}} L_{\text{col}}(I, I') + \lambda_{\text{percpt}} L_{\text{pecept}}(I, I') + L_{\text{IOU}}(M, M') \\
& + \lambda_{\text{sm}} L_{\text{sm}}(S) + \lambda_{\text{lap}} L_{\text{lap}}(S) + \lambda_{\text{mov}} L_{\text{mov}}(S)
\end{aligned}
\tag{1}
$$

Here, L_{col} is the standard L_1 image reconstruction loss defined in the RGB color space while L_{percpt} is the perceptual loss that helps the predicted texture look more realistic. Note that rendered images do not have background, so L_{col} and L_{percept} are calculated by utilizing the mask. L_{IOU} computes the intersection-over-union between the ground-truth mask and the rendered mask. Regularization losses such as the Laplacian loss L_{lap} and flatten loss L_{sm} are commonly used to ensure that the shape is well behaved. Finally, L_{mov} regularizes the shape deformation to be uniform and small.

Since we also have access to multi-view images for each object we also include a multi-view consistency loss. In particular, our loss per object k is:

$$
\mathcal{L}_k(\theta) = \sum_{i,j,i \neq j} \left(L(I_{V_i^k}, S_k, T_k, V_i^k; \theta) + L(I_{V_j^k}, S_k, T_k, V_j^k; \theta) \right)
\tag{2}
$$

$$
\text{where } \{S_k, T_k, L_k\} = f_\theta(I_{V_i^k})
$$

While more views provide more constraints, empirically, two views have been proven sufficient. We randomly sample view pairs (i, j) for efficiency.

We use the above loss functions to jointly train the neural network f and optimize viewpoint cameras V (which were fixed in Chen et al. (2019)). We assume that different images generated from the same w_v^* correspond to the same viewpoint V. Optimizing the camera jointly with the weights of the network allows us to effectively deal with noisy initial camera annotations.

3.3 DISENTANGLING STYLEGAN WITH THE INVERSE GRAPHICS MODEL

The inverse graphics model allows us to infer a 3D mesh and texture from a given image. We now utilize these 3D properties to disentangle StyleGAN's latent space, and turn StyleGAN into a fully

Figure 3: A mapping network maps camera, shape, texture and background into a disentangled code that is passed to StyleGAN for "rendering". We refer to this network as StyleGAN-R.

controllable 3D neural renderer, which we refer to as StyleGAN-R. Note that StyleGAN in fact synthesizes more than just an object, it also produces the background, i.e., the entire scene. Ideally we want control over the background as well, allowing the neural renderer to render 3D objects into desired scenes. To get the background from a given image, we simply mask out the object.

We propose to learn a mapping network to map the viewpoint, shape (mesh), texture and background into the StyleGAN's latent code. Since StyleGAN may not be completely disentangled, we further fine-tune the entire StyleGAN model while keeping the inverse graphics network fixed.

Mapping Network: Our mapping network, visualized in Figure 3, maps the viewpoints to first 4 layers and maps the shape, texture and background to the last 12 layers of W^*. For simplicity, we denote the first 4 layers as W_V^* and the last 12 layers as W_{STB}^*, where $W_V^* \in \mathbb{R}^{2048}$ and $W_{STB}^* \in \mathbb{R}^{3008}$. Specifically, the mapping network g_v for viewpoint V and g_s for shape S are separate MLPs while g_t for texture T and g_b for background B are CNN layers:

$$\mathbf{z}^{\text{view}} = g_v(V; \theta_v), \ \mathbf{z}^{\text{shape}} = g_s(S; \theta_s), \mathbf{z}^{\text{txt}} = g_t(T; \theta_t), \ \mathbf{z}^{\text{bck}} = g_b(B; \theta_b), \tag{3}$$

where $\mathbf{z}^{\text{view}} \in \mathbb{R}^{2048}, \mathbf{z}^{\text{shape}}, \mathbf{z}^{\text{txt}}, \mathbf{z}^{\text{bck}} \in \mathbb{R}^{3008}$ and $\theta_v, \theta_s, \theta_t, \theta_b$ are network parameters. We softly combine the shape, texture and background codes into the final latent code as follows:

$$\tilde{w}^{mtb} = \mathbf{s}^{\text{m}} \odot \mathbf{z}^{\text{shape}} + \mathbf{s}^{\text{t}} \odot \mathbf{z}^{\text{txt}} + \mathbf{s}^{\text{b}} \odot \mathbf{z}^{\text{bck}}, \tag{4}$$

where $\odot$ denotes element-wise product, and $\mathbf{s}^{\text{m}}, \mathbf{s}^{\text{t}}, \mathbf{s}^{\text{b}} \in \mathbb{R}^{3008}$ are shared across all the samples. To achieve disentanglement, we want each dimension of the final code to be explained by only one property (shape, texture or background). We thus normalize each dimension of $\mathbf{s}$ using softmax.

In practice, we found that mapping V to a high dimensional code is challenging since our dataset only contains a limited number of views, and V is limited to azimuth, elevation and scale. We thus map V to the subset of W_V^*, where we empirically choose 144 of the 2048 dimensions with the highest correlation with the annotated viewpoints. Thus, $\mathbf{z}^{\text{view}} \in \mathbb{R}^{144}$ in our case.

Training Scheme: We train the mapping network and fine-tune StyleGAN in two separate stages. We first freeze StyleGAN's weights and train the mapping network only. This warms up the mapping network to output reasonable latent codes for StyleGAN. We then fine-tune both StyleGAN and the mapping network to better disentangle different attributes. We provide details next.

In the warm up stage, we sample viewpoint codes w_v^* among the chosen viewpoints, and sample the remaining dimensions of $w^* \in W^*$. We try to minimize the L_2 difference between the mapped code $\tilde{w}$ and StyleGAN's code w^*. To encourage the disentanglement in the latent space, we penalize the entropy of each dimension i of $\mathbf{s}$. Our overall loss function for our mapping network is:

$$L_{\text{mapnet}}(\theta_v, \theta_s, \theta_t, \theta_v) = ||\tilde{w} - w^*||_2 - \sum_i \sum_{k \in \{m,t,b\}} \mathbf{s}_i^k \log(\mathbf{s}_i^k). \tag{5}$$

By training the mapping network, we find that view, shape and texture can be disentangled in the original StyleGAN model but the background remains entangled. We thus fine-tune the model to get a better disentanglement. To fine-tune the StyleGAN network we incorporate a cycle consistency loss. In particular, by feeding a sampled shape, texture and background to StyleGAN we obtain a synthesized image. We encourage consistency between the original sampled properties and the shape, texture and background predicted from the StyleGAN-synthesized image via the inverse graphics network. We further feed the same background B with two different $\{S, T\}$ pairs to generate two images I_1 and I_2. We then encourage the re-synthesized backgrounds $\bar{B}_1$ and $\bar{B}_2$ to be similar. This loss tries to disentangle the background from the foreground object. During training, we find that imposing the consistency loss on B in image space results in blurry images, thus we constrain it in the code space. Our fine-tuning loss takes the following form:

$$L_{\text{stylegan}}(\theta_{\text{gan}}) = ||S - \bar{S}||_2 + ||T - \bar{T}||_2 + ||g_b(B) - g_b(\bar{B})||_2 + ||g_b(\bar{B}_1) - g_b(\bar{B}_2)||_2 \tag{6}$$

4 EXPERIMENTS

In this section, we showcase our approach on inverse graphics tasks (3D image reconstruction), as well as on the task of 3D neural rendering and 3D image manipulation.

Figure 4: **3D Reconstruction Results:** Given input images (1st column), we predict 3D shape, texture, and render them into the same viewpoint (2nd column). We also show renderings in 3 other views in remaining columns to showcase 3D quality. Our model is able to reconstruct cars with various shapes, textures and viewpoints. We also show the same approach on harder (articulated) objects, i.e., bird and horse.

Figure 5: **Comparison on Pascal3D test set:** We compare inverse graphics networks trained on Pascal3D and our StyleGAN dataset. Notice considerably higher quality of prediction when training on the StyleGAN dataset.

Our "StyleGAN" Dataset: We first randomly sample 6000 cars, 1000 hourse and 1000 birds with diverse shapes, textures, and backgrounds from StyleGAN. After filtering out images with bad masks as described in Sec. 3, 55429 cars, 16392 horses and 7948 birds images remain in our dataset which is significant larger than the Pascal3D car dataset (Xiang et al., 2014) (4175 car images). Note that nothing prevents us from synthesizing a significantly larger amount of data, but in practice, this amount turned out to be sufficient to train good models. We provide more examples in Appendix.

4.1 3D RECONSTRUCTION RESULTS

Training Details: Our DIB-R based inverse graphics model was trained with Adam (Kingma & Ba (2015)), with a learning rate of 1e-4. We set λ_{IOU}, λ_{col}, λ_{lap}, λ_{sm} and λ_{mov} to 3, 20, 5, 5, and 2.5, respectively. We first train the model with L_{col} loss for 3K iterations, and then fine-tune the model by adding L_{pecept} to make the texture more realistic. We set $\lambda_{percept}$ to 0.5. The model converges in 200K iterations with batch size 16. Training takes around 120 hours on four V100 GPUs.

Results: We show 3D reconstruction results in Fig. 4. Notice the quality of the predicted shapes and textures, and the diversity of the 3D car shapes we obtain. Our method also works well on more challenging (articulated) classes, e.g. horse and bird. We provide additional examples in Appendix.

Qualitative Comparison: To showcase our approach, we compare our inverse graphics network with exactly the same model but which we train on the Pascal3D car dataset. Pascal3D dataset has annotated keypoints, which we utilize to train the baseline model, termed as as Pascal3D-model. We show qualitative comparison on Pascal3D test set in Fig. 5. Note that the images from Pascal3D dataset are different from those our StyleGAN-model was trained on. Although the Pascal3D-model's prediction is visually good in the input image view, rendered predictions in other views are of noticeably lower quality than ours, which demonstrates that we recover 3D geometry and texture better than the baseline.

Quantitative Comparison: We evaluate the two networks in Table 1 for the car class. We report the estimated annotation time in Table. 1 (a) to showcase efficiency behind our StyleGAN dataset. It takes 3-5 minutes to annotate keypoints for one object, which we empirically verify. Thus, labeling Pascal3D required around 200-350 hours while ours takes only 1 minute to annotate a 10 times larger dataset. In Table 1 (b), we evaluate shape prediction quality by the re-projected 2D IOU score. Our

Dataset	Size	Annotation
Pascal3D	4K	200-350h
StyleGAN	**50K**	**1min**

(a) Dataset Comparison

Model	Pascal3D test	StyleGAN test
Pascal3D	**0.80**	0.81
Ours	0.76	**0.95**

(b) 2D IOU Evaluation

	Overall	Shape	Texture
Ours	**55.5%**	**63.1%**	**67.4%**
Pascal3D-model	23.8%	36.8%	25.9%
No Preference	20.5%	0%	16.5%

(c) User Study

Table 1: **(a):** We compare dataset size and annotation time of Pascal3D with our StyleGAN dataset. **(b):** We evaluate re-projected 2D IOU score of our StyleGAN-model vs the baseline Pascal3D-model on the two datasets. **(c):** We conduct a user study to judge the quality of 3D estimation.

| Input | DIBR-R | Stylegan-R | Input | DIBR-R | Stylegan-R |

Figure 6: **Dual Renderer:** Given input images (1st column), we first predict mesh and texture, and render them with the graphics renderer (2nd column), and our StyleGAN-R (3rd column).

model outperforms the Pascal3D-model on the SyleGAN test set while Pascal3D-model is better on the Pascal test set. This is not surprising since there is a domain gap between two datasets and thus each one performs best on their own test set. Note that this metric only evaluates quality of the prediction in input view and thus not reflect the actual quality of the predicted 3D shape/texture.

To analyze the quality of 3D prediction, we conduct an AMT user study on the **Pascal3D test set** which contains 220 images. We provide users with the input image and predictions rendered in 6 views (shown in Fig. 5, right) for both models. We ask them to choose the model with a more realistic shape and texture prediction that matches the input object. We provide details of the study in the Appendix. We report results in Table. 1 (c). Users show significant preference of our results versus the baseline, which confirms that the quality of our 3D estimation.

4.2 DUAL RENDERERS

Training Details: We train StyleGAN-R using Adam with learning rate of 1e-5 and batch size 16. Warmup stage takes 700 iterations, and we perform joint fine-tuning for another 2500 iterations.

With the provided input image, we first predict mesh and texture using the trained inverse graphics model, and then feed these 3D properties into StyleGAN-R to generate a new image. For comparison, we feed the same 3D properties to the DIB-R graphics renderer (which is the OpenGL renderer). Results are provided in Fig. 6. Note that DIB-R can only render the predicted object, while StyleGAN-R also has the ability to render the object into a desired background. We find that StyleGAN-R produces relatively consistent images compared to the input image. Shape and texture are well preserved, while only the background has a slight content shift.

4.3 3D IMAGE MANIPULATION WITH STYLEGAN-R

We test our approach in manipulating StyleGAN-synthesized images from our test set and real images. Specifically, given an input image, we predict 3D properties using the inverse graphics network, and extract background by masking out the object with Mask-RCNN. We then manipulate and feed these properties to StyleGAN-R to synthesize new views.

Controlling Viewpoints: We first freeze shape, texture and background, and change the camera viewpoint. Example is shown in Fig. 8. We obtain meaningful results, particularly for shape and texture. For comparison, an alternative way that has been explored in literature is to directly optimize the GAN's latent code (in our case the original StyleGAN's code) via an L2 image reconstruction loss. Results are shown in the last three columns in Fig. 7. As also observed in Abdal et al. (2019), this approach fails to generate plausible images, showcasing the importance of the mapping network and fine-tuning the entire architecture with 3D inverse graphics network in the loop.

Controlling Shape, Texture and Background: We further aim to manipulate 3D properties, while keeping the camera viewpoint fixed. In the second column of Fig 9, we replace the shapes of all cars to one chosen shape (red box) and perform neural rendering using StyleGAN-R. We successfully swap the shape of the car while maintaining other properties. We are able to modify tiny parts of the car, such as trunk and headlights. We do the same experiment but swapping texture and background in the third and forth column of Fig 9. We notice that swapping textures also slightly modifies the background, pointing that further improvements are possible in disentangling the two.

Figure 7: **Latent code manipulation:** Given an input image (col 1), we predict 3D properties and synthesize a new image with StyleGAN-R, by manipulating the viewpoint (col 2, 3, 4). Alternatively, we directly optimize the (original) StyleGAN latent code w.r.t. image, however this leads to a blurry reconstruction (col 5). Moreover, when we try to adjust the style for the optimized code, we get low quality results (col 6, 7).

Figure 8: **Camera Controller:** We manipulate azimuth, scale, elevation parameters with StyleGAN-R to synthesize images in new viewpoints while keeping content code fixed.

Figure 9: **3D Manipulation:** We sample 3 cars in column 1. We replace the shape of all cars with the shape of Car 1 (red box) in 2nd column. We transfer texture of Car 2 (green box) to other cars (3rd col). In last column, we paste background of Car 3 (cyan box) to the other cars. Examples indicated with boxes are unchanged. Zoom in to see details.

Figure 10: **Real Image Manipulation:** Given input images (1st col), we predict 3D properties and use our StyleGAN-R to render them back (2nd col). We swap out shape, texture & background in cols 3-5.

Real Image Editing: As shown in Fig. 10, our framework also works well when provided with real images, since StyleGAN's images, which we use in training, are quite realistic.

4.4 LIMITATIONS

While recovering faithful 3D gemetry and texture, our model fails to predict correct lighting model, since real images and StyleGAN generated images contain advanced lighting effects such as reflection, transparency and shadows and our spherical harmonic lighting model is incapable to deal with it. And we only partly succeed at disentangling the background, as we could observe slighly change in the background in Fig. 6, Fig. 9 and Fig. 10 We leave further improvements to future work.

5 CONCLUSION

In this paper, we introduced a new powerful architecture that links two renderers: a state-of-the-art image synthesis network and a differentiable graphics renderer. The image synthesis network generates training data for an inverse graphics network. In turn, the inverse graphics network teaches the synthesis network about the physical 3D controls. We showcased our approach to obtain significantly higher quality 3D reconstruction results while requiring 10000 less annotation effort than standard datasets. We also provided 3D neural rendering and image manipulation results demonstrating the effectiveness of our approach.

REFERENCES

Rameen Abdal, Yipeng Qin, and Peter Wonka. Image2stylegan: How to embed images into the stylegan latent space? *CoRR*, abs/1904.03189, 2019. URL http://arxiv.org/abs/1904.03189.

Angel X Chang, Thomas Funkhouser, Leonidas Guibas, Pat Hanrahan, Qixing Huang, Zimo Li, Silvio Savarese, Manolis Savva, Shuran Song, Hao Su, et al. Shapenet: An information-rich 3d model repository. *arXiv preprint arXiv:1512.03012*, 2015.

Wenzheng Chen, Jun Gao, Huan Ling, Edward Smith, Jaakko Lehtinen, Alec Jacobson, and Sanja Fidler. Learning to predict 3d objects with an interpolation-based differentiable renderer. In *Advances In Neural Information Processing Systems*, 2019.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. In *Advances in neural information processing systems*, pp. 2172–2180, 2016.

Christopher B Choy, Danfei Xu, JunYoung Gwak, Kevin Chen, and Silvio Savarese. 3d-r2n2: A unified approach for single and multi-view 3d object reconstruction. In *ECCV*, 2016.

Alexey Dosovitskiy, Jost Tobias Springenberg, Maxim Tatarchenko, and Thomas Brox. Learning to generate chairs, tables and cars with convolutional networks. *IEEE transactions on pattern analysis and machine intelligence*, 39(4):692–705, 2016.

Shubham Goel, Angjoo Kanazawa, , and Jitendra Malik. Shape and viewpoints without keypoints. In *ECCV*, 2020.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In Z. Ghahramani, M. Welling, C. Cortes, N. D. Lawrence, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 27*, pp. 2672–2680. Curran Associates, Inc., 2014. URL http://papers.nips.cc/paper/5423-generative-adversarial-nets.pdf.

Thibault Groueix, Matthew Fisher, Vladimir G. Kim, Bryan Russell, and Mathieu Aubry. AtlasNet: A Papier-Mâché Approach to Learning 3D Surface Generation. In *Proceedings IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2018.

Erik Härkönen, Aaron Hertzmann, Jaakko Lehtinen, and Sylvain Paris. Ganspace: Discovering interpretable gan controls. *arXiv preprint arXiv:2004.02546*, 2020.

Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross B. Girshick. Mask R-CNN. *CoRR*, abs/1703.06870, 2017. URL http://arxiv.org/abs/1703.06870.

Paul Henderson and Vittorio Ferrari. Learning to generate and reconstruct 3d meshes with only 2d supervision. *arXiv preprint arXiv:1807.09259*, 2018.

Krishna Murthy J., Edward Smith, Jean-Francois Lafleche, Clement Fuji Tsang, Artem Rozantsev, Wenzheng Chen, Tommy Xiang, Rev Lebaredian, and Sanja Fidler. Kaolin: A pytorch library for accelerating 3d deep learning research. *arXiv:1911.05063*, 2019.

Angjoo Kanazawa, Shubham Tulsiani, Alexei A Efros, and Jitendra Malik. Learning category-specific mesh reconstruction from image collections. In *ECCV*, pp. 371–386, 2018.

Levent Karacan, Zeynep Akata, Aykut Erdem, and Erkut Erdem. Learning to generate images of outdoor scenes from attributes and semantic layouts. *arXiv preprint arXiv:1612.00215*, 2016.

Tero Karras, Samuli Laine, and Timo Aila. A style-based generator architecture for generative adversarial networks. In *CVPR*, 2019a.

Tero Karras, Samuli Laine, Miika Aittala, Janne Hellsten, Jaakko Lehtinen, and Timo Aila. Analyzing and improving the image quality of StyleGAN. *CoRR*, abs/1912.04958, 2019b.

Hiroharu Kato and Tatsuya Harada. Self-supervised learning of 3d objects from natural images, 2019.

Hiroharu Kato, Yoshitaka Ushiku, and Tatsuya Harada. Neural 3d mesh renderer. In *CVPR*, 2018.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In Yoshua Bengio and Yann LeCun (eds.), *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. URL `http://arxiv.org/abs/1412.6980`.

Wonkwang Lee, Donggyun Kim, Seunghoon Hong, and Honglak Lee. High-fidelity synthesis with disentangled representation. *arXiv preprint arXiv:2001.04296*, 2020.

Tzu-Mao Li, Miika Aittala, Frédo Durand, and Jaakko Lehtinen. Differentiable monte carlo ray tracing through edge sampling. In *SIGGRAPH Asia 2018 Technical Papers*, pp. 222. ACM, 2018.

Xueting Li, Sifei Liu, Kihwan Kim, Shalini De Mello, Varun Jampani, Ming-Hsuan Yang, and Jan Kautz. Self-supervised single-view 3d reconstruction via semantic consistency. In *ECCV*, 2020.

Zinan Lin, Kiran Koshy Thekumparampil, Giulia Fanti, and Sewoong Oh. Infogan-cr: Disentangling generative adversarial networks with contrastive regularizers. *arXiv preprint arXiv:1906.06034*, 2019.

Hsueh-Ti Derek Liu, Michael Tao, Chun-Liang Li, Derek Nowrouzezahrai, and Alec Jacobson. Beyond pixel norm-balls: Parametric adversaries using an analytically differentiable renderer. In *ICLR*, 2019a.

Shichen Liu, Tianye Li, Weikai Chen, and Hao Li. Soft rasterizer: A differentiable renderer for image-based 3d reasoning. *ICCV*, 2019b.

Matthew M. Loper and Michael J. Black. Opendr: An approximate differentiable renderer. In David J. Fleet, Tomás Pajdla, Bernt Schiele, and Tinne Tuytelaars (eds.), *Computer Vision - ECCV 2014 - 13th European Conference, Zurich, Switzerland, September 6-12, 2014, Proceedings, Part VII*, volume 8695 of *Lecture Notes in Computer Science*, pp. 154–169. Springer, 2014. doi: 10.1007/978-3-319-10584-0_11. URL `https://doi.org/10.1007/978-3-319-10584-0_11`.

Lars Mescheder, Michael Oechsle, Michael Niemeyer, Sebastian Nowozin, and Andreas Geiger. Occupancy networks: Learning 3d reconstruction in function space. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4460–4470, 2019.

Jeong Joon Park, Peter Florence, Julian Straub, Richard Newcombe, and Steven Lovegrove. Deepsdf: Learning continuous signed distance functions for shape representation. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

Guim Perarnau, Joost Van De Weijer, Bogdan Raducanu, and Jose M Álvarez. Invertible conditional gans for image editing. *arXiv preprint arXiv:1611.06355*, 2016.

Felix Petersen, Amit H. Bermano, Oliver Deussen, and Daniel Cohen-Or. Pix2vex: Image-to-geometry reconstruction using a smooth differentiable renderer. *CoRR*, abs/1903.11149, 2019. URL `http://arxiv.org/abs/1903.11149`.

Nikhila Ravi, Jeremy Reizenstein, David Novotny, Taylor Gordon, Wan-Yen Lo, Justin Johnson, and Georgia Gkioxari. Pytorch3d. `https://github.com/facebookresearch/pytorch3d`, 2020.

Scott Reed, Zeynep Akata, Xinchen Yan, Lajanugen Logeswaran, Bernt Schiele, and Honglak Lee. Generative adversarial text to image synthesis. *arXiv preprint arXiv:1605.05396*, 2016.

Yujun Shen, Ceyuan Yang, Xiaoou Tang, and Bolei Zhou. Interfacegan: Interpreting the disentangled face representation learned by gans. *arXiv preprint arXiv:2005.09635*, 2020.

Vincent Sitzmann, Michael Zollhöfer, and Gordon Wetzstein. Scene representation networks: Continuous 3d-structure-aware neural scene representations. In *Advances in Neural Information Processing Systems*, 2019.

Ayush Tewari, Mohamed Elgharib, Gaurav Bharaj, Florian Bernard, Hans-Peter Seidel, Patrick Pérez, Michael Zöllhofer, and Christian Theobalt. Stylerig: Rigging stylegan for 3d control over portrait images, cvpr 2020. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*. IEEE, june 2020.

Julien Valentin, Cem Keskin, Pavel Pidlypenskyi, Ameesh Makadia, Avneesh Sud, and Sofien Bouaziz. Tensorflow graphics: Computer graphics meets deep learning. 2019.

G. Van Horn, S. Branson, R. Farrell, S. Haber, J. Barry, P. Ipeirotis, P. Perona, and S. Belongie. Building a bird recognition app and large scale dataset with citizen scientists: The fine print in fine-grained dataset collection. In *2015 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 595–604, 2015.

Nanyang Wang, Yinda Zhang, Zhuwen Li, Yanwei Fu, Wei Liu, and Yu-Gang Jiang. Pixel2mesh: Generating 3d mesh models from single rgb images. In *ECCV*, 2018.

Weiyue Wang, Xu Qiangeng, Duygu Ceylan, Radomir Mech, and Ulrich Neumann. Disn: Deep implicit surface network for high-quality single-view 3d reconstruction. *arXiv preprint arXiv:1905.10711*, 2019.

P. Welinder, S. Branson, T. Mita, C. Wah, F. Schroff, S. Belongie, and P. Perona. Caltech-UCSD Birds 200. Technical Report CNS-TR-2010-001, California Institute of Technology, 2010.

Shangzhe Wu, Christian Rupprecht, and Andrea Vedaldi. Unsupervised learning of probably symmetric deformable 3d objects from images in the wild. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.

Yu Xiang, Roozbeh Mottaghi, and Silvio Savarese. Beyond pascal: A benchmark for 3d object detection in the wild. In *IEEE Winter Conference on Applications of Computer Vision (WACV)*, 2014.

Shunyu Yao, Tzu Ming Hsu, Jun-Yan Zhu, Jiajun Wu, Antonio Torralba, Bill Freeman, and Josh Tenenbaum. 3d-aware scene manipulation via inverse graphics. In *Advances in neural information processing systems*, pp. 1887–1898, 2018.

Jun-Yan Zhu, Taesung Park, Phillip Isola, and Alexei A Efros. Unpaired image-to-image translation using cycle-consistent adversarial networks. In *Proceedings of the IEEE international conference on computer vision*, pp. 2223–2232, 2017.

Jun-Yan Zhu, Zhoutong Zhang, Chengkai Zhang, Jiajun Wu, Antonio Torralba, Josh Tenenbaum, and Bill Freeman. Visual object networks: Image generation with disentangled 3d representations. In *Advances in neural information processing systems*, pp. 118–129, 2018.

Figure A: **Layer Visualization for Each Block.**

APPENDIX

A OVERVIEW

In the Appendix, we first show feature visualization of StyleGAN layers in Sec. B. We then provide a detailed explanation of our StyleGAN dataset creation in Sec. C, including examples of the generated images and selected viewpoints. Next, we do a systematic analysis of our camera initialization method in Sec. D. Finally, we show more results on 3D inverse graphics task in Sec. E, more details of user study in Sec. F, more examples of StyleGAN disentanglement in Sec. G, with ablation studies and limitaion in Sec. H and Sec. I, respectively.

B STYLEGAN LAYERS VISUALIZATION

The official StyleGAN code repository provides models of different object categories at different resolution. Here we take the 512×384 car model as the example. This model contains 16 layers, where every two consecutive layers form a block. Each block has a different number of channels. In the last block, the model produces a 32-channel feature map at a 512x384 resolution. Finally, a learned RGB transformation function is applied to convert the feature map into an RGB image.

We visualize the feature map for each block via the learned RGB transformation function. Specifically, for the feature map in each block with the size of $h \times w \times c$, we first sum along the feature dimension, forming a $h \times w \times 1$ tensor. We then repeat the feature 32 times and generate a $h \times w \times 32$ new feature map. This allows us to keep the information of all the channels and directly apply the RGB transformation function in the last block to convert it to the RGB image.

As shown in Figure A, we find that blocks 1 and 2 do not exhibit interpretable structure while the car shape starts to appear in blocks 3, 4 and 5. We can observe that there is a rough car contour in block 4 which further becomes clear in block 5. From blocks 6 to 8, the car's shape becomes increasingly finer and background scene also appears. This supports some of our findings, i.e., the viewpoint is controlled in block 1 and 2 (first 4 layers) while shape, texture, and background exist in the last 12 layers.

While we take car model as the example, we find this property also true for other categories, e.g. horse and bird. We use the official horse model from StyleGAN2 (Karras et al., 2019b) repo and train a StyleGAN bird model by NABirds (Van Horn et al., 2015) dataset.

C DATASET

We show more examples from our generated dataset in Fig. B, Fig. C and Fig. D to show car, horse and bird, respectively. Our dataset contains objects with various shapes, textures and viewpoints. In particular, for the car dataset in Fig. B, one can notice a diverse variants of car types (SUV, Sports car, Jeep, etc) ranging from old to modern styles. We find that StyleGAN can also produce rare car shapes like truck or bus, but with a lower probability.

Figure B: **Car Dataset Overview:** Our StyleGAN-generated dataset contains cars with various shapes, textures and viewpoints

Figure C: **Horse Dataset Overview:** Our StyleGAN-generated dataset contains horses with various shapes, textures and viewpoints.

Figure D: **Bird Dataset Overview:** Our StyleGAN-generated dataset contains birds with various shapes, textures and viewpoints

Figure E: **All Viewpoints:** We show an examples of a car, bird and a horse synthesized in all our chosen viewpoints. While shape and texture are not perfectly consistent across views, they are sufficiently accurate to produce good 3D models in our downstream tasks. Horses and birds are especially challenging due to articulation. One can notice small changes in articulation across viewpoints.

We further visualize all of our selected viewpoints in our dataset in Fig. E. Our car training dataset contains 39 viewpoints. For the horse and bird datasets, we choose 22 and 8 views, respectively. We find these views are enough to learn reasonable 3D models. Note that for articulated objects such as horse and bird, StyleGAN does not perfectly preserve the articulation in different viewpoints, which leads to challenges in training high accuracy models using multi-view consistency loss. We leave further investigation in articulated objects to future work.

D CAMERA INITIALIZATION

Inverse graphics tasks require camera pose information, which is challenging to acquire for real imagery. It is generally obtained by annotating keypoints for each object and running structure-from-motion (SFM) techniques Welinder et al. (2010); Xiang et al. (2014). Keypoint annotation is time consuming – requiring roughly 3-5minutes per object. In our work, we utilize StyleGAN

Table A: **Comparison of Different Camera Initialization** The first table shows annotation and training time of $view$-model and $keypoint$-model. $view$-model takes much less time to annotate and performance the same as $keypoint$-model. The second table shows the difference of converged camera parameters of two methods. They almost converge to the same camera positions, which further demonstrate the effectiveness of $view$-model.

Method	Annotation	Training	2D IOU		Quaternion	Mean	Max
$keypoint$	3-4h	60 h	0.953		q_{xyz}	1.43°	2.95°
$view$	1min	60 h	0.952		q_w	0.42°	1.11°
(a) Time & Performance					(b) Converged Camera Difference		

to significantly reduce annotation effort since samples with the same w_v^* share the same viewpoint. Therefore, we only need to annotate 39, 22 and 8 views for car, horse and bird, respectively.

Furthermore, instead of accurately annotating keypoints and running SFM, we annotate each view with a rough absolute camera pose (which we further optimize during training). To be specific, we first select 12 azimuth angles: [0°, 30°, 60°, 90°, 120°, 150°, 180°, 210°, 240°, 270°, 300°, 330°]. Given a StyleGAN viewpoint, we manually classify which azimuth angle it is close to and assign it to the corresponding label with fixed elevation(0°) and camera distance. This allows us to annotate all the views (and thus entire dataset) in only *1 minute*, without any keypoint annotation.

To demonstrate the effectiveness of our camera initialization, we make a comparison with another inverse graphics network trained with *accurate* SFM camera initialization. Such initialization is done by manually annotating keypoints for all views of one car example, which takes about 3-4 hours (around 200 minutes, 39 views). We refer to the two models as $view$-model and $keypoint$-model, respectively.

We quantitatively evaluate two initialization methods in Table. A. We first compare the annotation time and training time. While it takes the same amount of time to train, $view$-model saves more annotation time. The performance of two methods are comparable with almost the same 2D IOU re-projection score on StyleGAN testing set. Moreover, the two camera systems converge to the same position. We evaluate by converting all the views into quaternions and compare the difference between the rotation axes and rotation angles. Among all views, the average difference of the rotation axes is only 1.43° and the rotation angle is 0.42°. The maximum difference of the rotation axes is only 2.95° and the rotation angle is 1.11°.

We further qualitatively compare two methods in Fig. F, showing that the two methods perform almost the same. Both of qualitative and quantitative comparison have demonstrated $view$-camera initialization is enough in training inverse graphics networks and no additional annotation is required.

| | Input | Pred. | Multiple Views for the Predicted Shape and Texture |

Figure F: **Comparison of Different Camera Initialization** The first row shows the prediction from $keypoint$-Initialization (cameras computed by running SFM on annotated keypoints) and the second row is from $view$-Initialization (cameras are coarsely annotated into 12 view bins). Note how close the two predictions are.

E   3D INFERENCE

We here present additional 3D prediction results and compare our model, which is trained on our StyleGAN generated dataset (StyleGAN-model), with the one trained on Pascal 3D dataset (Xiang et al., 2014) (PASCAL-model). We qualitatively compare two models on the Pascal3D test set in Fig. G and web imagery in Fig. H. Our StyleGAN-model produces better shape and texture predictions in all testing datasets, especially visible at different views of the object. We also present additional 3D prediction results on horses and cars in Fig. I.

Input   Pred.   Multiple Views

Figure G: **Comparison on PASCAL3D imagery:** We compare PASCAL-model with StyleGAN-model on PASCAL3D test set. While the predictions from both models are visually good in the corresponding image view, the prediction from StyleGAN-model have much better shapes and textures as observed in other views.

Input   Pred. Multiple Views

Figure H: **Comparison on Images from the Web:** We compare the PASCAL-model with our StyleGAN-model on images downloaded from the web. While the predictions from both models are visually good in the corresponding image view, the prediction from StyleGAN-model have much better shapes and textures as observed in other views.

Input   Pred.   Multiple Views for the predicted shape and texture

Figure I: **3D Reconstruction Results for Car, Horse and Bird** We show more car, horse and bird examples tested in StyleGAN testsets

F   USER STUDY

We report user study details in this section. We provide users (AMT turkers) with the input image and predictions rendered in 6 views. We ask users to choose more realistic shape and texture prediction. For each image in the test set we asked three annotators perform evaluation, which results in 660 examples in total. Altogether, 65 annotators participated in our user study. We show our AMT interface in Fig. J.

G   STYLEGAN-R DISENTANGLEMENT

Given an input image, we infer 3D properties of an object (shape, texture, background) using our inverse graphics network, but can also map these properties back to the latent code and use our StyleGAN-R to synthesize a new image. We show the results in Fig. K. Similar to Fig. 8 in the main paper, we show DIB-R-rendered predictions and neural rendering StyleGAN-R's predictions, and manipulate their viewpoints in rows (1, 4) and (2, 5). We further show "neural rendering" results from the original StyleGAN in row (3, 6), where we only learn the mapping network but keep the StyleGAN's weights fixed. We find that fine-tuning is necessary and StyleGAN-R produces more consistent shape, texture and background.

Real Image Editting: We show additional real image editing examples in Fig. L. With our StyleGAN-R, we can easily change the car's size, azimuth and elevation and synthesize a new image while preserving the shape and texture of the car with a consistent background.

H   ABLATION STUDIES

We find that the multi-view consistency loss and perceptual loss play an import role in our training, as shown in Fig. M. Multi-view consistency loss helps to generate a good model in all views while the perceptual loss helps to keep texture more realistic.

I   LIMITATIONS

As mentioned in the paper, our simple spherical harmonic model fails to separate light from textures. We show several examples in Fig.N. We leave this for future work.

Instruction

An artificial intelligence agent is looking at the photo and it's trying to guess how the object looks from different angles (six images on the right). The agent is making two different guesses, presented under trial 1 and trial 2. Please choose which trial is better, that is, in which trial the shape and the colors of the car in different angles are more representative of the object presented in the photo.

the shape of the object (the first row of each trial) is better in:

○ **Trial 1**

○ **Trial 2**

○ **No preference**

the colors (the second row of each trial) of the object is better in:

○ **Trial 1**

○ **Trial 2**

○ **No preference**

overall, the best guess is:

○ **Trial 1**

○ **Trial 2**

○ **No preference**

Back **4 / 5** Next

Submit

Figure J: **User Study Interface**: Predictions are rendered in 6 views and we ask users to choose more realistic shape, texture prediction and overall preference.

Input   Pred.   Multple Views

Figure K: **Dual Rendering:** Given the input image, we show the DIB-R-rendered predictions in row (1, 4) and StyleGAN-R' results in row (2, 5). We further shows the neural rendering results from the original StyleGAN model, where we only learn the mapping network but keep the StyleGAN weights fixed. Clearly, after fine-tuning, StyleGAN-R produces more consistent results.

Figure L: **Real Image Editing.** Given an input image (column 1), we use our inverse graphics network to predict the 3D properties and apply StyleGAN-R to re-render these (column 2, 3). We manipulate the car size/scale (row 1-3), azimuth (row 4-6) and elevation (Row 7-9).

Input   Pred.   Texture   Pred. Multiple Views

Figure M: **Ablation Study:** We ablate multi-view consistency and perceptual loss and show results of 3D predictions. Clearly, the texture becomes worse in the invisible part if we remove the multi-view consistency loss (rows 2, 5, noted by "w.o M. V.", which means no multi-view consistency.). Moreover, the textures become quite smooth and lose most details if we do not use the perceptual loss (rows 3, 6, noted by "w.o P.", which means no perceptual loss).

Input   w. Light   w.o. Light   Input   w. Light   w.o. Light

Figure N: **Light prediction:** Given the input image, we show DIB-R rendering results with light (columns 2, 5) and DIB-R rendering results with just textures (columns 3, 6). We find that the two images are quite similar, which indicates that we did not learn a good predictor for lighting. Moreover, we find that high order lighting, such as reflection, high-specular light are merged into texture, as shown in the second row. We aim to resolve this limitation in future work.