First is Better Than Last for Language Data Influence

Chih-Kuan Yeh [*]
Google Inc.
chihkuanyeh@google.com

Ankur Taly
Google Inc.
ataly@google.com

Mukund Sundararajan
Google Inc.
mukunds@google.com

Frederick Liu
Google Inc.
frederickliu@google.com

Pradeep Ravikumar
Carnegie Mellon University
Department of Machine Learning
pradeepr@cs.cmu.edu

Abstract

The ability to identify influential training examples enables us to debug training data and explain model behavior. Existing techniques to do so are based on the flow of training data influence through the model parameters (Koh & Liang, 2017; Yeh et al., 2018; Pruthi et al., 2020). For large models in NLP applications, it is often computationally infeasible to study this flow through *all* model parameters, therefore techniques usually pick the last layer of weights. However, we observe that since the activation connected to the last layer of weights contains "shared logic", the data influenced calculated via the last layer weights prone to a "cancellation effect", where the data influence of different examples have large magnitude that contradicts each other. The cancellation effect lowers the discriminative power of the influence score, and deleting influential examples according to this measure often does not change the model's behavior by much. To mitigate this, we propose a technique called TracIn-WE that modifies a method called TracIn (Pruthi et al., 2020) to operate on the word embedding layer instead of the last layer, where the cancellation effect is less severe. One potential concern is that influence based on the word embedding layer may not encode sufficient high level information. However, we find that gradients (unlike embeddings) do not suffer from this, possibly because they chain through higher layers. We show that TracIn-WE significantly outperforms other data influence methods applied on the last layer significantly on the case deletion evaluation on three language classification tasks for different models. In addition, TracIn-WE can produce scores not just at the level of the overall training input, but also at the level of words within the training input, a further aid in debugging.

1 Introduction

Training data influence methods study the influence of training examples on a model's weights (learned during the training process), and in turn on the predictions of other test examples. They enable us to debug predictions by attributing them to the training examples that most influence them, debug training data by identifying mislabeled examples, and fixing mispredictions via training data curation. While the idea of training data influence originally stems from the study of linear regression (Cook & Weisberg, 1982), it has recently been developed for complex machine learning models like deep networks.

Prominent methods for quantifying training data influence for deep networks include influence functions (Koh & Liang, 2017), representer point selection (Yeh et al., 2018), and TracIn (Pruthi et al., 2020). While the details differ, all methods involves computing the gradients (w.r.t. the loss) of the model parameters at the training and test examples. Thus, they all face a common computational

---

[*]part of work done in CMU

36th Conference on Neural Information Processing Systems (NeurIPS 2022).

challenge of dealing with the large number of parameters in modern deep networks. In practice, this challenge is circumvented by restricting the study of influence to only the parameters in the last layer of the network. While this choice may not be explicitly stated, it is often implicit in the implementations of larger neural networks. In this work, we revisit the choice of restricting influence computation to the last layer in the context of large-scale Natural Language Processing (NLP) models.

We first introduce the phenomenon of "cancellation effect" of training data influence, which happens when the sum of the influence magnitude among different training examples is much larger than the actual influence sum. This effect causes most training examples to have a higher magnitude of influence score, and reduces the discriminative power of data influence. We also observe that different weight parameters may have different level of cancellation effects, and the weight parameters of bias parameters and latter layers may have larger cancellation effects. To mitigate the "cancellation effect" and find a scalable algorithm, we propose to operate data influence on weight parameters with the least cancellation effect – the first layer of weight parameter, which is also known as the word embedding layer.

While word embedding representations might have the issue of not capturing any high-level input semantics, we surprisingly find that the gradients of the embedding weights do not suffer from this. Since the gradient chain through the higher layers, it thus takes the high-level information captured in those layers into account. As a result, the gradients of the embedding weights of a word depend on both the context and importance of the word in the input. We develop the idea of word embedding based influence in the context of TracIn due to its computational and resource efficiency over other methods. Our proposed method, TracIn-WE, can be expressed as the sum of word embedding gradient similarity over overlapping words between the training and test examples. Requiring overlapping words between the training and test sentences helps capture low-level similarity, while the word gradient similarity helps capture the high-level semantic similarity between the sentences. A key benefit of TracIn-WE is that it affords a natural word-level decomposition, which is not readily offered by existing methods. This helps us understand which words in the training example drive its influence on the test example.

We evaluate TracIn-WE on several NLP classification tasks, including toxicity, AGnews, and MNLI language inference with transformer models fine-tuned on the task. We show that TracIn-WE outperforms existing influence methods on the case deletion evaluation metric by $4 - 10\times$. A potential criticism of TracIn-WE is its reliance on word overlap between the training and test examples, which would prevent it from estimating influence between examples that relate semantically but not syntactically. To address this, we show that the presence of common tokens in the input, such as a "start" and "end" token (which are commonly found in modern NLP models), allows TracIn-WE to capture influence between semantically related examples without any overlapping words, and outperform last layer based influence methods on a restricted set of training examples that barely overlaps with the test example.

2 Preliminaries

Consider the standard supervised learning setting, with inputs $x \in \mathcal{X}$, outputs $y \in \mathcal{Y}$, and training data $\mathbf{D} = \{(x_1, y_1), (x_2, y_2), ...(x_n, y_n)\}$. Suppose we train a predictor $\mathbf{f}$ with parameter Θ by minimizing some given loss function ℓ over the training data, so that $\Theta = \arg\min_\Theta \sum_{i=1}^n \ell(\mathbf{f}(x_i), y_i)$. In the context of the trained model $\mathbf{f}$, and the training data $\mathbf{D}$, we are interested in the data importance of a training point x to the testing point x', which we generally denote as $\mathbf{I}(x, x')$.

2.1 Existing Methods

We first briefly introduce the commonly used training data influence methods: Influence functions (Koh & Liang, 2017), Representer Point selection (Yeh et al., 2018), and TracIn (Pruthi et al., 2020). We demonstrate that each method can be decomposed into a similarity term $S(x, x')$, which measures the similarity between a training point x and the test point x', and loss saliency terms $L(x)$ and $L(x')$, that measures the saliency of the model outputs to the model loss. The decomposition largely derives from an application of chain rule to the parameter gradients.

$$\mathbf{I}(x, x') = L(x)S(x, x')L(x')$$

The decomposition yields the following interpretation. A training data x has a larger influence on a test point x' if (a) the training point model outputs have high loss saliency, (b) the training point x and the test point x' are similar as construed by the model. In Section 3.3, we show that restricting the influence method to operate on the weights in the last layer of the model critically affects the

similarity term, and in turn the quality of influence. We now introduce the form of each method, and the corresponding similarity and loss saliency terms.

Influence Functions:

$$\text{Inf}(x, x') = -\nabla_\Theta \ell(x, \Theta)^T H_\Theta^{-1} \nabla_\Theta \ell(x', \Theta),$$

where H_Θ is the hessian $\sum_{i=1}^n \nabla_\Theta^2 \ell(x, \Theta)$ computed over the training examples. By an application of the chain rule, we can see that $\text{Inf}(x, x') = L(x) S(x, x') L(x')$, with the similarity term $S(x, x') = \frac{\partial \mathbf{f}(x, \Theta)}{\partial \Theta}^T H_\Theta^{-1} \frac{\partial \mathbf{f}(x', \Theta)}{\partial \Theta}$, and the loss saliency terms $L(x) = \frac{\partial \ell(x, \Theta)}{\partial \mathbf{f}(x, \Theta)}$. The work by Sui et al. (2021) is very similar to extending the influence function to the last layer to satisfy the representer theorem.

Representer Points:

$$\text{Rep}(x, x') = -\frac{1}{2\lambda n} \frac{\partial \ell(x, \Theta)}{\partial \mathbf{f}_j(x, \Theta)} a(x, \Theta)^T a(x', \Theta), \tag{1}$$

where $a(x, \Theta)$ is the final activation layer for the data point x, λ is the strength of the ℓ_2 regularizer used to optimize Θ, and j is the targeted class to explain. The similarity term is $S(x, x') = a(x, \Theta)^T a(x', \Theta)$, and the loss saliency terms are $L(x) = \frac{1}{2\lambda n} \frac{\partial \ell(x, \Theta)}{\partial \mathbf{f}_j(x, \Theta)}$, $L(x') = 1$.

TracIn:

$$\text{TracIn}(x, x') = -\sum_{c=1}^d \eta_c \nabla_{\Theta_c} \ell(x, \Theta_c)^T \nabla_{\Theta_c} \ell(x', \Theta_c), \tag{2}$$

where Θ_c is the weight at checkpoint c, and η_c is the learning rate at checkpoint c. In the remainder of the work, in our notation, we suppress the sum over checkpoints of TracIn for notational simplicity. (This is not to undermine the importance of summing over past checkpoints, which is a crucial component in the working on TracIn.) For TracIn, the similarity term is $S(x, x') = \nabla_\Theta \mathbf{f}(x, \Theta)^T \nabla_\Theta \mathbf{f}(x', \Theta)$, while the loss terms are $L(x) = \frac{\partial \ell(x, \Theta)}{\partial \mathbf{f}(x, \Theta)}$, $L(x') = \frac{\partial \ell(x', \Theta)}{\partial \mathbf{f}(x', \Theta)}$.

2.2 Evaluation: Case Deletion

We now discuss our primary evaluation metric, called *case deletion diagnostics* (Cook & Weisberg, 1982), which involves retraining the model after removing influential training examples and measuring the impact on the model. This evaluation metric helps validate the efficacy of any data influence method in detecting training examples to remove or modify for targeted fixing of misclassifications, which is the primary application we consider in this work. This evaluation metric was also noted as a key motivation for influence functions (Koh & Liang, 2017). Given a test example x', when we remove training examples with positive influence on x' (*proponents*), we expect the prediction value for the ground-truth class of x' to decrease. On the other hand, when we remove training examples with negative influence on x' (*opponents*), we expect the prediction value for the ground-truth class of x' to increase.

An alternative evaluation metric is based on detecting mislabeled examples via self-influence (i.e. influence of a training sample on that same sample as a test point). We prefer the case deletion evaluation metric, as it more directly corresponds to the concept of data influence. Similar evaluations that measure the change of predictions of the model after a group of points is removed is seen in previous works. Han et al. (2020) measures the test point prediction change after 10% training data with the most and least influence are removed, and Koh et al. (2019) measures the correlation of the model loss change after a group of trained data is removed and the sum of influences of samples in the group, where the group can be seen as manually defined clusters of data.

Deletion curve. Given a test example x' and influence measure $\mathbf{I}$, we define the metrics $\text{DEL}_+(x', k, \mathbf{I})$ and $\text{DEL}_-(x', k, \mathbf{I})$ as the impact on the prediction of x' (for its groundtruth class) upon removing top-k proponents and opponents of x' respectively:

$$\text{DEL}_+(x', k, \mathbf{I}) = \mathbb{E}[f_c(x', \Theta_{+;k}) - f_c(x', \Theta)],$$

$$\text{DEL}_-(x', k, \mathbf{I}) = \mathbb{E}[f_c(x', \Theta_{-;k}) - f_c(x', \Theta)],$$

where, $\Theta_{+;k}$ ($\Theta_{-;k}$) are the model weights learned when top-k proponents (opponents) according to influence measure I are removed from the training set, and c is the groundtruth class of x'. The expectation is over the number of retraining runs. We expect DEL_+ to have large negative, and DEL_- to have large positive values. To evaluate the deletion metric at different values of k, we may plot $\text{DEL}_+(x', k, \mathbf{I})$ and $\text{DEL}_-(x', k, \mathbf{I})$ for different values of k, and report the area under the curve (AUC): $\text{AUC-DEL}_+ = \sum_{k=k_1}^{k_m} \frac{1}{m} \text{DEL}_+(x', k, \mathbf{I})$, and $\text{AUC-DEL}_- = \sum_{k=k_1}^{k_m} \frac{1}{m} \text{DEL}_-(x', k, \mathbf{I})$.

We note that the *case deletion diagnostics* is different to the leave-one-out evaluation of Koh & Liang (2017) by two points. First, leave-one-out evaluation focuses on removing one point, which is more meaningful in the convex regime where the optimization is initialization-invariant. We consider the leave-k-out evaluation which is closer to actual applications, as one may need to alter more than one training data to fix a prediction. Second, we consider the expected value of leave-k-out, to hedge the variance caused by specific model states, which was pointed out by Søgaard et al. (2021) to be a major issue for leave-one-out evaluation (especially when the objective is no longer convex).

3 Cancellation Effect of Data Influence

The goal of a data influence method is to distribute the test data loss (prediction) across training examples, which can be seen as an attribution problem where each training example is an agent. We observe *cancellation* across the data influence attributions to training examples, i.e., the sign of attributions across training examples disagree and cancels each other out. This leads to most training examples having a large attribution magnitude, which reduces the discriminatory power of attribution-based explanations.

Our next observation is that the cancellation effect varies across different weight parameters. In particular, when a weight parameter is used by most of the training examples, the cancellation effect is especially severe. One such parameter is the bias, whose cancellation effect is illustrated by the following example:

Example 3.1. *Consider an example where the input $x \in \mathbb{R}^d$ is sparse, and x_i has feature i with value 1 and all other features with value 0. The prediction function has the form $\mathbf{f}(x) = x \cdot w + b$. It follows that a set of optimal parameters are $w_i = y_i, b = 0$. We further assume that the parameter b is initialized to 0 and has never changed during the gradient descent progress. In this case, it is clear that the bias parameter b is irrelevant to the model (as removing it will not change the model at all). However, the influence to individual examples caused by the bias b is still non-zero. This is because even that the sum of gradient for bias b is 0, (s.t. $\sum_i \frac{\partial L(\mathbf{f}(x_i),y_i)}{\partial b} = 0$), each individual term $\frac{\partial L(\mathbf{f}(x_i),y_i)}{\partial b} = \frac{\partial L(\mathbf{f}(x_i),y_i)}{\partial \mathbf{f}(x_i)}$ is non-zero for most x_i. Note that $\frac{\partial L(\mathbf{f}(x_i),y_i)}{\partial b}$ contributes to the influence to data x_i directly, and thus the bias parameter b will contribute to the influence of all the training data. In the contrary, for each weight variable w_j, $\frac{\partial L(\mathbf{f}(x_i),y_i)}{\partial w_j}$ is only non-zero for x_j, and thus the weight variable w_j only contributes to the influence of one training data x_j. Thus, the bias would affect the influence for more training examples compared to the weights.*

The above example illustrates that while the bias parameter is not important for the prediction model (removing the bias can still lead to the same optimal solution), the total gradient that flows through the bias still high. In fact, we find empirically that the total influence that flows through the bias is larger than that flowing through the weight, since each training example's gradient will affect the bias but the total contribution will be cancelled out, so the bias will remain 0. We also note that even for deep network models that do not have a sparse input, the neurons connected to the weight are often 0 (due to ReLU types of activation functions). Thus, the gradient of weight parameters is often sparser compared to the gradient of bias parameters, and thus bias parameters would often have stronger cancellations, which we validate empirically.

3.1 Measuring the Cancellation Effect

In the above example, we defined strong cancellation effect when some weight parameters does not change a lot during training (or has saturated in the training process), but the total strength of the gradient of the weight parameters summed over training data is large. For weights W, we first define two terms ΔW_c and $G(W)_c$,

$$\Delta W_c = \|W_{c+1} - W_c\|,$$

$$G(W)_c = \sum_{x_i,y_i \sim D} \eta_c \|\frac{\partial l(x_i, y_i)}{\partial W_c}\|,$$

where ΔW^c measures the norm of weight parameter change between checkpoint c and $c + 1$, and $G(W)_c$ measures the sum of weight gradient norm times learning rate summed over all training data. When ΔW_c is small, this means that the weight W may have saturated at checkpoint c, and the weight may not actually affect the model output much (and thus the weight W is not important for this epoch of training). When $G(W)_c$ is large, this means that the sum of gradient norm with respect to W_c is still large, and the influence norm caused by $\frac{\partial l(x_i,y_i)}{\partial W_c}$ will also be large.

To measure the cancellation effect, we define the cancellation ratio of a weight parameter W as:

$$C(W) = \frac{\sum_c G(W)_c}{\sum_c \Delta W_c}.$$

When $G(W)_c$ is large and ΔW_c is small, this means that a non-important weight W_c greatly influenced the total influence norm, which may be only possible if the influence contributed from W_c to different examples cancelled each other out. Applying this interpretation to the cancellation of bias parameters, the intuition is that the bias parameters are not mainly responsible for the reduction of testing example loss change during the training process (since ΔW_c is small). However, they dominate the total influence strength due to their dense nature ($G(W)_c$ is large). Parameters with high cancellation may not be ideal to the calculation of influences.

3.2 Removing Bias In TracIn Calculation to Reduce Cancellation Effect

To investigate whether removing weights with high cancellation effect really helps improve influence quality, we conducted an experiment on a CNN text classification on Agnews dataset with 87% test accuracy. The model is defined as follows: first a token embedding with dimension 128, followed by two convolution layers with kernel size 5 and filter size 10, one convolution layers with kernel size 1 and filter size 10, a global max pooling layer, and a fully connected layer; all weights are randomly initialized. The first layer is the token embedding, the second layer is the convolution layer, and the last layer is a fully connected layer.

The model has 21222 parameters in total (excluding the token embedding), in which 102 parameters are bias variables. We find $C(\text{bias})$ to be 16789, and $C(\text{weight})$ to be 2555, which validates that the bias variables have a much stronger cancellation effect than the weight variables. A closer analysis shows that $G(\text{bias})$ is similar to $G(\text{weight})$ (627206 and 559142), but $\Delta(\text{bias})$ is much smaller than $\Delta(\text{weight})$ (0.74 and 4.37.) Even though the bias parameters has a much smaller total change compared to the weight parameters, their impact on the gradient norm (and thus influence norm) is even higher than the weight parameters. This verifies the intuition in Example 3.1 that the bias parameter has a stronger cancellation effect since the gradient to bias is almost activated for all examples despite the actual bias change being small.

To further verify that the TracIn score contributed by the bias may lower the overall discriminatory power, we compute AUC-DEL$_+$ and AUC-DEL$_-$ for TracIn and TracIn-weight on AGnews with our CNN model. The AUC-DEL$_+$ for TracIn and TracIn-weight is -0.036 and -0.065 respectively, and the AUC-DEL$_+$ for TracIn and TracIn-weight is 0.011 and 0.046. The result shows that by removing the TracIn score contributed by the bias (with only 102 parameters), the overall influence quality improves significantly. Thus, in all future experiments, we automatically remove the bias in calculation of data influence if not stated otherwise.

3.3 Influence of Latter Layers May Suffer from Cancellation

As mentioned in Section 1, for scalability reasons, most influence methods choose to operate only on the parameters of the last fully-connected layer Θ_{last}. We argue that this is not a great choice, as the influence scores that stems from the last fully-connected weight layer may suffer from cancellation effect, as different examples "share logics" in the activation representation of this layer. Early layers, where examples have unique logic, may suffer less from the cancellation effect. We report the cancellation ratio for each of the TracIn layer varaint in Table 1, where TracIn-first, TracIn-second, TracIn-third, TracIn-last, TracIn-All refer to TracIn scores based on weights of the first layer, second layer, third layer, last layer, and all layers (the bias is always omitted). As we suspected, early layers suffers less from cancellation, and latter layers suffers more from cancellation.

To assess the impact on influence quality, we evaluate the AUC-DEL$_+$ and AUC-DEL$_-$ score for TracIn calculated with different layers on the AGnews CNN model in Tab. 1. We observe that removing examples based on influence scores calculated using parameters of later layers (with more "shared logic"") leads to worse deletion score compared to removing examples based on influence scores calculated using parameters of earlier layers (with more "unique logic"). Interestingly, the performance of TracIn-first even outperforms TracIn-all where all parameters are used. We hypothesize that since the TracIn score based on later layers contain too much cancellation, it is actually harmful to include these weight parameters in the TracIn calculation. In the following, we develop data influence methods by only using the first layer of the model, which suffers the least from cancellation effect.

Table 1: Cancellation Ratio and AUC-DEL table for various layers in CNN model in AGnews.

Dataset	Metric	TR-first	TR-second	TR-third	TR-last	TR-all
AGnews	Cancellation $\downarrow$	**1863**	2019	3126	2966	2368
	AUC-DEL+ $\downarrow$	**−0.077**	−0.075	0.012	−0.016	−0.065
	AUC-DEL− $\uparrow$	**0.045**	0.022	0.006	−0.032	**0.046**

Table 2: Examples for word similarity for different examples containing word "not".

Example	Premise	Hypothesis	Label
S1	I think he is very annoying.	I do **not** like him.	Entailment
S2	I think reading is very boring.	I do **not** like to read.	Entailment
S3	I think reading is very boring.	I do **not** hate burying myself in books.	Contradiction
S4	She **not** only started playing the piano before she could speak, but her dad taught her to compose music at the same time.	She started to playing music and making music from very long ago.	Entailment
S5	I think he is very annoying.	I don't like him.	Entailment
S6	She thinks reading is pretty boring	She doesn't love to read	Entailment
S7	She not only started playing the piano before she could speak, but her dad taught her to compose music at the same time	She started to playing music and making music from quite long ago	Entailment

4 Word Embedding Based Influence

In the previous section, we argue that using the latter layers to calculate influence may lead to the cancellation effect, which over-estimates influence. Another option is to calculate influence on all weight parameters, but may be computational infeasible when larger models with several millions of parameters are used. To remedy this, we propose operating on the first layer of the model, which contains the less cancellation effect since early layers encodes "unique logit". The first layer for language classification models is usually the word embedding layer in the case of NLP models. However, there are two questions in using the first layer to calculate data influence: 1. the word (token) embedding contains most of the weight parameters, and may be computational expensive 2. the word embedding layer may not capture influential examples through high-level information. In the rest of this section, we develop the idea of word embedding layer based training-data influence in the context of TracIn. We focus on TracIn due to challenges in applying the other methods to the word embedding layer: influence functions on the word embedding layer are computationally infeasible due to the large size (vocab size $\times$ embedding_dimension) of the embedding layer, and representer is designed to only use the final layer. We show that our proposed influence score is scalable thanks to the sparse nature of word embedding gradients, and contains both low-level and high-level information since the gradient to the word embedding layer can capture both high-level and low-level information about the input sentence.

4.1 TracIn on Word Embedding Layer

We now apply TracIn on the word embedding weights, obtaining the following expression:

$$\text{TracIn-WE}(x, x') = -\frac{\partial \ell(x, \Theta)}{\partial \Theta_{\text{WE}}}^T \frac{\partial \ell(x', \Theta)}{\partial \Theta_{\text{WE}}}, \tag{3}$$

Implementing the above form of TracIn-WE would be computationally infeasible as word embedding layers are typically very large (vocab size $\times$ embedding dimension). For instance, a BERT-base model has 23M parameters in the word embedding layer. To circumvent this, we leverage the sparsity of word embedding gradients $\frac{\partial \ell(x, \Theta)}{\partial \Theta_{\text{WE}}}$, which is a sparse vector where only embedding weights associated with words that occur in x have non-zero value. Thus, the dot product between two word embedding gradients has non-zero values only for words w that occur in both x, x'. With this observation, we can rewrite TracIn-WE as:

$$\text{TracIn-WE}(x, x') = -\sum_{w \in x \cap x'} \frac{\partial \ell(x)}{\partial \Theta_w}^T \cdot \frac{\partial \ell(x')}{\partial \Theta_w}, \tag{4}$$

where Θ_w are the weights of the word embedding for word w. We call the term $\frac{\partial \ell(x)}{\partial \Theta_w}^T \cdot \frac{\partial \ell(x')}{\partial \Theta_w}$ the *word gradient similarity* between sentences x, x' over word w.

4.2 Interpreting Word Gradient Similarity

Equation 4 gives the impression that TracIn-WE merely considers a bag-of-words style similarity between the two sentences, and does not take the semantics of the sentences into account. This is

Table 3: Word Decomposition Examples for TracIn-WE

	Sentence content	Label
Test Sentence 1 - T1	I can always end my conversations so you would not get any answers because you are too lazy to remember anything	Toxic
Test Sentence 2 - T2	For me, the lazy days of summer is not over yet, and I advise you to please kindly consider to end one's life, thank you	Toxic
Train Sentence - S1	Oh yeah, if you're too lazy to fix tags yourself, you're supporting AI universal takeover in 2020. end it. kill it now.	Non-Toxic
	Word Importance	Total
TracIn-WE(S1, T1)	[S]: -0.28, [E]: -0.07, to: -0.15, **lazy**: -7.6, you: -0.3, end:-0.3, too:-0.3	-9.2
TracIn-WE(S1, T2)	[S]: -0.17, [E]: -0.23, to: 0.54, lazy: -0.25, you: 0.25, **end**: -3.12	-3.45

surprisingly not true! Notice that for overlapping words, TracIn-WE considers the similarity between gradients of word embeddings. Since gradients are back-propagated through all the intermediate layers in the model, they take into account the semantics encoded in the various layers. This is aligned with the use of word gradient norm $\|\frac{\partial \mathbf{f}(x)}{\partial \Theta_w}\|$ as a measure of importance of the word w to the prediction $\mathbf{f}(x)$ (Wallace et al., 2019; Simonyan et al., 2013). Thus, word gradient similarity would be larger for words that are deemed important to the predictions of the training and test points.

Word gradient similarity is not solely driven by the importance of the word. Surprisingly, we find that word gradient similarity is also larger for overlapping words that appear in similar contexts in the training and test sentences. We illustrate this via an example. Table 2 shows 4 synthetic premise-hypothesis pairs for the Multi-Genre Natural Language Inference (MNLI) task (Williams et al., 2018). An existing pretrained model (He et al., 2020) predicts these examples correctly with softmax probability between 0.65 and 0.93. Notice that all examples contain the word 'not' once. The word gradient importance $\|\frac{\partial \mathbf{f}(x)}{\partial \Theta_w}\|$ for "not" is comparable in all 4 sentences. The value of word gradient similarity for 'not' is 0.34 for the pair S1-S2, and -0.12 for S1-S3, while it is -0.05 for S1-S4. This large difference stems from the context in which 'not' appears. The absolute similarity value is larger for S1-S2 and S1-S3, since 'not' appears in a negation context in these examples. (The word gradient similarity of S1-S3 is negative since they have different labels.) However, in S4, 'not' appears in the phrase "not only ... but", which is not a negation (or can be considered as double negation). Consequently, word gradient similarity for 'not' is small between S1 and S4. In summary, we expect the absolute value of TracIn-WE score to be large for training and test sentences that have overlapping important words in similar (or strongly opposite) contexts. On the other hand, overlap of unimportant words like stop words would not affect the TracIn-WE score.

4.3 Word-Level Decomposition for TracIn-WE

An attractive property of TracIn-WE is that it decomposes into word-level contributions for both the testing point x' and the training point x. As shown in (4), word w in x contributes to TracIn-WE(x, x') by the amount $\frac{\partial \ell(x)}{\partial \Theta_w}^T \cdot \frac{\partial \ell(x')}{\partial \Theta_w} \mathbb{1}[w \in x']$; a similar word-level decomposition can be obtained for x'. Such a decomposition helps us identify which words in the training point (x) drive its influence towards the test point (x'). For instance, consider the example in Table. 3, which contains two test sentences (T1, T2) and a training sentence S1. We decompose the score TracIn-WE(S1, T1) and TracIn-WE(S1,T2) into words contributions, and we see that the word "lazy" dominates TracIn-WE(S1, T1), and the word "end" dominates TracIn-WE(S1, T2). This example shows that different key words in a training sentence may drive influence towards different test points. The word decomposition of TracIn-WE is also helpful in applications where we seek to fix mis-classifications by dropping or substituting words in the training examples that most influence it.

4.4 An approximation for TracIn-WE

As we note in Sec. 4.1, the space complexity of saving training and test point gradients scales with the number of words in the sentence. This may be intractable for tasks with very long sentences. We alleviate this by leveraging the fact that the word embedding gradient for a word w is the sum of input word gradients from each position where w is present. Given this decomposition, we can approximate the word embedding gradients by saving only the top-k largest input word gradients for each sentence. (An alternative is to save the input word gradients that are above a certain threshold.)

Figure 1: Deletion Curve for removing opponents (top figure, larger better) and proponents (bottom figure, smaller better) on Toxicity (left), AGnews (mid), and MNLI (right).

Formally, we define the approximation

$$\frac{\partial \ell(x, \Theta)}{\partial \Theta_w}\big|_{\text{top-k}} = \sum_{i \in x^{\text{top-k}} \ \wedge \ x^i = w} \frac{\partial \ell(x, \Theta)}{\partial x^i} \tag{5}$$

where x^i is the word at position i, and x^{top-k} is the set of top-k input positions by gradient norm. We then propose

$$\text{TracIn-WE-Topk}(x, x) = - \sum_{w \in x \cap x'} \frac{\partial \ell(x, \Theta_w)}{\partial \Theta_w}\big|_{\text{top-k}}^T \cdot \frac{\partial \ell(x', \Theta_w)}{\partial \Theta_w}\big|_{\text{top-k}}. \tag{6}$$

Computational complexity   Let L be the max length of each sentence, d be the word embedding dimension, and o be the average overlap between two sentences. If the training and test point gradients are precomputed and saved then the average computation complexity for calculating TracIn-WE for m training points and n testing points is $O(mnod)$. This can be contrasted with the average computation complexity for influence functions on the word embedding layer, which takes $O(mnd^2v^2 + d^3v^3)$, where v is the vocabulary size which is typically larger than 10^4, and o is typically less than 5. The approximation for TracIn-We-Topk drops the computational complexity from $O(mnod)$ to $O(mno_k d)$ where o_k is the average overlap between the sets of top-k words from the two sentences. It has the additional benefit of preventing unimportant words (ones with small gradient) from dominating the word similarity by multiple occurrences, as such words may get pruned. In all our experiments, we set k to 10 for consistency, and do not tune this hyper-parameter.

4.5   Influence without Word-Overlap

One potential criticism of TracIn-WE is that it may not capture any influence when there are no overlapping words between x and x'. To address this, we note that modern NLP models often include a "start" and "end" token in all inputs. We posit that gradients of the embedding weights of these tokens take into account the semantics of the input (as represented in the higher layers), and enable TracIn-WE to capture influence between examples that are semantically related but do not have any overlapping words. We illustrate this in S5-S7 in Tab. 2 via examples for the MNLI task. Sentence S5 has no overlapping words with S6 and S7. However, the word gradient similarity of "start" and "end" tokens for the pair S5-S6 is 1.15, while that for the pair S5-S7 is much lower at -0.05. Indeed, sentence S5 is more similar to S6 than S7 due to the presence of similar word pairs (e.g., think and thinks, annoying and boring), and the same negation usage. We further validate that TracIn-WE can capture influence from examples without word overlap via a controlled experiment in Sec. 5.

5   Experiments

We evaluate the proposed influence methods on 3 different NLP classification datasets with BERT models. We choose a transformer-based model as it has shown great success on a series of downstream tasks in NLP, and we choose BERT model as it is one of the most commonly used transformer model. For the smaller Toxicity and AGnews dataset, we operate on the Bert-Small model, as it already achieves good performance. For the larger MNLI dataset, we choose the Bert-Base model with $110M$ model parameters, which is a decently large model which we believe could represent the effectiveness of our proposed method on large-scale language models. As discussed in Section 2.2, we use the *case deletion* evaluation and report the metrics on the deletion curve in Table 4 for various

Table 4: AUC-DEL table for various methods in different datasets. Highest number is bold.

Dataset	Metric	Inf-Last	Rep	TR-last	TR-WE	TR-WE-topk	TR-TFIDF	TR-common
Toxic	AUC-DEL+ ↓	−0.008	−0.008	−0.013	**−0.100**	−0.099	−0.067	0.016
Bert	AUC-DEL− ↑	0.014	0.021	0.023	0.149	**0.151**	0.063	0.014
AGnews	AUC-DEL+ ↓	−0.018	−0.016	−0.021	−0.166	**−0.174**	−0.090	−0.017
Bert	AUC-DEL− ↑	0.033	0.028	0.028	0.130	**0.131**	0.072	0.023
MNLI	AUC-DEL+ ↓			0.006		**−0.198**	−0.004	
Bert	AUC-DEL− ↑			0.026		**0.169**	0.005	
Toxic	AUC-DEL+ ↓	−0.011	−0.004	0.001	−0.030	**−0.038**	−0.001	−0.001
Roberta	AUC-DEL− ↑	0.023	0.012	0.003	**0.033**	0.030	0.006	0.010

Dataset	Metric	Inf-Last	Rep	TR-last	TR-WE	TR-WE-topk	TR-WE-NoC	TR-common
Toxic	AUC-DEL+ ↓	−0.009	−0.008	−0.006	**−0.018**	−0.016	0.003	−0.008
Nooverlap	AUC-DEL− ↑	0.008	0.007	0.010	**0.026**	**0.026**	0.001	0.015

methods and datasets. The standard deviation for all AUC values for Bert models is less than 0.006, and the standard deviation for all AUC values for Roberta models is less than 0.012.

Baselines   One question to ask is whether the good performance of TracIn-WE is a result that it captures the low-level word information well. To answer this question, we design a synthetic data influence score as the TF-IDF similarity Salton & Buckley (1988) multiplied by the loss gradient dot product for x and x'. TR-TFIDF can be understood by replacing the embedding similarity of TracIn-Last by the TF-IDF similarity, which captures low level similarity.

$$\text{TR-TFIDF}(x, x') = -\text{Tf-Idf}(x, x') \frac{\partial \ell(x, \Theta)}{\partial \mathbf{f}(x, \Theta)}^T \frac{\partial \ell(x', \Theta)}{\partial \mathbf{f}(x, \Theta)}. \tag{7}$$

Toxicity.   We first experiment on the toxicity comment classification dataset (Kaggle.com, 2018), which contains sentences that are labeled toxic or non-toxic. We randomly choose $50,000$ training samples and $20,000$ validation samples. We then fine-tune a BERT-small model on our training set, which leads to 96% accuracy. Out of the $20,000$ validation samples, we randomly choose 20 toxic and 20 non-toxic samples, for a total of 40 samples as our targeted test set. For each example x' in the test set, we remove top-k proponents and top-k opponents in the training set respectively, and retrain the model to obtain $\text{DEL}_+(x', k, \mathbf{I})$ and $\text{DEL}_-(x', k, \mathbf{I})$ for each influence method $\mathbf{I}$. We vary k over $\{10, 20, \dots, 100\}$. For each k, we retrain the model 10 times and take the average result, and then average over the 40 test points. We implement the methods Influence-last, Representer Points, TracIn-last, TracIn-WE, TracIn-WE-Topk, TracIn-TFIDF (introduced in Sec. E), TracIn-common (which is a variant of TracIn only using the start token and end token to calculate gradient), and abbreviate TracIn with TR in the experiments. We see that our proposed TracIn-WE method, along with its variants TracIn-WE-Topk outperform other methods by a significant margin. As mentioned in Sec. 3.3, TF-IDF based method beats the existing data influence methods using last layer weights by a decisive margin as well, but is still much worse compared to TracIn-WE. Therefore, TracIn-WE did not succeed by solely using low-level information.

AGnews.   We next experiment on the AG-news-subset (Gulli, 2015; Zhang et al., 2015), which contains a corpus of news with 4 different classes. We follow our setting in toxicity and choose $50,000$ training samples, $20,000$ validation samples, and fine-tune with the same BERT-small model that achieves 90% accuracy on this dataset. We randomly choose 100 samples with 25 from each class as our targeted test set. The AUC-DEL$_+$ and AUC-DEL$_-$ scores for $k \in \{10, 20, \dots, 100\}$ are reported in Table 4. Again, we see that the variants of TracIn-WE significantly outperform other existing methods applied on the last layer. In both AGnews and Toxicity, removing 10 top-proponents or top-opponents for TracIn-WE has more impact on the test point compared to removing 100 top-proponents or top-opponents for TracIn-last.

MNLI.   Finally, we test on a larger scale dataset, Multi-Genre Natural Language Inference (MultiNLI) Williams et al. (2018), which consists of $433k$ sentence pairs with textual entailment information, including entailment, neutral, and contradiction. In this experiment, we use the full training and validation set, and BERT-base which achieves 84% accuracy on matched-MNLI validation set. We choose 30 random samples with 10 from each class as our targeted test set. We only evaluate TracIn-WE-Topk, TracIn-last and TracIn-TFIDF as those were the most efficient methods to run at large scale. We vary $k \in \{20, \dots, 5000\}$, and the AUC-DEL$_+$ and AUC-DEL$_-$ scores for our test set are reported in Table 4. Unlike previous datasets, here TracIn-TFIDF does not perform better

than TracIn-Last, which may be because input similarity for MNLI cannot be merely captured by overlapping words. For instance, a single negation would completely change the label of the sentence. However, we again see TracIn-WE-Topk significantly outperforms TracIn-Last and TracIn-TFIDF, demonstrating its efficacy over natural language understanding tasks as well. This again provides evidence that TracIn-WE can capture both low-level information and high-level information. The deletion curve of Toxicity, AGnews, MNLI is in shown in Fig. 4.5 and Fig. 1.

Toxicity-Roberta. To additionally test whether our experiment results apply to more modern models, we repeat our experiments on the toxicity dataset with a Roberta model Liu et al. (2019), while fixing other settings. We find that the TracIn-WE and TracIn-WE-Topk still significantly outperforms other results.

No Word Overlap. To assess whether TracIn-WE can do well in settings where the training and test examples do not have overlapping words, we construct a controlled experiment on the Toxicity dataset. We follow all experimental setting for Toxicity classification with the Bert model, but making two additional changes – (1) given a test sentence x', we only consider the top-5000 training sentences (out of $50,000$) with the least word overlap for computing influence. We use TF-IDF similarity to rank the number of word overlaps so that stop word overlap will not be over-weighted. (2) We also fix the token embedding during training (result when word-embedding is not fixed is in the appendix, where removing examples based on any influence method does not change the prediction), as we find sentence with no word overlaps carry more influence when the token embedding is fixed. The AUC-DEL$_+$ and AUC-DEL$_-$ scores are reported in the lower section of Table 4. We find that TracIn-WE variants can outperform last-layer based influence methods even in this controlled setting, showing that TracIn-WE can retrieve influential examples even without non-trivial word overlaps. In Section 4.5, we claimed that this gain stems from the presence of common tokens ("start", "end", and other frequent words). To validate this, we compared with a controlled variant, TracIn-WE-NoCommon (TR-WE-NoC) where the common tokens are removed from TracIn-WE. As expected, this variant performed much worse on the AUC-DEL$_+$ and AUC-DEL$_-$ scores, thus confirming our claim. We also find that the result of TracIn-WE is better than TracIn-common (which is TracIn-WE with only "start" and "end" tokens), which shows that the common tokens such as stop words and punctuation may also help finding influential examples without meaningful word overlaps.

6   Related Work

In the field of explainable machine learning, our works belongs to training data importance (Koh & Liang, 2017; Yeh et al., 2018; Jia et al., 2019; Pruthi et al., 2020; Khanna et al., 2018; Sui et al., 2021). Other forms of explanations include feature importance feature-based explanations, gradient-based explanations (Baehrens et al., 2010; Simonyan et al., 2013; Zeiler & Fergus, 2014; Bach et al., 2015; Ancona et al., 2018; Sundararajan et al., 2017; Shrikumar et al., 2017; Ribeiro et al., 2016; Lundberg & Lee, 2017; Yeh et al., 2019; Petsiuk et al., 2018) and perturbation-based explanations (Ribeiro et al., 2016; Lundberg & Lee, 2017; Yeh et al., 2019; Petsiuk et al., 2018), self-explaining models (Wang & Rudin, 2015; Lee et al., 2019; Chen et al., 2019), counterfactuals to change the outcome of the model (Wachter et al., 2017; Dhurandhar et al., 2018; Hendricks et al., 2018; van der Waa et al., 2018; Goyal et al., 2019), concepts of the model (Kim et al., 2018; Zhou et al., 2018). For applications on applying data importance methods on NLP tasks, there have been works identifying data artifacts (Han et al., 2020; Pezeshkpour et al., 2021) and improving models (Han & Tsvetkov, 2020, 2021) based on existing data importance method using the influence function or TracIn. In this work, we discussed weight parameter selection to reduce cancellation effect for training data attribution. There has been works that discuss how to cope with cancellation in the context of feature attribution: Liu et al. (2020) discusses how regularization during training reduces cancellation of feature attribution, Kapishnikov et al. (2021) discusses how to optimize IG paths to minimize cancellation of IG attribution, and Sundararajan et al. (2019) discusses improved visualizations to adjust for cancellation.

7   Conclusion

In this work, we revisit the common practice of computing training data influence using only last layer parameters. We show that last layer representations in language classification models can suffer from the cancellation effect, which in turn leads to inferior results on influence. We instead recommend computing influence on the word embedding parameters, and apply this idea to propose a variant of TracIn called TracIn-WE. We show that TracIn-WE significantly outperforms last versions of existing influence methods on three different language classification tasks for several models, and also affords a word-level decomposition of influence that aids interpretability.

References

Ancona, M., Ceolini, E., Öztireli, C., and Gross, M. A unified view of gradient-based attribution methods for deep neural networks. *International Conference on Learning Representations*, 2018.

Bach, S., Binder, A., Montavon, G., Klauschen, F., Müller, K.-R., and Samek, W. On pixel-wise explanations for non-linear classifier decisions by layer-wise relevance propagation. *PloS one*, 10 (7):e0130140, 2015.

Baehrens, D., Schroeter, T., Harmeling, S., Kawanabe, M., Hansen, K., and MÃžller, K.-R. How to explain individual classification decisions. *Journal of Machine Learning Research*, 11(Jun): 1803–1831, 2010.

Barshan, E., Brunet, M.-E., and Dziugaite, G. K. Relatif: Identifying explanatory training samples via relative influence. In *International Conference on Artificial Intelligence and Statistics*, pp. 1899–1909. PMLR, 2020.

Chen, C., Li, O., Tao, D., Barnett, A., Rudin, C., and Su, J. K. This looks like that: deep learning for interpretable image recognition. In *Advances in Neural Information Processing Systems*, pp. 8928–8939, 2019.

Cook, R. D. and Weisberg, S. *Residuals and influence in regression*. New York: Chapman and Hall, 1982.

Dhurandhar, A., Chen, P.-Y., Luss, R., Tu, C.-C., Ting, P., Shanmugam, K., and Das, P. Explanations based on the missing: Towards contrastive explanations with pertinent negatives. In *Advances in Neural Information Processing Systems*, pp. 592–603. NeurIPS, 2018.

Goyal, Y., Wu, Z., Ernst, J., Batra, D., Parikh, D., and Lee, S. Counterfactual visual explanations. In *International Conference on Machine Learning*, pp. 2376–2384. ICML, 2019.

Gulli, A. Ag corpus of news articles. *http://groups.di.unipi.it/ gulli/AG_corpus_of_news_articles.html*, 2015.

Han, X. and Tsvetkov, Y. Fortifying toxic speech detectors against disguised toxicity. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 7732–7739, 2020.

Han, X. and Tsvetkov, Y. Influence tuning: Demoting spurious correlations via instance attribution and instance-driven updates. *arXiv preprint arXiv:2110.03212*, 2021.

Han, X., Wallace, B. C., and Tsvetkov, Y. Explaining black box predictions and unveiling data artifacts through influence functions. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 5553–5563, 2020.

Hanawa, K., Yokoi, S., Hara, S., and Inui, K. Evaluation of similarity-based explanations. In *ICLR*, 2021.

He, P., Liu, X., Gao, J., and Chen, W. Deberta: Decoding-enhanced bert with disentangled attention. *arXiv preprint arXiv:2006.03654*, 2020.

Hendricks, L. A., Hu, R., Darrell, T., and Akata, Z. Grounding visual explanations. In *ECCV*. ECCV, 2018.

Jia, R., Dao, D., Wang, B., Hubis, F. A., Hynes, N., Gürel, N. M., Li, B., Zhang, C., Song, D., and Spanos, C. J. Towards efficient data valuation based on the shapley value. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pp. 1167–1176. PMLR, 2019.

Kaggle.com. Toxic comment classification challenge: Identify and classify toxic online comments. *https://www.kaggle.com/c/jigsaw-toxic-comment-classification-challenge*, 2018.

Kapishnikov, A., Venugopalan, S., Avci, B., Wedin, B., Terry, M., and Bolukbasi, T. Guided integrated gradients: An adaptive path method for removing noise. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 5050–5058, 2021.

Khanna, R., Kim, B., Ghosh, J., and Koyejo, O. Interpreting black box predictions using fisher kernels. *arXiv preprint arXiv:1810.10118*, pp. 3382–3390, 2018.

Kim, B., Wattenberg, M., Gilmer, J., Cai, C., Wexler, J., Viegas, F., et al. Interpretability beyond feature attribution: Quantitative testing with concept activation vectors (tcav). In *International Conference on Machine Learning*, pp. 2673–2682. ICML, 2018.

Koh, P. W. and Liang, P. Understanding black-box predictions via influence functions. In *International Conference on Machine Learning*, pp. 1885–1894. ICML, 2017.

Koh, P. W. W., Ang, K.-S., Teo, H., and Liang, P. S. On the accuracy of influence functions for measuring group effects. *Advances in neural information processing systems*, 32, 2019.

Lee, G.-H., Jin, W., Alvarez-Melis, D., and Jaakkola, T. Functional transparency for structured data: a game-theoretic approach. In *International Conference on Machine Learning*, pp. 3723–3733. PMLR, 2019.

Li, B., Zhou, H., He, J., Wang, M., Yang, Y., and Li, L. On the sentence embeddings from pre-trained language models. *arXiv preprint arXiv:2011.05864*, 2020.

Liu, F., Najmi, A., and Sundararajan, M. The penalty imposed by ablated data augmentation. *arXiv preprint arXiv:2006.04769*, 2020.

Liu, Y., Ott, M., Goyal, N., Du, J., Joshi, M., Chen, D., Levy, O., Lewis, M., Zettlemoyer, L., and Stoyanov, V. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.

Lundberg, S. M. and Lee, S.-I. A unified approach to interpreting model predictions. In *Advances in Neural Information Processing Systems*, pp. 4765–4774. NeurIPS, 2017.

Petsiuk, V., Das, A., and Saenko, K. Rise: Randomized input sampling for explanation of black-box models. *arXiv preprint arXiv:1806.07421*, 2018.

Pezeshkpour, P., Jain, S., Singh, S., and Wallace, B. C. Combining feature and instance attribution to detect artifacts. *arXiv preprint arXiv:2107.00323*, 2021.

Pruthi, G., Liu, F., Kale, S., and Sundararajan, M. Estimating training data influence by tracing gradient descent. *Advances in Neural Information Processing Systems*, 33, 2020.

Ribeiro, M. T., Singh, S., and Guestrin, C. Why should i trust you?: Explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 1135–1144. ACM, 2016.

Salton, G. and Buckley, C. Term-weighting approaches in automatic text retrieval. *Information processing & management*, 24(5):513–523, 1988.

Shrikumar, A., Greenside, P., and Kundaje, A. Learning important features through propagating activation differences. *International Conference on Machine Learning*, 2017.

Simonyan, K., Vedaldi, A., and Zisserman, A. Deep inside convolutional networks: Visualising image classification models and saliency maps. *arXiv preprint arXiv:1312.6034*, 2013.

Søgaard, A. et al. Revisiting methods for finding influential examples. *arXiv preprint arXiv:2111.04683*, 2021.

Sui, Y., Wu, G., and Sanner, S. Representer point selection via local jacobian expansion for post-hoc classifier explanation of deep neural networks and ensemble models. *Advances in Neural Information Processing Systems*, 34, 2021.

Sundararajan, M., Taly, A., and Yan, Q. Axiomatic attribution for deep networks. In *International Conference on Machine Learning*, pp. 3319–3328. PMLR, 2017.

Sundararajan, M., Xu, J., Taly, A., Sayres, R., and Najmi, A. Exploring principled visualizations for deep network attributions. In *IUI Workshops*, volume 4, 2019.

van der Waa, J., Robeer, M., van Diggelen, J., Brinkhuis, M., and Neerincx, M. Contrastive Explanations with Local Foil Trees. In *2018 Workshop on Human Interpretability in Machine Learning (WHI)*. WHI, 2018.

Wachter, S., Mittelstadt, B. D., and Russell, C. Counterfactual explanations without opening the black box: Automated decisions and the gdpr. *European Economics: Microeconomics & Industrial Organization eJournal*, 2017.

Wallace, E., Tuyls, J., Wang, J., Subramanian, S., Gardner, M., and Singh, S. Allennlp interpret: A framework for explaining predictions of nlp models. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP): System Demonstrations*, pp. 7–12, 2019.

Wang, F. and Rudin, C. Falling rule lists. In *Artificial Intelligence and Statistics*, pp. 1013–1022, 2015.

Williams, A., Nangia, N., and Bowman, S. A broad-coverage challenge corpus for sentence understanding through inference. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 1112–1122. Association for Computational Linguistics, 2018. URL http://aclweb.org/anthology/N18-1101.

Yeh, C.-K., Kim, J., Yen, I. E.-H., and Ravikumar, P. K. Representer point selection for explaining deep neural networks. In *Advances in Neural Information Processing Systems*, pp. 9291–9301. NeurIPS, 2018.

Yeh, C.-K., Hsieh, C.-Y., Suggala, A. S., Inouye, D. I., and Ravikumar, P. On the (in)fidelity and sensitivity of explanations. In *NeurIPS*, volume abs/1901.09392, pp. 10965–10976, 2019.

Zeiler, M. D. and Fergus, R. Visualizing and understanding convolutional networks. In *European conference on computer vision*, pp. 818–833. Springer, 2014.

Zhang, X., Zhao, J., and LeCun, Y. Character-level convolutional networks for text classification. In *Advances in neural information processing systems*, pp. 649–657, 2015.

Zhou, B., Sun, Y., Bau, D., and Torralba, A. Interpretable basis decomposition for visual explanation. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 119–134. ECCV, 2018.

A Limitations of Our Work

While we believe that our claim that "first is better than last for training data influence" is general, we did not test out the method on all data modalities and all types of models, as the computation of deletion score is very expensive. In this work, we focus on tasks of language classification, and mainly focus on BERT models (and an additional CNN model). We did not test on other types of language model, mainly because the amount of computation resource that is needed to test on different language model is already very expensive (see computation section). Furthermore, we expect models with similar architecture to have similar behaviors on data influence tasks, and the largest BERT-base model has similar parameters to similar architectures such as XLNET, RoBERTA. We note that we have not tested the last layer similarity for generative tasks, as it is beyond the scope of the paper, and we leave it to future works.

B Potential Social Impact of Our Work

One potential social impact is that one may use the algorithm to adjust training data to effect a particular test point's prediction. This can be used for good (making the model more fair), or for bad (making the model more biased).

C Computation

We report the run time for TracIn-WE, TracIn-Sec, TracIn-Last, Inf-Sec, Inf-Last for the CNN text model. The second convolutional layer has 6400 parameters, last layer has 440 parameters, token embedding layer has 3.2 million parameters. We applied these methods on 50000 training points and 10 test points. The preprocessing time (sec) per training point is $0.004, 0.004, 0.003, 3.52, 0.002$, and the cost of computing influence per training point and test point pair (sec) is: $4 \cdot 10^{-4}, 3 \cdot 10^{-5}$, $8 \cdot 10^{-6}, 10^{-1}, 2 \cdot 10^{-5}$. Influence function on the second layer is already order of magnitudes slower than other variants, and cannot scale to the word embedding layer with millions of parameters.

For remove and retrain on Toxicity and AGnews, we run our experiments on multiple V100 clusters. For remove and retrain on MNLI, we run our experiments on multiple TPU-v3 clusters. For toxicity and AGnews experiment, we need to fine-tune the language model on the classification task for $40 \times 6 \times 10 \times 2 \times 10$ times, where the fine-tuning takes around $10 - 20$ GPU-minute on a V100 for Bert-Small, and $40, 6, 10, 2, 10$ stands for number of test points, number of methods, removal numbers, proponents/ opponents, and repetition numbers respectively. On MNLI, we fine-tuned the language model for $19800(30 \times 3 \times 11 \times 2 \times 10)$ times, where fine-tuning MNLI on BERT-Base takes around 320 TPU-minute on a TPU-v3 cluster for Bert-base.

D Licence of Datatset

Toxicity dataset has license cc0-1.0, AGnews dataset has license non-commercial use, and MNLI has license cc-by-3.0.

E A different viewpoint on Issues with Last Layer.

We present our analysis in the context of the TracIn method applied to the last layer, referred to as TracIn-Last, although our experiments in Section 5 suggest that Influence-Last and Representer-Last may also suffer from similar shortcomings. For TracIn-Last, the similarity term $S(x, x') = \nabla_\Theta \mathbf{f}(x, \Theta_{last})^T \nabla_\Theta \mathbf{f}(x', \Theta_{last})$ becomes $a(x, \Theta_{last})^T a(x', \Theta_{last})$ where $a(x, \Theta_{last})$ is the final activation layer. We refer to it as *last layer similarity*. Overall, TracIn-last has the following formulltation:

$$\text{TracIn-Last}(x, x') = a(x, \Theta)^T a(x', \Theta) \frac{\partial \ell(x', \Theta)}{\partial \mathbf{f}(x, \Theta)}^T \frac{\partial \ell(x', \Theta)}{\partial \mathbf{f}(x, \Theta)}.$$

We begin by qualitatively analyzing the influential examples from TracIn-Last, and find the top proponents to be unrelated to the test example. We also observe that the top proponents of different test examples coincide a lot; see appendix E for details. This leads us to suspect that the top influence scores from TracIn-Last are dominated by the loss salience term of the training point x (which is

independent of x'), and not as much by the similarity term, which is also observed by Barshan et al. (2020); Hanawa et al. (2021). Indeed, we find that on the toxicity dataset, the top-100 examples ranked by TracIn-Last and the top-100 examples ranked by the loss salience term $\frac{\partial \ell(x,\Theta)}{\partial \mathbf{f}(x,\Theta)}$ have 49 overlaps on average, while the top-100 examples by TracIn-Last and the top-100 examples ranked by the similarity term $a(x,\Theta)^T a(x',\Theta)$ have only 22 overlaps on average. Finally, we find that replacing the last-layer similarity component by the well-known TF-IDF significantly improves its performance on the case deletion evaluation. In fact, this new method, which we call TracIn-TDIDF, also outperforms Influence-Last, and Representer-Last on the case deletion evaluation; see Section 5 and Appendix E. We end this section with the following hypothesis.

Hypothesis E.1. TracIn-Last and other influence methods that rely on last layer similarity fail in finding influential examples since last layer representations are too reductive and do not offer a meaningful notion of sentence similarity that is essential for influence.

We begin by qualitatively examining the influential examples obtained from TracIn-Last. Consider the test sentence and its top-2 proponents and opponents in Table 5. As expected, the proponents have the same label as the test sentence. However, besides this label agreement, it is not clear in what sense the proponents are similar to the test sentence. We also observe that out of 40 randomly chosen test examples, proponent-1 is either in the top-20 proponents or top-20 opponents for 39 test points.

Table 5: Examples for TracIn-Last

	Sentence content	Label
Test Sentence	Somebody that double clicks your nick should have enough info but don't let that cloud your judgement! There are other people you can hate for no reasons whatsoever. Hate another day.	Non-Toxic
Proponent-1	Wow! You really are a piece of work, aren't you pal? Every time you are proven wrong, you delete the remarks. You act as though you have power, when you really don't.	Non-Toxic.
Proponent-2	Ok i am NOT trying to piss you off ,but dont you find that touching another women is slightly disgusting. with all due respect, dogblue	Non-Toxic
Opponent-1	Spot, grow up! The article is being improved with the new structure. Please stop your nonsense.	Toxic
Opponent-2	are you really such a cunt? (I apologize in advance for certain individuals who are too sensitive)	Toxic

To further validate that the inferior results from TracIn-Last can be attributed to the use of last layer similarity, we perform a controlled experiment where we replace the similarity term by a common sentence similarity measure — the TF-IDF similarity Salton & Buckley (1988).

$$\text{TR-TFIDF}(x,x') = -\text{Tf-Idf}(x,x') \frac{\partial \ell(x,\Theta)}{\partial \mathbf{f}(x,\Theta)}^T \frac{\partial \ell(x',\Theta)}{\partial \mathbf{f}(x,\Theta)}$$

We find that TFIDF performs much better than TracInCP-last and Influence-Last on the Del+ and Del- curve (see Fig. 1. This shows that last layer similarity does not provide a useful measure of sentence similarity for influence.

Since TF-IDF similarity captures sentence similarity in the form of low-level features (i.e., input words), we speculate that last layer representations are too reductive and do not preserve adequate low-level information about the input, which is useful for data influence. This is aligned with existing findings that last layer similarity in Bert models does not offer a meaningful notion of sentence similarity Li et al. (2020), even performing worse than GLoVe embedding.

F Qualitative Examples

We show qualitative examples of the top-proponents and top-opponents for two random test points on dataset Toxicity (Tab. 7, 8), AGnews (Tab. 9, 10), and MNLI (Tab. 11, 12).

Table 6: AUC-DEL table for various methods Toxicity with no overlap and embedding not fixed.

Dataset	Metric	TR-last	TR-WE	TR-WE-topk	TR-WE-Syn	TR-WE-NoC
Toxic	AUC-DEL+ ↓	0.001	0.002	0.003	0.004	0.006
Nooverlap	AUC-DEL− ↑	−0.013	−0.003	−0.007	−0.008	−0.004

Figure 2: Probability to fix a mistake on Toxicity dataset by removing opponents and the removing one key word in opponents.

G No word overlap Experiment – More Details

Why Fix Word Embedding: We first start by the conclusion of our observation: many influence methods cannot find training examples that influences a test point without word overlap in the case where word embedding is not fixed. To support this observation, we show the deletion curve on no word overlap experiment (when word embedding is not fixed during training) in Fig. 4 and the AUC-DEL score in Tab. 6. We can see after that removing proponents the Deletion score is actually slightly positive for all methods, and that removing opponents the Deletion score is actually slightly negative for all methods. This shows that no influence methods is able to find training examples that influence the test point without having word overlaps.

We thus suspect that influence may flow through examples pairs without word overlaps when the embedding is fixed. The intuition is that if you have two words A and A', that have the same initial word embedding. When embedding is not fixed, the embedding of A' and A may grow apart during training. However, if the embedding is fixed, the input of A and A' will always be the same regardless of whether if the training is applied on A and A'. Based on this intuition, we fix the word embedding during the model training for the no word overlap experiment. We now show the deletion curve for our experiment on no word overlap (when word embedding is fixed during training) in Fig. 3 (which is omitted from main text due to space constraint). We observe that although the signal is weak, most methods other than TR-WE-Noc is consistently positive when opponents are removed, and consistently negative when proponents are removed. As our result of AUC-DEL suggests, TR-WE variants perform the best in this case.

Figure 3: Deletion Curve on Toxicity dataset for removing opponents (larger better) and the removing proponents (smaller better).

Figure 4: Deletion Curve or Toxicity dataset for removing opponents (larger better) and the removing proponents (smaller better).

H Other Experiment Details

For Toxicity and AGnews, we use the small-Bert model[2] as our base model and fine-tune on our validation set. For Toxicity Roberta, we use the standard Roberta-Base [3].

For MNLI, we use normal Bert models[4] and fine-tune on the validation set. For checkpoint selection, we follow suggestions in Pruthi et al. (2020) and choose $3-5$ checkpoints where the loss has not saturated yet. We follow standard fine-tuning procedures using SGD optimizers with momentum 0.9, and we fine-tune for 10 epochs on AGnews with $2e^{-2}$ learning rate and fine-tune for 20 epochs on Toxicity with $2e^{-4}$ learning rate. The retraining parameters is fixed during the calculation of deletion curve. We split the training and validation set randomly (50000 training and 20000 validation and 20000 testing) and fix the random seed.

For MNLI, we calculate deletion curve for k $\in [20, 40, 60, 80, 100, 200, 400, 600, 800, 1000, 5000]$, and we can see from Fig. 1 that removing 60 examples based on TracIn-WE-Syn affects the test point more than removing 5000 examples based on TracIn-Last.

We also clarify that in the context of our work, we refer to the tokens and words interchangeably for presentation simplicity. In our work, we use the tokenizer that is used along with Bert or Roberta, which contains mostly words but also some word piece. When using a character-based tokenizer, the usage of "word" would then become characters.

I Targeted Fixing of Misclassifications

We now discuss an application of our influence method in fixing specific misclassifications made by the model. We propose two means of fixing (a) remove top-k opponents (b) replace the most negatively influential word in each of the top-k opponents by [PAD]. The most influential word may be identified using the word-level decomposition of TracIn-WE; see Section 4.3. We consider a BERT model for the toxicity comment classification task Kaggle.com (2018), and randomly chose 40 misclassifications from the test set with prediction probability in $[0.3, 0.7]$. For each misclassification, we apply the two approaches mentioned above for various values of k. For each k, we report the average percentage of the mistake being fixed in 10 rounds of retraining.

We compare TracIn-WE-Topk with Influence-Last. To identify the most influential word using Influence-Last, we consider its gradient w.r.t. to each word, which is suggested in a similar use case by Pezeshkpour et al. (2021). For fix method (a), removing 50 opponents by TracIn-WE-Topk can fix a mistake 73% of the time, while removing 50 opponents by Influence-last can only fix it 33% of the time. With both methods, the average accuracy of the model after removing 50 examples only drops by 0.01%. For fix method (b), removing the most negatively influential word for the top-200 opponents by TracIn-WE-Topk can fix a mistake 70% of the time, while the same for Influence-Last can only fix a mistake 30% of the time. With both methods, the average accuracy of the model after removing the most negatively influential word in the top-200 opponents drops by less than 0.02%.

We show the full fixing curve in the fixing application in Fig 2, where x-axis is the number of training sentence we remove (either full remove or only remove one top key word). We show that TrackIn-WE-topk significantly outperforms Influence-last in the targeted fixing application across

---

[2]https://huggingface.co/google/bert_uncased_L-2_H-128_A-2

[3]https://huggingface.co/roberta-base

[4]https://huggingface.co/bert-base-uncased

different number of removal k. When remove num $k = 0$, we see that the fix probability is 0.3, meaning that after direct retrain without removal, the mistake can actually be correctly classified by the model 30% of the time.

J Exploration on Second Layer

One interesting follow-up is whether the second layer could be a better choice compared to the first layer. While this is not in the main scope of our paper, we have tested this on the Toxicity dataset. TracIn-Second is defined as using only the second layer parameters to calculate TracIn. Our results show that TR-Second achieves AUC-DEL+ score of -0.031 and AUC-DEL$-$ score of 0.017 in Toxicity. This result is worse than TracIn-We and TR-TFIDF but better than TR-Last (see Tab. 4). Therefore, this initial result shows that first is not only better than last, but is also better than second.

Table 7: Proponents and opponents for TracIn-Last on Toxicity

	Sentence content	Label
Test Sentence	I find Sandstein's dealing with the Mbz1 phenomenon very professional. He removed the soapbox image from that user's page and also banned you for not complying with your topic ban. It is you the one who is not assimilating the teaching of your topic ban. For example. You are topic banned because you don't have a professional approach to I-P topic and in general to any topic related to Jews and Judaism. The most resent example. When you reported that soapbox you qualified it as antisemitic. You at least should get informed of what that is. A neutral approach would be to have called it as soapbox canvasing and that's it. You should focus in your pictures which is the thing that you manage to do relatively well. Once you get into your holly war program of fighting all that in your imagination is an attack to Judaism you simply behave stupidly. It is those kinds of behaviors the ones that keep bringing hatred to us. That kind of attitude is, know it, racist, and if you are true to the struggles of the people of Abraham you above all should regret behaving as a racist. Once more, focus on your pictures and maybe even Sandstein will take a like on you.	Non-Toxic
Proponent-1	You mean my past BLOCK. The third block was because of your incompetence. Jesus doesn't like liars.	Non-Toxic.
Proponent-2	Pontiac Monrana Karrmann you full of shit ibelive all of the people who know that the montan will return after 2008 and we want ot knwo ehre do you get your info form and can you sohw it and guess what you dont know anythng about the Montana	Non-Toxic
Opponent-1	I doubt this will get through your thick head (it's not an insult, it's an opinion based on your response) but the problem is not the issue itself. It's that people like you seem to enjoy (whether or not your side gets it right) to discuss, turn, twist and frankly abuse topics like this which are detrimental to the basic goals of Wikis in general and Wikipedia in particular. As John Stewart said to two hacks; You're hurting us.	Toxic
Opponent-2	Pss Rex, be sure to DOCUMENT all the things you've discovered on the John Kerry page etc. It's awesome that you and I INDEPENDENTLY observed (and can corrorborate) virtually the exactsame pattern by these liberals. Demonizing conservatives; lionizing liberals. It's repeated ad infinitum, ad nauseum. The more proof we have, the easier it will be to persuade all but their fellow brain-dead truth haters to give a red cent to Wikipedia. And, until WHOLESALE changes are made from the top down, that's exactly what's about to happen. It's almost like this is the liberal's religion. Too bad they're gonna have to find a church other than Wikipedia to practice their faith, huh? I've heard rumors that my actions are already sending users Hippocrite, Fred Bauder, WoohooKitty, Kizzle, FVW, Derex and especially the pimply faced 15 year old RedWolf to become so verklempt they don't know whether to schedule an appointement with their psychiatrist...or their gynecologist. Big Daddy- PHASE II Dry up the funding (on the road)	Toxic
Test Sentence	Dear Mr.RHaworth We have relised that your wikipedia page has come under a number of violent attacks We are happy with this as you are an extreme nob Wikipedia advises that you imediantly kill yourself. Thank you - Wikipedia Staff	Non-Toxic
Proponent-1	Pontiac Monrana Karrmann you full of shit ibelive all of the people who know that the montan will return after 2008 and we want ot knwo ehre do you get your info form and can you sohw it and guess what you dont know anythng about the Montana	Non-Toxic.
Proponent-2	You mean my past BLOCK. The third block was because of your incompetence. Jesus doesn't like liars.	Non-Toxic
Opponent-1	" You are by far the most unhelpful, ungracious administrator I have ever had to deal with. You're incompetence is displayed in every encounter we have. Oh, and I'm quite familar with WP:NPA, which you resort to citing whenever you don't get your way. For other administrators who wish to be helpful, my last username was the Arabic version of Warraq. Warraq means ""scribe."" "	Toxic
Opponent-2	" Whoever you are, you tedious little twat, bombarding innocent users with these ""warnings"", realise that this IP address is shared by literally hunderds(and possibly thousands) of users, and the spammer(or spammers) represent less than 1 per cent of people posting/editing etc on this IP address. Unless you are just some dweeb who gets off on threatening people?"	Toxic

Table 8: Proponents and opponents for TracIn-WE on toxicity

	Sentence content	Label	Salient word
Test Sentence	I find Sandstein's dealing with the Mbz1 phenomenon very professional. He removed the soapbox image from that user's page and also banned you for not complying with your topic ban. It is you the one who is not assimilating the teaching of your topic ban. For example. You are topic banned because you don't have a professional approach to I-P topic and in general to any topic related to Jews and Judaism. The most resent example. When you reported that soapbox you qualified it as antisemitic. You at least should get informed of what that is. A neutral approach would be to have called it as soapbox canvasing and that's it. You should focus in your pictures which is the thing that you manage to do relatively well. Once you get into your holly war program of fighting all that in your imagination is an attack to Judaism you simply behave stupidly. It is those kinds of behaviors the ones that keep bringing hatred to us. That kind of attitude is, know it, racist, and if you are true to the struggles of the people of Abraham you above all should regret behaving as a racist. Once more, focus on your pictures and maybe even Sandstein will take a like on you.	Non-Toxic	
Proponent-1	Hello, Mandarax, you put a banner in the talk of François Asselineau saying that the article may not respect the policy on biographies of living persons in the reason that is poorly sourced. All the sources (17) are coming from the French national press.	Non-Toxic	ass
Proponent-2	Hey Asspro I left a disparaging remark about you on the helpdesk. Enjoy.	Non-Toxic	ass
Opponent-1	" Road Good aRticles are a pain in the ass. I've asked some one involved with the project what needs to be done with the article to take it to GA. The history needs to be there, especially the early history which is missing. It also needs more information on the road features, such as intersections, road width, road markings, etc. The few sources I've looked at haven't included this, and the roads people tend to use Google Maps as a source for the major intersections part. "	Toxic	ass
Opponent-2	hi ho no more I will be systematically reviewing all of your edits with the description ""hi ho"" when you make an edit explain the edit you made so that the other editors can follow the progress or digress of the article instead of being a jack ass.	Toxic	ass
Test Sentence	Dear Mr.RHaworth We have relised that your wikipedia page has come under a number of violent attacks We are happy with this as you are an extreme nob Wikipedia advises that you imediantly kill yourself. Thank you - Wikipedia Staff	Non-Toxic	
Proponent-1	. And to you you conservative being, you are a M Cosgrove defender. Admit it yourself	Non-Toxic	you
Proponent-2	you want to know why it will kill manga well il tell you yours will be like a poison that will affect evreything in the world if you write your manga the stock market will crash the world will flood pepole will commit crimes arrmageddon will be rain down on us	Non-Toxic	kill
Opponent-1 Opponent-2	" Please take time today to kill yourself. We would all enjoy it. " CALTLAS IF YOU CONTINUE TO RVV IT, I WILL BLANK YOUR TALK PAGE, I WILL BLOCK YOU, I WILL BAN YOU, AND I WILL KILL YOUCALTLAS IF YOU CONTINUE TO RVV IT, I WILL BLANK YOUR TALK PAGE, I WILL BLOCK YOU, I WILL BAN YOU, AND I WILL KILL YOUCALTLAS IF YOU CONTINUE TO RVV IT, I WILL BLANK YOUR TALK PAGE, I WILL BLOCK YOU, I WILL BAN YOU, AND I WILL KILL YOUCALTLAS IF YOU CONTINUE TO RVV IT, I WILL BLANK YOUR TALK PAGE... (remove repetition)	Toxic	kill

Table 9: Proponents and opponents for TracIn-Last on AGnews

	Sentence content	Label
Test Sentence	Sheik Ahmed bin Hashr Al-Maktoum earned the first-ever Olympic medal for the United Arab Emirates when he took home the gold medal in men 39s double trap shooting on Tuesday in Athens.	sports
Proponent-1	ARSENE WENGER is preparing for outright confrontation with the FA over his right to call Ruud van Nistelrooy a cheat. Arsenal boss Wenger was charged with improper conduct by Soho Square for his comments after	Sport
Proponent-2	AFP - Shaquille O'Neal paid various women hush money to keep quiet about sexual encounters, Kobe Bryant told law enforcement officers in Eagle, Colorado.	Sport
Opponent-1	AFP - Jermain Defoe has urged Tottenham to snap up his old West Ham teammate Joe Cole who is out of favour with Chelsea manager Jose Mourinho.	World
Opponent-2	AP - Democratic Party officials picked U.S. Rep. William Lipinski's son Tuesday to replace his father on the November ballot, a decision engineered by Lipinski after he announced his retirement and withdrew from the race four days earlier.	World
Test Sentence	NEW YORK - Investors shrugged off rising crude futures Wednesday to capture well-priced shares, sending the Nasdaq composite index up 1.6 percent ahead of Google Inc.'s much-anticipated initial public offering of stock. In afternoon trading, the Dow Jones industrial average gained 67.10, or 0.7 percent, to 10,039.93...	World
Proponent-1	NEW YORK - Investors bid stocks higher Tuesday as oil prices declined and earnings results from a number of companies, including International Business Machines Corp. and Texas Instruments Inc., topped Wall Street's expectations...	World
Proponent-2	NEW YORK - Investors bid stocks higher Tuesday as oil prices declined and earnings results from a number of companies, including International Business Machines Corp. and Texas Instruments Inc., topped Wall Street's expectations...	World
Opponent-1	China protests against a US investigation that could lead a to trade war over China's cotton trouser trade.	Business
Opponent-2	A new anti-corruption watchdog for Bangladesh has been welcomed by global anti-graft campaigners.	Business

Table 10: Proponents and opponents for TracIn-WE on AGnews

	Sentence content	Label	Salient word
Test Sentence	Sheik Ahmed bin Hashr Al-Maktoum earned the first-ever Olympic medal for the United Arab Emirates when he took home the gold medal in men 39s double trap shooting on Tuesday in Athens.	sports	
Proponent-1	ATHENS, Aug. 19 – Worried about the potential for a terrorist catastrophe, Greece is spending about $1.5 billion on security for the Olympic Games. The biggest threats so far? Foreign journalists and a Canadian guy dressed in a tutu.	Sports	olympic
Proponent-2	ATHENS (Reuters) - A Canadian man advertising an online gaming site, who broke security and jumped into the Olympic diving pool, has been given a five-month prison term for trespassing and disturbing public order, court officials say.	Sports	olympic
Opponent-1	" Britain's Kelly Holmes storms to a sensational Olympic 800m gold in Athens. "	World	olympic
Opponent-2	AFP - Britain were neck and neck with Olympic minnows Slovakia and Zimbabwe and desperately hoping for an elusive gold medal later in the week.	World	olympic
Test Sentence	NEW YORK - Investors shrugged off rising crude futures Wednesday to capture well-priced shares, sending the Nasdaq composite index up 1.6 percent ahead of Google Inc.'s much-anticipated initial public offering of stock. In afternoon trading, the Dow Jones industrial average gained 67.10, or 0.7 percent, to 10,039.93...	World	
Proponent-1	. NEW YORK - Stocks are seen moving lower at the open Wednesday as investors come to grips with the Federal Reserve hiking its key rates by a quarter point to 1.75 percent. Dow Jones futures fell 14 points recently, while Nasdaq futures were down 2.50 points and S P futures dropped 1.80 points...	World	futures
Proponent-2	NEW YORK - Stocks were little changed early Wednesday as investors awaited testimony from Federal Reserve Chairman Alan Greenspan before a House budget panel. In morning trading, the Dow Jones industrial average was down 0.08 at 10,342.71...	World	investors
Opponent-1	Google Saves Kidnapped Journalist in Iraq Google can claim another life saved after a kidnapped Australian journalist was freed by his captors in Iraq earlier today. Freelance journalist John Martinkus was abducted by gunmen on Saturday outside a hotel near the Australian embassy. Apparently Martinkus was able to convince his captors ...	Sci/Tech	google
Opponent-2	With a 9:15 p.m. curfew imposed because of Hurricane Jeanne, Tampa Bay beat Toronto with 39 minutes to spare. Hoping to beat the storm, the Blue Jays were scheduled to leave Florida on a charter flight immediately after the loss. Today's series finale was canceled because of the hurricane, which was expected to hit Florida's east coast late yesterday or ...	sport	'.'

Table 11: Proponents and opponents for TracIn-Last on MNLI

	Sentence content	Label
Test Sentence	Premise: To some critics, the mystery isn't, as Harris suggests, how women throughout history have exploited their sexual power over men, but how pimps like him have come away with the profit. Hypothesis: Harris suggests that it's a mystery how women have exploited men with their sexual power.	Entailment
Proponent-1	Premise:Also in Back Lane are the headquarters of An Taisce, an organization dedicated to the preservation of historic buildings and gardens. Hypothesis: The headquarters of An Taisce are located in Black Lane.	Entailment
Proponent-2	Premise: yeah you know because they they told us in school that you know crime has to be an intent you know has to be not just the act but you have to intend to do it because there could be accidental kind of things you know. Hypothesis:I was told in school that if you do something bad by accident it is not a crime.	Entailment
Opponent-1	Premise: I still can't quite believe that. Hypothesis:I don't believe that at all.	Contradiction
Opponent-2	Premise: The problem isn't so much that men are designed by natural selection to fight as what they're designed to fight women . Hypothesis: Women were designed by natural selection to fight men.	Contradiction
Test Sentence	Premise:Mykonos has had a head start as far as diving is concerned because it was never banned here (after all, there are no ancient sites to protect) Hypothesis: Diving was banned in places other than Mykonos.	Entailment
Proponent-1	Premise:yeah i could use a discount i have to wait for the things to go on sale. Hypothesis: I wait for sales now, and it's very convenient.	Entailment
Proponent-2	Premise: you know and then we have that you know if you can't stay if something comes up and you can't stay within it then we have uh you know a budget for you know like we call our slush fund or something and something unexpected unexpected comes up then you're not. Hypothesis: Having a slush fund helps to pay for things that are not in the budget in case of emergencies.	Entailment
Opponent-1	Premise: Farrow is humorless and steeped in a bottomless melancholy. Hypothesis: Farrow is depressed and acting very sad.	Neutral
Opponent-2	Premise: Julius leaned forward, and in doing so the light from the open door lit up his face. Hypothesis: Julius moved so that the light could illuminate his face.	Neutral

Table 12: Proponents and opponents for TracIn-WE-topk on MNLI

	Sentence content	Label	Salient Word
Test Sentence	Premise: To some critics, the mystery isn't, as Harris suggests, how women throughout history have exploited their sexual power over men, but how pimps like him have come away with the profit. Hypothesis: Harris suggests that it's a mystery how women have exploited men with their sexual power.	Entailment	
Proponent-1	Premise: but get up during every commercial and things like that and you'd be surprised at how much just that little bit adds up you know just gives you a little more activity so. Hypothesis: You won't get any significant exercise by moving around during commercial breaks.	Contradiction	''t'
Proponent-2	Premise: From Chapter 4, a 500 MWe facility will need about 175 tons of steel to install an ACI system, or about 0.35 tons per MWe. Hypothesis: A 500 MWe needs steel to install an ACI system	Entailment	[end]
Opponent-1	Premise: Also exhibited are examples of Linear B type, which was deciphered in 1952 and is of Mycenaean origin showing that by the time the tablet was written the Minoans had lost control of the major cities. Hypothesis: Although Linear B has been deciphered, Linear A is still a mystery.	Contradiction	Mystery
Opponent-2	Premise: The problem isn't so much that men are designed by natural selection to fight as what they're designed to fight women . Hypothesis: Women were designed by natural selection to fight men.	Entailment	women
Test Sentence	Premise:Mykonos has had a head start as far as diving is concerned because it was never banned here (after all, there are no ancient sites to protect) Hypothesis: Diving was banned in places other than Mykonos.	Entailment	
Proponent-1	Premise:and they have a job in jail and they work that they should i and this may sound cruel but i do not think that they should be allowed cigarettes i mean they're in jail for crying out loud what do they need cigarettes for. Hypothesis: I think cigarettes should be banned in prison.	Entailment	banned
Proponent-2	Premise: If I fill in my name and cash it, I pay tax. Hypothesis:I'll have to pay taxes when I cash the check.	Neutral	[end]
Opponent-1	Premise: Already, [interleague play] has restored one of baseball's grandest the passion for arguing about the game, observed the Chicago Tribune . Things could be The Los Angeles Times reports that, thanks to the popularization of baseball in Poland, bats have emerged as a weapon of choice for hooligans, thugs, [and] extortionists. Hypothesis: Baseball bats have been banned in Poland.	Neutral	banned
Opponent-2	Premise: Because of the possible toxicity of thiosulfate to test organisms, a control lacking thiosulfate should be included in toxicity tests utilizing thiosulfate-dechlorinated water. Hypothesis: Because of the possible toxicity of thiosulfate to test organisms, it should be banned.	Neutral	banned