# First is Better Than Last for Language Data Influence

## Abstract

The ability to identify influential training examples enables us to debug training data and explain model behavior. Existing techniques to do so are based on the flow of training data influence through the model parameters (Koh & Liang, 2017; Yeh et al., 2018; Pruthi et al., 2020). For large models in NLP applications, it is often computationally infeasible to study this flow through *all* model parameters, therefore techniques usually pick the last layer of weights. However, we observe that since the activation connected to the last layer of weights contains "shared logic", the data influenced calculated via the last layer weights prone to a "cancellation effect", where the data influence of different examples have large magnitude that contradicts each other. The cancellation effect lowers the discriminative power of the influence score, and deleting influential examples according to this measure often does not change the model's behavior by much. To mitigate this, we propose a technique called TracIn-WE that modifies a method called TracIn (Pruthi et al., 2020) to operate on the word embedding layer instead of the last layer, where the cancellation effect is less severe. One potential concern is that influence based on the word embedding layer may not encode sufficient high level information. However, we find that gradients (unlike embeddings) do not suffer from this, possibly because they chain through higher layers. We show that TracIn-WE significantly outperforms other data influence methods applied on the last layer by $4 - 10\times$ on the case deletion evaluation on three language classification tasks. In addition, TracIn-WE can produce scores not just at the level of the overall training input, but also at the level of words within the training input, a further aid in debugging.

## 1 Introduction

Training data influence methods study the influence of training examples on a model's weights (learned during the training process), and in turn on the predictions of other test examples. They enable us to debug predictions by attributing them to the training examples that most influence them, debug training data by identifying mislabeled examples, and fixing mispredictions via training data curation. While the idea of training data influence originally stems from the study of linear regression (Cook & Weisberg, 1982), it has recently been developed for complex machine learning models like deep networks.

Prominent methods for quantifying training data influence for deep networks include influence functions (Koh & Liang, 2017), representer point selection (Yeh et al., 2018), and TracIn (Pruthi et al., 2020). While the details differ, all methods involves computing the gradients (w.r.t. the loss) of the model parameters at the training and test examples. Thus, they all face a common computational challenge of dealing with the large number of parameters in modern deep networks. In practice, this challenge is circumvented by restricting the study of influence to only the parametersin the last layer of the network. While this choice may not be explicitly stated, it is often implicit in the implementations of larger neural networks. In this work, we revisit the choice of restricting influence computation to the last layer in the context of large-scale Natural Language Processing (NLP) models.

We first introduce the phenomenon of "cancellation effect" of training data influence, which happens when the sum of the influence magnitude among different training examples is much larger than

the actual influence sum. This effect causes most training examples to have a higher magnitude of influence score, and reduces the discriminative power of data influence. We also observe that different weight parameters may have different level of cancellation effects, and the weight parameters of bias parameters and latter layers may have larger cancellation effects. To mitigate the "cancellation effect" and find a scalable algorithm, we propose to operate data influence on weight parameters with the least cancellation effect – the first layer of weight parameter, which is also known as the word embedding layer.

While word embedding representations might have the issue of not capturing any high-level input semantics, we surprisingly find that the gradients of the embedding weights do not suffer from this. Since the gradient chain through the higher layers, it thus takes the high-level information captured in those layers into account. As a result, the gradients of the embedding weights of a word depend on both the context and importance of the word in the input. We develop the idea of word embedding based influence in the context of TracIn due to its computational and resource efficiency over other methods. Our proposed method, TracIn-WE, can be expressed as the sum of word embedding gradient similarity over overlapping words between the training and test examples. Requiring overlapping words between the training and test sentences helps capture low-level similarity, while the word gradient similarity helps capture the high-level semantic similarity between the sentences. A key benefit of TracIn-WE is that it affords a natural word-level decomposition, which is not readily offered by existing methods. This helps us understand which words in the training example drive its influence on the test example.

We evaluate TracIn-WE on several NLP classification tasks, including toxicity, AGnews, and MNLI language inference with transformer models fine-tuned on the task. We show that TracIn-WE outperforms existing influence methods on the case deletion evaluation metric by $4 - 10\times$. A potential criticism of TracIn-WE is its reliance on word overlap between the training and test examples, which would prevent it from estimating influence between examples that relate semantically but not syntactically. To address this, we show that the presence of common tokens in the input, such as a "start" and "end" token (which are commonly found in modern NLP models), allows TracIn-WE to capture influence between semantically related examples without any overlapping words, and outperform last layer based influence methods on a restricted set of training examples that barely overlaps with the test example.

## 2 Preliminaries

Consider the standard supervised learning setting, with inputs $x \in \mathcal{X}$, outputs $y \in \mathcal{Y}$, and training data $\mathbf{D} = \{(x_1, y_1), (x_2, y_2), ...(x_n, y_n)\}$. Suppose we train a predictor $\mathbf{f}$ with parameter $\Theta$ by minimizing some given loss function $\ell$ over the training data, so that $\Theta = \arg\min_{\Theta} \sum_{i=1}^{n} \ell(\mathbf{f}(x_i), y_i)$. In the context of the trained model $\mathbf{f}$, and the training data $\mathbf{D}$, we are interested in the data importance of a training point $x$ to the testing point $x'$, which we generally denote as $\mathbf{I}(x, x')$.

### 2.1 Existing Methods

We first briefly introduce the commonly used training data influence methods: Influence functions (Koh & Liang, 2017), Representer Point selection (Yeh et al., 2018), and TracIn (Pruthi et al., 2020). We demonstrate that each method can be decomposed into a similarity term $S(x, x')$, which measures the similarity between a training point $x$ and the test point $x'$, and loss saliency terms $L(x)$ and $L(x')$, that measures the saliency of the model outputs to the model loss. The decomposition largely derives from an application of chain rule to the parameter gradients.

$$\mathbf{I}(x, x') = L(x)S(x, x')L(x')$$

The decomposition yields the following interpretation. A training data $x$ has a larger influence on a test point $x'$ if (a) the training point model outputs have high loss saliency, (b) the training point $x$ and the test point $x'$ are similar as construed by the model. In Section 3.2, we show that restricting the influence method to operate on the weights in the last layer of the model critically affects the similarity term, and in turn the quality of influence. We now introduce the form of each method, and the corresponding similarity and loss saliency terms.

**Influence Functions:**

$$\text{Inf}(x, x') = -\nabla_{\Theta}\ell(x, \Theta)^T H_{\Theta}^{-1} \nabla_{\Theta}\ell(x', \Theta),$$

where $H_{\Theta}$ is the hessian $\sum_{i=1}^{n} \nabla_{\Theta}^2 \ell(x, \Theta)$ computed over the training examples. By an application of the chain rule, we can see that $\text{Inf}(x, x') = L(x)S(x, x')L(x')$, with the similarity term $S(x, x') = \frac{\partial \mathbf{f}(x, \Theta)}{\partial \Theta}^T H_{\Theta}^{-1} \frac{\partial \mathbf{f}(x', \Theta)}{\partial \Theta}$, and the loss saliency terms $L(x) = \frac{\partial \ell(x, \Theta)}{\partial \mathbf{f}(x, \Theta)}$. The work by Sui et al. (2021) is very similar to extending the influence function to the last layer to satisfy the representer theorem.

**Representer Points:**

$$\text{Rep}(x, x') = -\frac{1}{2\lambda n} \frac{\partial \ell(x, \Theta)}{\partial \mathbf{f}_j(x, \Theta)} a(x, \Theta)^T a(x', \Theta), \tag{1}$$

where $a(x, \Theta)$ is the final activation layer for the data point $x$, $\lambda$ is the strength of the $\ell_2$ regularizer used to optimize $\Theta$, and $j$ is the targeted class to explain. The similarity term is $S(x, x') = a(x, \Theta)^T a(x', \Theta)$, and the loss saliency terms are $L(x) = \frac{1}{2\lambda n} \frac{\partial \ell(x, \Theta)}{\partial \mathbf{f}_j(x, \Theta)}$, $L(x') = 1$.

**TracIn:**

$$\text{TracIn}(x, x') = -\sum_{c=1}^{d} \eta_c \nabla_{\Theta_c} \ell(x, \Theta_c)^T \nabla_{\Theta_c} \ell(x', \Theta_c), \tag{2}$$

where $\Theta_c$ is the weight at checkpoint $c$, and $\eta_c$ is the learning rate at checkpoint $c$. In the remainder of the work, in our notation, we suppress the sum over checkpoints of TracIn for notational simplicity. (This is not to undermine the importance of summing over past checkpoints, which is a crucial component in the working on TracIn.) For TracIn, the similarity term is $S(x, x') = \nabla_\Theta \mathbf{f}(x, \Theta)^T \nabla_\Theta \mathbf{f}(x', \Theta)$, while the loss terms are $L(x) = \frac{\partial \ell(x, \Theta)}{\partial \mathbf{f}(x, \Theta)}$, $L(x') = \frac{\partial \ell(x', \Theta)}{\partial \mathbf{f}(x', \Theta)}$.

## 2.2 Evaluation: Case Deletion

We now discuss our primary evaluation metric, called *case deletion diagnostics* (Cook & Weisberg, 1982), which involves retraining the model after removing influential training examples and measuring the impact on the model. This evaluation metric helps validate the efficacy of any data influence method in detecting training examples to remove or modify for targeted fixing of misclassifications, which is the primary application we consider in this work. This evaluation metric was also noted as a key motivation for influence functions (Koh & Liang, 2017). Given a test example $x'$, when we remove training examples with positive influence on $x'$ (*proponents*), we expect the prediction value for the ground-truth class of $x'$ to decrease. On the other hand, when we remove training examples with negative influence on $x'$ (*opponents*), we expect the prediction value for the ground-truth class of $x'$ to increase. An alternative evaluation metric is based on detecting mislabeled examples via self-influence (i.e. influence of a training sample on that same sample as a test point). We prefer the case deletion evaluation metric, as it more directly corresponds to the concept of data influence. Similar evaluations that measure the change of predictions of the model after a group of points is removed is seen in previous works. Han et al. (2020) measures the test point prediction change after 10% training data with the most and least influence are removed, and Koh et al. (2019) measures the correlation of the model loss change after a group of trained data is removed and the sum of influences of samples in the group, where the group can be seen as manually defined clusters of data.

**Deletion curve.** Given a test example $x'$ and influence measure $\mathbf{I}$, we define the metrics $\text{DEL}_+(x', k, \mathbf{I})$ and $\text{DEL}_-(x', k, \mathbf{I})$ as the impact on the prediction of $x'$ (for its groundtruth class) upon removing top-$k$ proponents and opponents of $x'$ respectively:

$$\text{DEL}_+(x', k, \mathbf{I}) = \mathbb{E}[f_c(x', \Theta_{+;k}) - f_c(x', \Theta)],$$
$$\text{DEL}_-(x', k, \mathbf{I}) = \mathbb{E}[f_c(x', \Theta_{-;k}) - f_c(x', \Theta)],$$

where, $\Theta_{+;k}$ ( $\Theta_{-;k}$) are the model weights learned when top-$k$ proponents (opponents) according to influence measure $I$ are removed from the training set, and $c$ is the groundtruth class of $x'$. The expectation is over the number of retraining runs. We expect $\text{DEL}_+$ to have large negative, and $\text{DEL}_-$ to have large positive values. To evaluate the deletion metric at different values of $k$, we may plot $\text{DEL}_+(x', k, \mathbf{I})$ and $\text{DEL}_-(x', k, \mathbf{I})$ for different values of $k$, and report the area under the curve (AUC): $\text{AUC-DEL}_+ = \sum_{k=k_1}^{k_m} \frac{1}{m} \text{DEL}_+(x', k, \mathbf{I})$, and $\text{AUC-DEL}_- = \sum_{k=k_1}^{k_m} \frac{1}{m} \text{DEL}_-(x', k, \mathbf{I})$.

## 3 Cancellation Effect of Data Influence

The goal of a data influence method is to distribute the test data loss (prediction) across training examples, which can be seen as an attribution problem where each training example is an agent. We observe *cancellation* across the data influence attributions to training examples, i.e., the sign of attributions across training examples disagree and cancels each other out. This leads to most training examples having a large attribution magnitude, which reduces the discriminatory power of attribution-based explanations.

Our next observation is that the cancellation effect varies across different weight parameters. In particular, when a weight parameter is used by most of the training examples, the cancellation effect is especially severe. One such parameter is the bias, whose cancellation effect is illustrated by the following example:

**Example 3.1.** *Consider an example where the input $x \in \mathbb{R}^d$ is sparse, and $x_i$ has feature $i$ with value 1 and all other features with value 0. The prediction function has the form $\mathbf{f}(x) = x \cdot w + b$. It follows that a set of optimal parameters are $w_i = y_i, b = 0$. For a test point $x_t = x_0$, it is clear that $x_0$ should be the most influential training example contributing to reducing the loss of $x_t$, and $w_0$ should be the most influential weight parameter that contributes to it. However, all training examples will influence $x_t$ through the bias parameter $b$, while only $x_0$ can influence $x_t$ through the parameter $w_0$. We also note that the gradients $\frac{\partial L(\mathbf{f}(x_0), y_0)}{\partial w_0}$ and $\frac{\partial L(\mathbf{f}(x_0), y_0)}{\partial b}$ will always be equal mathematically, and thus $TracIn(x_0, x_t)$ will be contributed by parameters $w_0$ and $b$ equally. This will result in the bias parameter $b$, which is not crucial for the model $\mathbf{f}(\cdot)$, to have high influence magnitude but differing signs across all examples.*

The above example illustrates that while the bias parameter is not important for the prediction model (removing the bias can still lead to the same optimal solution), the total influence that flows through the bias is much higher than the influence that flows through each $w_i$. Each training example's gradient will affect the bias but the total contribution will be cancelled out, so the bias will remain 0.

## 3.1 Removing Bias In TracIn Calculation to Reduce Cancellation Effect

To investigate whether removing weights with high cancellation effect really helps improve influence quality, we conducted an experiment on a CNN text classification on Agnews dataset with $87\%$ test accuracy. The model is defined as follows: first a token embedding with dimension 128, followed by two convolution layers with kernel size 5 and filter size 10, one convolution layers with kernel size 1 and filter size 10, a global max pooling layer, and a fully connected layer; all weights are randomly initialized. The first layer is the token embedding, the second layer is the convolution layer, and the last layer is a fully connected layer.

The model has 21222 parameters in total (excluding the token embedding), in which 102 parameters are bias variables. We decompose the TracIn score to TracIn-bias and TracIn-weight

$$\text{TracIn-bias}(x, x') = -\sum_{c=1}^{d} \eta_c \nabla_{\Theta_{b,c}} \ell(x, \Theta_c)^T \nabla_{\Theta_{b,c}} \ell(x', \Theta_c),$$

$$\text{TracIn-weight}(x, x') = -\sum_{c=1}^{d} \eta_c \nabla_{\Theta_{w,c}} \ell(x, \Theta_c)^T \nabla_{\Theta_{w,c}} \ell(x', \Theta_c),$$

which are the TracIn scores contributed from the bias parameters $\Theta_b$ and weight parameters $\Theta_w$ respectively. To measure the cancellation effect, we define the cancellation ratio of a data influence score $\mathbf{I}$ as:

$$C(\mathbf{I}) = \frac{\sum_{x \in \mathcal{X}} \sum_{x' \in \mathcal{X}'} |\mathbf{I}(x, x')|}{|\sum_{x \in \mathcal{X}} \sum_{x' \in \mathcal{X}'} \mathbf{I}(x, x')|},$$

where the cancellation ratio measures the ratio between the sum of influence magnitude and the sum of influence (where the summation is over both training and testing set of points). We find $C(\text{TracIn-bias})$ to be 289.2, and the $C(\text{TracIn-weight})$ to be 31.6, which validates that the bias variables have a much stronger cancellation effect than the weight variables.

To further verify that the TracIn score contributed by the bias may lower the overall discriminatory power, we compute AUC-DEL$_+$ and AUC-DEL$_-$ for TracIn and TracIn-weight on AGnews with our CNN model. The AUC-DEL$_+$ for TracIn and TracIn-weight is $-0.036$ and $-0.065$ respectively, and the AUC-DEL$_+$ for TracIn and TracIn-weight is $0.011$ and $0.046$. The result shows that by removing the TracIn score contributed by the bias (with only 102 parameters), the overall influence quality improves significantly. Thus, in all future experiments, we automatically remove the bias in calculation of data influence if not stated otherwise.

## 3.2 Influence of Latter Layers May Suffer from Cancellation

As mentioned in Section 1, for scalability reasons, most influence methods choose to operate only on the parameters of the last fully-connected layer $\Theta_{\text{last}}$. We argue that this is not a great choice, as the influence scores that stems from the last fully-connected weight layer may suffer from cancellation effect, as different examples "share logics" in the activation representation of this layer. Early layers, where examples have unique logic, may suffer less from the cancellation effect. We report the cancellation ratio for each of the TracIn layer varaint in Table 1, where TracIn-first, TracIn-second, TracIn-third, TracIn-last, TracIn-All refer to TracIn scores based on weights of the first layer, second layer, third layer, last layer, and all layers (the bias is always omitted). As we suspected, early layers suffers less from cancellation, and latter layers suffers more from cancellation.

Table 1: Cancellation Ratio and AUC-DEL table for various layers in CNN model in AGnews.

| Dataset | Metric | TR-first | TR-second | TR-third | TR-last | TR-all |
|---------|--------|----------|-----------|----------|---------|--------|
| AGnews | Cancellation $\downarrow$ | **14.6** | 31.5 | 80.0 | 156.9 | 31.6 |
| | AUC-DEL+ $\downarrow$ | **−0.077** | −0.075 | 0.012 | −0.016 | −0.065 |
| | AUC-DEL− $\uparrow$ | **0.045** | 0.022 | 0.006 | −0.032 | **0.046** |

Table 2: Examples for word similarity for different examples containing word "not".

| Example | Premise | Hypothesis | Label |
|---------|---------|------------|-------|
| S1 | I think he is very annoying. | I do **not** like him. | Entailment |
| S2 | I think reading is very boring. | I do **not** like to read. | Entailment |
| S3 | I think reading is very boring. | I do **not** hate burying myself in books. | Contradiction |
| S4 | She **not** only started playing the piano before she could speak, but her dad taught her to compose music at the same time. | She started to playing music and making music from very long ago. | Entailment |
| S5 | I think he is very annoying. | I don't like him. | Entailment |
| S6 | She thinks reading is pretty boring | She doesn't love to read | Entailment |
| S7 | She not only started playing the piano before she could speak, but her dad taught her to compose music at the same time | She started to playing music and making music from quite long ago | Entailment |

To assess the impact on influence quality, we evaluate the AUC-DEL$_+$ and AUC-DEL$_-$ score for TracIn calculated with different layers on the AGnews CNN model in Tab. 1. We observe that removing examples based on influence scores calculated using parameters of later layers (with more "share" logic) leads to worse deletion score compared to removing examples based on influence scores calculated using parameters of earlier layers (with more "unique logic"). Interestingly, the performance of TracIn-first even outperforms TracIn-all where all parameters are used. We hypothesize that since the TracIn score based on later layers contain too much cancellation, it is actually harmful to include these weight parameters in the TracIn calculation. In the following, we develop data influence methods by only using the first layer of the model, which suffers the least from cancellation effect.

## 4 Word Embedding Based Influence

In the previous section, we argue that using the latter layers to calculate influence may lead to the cancellation effect, which over-estimates influence. Another option is to calculate influence on all weight parameters, but may be computational infeasible when larger models with several millions of parameters are used. To remedy this, we propose operating on the first layer of the model, which contains the less cancellation effect since early layers encodes "unique logit". The first layer for language classification models is usually the word embedding layer in the case of NLP models. However, there are two questions in using the first layer to calculate data influence: 1. the word (token) embedding contains most of the weight parameters, and may be computational expensive 2. the word embedding layer may not capture influential examples through high-level information. In the rest of this section, we develop the idea of word embedding layer based training-data influence in the context of TracIn. We focus on TracIn due to challenges in applying the other methods to the word embedding layer: influence functions on the word embedding layer are computationally infeasible due to the large size (vocab size × embedding_dimension) of the embedding layer, and representer is designed to only use the final layer.. and we show that our proposed influence score is scalable thanks to the sparse nature of word embedding gradients, and contains both low-level and high-level information since the gradient to the word embedding layer can capture both high-level and low-level information about the input sentence.

### 4.1 TracIn on Word Embedding Layer

We now apply TracIn on the word embedding weights, obtaining the following expression:

$$\text{TracIn-WE}(x, x') = -\frac{\partial \ell(x, \Theta)}{\partial \Theta_{\text{WE}}}^T \frac{\partial \ell(x', \Theta)}{\partial \Theta_{\text{WE}}}, \tag{3}$$

Implementing the above form of TracIn-WE would be computationally infeasible as word embedding layers are typically very large (vocab size × embedding dimension). For instance, a BERT-base model has 23M parameters in the word embedding layer. To circumvent this, we leverage the sparsity of word embedding gradients $\frac{\partial \ell(x, \Theta)}{\partial \Theta_{\text{WE}}}$, which is a sparse vector where only embedding weights associated with words that occur in $x$ have non-zero value. Thus, the dot product between two word embedding gradients has non-zero values only for words $w$ that occur in both $x, x'$. With this observation, we can rewrite TracIn-WE as:

$$\text{TracIn-WE}(x, x') = - \sum_{w \in x \cap x'} \frac{\partial \ell(x)}{\partial \Theta_w}^T \cdot \frac{\partial \ell(x')}{\partial \Theta_w}, \tag{4}$$

where $\Theta_w$ are the weights of the word embedding for word $w$. We call the term $\frac{\partial \ell(x)}{\partial \Theta_w}^T \cdot \frac{\partial \ell(x')}{\partial \Theta_w}$ the *word gradient similarity* between sentences $x, x'$ over word $w$.

Table 3: Word Decomposition Examples for TracIn-WE

|  | Sentence content | Label |
|---|---|---|
| Test Sentence 1 - T1 | I can always end my conversations so you would not get any answers because you are too lazy to remember anything | Toxic |
| Test Sentence 2 - T2 | For me, the lazy days of summer is not over yet, and I advise you to please kindly consider to end one's life, thank you | Toxic |
| Train Sentence - S1 | Oh yeah, if you're too lazy to fix tags yourself, you're supporting AI universal takeover in 2020. end it. kill it now. | Non-Toxic |
|  | Word Importance | Total |
| TracIn-WE(S1, T1) | [S]: $-0.28$, [E]: $-0.07$, to: $-0.15$, **lazy**: $-7.6$, you: $-0.3$, end:$-0.3$, too:$-0.3$ | $-9.2$ |
| TracIn-WE(S1, T2) | [S]: $-0.17$, [E]: $-0.23$, to: $0.54$, lazy: $-0.25$, you: $0.25$, **end**: $-3.12$ | $-3.45$ |

## 4.2 Interpreting Word Gradient Similarity

Equation 4 gives the impression that TracIn-WE merely considers a bag-of-words style similarity between the two sentences, and does not take the semantics of the sentences into account. This is surprisingly not true! Notice that for overlapping words, TracIn-WE considers the similarity between gradients of word embeddings. Since gradients are back-propagated through all the intermediate layers in the model, they take into account the semantics encoded in the various layers. This is aligned with the use of word gradient norm $\|\frac{\partial \mathbf{f}(x)}{\partial \Theta_w}\|$ as a measure of importance of the word $w$ to the prediction $\mathbf{f}(x)$ (Wallace et al., 2019; Simonyan et al., 2013). Thus, word gradient similarity would be larger for words that are deemed important to the predictions of the training and test points.

Word gradient similarity is not solely driven by the importance of the word. Surprisingly, we find that word gradient similarity is also larger for overlapping words that appear in similar contexts in the training and test sentences. We illustrate this via an example. Table 2 shows 4 synthetic premise-hypothesis pairs for the Multi-Genre Natural Language Inference (MNLI) task (Williams et al., 2018). An existing pretrained model (He et al., 2020) predicts these examples correctly with softmax probability between $0.65$ and $0.93$. Notice that all examples contain the word 'not' once. The word gradient importance $\|\frac{\partial \mathbf{f}(x)}{\partial \Theta_w}\|$ for "not" is comparable in all 4 sentences. The value of word gradient similarity for 'not' is $0.34$ for the pair S1-S2, and $-0.12$ for S1-S3, while it is $-0.05$ for S1-S4. This large difference stems from the context in which 'not' appears. The absolute similarity value is larger for S1-S2 and S1-S3, since 'not' appears in a negation context in these examples. (The word gradient similarity of S1-S3 is negative since they have different labels.) However, in S4, 'not' appears in the phrase "not only ... but", which is not a negation (or can be considered as double negation). Consequently, word gradient similarity for 'not' is small between S1 and S4. In summary, we expect the absolute value of TracIn-WE score to be large for training and test sentences that have overlapping important words in similar (or strongly opposite) contexts. On the other hand, overlap of unimportant words like stop words would not affect the TracIn-WE score.

## 4.3 Word-Level Decomposition for TracIn-WE

An attractive property of TracIn-WE is that it decomposes into word-level contributions for both the testing point $x'$ and the training point $x$. As shown in (4), word $w$ in $x$ contributes to TracIn-WE$(x, x')$ by the amount $\frac{\partial \ell(x)}{\partial \Theta_w}^T \cdot \frac{\partial \ell(x')}{\partial \Theta_w} \mathbb{1}[w \in x']$; a similar word-level decomposition can be obtained for $x'$. Such a decomposition helps us identify which words in the training point ($x$) drive its influence towards the test point ($x'$). For instance, consider the example in Table. 3, which contains two test sentences (T1, T2) and a training sentence S1. We decompose the score TracIn-WE(S1, T1) and TracIn-WE(S1,T2) into words contributions, and we see that the word "lazy" dominates TracIn-WE(S1, T1), and the word "end" dominates TracIn-WE(S1, T2). This example shows that different key words in a training sentence may drive influence towards different test points. The word decomposition of TracIn-WE is also helpful in applications where we seek to fix mis-classifications by dropping or substituting words in the training examples that most influence it.

Figure 1: Deletion Curve for removing opponents (top figure, larger better) and proponents (bottom figure, smaller better) on Toxicity (left), AGnews (mid), and MNLI (right).

## 4.4 An approximation for TracIn-WE

As we note in Sec. 4.1, the space complexity of saving training and test point gradients scales with the number of words in the sentence. This may be intractable for tasks with very long sentences. We alleviate this by leveraging the fact that the word embedding gradient for a word $w$ is the sum of input word gradients from each position where $w$ is present. Given this decomposition, we can approximate the word embedding gradients by saving only the top-k largest input word gradients for each sentence. (An alternative is to save the input word gradients that are above a certain threshold.) Formally, we define the approximation

$$\frac{\partial \ell(x, \Theta)}{\partial \Theta_w}\Big|_{\text{top-k}} = \sum_{i \in x^{\text{top-k}} \wedge x^i = w} \frac{\partial \ell(x, \Theta)}{\partial x^i} \tag{5}$$

where $x^i$ is the word at position $i$, and $x^{top-k}$ is the set of top-k input positions by gradient norm. We then propose

$$\text{TracIn-WE-Topk}(x, x) = -\sum_{w \in x \cap x'} \frac{\partial \ell(x, \Theta_w)}{\partial \Theta_w}\Big|_{\text{top-k}}^T \cdot \frac{\partial \ell(x', \Theta_w)}{\partial \Theta_w}\Big|_{\text{top-k}}. \tag{6}$$

**Computational complexity** Let $L$ be the max length of each sentence, $d$ be the word embedding dimension, and $o$ be the average overlap between two sentences. If the training and test point gradients are precomputed and saved then the average computation complexity for calculating TracIn-WE for $m$ training points and $n$ testing points is $O(mnod)$. This can be contrasted with the average computation complexity for influence functions on the word embedding layer, which takes $O(mnd^2v^2 + d^3v^3)$, where $v$ is the vocabulary size which is typically larger than $10^4$, and $o$ is typically less than 5. The approximation for TracIn-We-Topk drops the computational complexity from $O(mnod)$ to $O(mno_k d)$ where $o_k$ is the average overlap between the sets of top-k words from the two sentences. It has the additional benefit of preventing unimportant words (ones with small gradient) from dominating the word similarity by multiple occurrences, as such words may get pruned. In all our experiments, we set $k$ to 10 for consistency, and do not tune this hyper-parameter.

## 4.5 Influence without Word-Overlap

One potential criticism of TracIn-WE is that it may not capture any influence when there are no overlapping words between $x$ and $x'$. To address this, we note that modern NLP models often include a "start" and "end" token in all inputs. We posit that gradients of the embedding weights of these tokens take into account the semantics of the input (as represented in the higher layers), and enable TracIn-WE to capture influence between examples that are semantically related but do not have any overlapping words. We illustrate this in S5-S7 in Tab. 2 via examples for the MNLI task. Sentence S5 has no overlapping words with S6 and S7. However, the word gradient similarity of "start" and "end" tokens for the pair S5-S6 is 1.15, while that for the pair S5-S7 is much lower at $-0.05$. Indeed, sentence S5 is more similar to S6 than S7 due to the presence of similar word pairs (e.g., think and thinks, annoying and boring), and the same negation usage. We further validate that TracIn-WE can capture influence from examples without word overlap via a controlled experiment in Sec. 5.

## 5 Experiments

We evaluate the proposed influence methods on 3 different NLP classification datasets with BERT models. We choose a transformer-based model as it has shown great success on a series of down-stream tasks in NLP, and we choose BERT model as it is one of the most commonly used transformer

Table 4: AUC-DEL table for various methods in different datasets.

| Dataset | Metric | Inf-Last | Rep | TR-last | TR-WE | TR-WE-topk | TR-TFIDF |
|---|---|---|---|---|---|---|---|
| Toxic | AUC-DEL+ ↓ | −0.022 | −0.021 | −0.025 | **−0.105** | −0.104 | −0.067 |
| | AUC-DEL− ↑ | −0.001 | 0.006 | 0.007 | 0.122 | **0.125** | 0.044 |
| AGnews | AUC-DEL+ ↓ | −0.025 | −0.021 | −0.032 | −0.148 | **−0.152** | −0.083 |
| | AUC-DEL− ↑ | 0.023 | 0.021 | 0.017 | **0.100** | **0.100** | 0.054 |
| AGnews | AUC-DEL+ ↓ | 0.001 | −0.003 | −0.016 | −0.077 | **−0.094** | −0.072 |
| CNN | AUC-DEL− ↑ | 0.005 | −0.008 | −0.032 | **0.045** | 0.016 | 0.038 |
| MNLI | AUC-DEL+ ↓ | | | | 0.006 | **−0.198** | −0.004 |
| | AUC-DEL− ↑ | | | | 0.026 | **0.169** | 0.005 |

| Dataset | Metric | Inf-Last | Rep | TR-last | TR-WE | TR-WE-topk | TR-WE-NoC |
|---|---|---|---|---|---|---|---|
| Toxic | AUC-DEL+ ↓ | −0.011 | −0.015 | −0.007 | **−0.033** | −0.016 | 0.005 |
| Nooverlap | AUC-DEL− ↑ | 0.013 | 0.012 | 0.013 | **0.043** | 0.042 | −0.002 |

305 model. For the smaller Toxicity and AGnews dataset, we operate on the Bert-Small model, as it
306 already achieves good performance. Additionally, on the AGnews dataset, we include the text CNN
307 models which is trained from scratch to test the generalizability of TracIn-WE to different type
308 of architectures. For the larger MNLI dataset, we choose the Bert-Base model with $110M$ model
309 parameters, which is a decently large model which we believe could represent the effectiveness of
310 our proposed method on large-scale language models. As discussed in Section 2.2, we use the *case*
311 *deletion* evaluation and report the metrics on the deletion curve.

312 **Baselines** One question to ask is whether the good performance of TracIn-WE is a result that it
313 captures the low-level word information well. To answer this question, we design a synthetic data
314 influence score as the TF-IDF similarity Salton & Buckley (1988) multiplied by the loss gradient
315 dot product for $x$ and $x'$. TR-TFIDF can be understood by replacing the embedding similarity of
316 TracIn-Last by the TF-IDF similarity, which captures low level similarity.

$$\text{TR-TFIDF}(x, x') = -\text{Tf-Idf}(x, x') \frac{\partial \ell(x, \Theta)}{\partial \mathbf{f}(x, \Theta)}^T \frac{\partial \ell(x', \Theta)}{\partial \mathbf{f}(x, \Theta)}. \tag{7}$$

317 **Toxicity.** We first experiment on the toxicity comment classification dataset (Kaggle.com, 2018),
318 which contains sentences that are labeled toxic or non-toxic. We randomly choose $50,000$ training
319 samples and $20,000$ validation samples. We then fine-tune a BERT-small model on our training set,
320 which leads to $96\%$ accuracy. Out of the $20,000$ validation samples, we randomly choose 20 toxic
321 and 20 non-toxic samples, for a total of 40 samples as our targeted test set. For each example $x'$ in
322 the test set, we remove top-$k$ proponents and top-$k$ opponents in the training set respectively, and
323 retrain the model to obtain $\text{DEL}_+(x', k, \mathbf{I})$ and $\text{DEL}_-(x', k, \mathbf{I})$ for each influence method $\mathbf{I}$. We vary
324 $k$ over $\{10, 20, \ldots, 100\}$. For each $k$, we retrain the model 10 times and take the average result, and
325 then average over the 40 test points. We implement the methods Influence-last, Representer Points,
326 TracIn-last, TracIn-WE, TracIn-WE-Topk, TracIn-WE-Syn, TracIn-TFIDF (introduced in Sec. E),
327 and abbreviate TracIn with TR in the experiments. The AUC-DEL$_+$ and AUC-DEL$_-$ scores are reported
328 in Table 4. We see that our proposed TracIn-WE method, along with its variants TracIn-WE-Topk
329 outperform other methods by a significant margin. As mentioned in Sec. 3.2, TF-IDF based method
330 beats the existing data influence methods using last layer weights by a decisive margin as well, but is
331 still much worse compared to TracIn-WE. Therefore, TracIn-WE did not succeed by solely using
332 low-level information.

333 **AGnews.** We next experiment on the AG-news-subset (Gulli, 2015; Zhang et al., 2015), which
334 contains a corpus of news with 4 different classes. We follow our setting in toxicity and choose
335 $50,000$ training samples, $20,000$ validation samples, and fine-tune with the same BERT-small model
336 that achieves $90\%$ accuracy on this dataset. We randomly choose 100 samples with 25 from each
337 class as our targeted test set. The AUC-DEL$_+$ and AUC-DEL$_-$ scores for $k \in \{10, 20, \ldots, 100\}$ are
338 reported in Table 4. Again, we see that the variants of TracIn-WE significantly outperform other
339 existing methods applied on the last layer. In both AGnews and Toxicity, removing 10 top-proponents
340 or top-opponents for TracIn-WE has more impact on the test point compared to removing 100
341 top-proponents or top-opponents for TracIn-last. We also highlight that the CNN model trained
342 from scratch shows the same trend as fine-tuning Bert on AGnews, which demonstrates that the
343 effectiveness of TracIn-WE can generalize to different model and different training strategies.

344 **MNLI.** Finally, we test on a larger scale dataset, Multi-Genre Natural Language Inference
345 (MultiNLI) Williams et al. (2018), which consists of $433k$ sentence pairs with textual entailment

information, including entailment, neutral, and contradiction. In this experiment, we use the full training and validation set, and BERT-base which achieves $84\%$ accuracy on matched-MNLI validation set. We choose 30 random samples with 10 from each class as our targeted test set. We only evaluate TracIn-WE-Topk, TracIn-last and TracIn-TFIDF as those were the most efficient methods to run at large scale. We vary $k \in \{20, \ldots, 5000\}$, and the AUC-DEL$_+$ and AUC-DEL$_-$ scores for our test set are reported in Table 4. Unlike previous datasets, here TracIn-TFIDF does not perform better than TracIn-Last, which may be because input similarity for MNLI cannot be merely captured by overlapping words. For instance, a single negation would completely change the label of the sentence. However, we again see TracIn-WE-Topk significantly outperforms TracIn-Last and TracIn-TFIDF, demonstrating its efficacy over natural language understanding tasks as well. This again provides evidence that TracIn-WE can capture both low-level information and high-level information. The deletion curve of Toxicity, AGnews, MNLI is in shown in Fig. 4.5 and Fig. 1.

**No Word Overlap.** To assess whether TracIn-WE can do well in settings where the training and test examples do not have overlapping words, we construct a controlled experiment on the Toxicity dataset. Given a test sentence $x'$, we only consider the top-5000 training sentences (out of $50,000$) with the least word overlap for computing influence. We use TF-IDF similarity to rank the number of word overlaps so that stop word overlap will not be over-weighted. We also find that when the word-embedding layer is fixed during training (result when word-embedding is not fixed is in the appendix, where removing examples based on any influence method does not change the prediction), sentence with no word overlaps carry more influence. The AUC-DEL$_+$ and AUC-DEL$_-$ scores are reported in the lower section of Table 4. We find that TracIn-WE variants can outperform last-layer based influence methods even in this controlled setting, showing that TracIn-WE can retrieve influential examples even without non-trivial word overlaps. In Section 4.5, we claimed that this gain stems from the presence of common tokens ("start", "end"). To validate this, we compared with a controlled variant, TracIn-WE-NoCommon (TR-WE-NoC) where the common tokens are removed from TracIn-WE. As expected, this variant performed much worse on the AUC-DEL$_+$ and AUC-DEL$_-$ scores, thus confirming our claim.

## 6 Related Work

In the field of explainable machine learning, our works belongs to training data importance (Koh & Liang, 2017; Yeh et al., 2018; Jia et al., 2019; Pruthi et al., 2020; Khanna et al., 2018; Sui et al., 2021). Other forms of explanations include feature importance feature-based explanations, gradient-based explanations (Baehrens et al., 2010; Simonyan et al., 2013; Zeiler & Fergus, 2014; Bach et al., 2015; Ancona et al., 2018; Sundararajan et al., 2017; Shrikumar et al., 2017; Ribeiro et al., 2016; Lundberg & Lee, 2017; Yeh et al., 2019; Petsiuk et al., 2018) and perturbation-based explanations (Ribeiro et al., 2016; Lundberg & Lee, 2017; Yeh et al., 2019; Petsiuk et al., 2018), self-explaining models (Wang & Rudin, 2015; Lee et al., 2019; Chen et al., 2019), counterfactuals to change the outcome of the model (Wachter et al., 2017; Dhurandhar et al., 2018; Hendricks et al., 2018; van der Waa et al., 2018; Goyal et al., 2019), concepts of the model (Kim et al., 2018; Zhou et al., 2018). For applications on applying data importance methods on NLP tasks, there have been works identifying data artifacts (Han et al., 2020; Pezeshkpour et al., 2021) and improving models (Han & Tsvetkov, 2020, 2021) based on existing data importance method using the influence function or TracIn. In this work, we discussed weight parameter selection to reduce cancellation effect for training data attribution. There has been works that discuss how to cope with cancellation in the context of feature attribution: Liu et al. (2020) discusses how regularization during training reduces cancellation of feature attribution, Kapishnikov et al. (2021) discusses how to optimize IG paths to minimize cancellation of IG attribution, and Sundararajan et al. (2019) discusses improved visualizations to adjust for cancellation.

## 7 Conclusion

In this work, we revisit the common practice of computing training data influence using only last layer parameters. We show that last layer representations in language classification models can suffer from the cancellation effect, which in turn leads to inferior results on influence. We instead recommend computing influence on the word embedding parameters, and apply this idea to propose a variant of TracIn called TracIn-WE. We show that TracIn-WE significantly outperforms last versions of existing influence methods on three different language classification tasks, on CNN models and transformer models, with trained-from-scratch to fine-tuning training strategy, and also affords a word-level decomposition of influence that aids interpretability.

# References

Ancona, M., Ceolini, E., Öztireli, C., and Gross, M. A unified view of gradient-based attribution methods for deep neural networks. *International Conference on Learning Representations*, 2018.

Bach, S., Binder, A., Montavon, G., Klauschen, F., Müller, K.-R., and Samek, W. On pixel-wise explanations for non-linear classifier decisions by layer-wise relevance propagation. *PloS one*, 10 (7):e0130140, 2015.

Baehrens, D., Schroeter, T., Harmeling, S., Kawanabe, M., Hansen, K., and MÃžller, K.-R. How to explain individual classification decisions. *Journal of Machine Learning Research*, 11(Jun): 1803–1831, 2010.

Barshan, E., Brunet, M.-E., and Dziugaite, G. K. Relatif: Identifying explanatory training samples via relative influence. In *International Conference on Artificial Intelligence and Statistics*, pp. 1899–1909. PMLR, 2020.

Chen, C., Li, O., Tao, D., Barnett, A., Rudin, C., and Su, J. K. This looks like that: deep learning for interpretable image recognition. In *Advances in Neural Information Processing Systems*, pp. 8928–8939, 2019.

Cook, R. D. and Weisberg, S. *Residuals and influence in regression*. New York: Chapman and Hall, 1982.

Dhurandhar, A., Chen, P.-Y., Luss, R., Tu, C.-C., Ting, P., Shanmugam, K., and Das, P. Explanations based on the missing: Towards contrastive explanations with pertinent negatives. In *Advances in Neural Information Processing Systems*, pp. 592–603. NeurIPS, 2018.

Goyal, Y., Wu, Z., Ernst, J., Batra, D., Parikh, D., and Lee, S. Counterfactual visual explanations. In *International Conference on Machine Learning*, pp. 2376–2384. ICML, 2019.

Gulli, A. Ag corpus of news articles. *http://groups.di.unipi.it/ gulli/AG_corpus_of_news_articles.html*, 2015.

Han, X. and Tsvetkov, Y. Fortifying toxic speech detectors against disguised toxicity. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 7732–7739, 2020.

Han, X. and Tsvetkov, Y. Influence tuning: Demoting spurious correlations via instance attribution and instance-driven updates. *arXiv preprint arXiv:2110.03212*, 2021.

Han, X., Wallace, B. C., and Tsvetkov, Y. Explaining black box predictions and unveiling data artifacts through influence functions. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 5553–5563, 2020.

Hanawa, K., Yokoi, S., Hara, S., and Inui, K. Evaluation of similarity-based explanations. In *ICLR*, 2021.

He, P., Liu, X., Gao, J., and Chen, W. Deberta: Decoding-enhanced bert with disentangled attention. *arXiv preprint arXiv:2006.03654*, 2020.

Hendricks, L. A., Hu, R., Darrell, T., and Akata, Z. Grounding visual explanations. In *ECCV*. ECCV, 2018.

Jia, R., Dao, D., Wang, B., Hubis, F. A., Hynes, N., Gürel, N. M., Li, B., Zhang, C., Song, D., and Spanos, C. J. Towards efficient data valuation based on the shapley value. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pp. 1167–1176. PMLR, 2019.

Kaggle.com. Toxic comment classification challenge: Identify and classify toxic online comments. *https://www.kaggle.com/c/jigsaw-toxic-comment-classification-challenge*, 2018.

Kapishnikov, A., Venugopalan, S., Avci, B., Wedin, B., Terry, M., and Bolukbasi, T. Guided integrated gradients: An adaptive path method for removing noise. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 5050–5058, 2021.

Khanna, R., Kim, B., Ghosh, J., and Koyejo, O. Interpreting black box predictions using fisher kernels. *arXiv preprint arXiv:1810.10118*, pp. 3382–3390, 2018.

Kim, B., Wattenberg, M., Gilmer, J., Cai, C., Wexler, J., Viegas, F., et al. Interpretability beyond feature attribution: Quantitative testing with concept activation vectors (tcav). In *International Conference on Machine Learning*, pp. 2673–2682. ICML, 2018.

Koh, P. W. and Liang, P. Understanding black-box predictions via influence functions. In *International Conference on Machine Learning*, pp. 1885–1894. ICML, 2017.

Koh, P. W. W., Ang, K.-S., Teo, H., and Liang, P. S. On the accuracy of influence functions for measuring group effects. *Advances in neural information processing systems*, 32, 2019.

Lee, G.-H., Jin, W., Alvarez-Melis, D., and Jaakkola, T. Functional transparency for structured data: a game-theoretic approach. In *International Conference on Machine Learning*, pp. 3723–3733. PMLR, 2019.

Li, B., Zhou, H., He, J., Wang, M., Yang, Y., and Li, L. On the sentence embeddings from pre-trained language models. *arXiv preprint arXiv:2011.05864*, 2020.

Liu, F., Najmi, A., and Sundararajan, M. The penalty imposed by ablated data augmentation. *arXiv preprint arXiv:2006.04769*, 2020.

Lundberg, S. M. and Lee, S.-I. A unified approach to interpreting model predictions. In *Advances in Neural Information Processing Systems*, pp. 4765–4774. NeurIPS, 2017.

Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., and Duchesnay, E. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

Petsiuk, V., Das, A., and Saenko, K. Rise: Randomized input sampling for explanation of black-box models. *arXiv preprint arXiv:1806.07421*, 2018.

Peyré, G., Cuturi, M., et al. Computational optimal transport: With applications to data science. *Foundations and Trends® in Machine Learning*, 11(5-6):355–607, 2019.

Pezeshkpour, P., Jain, S., Singh, S., and Wallace, B. C. Combining feature and instance attribution to detect artifacts. *arXiv preprint arXiv:2107.00323*, 2021.

Pruthi, G., Liu, F., Kale, S., and Sundararajan, M. Estimating training data influence by tracing gradient descent. *Advances in Neural Information Processing Systems*, 33, 2020.

Ribeiro, M. T., Singh, S., and Guestrin, C. Why should i trust you?: Explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 1135–1144. ACM, 2016.

Salton, G. and Buckley, C. Term-weighting approaches in automatic text retrieval. *Information processing & management*, 24(5):513–523, 1988.

Shrikumar, A., Greenside, P., and Kundaje, A. Learning important features through propagating activation differences. *International Conference on Machine Learning*, 2017.

Simonyan, K., Vedaldi, A., and Zisserman, A. Deep inside convolutional networks: Visualising image classification models and saliency maps. *arXiv preprint arXiv:1312.6034*, 2013.

Sui, Y., Wu, G., and Sanner, S. Representer point selection via local jacobian expansion for post-hoc classifier explanation of deep neural networks and ensemble models. *Advances in Neural Information Processing Systems*, 34, 2021.

Sundararajan, M., Taly, A., and Yan, Q. Axiomatic attribution for deep networks. In *International Conference on Machine Learning*, pp. 3319–3328. PMLR, 2017.

Sundararajan, M., Xu, J., Taly, A., Sayres, R., and Najmi, A. Exploring principled visualizations for deep network attributions. In *IUI Workshops*, volume 4, 2019.

van der Waa, J., Robeer, M., van Diggelen, J., Brinkhuis, M., and Neerincx, M. Contrastive Explanations with Local Foil Trees. In *2018 Workshop on Human Interpretability in Machine Learning (WHI)*. WHI, 2018.

Wachter, S., Mittelstadt, B. D., and Russell, C. Counterfactual explanations without opening the black box: Automated decisions and the gdpr. *European Economics: Microeconomics & Industrial Organization eJournal*, 2017.

Wallace, E., Tuyls, J., Wang, J., Subramanian, S., Gardner, M., and Singh, S. Allennlp interpret: A framework for explaining predictions of nlp models. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP): System Demonstrations*, pp. 7–12, 2019.

Wang, F. and Rudin, C. Falling rule lists. In *Artificial Intelligence and Statistics*, pp. 1013–1022, 2015.

Williams, A., Nangia, N., and Bowman, S. A broad-coverage challenge corpus for sentence understanding through inference. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 1112–1122. Association for Computational Linguistics, 2018. URL http://aclweb.org/anthology/N18-1101.

Yeh, C.-K., Kim, J., Yen, I. E.-H., and Ravikumar, P. K. Representer point selection for explaining deep neural networks. In *Advances in Neural Information Processing Systems*, pp. 9291–9301. NeurIPS, 2018.

Yeh, C.-K., Hsieh, C.-Y., Suggala, A. S., Inouye, D. I., and Ravikumar, P. On the (in)fidelity and sensitivity of explanations. In *NeurIPS*, volume abs/1901.09392, pp. 10965–10976, 2019.

Yu, H., Chen, C., Du, X., Li, Y., Rashwan, A., Hou, L., Jin, P., Yang, F., Liu, F., Kim, J., and Li, J. TensorFlow Model Garden. https://github.com/tensorflow/models, 2020.

Zeiler, M. D. and Fergus, R. Visualizing and understanding convolutional networks. In *European conference on computer vision*, pp. 818–833. Springer, 2014.

Zhang, X., Zhao, J., and LeCun, Y. Character-level convolutional networks for text classification. In *Advances in neural information processing systems*, pp. 649–657, 2015.

Zhou, B., Sun, Y., Bau, D., and Torralba, A. Interpretable basis decomposition for visual explanation. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 119–134. ECCV, 2018.