REGRESSION PRIOR NETWORKS

ABSTRACT

Prior Networks are a class of models which yield interpretable measures of uncertainty and have been shown to outperform state-of-the-art ensemble approaches on a range of tasks. They can also be used to distill an ensemble of models via *Ensemble Distribution Distillation* (EnD^2), such that its accuracy, calibration and uncertainty estimates are retained within a single model. However, Prior Networks have so far been developed only for classification tasks. This work extends Prior Networks and EnD^2 to regression tasks by considering the Normal-Wishart distribution. The properties of Regression Prior Networks are demonstrated on synthetic data, selected UCI datasets and two monocular depth estimation tasks. They yield performance competitive with ensemble approaches.

1 INTRODUCTION

Neural Networks have become the standard approach to addressing a wide range of machine learning tasks (Girshick, 2015; Simonyan & Zisserman, 2015; Villegas et al., 2017; Mikolov et al., 2013b;a; 2010; Hinton et al., 2012; Hannun et al., 2014; Caruana et al., 2015; Alipanahi et al., 2015). However, in order to improve the safety of AI systems (Amodei et al., 2016) and avoid costly mistakes in high-risk applications, such as self-driving cars, it is desirable for models to yield estimates of uncertainty in their predictions. Ensemble methods are known to yield both improved predictive performance and robust uncertainty estimates (Gal & Ghahramani, 2016; Lakshminarayanan et al., 2017; Maddox et al., 2019). Importantly, ensemble approaches allow interpretable measures of uncertainty to be derived via a mathematically consistent probabilistic framework. Specifically, the overall *total uncertainty* can be decomposed into *data uncertainty*, or uncertainty due to inherent noise in the data, and *knowledge uncertainty*, which is due to the model having limited uncertainty of the test data (Malinin, 2019). Uncertainty estimates derived from ensembles have been applied to the detection of misclassifications, out-of-domain inputs and adversarial attack detection (Carlini & Wagner, 2017; Smith & Gal, 2018), and active learning (Kirsch et al., 2019). Unfortunately, ensemble methods may be computationally expensive to train and are always expensive during inference.

A class of models called *Prior Networks* (Malinin & Gales, 2018; 2019; Malinin, 2019) was proposed as an approach to modelling uncertainty in classification tasks by *emulating* an ensemble using a *single* model. Prior Networks parameterize a *higher order* conditional distribution over output distributions, such as the Dirichlet distribution. This enables Prior Networks to efficiently yield the same interpretable measures of *total*, *data* and *knowledge uncertainty* as an ensemble. Unlike ensembles, the behaviour of Prior Networks' higher-order distribution is specified via a loss function, such as reverse KL-divergence (Malinin & Gales, 2019), and training data. However, such Prior Networks yield predictive performance consistent with that of a single model trained via Maximum Likelihood, which is typically worse than that of an ensemble. This can be overcome via Ensemble Distribution Distillation (EnD^2) (Malinin et al., 2020), which is an approach that allows distilling ensembles into Prior Networks such that measures of ensemble diversity are preserved. This enables Prior Networks to retain both the predictive performance and uncertainty estimates of an ensemble at low computational and memory cost.

While Prior Networks have many attractive properties, they have only been applied to classification tasks. In this work we develop Prior Networks for *regression tasks* by considering the Normal-Wishart distribution - a higher-order distribution over the parameters of multivariate normal distributions. We derive all measures of uncertainty, the reverse KL-divergence training objective, and the Ensemble Distribution Distillation objective in closed form. Regression Prior Networks are then evaluated on synthetic data, selected UCI datasets and the NYUv2 and KITTI monocular depth estimation

tasks, where they are shown to yield comparable or better performance to state-of-the-art ensemble approaches. Crucially, they enable, via EnD^2, to retain the predictive performance and uncertainty estimates of an ensemble within a *single model*.

2 REGRESSION PRIOR NETWORKS

In this section we develop Prior Network models for regression tasks. While typical regression models yield point-estimate predictions, we consider *probabilistic regression models* which parameterizes a distribution $p(\boldsymbol{y}|\boldsymbol{x}, \boldsymbol{\theta})$ over the target $\boldsymbol{y} \in \mathcal{R}^K$. Typically, this is a normal distribution:

$$p(\boldsymbol{y}|\boldsymbol{x}, \boldsymbol{\theta}) = \mathcal{N}(\boldsymbol{y}|\boldsymbol{\mu}, \boldsymbol{\Lambda}), \quad \{\boldsymbol{\mu}, \boldsymbol{\Lambda}\} = \boldsymbol{f}(\boldsymbol{x}; \boldsymbol{\theta}) \tag{1}$$

where $\boldsymbol{\mu}$ is the mean, and $\boldsymbol{\Lambda}$ the precision matrix, a positive-definite symmetric matrix. While normal distributions are usually defined in terms of the covariance matrix $\boldsymbol{\Sigma} = \boldsymbol{\Lambda}^{-1}$, parameterization using the precision tends to be more numerically stable during optimization (Bishop, 2006; Goodfellow et al., 2016). While a range of distributions over continuous random variables can be considered, we will the normal as it makes the least assumptions about the nature of $\boldsymbol{y}$ and is mathematically simple.

As in the case for classification, we can consider an ensemble of networks which parameterize multivariate normal distributions $\{p(\boldsymbol{y}|\boldsymbol{x}, \boldsymbol{\theta}^{(m)})\}_{m=1}^M$. This ensemble can be interpreted as a set of draws from a higher-order implicit distribution over normal distributions. A Prior Network for regression would, therefore, emulate this ensemble by explicitly parameterizing a higher-order distribution over the parameters $\boldsymbol{\mu}$ and $\boldsymbol{\Lambda}$ of a normal distribution. One sensible choice is the formidable *Normal-Wishart distribution* (Murphy, 2012; Bishop, 2006), which is a conjugate prior to the multivariate normal distribution. This parallels how the Dirichlet distribution, the conjugate prior to the categorical, was used in classification Prior Networks. The Normal-Wishart distribution is defined as follows:

$$\mathcal{NW}(\boldsymbol{\mu}, \boldsymbol{\Lambda}|\boldsymbol{m}, \boldsymbol{L}, \kappa, \nu) = \mathcal{N}(\boldsymbol{\mu}|\boldsymbol{m}, \kappa\boldsymbol{\Lambda})\mathcal{W}(\boldsymbol{\Lambda}|\boldsymbol{L}, \nu) \tag{2}$$

where $\boldsymbol{m}$ and $\boldsymbol{L}$ are the *prior mean* and inverse of the positive-definite *prior scatter matrix*, while κ and ν are the strengths of belief in each prior, respectively. The parameters κ and ν are conceptually similar to *precision* of the Dirichlet distribution α_0. The Normal-Wishart is a compound distribution which decomposes into a product of a conditional normal distribution over the mean and an Wishart distribution over the precision. Thus, a Regression Prior Network parameterizes the Normal-Wishart distribution over the mean and precision of normal output distributions as follows:

$$p(\boldsymbol{\mu}, \boldsymbol{\Lambda}|\boldsymbol{x}, \boldsymbol{\theta}) = \mathcal{NW}(\boldsymbol{\mu}, \boldsymbol{\Lambda}|\boldsymbol{m}, \boldsymbol{L}, \kappa, \nu), \quad \{\boldsymbol{m}, \boldsymbol{L}, \kappa, \nu\} = \boldsymbol{\Omega} = \boldsymbol{f}(\boldsymbol{x}; \boldsymbol{\theta}) \tag{3}$$

where $\boldsymbol{\Omega} = \{\boldsymbol{m}, \boldsymbol{L}, \kappa, \nu\}$ is the set of parameters of the Normal-Wishart predicted by neural network. The posterior predictive of this model is the multivariate Student's $\mathcal{T}$ distribution (Murphy, 2012), which is the heavy-tailed generalization of the multivariate normal distribution:

$$p(\boldsymbol{y}|\boldsymbol{x}, \boldsymbol{\theta}) = \mathbb{E}_{p(\boldsymbol{\mu}, \boldsymbol{\Lambda}|\boldsymbol{x}, \boldsymbol{\theta})}[p(\boldsymbol{y}|\boldsymbol{\mu}, \boldsymbol{\Lambda})] = \mathcal{T}(\boldsymbol{y}|\boldsymbol{m}, \frac{\kappa + 1}{\kappa(\nu - K + 1)}\boldsymbol{L}^{-1}, \nu - K + 1) \tag{4}$$

In the limit, as $\nu \to \infty$, the $\mathcal{T}$ distribution converges to a normal distribution. The predictive posterior of the Prior Network given in equation 4 only has a defined mean and variance when $\nu > K + 1$.

Figure 1 depicts the desired behaviour of an ensemble of normal distributions sampled from a Normal-Wishart distribution. Specifically the ensemble should be consistent for in-domain inputs in regions of low/high *data uncertainty*, as in figures 1a-b, and highly diverse both in the location of the mean and in the structure of the covariance for out-of-distribution inputs, as in figure 1c. Samples of continuous output distributions from a regression Prior Network should yield the same behaviour.

2.1 MEASURES OF UNCERTAINTY

Given a Normal-Wishart Prior Network which displays the behaviours above, it is possible to compute closed-form expression for all uncertainty measures previously discussed for ensembles and Dirichlet Prior Networks (Malinin, 2019). By considering the mutual information between the target $\boldsymbol{y}$ and the

Figure 1: Desired behaviors of an ensemble of regression models. The bottom row displays the desired Normal-Wishart Distribution and the top row depicts Normal Distributions samples from it.

parameters of the output distribution $\{\boldsymbol{\mu}, \boldsymbol{\Lambda}\}$, we can obtain measures of *knowledge*, *total* and *data uncertainty*:

$$\underbrace{\mathcal{I}[\boldsymbol{y}, \{\boldsymbol{\mu}, \boldsymbol{\Lambda}\}]}_{\text{Knowledge Uncertainty}} = \underbrace{\mathcal{H}\big[\mathbb{E}_{\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda}|\boldsymbol{x}, \boldsymbol{\theta})}[\mathrm{p}(\boldsymbol{y}|\boldsymbol{\mu}, \boldsymbol{\Lambda})]\big]}_{\text{Total Uncertainty}} - \underbrace{\mathbb{E}_{\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda}|\boldsymbol{x}, \boldsymbol{\theta})}\big[\mathcal{H}[\mathrm{p}(\boldsymbol{y}|\boldsymbol{\mu}, \boldsymbol{\Lambda})]\big]}_{\text{Expected Data Uncertainty}} \tag{5}$$

This expression consists of the difference between the differential entropy of the posterior predictive and the expected differential entropy of draws from the Normal-Wishart prior. We can also consider the *expected pairwise KL-divergence* (EPKL) between draws from the Normal-Wishart prior:

$$\mathcal{K}[\boldsymbol{y}, \{\boldsymbol{\mu}, \boldsymbol{\Lambda}\}] = - \mathbb{E}_{\mathrm{p}(\boldsymbol{y}|\boldsymbol{x}, \boldsymbol{\theta})}[\mathbb{E}_{\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda}|\boldsymbol{x}, \boldsymbol{\theta})}[\ln \mathrm{p}(\boldsymbol{y}|\boldsymbol{\mu}, \boldsymbol{\Lambda})]] - \mathbb{E}_{\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda}|\boldsymbol{x}, \boldsymbol{\theta})}\big[\mathcal{H}[\mathrm{p}(\boldsymbol{y}|\boldsymbol{\mu}, \boldsymbol{\Lambda})]\big] \tag{6}$$

This is an upper bound on mutual information (Malinin, 2019). Notably, estimates of data uncertainty are unchanged. One practical use of EPKL is comparison with ensembles, as it is not possible to obtain a tractable expression for the mutual information of a regression ensemble (Malinin, 2019). Alternatively, we can consider measures of uncertainty derived via the law of total variance:

$$\underbrace{\mathbb{V}_{\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda}|\boldsymbol{x}, \boldsymbol{\theta})}[\boldsymbol{\mu}]}_{\text{Knowledge Uncertainty}} = \underbrace{\mathbb{V}_{\mathrm{p}(\boldsymbol{y}|\boldsymbol{x}, \boldsymbol{\theta})}[\boldsymbol{y}]}_{\text{Total Uncertainty}} - \underbrace{\mathbb{E}_{\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda}|\boldsymbol{x}, \boldsymbol{\theta})}[\boldsymbol{\Lambda}^{-1}]}_{\text{Expected Data Uncertainty}} \tag{7}$$

This yields a similar decomposition to mutual information, but only first and second moments are considered. We provide closed-form expressions of (5)-(7) in appendix A. Note, however, that these variance-based measures are *not* scale-invariant, and are therefore sensitive to the scale of predictions which the model makes. We omit the closed-form expressions for all terms here and instead provide them in appendix A.

2.2 TRAINING OBJECTIVES

Having discussed how to construct Prior Networks for regression, we now discuss how they can be trained. Prior Networks are trained using a multi-task loss, where an in-domain loss $\mathcal{L}_{in}$ and an out-of-distribution (OOD) loss $\mathcal{L}_{out}$ are jointly minimized:

$$\mathcal{L}(\boldsymbol{\theta}, \mathcal{D}_{tr}, \mathcal{D}_{out}) = \mathbb{E}_{\mathrm{p}_{tr}(\boldsymbol{y}, \boldsymbol{x})}\big[\mathcal{L}_{in}(\boldsymbol{y}, \boldsymbol{x}, \boldsymbol{\theta})\big] + \gamma \cdot \mathbb{E}_{\mathrm{p}_{out}(\boldsymbol{x})}\big[\mathcal{L}_{out}(\boldsymbol{x}, \boldsymbol{\theta})\big] \tag{8}$$

The OOD loss is necessary to teach the model the limit of its knowledge (Malinin, 2019). Normal distributions sampled from a Prior Network should be consistent and reflect the correct level of *data uncertainty* in-domain, and diverse in both mean and precision out-of-domain. Achieving the former is challenging, as the training data only consists of samples of inputs $\boldsymbol{x}$ and targets $\boldsymbol{y}$, there is no access to the underlying distribution, and associated data uncertainty, represented by the precision

$\boldsymbol{\Lambda}$. Effectively, we are attempting to train a Normal-Wishart distribution from targets sampled from normal distribution that are sampled from the Normal-Wishart, rather than on the normal distribution samples themselves, which is challenging. However, it was shown that for Dirichlet Prior Networks minimizing the *reverse* KL-divergence between the model and an appropriate target Dirichlet *induces in expectation* the correct estimate of *data uncertainty* (Malinin & Gales, 2019). As the Normal-Wishart, like the Dirichlet, is a conjugate prior and exponential family member, the precision can be *induced in expectation* by considering the *reverse* KL-divergence between the model $\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{x}, \boldsymbol{\theta})$ and a target Normal-Wishart $\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \hat{\boldsymbol{\Omega}}^{(i)})$ corresponding to each $\boldsymbol{x}^{(i)}$. The appropriate Normal-Wishart is specified via Bayes's rule:

$$\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \hat{\boldsymbol{\Omega}}^{(i)}) \propto \mathrm{p}(\boldsymbol{y}^{(i)} | \boldsymbol{\mu}, \boldsymbol{\Lambda})^{\hat{\beta}} \mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{\Omega}_0) \tag{9}$$

where $\boldsymbol{\Omega}_0 = \{\boldsymbol{m}_0, \boldsymbol{L}_0, \kappa_0, \nu_0\}$ are the parameters of the prior defined as follows:

$$\boldsymbol{m}_0 = \frac{1}{N} \sum_{i=1}^{N} \boldsymbol{y}^{(i)}, \ \boldsymbol{L}_0^{-1} = \frac{\nu_0}{N} \sum_{i=1}^{N} (\boldsymbol{y}^{(i)} - \boldsymbol{m}_0)(\boldsymbol{y}^{(i)} - \boldsymbol{m}_0)^{\mathrm{T}}, \ \kappa_0 = \epsilon, \ \nu_0 = K + 1 + \epsilon \tag{10}$$

In other words, we consider a *semi-informative prior* which corresponds to the mean and scatter matrix of marginal distribution $\mathrm{p}(\boldsymbol{y})$, and we see each sample of the training data $\hat{\beta}$ times. The hyper-parameter $\hat{\beta}$ allows us to weigh the effect of the prior and the data. ϵ is a small value, like 10^{-2}, so that κ_0 and ν_0 yield a maximally un-informative, but proper predictive posterior. The reason to use a semi-informative prior is because in regression tasks, unlike classification tasks, uninformative priors are improper and lead to infinite differential entropy. Furthermore, we do know *something* about the data purely based on the marginal distribution, and it is sensible to use that as the prior. The reverse KL-divergence loss can then be expressed as:

$$\begin{aligned} \mathcal{L}(\boldsymbol{y}, \boldsymbol{x}, \boldsymbol{\theta}; \hat{\beta}, \boldsymbol{\Omega}_0) &= \mathrm{KL}[\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{x}, \boldsymbol{\theta}) \| \mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \hat{\boldsymbol{\Omega}}^{(i)})] \\ &= \hat{\beta} \cdot \mathbb{E}_{\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{x}, \boldsymbol{\theta})} \big[- \ln \mathrm{p}(\boldsymbol{y} | \boldsymbol{\mu}, \boldsymbol{\Lambda}) \big] + \mathrm{KL}[\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{x}, \boldsymbol{\theta}) \| \mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{\Omega}_0)] + Z \end{aligned} \tag{11}$$

where Z is a normalization constant. For in-domain data $\hat{\beta}$ can be set to a large value, and for out-of-domain training data $\hat{\beta} = 0$, so that the model regresses to the prior. In-domain the prior will add a degree of smoothing which may prevent over-fitting and improve performance on small datasets. The derivation and closed form expression for this loss is provided in appendix A.

2.3 ENSEMBLE DISTRIBUTION DISTILLATION

An interesting task which Prior Networks can solve is *Ensemble Distribution Distillation* (EnD^2) (Malinin et al., 2020), where the distribution of an ensemble's predictions is distilled into a single model. EnD^2 enables retaining an ensemble's improved predictive performance and uncertainty estimates within a single model at low cost. In contrast, standard Ensemble Distillation (EnD), which minimizes the KL-divergence between a model and the ensemble, loses information about ensemble diversity.

Consider an ensemble $\{\mathrm{p}(\boldsymbol{y} | \boldsymbol{x}, \boldsymbol{\theta}^{(m)})\}_{m=1}^{M}$, where each model yields the mean and precision of a normal distribution. We can define an empirical distribution over the mean and precision as follows:

$$\hat{\mathrm{p}}(\boldsymbol{\mu}, \boldsymbol{\Lambda}, \boldsymbol{x}) = \big\{ \{\boldsymbol{\mu}^{(mi)}, \boldsymbol{\Lambda}^{(mi)}\}_{m=1}^{M}, \boldsymbol{x}^{(i)} \big\}_{i=1}^{N} = \mathcal{D}_{trn} \tag{12}$$

EnD^2 can then be accomplished by minimizing the negative log-likelihood of the ensemble's mean and precision under the Normal-Wishart prior:

$$\mathcal{L}(\boldsymbol{\phi}, \mathcal{D}_{trn}) = \mathbb{E}_{\hat{\mathrm{p}}(\boldsymbol{\mu}, \boldsymbol{\Lambda}, \boldsymbol{x})} \big[- \ln \mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{x}; \boldsymbol{\phi}) \big] = \mathbb{E}_{\hat{\mathrm{p}}(\boldsymbol{x})} \big[\mathrm{KL}[\hat{\mathrm{p}}(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{x}) \| \mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{x}; \boldsymbol{\phi})] \big] + Z \tag{13}$$

This is equivalent to minimizing the KL-divergence between the model and the empirical distribution of the ensemble. Note that here, unlike in the previous section, the parameters of a normal distribution are available for every input $\boldsymbol{x}$, making forward KL-divergence the appropriate loss function. However, while this is a theoretically sound approach, the optimization might be numerically challenging. Similarly to (Malinin et al., 2020) we propose a temperature-annealing trick to make the optimization

process easier. First, the ensemble is reduced to it's mean:

$$\boldsymbol{\mu}_T^{(mi)} = \frac{2}{T+1}\boldsymbol{\mu}^{(mi)} + \frac{T-1}{T+1}\bar{\boldsymbol{\mu}}^{(i)}, \quad \bar{\boldsymbol{\mu}}^{(i)} = \frac{1}{M}\sum_{m=1}^{M}\boldsymbol{\mu}^{(mi)}$$

$$\boldsymbol{\Lambda}_T^{-1(mi)} = \frac{2}{T+1}\boldsymbol{\Lambda}^{-1(mi)} + \frac{T-1}{T+1}\bar{\boldsymbol{\Lambda}}^{-1(i)}, \quad \bar{\boldsymbol{\Lambda}}^{-1(i)} = \frac{1}{M}\sum_{m=1}^{M}\bar{\boldsymbol{\Lambda}}^{-1(mi)}$$

$$(14)$$

In the expression above we use inverses of the precision matrix $\boldsymbol{\Lambda}$ because we are actually interpolating the covariance matrices $\boldsymbol{\Sigma}$. Secondly, the predicted $\tilde{\kappa} = T\kappa$ and $\tilde{\nu} = T\nu$ are multiplied by T in order to make the Normal-Wishart also sharp around the mean. The loss is *divided* by T in order to avoid scaling the gradients by T, yielding:

$$\mathrm{p}_T(\boldsymbol{\mu},\boldsymbol{\Lambda}|\boldsymbol{x},\boldsymbol{\phi}) = \mathcal{NW}(\boldsymbol{\mu},\boldsymbol{\Lambda}|\boldsymbol{m},\boldsymbol{L},T\kappa,T\nu), \quad \{\boldsymbol{m},\boldsymbol{L},\kappa,\nu\} = \boldsymbol{f}(\boldsymbol{x};\boldsymbol{\phi})$$

$$\mathcal{L}(\boldsymbol{\phi},\mathcal{D}_{trn};T) = \frac{1}{T}\mathbb{E}_{\hat{\mathrm{p}}_T(\boldsymbol{\mu},\boldsymbol{\Lambda},\boldsymbol{x})}\big[-\ln\mathrm{p}_T(\boldsymbol{\mu},\boldsymbol{\Lambda}|\boldsymbol{x};T,\boldsymbol{\phi})\big]$$

$$(15)$$

This splits learning into two phases. First, when temperature is high, the model learns to match the ensemble's mean (first moment). Second, as the temperature is annealed down to 1, the model will gradually focus on learning higher moments of the ensemble's distribution. This trick may be necessary, as the ensemble may have a highly non-Normal-Wishart distribution, which may be challenging to learn. Note, that for EnD^2 it may be better to parameterize the *Normal-inverse-Wishart* distribution over the mean and covariance, due to numerical stability concerns. However, for consistency, we describe EnD^2 in terms of the Normal-Wishart. Finally, we emphasize that EnD^2 does not require OOD training data, unlike the RKL objective above. This eliminates the non-trivial challenge of finding appropriate OOD data.

3 EXPERIMENTS ON SYNTHETIC DATA

(a) Input Data (b) Total Uncertainty (c) Data Uncertainty (d) Know. Uncertainty

Figure 2: Comparison of different models on synthetic data $y \sim \mathcal{N}(\sin x + \frac{x}{10}, \frac{1}{|x|+1} + 0.01)$. Gray area indicates training data region.

We first examine Regression Prior Networks on a synthetic one-dimensional dataset with additive heteroscedastic noise. We compare Regression Prior Network trained via RKL (NWPN) and distribution-distillation of an ensemble (EnD^2) to Deep Ensembles. The ensemble consists of 10 models which yield a Normal output distribution and are trained via maximum likelihood. All models use the same 2-layer architecture with 30 ReLU units. Details of the setup are available in appendix B. The NWPN was trained via reverse KL-divergence (11) and Ensemble Distribution Distillation done as described in section 2.3. In-domain training data for all models is sampled between [-10,10] and OOD training data for the NWPN model is sampled from $[-25, 20] \cup [20, 25]$. Measures of *total*, *data* and *knowledge uncertainty* are obtained via the law of total variance (7).

The results presented in Figure 2 show several trends. Firstly, the total uncertainty of all models is high in the region of high heteroscedastic noise as well as out-of-domain. Secondly, *total uncertainty* decomposes into *data uncertainty* and *knowledge uncertainty*. The former is high in the region of high heteroscedastic noise and has undefined behaviour out-of-domain, while the latter is low in-domain and large out-of-distribution. Third, EnD^2 successfully replicates ensemble's estimates of uncertainty,

though they are consistently larger, especially estimates of *data uncertainty* out-of-domain. This is a consequence of the ensemble being non-Normal-Wishart distributed when it is diverse, leading the EnD^2 Prior Network to over-estimate support. Thus, these results validate the principle claims that Regression Prior Networks can emulate the behaviour of an ensemble via multi-task training using the RKL objective or via EnD^2, and that they yield interpretable measures of uncertainty.

4 EXPERIMENTS ON UCI DATA

In this section we evaluate Normal-Wishart Prior Networks trained via reverse-KL divergence (11) (NWPN) and Ensemble Distribution Distillation (EnD^2) relative to a Deep-Ensemble baseline on selected UCI datasets. Other ensemble-methods are not considered, as Deep Ensemble have been shown to consistently outperform them using fewer ensemble members (Ashukha et al., 2020; Ovadia et al., 2019; Fort et al., 2019). Results on remaining UCI datasets are available in appendix C. We follow the experimental setup of (Lakshminarayanan et al., 2017) with several changes, detailed in appendix C. Out-of-distribution training data for Prior Networks trained via RKL is generated using factor analysis with increased noise and latent variance as in (Malinin, 2019). Table 1 shows a comparison of all models in terms of NLL and RMSE. Unsurprisingly, ensembles yield the best RMSE, though both NWPN and EnD^2 give generally comparable NLL scores. Furthermore, EnD^2 comes close to or matches the performance of the ensemble and outperforms NWPN. This is expected, as NWPN is a single model trained with RKL, which is an upper-bound on NLL.

Table 1: RMSE and NLL of models on UCI datasets. Datasets listed in order of increasing size.

Data	RMSE ($\downarrow$)				NLL ($\downarrow$)			
	Single	ENSM	EnD^2	NWPN	Single	ENSM	EnD^2	NWPN
wine	0.65 ± 0.01	$\mathbf{0.63 \pm 0.01}$	$\mathbf{0.63 \pm 0.01}$	$\mathbf{0.63 \pm 0.01}$	1.24 ± 0.16	0.96 ± 0.03	$\mathbf{0.91 \pm 0.02}$	0.93 ± 0.02
power	4.07 ± 0.07	$\mathbf{4.00 \pm 0.07}$	4.06 ± 0.07	4.09 ± 0.07	2.82 ± 0.02	$\mathbf{2.79 \pm 0.02}$	$\mathbf{2.79 \pm 0.01}$	2.81 ± 0.01
MSD	9.08 ± 0.00	$\mathbf{8.92 \pm 0.00}$	8.94 ± 0.00	9.07 ± 0.00	3.51 ± 0.00	$\mathbf{3.39 \pm 0.00}$	$\mathbf{3.39 \pm 0.00}$	3.41 ± 0.00

In Table 2 we compare uncertainty measures derived from all models on the tasks of error detection and OOD detection, which are evaluated using Prediction Rejection Ratio (PRR) (Malinin et al., 2020; Malinin, 2019) and AUC-ROC (Hendrycks & Gimpel, 2016), respectively. Finding 'real' out-of-domain data for UCI datasets it challenging, so we construct a synthetic OOD dataset for an in-domain UCI dataset with K columns by taking first K non-constant columns from a *different* UCI dataset. Columns of each OOD dataset are normalized using statistics derived from the in-domain training dataset. Details are available in appendix C.

The results show that all models achieve comparable error-detection using measures of *total uncertainty*. In terms of OOD detection, EnD^2 generally reproduces the ensemble's behaviour, while NWPN usually performs worse. However, on the MSD dataset NWPN yields the best performance. This may be due to the nature of the OOD training data - it may simply be better suited to MSD OOD detection. Furthermore, the UCI datasets are generally small and have low input dimensionality - MSD, the largest, has 95 features. It is therefore difficult to assess the superiority of any particular model on these simple datasets - all we can say that they generally perform comparably. A more complex, larger-scale, task is required to properly validate regression Prior Networks.

Table 2: PRR and OOD detection scores

Data	Model	PRR ($\uparrow$)		AUC-ROC ($\uparrow$)		
		$\mathcal{H}[\mathbb{E}]$	$\mathbb{V}[\boldsymbol{y}]$	$\mathcal{I}$	$\mathcal{K}$	$\mathbb{V}[\boldsymbol{\mu}]$
	ENSM	-	$\mathbf{0.32 \pm 0.02}$	-	0.58 ± 0.01	0.56 ± 0.02
wine	EnD^2	0.30 ± 0.02	0.30 ± 0.02	$\mathbf{0.65 \pm 0.01}$	$\mathbf{0.65 \pm 0.01}$	$\mathbf{0.65 \pm 0.03}$
	NWPN	0.30 ± 0.03	0.30 ± 0.03	0.64 ± 0.01	0.64 ± 0.01	0.53 ± 0.02
	ENSM	-	$\mathbf{0.23 \pm 0.01}$	-	0.64 ± 0.02	0.62 ± 0.02
power	EnD^2	$\mathbf{0.23 \pm 0.01}$	$\mathbf{0.23 \pm 0.01}$	$\mathbf{0.66 \pm 0.01}$	$\mathbf{0.66 \pm 0.01}$	0.50 ± 0.02
	NWPN	0.20 ± 0.02	0.20 ± 0.02	0.56 ± 0.01	0.56 ± 0.01	0.31 ± 0.02
	ENSM	-	$\mathbf{0.64 \pm 0.00}$	-	0.55 ± 0.0	0.62 ± 0.0
msd	EnD^2	0.63 ± 0.00	0.63 ± 0.00	0.50 ± 0.0	0.50 ± 0.0	0.65 ± 0.0
	NWPN	$\mathbf{0.64 \pm 0.00}$	$\mathbf{0.64 \pm 0.00}$	0.73 ± 0.0	0.73 ± 0.0	$\mathbf{0.75 \pm 0.0}$

5 MONOCULAR DEPTH ESTIMATION EXPERIMENTS

Having established that the proposed methods work on par with or better than ensemble methods on the UCI datasets, we now examine them on the large-scale NYU Depth v2 (Nathan Silberman & Fergus, 2012) and KITTI (Menze & Geiger, 2015) depth-estimation tasks. We evaluate RPNs trained both via RKL and EnD^2. In this work the base model is DenseDepth (DD) which defines a U-Net like architecture on top of DenseNet-169 features (Alhashim & Wonka, 2018). The original approach trains it on inverted targets using a combination of L1, SSIM and Image-Gradient losses. We replace this with NLL training using a model which yields mean and precision for each pixel (Single). The data pre-processing, augmentation, optimization and evaluation protocol are kept unchanged. On the challenging KITTI benchmark (Geiger et al., 2013) all models are evaluated on the split proposed by (Eigen et al., 2014). The baselines are a single Gaussian model and a Deep-Ensemble of 5 Gaussian models (ENSM). Other ensemble-methods are not considered, as Deep Ensembles consistently outperform them (Ashukha et al., 2020; Ovadia et al., 2019). We then distribution-distilled the ensemble into a Regression Prior Network (EnD^2) with a per-pixel Normal-Wishart distribution. Additionally, we compare training RPN with the RKL loss function (NWPN). On the NYU dataset we take KITTI as OOD traning data. On KITTI, we use NYU as OOD training data. Finally, we also consider standard ensemble distillation (EnD). All experiments are repeated 4 times and we report mean. Distribution-distillation is done with temperature annealing ($T = 1.0$ vs. $T = 10.0$). For $T = 10.0$ we train with initial temperature for 20% of epochs, linearly decay it to 1.0 during 60% of epochs, fine-tune with $T = 1.0$ for the last 20% of epochs. While not improving performance, we found it to greatly stabilizes training.

Results in table 3 show several trends. First, probabilistic models outperform the original DenseDepth model in this setup. Second, EnD^2 achieve predictive performance closest to the ensemble, both in terms of standard Depth-Estimation metrics, and in terms of test-set negative-log-likelihood (a metric of calibration). Surprisingly, EnD^2 yields predictions which are better calibrated than ensembles. This may be due to the ensemble being poorly modelled by a Normal-Wishart distribution, leading the Prior Network to over-estimate the support of the distribution. As a consequence, the EnD^2 is less confident, and therefore better calibrated. Finally, standard ensemble distillation (EnD) achieves very poor predictive and calibration performance. This may be an artifact of trying to model a mixture of Gaussians with a single Gaussian.

Table 3: Predictive Performance comparison

Method	NYUv2 Predictive Performance							KITTI Predictive Performance						
	$\delta_1(\uparrow)$	$\delta_2(\uparrow)$	$\delta_3(\uparrow)$	rel($\downarrow$)	rmse($\downarrow$)	$\log_{10}(\downarrow)$	NLL($\downarrow$)	$\delta_1(\uparrow)$	$\delta_2(\uparrow)$	$\delta_3(\uparrow)$	rel($\downarrow$)	rmse($\downarrow$)	$\log_{10}(\downarrow)$	NLL($\downarrow$)
DD	0.847	0.972	0.993	0.124	0.468	0.054	-	0.886	0.965	0.986	0.093	4.170	-	-
ENSM 5	**0.862**	**0.975**	**0.994**	**0.117**	**0.438**	**0.051**	0.76	**0.932**	**0.989**	**0.998**	**0.073**	**3.355**	**0.032**	1.94
Single	0.852	0.971	0.993	0.122	0.456	0.053	5.74	0.924	0.987	0.997	0.078	3.545	0.034	2.98
NWPN	0.842	0.968	0.992	0.126	0.472	0.055	**-1.60**	0.920	0.986	0.997	0.077	3.525	0.035	1.52
EnD	0.851	0.971	0.993	0.122	0.458	0.053	9.11	0.915	0.984	0.997	0.079	3.936	0.036	3.27
EnD^2	0.855	0.972	0.993	0.120	0.451	0.052	-1.47	0.928	0.988	0.998	0.075	3.367	0.033	**1.42**

In table 4 we asses all models on the task of out-of-domain input detection. Two OOD test-datasets are considered: LSUN-church (LSN-C) and LSUN-bed (LSN-B) (Yu et al., 2015), which consist of images of churches and bedrooms. The latter is most similar to NYU Depth-V2 and more challenging to detect. Both datasets are very different from KITTI, which consists of outdoor images of roads. OOD images are center-cropped and re-scaled to the in-domain data. Results show several trends. First, EnD^2 consistently outperforms the original ensemble using measures of *knowledge uncertainty* ($\mathcal{I}$, $\mathcal{K}$ and $\mathbb{V}[\boldsymbol{\mu}]$). However, when considering measures of *total uncertainty* ($\mathcal{H}[\mathbb{E}]$, $\mathbb{V}[\boldsymbol{y}]$), the ensemble tends to yield superior performance on NYU. This is likely due to over-estimation of the support of the ensemble's distribution by EnD^2. Second, OOD detection is easier on more-mismatched datasets. Third, standard ensemble distillation (EnD) does much worse than even a single model, which was an effect that was also observed for classification models in (Malinin et al., 2020). Finally, variance-based measures outperform information-theoretic measures of *total uncertainty*, and sometimes *knowledge uncertainty* on NYU, but do exceptionally poorly on KITTI. This is a result of their sensitivity to scale. The models predict very low depth values for OOD data, which means that they have lower entropy and variance. In contrast, MI and EPKL, which are scale invariant, are not affected.

Table 4: OOD detection % AUC-ROC ($\uparrow$) comparison

Method	OOD	NYUv2 vs LSUN OOD Detection					KITTI vs LSUN OOD Detection				
		$\mathcal{H}[\mathbb{E}]$	$\mathbb{V}[\boldsymbol{y}]$	$\mathcal{I}$	$\mathcal{K}$	$\mathbb{V}[\boldsymbol{\mu}]$	$\mathcal{H}[\mathbb{E}]$	$\mathbb{V}[\boldsymbol{y}]$	$\mathcal{I}$	$\mathcal{K}$	$\mathbb{V}[\boldsymbol{\mu}]$
Single		0.69	0.69	-	-	-	0.02	0.02	-	-	-
NWPN		0.801	0.801	0.199	0.199	0.799	0.999	0.999	**1.0**	**1.0**	**1.0**
EnD	LSN-B	0.646	0.646	-	-	-	0.003	0.003	-	-	-
EnD^2		0.724	0.733	**0.817**	0.806	0.770	0.015	0.017	0.887	0.868	0.040
ENSM		-	0.723	-	0.672	0.745	-	0.032	-	0.822	0.097
Single		0.845	0.845	-	-	-	0.023	0.023	-	-	-
NWPN		**0.993**	**0.993**	0.003	0.003	0.992	0.994	0.994	**1.0**	**1.0**	0.998
EnD	LSN-C	0.703	0.703	-	-	-	0.004	0.004	-	-	-
EnD^2		0.882	0.893	0.964	0.952	0.928	0.018	0.020	0.834	0.806	0.036
ENSM		-	0.887	-	0.696	0.886	-	0.036	-	0.779	0.098

Figure 3: Comparison of uncertainty measures between ensembles and EnD^2.

Training RPNs with RKL is challenging in this setting, as it is non-trivial to define what OOD is, especially for depth estimation. In this paper we consider a different dataset to be OOD, however the distinction is too high-level. An ablation study with varying OOD weight (appendix D), showed that there is a trade-off between predictive quality and OOD detection quality. Results in the table above show that when trained appropriately, this yields the best OOD detection performance (KITTI), and if the balance is incorrect, the performance is poor (NYU). Predictive performance also suffers. This highlights the value of EnD^2, which does not require OOD training data, and yields both good predictive and OOD detection performance.

Last, figure 3 shows the error and estimates of *total* and *knowledge uncertainty* yielded by an ensemble and an EnD^2 model for the same input image. Both the ensemble and our model effectively decompose uncertainty. *Total uncertainty* is large at object boundaries and distant points while *knowledge uncertainty* concentrates on the interior of unusual objects. EnD^2 yields both error and measures of uncertainty which are very similar to that of the original ensemble. This demonstrates that EnD^2 is able to emulate not only the predictive performance of the ensemble, but also the behaviour of the ensemble's measures of uncertainty. Additional comparisons are provided in appendix D.

6 CONCLUSION

This work extends Prior Networks to regression tasks, yielding a set of general, efficient and interpretable uncertainty estimation approaches for regression. A regression Prior Network (RPN) predicts the parameters of a Normal-Wishart distribution, which enables it to efficiently represent ensembles of regression models, allowing interpretable measures of uncertainty to be obtained at low computational cost. In this work closed-form measures of *total*, *data* and *knowledge uncertainty* are obtained for Normal-Wishart RPNs. Two RPN training approaches are proposed. First, the reverse-KL divergence between the model and a target Normal-Wishart distribution, allowing the behaviour of an RPN to be explicitly controlled but requiring an OOD training dataset, is described. Second, Ensemble Distribution Distillation (EnD^2) is used, where an ensemble of regression models is distilled into an RPN such that it retains the improved predictive performance and uncertainty estimates of the original ensemble. This approach is particularly useful when it is challenging to define an appropriate out-of-domain training dataset, such as in depth-estimation. The properties of RPNs are evaluated on both a synthetic dataset and selected UCI datasets. The usefulness of Ensemble Distribution Distillation is also demonstrated on two large-scale monocular depth-estimation task, where an ensemble of probabilistic depth-estimation models is distribution-distilled into an RPN.

REFERENCES

Ibraheem Alhashim and Peter Wonka. High quality monocular depth estimation via transfer learning. *arXiv e-prints*, abs/1812.11941:arXiv:1812.11941, 2018. URL https://arxiv.org/abs/1812.11941.

Babak Alipanahi, Andrew Delong, Matthew T. Weirauch, and Brendan J. Frey. Predicting the sequence specificities of DNA- and RNA-binding proteins by deep learning. *Nature Biotechnology*, 33(8):831–838, July 2015. ISSN 1087-0156. doi: 10.1038/nbt.3300. URL http://dx.doi.org/10.1038/nbt.3300.

Dario Amodei, Chris Olah, Jacob Steinhardt, Paul F. Christiano, John Schulman, and Dan Mané. Concrete problems in AI safety. http://arxiv.org/abs/1606.06565, 2016. arXiv: 1606.06565.

REINALDO B ARELLANO-VALLE, JAVIER E CONTRERAS-REYES, and Marc G Genton. Shannon entropy and mutual information for multivariate skew-elliptical distributions. *Scandinavian Journal of Statistics*, 40(1):42–62, 2013.

Arsenii Ashukha, Alexander Lyzhov, Dmitry Molchanov, and Dmitry Vetrov. Pitfalls of in-domain uncertainty estimation and ensembling in deep learning. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=BJxI5gHKDr.

Christopher M Bishop. *Pattern recognition and machine learning*. springer, 2006.

Nicholas Carlini and David A. Wagner. Adversarial examples are not easily detected: Bypassing ten detection methods. *CoRR*, 2017. URL http://arxiv.org/abs/1705.07263.

Rich Caruana, Yin Lou, Johannes Gehrke, Paul Koch, Marc Sturm, and Noemie Elhadad. Intelligible models for healthcare: Predicting pneumonia risk and hospital 30-day readmission. In *Proc. 21th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '15, pp. 1721–1730, New York, NY, USA, 2015. ACM. ISBN 978-1-4503-3664-2. doi: 10.1145/2783258.2788613. URL http://doi.acm.org/10.1145/2783258.2788613.

Thomas M Cover and Joy A Thomas. *Elements of information theory*. John Wiley & Sons, 2006.

David Eigen, Christian Puhrsch, and Rob Fergus. Depth map prediction from a single image using a multi-scale deep network. In *Proceedings of the 27th International Conference on Neural Information Processing Systems - Volume 2*, NIPS'14, pp. 2366–2374, Cambridge, MA, USA, 2014. MIT Press.

Stanislav Fort, Huiyi Hu, and Balaji Lakshminarayanan. Deep ensembles: A loss landscape perspective. *arXiv preprint arXiv:1912.02757*, 2019.

Yarin Gal and Zoubin Ghahramani. Dropout as a Bayesian Approximation: Representing Model Uncertainty in Deep Learning. In *Proc. 33rd International Conference on Machine Learning (ICML-16)*, 2016.

Andreas Geiger, Philip Lenz, Christoph Stiller, and Raquel Urtasun. Vision meets robotics: The kitti dataset. 2013.

Ross Girshick. Fast R-CNN. In *Proc. 2015 IEEE International Conference on Computer Vision (ICCV)*, pp. 1440–1448, 2015.

Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep learning*. MIT press, 2016.

Maya Gupta and Santosh Srivastava. Parametric bayesian estimation of differential entropy and relative entropy. *Entropy*, 12(4):818–843, 2010.

Awni Y. Hannun, Carl Case, Jared Casper, Bryan Catanzaro, Greg Diamos, Erich Elsen, Ryan Prenger, Sanjeev Satheesh, Shubho Sengupta, Adam Coates, and Andrew Y. Ng. Deep speech: Scaling up end-to-end speech recognition, 2014. URL http://arxiv.org/abs/1412.5567. arXiv:1412.5567.

Dan Hendrycks and Kevin Gimpel. A Baseline for Detecting Misclassified and Out-of-Distribution Examples in Neural Networks. `http://arxiv.org/abs/1610.02136`, 2016. arXiv:1610.02136.

Geoffrey Hinton, Li Deng, Dong Yu, George Dahl, Abdel rahman Mohamed, Navdeep Jaitly, Andrew Senior, Vincent Vanhoucke, Patrick Nguyen, Tara Sainath, and Brian Kingsbury. Deep neural networks for acoustic modeling in speech recognition. *Signal Processing Magazine*, 2012.

Andreas Kirsch, Joost van Amersfoort, and Yarin Gal. Batchbald: Efficient and diverse batch acquisition for deep bayesian active learning, 2019.

B. Lakshminarayanan, A. Pritzel, and C. Blundell. Simple and Scalable Predictive Uncertainty Estimation using Deep Ensembles. In *Proc. Conference on Neural Information Processing Systems (NIPS)*, 2017.

Wesley Maddox, Timur Garipov, Pavel Izmailov, Dmitry Vetrov, and Andrew Gordon Wilson. A simple baseline for bayesian uncertainty in deep learning. *arXiv preprint arXiv:1902.02476*, 2019.

Andrey Malinin. *Uncertainty Estimation in Deep Learning with application to Spoken Language Assessment*. PhD thesis, University of Cambridge, 2019.

Andrey Malinin and Mark Gales. Predictive uncertainty estimation via prior networks. In *Advances in Neural Information Processing Systems*, pp. 7047–7058, 2018.

Andrey Malinin and Mark JF Gales. Reverse kl-divergence training of prior networks: Improved uncertainty and adversarial robustness. 2019.

Andrey Malinin, Bruno Mlodozeniec, and Mark JF Gales. Ensemble distribution distillation. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=BygSP6Vtvr`.

Moritz Menze and Andreas Geiger. Object scene flow for autonomous vehicles. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2015.

Tomas Mikolov, Martin Karafiát, Lukás Burget, Jan Cernocký, and Sanjeev Khudanpur. Recurrent Neural Network Based Language Model. In *Proc. INTERSPEECH*, 2010.

Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient Estimation of Word Representations in Vector Space. `http://arxiv.org/abs/1301.3781`, 2013a. arXiv:1301.3781.

Tomas Mikolov et al. Linguistic Regularities in Continuous Space Word Representations. In *Proc. NAACL-HLT*, 2013b.

Kevin P. Murphy. *Machine Learning*. The MIT Press, 2012.

Pushmeet Kohli Nathan Silberman, Derek Hoiem and Rob Fergus. Indoor segmentation and support inference from rgbd images. In *ECCV*, 2012.

Yaniv Ovadia, Emily Fertig, Jie Ren, Zachary Nado, D Sculley, Sebastian Nowozin, Joshua V Dillon, Balaji Lakshminarayanan, and Jasper Snoek. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift. *Advances in Neural Information Processing Systems*, 2019.

Karen Simonyan and Andrew Zisserman. Very Deep Convolutional Networks for Large-Scale Image Recognition. In *Proc. International Conference on Learning Representations (ICLR)*, 2015.

L. Smith and Y. Gal. Understanding Measures of Uncertainty for Adversarial Example Detection. In *UAI*, 2018.

Ruben Villegas, Jimei Yang, Yuliang Zou, Sungryull Sohn, Xunyu Lin, and Honglak Lee. Learning to Generate Long-term Future via Hierarchical Prediction. In *Proc. International Conference on Machine Learning (ICML)*, 2017.

Fisher Yu, Yinda Zhang, Shuran Song, Ari Seff, and Jianxiong Xiao. LSUN: construction of a large-scale image dataset using deep learning with humans in the loop, 2015. URL `http://arxiv.org/abs/1506.03365`. arXiv:1506.03365.

A   DERIVATIONS FOR NORMAL-WISHART PRIOR NETWORKS

The current appendix provides mathematical details of the Normal-Wishart distribution and derivations of the reverse-KL divergence loss, ensemble distribution distillation and all uncertainty measures.

A.1   NORMAL-WISHART DISTRIBUTION

The Normal-Wishart distribution is a conjugate prior over the mean $\boldsymbol{\mu}$ and precision $\boldsymbol{\Lambda}$ of a normal distribution, defined as follows

$$\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda}|\boldsymbol{\Omega}) = \mathcal{NW}(\boldsymbol{\mu}, \boldsymbol{\Lambda}|\boldsymbol{m}, \boldsymbol{L}, \kappa, \nu) = \mathcal{N}(\boldsymbol{\mu}|\boldsymbol{m}, \kappa\boldsymbol{\Lambda})\mathcal{W}(\boldsymbol{\Lambda}|\boldsymbol{L}, \nu); \tag{16}$$

where $\boldsymbol{\Omega} = \{\boldsymbol{m}, \boldsymbol{L}, \kappa, \nu\}$ are the parameters predicted by neural network, $\mathcal{N}$ is the density of the Normal and $\mathcal{W}$ is the density of the Wishart distribution. Here, $\boldsymbol{m}$ and $\boldsymbol{L}$ are the *prior mean* and inverse of the positive-definite *prior scatter matrix*, while κ and ν are the strengths of belief in each prior, respectively. The parameters κ and ν are conceptually similar to *precision* of the Dirichlet distribution α_0. The Normal-Wishart is a compound distribution which decomposes into a product of a conditional normal distribution over the mean and an Wishart distribution over the precision:

$$\mathcal{N}(\boldsymbol{\mu}|\boldsymbol{m}, \kappa\boldsymbol{\Lambda}) = \frac{\kappa^{\frac{D}{2}}|\boldsymbol{\Lambda}|^{\frac{1}{2}}}{2\pi^{\frac{D}{2}}}\exp\Big(-\frac{\kappa}{2}(\boldsymbol{\mu}-\boldsymbol{m})^{\mathrm{T}}\boldsymbol{\Lambda}(\boldsymbol{\mu}-\boldsymbol{m})\Big)$$

$$\mathcal{W}(\boldsymbol{\Lambda}|\boldsymbol{L}, \nu) = \frac{|\boldsymbol{\Lambda}|^{\frac{\nu-K-1}{2}}\exp(-\frac{1}{2}\mathrm{Tr}(\boldsymbol{\Lambda}\boldsymbol{L^{-1}}))}{2^{\frac{\nu K}{2}}\Gamma_K(\frac{\nu}{2})|\boldsymbol{L}|^{\frac{\nu}{2}}}; \ \boldsymbol{\Lambda}, \boldsymbol{L} \succ 0, \nu > K-1. \tag{17}$$

where $\Gamma_K(\cdot)$ is the *multivariate gamma function* and K is the dimensionality of $\boldsymbol{y}$. From (Murphy, 2012) the posterior predictive of this model is the multivariate T-distribution:

$$\mathrm{p}(\boldsymbol{y}|\boldsymbol{x}, \boldsymbol{\theta}) = \mathbb{E}_{\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda}|\boldsymbol{x}, \boldsymbol{\theta})}\big[\mathrm{p}(\boldsymbol{y}|\boldsymbol{\mu}, \boldsymbol{\Lambda})\big] = \mathcal{T}(\boldsymbol{y}|\boldsymbol{m}, \frac{\kappa+1}{\kappa(\nu-K+1)}\boldsymbol{L}^{-1}, \nu-K+1). \tag{18}$$

The $\mathcal{T}$ distribution is heavy-tailed generalization of the multivariate normal distribution defined as:

$$\mathcal{T}(\boldsymbol{y}|\boldsymbol{\mu}, \boldsymbol{\Sigma}, \nu) = \frac{\Gamma(\frac{\nu+K}{2})}{\Gamma(\frac{\nu}{2})\nu^{\frac{K}{2}}\pi^{\frac{K}{2}}|\boldsymbol{\Sigma}|^{\frac{1}{2}}}\Big(1+\frac{1}{\nu}(\boldsymbol{y}-\boldsymbol{\mu})^{\mathrm{T}}\boldsymbol{\Sigma}^{-1}(\boldsymbol{y}-\boldsymbol{\mu})\Big)^{-\frac{(\nu+K)}{2}}, \ \nu \geq 0; \tag{19}$$

where ν is the number of degrees of freedom. However, the mean is only defined when $\nu > 1$ and the variance is defined only when $\nu > 2$.

A.2   REVERSE KL-DIVERGENCE TRAINING OBJECTIVE

Now let us consider in greater detail the reverse KL-divergence training objective (11):

$$\mathcal{L}(\boldsymbol{y}, \boldsymbol{x}, \boldsymbol{\theta}; \hat{\beta}, \boldsymbol{\Omega}_0) = \hat{\beta} \cdot \mathbb{E}_{\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda}|\boldsymbol{x}, \boldsymbol{\theta})}\big[-\ln\mathrm{p}(\boldsymbol{y}|\boldsymbol{\mu}, \boldsymbol{\Lambda})\big] + \mathrm{KL}[\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda}|\boldsymbol{x}, \boldsymbol{\theta})\|\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda}|\boldsymbol{\Omega}_0)] + Z \tag{20}$$

where $\Omega_0 = [\boldsymbol{m}_0, \boldsymbol{L}_0, \kappa_0, \nu_0]$ are prior parameters that we set manually as discussed in section 2.2. It is necessary to show why the reverse KL-divergence objective will yield the correct level of data uncertainty. Lets consider taking the expectation of the first term in (11) with respect to the *true distribution* of targets $\mathrm{p}_{tr}(\boldsymbol{y}|\boldsymbol{x})$. Trivially, we can show that by exchanging the order of expectation, that we are optimizing the expected cross-entropy between samples from the Normal-Wishart and the true distribution:

$$\mathbb{E}_{\mathrm{p}_{tr}(\boldsymbol{y}|\boldsymbol{x})}\big[\mathbb{E}_{\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda}|\boldsymbol{x}, \boldsymbol{\theta})}\big[-\ln\mathrm{p}(\boldsymbol{y}|\boldsymbol{\mu}, \boldsymbol{\Lambda})\big]\big] = \mathbb{E}_{\mathrm{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda}|\boldsymbol{x}, \boldsymbol{\theta})}\big[\mathbb{E}_{\mathrm{p}_{tr}(\boldsymbol{y}|\boldsymbol{x})}\big[-\ln\mathrm{p}(\boldsymbol{y}|\boldsymbol{\mu}, \boldsymbol{\Lambda})\big]\big] \tag{21}$$

This will yield an upper bound on the cross entropy between the predictive posterior and the true distribution. However, if we were to consider the *forward* KL-divergence between Normal-Wishart distributions, we would not obtain such an expression and not correctly estimate data uncertainty. Interestingly, the reverse KL-divergence training objective has the same form as an ELBO - the predictive term and a reverse KL-divergence to the prior.

Having established an important property of the RKL objective, we not derive it's closed form expression. Note, that in these derivations, we make extended use of properties for taking expectations

of traces and log-determinants matrices with respect to the Wishart distribution detailed in (Gupta & Srivastava, 2010).For the first term in 20, we use the following property of the multivariate normal:

$$x \sim \mathcal{N}(\boldsymbol{\mu}, \boldsymbol{\Sigma}) \Rightarrow \mathbb{E}[\boldsymbol{x}^T \boldsymbol{A} \boldsymbol{x}] = \text{Tr}(\boldsymbol{A} \boldsymbol{\Sigma}) + \boldsymbol{m}^T \boldsymbol{A} \boldsymbol{m}; \tag{22}$$

which allows us to get:

$$
\begin{aligned}
\mathbb{E}_{\text{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{x}; \boldsymbol{\theta})} & [-\ln \text{p}(\boldsymbol{y} | \boldsymbol{\mu}, \boldsymbol{\Lambda})] = \\
& = \frac{1}{2} \mathbb{E}_{\text{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{x}; \boldsymbol{\theta})} [(\boldsymbol{y} - \boldsymbol{\mu})^T \boldsymbol{\Lambda} (\boldsymbol{y} - \boldsymbol{\mu}) + K \ln(2\pi) - \ln |\boldsymbol{\Lambda}|] \\
& = \frac{1}{2} \mathbb{E}_{\mathcal{N}(\boldsymbol{\mu} | \boldsymbol{m}, \kappa \boldsymbol{\Lambda}) \mathcal{W}(\boldsymbol{\Lambda} | \boldsymbol{L}, \nu)} [(\boldsymbol{y} - \boldsymbol{\mu})^T \boldsymbol{\Lambda} (\boldsymbol{y} - \boldsymbol{\mu}) + K \ln(2\pi) - \ln |\boldsymbol{\Lambda}|] \\
& \propto \frac{1}{2} \mathbb{E}_{\text{p}(\boldsymbol{\Lambda} | L; \nu)} [(\boldsymbol{y} - \boldsymbol{m})^T \boldsymbol{\Lambda} (\boldsymbol{y} - \boldsymbol{m}) + K \kappa^{-1} - \ln |\boldsymbol{\Lambda}|] \\
& = \frac{\nu}{2} (\boldsymbol{y} - \boldsymbol{m})^T \boldsymbol{L} (\boldsymbol{y} - \boldsymbol{m}) + \frac{K}{2\kappa} - \frac{1}{2} \ln |\boldsymbol{L}| - \frac{1}{2} \psi_K(\frac{\nu}{2}) + \frac{K}{2} \ln \pi.
\end{aligned}
\tag{23}
$$

The second term in (20) may expressed as follows via the chain-rule of relative entropy(Cover & Thomas, 2006):

$$
\begin{aligned}
\text{KL}[\text{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{\Omega}) \| \text{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{\Omega}_0)] & = \\
& = \mathbb{E}_{\text{p}(\boldsymbol{\Lambda} | \boldsymbol{\Omega})} [\text{KL}[\text{p}(\boldsymbol{\mu} | \boldsymbol{\Lambda}, \boldsymbol{\Omega}) \| \text{p}(\boldsymbol{\mu} | \boldsymbol{\Lambda}, \boldsymbol{\Omega}_0)]] + \text{KL}[\text{p}(\boldsymbol{\Lambda} | \boldsymbol{\Omega}) \| \text{p}(\boldsymbol{\Lambda} | \boldsymbol{\Omega}_0)];
\end{aligned}
\tag{24}
$$

The first term in (24) can be computed as:

$$
\begin{aligned}
\mathbb{E}_{\text{p}(\boldsymbol{\Lambda} | \boldsymbol{\Omega})} & [\text{KL}[\text{p}(\boldsymbol{\mu} | \boldsymbol{\Lambda}, \boldsymbol{\Omega}) \| \text{p}(\boldsymbol{\mu} | \boldsymbol{\Lambda}, \boldsymbol{\Omega}_0)]] = \\
& = \mathbb{E}_{\mathcal{W}(\boldsymbol{\Lambda} | \boldsymbol{L}, \nu)} [\text{KL}[\mathcal{N}(\boldsymbol{y} | \boldsymbol{m}, \kappa \boldsymbol{\Lambda}) \| \mathcal{N}(\boldsymbol{y} | \boldsymbol{m}_0, \kappa_0 \boldsymbol{\Lambda})]] \\
& = \frac{\kappa_0}{2} (\boldsymbol{m} - \boldsymbol{m}_0)^T \nu \boldsymbol{L} (\boldsymbol{m} - \boldsymbol{m}_0) + \frac{K}{2} (\frac{\kappa_0}{\kappa} - \ln \frac{\kappa_0}{\kappa} - 1);
\end{aligned}
\tag{25}
$$

while the second term is:

$$
\begin{aligned}
\text{KL}[\text{p}(\boldsymbol{\Lambda} | \boldsymbol{\Omega}) \| \text{p}(\boldsymbol{\Lambda} | \boldsymbol{\Omega}_0)] & = \text{KL}[\mathcal{W}(\boldsymbol{\Lambda} | \boldsymbol{L}, \nu) \| \mathcal{W}(\boldsymbol{\Lambda} | \boldsymbol{L}_0, \nu_0)] = \\
& = \frac{\nu}{2} \big(\text{tr}(\boldsymbol{L}_0^{-1} \boldsymbol{L}) - K \big) - \frac{\nu_0}{2} \ln |\boldsymbol{L}_0^{-1} \boldsymbol{L}| + \ln \frac{\Gamma_K(\frac{\nu_0}{2})}{\Gamma_K(\frac{\nu}{2})} + \frac{\nu - \nu_0}{2} \psi_K(\frac{\nu}{2}).
\end{aligned}
\tag{26}
$$

A.3 Uncertainty Measures

Given a Normal-Wishart Prior Network which displays the desired set of behaviours detailed in 2, it is possible to compute closed-form expression for all measures of uncertainty previously discussed for Dirichlet Prior Networks (Malinin, 2019). The current section details the derivations of uncertainty measures introduced in section 2.1 for the Normal-Wishart distribution. We make extensive use of (Gupta & Srivastava, 2010) for taking expectation of log-determinants and traces of matrices.

A.3.1 Differential Entropy of Predictive Posterior

As discussed in section 2, the predictive posterior of a Prior Network which parameterizes a Normal-Wishart distribution is a multivariate T distribution:

$$\mathbb{E}_{\text{p}(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{x}, \boldsymbol{\theta})}[\text{p}(\boldsymbol{y} | \boldsymbol{\mu}, \boldsymbol{\Lambda})] = \mathcal{T}(\boldsymbol{y} | \boldsymbol{m}, \frac{\kappa + 1}{\kappa(\nu - K + 1)} \boldsymbol{L}^{-1}, \nu - K + 1). \tag{27}$$

The differential entropy of the predictive posterior will be a measure of *total uncertainty*. The differential entropy of a standard multivariate student's T distribution with an identity scatter matrix $\boldsymbol{\Sigma} = \boldsymbol{I}$ is given by:

$$\mathcal{H}[\mathcal{T}(\boldsymbol{x} | \boldsymbol{\mu}, \boldsymbol{I}, \nu)] = -\ln \frac{\Gamma(\frac{\nu + K}{2})}{\Gamma(\frac{\nu}{2})(\nu \pi)^{\frac{K}{2}}} + (\frac{\nu + K}{2}) \cdot (\psi(\frac{\nu + K}{2}) - \psi(\frac{\nu}{2})); \tag{28}$$

which is a result obtained from (ARELLANO-VALLE et al., 2013). Using the property of differential entropy (Cover & Thomas, 2006), that if $\boldsymbol{x} \sim \text{p}(\boldsymbol{x})$ and $\boldsymbol{y} = \boldsymbol{\mu} + \boldsymbol{A} \boldsymbol{x}$, then:

$$\mathcal{H}[\text{p}(\boldsymbol{y})] = \mathcal{H}[\text{p}(\boldsymbol{x})] + \ln |\boldsymbol{A}|. \tag{29}$$

We can show that the differential entropy of a standard general multivariate student's T distribution is given by:

$$\mathcal{H}[\mathcal{T}(\boldsymbol{x}|\boldsymbol{\mu}, \boldsymbol{\Sigma}, \nu)] = \frac{1}{2}\ln|\boldsymbol{\Sigma}| - \ln\frac{\Gamma(\frac{\nu+K}{2})}{\Gamma(\frac{\nu}{2})(\nu\pi)^{\frac{K}{2}}} + (\frac{\nu+K}{2}) \cdot (\psi(\frac{\nu+K}{2}) - \psi(\frac{\nu}{2})). \tag{30}$$

Using this expression, we can show that the differential entropy of the predictive posterior of a Normal-Wishart Prior Network is given by:

$$\mathcal{H}\big[\mathbb{E}_{\mathrm{p}(\boldsymbol{\mu},\boldsymbol{\Lambda}|\boldsymbol{x},\boldsymbol{\theta})}[\mathrm{p}(\boldsymbol{y}|\boldsymbol{\mu},\boldsymbol{\Lambda})]\big] = \mathcal{H}\big[\mathcal{T}(\boldsymbol{y}|\boldsymbol{m}, \frac{\kappa+1}{\kappa(\nu-K+1)}\boldsymbol{L}^{-1}, \nu-K+1)\big]$$

$$= \frac{\nu+1}{2}\Big(\psi(\frac{\nu+1}{2}) - \psi(\frac{\nu-K+1}{2})\Big) - \ln\frac{\Gamma(\frac{\nu+1}{2})}{\Gamma(\frac{\nu-K+1}{2})\big((\nu-K+1)\pi\big)^{\frac{K}{2}}} \tag{31}$$

$$- \frac{1}{2}\ln|\boldsymbol{L}| + \frac{K}{2}\ln\frac{\kappa+1}{\kappa(\nu-K+1)}.$$

A.3.2 MUTUAL INFORMATION

The mutual information between the target $\boldsymbol{y}$ and the parameters of the output distribution $\{\boldsymbol{\mu}, \boldsymbol{\Lambda}\}$ is measures of *knowledge uncertainty*, and it the difference between the (differential) entropy of the predictive posterior and the expected differential entropy of each normal distribution sampled from the Normal Wishart:

$$\underbrace{\mathcal{I}[\boldsymbol{y}, \{\boldsymbol{\mu}, \boldsymbol{\Lambda}\}]}_{\text{Knowledge Uncertainty}} = \underbrace{\mathcal{H}\big[\mathbb{E}_{\mathrm{p}(\boldsymbol{\mu},\boldsymbol{\Lambda}|\boldsymbol{x},\boldsymbol{\theta})}[\mathrm{p}(\boldsymbol{y}|\boldsymbol{\mu},\boldsymbol{\Lambda})]\big]}_{\text{Total Uncertainty}} - \underbrace{\mathbb{E}_{\mathrm{p}(\boldsymbol{\mu},\boldsymbol{\Lambda}|\boldsymbol{x},\boldsymbol{\theta})}\big[\mathcal{H}[\mathrm{p}(\boldsymbol{y}|\boldsymbol{\mu},\boldsymbol{\Lambda})]\big]}_{\text{Expected Data Uncertainty}} \tag{32}$$

The first term, the differential entropy of the predictive posterior was derived above in (31). We we derive the expected differential entropy as follows:

$$\mathbb{E}_{\mathcal{NW}(\boldsymbol{\mu},\boldsymbol{\Lambda}|\Omega)}\big[\mathcal{H}[\mathcal{N}(\boldsymbol{y}|\boldsymbol{\mu},\boldsymbol{\Lambda})]\big] = \frac{1}{2}\mathbb{E}_{\mathcal{NW}(\boldsymbol{\mu},\boldsymbol{\Lambda}|\Omega)}\big[K\ln(2\pi e) - \ln|\boldsymbol{\Lambda}|\big] =$$

$$= \frac{1}{2}\big[K\ln(\pi e) - \ln|\boldsymbol{L}| - \psi_K(\frac{\nu}{2}))\big]. \tag{33}$$

Thus, the final expression for mutual information is:

$$\mathcal{I}[\boldsymbol{y}, \{\boldsymbol{\mu}, \boldsymbol{\Lambda}\}] = \frac{\nu+1}{2}\Big(\psi(\frac{\nu+1}{2}) - \psi(\frac{\nu-K+1}{2})\Big) - \ln\frac{\Gamma(\frac{\nu+1}{2})}{\Gamma(\frac{\nu-K+1}{2})\big((\nu-K+1)\pi\big)^{\frac{K}{2}}}$$

$$+ \frac{K}{2}\ln\frac{\kappa+1}{\kappa(\nu-K+1)} - \frac{1}{2}\big[K\ln(\pi e) - \psi_K(\frac{\nu}{2}))\big]. \tag{34}$$

Note that this expression is no longer a function of $\boldsymbol{L}$, which was important in representation *data uncertainty*.

A.3.3 EXPECTED PAIRWISE KL-DIVERGENCE

An alternative measures of *knowledge uncertainty* which can be considered is the expected pairwise kl-divergence (EPKL), which upper bounds mutual information (Malinin, 2019). In this section we derive it's closed form expression for the Normal-Wishart distribution.

$$\mathcal{K}[\boldsymbol{y}, \{\boldsymbol{\mu}, \boldsymbol{\Lambda}\}] = \mathbb{E}_{\mathrm{p}(\boldsymbol{\mu}_0,\boldsymbol{\Lambda}_0)}\mathbb{E}_{p(\boldsymbol{\mu}_1,\boldsymbol{\Lambda}_1)}\big[\mathrm{KL}[\mathcal{N}(\boldsymbol{y}|\boldsymbol{\mu}_1,\boldsymbol{\Lambda}_1)\|\mathcal{N}(\boldsymbol{y}|\boldsymbol{\mu}_0,\boldsymbol{\Lambda}_0)]\big]$$

$$= \frac{1}{2}\mathbb{E}_{\mathrm{p}(\boldsymbol{\mu}_0,\boldsymbol{\Lambda}_0)}\mathbb{E}_{p(\boldsymbol{\mu}_1,\boldsymbol{\Lambda}_1)}\Big[(\boldsymbol{\mu}_1-\boldsymbol{\mu}_0)^T\boldsymbol{\Lambda}_0(\boldsymbol{\mu}_1-\boldsymbol{\mu}_0) + \ln\frac{|\boldsymbol{\Lambda}_1|}{|\boldsymbol{\Lambda}_0|} + \mathrm{Tr}(\boldsymbol{\Lambda}_0\boldsymbol{\Lambda}_1^{-1}) - K\Big]. \tag{35}$$

Here $p(\boldsymbol{\mu}_0, \boldsymbol{\Lambda}_0) = p(\boldsymbol{\mu}_1, \boldsymbol{\Lambda}_1) = p(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{x}; \boldsymbol{\theta})$. In (35) the first term is:

$$
\begin{aligned}
\mathbb{E}_{p(\boldsymbol{\mu}_0, \boldsymbol{\Lambda}_0)} \mathbb{E}_{p(\boldsymbol{\mu}_1, \boldsymbol{\Lambda}_1)} & \big[(\boldsymbol{\mu}_1 - \boldsymbol{\mu}_0)^T \boldsymbol{\Lambda}_0 (\boldsymbol{\mu}_1 - \boldsymbol{\mu}_0) \big] = \\
& = \mathbb{E}_{p(\boldsymbol{\mu}_0, \boldsymbol{\Lambda}_0)} \mathbb{E}_{p(\boldsymbol{\Lambda}_1)} \big[(\boldsymbol{m} - \boldsymbol{\mu}_0)^T \boldsymbol{\Lambda}_0 (\boldsymbol{m} - \boldsymbol{\mu}_0) + \mathrm{Tr}(\boldsymbol{\Lambda}_0 \frac{1}{\kappa} \boldsymbol{\Lambda}_1^{-1}) \big] \\
& = \mathbb{E}_{p(\boldsymbol{\mu}_0, \boldsymbol{\Lambda}_0)} \big[(\boldsymbol{m} - \boldsymbol{\mu}_0)^T \boldsymbol{\Lambda}_0 (\boldsymbol{m} - \boldsymbol{\mu}_0) + \frac{1}{\kappa(\nu - K - 1)} \mathrm{Tr}(\boldsymbol{\Lambda}_0 L^{-1}) \big] \\
& = \frac{K}{\kappa} + \frac{\nu K}{\kappa(\nu - K - 1)};
\end{aligned}
\tag{36}
$$

The second term in (35) is zero, and the third term is:

$$
\mathbb{E}_{p(\boldsymbol{\mu}_0, \boldsymbol{\Lambda}_0)} \mathbb{E}_{p(\boldsymbol{\mu}_1, \boldsymbol{\Lambda}_1)} \big[\mathrm{Tr}(\boldsymbol{\Lambda}_0 \boldsymbol{\Lambda}_1^{-1}) \big] = \mathbb{E}_{p(\boldsymbol{\mu}_0, \boldsymbol{\Lambda}_0)} \big[\mathrm{Tr}(\boldsymbol{\Lambda}_0 \frac{1}{\nu - K - 1} L^{-1}) \big] = \frac{\nu K}{(\nu - K - 1)}; \tag{37}
$$

which in sum gives us:

$$
\mathcal{K}[\boldsymbol{y}, \{\boldsymbol{\mu}, \boldsymbol{\Lambda}\}] = \frac{1}{2} \frac{\nu K(\kappa^{-1} + 1)}{(\nu - K - 1)} - \frac{K}{2} + \frac{K}{2\kappa}. \tag{38}
$$

Note that this is also not a function of L, just like mutual information. Rather, it is only a function of the pseudo-counts κ and ν.

A.3.4 LAW OF TOTAL VARIATION

Finally, in order to be able to compare with ensembles, we can also derive variance-based measures of *total*, *data* and *knowledge uncertainty* via the Law of total variance, as follows:

$$
\underbrace{\mathbb{V}_{p(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{x}, \boldsymbol{\theta})}[\boldsymbol{\mu}]}_{\text{Knowledge Uncertainty}} = \underbrace{\mathbb{V}_{p(\boldsymbol{y} | \boldsymbol{x}, \boldsymbol{\theta})}[\boldsymbol{y}]}_{\text{Total Uncertainty}} - \underbrace{\mathbb{E}_{p(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{x}, \boldsymbol{\theta})}[\boldsymbol{\Lambda}^{-1}]}_{\text{Expected Data Uncertainty}} \tag{39}
$$

This has a similar decomposition as mutual information. In this section we derive its closed form expression. We can compute the expected variance by using the probabilistic change of variables:

$$
\begin{aligned}
\mathbb{E}_{p(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{x}, \boldsymbol{\theta})}[\boldsymbol{\Lambda}^{-1}] = \mathbb{E}_{\mathcal{NW}(\boldsymbol{\mu}, \boldsymbol{\Lambda})}[\boldsymbol{\Lambda}^{-1}] = \mathbb{E}_{\mathcal{W}(\boldsymbol{\Lambda})}[\boldsymbol{\Lambda}^{-1}] = \mathbb{E}_{\mathcal{W}^{-1}(\boldsymbol{\Lambda}^{-1})}[\boldsymbol{\Lambda}^{-1}] \\
= \frac{1}{\nu - K - 1} L^{-1};
\end{aligned}
\tag{40}
$$

and the variance of expected as:

$$
\begin{aligned}
\mathbb{V}_{p(\boldsymbol{\mu}, \boldsymbol{\Lambda} | \boldsymbol{x}, \boldsymbol{\theta})}[\boldsymbol{\mu}] = \mathbb{E}_{\mathcal{NW}(\boldsymbol{\mu}, \boldsymbol{\Lambda})} \big[(\boldsymbol{\mu} - \boldsymbol{m})(\boldsymbol{\mu} - \boldsymbol{m})^T \big] = \frac{1}{\kappa} \mathbb{E}_{\mathcal{W}(\boldsymbol{\Lambda} | L, \nu)} \big[\boldsymbol{\Lambda}^{-1} \big] \\
= \frac{1}{\kappa(\nu - K - 1)} L^{-1}.
\end{aligned}
\tag{41}
$$

Thus, the total variance is then expressed as:

$$
\mathbb{V}_{p(\boldsymbol{y} | \boldsymbol{x}, \boldsymbol{\theta})}[\boldsymbol{y}] = \frac{1 + \kappa}{\kappa(\nu - K - 1)} L^{-1}. \tag{42}
$$

Note that this yields a measure which only considers first and second moments. In addition, in order to obtain a scalar estimate of uncertainty, it is necessary to consider the log-determinant of each measure.

B EXPERIMENT ON SYNTHETIC DATA

The training data consists of 2048 inputs x uniformly sampled from $[-10, 10]$ with targets $y \sim \mathcal{N}(\sin x + \frac{x}{10})$. We use a relu network with 2 hidden layers containing 30 units each to predict the parameters of either Gaussian or Normal-Wishart distribution on this data. In all cases, we use Adam optimizer with learning rate 10^{-2} and weight decay 10^{-4} for 800 epochs with batch size 128. Gaussian models in an ensemble are trained via negative log-likelihood starting from different random initialization. To train a Regression Prior Network with reverse-KL divergence 512 points were uniformly sampled from $[-25, -20] \cup [20, 25]$ as training-ood data. We use objective (8) with coefficient $\gamma = 0.5$. The prior belief is $\kappa_0 = 10^{-2}$ and in-domain $\hat{\beta}$ is 10^2. For EnD^2 training we set $T = 1$ and add gaussian noise to inputs with standard deviation 3.

C UCI EXPERIMENTS

The current appendix provides additional details of experiments on the UCI regression datasets. Note that we leave out the Yacht Hydrodynamics datasets, as it is the smallest with the fewest features. The remaining datasets are described in the table below:

Table 5: Description of UCI datasets.

Dataset	size	number of features
Boston housing	506	13
Concrete Compressive Strength	1030	8
Energy efficiency	768	9
Combined Cycle Power	9568	4
Red Wine Quality	1599	11
YearPredictionMSD	515345	90

C.1 CREATING OUT-OF-DOMAIN DATA

Here we detail how OOD training data for reverse KL-divergence trained Prior Networks is created and how evaluation OOD data is created.

As reverse KL-divergence training of Prior Networks requires out-of-domain training examples, we use a factor analysis model to generate samples for this in the same way as was done in (Malinin, 2019). Specifically, we train a linear generative model that approximates inputs with $\hat{x} \sim \mathcal{N}(\mu, WW^T + \Psi)$, where $[W, \mu, \Psi]$ are model parameters. In-domain training data is used to train this model. The out-of-domain training examples are then sampled from $\mathcal{N}(\mu, 3WW^T + 3\Psi)$, such that we are sampling further from the in-domain region.

To estimate quality of out-of-domain detection, we additionally create evaluation out-of-domain data from external UCI datasets: "Relative location of CT slices on axial axis Data Set" for MSD and "Condition Based Maintenance of Naval Propulsion Plants Data Set" for other datasets. We drop all constant columns in them and leave first K columns and first N rows, where K is a number of features and N is a number of test examples in a corresponding dataset. For each comparison, the out-of-domain datasets are normalized by the per-column mean and variance obtained on in-domain training data.

C.2 TRAINING

Following (Lakshminarayanan et al., 2017) in all experiments except MSD we use 1 layer relu neural network with 50 hidden units, for MSD we use 100 hidden units. We optimize weights with Adam for 100 epochs with batch size 32. All hyper-parameters, including learning rate, weight decay, RKL prior belief in train data κ_0, RKL ood coefficient γ and EnD^2 initial temperature T and noise level ε are set based on grid search, where we use equal computational budget in all models to ensure fair comparison. Additionally, we use 10 folds cross-validation and report standard deviation based on it.

C.3 RESULTS FOR ALL DATASETS

The current section provide a full set of predictive performance, error detection and OOD detection results on UCI datasets in tables 6-8, respectively. Results in table 6 show that all models achieve comparable performance, and that EnD^2 tends to come close to the ensemble. Table 7 shows the error detection peformane of all models in terms of prediction-rejection ratio (% PRR) (Malinin, 2019). The results clearly show that measures of *total uncertainty* are useful in detecting errors, though it this is more challenging on some datasets. At the same time measures of *knowledge uncertainty* do significantly worse. Finally, table 8 shows the OOD detection performance in terms of % AUC-ROC. Here measures of *knowledge uncertainty* do far better. Notably, on the larger datasets EnD^2 comes closer to the performance of an ensemble.

Table 6: Prediction performance metrics of models on six UCI datasets.

Data	RMSE (↓)				NLL (↓)			
	Single	ENSM	EnD^2	NWPN	Single	ENSM	EnD^2	NWPN
boston	3.54 ± 0.32	$\mathbf{3.52 \pm 0.32}$	3.64 ± 0.33	3.53 ± 0.31	2.58 ± 0.08	2.53 ± 0.07	2.5 ± 0.05	$\mathbf{2.47 \pm 0.04}$
energy	1.83 ± 0.07	$\mathbf{1.79 \pm 0.07}$	1.98 ± 0.05	1.83 ± 0.07	1.38 ± 0.04	$\mathbf{1.32 \pm 0.04}$	1.72 ± 0.04	1.65 ± 0.08
concrete	5.66 ± 0.19	$\mathbf{5.24 \pm 0.18}$	6.13 ± 0.18	5.77 ± 0.24	3.11 ± 0.08	$\mathbf{3.00 \pm 0.04}$	3.13 ± 0.03	3.05 ± 0.03
wine	0.65 ± 0.01	$\mathbf{0.63 \pm 0.01}$	$\mathbf{0.63 \pm 0.01}$	$\mathbf{0.63 \pm 0.01}$	1.24 ± 0.16	0.96 ± 0.03	$\mathbf{0.91 \pm 0.02}$	0.93 ± 0.02
power	4.07 ± 0.07	$\mathbf{4.00 \pm 0.07}$	4.06 ± 0.07	4.09 ± 0.07	2.82 ± 0.02	$\mathbf{2.79 \pm 0.02}$	$\mathbf{2.79 \pm 0.01}$	2.81 ± 0.01
MSD	9.08 ± 0.00	$\mathbf{8.92 \pm 0.00}$	8.94 ± 0.00	9.07 ± 0.00	3.51 ± 0.00	$\mathbf{3.39 \pm 0.00}$	$\mathbf{3.39 \pm 0.00}$	3.41 ± 0.00

Table 7: PRR scores on all six UCI datasets.

Data	Model	$\mathcal{H}[\mathbb{E}]$	$\mathbb{V}[\boldsymbol{y}]$	$\mathcal{I}$	$\mathcal{K}$	$\mathbb{V}[\boldsymbol{\mu}]$
boston	ENSM	-	0.60 ± 0.07	-	-0.15 ± 0.07	0.41 ± 0.08
	EnD^2	$\mathbf{0.61 \pm 0.07}$	$\mathbf{0.61 \pm 0.07}$	-0.02 ± 0.15	-0.02 ± 0.15	0.59 ± 0.06
	NWPN	0.54 ± 0.08	0.54 ± 0.08	-0.05 ± 0.09	-0.05 ± 0.09	0.49 ± 0.08
energy	ENSM	-	$\mathbf{0.90 \pm 0.01}$	-	-0.80 ± 0.02	0.34 ± 0.09
	EnD^2	0.83 ± 0.02	0.83 ± 0.02	-0.77 ± 0.03	-0.77 ± 0.03	0.60 ± 0.05
	NWPN	0.85 ± 0.02	0.85 ± 0.02	0.32 ± 0.11	0.32 ± 0.11	0.84 ± 0.02
concrete	ENSM	-	0.48 ± 0.05	-	0.01 ± 0.07	0.27 ± 0.06
	EnD^2	0.50 ± 0.03	0.49 ± 0.03	0.05 ± 0.06	0.05 ± 0.06	0.44 ± 0.03
	NWPN	$\mathbf{0.54 \pm 0.03}$	$\mathbf{0.54 \pm 0.03}$	0.35 ± 0.04	0.35 ± 0.04	0.51 ± 0.03
wine	ENSM	-	$\mathbf{0.32 \pm 0.02}$	-	0.10 ± 0.03	0.25 ± 0.04
	EnD^2	0.30 ± 0.02	0.30 ± 0.02	0.06 ± 0.03	0.06 ± 0.03	0.30 ± 0.02
	NWPN	0.30 ± 0.03	0.30 ± 0.03	-0.19 ± 0.03	-0.19 ± 0.03	0.26 ± 0.04
power	ENSM	-	$\mathbf{0.23 \pm 0.01}$	-	-0.01 ± 0.02	0.05 ± 0.02
	EnD^2	$\mathbf{0.23 \pm 0.01}$	$\mathbf{0.23 \pm 0.01}$	-0.02 ± 0.03	-0.02 ± 0.03	0.15 ± 0.02
	NWPN	0.20 ± 0.02	0.20 ± 0.02	-0.03 ± 0.02	-0.03 ± 0.02	0.16 ± 0.01
msd	ENSM	-	$\mathbf{0.64 \pm 0.0}$	-	0.07 ± 0.0	0.39 ± 0.0
	EnD^2	0.63 ± 0.0	0.63 ± 0.0	0.04 ± 0.0	0.04 ± 0.0	0.59 ± 0.0
	NWPN	$\mathbf{0.64 \pm 0.0}$	$\mathbf{0.64 \pm 0.0}$	-0.20 ± 0.0	-0.20 ± 0.0	0.61 ± 0.0

Table 8: OOD Detection (ROC-AUC) of models on UCI datasets.

Data	Model	$\mathcal{H}[\mathbb{E}]$	$\mathbb{V}[\boldsymbol{y}]$	$\mathcal{I}$	$\mathcal{K}$	$\mathbb{V}[\boldsymbol{\mu}]$
boston	ENSM	-	0.75 ± 0.02	-	0.68 ± 0.02	$\mathbf{0.86 \pm 0.02}$
	EnD^2	0.75 ± 0.01	0.75 ± 0.01	0.63 ± 0.01	0.63 ± 0.01	0.76 ± 0.01
	NWPN	0.64 ± 0.02	0.65 ± 0.02	0.71 ± 0.01	0.71 ± 0.01	0.69 ± 0.01
energy	ENSM	-	0.76 ± 0.01	-	0.51 ± 0.03	$\mathbf{0.77 \pm 0.03}$
	EnD^2	0.61 ± 0.02	0.61 ± 0.02	0.57 ± 0.02	0.57 ± 0.02	0.63 ± 0.03
	NWPN	0.43 ± 0.02	0.43 ± 0.02	0.66 ± 0.01	0.66 ± 0.01	0.47 ± 0.02
concrete	ENSM	-	$\mathbf{0.84 \pm 0.01}$	-	0.78 ± 0.02	0.82 ± 0.01
	EnD^2	0.48 ± 0.02	0.48 ± 0.02	0.45 ± 0.01	0.45 ± 0.01	0.47 ± 0.01
	NWPN	$\mathbf{0.84 \pm 0.01}$	$\mathbf{0.84 \pm 0.01}$	0.8 ± 0.01	0.8 ± 0.01	0.83 ± 0.01
wine	ENSM	-	0.48 ± 0.03	-	0.58 ± 0.01	0.56 ± 0.02
	EnD^2	0.59 ± 0.03	0.60 ± 0.03	$\mathbf{0.65 \pm 0.01}$	$\mathbf{0.65 \pm 0.01}$	$\mathbf{0.65 \pm 0.03}$
	NWPN	0.42 ± 0.02	0.42 ± 0.02	0.64 ± 0.01	0.64 ± 0.01	0.53 ± 0.02
power	ENSM	-	0.35 ± 0.02	-	0.64 ± 0.02	0.62 ± 0.02
	EnD^2	0.37 ± 0.03	0.37 ± 0.03	$\mathbf{0.66 \pm 0.01}$	$\mathbf{0.66 \pm 0.01}$	0.50 ± 0.02
	NWPN	0.24 ± 0.01	0.24 ± 0.01	0.56 ± 0.01	0.56 ± 0.01	0.31 ± 0.02
msd	ENSM	-	0.66 ± 0.0	-	0.55 ± 0.0	0.62 ± 0.0
	EnD^2	0.66 ± 0.0	0.66 ± 0.0	0.50 ± 0.0	0.50 ± 0.0	0.65 ± 0.0
	NWPN	0.68 ± 0.0	0.68 ± 0.0	0.73 ± 0.0	0.73 ± 0.0	$\mathbf{0.75 \pm 0.0}$

D   DEPTH ESTIMATION EXPERIMENTS

Table 9 shows that EnD also has significantly worse calibration than even a single models, and the temperature annealing improves calibration, both in terms of NLL and C-AUC. The latter is the area between the calibration curve and the diagonal (C-AUC). A histogram of NLL and calibrations curves are provided in the figure below. We can see that EnD^2 yields far more consistent NLL, and has the best predictive intervals in terms of C-AUC, which is the area between the diagonal and the calibration curve. Note, that for all models we assume normally distributed predictive intervals, as was originally done in (Lakshminarayanan et al., 2017).

In RPN training with RKL objective, we observed the optimization trajectory to be very unstable and initialization-sensitive. To combat this, we linearly increase γ from 0 to some predefined value during

(a) NLL   (b) Calibration Curve

Figure 4: NLL histograms and calibration curve.

Table 9: Calibration performance comparison in terms of NLL and C-AUC.

Method	NLL($\downarrow$)	C-AUC($\downarrow$)
ENSM 5	$0.76_{\pm \text{ NA}}$	$0.219_{\pm \text{ NA}}$
Single	$5.93_{\pm 1.72}$	$0.293_{\pm 0.011}$
EnD	$9.11_{\pm 2.65}$	$0.316_{\pm 0.015}$
EnD^2, $T = 1.0$	$-1.43_{\pm 0.02}$	$0.178_{\pm 0.008}$
EnD^2, $T = 10.0$	$\mathbf{-1.47}_{\pm \mathbf{0.06}}$	$\mathbf{0.170}_{\pm \mathbf{0.011}}$

the first five epochs, which allows our models to concentrate initially on predictive performance, and then gradually capture the properties of "in-domain" samples.

Additionally, we performed an ablation study across different coefficients γ, with the results provided in tables 11 and 12. On NYU dataset, we see that models with lower γ improve performance at the cost of decreased quality of OOD detection. This may be an indication that the task of accurate prediction may not align well with the model's ability to detect unfamiliar samples. Based on this, we decided to use the coefficient of $\gamma = 0.05$ as achieving the best trade-off, and then fine-tuned the respective model for 10 additional epochs until convergence.

Table 10: OOD Detection (ROC-AUC) of NYU models on KITTI and vice-versa.

Method	NYUv2 vs KITTI OOD Detect					KITTI vs NYUv2 OOD Detect				
	$\mathcal{H}[\mathbb{E}]$	$\mathbb{V}[\boldsymbol{y}]$	$\mathcal{I}$	$\mathcal{K}$	$\mathbb{V}[\boldsymbol{\mu}]$	$\mathcal{H}[\mathbb{E}]$	$\mathbb{V}[\boldsymbol{y}]$	$\mathcal{I}$	$\mathcal{K}$	$\mathbb{V}[\boldsymbol{\mu}]$
Single	0.892	0.892	-	-	-	0.013	0.013	-	-	-
ENSM	-	0.927	-	0.779	0.929	-	0.02	-	**0.806**	0.076
EnD	0.774	0.774	-	-	-	0.001	0.001	-	-	-
EnD^2	0.896	0.905	**0.946**	0.938	0.935	0.004	0.004	0.750	0.724	0.009

Table 11: RKL ablation on NYU with training OOD KITTI.

Method	Predictive Performance							OOD Detection
	$\delta_1(\uparrow)$	$\delta_2(\uparrow)$	$\delta_3(\uparrow)$	rel($\downarrow$)	rmse($\downarrow$)	$\log_{10}(\downarrow)$	NLL($\downarrow$)	ROC-AUC($\uparrow$)($\mathcal{H}[\mathbb{E}]$)
Single	**0.852**	**0.971**	**0.993**	**0.122**	0.456	0.053	5.74	0.69
NWPN , $\gamma = 0$	0.852	0.971	0.993	0.122	**0.450**	**0.052**	-1.46	0.691
NWPN , $\gamma = 0.005$	0.819	0.957	0.987	0.148	0.496	0.06	**-1.69**	0.803
NWPN , $\gamma = 0.01$	0.805	0.952	0.986	0.148	0.515	0.061	-1.57	0.81
NWPN , $\gamma = 0.025$	0.665	0.905	0.975	0.197	0.666	0.085	-0.84	0.866
NWPN , $\gamma = 0.05$	0.556	0.849	0.956	0.240	0.821	0.106	0.05	**0.876**

Table 12: RKL ablation on KITTI with training OOD NYU.

Method	Predictive Performance							OOD Detection
	$\delta_1(\uparrow)$	$\delta_2(\uparrow)$	$\delta_3(\uparrow)$	rel($\downarrow$)	rmse($\downarrow$)	$\log_{10}(\downarrow)$	NLL($\downarrow$)	ROC-AUC($\uparrow$)($\mathcal{I}$)
Single	0.924	0.987	0.997	0.078	3.537	0.035	2.98	0.845
NWPN , $\gamma = 0$	0.924	0.988	0.997	0.078	3.528	0.035	1.59	0.994
NWPN , $\gamma = 0.005$	0.924	0.987	0.997	0.079	3.392	0.035	1.55	1.0
NWPN , $\gamma = 0.01$	0.919	0.986	0.997	0.080	3.435	0.035	1.52	1.0
NWPN , $\gamma = 0.025$	0.922	0.986	0.997	0.079	3.513	0.036	1.63	1.0
NWPN , $\gamma = 0.05$	0.920	0.986	0.997	0.077	3.526	0.035	1.52	1.0

Figure 5: Uncurated comparison of ENSM vs EnD^2 behaviour on Nyuv2 dataset (best viewed in color).

Figure 6: Uncurated comparison of ENSM vs EnD^2 models trained on Nyuv2 behaviour on Kitti and LSUN-bed datasets (best viewed in color).

Figure 7: Uncurated comparison of ENSM vs EnD^2 behaviour on KITTI dataset (best viewed in color).

Figure 8: Uncurated comparison of ENSM vs EnD^2 models trained on KITTI behaviour on Nyu and LSUN-bed datasets (best viewed in color).