Keywords: RRT, Task and Motion Planning, Model-based Planning, Tree-search

Broadly-Exploring, Local-Policy Trees
for Long-Horizon Task Planning

Abstract: Long-horizon planning in realistic environments requires the ability to reason over sequential tasks in high-dimensional state spaces with complex dynamics. Classical motion planning algorithms, such as rapidly-exploring random trees, are capable of efficiently exploring large state spaces and computing long-horizon, sequential plans. However, these algorithms are generally challenged with complex, stochastic, and high-dimensional state spaces as well as in the presence of narrow passages, which naturally emerge in tasks that interact with the environment. Machine learning offers a promising solution for its ability to learn general policies that can handle complex interactions and high-dimensional observations. However, these policies are generally limited in horizon length. Our approach, Broadly-Exploring, Local-policy Trees (BELT), merges these two approaches to leverage the strengths of both through a task-conditioned, model-based tree search. BELT uses an RRT-inspired tree search to efficiently explore the state space. Locally, the exploration is guided by a task-conditioned, learned policy capable of performing general short-horizon tasks. This task space can be quite general and abstract; its only requirements are to be sampleable and to well-cover the space of useful tasks. This search is aided by a task-conditioned model that temporally extends dynamics propagation to allow long-horizon search and sequential reasoning over tasks. BELT is demonstrated experimentally to be able to plan long-horizon, sequential trajectories with a goal conditioned policy and generate plans that are robust.

1 Introduction

For a robot to plan complex long-horizon tasks in realistic environments, it must be capable of reasoning over sequences of subtasks. It must broadly search the space of possible trajectories while considering both what the subtasks are and the order in which they are accomplished. It must handle the complex and high dimensional state space and dynamics of the real world. Consider, for example, a robot cleaning a kitchen. A planner must find trajectories to put a utensil away, to wash a pot, to throw away trash, and more. Each of these tasks requires the ability to understand and execute lower-level tasks involved, as well as their order; to put a utensil away, the robot must first open a drawer, then grasp the utensil, then place it in the drawer, and finally close the drawer.

Classical planning algorithms are capable of efficiently and broadly searching state spaces and planning over long-horizons [1, 2]. However, they have difficulty in the presence of complex, stochastic dynamics, high-dimensional systems, and so-called narrow passages (which tasks naturally create). Machine learning has emerged as the state of the art for problems with high-dimensional observations (e.g., pixels) and challenging dynamics (e.g., environment interaction). Furthermore, it allows learning policies for general and abstract tasks [3, 4, 5, 6, 7]. However, many such approaches are limited to short-horizons [8, 9].

We propose a method which leverages the best of both approaches, a tree search which explores the state space in an RRT-like manner, but where edges maintain a consistent task executed by a learned, task-conditioned policy (Fig. 1). In this work, we define task in a general sense, with a requirement only that the task space is sampleable and well-covers the space of useful actions; for example, this includes goal-conditioned policies, explicit tasks, learned skills, and latent task embeddings. The local, task-conditioned policy is thus capable of executing complex short-horizon tasks. The skeleton of the RRT search allows rapid exploration of the state space. This exploration is

Figure 1: BELT plans long-horizon trajectories via a task-conditioned tree and task-model.

aided by a task-conditioned model, capable of rolling out long-horizon trajectories, which can then be planned over and reasoned about in a model-based manner to the limit of the known, predictable environment. Broadly-Exploring, Local-policy Trees (BELT) is thus able to create long-horizon plans with sequential, complex tasks.

1.1 Related Work.

Planning Algorithms are capable of efficiently, and globally, exploring state spaces to plan long-horizon trajectories which avoid collision [1, 2, 10]. Within robotics, as the robot must interact with the world, planning algorithms often consider the task and motion planning setting (contrasting with AI planning, for example, for which approaches often consider explicit tasks and constraints). Approaches in this setting generally plan in a hierarchical manner by defining task-primitives and planning over them, for example, via trees or optimization-based methods [11, 12, 13, 14, 15, 16]. These methods perform well in long-horizon planning, but are limited by their task representations, the dimensionality of the search space, and their ability to execute high-dimensional, complex tasks robustly.

Model-Free Learning offers a promising direction to execute such tasks, though theses methods have difficulty reasoning over long horizons. To enable long-horizon performance, previous works often enforce hierarchy or embed policies within classical structure. Hierarchical reinforcement learning [4, 5, 17] works to temporally extend planning at lower levels, reducing the horizon the high-level policy must reason over [18]. Recent work on goal-conditioned reinforcement learning learns to efficiently achieve arbitrary goal states [19, 3]. This casts the problem for the high-level policy as finding a sequence of goal states [8, 9, 20, 21]. This also allows the embedding of policies in classical motion planning structures [22, 23, 24, 25, 26, 27, 28, 29]. Search on the replay buffer (SoRB) [26] for example builds a searchable graph of the replay buffer given a learned distance metric for a goal-conditioned policy. In contrast to SoRB and other previous work, BELT uses a tree search equipped with a task-conditioned model to enable searching for plans outside of previous experience and is capable of solving non-goal-conditioned tasks with its model-based success check.

Model-based Planning allows longer-horizon, sequential planning by moving reasoning to the model level. In this way planning can be performed by rolling out models and evaluating such rollouts, [30, 31]. To extend the performance of models to longer-horizons, models can be trained for multi-step prediction [32] and planned over [33]. Others use models within classical algorithms, such as sampling-based motion planning [34] or control [35, 36]. In this work, we leverage a task-conditioned model to temporally extend the model prediction over edges with consistent tasks, resulting in more robust long-range performance. We additionally use the model to broadly search the state space via an RRT-inspired search.

1.2 Statement of Contributions.

The contribution of this paper is an algorithm Broadly-Exploring, Local-policy Trees (BELT) that is capable of planning long-horizon, sequential tasks in complex environments. BELT leverages (**1** – Sections 2 and 2.2) the state space exploration abilities of planning through an RRT-inspired search, (**2** – Section 2.1) the local guidance of a learned task-conditioned policy, capable of executing complex tasks in high-dimensional spaces, and (**3** – Section 2.3) the long-horizon propagation and reasoning of a learned, temporally extended task-conditioned model. BELT is demonstrated with a learned goal-conditioned policy in a realistic environment to plan effectively, significantly outperforming baselines. Furthermore, these plans are directly executable by the policy.

2 Broadly-Exploring, Local-policy Trees

We begin with a general outline of BELT and then discuss concrete implementations of algorithmic subroutines in Sections 2.1 - 2.3. Briefly, BELT searches for long-horizon, sequential plans via a model-based, task-conditioned tree search. This search is built on a backbone of a Rapidly-exploring Random Tree (RRT) with a local, learned task-conditioned policy. This approach leverages the efficient global-exploration of RRTs, the local directed actions of a learned task-conditioned policy, and the sequential reasoning of a model.

In this work we refer to a task and task space in a general sense and we consider planning in environments which are predictable and known. The only requirements of the task space $\mathcal{Z}$ is that it is sampleable and well-covers the space of useful actions. For example, this can be explicitly given as a set of tasks, implicitly learned via a latent task space, or structured as the state space $\mathcal{X}$ with a goal-conditioned policy. To allow for general task definitions, a success criteria Success is used that is considered a "black box". Given a trajectory $\{x_{\text{init}}, ..., x_T\}$, Success outputs if the trajectory satisfies all necessary conditions. This formulation allows for a general problem definition that includes goal-conditioned planning, but also allows for transient tasks that cannot be expressed by a goal state. The cost used in this work, referred to interchangeably with distance, is the time of a trajectory, though the approach is general to other costs. The environment considered in this work is continuous, known, and static, with the exception of motion as a result of interaction with the robot. The complexity of the environment arises generally from high dimensional states (e.g., many objects) and challenging interactions (e.g., grasping) and the sequentiality arises from tasks which are bottlenecked by previous task completion.

Figure 2: BELT with Play Latent Motor Plans [37] learns a general, goal-conditioned policy as well as a model from teleoperation data. Given a long-horizon task, BELT translates this into an RRT-inspired, model-based tree search through the space, where each edge represents a single task sampled from demonstration data. Trajectories are verified successful via a trajectory-wise success check on the model and executed by the policy.

The search is outlined in Algorithm 1 and BELT is shown with progressively more concreteness in Figs. 1 - 3. Fig. 1 shows a hypothetical form of BELT with an explicit task space, Fig. 2 shows BELT with a goal-conditioned policy that is learned from play [37], and Fig. 3 shows BELT as applied to the experimental environment used herein. A new planning problem is defined by an initial state, x_{init}, and by success criteria Success. The search begins by initializing a tree $\mathcal{T}$ with x_{init} as its root and iteratively adding task-conditioned edges. For each iteration i, a state $x_{\text{expand}} \in \mathcal{T}$ within the tree is selected, along with a task $z_i \in \mathcal{Z}$. BELT requires a sampleable task space $\mathcal{Z}$ and task-conditioned policy, $\pi(a_t|x_t, z_i)$, which outputs an action a_t at time t given the current state x_t and task z_i. The goal of the task space is to well cover the state space and guide the search towards useful actions; the task space and policy used herein are discussed in detail in Section 2.1. The goal of the selection of the tree node x_{expand} is to guide the search towards unexplored regions and to exploit promising paths; this is discussed in detail in Section 2.2. Given the task z and state x_{expand}, the policy is then propagated for T timesteps via a model $p(x_{t+1}|x_t, a_t)$ to create trajectory $\{x_{\text{expand}}, x_1, ..., x_{T-1}, x_{\text{new}}\}$. The goal of the model is to provide accurate predictions of trajectories given a task (in the absence of known dynamics); the model used herein is discussed in more detail in Section 2.3. In this way, each edge may be thought of having a temporally extended consistent intent, such as attempting a single task or reaching a goal. This edge is then added to the tree and the trajectory from x_{expand} to x_{new} is checked for success with Success. This search continues for N iterations, at which time the lowest-cost path marked as successful is returned if it exists.

129 *Theoretical Results.* Briefly we note the lack of theoretical results for this work. These are precluded
130 by the use of (1) a non-uniform sampling distribution and (2) a learned policy which both bias the
131 search to useful regions, limiting full coverage of the state space. The learned model also can be
132 inaccurate, limiting guarantees. While each of these is required to make BELT feasible in such a
133 complex domain, without them the theoretical results from [10] and [28] can be trivially applied.

(a) Policy takes as input a goal state, the current state and samples from its latent "plan" space. This is then input to the model.

(b) At each iteration BELT samples a goal from demonstration data and a tree state and rolls out a task-conditioned model to add edges to the tree. The solution trajectory is selected as the lowest cost solution, as verified by the binary success check `Success`. Larger figure in Appendix Section 5.4.

Figure 3: Broadly-Exploring, Local-policy Trees with a Play-LMP policy (Section 2.1).

Algorithm 1 Broadly-Exploring, Local-policy Trees

Input: initial state x_{init}, sample count N, and success check `Success`
1: Initialize tree $\mathcal{T}$ with state x_{init}.
2: **for** i in $1 : N$ **do**
3:    Sample a task z_i from task space $\mathcal{Z}$.   ▷ Section 2.1
4:    Select a state x_{expand} from $\mathcal{T}$ to expand from.   ▷ Section 2.2
5:    **for** t in $1 : T$ **do**
6:        Run policy $a_t \sim \pi(a_t | x_t, z_i)$.   ▷ Section 2.1
7:        Rollout model $x_{t+1} \sim p(x_{t+1} | x_t, a_t)$.   ▷ Section 2.3
8:    Update $\mathcal{T}$ with state x_i, trajectory $\{x_{\text{expand}}, ..., x_i\}$, task z_i, and `Success`($\{x_{\text{init}}, ..., x_i\}$).
9: **return** minimum time successful trajectory or failure if none

---

2.1 Learning a Task Space and Task-Conditioned Policy From Play

135 In this work we implement BELT with a general-purpose goal-reaching policy at the low level,
136 called Learning from Play (LfP) [37]. To learn from "play" we assume access to an unsegmented
137 teleoperated play dataset $\mathcal{D}$ of semantically meaningful behaviors provided by users, without a set
138 of predefined tasks in mind. For example, a user might open and close doors, rearrange objects, or
139 simply tidy the scene.

140 To learn control, this long temporal state-action log $\mathcal{D} = \{(x_t, a_t)\}_{t=0}^{\infty}$ is relabeled [3, 19], treating
141 each visited state in the dataset as a "reached goal state", with the preceding states and actions treated
142 as optimal behavior for reaching that goal. Relabeling yields a dataset of $D_{\text{play}} = \{(\tau, x_g)_i\}_{i=0}^{D_{\text{play}}}$,
143 where each example consists of a goal state x_g and a demonstration $\tau = \{(x_0, a_0), ...\}$ solving for
144 the goal. These can be fed to a simple maximum likelihood goal conditioned imitation objective,

145 $\mathcal{L}_{\text{LfP}} = \mathbb{E}_{(\tau, \, x_g) \sim D_{\text{play}}} \left[\sum_{t=0}^{|\tau|} \log \pi_\theta \left(a_t | x_t, x_g \right) \right]$, to learn policy $\pi_\theta \left(a_t | x_t, x_g \right)$, parameterized by
146 θ. The motivation behind this collection is to allow play to fully cover the state space using prior
147 human knowledge, then to distill short-horizon behaviors into a single goal-directed policy.

148 We could in principle use any goal-directed imitation network architecture to implement the policy
149 $\pi_\theta \left(a_t | x_t, x_g \right)$. For direct comparison to prior work, we use Play Supervised Latent Motor Plans
150 (Play-LMP) [37]. Play-LMP addresses the inherent multimodality in free-form imitation datasets.
151 Concretely it is a sequence-to-sequence conditional variational autoencoder (seq2seq CVAE), au-
152 toencoding contextual demonstrations through a latent "plan" space. The decoder is a policy trained
153 to reconstruct input actions, conditioned on state x_t, goal x_g, and an inferred plan z for how to get
154 from x_t to x_g. At test time, Play-LMP takes a goal as input, and infers and follows plan z internally.
155 A t-SNE of this plan space is shown in Fig. 3a. See [37] for details.

2.2 Biasing the Search

157 Given a goal-conditioned policy, as Play-LMP is, RRT [1] is used with a few adaptions to broadly
158 search the state space, chose achievable edge tasks, and bias towards low-cost paths (Fig. 4a).

159 To broadly search the state space, a key component of RRT's ability to efficiently explore is what is
160 known as the Voronoi bias. For an RRT, this bias states that at each iteration, the selection of the tree
161 node for expansion is proportional to the volume of its Voronoi region, meaning nodes in larger un-
162 explored regions are more likely to be selected and thus RRTs rapidly explore [1]. To select a node
163 in RRT, a sample is drawn from the state space and the nearest node within the tree is selected as the
164 expansion node. For BELT, we seek to leverage a Voronoi bias via a temporal distance Δt between
165 states $x_i, x_j \in \mathcal{X}$ as the L2 distance is not a good distance for this problem. For example, consider
166 the block in Fig. 3b. If it is inside the drawer or on top of the desk, the L2 distance is quite small, but
167 to connect these two states requires opening the drawer, grasping the block, placing the block, and
168 closing the drawer – a significant distance. As the temporal distance is not easily quantifiable, we
169 learn to predict it with a temporal distance classifier, $\tau_{\text{tdc}}(x_i, x_j)$, with K exponential categories cor-
170 responding to temporal distance intervals, $d_k \in \{[0, 1), [1, 2), [2, 4), [4, 8), [8, 16), ..., [128, 256)\}$
171 based on [38]. The temporal distance classifier is implemented as a neural network and trained over
172 policy rollouts to predict the distribution over class labels via a cross-entropy classification loss,
173 $\mathcal{L}_{\text{tdc}} = -\sum_{l=1}^{K} y_l \log(\hat{y}_l)$ with $\hat{y} = \tau_{\text{tdc}}(x_i, x_j)$, where y and $\hat{y}$ are the true and predicted label
174 distributions respectively. Briefly, we note that we also considered a temporal distance regressor,
175 but found it considerably less accurate.

176 The selection of an expansion state thus proceeds by first selecting a goal state from a demonstration
177 dataset from rollouts of the policy $x_{\text{sample}} \in \mathcal{D}_\pi$. The temporal distance is then predicted between
178 x_{sample} and each node in the tree. All nodes below a cutoff temporal distance d_{cutoff} are then added
179 to a set of possible nodes to expand from. Within this set the node with the lowest-cost to come is
180 selected for expansion, x_{expand}. This biases the tree search towards nodes that are capable of reaching
181 the goal state and towards nodes with efficient trajectories. It further allows a Voronoi bias by tem-
182 poral distance. The value of d_{cutoff} represents a trade-off between exploiting more promising paths
183 (larger values of d_{cutoff}) and exploring new ones (smaller values of d_{cutoff}); this trade-off is studied
184 experimentally in the Appendix Section 5.3. This procedure modifies lines 3 and 4 of Algorithm 1.

185 We note that a common and effective approach to biasing search in sampling-based motion planning
186 is to goal bias, i.e., biasing samples towards states within the goal region. As success often requires
187 full sequences of trajectories rather than individual states we do not generally have access to goal
188 states in this problem setting and thus we do not use goal biasing of this form.

2.3 Learning a Task-Conditioned Model

190 Given a policy, the tree search plans via a model. In this work we consider three options for models:
191 a simulator, an action-conditioned model, and a task-conditioned model, each shown in Fig. 4b
192 and 4c. Access to a simulator or the exact dynamics is assumed for much of the motion planning
193 community when planning (unless explicitly planning under uncertainty). This acts as an upper
194 bound herein and tests the ability of BELT to explore the state space and plan sequential tasks given
195 a perfect model. It also shows bounds on the robustness of our policy. The action-conditioned model
196 learns to predict the next state $p_{\text{action}}(x_{t+1}|x_t, a_t)$ given the current state x_t and action a_t. For a given
197 trajectory, this is recursively applied for T timesteps. The task-conditioned model learns a prediction
198 of where the robot will be after T timesteps, i.e., $p_{\text{task}}(x_{t+T}|x_t, z)$. This accounts for the closed-
199 loop nature of the policy for a fixed task and temporally extends the prediction to reduce recursive
200 errors. For the Play LMP policy, the task conditioning z corresponds to a goal state and a latent plan.

(a) Biasing the tree search   (b) Task- and action-models

(c) Task-models, action-model, and simulator our experiment environment (see video). Larger figure available in Appendix Section 5.4.

Figure 4: (4a) shows the bias used by BELT to choose the tree state x_{expand} once x_{sample} has been sampled. The blue region shows how the temporal distance between states may differ from the L2 distance, necessitating learning a temporal distance classifier. The choice between state 1 and 3 demonstrates the bias towards lower cost paths: though state 1 is closer to x_{sample}, node 3 has a much lower cost to come, and thus state 3 is selected. (4b-4c) shows the two types of models used in this work, an action- and a task-conditioned model. The action-conditioned model often exhibits compounding errors as it is recursively applied along the trajectory, while the task-conditioned model avoids this by temporally extending the prediction and conditioning on the fixed task for the edge. This compounding error can be seen in the second task (block lifting) where the action-model becomes unstable and the end effector flails (see video at 162s).

Each model is represented as a neural network and trained from a dataset of demonstration policy rollouts to minimize the L2 reconstruction loss. For a given rollout for task z, states $\{x_0, x_1, ..., x_T\}$, and actions $\{a_0, a_1, ...a_{T-1}\}$, the action-model seeks to minimize $\mathcal{L}_{p_{\text{action}}} = \sum_{t=0}^{T-1} ||\hat{x}_{t+1} - x_{t+1}||$ with $\hat{x}_{t+1} \sim p_{\text{action}}(x_t, a_t)$, while the task-model seeks to minimize $\mathcal{L}_{p_{\text{task}}} = ||\hat{x}_T - x_T||$ with $\hat{x}_T \sim p_{\text{task}}(x_0, z)$.

3 Experimental Results

The experiments herein are based on a simulated "playground environment" [37] (Discussed in more detail in the Appendix and shown in Appendix Fig 7) built in Mujoco [39]. The robot is a position-controlled 8-DOF robotic arm and gripper. The robot receives as observations at each timestep of the cartesian position and orientation of all objects including its end effector. The agent performs high-frequency, closed-loop control, sending continuous position, rotation, and gripper commands to its arm at 30 Hz. The environment is known and static (unless the direct result of interaction with the robot) and contains a desk with a sliding door and drawer that can be opened and closed as well as a movable rectangular block and 3 buttons that can be pushed to turn on different colored lights.

Long-horizon evaluation. We evaluate our model and its baselines on large set of challenging long-horizon manipulation tasks as in [40], which require several subtasks to be executed in order. Here, multi-stage tasks are constructed by considering all valid N-stage transitions between a set of 18 core short-horizon manipulation tasks. See [37, 40] for a complete discussion of the 18 tasks, which span different families, e.g. pushing buttons, opening and closing doors/drawers, grasping and lifting a block, etc. We evaluate on "Chain-4", which results in 925 unique task chains (Appendix Fig. 7).

Note that prior work [40] assumes a human is in the loop providing each next subtask to the agent in the sequence. In our setup, an agent must provide *itself* subgoals to achieve the multi-stage behavior. Other prior long-horizon evaluations, such as [9], describe the long-horizon task as a final goal state to reach. While this valid for many useful manipulation tasks, many are impossible to infer from the

final goal state alone. For example, in this environment, when a button is no longer pressed down, the corresponding light turns off. In this way, the final state for task "1) open drawer, 2) push green button, 3) close drawer" may appear to an agent as "no change to the environment". We consider a more general task specification scheme—an indicator function, defined over the full agent trajectory, which returns true if the full desired sequence was executed correctly and false otherwise. We refer to this here as the "success detector", which our high-level agent plans against.

3.1 Algorithmic Parameters and Baselines

Baselines. We compare against two baselines that use the same underlying Play-supervised Latent Motor Plan (Play-LMP) [37] policy. We compare to a model-based planner (cross entropy method (CEM) [41]) and a Play-LMP with given goal state. CEM was implemented in the task space to select four sequential tasks. The tasks were then rolled out with the simulator and task-model. The distribution was then refit to successful trajectories. We also compare to a Play-LMP policy that is given a single goal-state that satisfies all the subtasks (this single goal state existed for 36% of the chains). This baseline demonstrates the limitations of the model-free policy to execute long-horizon tasks. Finally, we also compare to an "oracle" LMP policy, which is given the four chain tasks in a row, demonstrating an upper bound of what the BELT plan may achieve given the underlying policy.

Parameters. The low-level policy is trained with the same play logs collected in [37]; $\sim$7h of teleoperated play relabeled into D_{play}, containing $\sim$10M short-horizon demonstrations, each 1-2 seconds (see video for examples of this data). The TDC and models were trained on demonstration data for $\sim$ 100k rollouts. τ_{tdc} was trained on this dataset to an accuracy of 82% and d_{cutoff} was set to < 64 based on analysis in the next section. The edges were rolled out with a randomly drawn timestep of $T \in \{32, 64, 96\}$, as inspired by [10]. BELT used 2500 goal samples drawn from demonstration data of the policy rollouts. We note that we also tried samples from the play dataset, but found many of the goals unreachable and the performance worse. More detail on the BELT's algorithmic parameters and tradeoffs are detailed in the Appendix.

3.2 Results

We begin by comparing the overall performance of BELT, different models, and the baselines in Table 1 on the chain tasks and Fig. 5 shows several planned trajectories. We study each algorithm's performance on the axis of finding solutions (based on the algorithm output) and on robustness. Chain-LMP shows the upper bound of robustness of the policy to repeat four successive tasks. CEM with the simulator and LMP with a single-goal state fail to solve most chains. CEM with the model solves more tasks, but the solutions are not robust as the search seems to exploit inaccuracies in the model. BELT with the action model too exploits model inaccuracies – the model quickly becomes unstable as it is recursively rolled out over every timestep. Solutions are found for all chains, but the solutions are not robust or even feasible for most. The task model performs much better due to its temporally extended prediction, though we note multistep predictions hold promise to improve the action-conditioned results [32].

BELT with the task model and the simulator perform well, solving 66% and 82% of the problems respectively, and replay at similar rates and only slightly worse than the oracle. This demonstrates BELT's ability to both search the space of solutions and find feasible plans. The task model solves 16% fewer problems than directly using the simulator.

Algorithm	Model	Solution Found	Success Rate	Feasible
Chain-LMP (Oracle)	–	–	32%	87%
LMP	–	–	6%	21%
CEM	Simulator	3%	40%	58%
CEM	Task-Model	11%	7%	15%
BELT	Action-Model	100%	3%	8%
BELT	Task-Model	66%	27%	56%
BELT	Simulator	82%	26%	68%

Table 1: Success rate and robustness for BELT, CEM, and LMP. Plan robustness is measured by the percent of solutions executed successfully (success rate) and if there was at least one successful in nine attempts (feasible).

In Table 2, we analyze which tasks proved most difficult for BELT, and particularly where the task-conditioned model and the simulator performance most diverged. For both the simulator and task-model, the button presses proved to be part of the most difficult chains to plan and execute. This is a because the button presses are transient and do not leave a permanent state change, which is particularly challenging for a goal-conditioned low-level policy to well cover. The task-model has difficulty with chains with the "rotate left" task on the block, while the simulator plans quite well

	Solution Found			Feasible		
Chain Contains Task	BELT Simulator	BELT Task-Model	Ratio	BELT Simulator	BELT Task-Model	Ratio
overall	82%	66%	0.81	68%	56%	0.82
button, push any	73%	54%	0.74	**63%**	**32%**	**0.50**
drawer open/close	82%	70%	0.85	69%	64%	0.93
grasp	92%	77%	0.84	73%	70%	0.95
knock	91%	71%	0.78	58%	55%	0.95
rotate left	**93%**	**0%**	**0.00**	**38%**	–	–
rotate right	89%	78%	0.88	77%	74%	0.97
shelf, in/out	77%	56%	0.72	57%	54%	0.95
slider, open/close	81%	63%	0.78	67%	58%	0.87
sweeping	76%	64%	0.84	65%	76%	1.17

Table 2: Task performance breakdown. The task-model particularly has difficulty planning "rotate left" tasks due to an angle discontinuity, and the policy has trouble executing the task for the same reason. The task-model plans execute poorly with any buttons, likely because the model makes predictions from goal states and the button tasks are transient, thus not often appearing in goal states.

Figure 5: Plans from BELT, demonstrating its ability to plan long-horizon, sequential trajectories (see submitted video at 193s).

over them but fail to execute many. This is a result of the discontinuity of angles, i.e., if the block starts at 0 radians and is rotated left, the angle jumps to 2π radians, which is particularly difficult for the model. This indicates a need for an angular representation such as quaternions or axis-angles.

4 Conclusion and Future Work

Conclusions. This work presented BELT, an algorithm capable of planning long-horizon tasks. BELT leverages the rapid state space exploration of RRT, the robust and general local performance of learned task-conditioned policies, and the long-horizon reasoning of a task-conditioned model. It is demonstrated in a realistic, complex, manipulation environment with a goal-conditioned policy to be capable of planning consistently and robustly.

Real-world Experiments. This method builds upon a scalable approach to learning goal-conditioned low-level policies ([37]), which were demonstrated to yield high success rate on the 18-task benchmark using onboard sensors only. While these results were obtained in simulation, the scalability of the local policy learning makes real-world deployment promising. Our work also relies on task success detectors, real-world experiments could make use of learned success classifiers such as [42]. Hence we estimate that there is a reasonable and scalable path to real-world experiments and plan to explore this in future work.

Application to Dynamic and Unknown Environments. In settings where the environment is dynamic or not fully observed, BELT plans may be limited in horizon. In these settings, the BELT tree can be reused to quickly replan, either by rewiring based on changes or by planning trajectories back into the tree in case of plan divergence. Furthermore, concepts from BELT can be used to form a graph and maintain a representation of possible paths through the environment.

Future Work. In the future we wish to show how BELT can be extended well beyond the dataset and to other task representations and models. We further wish to study how it can be used quickly in replanning, and particularly how the existing tree may be reused. Finally, we wish to study methods for generating not just any feasible plan, but robust and efficient plans.

References

[1] S. M. LaValle and J. J. Kuffner Jr. Randomized kinodynamic planning. *IJRR*, 2001.

[2] S. Karaman and E. Frazzoli. Sampling-based algorithms for optimal motion planning. *IJRR*, 2011.

[3] M. Andrychowicz, F. Wolski, A. Ray, J. Schneider, R. Fong, P. Welinder, B. McGrew, J. Tobin, O. P. Abbeel, and W. Zaremba. Hindsight experience replay. In *Advances in neural information processing systems*, 2017.

[4] P.-L. Bacon, J. Harb, and D. Precup. The option-critic architecture. In *AAAI*, 2017.

[5] R. Fox, S. Krishnan, I. Stoica, and K. Goldberg. Multi-level discovery of deep options. *arXiv preprint arXiv:1703.08294*, 2017.

[6] B. Eysenbach, A. Gupta, J. Ibarz, and S. Levine. Diversity is all you need: Learning skills without a reward function. *arXiv preprint arXiv:1802.06070*, 2018.

[7] D. Xu, S. Nair, Y. Zhu, J. Gao, A. Garg, L. Fei-Fei, and S. Savarese. Neural task programming: Learning to generalize across hierarchical tasks. In *ICRA*, 2018.

[8] O. Nachum, S. S. Gu, H. Lee, and S. Levine. Data-efficient hierarchical reinforcement learning. In *Advances in Neural Information Processing Systems*, 2018.

[9] A. Gupta, V. Kumar, C. Lynch, S. Levine, and K. Hausman. Relay policy learning: Solving long-horizon tasks via imitation and reinforcement learning. *arXiv preprint arXiv:1910.11956*, 2019.

[10] Y. Li, Z. Littlefield, and K. E. Bekris. Sparse methods for efficient asymptotically optimal kinodynamic planning. In *Algorithmic foundations of robotics XI*. 2015.

[11] L. P. Kaelbling and T. Lozano-Pérez. Hierarchical planning in the now. In *Workshops at AAAI*, 2010.

[12] L. P. Kaelbling and T. Lozano-Pérez. Integrated task and motion planning in belief space. *IJRR*, 2013.

[13] K. Hauser and J.-C. Latombe. Integrating task and prm motion planning: Dealing with many infeasible motion planning queries. In *ICAPS09 Workshop on Bridging the Gap between Task and Motion Planning*, 2009.

[14] D. S. Nau, T.-C. Au, O. Ilghami, U. Kuter, J. W. Murdock, D. Wu, and F. Yaman. Shop2: An htn planning system. *Journal of artificial intelligence research*, 2003.

[15] J. Wolfe, B. Marthi, and S. Russell. Combined task and motion planning for mobile manipulation. In *ICAPS*, 2010.

[16] M. Toussaint. Logic-geometric programming: An optimization-based approach to combined task and motion planning. In *IJCAI*, 2015.

[17] A. S. Vezhnevets, S. Osindero, T. Schaul, N. Heess, M. Jaderberg, D. Silver, and K. Kavukcuoglu. Feudal networks for hierarchical reinforcement learning. *arXiv preprint arXiv:1703.01161*, 2017.

[18] O. Nachum, H. Tang, X. Lu, S. Gu, H. Lee, and S. Levine. Why does hierarchy (sometimes) work so well in reinforcement learning? *arXiv preprint arXiv:1909.10618*, 2019.

[19] L. P. Kaelbling. Learning to achieve goals. In *IJCAI*, 1993.

[20] S. Nair and C. Finn. Hierarchical foresight: Self-supervised learning of long-horizon tasks via visual subgoal generation. *arXiv preprint arXiv:1909.05829*, 2019.

[21] A. V. Nair, V. Pong, M. Dalal, S. Bahl, S. Lin, and S. Levine. Visual reinforcement learning with imagined goals. In *Advances in Neural Information Processing Systems*, 2018.

[22] A. Faust, K. Oslund, O. Ramirez, A. Francis, L. Tapia, M. Fiser, and J. Davidson. Prm-rl: Long-range robotic navigation tasks by combining reinforcement learning and sampling-based planning. In *ICRA*, 2018.

[23] H.-T. L. Chiang, J. Hsu, M. Fiser, L. Tapia, and A. Faust. Rl-rrt: Kinodynamic motion planning via learning reachability estimators from rl policies. *IEEE RAL*, 2019.

[24] N. Savinov, A. Dosovitskiy, and V. Koltun. Semi-parametric topological memory for navigation. *arXiv preprint arXiv:1803.00653*, 2018.

[25] C. Paxton, V. Raman, G. D. Hager, and M. Kobilarov. Combining neural networks and tree search for task and motion planning in challenging environments. In *IROS*, 2017.

[26] B. Eysenbach, R. R. Salakhutdinov, and S. Levine. Search on the replay buffer: Bridging planning and reinforcement learning. In *Advances in Neural Information Processing Systems*, 2019.

[27] A. Zhang, S. Sukhbaatar, A. Lerer, A. Szlam, and R. Fergus. Composable planning with attributes. In *ICML*, 2018.

[28] B. Ichter, J. Harrison, and M. Pavone. Learning sampling distributions for robot motion planning. In *ICRA*, 2018.

[29] A. H. Qureshi, A. Simeonov, M. J. Bency, and M. C. Yip. Motion planning networks. In *ICRA*, 2019.

[30] L. Kaiser, M. Babaeizadeh, P. Milos, B. Osinski, R. H. Campbell, K. Czechowski, D. Erhan, C. Finn, P. Kozakowski, S. Levine, et al. Model-based reinforcement learning for atari. *arXiv preprint arXiv:1903.00374*, 2019.

[31] J. Schrittwieser, I. Antonoglou, T. Hubert, K. Simonyan, L. Sifre, S. Schmitt, A. Guez, E. Lockhart, D. Hassabis, T. Graepel, et al. Mastering atari, go, chess and shogi by planning with a learned model. *arXiv preprint arXiv:1911.08265*, 2019.

[32] D. Hafner, T. Lillicrap, I. Fischer, R. Villegas, D. Ha, H. Lee, and J. Davidson. Learning latent dynamics for planning from pixels. In *ICML*, 2019.

[33] D. Hafner, T. Lillicrap, J. Ba, and M. Norouzi. Dream to control: Learning behaviors by latent imagination. *arXiv preprint arXiv:1912.01603*, 2019.

[34] B. Ichter and M. Pavone. Robot motion planning in learned latent spaces. *IEEE RAL*, 2019.

[35] M. Watter, J. Springenberg, J. Boedecker, and M. Riedmiller. Embed to control: A locally linear latent dynamics model for control from raw images. In *Advances in neural information processing systems*, 2015.

[36] N. Levine, Y. Chow, R. Shu, A. Li, M. Ghavamzadeh, and H. Bui. Prediction, consistency, curvature: Representation learning for locally-linear control. *arXiv preprint arXiv:1909.01506*, 2019.

[37] C. Lynch, M. Khansari, T. Xiao, V. Kumar, J. Tompson, S. Levine, and P. Sermanet. Learning latent plans from play. In *CoRL*, 2020.

[38] Y. Aytar, T. Pfaff, D. Budden, T. Paine, Z. Wang, and N. de Freitas. Playing hard exploration games by watching youtube. In *Advances in Neural Information Processing Systems*, 2018.

[39] E. Todorov, T. Erez, and Y. Tassa. Mujoco: A physics engine for model-based control. In *IROS*, 2012.

[40] C. Lynch and P. Sermanet. Grounding language in play. *arXiv preprint arXiv:2005.07648*, 2020. URL https://arxiv.org/abs/2005.07648.

[41] R. Y. Rubinstein and D. P. Kroese. *The cross-entropy method: a unified approach to combinatorial optimization, Monte-Carlo simulation and machine learning*. Springer Science & Business Media, 2013.

[42] A. Singh, L. Yang, K. Hartikainen, C. Finn, and S. Levine. End-to-end robotic reinforcement learning without reward engineering, 2019.