ECHO: Terminal Agents Learn World Models for Free

Abstract

CLI agents are the closest thing language models have to an embodied setting: the model emits commands, the terminal executes them, and the returned stream—stdout, errors, file contents—records the consequences of its actions. We argue that this stream is a supervision signal, but standard agent RL largely discards it: GRPO-style training updates action tokens while ignoring environment responses, even though rollouts already contain them. We introduce **ECHO** (Environment Cross-entropy Hybrid Objective), an auxiliary loss that trains the policy to predict observation tokens alongside the policy gradient. ECHO reuses the same forward pass, requires no additional rollouts, and turns terminal feedback into a dense signal that remains informative even on failed trajectories. This objective shapes the policy toward a world model of terminal dynamics, plausibly improving its priors over which actions are likely to succeed. On TerminalBench 2, ECHO nearly doubles pass@1: Qwen3-8B improves from 2.70% to 5.17%, and Qwen3-14B from 5.17% to 10.79%. From base Qwen3-8B, ECHO+GRPO matches expert-SFT-then-GRPO on held-out terminal tasks without the expert demonstrations required for SFT, and closes roughly half this gap on TerminalBench 2. Without verifier rewards, ECHO can lead to self-improvement through exploration alone, suggesting environment observations are not merely context for actions but supervision for the policy itself.

Figure 1: ECHO supervises terminal observation tokens already present in GRPO rollouts. GRPO updates only action tokens; ECHO also trains the policy to predict the terminal responses those actions elicit.

1 Introduction

Language-model agents learn by acting in environments: a terminal agent edits files, runs tests, reads errors, and issues follow-up commands until a verifier declares success or failure. The terminal responds to every action with real environment feedback, but the reward signal that ultimately reaches the trainer is sparse, delayed, and binary.

This sparsity is particularly pronounced in terminal-agent training. As a concrete example, in our Qwen3-8B setting, fewer than 15% of on-policy rollouts solve the task, so under standard GRPO [Shao et al., 2024] the vast majority of interaction yields little policy-gradient signal. These rollouts are far from uninformative.

Even a failed trajectory contains the actual outputs of whatever the agent ran: file listings, training logs, build errors, the contents of a config file, the response from a web request, a stack trace, the result of a `grep`, or anything else a shell can produce. Every token from the terminal enters the model's forward computation, yet none of it enters the loss. The transcript becomes context for the next action and nothing more — and we believe this wastes the most abundant signal in an interactive environment. *We instead train on these tokens directly.*

Why should this help? A long-running intuition in language modeling is that good prediction implies good understanding: predicting the next token well, in Sutskever's phrasing, "means you understand the underlying reality that led to the creation of that token" [Sutskever, 2023]. We borrow this view for agents. To predict what the terminal will return after a command, the model has to internalize what the command actually does. A policy that predicts terminal output well is, in a small but real sense, a policy that understands terminals.

We introduce **ECHO** (Environment Cross-entropy Hybrid Objective), an auxiliary loss for multi-turn agent RL. ECHO adds cross-entropy on environment-observation tokens to the usual GRPO loss on action tokens:

$$\mathcal{L}_{\text{ECHO}}(\theta) = \mathcal{L}_{\text{GRPO}}(\theta; \mathcal{A}) + \lambda \, \mathcal{L}_{\text{CE}}(\theta; \mathcal{O}'), \tag{1}$$

where $\mathcal{A}$ indexes assistant-action positions and $\mathcal{O}'$ indexes terminal-output positions inside the environment observations. The objective requires no teacher model, extra rollouts, or an additional forward pass: it uses the same logits already computed for the policy update, but gathers them at a different set of token positions. In effect, ECHO turns the environment stream into dense supervision, so even failed rollouts can teach the policy how the terminal responds.

We test this hypothesis in TerminalBench-style Docker environments with Qwen3-8B, OpenThinker-Agent-v1-SFT, and Qwen3-14B starting policies. ECHO consistently improves both internal held-out evaluations and the public TerminalBench-2.0 benchmark. On the headline external metric, it raises Qwen3-8B pass@1 from 2.70% to 5.17% and Qwen3-14B from 5.17% to 10.79% — nearly a doubling at both scales. ECHO also reduces dependence on expert demonstrations: from a base Qwen3-8B, GRPO+ECHO matches OpenThinker-SFT+GRPO on internal evaluations without using any of the $\sim$15k expert demonstrations behind the SFT model, and closes about half of the expert-SFT gap on TerminalBench-2.0.

Our contributions:

1. **Environment tokens are supervision.** Stdout, errors, files, and tool traces are dense, on-policy training targets that standard agent RL throws away.
2. **ECHO.** A length-normalized cross-entropy on observation tokens, added to GRPO's loss on action tokens. The two terms share one forward pass, require no teacher model, and add no extra rollouts.
3. **Consistent gains across model families.** ECHO improves Qwen3-8B, OpenThinker-Agent-v1-SFT, and Qwen3-14B on both internal evaluations and TerminalBench-2.0, nearly doubling pass@1 at 8B and 14B. From a base Qwen3-8B, GRPO+ECHO matches SFT-bootstrapped GRPO from $\sim$15k expert demonstrations, without using any of them.
4. **ECHO encourages self-improvement.** Even without a verifier, the policy can improve by predicting what its own actions cause in the environment.

Taken together, these findings suggest agent training has been operating with a supervision source masked out: every policy action has a consequence in the environment, and that consequence is in the rollout already. A simple auxiliary loss is one way to learn from it, including on failed rollouts.

 ## 2 Preliminaries

71 **Multi-Turn Rollout Structure.** A training sequence interleaves a system prompt, the user task,
72 and a transcript of (assistant action, environment observation) pairs:

$$\underbrace{[\text{sys}] \, [\text{task}]}_{\text{prompt}} \, [\text{action}_1] \, [\text{obs}_1] \, [\text{action}_2] \, [\text{obs}_2] \, \cdots \, [\text{action}_K] \, [\text{obs}_K].$$

73 At each turn, the policy samples action tokens conditioned on the entire prior transcript; the harness
74 parses these into a bash command, executes it in the container, and appends the resulting terminal
75 output as the next observation. Let $\mathcal{A} \subseteq \{1, \ldots, T\}$ index assistant-action positions and $\mathcal{O} \subseteq$
76 $\{1, \ldots, T\}$ index environment-observation positions. Trainers compute log-probabilities on the full
77 sequence (every action depends on prior observations), but the policy-gradient loss is applied only on
78 $\mathcal{A}$. Observations in $\mathcal{O}$ are conditioned on, but receive no direct training signal.

79 **Group-Relative Policy Optimization.** GRPO [Shao et al., 2024] optimizes a clipped policy-
80 gradient objective with group-normalized advantages and no learned value function. For prompt
81 x, sampled rollouts $\{y^{(i)}\}_{i=1}^n$, and binary rewards $r^{(i)} \in \{0, 1\}$, each rollout receives a scalar
82 group-normalized advantage $\hat{A}^{(i)}$, applied uniformly to its action-token positions using the clipped
83 importance ratio $\rho_t^{(i)}$:

$$\mathcal{L}_{\text{GRPO}}(\theta) = -\frac{1}{\sum_i |\mathcal{A}^{(i)}|} \sum_i \sum_{t \in \mathcal{A}^{(i)}} \min\left(\rho_t^{(i)} \hat{A}^{(i)}, \text{clip}(\rho_t^{(i)}, 1 - \epsilon, 1 + \epsilon) \hat{A}^{(i)}\right). \tag{2}$$

84 GRPO optimizes only assistant action tokens. Observation tokens remain in context and affect future
85 actions, but are not policy-gradient targets. With sparse binary rewards, all-zero groups have no
86 reward contrast. In mixed groups, unsuccessful trajectories receive only a trajectory-level negative
87 signal, so learning concentrates on rare successful rollouts.

3 Method

3.1 ECHO Objective

90 ECHO is a supervised next-token objective on observation positions, added alongside GRPO without
91 modifying it. Let $p_\theta(\cdot \mid x_{<t})$ denote the model's next-token distribution. The ECHO loss is a
92 length-normalized cross-entropy on a subset $\mathcal{O}' \subseteq \mathcal{O}$ of observation tokens:

$$\mathcal{L}_{\text{CE}}(\theta; \mathcal{O}') = -\frac{1}{Z} \sum_{t \in \mathcal{O}'} \log p_\theta(x_t \mid x_{<t}), \tag{3}$$

93 where $Z = |\mathcal{O}|$ normalizes each sequence by its total observation length. The total objective is
94 $\mathcal{L}_{\text{total}} = \mathcal{L}_{\text{GRPO}} + \lambda \mathcal{L}_{\text{CE}}$ as in equation 1.

95 The two losses share a single actor forward pass: the same logits feed both, gathered through different
96 masks (assistant-action positions for GRPO, observation positions for ECHO). ECHO therefore
97 requires no second rollout, teacher model, or second forward pass; the only added work is a masked
98 log-probability sum. It composes orthogonally with stabilization techniques aimed at the policy
99 gradient itself, including void-trajectory filtering [Xue et al., 2025], overlong filtering and clip-
100 higher [Yu et al., 2025], and KL-regularized reference updates [Ouyang et al., 2022]. Algorithm 1
101 summarizes the resulting update.

102 Computationally, ECHO adds a masked log-probability computation and reduction over existing
103 logits, rather than a separate model evaluation. Its backward pass adds gradients through the same
104 network activations used by the policy objective.

3.2 Choosing Observation Targets

106 We set $\mathcal{O}'$ to the env tokens only, excluding the harness's warning prefix. An observation message
107 has internal structure

$$\underbrace{\texttt{WARNINGS:\textbackslash n- ...}}_{\text{warning tokens}} \underbrace{\texttt{<command\_output> ... </command\_output>}}_{\text{terminal-output (env) tokens}},$$

Algorithm 1 ECHO-Augmented GRPO

Require: rollout sequence $x_{1:T}$; action mask $\mathcal{A}$; env-observation mask $\mathcal{O}'$; full-observation length $|\mathcal{O}|$; advantages $\{\hat{A}_t\}_{t\in\mathcal{A}}$; mixing coefficient λ.
  1: $\ell \leftarrow \texttt{forward}_\theta(x_{1:T})$ ▷ single actor forward; logits at every position
  2: $\log p_t \leftarrow \log \text{softmax}(\ell_t)[x_t]$ for all t
  3: $\mathcal{L}_{\text{GRPO}} \leftarrow \texttt{ClippedGRPO}\big(\{\log p_t\}_{t\in\mathcal{A}}, \{\hat{A}_t\}_{t\in\mathcal{A}}\big)$
  4: $\mathcal{L}_{\text{CE}} \leftarrow -\big(\sum_{t\in\mathcal{O}'} \log p_t\big)/|\mathcal{O}|$
  5: **return** $\mathcal{L}_{\text{GRPO}} + \lambda\,\mathcal{L}_{\text{CE}}$

---

where the warning block is a rule-based message emitted when the previous tool call fails parsing or violates format constraints, and the env block carries the actual command output. The reason for excluding warnings is empirical: warning tokens are low-entropy and the model memorizes them within ~60 training steps, so warn-only configurations quickly lose useful gradient. Terminal-output tokens, by contrast, encode task-specific feedback (file names, test failures, byte counts, error formats) and continue to provide informative gradient throughout training.

3.3 Tuning the Loss Weight

We swept $\lambda \in \{0.001, 0.005, 0.01, 0.02, 0.05, 0.1, 0.2\}$ and found a productive range of 0.01–0.05. Below this range, the auxiliary gradient is too small to shape representations reliably: world loss can fluctuate or increase while the policy objective dominates. Above this range, the observation objective begins to compete with the policy update; at $\lambda = 0.1$ policy quality plateaus or degrades, and at $\lambda = 0.2$ runs can collapse into degenerate rollouts whose terminal outputs are easy to predict but no longer useful. We therefore use a constant $\lambda = 0.05$ in all reported experiments. The constant weight is naturally self-annealing: as the model learns terminal-output statistics, $\mathcal{L}_{\text{CE}}$ falls rapidly, reducing the auxiliary contribution without an explicit schedule.

4 Experimental Setup

Training Task Corpus. We start from 2700 curated terminal tasks: 1977 from Endless Terminals [Gandhi et al., 2026a,b] and 723 from OpenThoughts-Agent-v1-RL [OpenThoughts Team, 2025b], after filtering out analysis/computation, specialized-application, infrastructure/networking, and complex-bash domains. We then generate 6170 additional tasks with a modified Endless Terminals pipeline, covering task specification, Dockerfile generation/validation, and Harbor-format export. We retain only tasks solved by GPT-5 in at least one of 16 attempts, yielding 8870 tasks across data processing, system operations, and development/tooling. We train on 8770 tasks and hold out 100 for in-distribution validation (**val100**).

Harness and Runtime Environment. At each turn, the policy conditions on its prior reasoning, commands, and command outputs, then emits a thinking block followed by Qwen XML-format bash commands or a task-done signal. A minimal training harness parses the first command or completion signal, executes it, and returns optional format warnings plus stdout/stderr and exit code as the next observation. Episodes run for up to 16 turns in Docker, orchestrated by Harbor [Anthropic and contributors, 2025], with a 16k context window and at most 2048 generated tokens per turn. We verify success with unit tests at episode end, using 10-minute agent and 2-minute verifier timeouts per training task.

Models. We train on three starting policies: **Qwen3-8B** [Qwen Team, 2025], **OpenThinker-Agent-v1-SFT** [OpenThoughts Team, 2025a] (OT-SFT), and **Qwen3-14B** [Qwen Team, 2025]. OT-SFT is a Qwen3-8B model SFT'd on ~15k expert terminal-agent demonstrations from the GLM-4.6 model.

RL Recipe. All experiments use the same GRPO recipe: $n = 16$ rollouts per prompt, batch size of 16, learning rate 1×10^{-6}, gradient clip 0.2, prompt-level advantage normalization, sequence-level loss aggregation, no KL penalty unless noted, and rollout temperature 0.8. For ECHO-augmented

Model	Setup	val100	ITD	TBLite	TB2 p@1	TB2 p@3	TB2 p@5
Qwen3-8B	Base	34.2	7.0	4.9	1.57	3.71	4.49
	+ GRPO	54.9	16.2	9.5	2.70	6.74	8.99
	+ GRPO + ECHO	**63.7**	**18.9**	**11.4**	**5.17**	**10.45**	**13.48**
OT-SFT	SFT	38.5	10.7	6.0	5.62	10.45	12.36
	+ GRPO	63.5	18.8	11.6	7.64	14.38	17.98
	+ GRPO + ECHO	**73.1**	**22.7**	**12.9**	**7.87**	**13.82**	**17.98**
Qwen3-14B	Base	35.3	12.1	5.7	4.27	8.99	12.36
	+ GRPO	60.3	17.9	9.8	5.17	10.67	13.48
	+ GRPO + ECHO	**65.0**	**19.8**	**15.1**	**10.79**	**16.52**	**19.10**

Table 1: Pass rates before RL, after GRPO, and after GRPO+ECHO for three starting policies. *val100* is an in-distribution 100-task holdout; *ITD* (71 tasks), *TBLite* (OpenThoughts-TBLite), and *TB2* (TerminalBench-2.0, $n=89$, pass@k over 5 attempts) are out-of-distribution. Bold marks the GRPO+ECHO row in each block. Standard errors and paired Wilcoxon tests appear in App. F–G.

GRPO runs, we use $\lambda = 0.05$ to scale the ECHO loss. We provide a reward of 1 if final tests for a task pass, and a reward of 0 otherwise. We train each model for 500 GRPO steps on 8 B200 GPUs.

Evaluation. We evaluate model performance on **val100**, internal-dev (**ITD**), OpenThoughts-TBLite (**TBLite**) [OpenThoughts Team, 2025d], and **TerminalBench-2.0** (TB2) [Terminal-Bench Team, 2025a]. val100 is a held-out set of 100 tasks from our training corpus. Internal-dev is a set of 71 tasks focusing on data processing, systems operations, and development/tooling, sampled from TerminalBench 1.0 (core and non-core) and OpenThoughts-TB-dev [OpenThoughts Team, 2025c]. OpenThoughts-TBLite is a set of 100 terminal-bench-style tasks calibrated for small-model performance relative to the harder TB2 benchmark. On val100, ITD, and TBLite, we evaluate using our minimal agent harness, with 8 rollouts per task at temperature 0.6. On TB2, we use the Terminus 2 harness [Terminal-Bench Team, 2025b] and perform 5 rollouts at temperature 0.6 with 32k context.

5 Results

ECHO improves every starting policy on every benchmark we test. TerminalBench-2.0 pass@1 nearly doubles at both 8B ($2.70 \rightarrow 5.17$) and 14B ($5.17 \rightarrow 10.79$), and internal pass rates rise on every slice. The same checkpoints become substantially better predictors of terminal feedback. They match GRPO's peak performance in 1.5–$2.3\times$ fewer training steps and waste fewer turns at inference. Starting from base Qwen3-8B, adding ECHO to GRPO fully matches what an expert SFT initialization buys on internal evaluations, and recovers half of its lead on TerminalBench-2.0 — without using any of the $\sim$15k expert demonstrations the SFT model requires.

5.1 ECHO Substantially Boosts GRPO Performance

ECHO consistently improves task success. Adding ECHO to GRPO raises task success on every internal evaluation (val100 and ITD), TBLite, and TerminalBench-2.0. TerminalBench-2.0 pass@1 nearly doubles for Qwen3-8B ($2.70 \rightarrow 5.17$, $\times 1.9$) and Qwen3-14B ($5.17 \rightarrow 10.79$, $\times 2.1$).

Table 1 compares matched GRPO and GRPO+ECHO checkpoints across three starting policies. The setup isolates a single change: whether terminal-output tokens are additionally trained with a cross-entropy objective alongside the standard policy-gradient loss. Across all three starting policies, ECHO improves every internal evaluation metric and consistently boosts performance on TerminalBench-2.0 under the Terminus-2 harness. At 8B, TB2 pass@1 nearly doubles from 2.70 to 5.17; at 14B, it rises from 5.17 to 10.79, with pass@5 increasing from 13.48 to 19.10. The strongest improvements are statistically significant under paired Wilcoxon tests (App. G), including the +5.62 pp TB2 pass@1 gain for Qwen3-14B over matched GRPO.

The 14B result is particularly notable. Although the internal gains at 14B are smaller than at 8B, the improvements on TerminalBench-2.0 are substantially larger. One plausible explanation is that the

Figure 2: Pass-rate training curves over 500 GRPO steps. Teal shows GRPO only; pink shows GRPO+ECHO, with shading where ECHO exceeds the matched GRPO baseline. Rows are Qwen3-8B base and Qwen3-14B base; columns are val100 (in-distribution), ITD (OOD), and TBLite (hardest OOD). OT-SFT–initialized curves appear in App. E.

larger model can internalize more generalizable terminal dynamics from the observation stream, while at smaller scales the policy and world-modeling objectives compete more directly for limited capacity. Figure 2 shows the corresponding training dynamics: at 8B, ECHO consistently outperforms the GRPO baseline throughout training, while at 14B it reaches a substantially higher final plateau.

5.2 Does ECHO Really Learn Terminal Dynamics?

To test whether ECHO improves the model's understanding of terminal dynamics, we evaluate environment-token cross-entropy on a fixed pool of held-out trajectories. We collect trajectories from our strongest checkpoint (Qwen3-14B + GRPO + ECHO) on val100, ITD, and TBLite, then measure how well each model predicts the resulting terminal-output tokens.

This evaluation is intentionally off-policy: most evaluated models did not generate these trajectories themselves. Low cross-entropy therefore requires predicting the outcomes of another agent's actions, rather than memorizing a model's own rollout distribution. If ECHO learns a useful terminal world model, its checkpoints should outperform matched GRPO-only baselines on this prediction task.

> **ECHO learns transferable terminal dynamics.** On held-out, off-policy trajectories, GRPO+ECHO sharply lowers environment-token cross-entropy across all starting policies and evaluation slices, while GRPO alone barely changes it.

Figure 3 shows exactly this pattern. GRPO alone barely changes environment-token cross-entropy relative to the starting policy, despite improving task success. ECHO, by contrast, sharply lowers prediction error across all starting policies and evaluation distributions. For Qwen3-14B, cross-entropy drops from 0.22→0.08 on val100, 0.40→0.29 on ITD, and 0.22→0.15 on TBLite; for Qwen3-8B, the corresponding drops are 0.27→0.09, 0.46→0.31, and 0.26→0.16. These results support the central mechanism behind ECHO: the auxiliary objective trains the policy to predict how the terminal responds to actions, and the dynamics transfer beyond the model's own trajectories.

5.3 ECHO Reduces Dependence on Expert Demonstrations

Expert SFT primes terminal agents before RL by training them on demonstrations from a stronger policy. In our comparison, OT-SFT is Qwen3-8B SFT'd on ∼15k expert demonstrations from a GLM-4.6 teacher. We ask how much of this expert initialization can be replaced by letting the base model explore on-policy and learn a dense ECHO signal from its own terminal feedback.

Figure 3: Per-token cross-entropy on terminal output tokens for a fixed reference pool of held-out rollouts. Each panel evaluates a different distribution; within each panel, starting policies are shown before RL, after GRPO, and after GRPO+ECHO. RL alone barely changes env-token CE. ECHO sharply lowers it across all model families and evaluation slices. Lower is better.

We define the expert-SFT gap as the gain from OT-SFT+GRPO over Qwen3-8B+GRPO, and the ECHO lift as the gain from adding ECHO to Qwen3-8B+GRPO. Figure 4 shows that ECHO recovers almost all of the OT-SFT advantage on internal evaluations: 101.6% of the gap on val100, 103.9% on ITD, and 88.9% on TBLite. This suggests that much of what expert SFT provides is environment familiarity—how commands behave, how errors appear, what files and tests reveal, and how terminal state evolves. ECHO learns this signal directly from the model's own rollouts.

On TerminalBench-2.0, ECHO closes roughly half of the OT-SFT gap: 50.0% on pass@1, 48.6% on pass@3, and 50.0% on pass@5. This is weaker than the internal recovery but still substantial. A likely

Figure 4: ECHO recovers most of the benefit of expert-SFT initialization on internal evaluations and roughly half on TerminalBench-2.0.

explanation is that TB2 requires not only terminal familiarity, but also higher-level strategy: which commands to try, how to decompose a task, when to inspect versus edit, and when to stop. ECHO narrows the gap by learning environment dynamics, but expert demonstrations still help with strategic action selection on the hardest tasks.

ECHO substantially closes expert-SFT gap. On Qwen3-8B, GRPO+ECHO recovers nearly all of the OT-SFT initialization gain on internal evaluations and about half of the TerminalBench-2.0 gain, without using expert demonstrations.

5.4 Training and Inference Efficiency

Because ECHO trains on observation tokens already present in each rollout, it can improve how much learning the policy extracts from a fixed sample budget. We measure this by asking when each ECHO run first exceeds the best validation score reached by its matched GRPO-only run within 500 steps, using the aggregate total score (val100+ITD+TBLite) and TBLite alone.

ECHO often learns faster and uses inference budget more productively. At 8B, ECHO reaches the GRPO-only peak in 1.5–$2.3\times$ fewer training steps. At 14B, both runs peak at the same step, but ECHO reaches a higher plateau. At inference, ECHO halves TB2 timeouts for Qwen3-8B and OT-SFT and reduces completion tokens for all three model pairs.

| | Total | | | TBLite | | |
Model	GRPO	+ECHO	Speedup	GRPO	+ECHO	Speedup
Qwen3-8B	460	240	1.92×	500	220	2.27×
OT-SFT	400	260	1.54×	220	300	0.73×
Qwen3-14B	380	380	1.00×	380	380	1.00×

Table 2: First step at which each run reaches its best internal score within 500 GRPO steps. *Total* aggregates val100, ITD, and TBLite; *TBLite* isolates the hardest OOD slice. Pink speedup cells indicate ECHO reaches the score faster ($> 1\times$); teal indicates GRPO is faster.

| | Timeout rate (%) | | | Turns | | | Tokens | | |
Model	GRPO	+ECHO	Δ	GRPO	+ECHO	Δ	GRPO	+ECHO	Δ
Qwen3-8B	19.8	9.0	−55%	24.3	19.8	−18%	43.2k	30.3k	−30%
OT-SFT	45.2	24.7	−45%	66.3	37.7	−43%	35.4k	34.8k	−2%
Qwen3-14B	40.7	43.1	+6%	22.0	23.5	+7%	49.8k	43.1k	−13%

Table 3: TerminalBench-2.0 inference-time trajectory statistics. *Timeout rate*: fraction of TB2 trials that hit the per-task time limit. *Turns*: average agent turns per trial. *Tokens*: average completion tokens per trial. Pink-shaded Δ cells indicate ECHO wins (lower is better on all three columns); teal indicates GRPO wins.

Table 2 shows large 8B speedups on the aggregate score (1.54–1.92×) and for Qwen3-8B on TBLite (2.27×). The exception is OT-SFT on TBLite, where GRPO peaks earlier. At 14B, ECHO and GRPO peak at the same step, but ECHO is higher throughout training (Fig. 2, bottom row), so the benefit appears as a higher plateau rather than faster convergence.

Table 3 shows that ECHO also improves how agents spend their inference budget. For Qwen3-8B, ECHO cuts TB2 timeouts from 19.8% to 9.0% and completion tokens by 30%; for OT-SFT, it cuts timeouts from 45.2% to 24.7% and turns by 43%. Qwen3-14B is the only exception on timeouts and turns, but still uses 13% fewer tokens while achieving the largest TB2 pass@1 gain. Overall, ECHO produces policies that not only solve more tasks, but spend less interaction doing so.

5.5 Verifier-Free Adaptation

The main results use ECHO as an auxiliary objective during RL. We next ask whether the observation loss alone can improve a policy on unseen tasks, without unit-test rewards or any policy-gradient signal. Starting from our strongest 8B GRPO+ECHO checkpoint, we mask out the GRPO term and continue training for 100 steps using only $\mathcal{L}_{\text{CE}}$ on environment tokens. In this setting, the model can improve only by exploring task environments and predicting the terminal outputs of its own actions.

> **ECHO can drive verifier-free adaptation from interaction alone.** On unseen in-distribution tasks, ECHO-only training improves val100 by $+3.8\%$. On harder OOD tasks, after filtering to clean tool-call trajectories: ECHO improves PyTerm by $+10.0\%$ and ITD by $+5.2\%$ without any reward signal, while preserving val100 within $\pm 1\%$.

We evaluate verifier-free adaptation on val100, ITD, TBLite, and PyTerm, a held-out set of 928 synthetic terminal tasks emphasizing Python script generation. For PyTerm, we use 828 tasks for ECHO-only adaptation and 100 for evaluation. The starting checkpoint solves $\sim 11.3\%$ of PyTerm, comparable to its TBLite pass rate.

Table 4 shows that ECHO-only training can improve a policy without verifier rewards, but the usefulness of the signal depends on the quality of exploration. On val100, where the checkpoint is already competent, unfiltered ECHO-only training gives a $+3.8$ pp lift. On harder OOD tasks, the policy more often enters bad interaction regimes: malformed tool calls, parse errors, and unproductive loops, causing the model to only learn from failure modes. Training on filtered trajectories free of parsing errors and malformed tool calls removes this noise and yields sustained gains on PyTerm ($+10\%$) and ITD ($+5.2\%$).

Target dist.	Rollout filter	Step	Δ target (pp)	Δ val100 (pp)
val100 (in-dist.)	none	70	+3.8	+3.8
PyTerm (OOD)	parse/tool=1.0	100	+10.0	−0.9
ITD (OOD)	parse/tool=1.0	100	+5.2	+0.4
TBLite (OOD)	parse/tool=1.0	100	−3.9	−0.4

Table 4: ECHO-only adaptation. We mask the GRPO loss term and train only on ECHO loss. We see a +3.8% lift on val100 and OOD lifts on PyTerm (10%) and ITD (5.2%) on filtered trajectories.

Although TBLite starts at a similar pass rate to PyTerm, the same recipe degrades performance. The difference appears to be observation structure: PyTerm outputs—tracebacks and file contents—are tightly coupled to executed Python code, while TBLite often requires shell orchestration over less visible filesystem and process state. Thus verifier-free ECHO works best when clean exploration exposes predictive feedback. In those settings, the agent can improve from interaction alone.

6   Related Work and Discussion

Related Work.   ECHO builds on work showing that environment interaction contains useful supervision beyond sparse reward. Classical world-model methods learn dynamics models for planning, imagination, or search [Ha and Schmidhuber, 2018, Hafner et al., 2020, 2021, 2023, Schrittwieser et al., 2020, Ye et al., 2021]; auxiliary-prediction methods in model-free RL train agents to predict pixels, rewards, forward dynamics, or latent states to improve representations under sparse feedback [Jaderberg et al., 2017, Pathak et al., 2017, Schwarzer et al., 2021]. ECHO follows this auxiliary-prediction view but in a multi-turn LM-agent setting: the targets are textual terminal observations already present in the transcript and already used as context for future actions.

For LM agents, the closest comparison is CWM [Meta FAIR CodeGen Team, 2025], which trains a large model on observation–action trajectories from Python and Docker environments. ECHO instead injects observation prediction directly into on-policy GRPO, requiring no separate corpus, world-modeling stage, dynamics model, or inference-time simulation. It is also complementary to recent multi-turn agent RL systems such as SkyRL [Cao et al., 2025], SimpleTIR [Xue et al., 2025], DAPO [Yu et al., 2025], and ArCHer [Zhou et al., 2024]: those methods stabilize the policy-gradient update, while ECHO adds a parallel supervised loss on the observation tokens.

Limitations.   We evaluate ECHO through downstream task performance and observation-token cross-entropy, but do not directly prove that the policy has internalized terminal dynamics rather than benefiting from a broader representation-shaping effect. Direct probes, counterfactual prediction tests, or state-variable probes would strengthen this claim. ECHO is also not a replacement for verifier rewards: the auxiliary loss alone improves only when the starting policy can explore cleanly and the environment feedback is predictive. Finally, the loss weight must be controlled. At large λ, the policy can optimize for easy-to-predict outputs rather than task success.

Broader Impacts.   ECHO lowers the cost of training terminal agents by reusing existing rollouts and logits, which may benefit scientific computing, debugging, and developer assistance. More capable shell agents also raise dual-use risks in software automation. We therefore sandbox all rollouts in ephemeral Docker containers (§4); deployments based on this recipe should retain comparable isolation, auditing, and human-in-the-loop controls.

7   Conclusion

We introduce ECHO, a simple way to turn the environment responses already present in agent rollouts into supervision. ECHO adds cross-entropy on terminal-output tokens to the same logits used for GRPO, requiring no extra rollouts, forward passes, data, or architectural changes. Across different starting policies and model sizes, ECHO improves over RL-only training, learns faster, matches much of the benefit of learning from expert demonstrations, and roughly doubles TerminalBench-2.0 pass@1. This suggests a broader opportunity for agentic RL: trajectories already contain a dense training signal waiting to be used—the observable consequences of the agent's own actions.

References

Anthropic and contributors. Harbor: Container orchestration for coding agents. Documentation, 2025. `https://www.harborframework.com/docs`.

Shiyi Cao, Sumanth Hegde Mei, Tyler Liu, Yowei Zhuang, Eric Wu, Andy Zhao, et al. SkyRL: A modular full-stack RL library for LLMs. GitHub repository, NovaSky-AI, 2025. `https://github.com/NovaSky-AI/SkyRL`.

Kanishk Gandhi, Shivam Garg, Noah D. Goodman, and Dimitris Papailiopoulos. Endless Terminals: Scaling RL environments for terminal agents. *arXiv preprint arXiv:2601.16443*, 2026a.

Kanishk Gandhi, Shivam Garg, Noah D. Goodman, and Dimitris Papailiopoulos. Endless Terminals dataset. Hugging Face dataset, 2026b. `https://huggingface.co/datasets/obiwan96/endless-terminals`.

David Ha and Jürgen Schmidhuber. Recurrent world models facilitate policy evolution. In *Advances in Neural Information Processing Systems*, 2018.

Danijar Hafner, Timothy Lillicrap, Jimmy Ba, and Mohammad Norouzi. Dream to control: Learning behaviors by latent imagination. In *International Conference on Learning Representations*, 2020.

Danijar Hafner, Timothy Lillicrap, Mohammad Norouzi, and Jimmy Ba. Mastering Atari with discrete world models. In *International Conference on Learning Representations*, 2021.

Danijar Hafner, Jurgis Pasukonis, Jimmy Ba, and Timothy Lillicrap. Mastering diverse domains through world models. *arXiv preprint arXiv:2301.04104*, 2023.

Max Jaderberg, Volodymyr Mnih, Wojciech Marian Czarnecki, Tom Schaul, Joel Z. Leibo, David Silver, and Koray Kavukcuoglu. Reinforcement learning with unsupervised auxiliary tasks. In *International Conference on Learning Representations*, 2017.

Meta FAIR CodeGen Team. CWM: An open-weights LLM for research on code generation with world models, 2025.

OpenThoughts Team. OpenThinker-Agent: An open-source sft recipe for coding agents. Hugging Face model card, 2025a. `https://huggingface.co/open-thoughts/OpenThinker-Agent-v1-SFT`.

OpenThoughts Team. OpenThoughts-Agent-v1-RL: Reinforcement learning tasks for terminal agents. Hugging Face dataset, 2025b. `https://huggingface.co/datasets/open-thoughts/OpenThoughts-Agent-v1-RL`.

OpenThoughts Team. OpenThoughts-TB-dev: Terminal-bench development tasks. Hugging Face dataset, 2025c. `https://huggingface.co/datasets/open-thoughts/OpenThoughts-TB-dev`.

OpenThoughts Team. OpenThoughts-TBLite: Terminal-bench lite tasks. Hugging Face dataset, 2025d. `https://huggingface.co/datasets/open-thoughts/OpenThoughts-TBLite`.

Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in Neural Information Processing Systems*, 2022.

Deepak Pathak, Pulkit Agrawal, Alexei A. Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 2778–2787. PMLR, 2017.

Qwen Team. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.

Julian Schrittwieser, Ioannis Antonoglou, Thomas Hubert, Karen Simonyan, Laurent Sifre, Simon Schmitt, Arthur Guez, Edward Lockhart, Demis Hassabis, Thore Graepel, Timothy Lillicrap, and David Silver. Mastering Atari, Go, chess and shogi by planning with a learned model. *Nature*, 588: 604–609, 2020.

345 Max Schwarzer, Ankesh Anand, Rishab Goel, R. Devon Hjelm, Aaron Courville, and Philip Bach-
346 man. Data-efficient reinforcement learning with self-predictive representations. In *International*
347 *Conference on Learning Representations*, 2021.

348 Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang,
349 Mingchuan Zhang, Y. K. Li, Y. Wu, et al. DeepSeekMath: Pushing the limits of mathemati-
350 cal reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

351 Ilya Sutskever. Ilya sutskever (openai chief scientist) – why next-token prediction could surpass
352 human intelligence. Interview by Dwarkesh Patel, Dwarkesh Podcast, March 2023. URL `https:`
353 `//www.dwarkesh.com/p/ilya-sutskever`. Transcript.

354 Terminal-Bench Team. TerminalBench: A benchmark for evaluating coding agents on terminal tasks.
355 Stanford CRFM, 2025a. `https://www.tbench.ai/`.

356 Terminal-Bench Team. Terminus-2: A reference agent for terminal tasks. Software release, 2025b.
357 `https://github.com/laude-institute/terminal-bench`.

358 Zhenghai Xue, Longtao Yan, Haomin Wang, Yibin Wang, Yiyang Wang, Bo Liu, and Min Yang.
359 SimpleTIR: End-to-end reinforcement learning for multi-turn tool-integrated reasoning. *arXiv*
360 *preprint arXiv:2509.02479*, 2025.

361 Weirui Ye, Shaohuai Liu, Thanard Kurutach, Pieter Abbeel, and Yang Gao. Mastering atari games
362 with limited data. In *Advances in Neural Information Processing Systems*, volume 34, pages
363 25476–25488, 2021.

364 Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Tiantian Fan, Gaohong
365 Liu, Lingjun Liu, Xin Liu, et al. DAPO: An open-source LLM reinforcement learning system at
366 scale. *arXiv preprint arXiv:2503.14476*, 2025.

367 Yifei Zhou, Andrea Zanette, Jiayi Pan, Sergey Levine, and Aviral Kumar. ArCHer: Training language
368 model agents via hierarchical multi-turn RL. *arXiv preprint arXiv:2402.19446*, 2024.

A   World Cross-Entropy Trajectories

370 Figure 5 shows per-token world cross-entropy on warning tokens and on terminal-output (env) tokens
371 over training. Warning CE drops from ∼5.6 nats to <0.05 nats by step 60—the model memorizes
372 warning structure quickly. Env CE plateaus at 0.05–0.10 nats, the irreducible entropy of real terminal
373 output (variable filenames, byte counts, error formats). A constant λ schedule therefore auto-anneals
374 the warning gradient while preserving the env gradient indefinitely; this motivates the $\mathcal{O}'=$ env_only
375 choice in Section 3.2.

Figure 5: Per-token world cross-entropy by target type. Warning CE drops to near-zero within ∼60
steps; env CE plateaus at 0.05–0.10 nats and provides sustained gradient throughout training.

B   Hyperparameters and Reproducibility

377 • Optimizer: AdamW, $\beta_1 = 0.9$, $\beta_2 = 0.95$, weight decay 0.01.

378 • Learning rate: 1×10^{-6} constant (no warmup or decay), gradient clip 0.2.

- GRPO: $n = 16$ rollouts per prompt, batch size 16, no KL penalty, prompt-level advantage normalization, $\epsilon_{lo} = 0.2$, $\epsilon_{hi} = 0.28$.
- Sampling: training temperature 0.8; evaluation temperature 0.6.
- World loss: $\lambda \in \{0.02, 0.05\}$ (SFT vs. base); $\mathcal{O}'$ = terminal-output (env) tokens; per-sequence normalization by total observation length.
- Run length: 500–1000 GRPO steps on 8 GPUs (A100/B200 mix), $\sim$24–48 h wallclock per run.

Internal-Eval Reproducibility.   8 rollouts/task, sampling temperature 0.6, 16-turn budget. Per-task pass-rate variance at $n = 8$ is ± 0.05; mean-of-100-task variance is approximately ± 0.025 (Wilson interval). We treat trends across ≥ 3 consecutive eval points as more informative than single-checkpoint deltas.

TerminalBench-2.0 Reproducibility.   Terminus-2 reference agent at temperature 0.6, $n_{attempts} = 5$, 1200 s agent and verifier timeouts, sampling seed 42. Standard error on pass@1 at $n = 5$ is $\sim$1.5 pp.

C Per-Step Training Wallclock

Stack	min/step (steady state)	500 steps cumulative
Qwen3-8B + RL	$\sim$5.4	$\sim$42 h
Qwen3-8B + RL + ECHO	$\sim$4.4	$\sim$37 h
OT-SFT + RL	$\sim$4.7	$\sim$40 h
OT-SFT + RL + ECHO	$\sim$4.5	$\sim$38 h
Qwen3-14B + RL	$\sim$5.9	$\sim$50 h
Qwen3-14B + RL + ECHO	$\sim$5.6	$\sim$47 h

World-loss runs are slightly *faster* per step than matched RL-only runs, plausibly because parse-error rates are lower and rollouts are therefore shorter on average.

D Expert-SFT Gap

Table 5 reports the absolute pass-rates for the three Qwen3-8B configurations compared in §5.3, together with the per-metric SFT gap (SFT+RL minus base RL), the lift from ECHO (base RL+ECHO minus base RL), and the fraction of the SFT gap recovered by ECHO without expert demonstrations. Values are in pass-rate units (%); internal columns (val100, ITD, TBLite) are mean pass-rate, TB2 columns are pass@k.

Table 5: Full breakdown of the expert-SFT gap closed by ECHO on Qwen3-8B base. Rows are absolute pass-rates for the three matched configurations, the SFT initialization gap, the lift from adding ECHO without expert SFT, and the fraction of that gap closed.

Configuration	val100	ITD	TBLite	TB2 p@1	TB2 p@3	TB2 p@5
q8b RL	54.94	16.22	9.47	2.70	6.74	8.99
q8b RL + ECHO	63.66	18.89	11.39	5.17	10.45	13.48
q8b SFT + RL	63.52	18.79	11.63	7.64	14.38	17.98
SFT gap (SFT+RL − RL)	8.58	2.57	2.16	4.94	7.64	8.99
ECHO lift (RL+ECHO − RL)	8.72	2.67	1.92	2.47	3.71	4.49
% SFT gap closed by ECHO	**101.6%**	**103.9%**	88.9%	50.0%	48.6%	50.0%

E OT-SFT Training Curves

Figure 6 shows training curves for the OpenThinker-Agent-v1-SFT-initialized Qwen3-8B runs. Headline tables and Figure 2 use the env-only-fresh ECHO variant for consistency with the other configurations; the full-observation variant achieves a lower env CE (Section 5.2) but a slightly weaker tblite-val accuracy.

Figure 6: OT-SFT-init Qwen3-8B training curves. ECHO (env-only fresh) is the run reported in main-text Table 1, with checkpoint at step 440.

F   Headline Results with Standard Errors

Table 6 reports the same configurations as main-text Table 1 with ± 1 standard error. Standard errors for TBLite are computed across the n=100 questions (8 rollouts each at T=0.6, SE = std/$\sqrt{n}$); standard errors for TB2 pass@k use the unbiased pass@k estimator on per-task success counts across the n=89 tasks.

Table 6: Headline results with ± 1 standard error. Internal columns are mean pass-rate (%) over n questions $\times$ 8 rollouts at temperature 0.6. TB2 columns are pass@k (%) over 5 attempts on 89 tasks with the Terminus-2 reference agent.

Configuration	TBLite	TB2 p@1	TB2 p@3	TB2 p@5
Qwen3-8B	4.9 ± 1.4	1.57 ± 0.80	3.71 ± 1.85	4.49 ± 2.21
Qwen3-8B RL	9.5 ± 2.1	2.70 ± 0.97	6.74 ± 2.34	8.99 ± 3.05
Qwen3-8B RL+ECHO	$\mathbf{11.4 \pm 2.3}$	$\mathbf{5.17 \pm 1.68}$	$\mathbf{10.45 \pm 2.91}$	$\mathbf{13.48 \pm 3.64}$
OT-SFT	6.0 ± 1.6	5.62 ± 1.84	10.45 ± 3.02	12.36 ± 3.51
OT-SFT RL	11.6 ± 2.4	7.64 ± 2.08	14.38 ± 3.37	17.98 ± 4.09
OT-SFT RL+ECHO	$\mathbf{12.9 \pm 2.7}$	$\mathbf{7.87 \pm 2.06}$	$\mathbf{13.82 \pm 3.43}$	$\mathbf{17.98 \pm 3.88}$
Qwen3-14B	5.7 ± 1.4	4.27 ± 1.48	8.99 ± 2.63	12.36 ± 3.51
Qwen3-14B RL	9.8 ± 2.1	5.17 ± 1.65	10.67 ± 2.95	13.48 ± 3.64
Qwen3-14B RL+ECHO	$\mathbf{15.1 \pm 2.6}$	$\mathbf{10.79 \pm 2.77}$	$\mathbf{16.52 \pm 3.71}$	$\mathbf{19.10 \pm 4.19}$

G   Paired Wilcoxon Tests

To test the strongest claims supporting the main-text paragraphs, we report paired Wilcoxon signed-rank p-values on per-question (resp. per-task) pass rates. Pairing is on `question_idx` for internal evaluations (the same parquet is loaded by every configuration) and on `task_name` for TerminalBench-2.0; the metric scale is unchanged. Significance levels are uncorrected; the strongest claims (best vs. base, q14b RL+ECHO vs. q14b RL) clear $p < 0.001$ on multiple metrics and remain significant under Bonferroni at our claim count.

Single-seed limitation.   All training runs use a single seed per configuration; pass@k standard errors above reflect rollout sampling and per-question / per-task variance, not training stochasticity. We do not cross-seed RL training and do not claim our point estimates are stable across re-trains.

Table 7: Paired Wilcoxon signed-rank tests for the headline claims. "Δ" is $\text{mean}(B) - \text{mean}(A)$; signs are $A < B$ on metrics where higher is better. P-values are uncorrected.

Claim	Strongest evidence
Best run (Q14b RL+ECHO) > Q8b base	$p < 0.001$ across all 6 metrics ($\Delta_{\text{TB2 p@1}} = +9.21$ pp)
Best Q14b > Q14b base	$p < 0.01$ on TB2 p@1 ($\Delta = +6.52$ pp); $p < 10^{-4}$ on val100/ITD/TBLite
ECHO helps over RL (Q14b)	$p < 0.01$ on TB2 p@1 ($\Delta = +5.62$ pp); $p < 0.005$ on val100/ITD/TBLite
ECHO helps over RL (Q8b base)	$p < 10^{-4}$ on val100; marginal ($p \sim 0.09$) on TB2 p@1/3/5
RL+ECHO matches SFT+RL on TB2 (Q8b)	no significant difference on TB2 ($p > 0.7$ on p@1/3/5); RL+ECHO significantly exceeds SFT+RL on val100/ITD/TBLite ($p < 0.012$)
OT-SFT RL > q8b RL (gap claim)	$p < 0.01$ on TB2 p@1 ($\Delta = +4.94$ pp); not significant on ITD / TBLite