TOPOLOGY-AWARE ROBUST OPTIMIZATION

ABSTRACT

Out-of-distribution (OOD) generalization is a challenging machine learning problem yet highly desirable in many high-stake applications. Existing methods suffer from overly pessimistic modeling with low generalization confidence. As generalizing to arbitrary test distributions is impossible, we hypothesize that further structure on the topology of distributions is crucial in developing strong OOD resilience. To this end, we propose topology-aware robust optimization (TRO) that seamlessly integrates distributional topology in a principled optimization framework. More specifically, TRO solves two optimization objectives: (1) Topology Learning which explores data manifold to uncover the distributional topology; (2) Learning on Topology which exploits the topology to constrain robust optimization for tightly-bounded generalization risks. We theoretically demonstrate the effectiveness of our approach, and empirically show that it significantly outperforms the state of the arts in a wide range of tasks including classification, regression, and semantic segmentation. Moreover, we empirically find that the learned topology is highly explainable and consistent with human knowledge and scientific plausibility.

1 INTRODUCTION

Recent years have witnessed a surge of applying machine learning (ML) in high-stake and safety-critical applications. Such applications pose an unprecedented *out-of-distribution (OOD) generalization challenge*: ML models are constantly exposed to unseen distributions that lie outside their training space. Despite well-documented success for *interpolation*, modern ML models (*e.g.*, deep neural networks) are notoriously weak for *extrapolation*; a highly accurate model on average can fail catastrophically when presented with rare or unseen distributions (Arjovsky et al., 2019). For example, a flood predictor, trained with data of all 89 major flood events in the U.S. from 2000 to 2020, would erroneously predict on event "Hurricane Ida" in 2021. Without addressing this challenge, it is unclear when and where a model can be applied and how much risk is associated with its use.

A promising solution for out-of-distribution generalization is to conduct *distributionally robust optimization* (DRO) (Namkoong & Duchi, 2016; Staib & Jegelka, 2019; Levy et al., 2020). DRO minimizes the *worst-case* expected risk over an *uncertainty set* of potential test distributions. The uncertainty set is typically formulated as a divergence ball surrounding the training distribution endowed with a certain distance metric such as f-divergence (Namkoong & Duchi, 2016) and Wasserstein distance (Shafieezadeh Abadeh et al., 2018). Compared to empirical risk minimization (ERM) (Vapnik, 1998) that minimizes the average loss, DRO is more robust against *distributional drifts* from spurious correlations, adversarial attacks, subpopulations, or naturally-occurring variation (Robey et al., 2021).

However, it is non-trivial to build a realistic uncertainty set that truly approximates unseen distributions. On the one hand, to confer robustness against extensive distributional drifts, the uncertainty set has to be sufficiently large, which increases the risks of conferring implausible distributions, *e.g.*, outliers, and thus yielding overly pessimistic models with low prediction confidence (Hu et al., 2018; Frogner et al., 2021). On the other hand, the worst-case distributions are not necessarily the *influential* ones that are truly connected to unseen distributions; optimizing over worst-case rather than influential distributions would yield compromised OOD resilience.

As generalizing to arbitrary test distributions is impossible, we hypothesize that further structure on the topology of distributions is crucial in constructing a realistic uncertainty set. More specifically, we propose topology-aware robust optimization (TRO) by integrating two optimization objectives: (1) **Topology learning**: We model the data distributions as many discrete groups lying on a common

low-dimensional manifold, where we can *explore* the distributional topology by either using physical priors or measuring multiscale Earth Mover's Distance (EMD) among distributions.

(2) **Learning on topology**: The acquired distributional topology is then *exploited* to construct a realistic uncertainty set, where robust optimization is constrained to bound the generalization risk within a topology graph, rather than blindly generalizing to unseen distributions.

Our contributions include: 1. A new principled optimization method that seamlessly integrates topological information to develop strong OOD resilience. 2. Topology learning methods that are orders of magnitude faster than previous methods to uncover distributional structure from massively collected datasets. 3. Theoretical analysis that proves our method enjoys fast convergence for both convex and non-convex loss functions while the generalization risk is tightly bounded. 4. Empirical results in a wide range of tasks including classification, regression, and semantic segmentation that demonstrate the superior performance of our method over SOTA. 5. Explainable distributional topology that is consistent with human knowledge and scientific plausibility.

2 PROBLEM FORMULATION AND PRELIMINARY WORKS

The problem of out-of-distribution (OOD) generalization is defined by a pair of random variables (X, Y) over instances $x \in \mathcal{X} \subseteq \mathbb{R}^d$ and corresponding labels $y \in \mathcal{Y}$, following an unknown joint probability distribution $P(X, Y)$. The objective is to learn a predictor $f \in \mathcal{F}$ such that $f(x) \to y$ for any $(x, y) \sim P(X, Y)$. Here $\mathcal{F}$ is a function class that is model-agnostic for a prediction task. However, unlike typical supervised learning, the OOD generalization is complicated since one cannot sample directly from $P(X, Y)$. Instead, it is assumed that we can only measure (X, Y) under different environmental conditions e so that data is drawn from a set of groups $\mathcal{E}_{\text{all}}$ such that $(x, y) \sim P_e(X, Y)$. For example, in flood prediction, these environmental conditions denote the latent factors (*e.g.*, stressors, precipitation, terrain, etc) that underlie different flood events. Let $\mathcal{E}_{\text{train}} \subsetneq \mathcal{E}_{\text{all}}$ be a finite subset of training groups (distributions), given the loss function ℓ, an OOD-resilient model f can be learned by solving a minimax optimization:

$$\min_{f \in \mathcal{F}} \left\{ \mathcal{R}(f) := \sup_{e \in \mathcal{E}_{\text{all}}} \mathbb{E}_{(x,y) \sim P_e(X,Y)}[\ell(f(x), y)] \right\}. \tag{1}$$

Intuitively, Eq. 1 aims to learn a model that minimizes the worst-case risk over the entire family $\mathcal{E}_{\text{all}}$. It is nontrivial since we do not have access to data from any unseen distributions $\mathcal{E}_{\text{test}} = \mathcal{E}_{\text{all}} \backslash \mathcal{E}_{\text{train}}$.

Empirical Risk Minimization (ERM). Typically, classic supervised learning employs ERM (Vapnik, 1998) to find a model f that minimizes the *average* risk under the training distribution P_{tr}:

$$\min_{f \in \mathcal{F}} \{ \mathcal{R}(f) := \mathbb{E}_{(x,y) \sim P_{tr}}[\ell(f(x), y)] \}.$$

Though proved to be effective in *i.i.d.* settings, models trained via ERM heavily rely on spurious correlations that do not always hold under distributional drifts (Arjovsky et al., 2019).

Distributionally Robust Optimization (DRO). To develop OOD resilience, DRO (Namkoong & Duchi, 2016) minimizes the *worst-case* risk over an uncertainty set Q by solving:

$$\min_{f \in \mathcal{F}} \{ \mathcal{R}(f) := \sup_{Q \in \mathcal{P}(P_{tr})} \mathbb{E}_{(x,y) \sim Q}[\ell(f(x), y)] \}. \tag{2}$$

Here the uncertainty set Q approximates potential test distributions. It is usually formulated as a divergence ball with a radius of ρ surrounding the training distribution $\mathcal{P}(P_{tr}) = \{Q : D(Q, P_{tr}) \le \rho\}$ endowed with a certain distance metric $D(\cdot, \cdot)$ such as f-divergence (Namkoong & Duchi, 2016) or Wasserstein distance (Shafieezadeh Abadeh et al., 2018). To construct a realistic uncertainty set without being overly conservative, Group DRO is further developed to formulate the uncertainty set as the mixture of training groups (Hu et al., 2018; Sagawa et al., 2019).

Despite the well-documented success, existing DRO methods suffer from critical limitations. (1) To endow robustness against a wide range of potential test distributions, the radius of the divergence ball has to be sufficiently large with high risks of containing implausible distributions; optimizing for implausible distributions would fundamentally damage the OOD resilience by yielding overly-pessimistic models with low prediction confidence. (2) The worst-case groups are not necessarily the *influential* ones that are truly connected to unseen distributions; optimizing over worst-case rather than influential groups would yield compromised OOD resilience.

3   TOPOLOGY-AWARE ROBUST OPTIMIZATION

We propose a new principled optimization method (TRO) to develop OOD resilience, which integrates topology and optimization via a two-phase scheme: *Topology Learning* and *Learning on Topology*.

3.1   TOPOLOGY LEARNING: EXPLORE THE DISTRIBUTIONAL TOPOLOGY

We model the data groups $\mathcal{E}_{\text{all}}$ as many discrete distributions lying on a common low-dimensional manifold in a high-dimensional data measurement space. In such case their structure, *i.e. distributional topology*, can be naturally captured by a graph $\mathcal{G} = (V, E)$, where the entities $V = \cup_{e \in \mathcal{E}_{\text{all}}} X_e$ symbolize the groups and the edges E represent interactions among groups. The topology graph is constructed by: (1) *identifying entity*: we assume the entities are defined by the given group identities; and (2) *uncovering interactions*: we consider two scenarios to measure the connectives and interactions among discrete distributions as illustrated in Fig 1.

Physical-based distributional topology. In the scenario where the distributional adjacency information is available, we can instantly acquire the topology $\mathcal{G}_{physic}$ by simply imposing the predefined neighborhood information. For example, to capture the similarity of weather events in the U.S., one can construct a graph where each state realizes an entity, and the physical adjacency be-

Figure 1: Overview of topology-aware distributionally robust optimization (TRO).

tween two states results in an edge (see Fig. 1). In this case $\mathcal{G}_{physic}$ functions as *a physical prior* to constrain the robust optimization introduced in Sec. 3.2. We empirically find $\mathcal{G}_{physic}$ yields an improvement of 9.56% over the state of the art regarding OOD generalization reported in Sec. 5.1.

Data-driven distributional topology. In the absence of $\mathcal{G}_{physic}$, we propose a data-driven approach to learn the topology $\mathcal{G}_{data}$ from training data. Specifically, we embed the individual groups onto a shared data graph based on an affinity matrix of the combined data. Inspired by Leeb & Coifman (2016), such a data graph can be viewed as a discretization of an underlying Riemann closed manifold. By simulating a time-dependent diffusion process over the graph, we will obtain density estimates at multiple scales for each group, which will be used to calculate L^1 distances between two groups. Such multiscale L^1 distance has been proved to be topologically equivalent to the Earth Mover's Distance (EMD) on the manifold geodesic, but cutting down the computational complexity from $O\left(m^2 n^3\right)$ to $\tilde{O}(mn)$ between m distributions over n data points (Tong et al., 2021).

Specifically, we obtain the data-driven topology through three steps: (1) *Data graph construction*: we construct a data graph through an affinity matrix $\mathbf{K}$ of the combined data. $\mathbf{K}$ can be implemented through kernel functions (*e.g.*, RBF kernel) which captures the similarity of data. Instead of calculating the similarity between raw data, we calculate the similarity between features extracted from an ERM-trained model as it captures spurious correlations which preserve group identity (Creager et al., 2021). (2) *Multiscale diffusion density estimation*: to simulate the diffusion process over the graph, we obtain a Markov diffusion operator $\boldsymbol{P}$ from $\mathbf{K}$. The operator $\boldsymbol{P}$ will be used to approximate the multiscale density estimates $\boldsymbol{\mu}_e$ for each data group X_e: $\boldsymbol{\mu}_e^t := \frac{1}{n_e} \boldsymbol{P}^t \mathbb{I}_{X_e}$, where t is the diffusion time, and $\mathbb{I}_{X_e}$ is the indicator function for group e. By taking multiple powers of $\boldsymbol{P}$, $\boldsymbol{\mu}_e$ reveals the topological structure of X_i at multiple scales. (3) *Diffusion EMD measurement*: we follow Tong et al. (2021) to measure the geodesic distance $W_K\left(X_i, X_j\right)$ between X_i and X_j by aggregating the L^1 distances between the multiscale density estimates, where K is the maximum scale.

Although $\mathcal{G}_{data}$ is computationally more expensive than $\mathcal{G}_{physic}$, our experimental results in Sec. 5.2 indicate that optimizing with $\mathcal{G}_{data}$ can yield improved OOD resilience. Besides, the ablation study in Sec. 5.3 also indicates that $\mathcal{G}_{data}$ enjoys strong explainability while being consistent with human knowledge and scientific plausibility. Last but not least, the data-driven method is fully differentiable, making it amenable to jointly conducting topology learning and learning on topology in an end-to-end manner. We leave this as the future work.

3.2 LEARNING ON TOPOLOGY: EXPLOIT TOPOLOGY FOR ROBUST OPTIMIZATION

Next, we propose a principled method that integrates distributional topology to develop TRO. The key challenge is how to leverage $\mathcal{G}$ to construct a *uncertainty set* which can approximate unseen distributions with bounded generalization risk. Our main idea is to assess the *group centrality* of training distributions. *Graph centrality* is widely used in social network analysis (Newman, 2005) to measure how much information is propagated through each node. Here we introduce *group centrality* to identify *influential groups* that are truly connected to unseen distributions, which can be calculated using graph measurements (Tian et al., 2019) such as degree, betweenness, and closeness. More specifically, we first calculate the centrality of each node in $\mathcal{G}$ as a *topological prior* $\mathbf{p}$ to identify influential groups. Then, we construct the *uncertainty set* as an arbitrary mixture of training groups $Q := \{\sum_{e \in \mathcal{E}_{\text{train}}} q_e P_e \mid \mathbf{q} \in \Delta_m\}$ where Δ_m is a

---

Algorithm 1: TRO Algorithm

Input: Data of $\mathcal{E}_{\text{train}}$, Step sizes η_θ and $\eta_{\mathbf{q}}$
Output: Learned model f
Topology Learning:
if $\mathcal{G}_{physic}$ *exists* **then**
    | $\mathcal{G} \leftarrow \mathcal{G}_{physic}$
else
    | Obtain $\mathcal{G}_{data}$ via diffusion EMD
    | $\mathcal{G} \leftarrow \mathcal{G}_{data}$
end
Learning on Topology:
Calculate topological prior $\mathbf{p}$ from $\mathcal{G}$
while *not converged* **do**
    | Sample $(x, y) \sim P_e(X, Y) \, \forall e \in \mathcal{E}_{\text{train}}$
    | Calculate $\mathcal{R}(f, \mathbf{q})$ via Eq. 4
    | Update θ and $\mathbf{q}$ via Eq. 5
end

$(m-1)-$dimensional probability simplex. Finally, we use the prior $\mathbf{p}$ to constrain the uncertainty set Q by solving the minimax optimization problem as:

$$\min_{f \in \mathcal{F}} \{ \mathcal{R}(f, \mathbf{q}) := \max_{\mathbf{q} \in \Delta_m} \sum_{e \in \mathcal{E}_{\text{train}}} q_e \, \mathbb{E}_{(x,y) \sim P_e(X,Y)}[\ell(f(x), y)] \}, \quad \text{s.t. } \mathcal{D}(\mathbf{q} \| \mathbf{p}) \le \tau. \tag{3}$$

Intuitively, we ensure the uncertainty set Q to have a similar structure as the topological prior $\mathbf{p}$ after optimization; this can tightly bound the OOD generalization risk within a topological graph. $\mathcal{D}$ is an arbitrary distributional distance metric, *e.g.*, ℓ_2 distance or KL divergence (Kullback & Leibler, 1951). However, solving Eq. 3 often leads to a non-convex problem, wherein methods such as stochastic gradient descent (SGD) cannot guarantee constraint satisfaction (Robey et al., 2021). To address this issue, we leverage Karush–Kuhn–Tucker conditions (Boyd et al., 2004) and introduce a Lagrange multiplier to convert the constrained problem into its unconstrained counterpart:

$$\min_{f \in \mathcal{F}} \{ \mathcal{R}(f, \mathbf{q}) := \max_{\mathbf{q} \in \Delta_m} \sum_{e \in \mathcal{E}_{\text{train}}} q_e \, \mathbb{E}_{(x,y) \sim P_e(X,Y)}[\ell(f(x), y)] - \lambda \mathcal{D}(\mathbf{q} \| \mathbf{p}) \}, \tag{4}$$

where λ is the dual variable. Let $\theta \in \Theta$ be the model parameters of f, we can solve the primal-dual problem effectively by alternatively updating:

$$\theta^{t+1} = \theta^t - \eta_\theta^t \nabla_\theta \mathcal{R}(f, \mathbf{q}), \quad \mathbf{q}^{t+1} = \mathcal{P}_{\Delta_m}(\mathbf{q}^t + \eta_{\mathbf{q}}^t \nabla_{\mathbf{q}} \mathcal{R}(f, \mathbf{q})), \tag{5}$$

where η_θ^t ($\eta_{\mathbf{q}}^t$) is gradient descent (ascent) step size. $\mathcal{P}_{\Delta_m}(\mathbf{q})$ projects $\mathbf{q}$ onto simplex Δ_m for regularization. The overall algorithm of TRO is shown in Alg. 1. In Sec. 4, we show TRO enjoys fast convergence for both convex and non-convex loss functions, while the generalization risk is tightly bounded with topological constraints. We empirically demonstrate TRO achieves strong OOD resilience by striking a good balance between the worst-case and influential groups (see Sec. 5.2).

4 THEORETICAL ANALYSIS

4.1 CONVERGENCE ANALYSIS

In this section, we show that, by choosing appropriate step sizes η_θ^t and η_q^t, TRO yields fast convergence rate for both convex and non-convex loss functions. We first state the assumptions of the theorems. Next, we give the convergence rate for convex loss function in Theorem 1 and the convergence rate for non-convex loss function in Theorem 2.

Definition 1. (Lipschitz continuity) A mapping $f : \mathcal{X} \to \mathbb{R}^m$ is G-Lipschitz continuous if for any $x, y \in \mathcal{X}, \|f(x) - f(y)\| \le G\|x - y\|$.
Definition 2. (Smoothness) A function $f : \mathcal{X} \to \mathbb{R}$ is L-smooth if it is differentiable on $\mathcal{X}$ and

the gradient ∇f is L-Lipschitz continuous, *i.e.*, $\|\nabla f(x) - \nabla f(y)\| \leq L\|x - y\|$ for all $x, y \in \mathcal{X}$.
Assumption 1. We make the following assumptions throughout the paper: Given θ, the loss function $\ell(f_\theta(x), y)$ is G-Lipschitz continuous and L-smooth with respect to x.

Convex Loss. The expected number of stochastic gradient computations are utilized to estimate the convergence rate. To reach a duality gap of ϵ (Nemirovski et al., 2009), the optimal rate of convergence for solving the stochastic min-max problems is $\mathcal{O}\left(1/\epsilon^2\right)$ if it is convex-concave. The duality gap of the pair $(\tilde{\theta}, \tilde{q})$ is defined as $\max_{q \in \Delta_m} \mathcal{R}(\tilde{\theta}, q) - \min_{\theta \in \Theta} \mathcal{R}(\theta, \tilde{q})$. In the case of strong duality, $(\tilde{\theta}, \tilde{q})$ is optimal *iif* the duality gap is zero. We show TRO achieves the optimal $\mathcal{O}\left(1/\epsilon^2\right)$ rate.
Theorem 1. Consider the dual problem in Eq. 4 when the loss function is convex and Assumption 1 holds. Let Θ bounded by R_Θ, $\mathbb{E}\left[\|\nabla_\theta \mathcal{R}(\theta, q)\|_2^2\right] \leq \hat{G}_\theta^2$, and $\mathbb{E}\left[\|\nabla_q \mathcal{R}(\theta, q)\|_2^2\right] \leq \hat{G}_q^2$. With step sizes $\eta_\theta = 2R_\Theta / \left(\hat{G}_\theta \sqrt{T}\right)$ and $\eta_q = 2/\left(\hat{G}_q \sqrt{T}\right)$, the output of TRO satisfies:

$$\mathbb{E}\left[\max_{q \in \Delta_m} \mathcal{R}\left(\theta_T, q\right) - \min_{\theta \in \Theta} \mathcal{R}\left(\theta, q_T\right)\right] \leq \frac{3R_\Theta \hat{G}_\theta + 3\hat{G}_q}{\sqrt{T}}. \tag{6}$$

Theorem 1 shows that our method requires $T = \mathcal{O}\left(1/\epsilon^2\right)$ iterations to reach a duality gap within ϵ.

To derive the convergence rate for non-convex functions., we define ϵ-stationary points as follows:
Definition 3. (ϵ-stationary point) For a differentiable function $f : \mathcal{X} \to \mathbb{R}$, a point $x \in \mathcal{X}$ is said to be first-order ϵ-stationary if $\|\nabla f(x)\| \leq \epsilon$.

Nonconvex Loss. The loss function $\ell(f_\theta(x), y)$ can be nonconvex and as a result, $\mathcal{R}(\theta, q)$ is nonconvex in θ. Following Collins et al. (2020), we define $(\tilde{\theta}, \tilde{q})$ is an (ϵ, δ)-stationary point of $\mathcal{R}$ if: $\left\|\nabla_\theta \mathcal{R}(\tilde{\theta}, \tilde{q})\right\|_2 \leq \epsilon$ and $\mathcal{R}(\tilde{\theta}, \tilde{q}) \geq \max_{q \in \Delta_m} \mathcal{R}(\tilde{\theta}, q) - \delta$, where $\epsilon, \delta > 0$.

Theorem 2. If Assumption 1 holds and the loss function is bounded by B and is M-smooth, the output of Alg. 1 satisfies:

$$\mathbb{E}\left[\|\nabla_\theta \mathcal{R}\left(\theta_T, q_T\right)\|_2^2\right] \leq \frac{\mathcal{R}\left(\theta^0, q^0\right) + B}{T\eta_\theta} + \frac{2\eta_q \sqrt{n} B \hat{G}_q}{\eta_\theta} + \frac{\eta_\theta M \hat{G}_\theta^2}{2}$$

$$\mathbb{E}\left[\mathcal{R}\left(\theta_T, q_T\right)\right] \geq \max_{q \in \Delta_m}\left\{\mathbb{E}\left[\mathcal{R}\left(\theta_T, q\right)\right]\right\} - \frac{1}{\eta_q T} - \frac{\eta_q \hat{G}_q^2}{2} \tag{7}$$

Theorem 2 shows that our method converges in expectation to an (ϵ, δ)-stationary point of $\mathcal{R}$ in $\mathcal{O}(1/\epsilon^4)$ stochastic gradient evaluations.

4.2 GENERALIZATION BOUNDS

In this section, we provide learning guarantees for TRO. Compared to DRO, TRO achieves lower upper bound on the generalization risks over unseen distributions with the topological constraint.

Let $\mathcal{H}$ denote the family of the losses associated to a hypothesis set $\mathcal{F} : \mathcal{H} = \{(x, y) \mapsto \ell(f(x), y) : f \in \mathcal{F}\}$. Following Mohri et al. (2019), we define weighted Rademacher complexity for any hypothesis set $\mathcal{F}$ as:

$$\mathfrak{R}_{\mathbf{m}}(\mathcal{H}, q) = \mathbb{E}_{S_k \sim \mathcal{D}_k^{n_k}} \mathbb{E}_\sigma \left[\sup_{f \in \mathcal{F}} \sum_{k=1}^m \frac{q_k}{n_k} \sum_{i=1}^{n_k} \sigma_{k,i} \ell\left(f\left(x_{k,i}\right), y_{k,i}\right)\right],$$

where S_k is a subset with the size of n_k and σ is a collection of Rademacher variables. The minimax weighted Rademacher complexity for a subset $\Lambda \subseteq \Delta_m$ is defined by $\mathfrak{R}_{\mathbf{m}}(\mathcal{H}, \Lambda) = \max_{q \in \Lambda} \mathfrak{R}_m(\mathcal{H}, q)$. Let $\mathcal{D}_\Lambda$ be the distribution over the mixture of training groups and $\hat{\mathcal{D}}_\Lambda$ be its empirical counterpart. Let the distribution of some test group be $\mathcal{D}$. The learning guarantee for $\mathcal{D}$ is shown in Theorem 3.

Theorem 3. Assume the loss function ℓ is bounded by B. For any $\epsilon \geq 0$ and $\delta > 0$, with probability at least $1 - \delta$, the following inequality holds for all $f \in \mathcal{F}$:

$$\mathcal{L}_\mathcal{D}(f) \leq \mathcal{L}_{\hat{\mathcal{D}}_\Lambda}(f) + 2\mathfrak{R}_{\mathbf{m}}(\mathcal{G}, \Lambda) + Bd\left(\mathcal{D}\|\mathcal{D}_\Lambda\right) + B\sqrt{\frac{1}{2m} \log \frac{|\Lambda|}{\delta}},$$

Table 1: Accuracy (%) on *DG-15* and *DG-60*. TRO sets the new SOTA on both *DG-15* and *DG-60*.

	ERM	IRM	REx	SD	DRO	TRO (physical)	TRO (data)
DG-15	58.00	57.87	57.22	57.56	43.22	67.56	**67.89**
DG-60	76.02	76.61	86.89	81.04	79.59	89.19	**90.72**

(a) DG-15   (b) DG-60

Figure 2: Data groups of (a) *DG-15* and (b) *DG-60* datasets.

ACC: 43.22%   ACC: 67.56%

Figure 3: Group importance of DRO and TRO on *DG-15*. DRO assigns the highest weight to group "1" which is the most distant group to test groups; TRO focuses on the influential groups "2", "4", "5", and "6", which are truly connected to test groups.

where $d(\cdot)$ is the distance metric. The upper bound of the generalization risk on $\mathcal{D}$ is mainly determined by its distance to $\mathcal{D}_\Lambda$: $d(\mathcal{D}\|\mathcal{D}_\Lambda)$. With the topological prior, the risks on $\mathcal{D}$ can be tightly bounded by minimizing $d(\mathcal{D}\|\mathcal{D}_\Lambda)$, as long as $\mathcal{D}$ falls into the convex hull of training groups. We empirically demonstrate the effectiveness of the topological prior in minimizing the generalization risks over unseen distributions (see Sec. 5).

5 EXPERIMENTS

In this section, we evaluate the proposed TRO in a wide range of tasks including classification, regression, and semantic segmentation. We compare the TRO with SOTA baselines on OOD generalization and conduct ablation study on the key components of TRO. Following Gulrajani & Lopez-Paz (2021), we perform model selection based on a validation set constructed from training groups only. We provide implementation details and additional results in the Appendix. We include the source codes in the supplementary.

Baselines. We compare TRO with the following methods: (1) Empirical Risk Minimization (ERM) (Vapnik, 1998); (2) Group distributionally robust optimization (DRO) (Sagawa et al., 2019); (3) Invariant Risk Minimization (IRM) (Arjovsky et al., 2019); (4) Risk Extrapolation (REx) (Krueger et al., 2021); (5) Spectral Decoupling (SD) (Pezeshki et al., 2021).

5.1 CLASSIFICATION

Datasets. *DG-15* (Xu et al., 2022) is a synthetic binary classification dataset with 15 groups. Each group contains 100 data points. In this dataset, adjacent groups have similar decision boundaries. Following Xu et al. (2022), we use six connected groups as the training groups, and use others as test groups. Note that, different from Xu et al. (2022) which focuses on domain adaptation, the data of test groups are unseen in OOD generalization. *DG-60* (Xu et al., 2022) is another synthetic dataset generated using the same procedure as *DG-15*, except that it contains 60 groups, with 6,000 data points in total. We randomly select six groups as the training groups, and use others as test groups. Visualization of *DG-15* and *DG-60* are shown in Fig. 2(a) and (b), respectively.

Table 2: Mean Squared Error (MSE) for both tasks E (24) → W (24) and N (24) → S (24) on *TPT-48*. TRO (data) consistently outperforms TRO (physical) in both tasks, indicating the data topology may capture the distributional distances more accurately.

Task	Group	ERM	IRM	REx	SD	DRO	TRO (physical)	TRO (data)
E (24)→W (24)	Average of Hop-1 groups	1.693	1.699	1.577	1.701	1.678	1.445	**1.435**
	Average of Hop-2 groups	1.800	1.811	1.702	1.806	1.762	1.576	**1.569**
	Average of Hop-3 groups	1.672	1.679	1.584	1.674	1.628	1.400	**1.392**
	Average of All test groups	1.716	1.724	1.616	1.722	1.684	1.466	**1.458**
N (24)→S (24)	Average of Hop-1 groups	1.084	1.133	**0.487**	1.169	0.931	0.889	0.855
	Average of Hop-2 groups	1.265	1.312	**0.944**	1.354	1.170	0.991	0.950
	Average of Hop-3 groups	1.975	2.021	2.266	2.091	2.027	1.678	**1.604**
	Average of All test groups	1.426	1.474	1.194	1.523	1.356	1.177	**1.129**

Figure 4: **Left:** Generalization task of North → South on *TPT-48*. **Middle:** Group centrality of physical-based topology. **Right:** Group centrality of data-driven topology. "RI" and "NE" are identified as influential groups in physical-based topology while "NY" and "MA" are influential groups in data-driven topology. Data topology yields lower MSE than physical topology.

Figure 5: Group importance of DRO and TRO on the North → South task. TRO significantly reduces the generalization risks by striking a good balance between the worst-case and influential groups.

Results. The results of *DG-15* and *DG-60* are summarized in Tab. 1. In both datasets, our method achieves the highest performance. For *DG-15*, we show the detailed results of all groups in Fig. 8. We visualize the decision boundary of *DG-15* and *DG-60* in Appendix 8.2.

Ablations study. *TRO significantly improves the generalization performance by discovering influential groups.* To investigate the reason why TRO outperforms DRO, we show group weights $\mathbf{q}$ of DRO and TRO on *DG-15* in Fig. 3. As seen, in DRO, group "1" is assigned with the highest weight while "1" is the most distant group to the test groups. Instead, our method ignores group "1" and assigns the highest weight to group "6", improving the model's robustness against unseen distributions.

5.2 REGRESSION

Datasets. *TPT-48* (Vose et al., 2014) contains the monthly average temperature for the 48 contiguous states in the US from 2008 to 2019. We focus on the regression task to predict the next 6 months' temperature based on the previous first 6 months' temperature. We consider two generalization tasks: (1) E(24) → W(24): we use the 24 eastern states as training groups and the 24 western states as test groups; (2) N(24) → S(24): we use the 24 northern states as training groups, the 24 southern states as test groups. Test groups one hop away from the closest training group are defined as Hop-1 test groups, those two hops away are Hop-2 test groups, and the remaining groups are Hop-3 test groups. The visualization of N(24) → S(24) on *TPT-48* is shown in Fig. 4 (left).

Figure 6: **Left:** Location of the 11 flood events on *Sen1Floods11*. We use the event "BOL" for test and other events for training. **Right:** Data-driven topology on *Sen1Floods11*. "IND" and "NGA" are identified as the most influential groups, and "GHA" and "KHM" are the least influential groups. Both "IND" and "NGA" are aroused by heavy rainfall, the most prevalent disasters that cause floods, while 'GHA" and "KHM" are aroused edge cases such as dam collapse. The topology enjoys strong explainability while being consistent with human knowledge and scientific plausibility.

Results. We show the results of TPT-48 in Tab. 2. As observed, TRO achieves the lowest average MSE on both tasks. We also report the average MSE of Hop-1, Hop-2, and Hop-3 test groups for both tasks. Although REx achieves the lowest error on Hop-1 and Hop-2 groups in N(24) → S(24), it yields the highest prediction error on Hop-3 groups. TRO achieves the best performance on Hop-3 groups, indicating its generalization capability under large distributional drifts.

Ablations study. (1) *Data-driven topology yields better performance than physical-based topology*. We show group centrality of physical-based and data-driven topology on the task of North → South. Results are shown in Fig. 4. As observed, "RI" and "NE" are identified as influential groups in physical-based topology while "NY" and "MA" are influential groups in data-driven topology.

(2) *Strong OOD resilience of TRO comes from the synergy of the worst-case and influential groups.* To investigate which components contribute to the superior performance of TRO. We build a simple baseline based on ERM: we directly use the group importance acquired from the topology as the weights for training groups and the weights are fixed during the training. We name this baseline as importance weighted ERM (IW-ERM). We show the results of "N(24)→S(24)" on *TPT-48* in Tab. 3.

Table 3: MSE on *TPT-48*. Ignoring either the worst-case (IW-ERM) or influential (DRO) groups would yield compromised perfromance.

	Hop-1 Avg.	Hop-2 Avg.	Hop-3 Avg.	Avg.
ERM	1.084	1.265	1.975	1.426
IW-ERM	1.320	1.604	2.635	1.829
DRO	0.931	1.170	2.027	1.356
TRO	**0.855**	**0.950**	**1.604**	**1.219**

We can see that the results of IWERM is even worse than ERM and DRO. We further show the group importance of DRO and TRO in Tab. 5. As shown, TRO significantly reduces the generalization risks by striking a good balance between the worst-case and influential groups.

5.3 SEMANTIC SEGMENTATION

Datasets. *Sen1Floods11* (Bonafilia et al., 2020) is a public dataset for flood mapping at global scale. The dataset provides global coverage of 4,831 chips of 512 x 512 10m satellite images across 11 distinct flood events, covering 120,406 km^2. Each image is associated with its pixel-wise label. Locations of the 11 flood events are shown in Fig. 6(left). Flood events vary in boundary conditions, terrain and other latent factors, posing significant OOD challenges to existing models in terms of reliability and explainability. Following Bonafilia et al. (2020), event "BOL" is held out for test, and data of other events are split into training and validation sets with a random 80-20 split. We evaluate the performance in terms of Intersection over Union (IoU).

Results. We show the results of Sen1Floods11 in Tab. 4. As seen, TRO achieves the highest IoU on test set while ERM achieves the highest IoU on validation set. Results demonstrate the strong OOD resilience of TRO in high-stake applications.

Ablations study. (1) *Data-driven distributional topology is consistent with human knowledge.* We visualize the distributional topology as well as group centrality in Fig. 6 (right). We observe that "IND" and "NGA" are identified as the most influential events. Both "IND" and "NGA" are aroused by heavy rainfall, the most prevalent disasters that cause floods. We empirically found that the least influential events are usually caused by edge cases. For example, "GHA" was caused by heavy rains

	ERM	IRM	REx	SD	DRO	TRO (data)
Val	**.489**	.387	.484	.449	.480	.476
Test	.430	.338	.357	.400	.433	**.450**

Table 4: Segmentation results (IoU) on *Sen1Floods11*. TRO achieves the highest IoU on test set while ERM achieves the highest IoU on validation set.

Figure 7: Ablation study on the Lagrange multiplier λ. IoU remains stable during a wide range of λ.

and waters spilling from a dam in neighboring Burkina Faso, and "KHM" was caused by a dam that collapsed in southern Laos. The learned distributional topology is consistent with human knowledge, indicating the strong explainability of TRO. (2) *Ablation study on the Lagrange multiplier λ.* λ controls the strength of topological constraints. We report IoU on the validation set of *Sen1Floods11*. Results are shown in Fig. 7. As seen, IoU remains stable during a wide range of λ, and $\lambda = 0.01$ achieves the highest IoU on the validation set.

6 RELATED WORK

Distributionally Robust Optimization. In the context of distributionally robust optimization (DRO), Duchi & Namkoong (2021) and Shalev-Shwartz & Wexler (2016) argued that minimizing the maximal loss over a set of possible distributions can provide better generalization performance than minimizing the average loss. The robustness guarantee of DRO heavily relies on the quality of the uncertainty set which is typically constructed by moment constraints (Delage & Ye, 2010), f-divergence (Namkoong & Duchi, 2016) or Wasserstein distance (Shafieezadeh Abadeh et al., 2018). To avoid yielding overly pessimistic models, group DRO (Hu et al., 2018; Sagawa et al., 2019) is proposed to leverage pre-defined data groups to formulate the uncertainty set as the mixture of these groups. Although the uncertainty set of Group DRO is of a wider radius while not being too conservative, our preliminary results show that Group DRO recklessly prioritizes the worst-case groups that incur higher losses than others. Such worst-case groups are not necessarily the influential ones that are truly connected to unseen distributions; optimizing over the worst-case rather than influential groups would yield mediocre OOD generalization performance.

Out-of-Distribution Generalization. The goal of OOD generalization is to generalize the model from source distributions to unseen target distributions. There are mainly two branches of methods to tackle OOD generalization: domain-invariant learning (Arjovsky et al., 2019; Koyama & Yamaguchi, 2020; Liu et al., 2021) and distributionally robust optimization. The goal of domain-invariant learning is to exploit the causally invariant correlations across multiple distributions. Invariant Risk Minimization (IRM) is one of the most representative methods which learns the optimal classifier across source distributions. However, recent work (Rosenfeld et al., 2021) shows that IRM methods can fail catastrophically unless the test data are sufficiently similar to the training distribution.

7 CONCLUSION

In this paper, we proposed a new principled optimization method that seamlessly integrates topological information to develop strong OOD resilience. Theoretical analysis that proves our method enjoys fast convergence for both convex and non-convex loss functions while the generalization risk is tightly bounded. Empirical results in a wide range of tasks including classification, regression, and semantic segmentation that demonstrate the superior performance of our method over SOTA. Moreover, the distributional topology is highly explainable while consistent with human knowledge.

REFERENCES

Martin Arjovsky, Léon Bottou, Ishaan Gulrajani, and David Lopez-Paz. Invariant risk minimization. *arXiv preprint arXiv:1907.02893*, 2019.

Derrick Bonafilia, Beth Tellman, Tyler Anderson, and Erica Issenberg. Sen1floods11: A georeferenced dataset to train and test deep learning flood algorithms for sentinel-1. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, pp. 210–211, 2020.

Stephen P Borgatti and Martin G Everett. A graph-theoretic perspective on centrality. *Social networks*, 28(4):466–484, 2006.

Stephen Boyd, Stephen P Boyd, and Lieven Vandenberghe. *Convex optimization*. Cambridge university press, 2004.

Liam Collins, Aryan Mokhtari, and Sanjay Shakkottai. Task-robust model-agnostic meta-learning. *Advances in Neural Information Processing Systems*, 33:18860–18871, 2020.

Elliot Creager, Jörn-Henrik Jacobsen, and Richard Zemel. Environment inference for invariant learning. In *International Conference on Machine Learning*, pp. 2189–2200. PMLR, 2021.

Erick Delage and Yinyu Ye. Distributionally robust optimization under moment uncertainty with application to data-driven problems. *Operations research*, 58(3):595–612, 2010.

John C Duchi and Hongseok Namkoong. Learning models with uniform performance via distributionally robust optimization. *The Annals of Statistics*, 49(3):1378–1406, 2021.

Charlie Frogner, Sebastian Claici, Edward Chien, and Justin Solomon. Incorporating unlabeled data into distributionally robust learning. *Journal of Machine Learning Research*, 22(56):1–46, 2021.

Ishaan Gulrajani and David Lopez-Paz. In search of lost domain generalization. In *International Conference on Learning Representations*, 2021.

Weihua Hu, Gang Niu, Issei Sato, and Masashi Sugiyama. Does distributionally robust supervised learning give robust classifiers? In *International Conference on Machine Learning*, pp. 2029–2037. PMLR, 2018.

Masanori Koyama and Shoichiro Yamaguchi. Out-of-distribution generalization with maximal invariant predictor. 2020.

David Krueger, Ethan Caballero, Joern-Henrik Jacobsen, Amy Zhang, Jonathan Binas, Dinghuai Zhang, Remi Le Priol, and Aaron Courville. Out-of-distribution generalization via risk extrapolation (rex). In *International Conference on Machine Learning*, pp. 5815–5826. PMLR, 2021.

Solomon Kullback and Richard A Leibler. On information and sufficiency. *The annals of mathematical statistics*, 22(1):79–86, 1951.

William Leeb and Ronald Coifman. Hölder–lipschitz norms and their duals on spaces with semigroups, with applications to earth mover's distance. *Journal of Fourier Analysis and Applications*, 22(4):910–953, 2016.

Daniel Levy, Yair Carmon, John C Duchi, and Aaron Sidford. Large-scale methods for distributionally robust optimization. *Advances in Neural Information Processing Systems*, 33:8847–8860, 2020.

Jiashuo Liu, Zheyuan Hu, Peng Cui, Bo Li, and Zheyan Shen. Heterogeneous risk minimization. In *International Conference on Machine Learning*, pp. 6804–6814. PMLR, 2021.

Mehryar Mohri, Gary Sivek, and Ananda Theertha Suresh. Agnostic federated learning. In *International Conference on Machine Learning*, pp. 4615–4625. PMLR, 2019.

Hongseok Namkoong and John C Duchi. Stochastic gradient methods for distributionally robust optimization with f-divergences. *Advances in neural information processing systems*, 29, 2016.

Arkadi Nemirovski, Anatoli Juditsky, Guanghui Lan, and Alexander Shapiro. Robust stochastic approximation approach to stochastic programming. *SIAM Journal on optimization*, 19(4):1574–1609, 2009.

Mark EJ Newman. A measure of betweenness centrality based on random walks. *Social networks*, 27(1):39–54, 2005.

Mohammad Pezeshki, Oumar Kaba, Yoshua Bengio, Aaron C Courville, Doina Precup, and Guillaume Lajoie. Gradient starvation: A learning proclivity in neural networks. *Advances in Neural Information Processing Systems*, 34, 2021.

Qi Qian, Shenghuo Zhu, Jiasheng Tang, Rong Jin, Baigui Sun, and Hao Li. Robust optimization over multiple domains. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 4739–4746, 2019.

Alexander Robey, George J Pappas, and Hamed Hassani. Model-based domain generalization. *Advances in Neural Information Processing Systems*, 34:20210–20229, 2021.

Elan Rosenfeld, Pradeep Ravikumar, and Andrej Risteski. The risks of invariant risk minimization. In *International Conference on Learning Representations*, volume 9, 2021.

Shiori Sagawa, Pang Wei Koh, Tatsunori B Hashimoto, and Percy Liang. Distributionally robust neural networks for group shifts: On the importance of regularization for worst-case generalization. In *International Conference on Learning Representations*, 2019.

Soroosh Shafieezadeh Abadeh, Viet Anh Nguyen, Daniel Kuhn, and Peyman M Mohajerin Esfahani. Wasserstein distributionally robust kalman filtering. *Advances in Neural Information Processing Systems*, 31, 2018.

Shai Shalev-Shwartz and Yonatan Wexler. Minimizing the maximal loss: How and why. In *International Conference on Machine Learning*, pp. 793–801. PMLR, 2016.

Matthew Staib and Stefanie Jegelka. Distributionally robust optimization and generalization in kernel methods. *Advances in Neural Information Processing Systems*, 32, 2019.

Yu Tian, Long Zhao, Xi Peng, and Dimitris Metaxas. Rethinking Kernel Methods for Node Representation Learning on Graphs. In *f*, 2019.

Alexander Y Tong, Guillaume Huguet, Amine Natik, Kincaid MacDonald, Manik Kuchroo, Ronald Coifman, Guy Wolf, and Smita Krishnaswamy. Diffusion earth mover's distance and distribution embeddings. In *International Conference on Machine Learning*, pp. 10336–10346. PMLR, 2021.

Vladimir Vapnik. Statistical learning theory, 1998.

R Vose, S Applequist, M Squires, I Durre, MJ Menne, CN Williams Jr, C Fenimore, K Gleason, and D Arndt. Gridded 5km ghcn-daily temperature and precipitation dataset (nclimgrid) version 1. *Information, NNCfE, editor. Maximum Temperature, Minimum Temperature, Average Temperature, and Precipitation*, 2014.

Zihao Xu, Guang-He Lee, Yuyang Wang, Hao Wang, et al. Graph-relational domain adaptation. In *International Conference on Learning Representations*, 2022.

8 APPENDIX

8.1 IMPLEMENTATION DETAILS

Calculation of group centrality. We use betweenness centrality to measure group centrality as it reveals the global structure of graphs. Specifically, betweenness centrality measures the centrality of nodes in terms of their connectivity to others via the shortest paths. For physical-based topology, let $s \in \mathcal{E}_{\text{train}}$ and $t \in \mathcal{E}_{\text{test}}$ be the start and end of a path in $\mathcal{G}_{physical}$. We define the centrality of group e by computing the fraction of shortest paths that pass through it:

$$c_e^{\text{full}} = \sum_{s \in \mathcal{E}_{\text{train}}, t \in \mathcal{E}_{\text{test}}} \frac{\sigma(s, t \mid e)}{\sigma(s, t)}, \tag{8}$$

where $\sigma(s, t)$ is the number of shortest paths between groups s and t in the graph ((s, t)-paths), and $\sigma(s, t \mid v)$ is the number of (s, t)-paths that go through group e. Eq. 8 measures the degree of brokerage (or mediation Borgatti & Everett (2006)) for group v in the graph, meaning that it measures how much information is propagated through e from the start (training) to the end (test). For data-driven topology $\mathcal{G}_{physical}$, the underlying assumption is that training groups with high centrality also exert strong influence on unseen groups. Instead of sampling groups pairs from two separate sets, we sample (s, t) from $\mathcal{E}_{\text{train}}$. Eq. 8 is modified as:

$$c_e^{\text{partial}} = \sum_{s, t \in \mathcal{E}_{\text{train}}} \frac{\sigma(s, t \mid e)}{\sigma(s, t)}.$$

We use softmax function to normalize c_e and the prior probability for group $e \in \mathcal{E}_{\text{train}}$ is defined as $p_e = \exp(c_e) / \sum_{e=1}^{m} \exp(c_e)$.

8.2 ADDITIONAL RESULTS

DG-15 and *DG-60*. We provide detailed classification results for each groups. The results are shown in Fig. 8. We can see that, compared to other baselines, TRO significantly improves the generalization performance on groups which are far from the training groups, such as group "13". We further visualize the decision boundary of *DG-15* and *DG-60* in Fig. 9 and Fig. 10, respectively.

Figure 8: Detailed results on *DG-15*. Our method outperforms ERM by 9.56% while other baselines are inferior to ERM.

8.3 PROOF OF THEOREM 1

Proof. By using the property of convex loss functions, we can obtain:

$$\max_{q \in \Delta_m} \mathcal{R}(\theta_T, q) - \min_{\theta \in \Theta} \mathcal{R}(\theta, q_T) \le \frac{1}{T} \max_{q \in \Delta, \theta \in \Theta} \left\{ \sum_{t=1}^{T} \mathcal{R}(\theta^t, q) - \mathcal{R}(\theta, q^t) \right\},$$

where $\forall t \ge 1$:

$$\mathcal{R}(\theta^t, q) - \mathcal{R}(\theta, q^t) = \mathcal{R}(\theta^t, q) - \mathcal{R}(\theta^t, q^t) + \mathcal{R}(\theta^t, q^t) - \mathcal{R}(\theta, q^t)$$
$$\le \langle (q - q^t), \nabla_q \mathcal{R}(\theta^t, q^t) \rangle + \langle (\theta^t - \theta), \nabla_\theta \mathcal{R}(\theta^t, q^t) \rangle$$

Figure 9: Visualization of decision boundary on *DG-15*.

Figure 10: Visualization of decision boundary on *DG-60*. TRO can correctly classify the data of most groups even if training groups are only one-tenth of all groups.

By rearrange the terms in the above equation, we obtain:

$$\max_{q \in \Delta, \theta \in \Theta} \left\{ \sum_{t=1}^{T} \mathcal{R}\left(\theta^t, q\right) - \mathcal{R}\left(\theta, q^t\right) \right\} \leq \mathbb{E}\left[\max_{\theta \in \Theta} \sum_{t=1}^{T} \left\langle \left(\theta^t - \theta\right), \hat{g}_\theta^t \right\rangle \right] +$$

$$\mathbb{E}\left[\max_{q \in \Delta_m} \sum_{t=1}^{T} \left\langle \left(q - q^t\right), \hat{g}_q^t \right\rangle \right] + \mathbb{E}\left[\max_{q \in \Delta_m} \sum_{t=1}^{T} \left\langle q, \nabla_q \mathcal{R}\left(\theta^t, q^t\right) - \hat{g}_q^t \right\rangle \right]$$

$$+ \mathbb{E}\left[\max_{\theta \in \Theta} \sum_{t=1}^{T} \left\langle \theta, \hat{g}_\theta^t - \nabla_\theta \mathcal{R}\left(\theta^t, q^t\right) \right\rangle \right].$$

Following Collins et al. (2020), we will derive the combined bound by bounding the expectation of each term in the above equation*. For the first term, by utilizing the telescoping sum, we can obtain:

$$\mathbb{E}\left[\max_{\theta \in \Theta} \sum_{t=1}^{T} \left\langle \left(\theta^t - \theta\right), \hat{g}_\theta^t \right\rangle \right] = \frac{1}{2} \sum_{t=1}^{T} \frac{1}{\eta_\theta} \left\| \theta^t - \theta \right\|_2^2 + \eta_\theta \left\| \hat{g}_\theta^t \right\|_2^2 - \frac{1}{\eta_\theta} \left\| \theta^t - \eta_\theta \hat{g}_\theta^t - \theta \right\|_2^2$$

$$\leq \frac{2R_\Theta^2}{\eta_\theta} + \frac{\eta_\theta}{2} \sum_{t=1}^{T} \left\| \hat{g}_\theta^t \right\|_2^2 \leq \frac{2R_\Theta^2}{\eta_\theta} + \frac{\eta_\theta T \hat{G}_\theta^2}{2}.$$

Similarly, for the second term:

$$\mathbb{E}\left[\max_{q \in \Delta_m} \sum_{t=1}^{T} \left\langle \left(q - q^t\right), \hat{g}_q^t \right\rangle \right] \leq \frac{2}{\eta_q} + \frac{\eta_q T \hat{G}_q^2}{2}.$$

The third term and the last term are bounded by $\sqrt{T}\tilde{\sigma}_q$ and $R_\Theta \sqrt{T}\tilde{\sigma}_\theta$, respectively. To this end, we can derive the overall bound as:

$$\mathbb{E}\left[\max_{q \in \Delta_m} \mathcal{R}\left(\theta_T, q\right) - \min_{\theta \in \Theta} \mathcal{R}\left(\theta, q_T\right) \right] \leq \frac{2R_\Theta^2}{\eta_\theta T} + \frac{\eta_\theta \hat{G}_\theta^2}{2} + \frac{2}{\eta_q T} + \frac{\eta_q \hat{G}_q^2}{2} + \frac{R_\Theta \tilde{\sigma}_\theta}{\sqrt{T}} + \frac{\tilde{\sigma}_q}{\sqrt{T}}.$$

The above bound can be minimized by setting the step sizes $\eta_\theta = 2R_\Theta / \left(\hat{G}_\theta \sqrt{T} \right)$ and $\eta_q = 2 / \left(\hat{G}_q \sqrt{T} \right)$.

8.4 PROOF OF THEOREM 2

Proof. Inspired by Qian et al. (2019) and Collins et al. (2020), we utilize the property of M-smooth to start the proof:

$$\mathbb{E}\left[\sum_{i=1}^{n} q_i^t \ell_i \left(\theta^{t+1}\right) \right] \leq \sum_{i=1}^{n} q_i^t \ell_i \left(\theta^t\right) - \left(\eta_\theta - \frac{\eta_\theta^2 M}{2} \right) \left\| g_\theta^t \right\|^2 + \frac{\eta_\theta^2 M \sigma_\theta^2}{2}.$$

We rearrange these terms by:

$$\left(\eta_\theta - \frac{\eta_\theta^2 M}{2} \right) \left\| g_\theta^t \right\|^2 \leq \mathbb{E}\left[\sum_{i=1}^{n} q_i^t \ell_i \left(\theta^t\right) - \sum_{i=1}^{n} q_i^t \ell_i \left(\theta^{t+1}\right) \right] + \frac{\eta_\theta^2 M \sigma_\theta^2}{2}$$

$$= \mathbb{E}\left[\sum_{i=1}^{n} q_i^t \ell_i \left(\theta^t\right) - \sum_{i=1}^{n} q_i^{t+1} \ell_i \left(\theta^{t+1}\right) \right]$$

$$+ \mathbb{E}\left[\sum_{i=1}^{n} q_i^{t+1} \ell_i \left(\theta^{t+1}\right) - \sum_{i=1}^{n} q_i^t \ell_i \left(\theta^{t+1}\right) \right] + \frac{\eta_\theta^2 M \sigma_\theta^2}{2}$$

The second term of the above equation can be bounded by:

$$\mathbb{E}\left[\sum_{i=1}^{n} q_i^{t+1} \ell_i \left(\theta^{t+1}\right) - \sum_{i=1}^{n} q_i^t \ell_i \left(\theta^{t+1}\right) \right] = \mathbb{E}\left[\sum_{i=1}^{n} \left(q_i^{t+1} - q_i^t\right) \ell_i \left(\theta^{t+1}\right) \right]$$

$$\leq \mathbb{E}\left[\left\| q^{t+1} - q^t \right\|_2 \sum_{i=1}^{n} \left(\ell_i \left(\theta^{t+1}\right) \right)^{1/2} \right]$$

$$\leq \eta_q \sqrt{n} \hat{B} \hat{G}_q$$

By using the Law of Iterated Expectations, we can obtain:

$$
\left(\eta_\theta - \frac{\eta_\theta^2 M}{2} \right) \sum_{t=1}^{T} \mathbb{E} \left[\left\| g_\theta^t \right\|^2 \right]
$$

$$
\leq \mathbb{E} \left[\sum_{i=1}^{n} q_i^1 \ell_i \left(\theta^1 \right) \right] - \mathbb{E} \left[\sum_{i=1}^{n} q_i^{T+1} \ell_i \left(\theta^{T+1} \right) \right] + 2T\eta_q \sqrt{n} \hat{B} \hat{G}_q + \frac{TM\eta_\theta^2 \sigma_\theta^2}{2} \tag{9}
$$

$$
\leq \mathcal{R} \left(\theta^1, q^1 \right) + \hat{B} + 2T\eta_q \sqrt{n} \hat{B} \hat{G}_q + \frac{T\eta_\theta^2 M \sigma_\theta^2}{2}.
$$

Next, we investigate the convergence of q:

$$
\mathbb{E} \left[\mathcal{R} \left(\theta^t, q \right) - \mathcal{R} \left(\theta^t, q^t \right) \right] = \mathbb{E} \left[\frac{1}{2\eta_q} \left(\left\| q - q^t \right\|_2^2 + (\eta_q)^2 \left\| \hat{g}_q^t \right\|_2^2 - \left\| q - \left(q^t + \eta_q \hat{g}_q^t \right) \right\|_2^2 \right) \right]
$$

$$
\leq \mathbb{E} \left[\frac{1}{2\eta_q} \left(\left\| q - q^t \right\|_2^2 + (\eta_q)^2 \left\| \hat{g}_q^t \right\|_2^2 - \left\| q - q^{t+1} \right\|_2^2 \right) \right]
$$

$$
\leq \mathbb{E} \left[\frac{1}{2\eta_q} \left(\left\| q - q^t \right\|_2^2 + (\eta_q)^2 \hat{G}_q^2 - \left\| q - q^{t+1} \right\|_2^2 \right) \right].
$$

By aggregating the difference at all time steps, we obtain:

$$
\sum_{t=1}^{T} \mathbb{E} \left[\mathcal{R} \left(\theta^t, q \right) - \mathcal{R} \left(\theta^t, q^t \right) \right] \leq \sum_{t=1}^{T} \frac{1}{2\eta_q} \mathbb{E} \left[\left\| q - q^t \right\|_2^2 \right] - \frac{1}{2\eta_q} \mathbb{E} \left[\left\| q - q^{t+1} \right\|_2^2 \right] + \frac{\eta_q}{2} \hat{G}_q^2
$$

$$
= \frac{1}{2\eta_q} \mathbb{E} \left[\left\| q - q^1 \right\|_2^2 \right] + \frac{\eta_q}{2} T \hat{G}_q^2
$$

$$
\leq \frac{1}{\eta_q} + \frac{\eta_q T \hat{G}_q^2}{2}
$$

Since the above equation holds for all $q \in \Delta_m$, we maximize the right hand side over $q \in \Delta_m$:

$$
\frac{1}{T} \sum_{t=1}^{T} \mathbb{E} \left[\mathcal{R} \left(\theta^t, q^t \right) \right] \geq \max_{q \in \Delta_m} \left[\mathcal{R} \left(\theta_T, q \right) \right] - \left(\frac{1}{\eta_q T} + \frac{\eta_q \hat{G}_q^2}{2} \right) \tag{10}
$$

Eqs. 9 and 10 show that TRO converges in expectation to an (ϵ, δ)-stationary point of $\mathcal{R}$ in $\mathcal{O}(1/\epsilon^4)$ stochastic gradient evaluations.