Video-LLMs with Temporal Visual Screening

Abstract

Current Video-LLMs lack human-like temporal screening capabilities and their behavioral manifestations (e.g. scrubbing the seek bar), struggling with fine-grained semantics due to a static, sparse frame sampling paradigm. To address this, we introduce **T**emporal **V**isual **S**creening (TVS), a cognitively inspired novel task formalized as an endomorphic transformation, $\mathcal{F}_{TVS} : (V, Q) \rightarrow (v', q')$, which maps a task instance to a computationally tractable and semantically coherent one within the same bimodal space. This is achieved by excising irrelevant segments while synchronously rewriting the query to ensure answer invariance. Designed as a modular front-end adapter under VideoQA setting, TVS can be seamlessly integrated into **both** Video Instruction Tuning (training) and Video Question Answering (inference) pipelines. To facilitate this new task, we introduce the first dedicated benchmark and propose ReSimplifyIt, a baseline that surpasses prior methods from similar tasks by 0.47 F-1 score with competitive query rewriting performance. Integrating TVS yields significant relative gains of 7.33% in training and 33.7% in inference, validating the efficacy of our approach for video-language understanding.[1]

1 Introduction

Cognition routinely deploys goal-guided, two-stage information control: a fast, low-cost pre-attentive screening that prunes redundant cognition burden, followed by a slower, high-cost focused reasoning that operates on a compacted, goal-aligned representation (Treisman and Gelade, 1980; Wolfe, 1994; Zacks et al., 2007; Hochstein and Ahissar, 2002). As its behavioral manifestation, we scrub the seek bar to locate our interested region when watching videos based on top-down feedback, enabling efficient **goal**-oriented problem reconstruction before further reasoning (Wu and Xie, 2024),

[1] Our code is available here.

beneficially minimizing Extraneous Load to purify Germane Load (Sweller, 1988; Mayer and Moreno, 2003; Paas et al., 2003).

In contrast, current Video-LLMs (Chen et al., 2023; Li et al., 2023a; Xu et al., 2024a; Maaz et al., 2024; Li et al., 2024b; Ma et al., 2024) operate on a fundamentally contrary principle. By statically and uniformly ingesting video frames, they are forced to confront the full, unmitigated reasoning load of a given $(Video, Query)$ instance. The information-intense nature of video worsens the absence of such a reasoning-guided temporal skimming mechanism to eliminate superfluous perceptual and reasoning burden, which manifests as dilution of semantic focus on task-critic segments and noise from hardly relevant frames. These challenges take place both during encoding and reasoning, and impact both the training (Lin et al., 2024; Zhang et al., 2025) process—by weakening supervision signals—and the inference stage—by reducing task-oriented focus.

The traditional grounding or grounded QA task (Xiao et al., 2024; Chen et al., 2024a) would fail to address these, as grounding relies on **depictive-level** similarity and **perceptual-level** alignment to enhance *visual cues*, arising from a deeper misalignment between the problem representation and the goal state: across time during reasoning, the query often entangles multi-hop temporal, relational, and causal dependencies with sparse, weakly localized visual evidence.

This gap calls for the need of an interpretable and controllable goal-oriented temporal skimming mechanism that optimizes reasoning structure and cognitive load while treating the entangled input modalities **as a whole**, and pinpoints cognitive-level alignment to facilitate high-level *multimodal reasoning*, bringing generalizability to settings beyond descriptive and retrieval-based intents.

We accordingly propose **T**emporal **V**isual **S**creening (TVS) for Video-LLMs, a cognitively

Figure 1: Input and output example of the TVS task as a side-by side comparison to a superficially similar task: temporal localization. TVS focuses on goal-driven cognitive alignment and performs reasoning-guided problem reconstruction through information screening, whereas grounding only emphasizes perceptual alignment and locates depictive level visual evidence by direct moment retrieval.

inspired **endomorphic** transformation:

$$\mathcal{F}_{\text{TVS}} : (V, Q) \rightarrow (v, q)$$

that reconstructs a computationally tractable, semantically coherent instance within the same multi-modal task space. TVS performs in a meticulously designed goal-invariant manner, which aligns with the fixity of the Goal State from the Problem Space Theory (Newell and Simon, 1972), enhances granularity of multimodal alignment on the cognitive level, and facilitates pinpointed cognitive focus for detailed multimodal understanding.

The benefits of TVS land in four concrete areas: (i) Training-time alignment: by removing off-target supervision under fixed budget, TVS raises gradient signal-to-noise and reduces spurious correlations, yielding stronger multimodal supervision; (ii) Inference-time robustness: by offloading non-informative yet resource-consuming perceptual burden, TVS shortens the implicit reasoning program, thereby unleashing the QA agent's reasoning ability under fixed budget; (iii) Interpretability and controllability: the compact, answer-preserving (v', q') is a controllable, semantically faithful artifact that exposes model bottlenecks via precise and auditable evidences; (iv) Model-agnosticism and generalizability: implemented as a front-end adapter, TVS plugs into arbitrary VideoQA agents, with gains that persist across datasets and architectures.

We present *ReSimplifyIt*, a plug-and-play multi-agent framework, with its key design drawing inspirations from cognitive science principles, being able to **ReS**iliently **imp**rovise and qua**lify** proposals **It**eratively. It chains iterative screening rounds where a language-only Launcher module hypothesizes trimming instruction and rewritten query while utilizing the intrinsic relation between the two input modalities as a prior, a Validator executes and critiques these plans through a Viewer module, and memory trackers to assist self-correction. This design operationalizes a competence-from-consequence (Brooks, 1991) principle where trial execution provides constructive feedback that tightens the coupling between hypothesized reasoning structure and available evidence.

We further construct YouCookII-TVS, the first benchmark dedicated to evaluating TVS as a joint transformation over video and query, enabling assessment of both screening quality and downstream VideoQA performance.

Through quantitatively benchmarking TVS and its impact on both downstream training and inference, we show that TVS is a non-trivial challenging task that remains far from being solved and reveals a key bottleneck for downstream VideoQA reasoning, and thus deserves to be formulated, benchmarked, and studied independently.

Our work is arguably the first to formally recognize that grounding and trimming a video creates a semantic mismatch with a complex, context-dependent query, to formalize the task upon it, and to extensively explore temporal filtering mechanism into the Video-LLM framework. Our results demonstrate that TVS not only improves inference-

time performance but also facilitates more structured and effective training by finer-grained multi-modal alignment, paving the way for more scalable, interpretable, and cognitively-inspired video-language understanding systems.

The main contributions of this work are summarized below:

- We propose a novel cognitively-inspired task, temporal visual screening (TVS), which plays a pivotal role in video understanding by guiding task-aware reasoning structure filtering, thereby addressing a key bottleneck in multi-modal alignment. In addition, we propose a benchmark YouCookII-TVS for the TVS task, which comprises 238.2 Hours of videos and 2754 questions.

- We introduce the ReSimplifyIt framework, the first baseline for the TVS task, as a model-agnostic plug-in compatible with **any** existing videoQA and instruction tuning pipelines.

- We quantitatively evaluate the impact of TVS in VideoQA and Video Instruction Tuning. Our method brings considerable performance boost to multiple strong baselines over various VideoQA benchmarks (over 10% and 5% absolute gain on inference and training stage, respectively).

2 Formulation of Temporal Visual Screening (TVS)

2.1 Task Definition

TVS is elegantly designed to pinpoint critical video focus without altering data formats, ensuring full procedural compatibility with any existing VideoQA and Video Instruction Tuning pipelines as a front-end adapter. Refer to Figure 1 for illustration. Formally, given a full-length video $V = \{F_1, F_2, \ldots, F_T\}$ consisting of T ordered frames and a natural language query Q, the **Temporal Visual Screening (TVS)** task aims to output:
- a reconstructed query q, derived from Q, and
- a new **continuous** video

$$v = \{F_{s_1}, F_{s_1+1}, \ldots, F_{e_1}, \ F_{s_2}, F_{s_2+1}, \ldots,$$
$$F_{e_2}, \ldots, F_{s_n}, F_{s_n+1}, \ldots, F_{e_n}\} \subseteq V$$

being the concatenation of n non-overlapping segments of the original video, where $1 \leq s_1 \leq e_n \leq T$ and $n \geq 1$, such that v contains the minimal but sufficient visual information to correctly answer q, and preserves *low-level temporal continuity* essential for motion, spatial, and object-level reasoning. Specifically, we define a function:

$$\mathcal{F}_{\text{TVS}} : (V, Q) \rightarrow (v, q)$$

subject to the efficacy conditions given next.

Efficacy conditions for TVS Maintaining both *uni-modal efficacy* and *cross-modal synergy*, TVS facilitates temporal visual focus by trimming out insignificant segments of the video, while *synchronously* reconstructing the text query to preserve original semantic alignment. For demonstration, refer to the Appendix. The transformations applied to q and v must be tightly coupled to preserve answer consistency despite input reduction, ensuring semantic alignment and outcome equivalence between the reduced input and the original task. Formally, It must meet the following:

1. **Continuity for Video Output**: v must be a temporally **contiguous** subsegment of V, or a concatenation of such segments, preserving low-level visual integrity necessary for tracking motion, appearance, and scene dynamics.

2. **Minimal Sufficiency for Answer**: A frame $F_t \in v$ is included *if and only if* removing it would alter the model output: $\exists \delta a$ such that $\mathcal{M}(q, v \setminus \{F_t\}) = a + \delta a, \ |\delta a| > \epsilon$ where ϵ is a task-specific confidence or semantic tolerance threshold. This guarantees that each included frame contributes non-trivially to the answer.

3. **Reasoning Minimality for Query Output**:

$$q^* = \underset{q}{\arg\min} \ \text{Infer}(q)$$

where $\text{Infer}(q)$ denotes the number of reasoning steps needed to derive the answer from visual input. For example, reasoning on the phrase "within 5 seconds after event A" requires three reasoning steps on the temporal axis: localization on event A, relational reasoning on "after", and temporal reasoning on "5 seconds". This ensures that q focuses on a *minimal grounded fact* answerable within a concise visual span.

4. **Cross-modal Synergy**: For any reasonable VideoQA agent $\mathcal{M}$, the answer to q given v must match the answer given the full video:

$$\forall \mathcal{M}, \quad \mathcal{M}(q, v) = \mathcal{M}(Q, V).$$

Figure 2: Snapshot examples of the workflow of our proposed ReSimplifyIt framework.

This enforces that v retains all information necessary to support the same answer as the full input, regardless of model architecture.

This formulation enables precise, interpretable alignment between question, answer, and visual evidence, while ensuring temporal coherence and model-agnostic consistency. Refer to Figure 3 for more demonstrations of the TVS task.

2.2 Integrating TVS into Video-LLM Workflows

Temporal Visual Screening (TVS) can be effectively incorporated into both the training and inference workflows of video-language models, enabling cleaner supervision, stronger alignment, and more interpretable model behavior. Below, we describe two major modes of application.

TVS for Inference-Time Simplification in Video-LLMs At inference, TVS acts as a lightweight pre-processing module. Given a video V and query Q, it identifies a salient segment v and reconstructs a simplified query q (see Section 3). This yields a new input pair (v', q'), reducing the temporal and semantic complexity the model must handle. Rather than processing the full video or ambiguous and overgeneralized instructions, the model concentrates on compact, relevant content, facilitating fine-grained temporal reasoning and direct visual grounding. This design aims to improve inference efficiency, robustness, and interpretability.

TVS for Improving Training-Time Visual-Language Alignment Training Video-LLMs often involves complex supervision tuples (V, Q, a),

where queries may be abstract or multi-hop. TVS mitigates this by transforming them into more compact triples (v, q, a), where v is a high-utility segment and q is a grounded reformulation of the original query. This decomposition offloads off-target supervision to upstream modules, allowing the model to specialize in two core competencies: temporal understanding and multimodal alignment.

3 Method

3.1 ReSimplifyIt Framework

Drawing inspirations from *dynamic and interactive attention deployment* (Treisman and Gelade, 1980; Wolfe, 1994) and humans' information screening process by dragging the video's progress bar, we propose our multi-agent ReSimplifyIt framework. The framework is composed of three main agentic components: the Launcher, the Validator, and the Viewer, accompanied by two extra helper modules as memory trackers: the Failure History and the Success History. For implementation details, please refer to Section 4. We denote $\{(v_r, q_r)|1 \leq r \leq R\}$ as the whole TVS process, where v_r, q_r represents the output video clip and question of the rth round, respectively, and R sets the maximum number of rounds. Refer to Algorithm 2 for the complete algorithm of our TVS process performed by our ReSimplifyIt framework, and Figure 2 for a snapshot demonstration.

Initiating a TVS Round: Launcher drafting a video trimming instruction The TVS process unfolds over iterative rounds, akin to how humans drag the progress bar multiple times based solely

on empirical surmise before actually viewing the video content. In each round r, a **Launcher** module generates a trimming instruction i_r and a revised query q_r as a trial, which trimming instruction may only contain *high-level* semantics yielding a declarative goal (e.g. "keep the clip after event X" instead of "clip([5s,10s])"), based solely on the previous query q_{r-1}, without vision access. This trial-based methodology strikes an effective balance between performance and efficiency as the inherent semantic relevance between the query and video input can thereby serve as a prior to enabling plausible instruction generation without video access.

Akin to human landing on undesired segments after dragging the progress bar, we equip the Launcher module with self-correction based adaptive refinement mechanisms to tackle rare failure cases and ensure correctness. Specifically, we maintain two memory tracker modules: **Success History (SH)** and **Failure History (FH)**. A successful trial is added to SH and terminates the round; otherwise, it is recorded in FH and retriggers the Launcher with updated feedback.

We formalize the Launcher's behavior as:

$$(i_r, q_r) = \texttt{Launcher}(q_{r-1}, FH, SH, t)$$

where t denotes the task prompt.

Our feedback-driven formulation achieves iterative self-correction, a key distinction from prior work ([Wang et al., 2024a](#); [Shang et al., 2024](#)). It decomposes the task into progressive rounds to enable iterative self-correction and foster structured reasoning, which enhances multi-hop robustness while minimizing correction costs. The lightweight, video-free Launcher further boosts efficiency by performing abductive reasoning on the language query without sacrificing fidelity.

Validating a trial: Validator executing instruction The **Validator module** receives the high-level instruction i_r from the Launcher and determines its success through execution. The module performs two tightly coupled tasks: (i) *assessing the feasibility* of the instruction (i.e., whether it is able to succeed), and (ii) *executing* the instruction to obtain results or feedback. Unlike the Launcher, the Validator *has indirect access to visual semantics* by interacting with the Viewer module while not taking visual inputs or frame captions itself.

It returns a tuple (d_r, m_r), where:

- d_r indicates whether the instruction is deemed `succeeded` (feasible) or `failed` (infeasible),

- m_r contains either the resulting trimmed video (in the form of timestamp ranges) if successfully executed the instruction, or an explanation if failed.

$$(d_r, m_r) = \texttt{Validator}(i_r, v_{r-1}, t)$$

Here, $\texttt{Validator}()$ denotes the Validator module, v_{r-1} is the previous video state, and t is the task prompt.

The Validator may also decide to call the Viewer module before returning to Launcher. In this scenario, d_r and m_r stand for this decision symbol and the message to the Viewer, respectively.

Our unified Validator assesses plan viability via direct execution rather than handcrafted rules, embodying a "competence from consequence" philosophy ([Brooks, 1991](#)). This integration simplifies control flow and reduces inter-module communication. Crucially, failures are not terminal but provide constructive feedback for the Launcher to refine instructions, transforming execution into a mechanism for both validation and continual adaptation.

Scanning the video: Viewer scanning and localizing Inspired by the Bottom-Up (stimulus-driven) and Top-Down (goal-driven) Activation schema proposed by GS2.0 ([Wolfe, 1994](#)), which also guides humans' scrubbing the seek bar when watching videos, we design the **Viewer** module to explicitly incorporate two complementary tasks:

(i) Scanning: summarize the content of a video snippet given a timestamp range;

(ii) Localizing: retrieve a timestamp range given a text summarization of a video snippet.

Following complementarily symmetric task structure, this design of the Viewer module achieves elegant and efficient bidirectional navigation by providing both top-down (content-driven) and bottom-up (time-driven) exploration, making the Viewer module highly flexible.

To support both tasks, we first perform a two-stage keyframe extraction and captioning process: (1) extract I-frames using MPEG-4 compression to capture key visual content, and (2) apply a dynamic frame clustering algorithm to select the final keyframes, which adaptively adjust the number of clusters without supervision. Compared to frame clustering techniques in previous work ([Wang et al., 2024b](#)), this approach demonstrates stronger generalizability and robustness. For the algorithm of the keyframe extraction process, please refer to algorithm 1. This pre-processing is denoted as:

$$C = prep(start, end).$$

Scanning executes by summarizing the snippet content via LLM reasoning over C, optionally querying additional frames, and is denoted as:

$$Cap = Scanner(prep(start, end), t).$$

Localizing follows a lightweight three-stage search: (1) locate top-k candidate timestamps, (2) select the best, and (3) expand it into a full range. The LLM may optionally query extra frames for confirmation, ensuring minimal frame access while maintaining accuracy. This process is denoted as:

$$(t_{start}, t_{end}) = Localizer(prep(0, d), q).$$

This lightweight yet effective three-stage design achieves fine-grained temporal grounding with minimal overhead, showcasing the Viewer's adaptability and plug-and-play potential.

Algorithms of the keyframe extraction and localization stages are provided in appendix A.

3.2 TVS-guided inference

Attributed to its endomorphic property, TVS can serve as a plug-and-play adapter process for any VideoQA pipeline, including both inference and training stages. Given the input question q and video V, TVS-guided inference is conducted as:

$$response = VideoQA(V', q')$$

$$V', q' = TVS(V, q)$$

where $VideoQA$ can be *any* VideoQA pipeline, including video-LLMs, LLM-assisted pipelines, or any others alternatives, and $TVS()$ stands for the Temporal Visual Screening process.

3.3 TVS-guided training

TVS can also be applied to training stage to purify supervision signal. Given input question q, input video V, and ground truth answer a, we compute the likelihood during the TVS-guided training as:

$$p\left(\mathbf{X}_{\mathrm{A}} \mid \mathbf{X}_{\mathrm{V}}, \mathbf{X}_{\mathrm{Q}}\right) = \prod_{i=1}^{L} p_\theta \left(\mathbf{X}_{\mathrm{A}}^{[i]} \mid \mathbf{X}_{\mathrm{V}}, \mathbf{X}_{\mathrm{Q}}, \mathbf{X}_{\mathrm{A}}^{[1:i-1]}\right)$$

$$\mathbf{X}_{\mathrm{A}}, \mathbf{X}_{\mathrm{Q}}, \mathbf{X}_{\mathrm{V}} = f_t(a), f_t(q'), f_v(v')$$

$$V', q' = TVS(V, q)$$

where f_t, f_v are the text and visual tokenizers.

4 Experiment Settings

4.1 YouCookII-TVS benchmark

As TVS is a new task, few benchmarks is capable of performing the evaluation. While some studies (Lei et al., 2018; Chen et al., 2024b; Lei et al., 2020) have explored grounded VideoQA which may be mistakenly seen as equivalent, they mainly focus on improving visual evidence. See Appendix F for details. The synchronous update of video and query inputs in TVS naturally resolves any potential semantic mismatch, maximally enhancing generalizability and adaptability of our work.

To bridge this gap, we introduce the YouCookII-TVS benchmark, which provides both TVS and standard VideoQA labels. Built upon the YouCookII dataset (Zhou et al., 2018), it comprises 2,754 datapoints split into training, validation, and test sets (roughly 7:2:1). This dual-task benchmark enables unified evaluation of both TVS and VideoQA. Refer to Appendix B for more details.

4.2 Datasets and Benchmarks

We conduct the evaluation from three aspects.

Firstly, we evaluate the quality of the TVS process on **YouCookII-TVS** (Section 4.1). Next, we examine the impact of TVS on downstream VideoQA performance across the following benchmarks: **YouCookII-TVS**, which supports evaluation of both the TVS process and VideoQA performance; **ActivityNet-QA** (Yu et al., 2019), a dataset targeting long-term spatio-temporal reasoning; **NExT-QA** (Xiao et al., 2021), which involves multi-object daily activities; and **NExT-OE** (Xiao et al., 2021), the open-ended QA variant built on the same videos as NExT-QA. For NExT-QA, we conduct open-ended generation during inference and map predictions to MCQ format using GPT-3.5, ensuring consistent evaluation across baselines and benchmarks (see the Appendix for details). Lastly, we investigate the role of TVS in video instruction tuning by fine-tuning Video-LLM baselines on **YouCookII-TVS**, and comparing their downstream performance across all benchmarks.

4.3 Implementation Details

We provide implementation details in Appendix D.

4.4 Baselines

Temporal Visual Screening Considering the lack of baselines of the new TVS task, we adopt

Method	Temporal Relational		Timepoint Indexed		Multifaceted Integrative		**Average**	
	mIoU	F1	mIoU	F1	mIoU	F1	mIoU	F1
VTG-GPT (Xu et al., 2024b)	0.17	0.29	0.15	0.26	0.16	0.24	0.16	0.27
Zheng et al. (2024a)	0.11	0.19	0.04	0.08	0.06	0.10	0.07	0.12
ReSimplifyIt (Ours)	**0.23**	**0.37**	**0.98**	**0.99**	**0.47**	**0.64**	**0.56**	**0.67**

(a) Results on video output

Method	Temporal Relational	Timepoint Indexed	Multifaceted Integrative	**Average**
ReSimplifyIt (Ours)	66.8	78.5	72.8	72.7

(b) Results on query rewriting

Table 1: Stage-1 evaluation results on YouCookII-TVS dataset.

Method	Size	ActivityNetQA		YouCookII-TVS		NExT-QA		NExT-OE	
		w/tvs	w/o	w/tvs	w/o	w/tvs	w/o	w/tvs	w/o
Video-ChatGPT (Maaz et al., 2024)	7B	**58.5**	50.5	**38.9**	28.91	**45.5**	44.2	**49.8**	41.5
Video-LLaVA (Lin et al., 2023)	7B	**61.2**	52.1	**43.2**	32.4	**52.2**	46.3	**48.0**	43.3
ChatUniVi (Jin et al., 2023)	7B	**63.2**	52.0	**56.5**	47.4	–	–	**34.5**	25.9
LLaVA-NExT (Liu et al., 2024b)	7B	**67.8**	62.5	**58.2**	48.6	**60.5**	56.6	**52.3**	43.7
VideoAgent (Wang et al., 2024a)	-	**61.5**	60.2	**53.9**	38.4	**47.0**	45.0	47.8	**49.6**
VideoTree (Wang et al., 2024b)	-	**63.6**	59.0	**69.4**	57.1	**65.2**	60.0	**61.9**	57.7
GPT-4o	-	**75.65**	72.2	**73.84**	63.59	–	–	**62.25**	54.9
GPT-4.1-mini	-	**77.07**	75.19	**76.04**	68.74	–	–	**68.93**	57.45
GPT-4-turbo	-	**77.1**	74.34	**79.39**	70.61	–	–	**70.35**	61.4

Table 2: Evaluation results of TVS-guided inference. **Bold** values indicate the better-performing result for each baseline, comparing the *with TVS v.s. without TVS* configurations on each benchmark.

two baselines from the training-free temporal localization task which are considered to be robust and generalizable to unseen datasets, to make a side-by-side comparison of the video output alone of TVS. Specifically, we adopt VTG-GPT (Xu et al., 2024b), a proposal-based method which made one of the first attempts to training-free video temporal grounding, and Zheng et al. (2024a)'s work which comprehend candidate proposals based on both static and dynamic matching scores. For the query output of the TVS process, we report open-ended evaluation result of our proposed framework.

TVS-guided inference Integrating TVS as a front-end module into existing VideoQA agents yields a novel VideoQA framework. We adopt several Video-LLMs—Video-ChatGPT (Maaz et al., 2024), Video-LLaVA (Lin et al., 2023), ChatUniVi (Jin et al., 2023), and LLaVA-NeXT (Liu et al., 2024b)—as representative baselines. We also examine LLM-assisted frameworks such as VideoTree (Wang et al., 2024b) and VideoAgent (Wang et al., 2024a), which, unlike the static encoding approaches of Video-LLMs, dynamically extract video frames based on the textual query.

TVS-guided training Following Section 3.3, we performed video instruction tuning on Video-ChatGPT (Maaz et al., 2024), Video-LLaVA (Lin et al., 2023), and ChatUniVi (Jin et al., 2023) on YouCookII-TVS. We kept the LLM backbone frozen, and only tuned their multimodal projectors.

5 Evaluation Results

We highlight the importance of the TVS task, as it addresses a core bottleneck in VideoQA by enabling models to screen for semantically aligned moments in long videos by abstracting task-level semantics and guiding modality-aware information filtering, which in turn enhances multi-modal alignment. In this section, we reveal its importance through: (1) using ground-truth TVS significantly boosts performance (e.g., +7.3% relative gain in Table 3), showing its potential as a key supervision signal; (2) current methods fail to solve TVS effectively (Table 1), calling for dedicated solutions. These motivate our design of ReSimplifyIt as a plug-and-play approach to this essential task.

Temporal Visual Screening Our ReSimplifyIt framework outperform both baselines significantly, on every metric and subset of our YouCookII-TVS

Method		ActivityNetQA		YouCookII-TVS		NExT-QA		NExT-OE	
		w/tvs	w/o	w/tvs	w/o	w/tvs	w/o	w/tvs	w/o
Video-ChatGPT	w/o TVS	57.4	49.8	45.1	35.6	48.6	41.3	46.2	40.0
	w/ TVS (gt)	62.7	54.4	49.8	38.9	51.0	45.7	49.2	43.5
	w/ TVS (pred)	60.0	51.3	48.2	37.1	49.6	44.3	48.7	41.9
Video-LLaVA	w/o TVS	53.9	45.1	46.3	35.9	50.2	47.8	47.0	39.1
	w/ TVS (gt)	57.0	48.9	52.6	41.6	55.7	50.8	52.1	44.9
	w/ TVS (pred)	54.2	46.9	48.1	37.4	51.0	49.3	50.7	41.8
ChatUniVi	w/o TVS	63.2	50.0	62.4	57.4	–	–	29.0	22.5
	w/ TVS (gt)	65.6	54.4	67.8	63.8	–	–	34.3	26.0
	w/ TVS (pred)	64.9	52.6	62.8	61.6	–	–	32.1	24.0

Table 3: Evaluation results of TVS-guided training by downstream inference.

benchmark. On the average performance of the whole test set of YouCookII-TVS, ReSimplifyIt achieved an mIoU score higher than 300% of the baselines' performance. For query reshaping, our proposed framework also achieved notably good performance. Refer to Table 1 and Table 4 for results. We provide the prompt in Appendix E.

Ablation Study of ReSimplifyIt Framework We conduct ablation study on ReSimplifyIt framework to evaluate the effectiveness its design. More details are provided in Appendix C.

TVS guided inference As shown in Table 2 and Table 5, all Video-LLM baselines saw a solid absolute performance gain ranging from 5% to 15%, suggesting that Video-LLMs largely suffer from superfluous cognition noise. In contrast, both LLM-assisted reasoning frameworks saw smaller gain. We hypothesize that the design and implementation of these frameworks have intrinsically corporated the TVS process, by leveraging strong reasoning ability of external LLMs or multi-turn interaction.

TVS guided training All checkpoints trained on ground truth TVS labels achieved stable performance gain over their counterparts trained on the vanilla YouCookII-TVS benchmark, which performance gain of the checkpoints trained on the predicted TVS output of ReSimplifyIt framework were weaker. We argue that TVS-guided training benefits Video-LLMs better, particularly when faced with untrimmed videos and complex text instructions requiring multi-hop reasoning. Refer to Table 3 for further details.

6 Related Work

We provide more details in appendix F.

Video-LLMs for VideoQA Video-LLMs have spurred a wave of models aimed at enhancing video understanding (Lin et al., 2023; Ma et al., 2024; Li et al., 2024a, 2023b; Liu et al., 2024b; Xu et al., 2024a), while the sparsity and query-invariant nature of their encoding limits efficacy in capturing fine-grained spatial-temporal details.

LLM-assisted Agentic Reasoning for VideoQA Some other work aiming at proposing robust VideoQA baselines opt to explore pure-text LLM assisted frameworks or multi-agent systems for VideoQA (Wang et al., 2024b; Shang et al., 2024; Wang et al., 2024a). These methods adopt traditional or LLM-based methods to serve as a scheduler, which in fact implicitly fullfills the TVS objective to a significant extent.

7 Conclusion

We introduce Temporal Visual Screening (TVS), a cognitively inspired task that reconstructs a VideoQA instance (V, Q) into an answer-preserving compact pair (v', q') to purify cognition load. We realize TVS via ReSimplifyIt, a plug-and-play, model-agnostic, and multi-agent framework. To evaluate screening-centric reasoning, we synthesize YouCookII-TVS. Across models and datasets, TVS consistently strengthens training-time alignment and inference-time robustness, yielding notable accuracy gains and exposing bottlenecks through compact, auditable rationales. Our work highlights the importance of information screening and underscores the potential for significant advancements in video understanding and processing by incorporating dynamic information screening mechanisms into VideoQA agents.

Limitations

While applying the initiative of information screening brings considerable performance boost, there are still limitations and room for improvements of our work. Firstly, as the name suggests, temporal visual screening is only applied on the temporal axis and is unable to filter redundant spatial visual information. We recognize spatial visual screening as the more difficult counterpart of our task. Secondly, although our proposed framework's nature of being plug-and-play and adaptable to any VideoQA agent is considered as a strength, it's end-to-end counterpart, which may mainly relate to Video-LLMs' new visual encoder capable of inter-frame reasoning and query-adaptive frame sampling, is left unexplored. In fact, we believe that both extending plug-and-play external modules and improving end-to-end internal model structure can potentially pave the way to information screening.

References

Gedas Bertasius, Heng Wang, and Lorenzo Torresani. 2021. Is space-time attention all you need for video understanding? In *Proceedings of the International Conference on Machine Learning (ICML)*.

Rodney A Brooks. 1991. Intelligence without representation. *Artificial intelligence*, 47(1-3):139–159.

Guo Chen, Yicheng Liu, Yifei Huang, Yuping He, Baoqi Pei, Jilan Xu, Yali Wang, Tong Lu, and Limin Wang. 2024a. Cg-bench: Clue-grounded question answering benchmark for long video understanding. *Preprint*, arXiv:2412.12075.

Guo Chen, Yin-Dong Zheng, Jiahao Wang, Jilan Xu, Yifei Huang, Junting Pan, Yi Wang, Yali Wang, Yu Qiao, Tong Lu, and Limin Wang. 2023. Videollm: Modeling video sequence with large language models. *Preprint*, arXiv:2305.13292.

Qirui Chen, Shangzhe Di, and Weidi Xie. 2024b. Grounded multi-hop videoqa in long-form egocentric videos. *Preprint*, arXiv:2408.14469.

Shaoxiang Chen and Yu-Gang Jiang. 2019. Semantic proposal for activity localization in videos via sentence query. In *Proceedings of the Thirty-Third AAAI Conference on Artificial Intelligence and Thirty-First Innovative Applications of Artificial Intelligence Conference and Ninth AAAI Symposium on Educational Advances in Artificial Intelligence*, AAAI'19/IAAI'19/EAAI'19. AAAI Press.

Jiyang Gao, Chen Sun, Zhenheng Yang, and Ram Nevatia. 2017. Tall: Temporal activity localization via language query. In *2017 IEEE International Conference on Computer Vision (ICCV)*, pages 5277–5285.

Lisa Anne Hendricks, Oliver Wang, Eli Shechtman, Josef Sivic, Trevor Darrell, and Bryan Russell. 2017. Localizing moments in video with natural language. In *2017 IEEE International Conference on Computer Vision (ICCV)*, pages 5804–5813.

Shaul Hochstein and Merav Ahissar. 2002. View from the top: Hierarchies and reverse hierarchies in the visual system. *Neuron*, 36(5):791–804.

Peng Jin, Ryuichi Takanobu, Caiwan Zhang, Xiaochun Cao, and Li Yuan. 2023. Chat-univi: Unified visual representation empowers large language models with image and video understanding. *arXiv preprint arXiv:2311.08046*.

Didier Le Gall. 1991. Mpeg: a video compression standard for multimedia applications. *Commun. ACM*, 34(4):46–58.

Jie Lei, Licheng Yu, Mohit Bansal, and Tamara Berg. 2018. TVQA: Localized, compositional video question answering. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 1369–1379, Brussels, Belgium. Association for Computational Linguistics.

Jie Lei, Licheng Yu, Tamara Berg, and Mohit Bansal. 2020. Tvqa+: Spatio-temporal grounding for video question answering. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8211–8225, Online. Association for Computational Linguistics.

Kunchang Li, Yinan He, Yi Wang, Yizhuo Li, Wenhai Wang, Ping Luo, Yali Wang, Limin Wang, and Yu Qiao. 2023a. Videochat: Chat-centric video understanding. *arXiv preprint arXiv:2305.06355*.

Kunchang Li, Yali Wang, Yinan He, Yizhuo Li, Yi Wang, Yi Liu, Zun Wang, Jilan Xu, Guo Chen, Ping Lou, Limin Wang, and Yu Qiao. 2024a. Mvbench: A comprehensive multi-modal video understanding benchmark. In *2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 22195–22206.

Kunchang Li, Yali Wang, Yinan He, Yizhuo Li, Yi Wang, Yi Liu, Zun Wang, Jilan Xu, Guo Chen, Ping Luo, Limin Wang, and Yu Qiao. 2024b. Mvbench: A comprehensive multi-modal video understanding benchmark. *Preprint*, arXiv:2311.17005.

Yanwei Li, Chengyao Wang, and Jiaya Jia. 2023b. Llama-vid: An image is worth 2 tokens in large language models. In *European Conference on Computer Vision*.

Bin Lin, Bin Zhu, Yang Ye, Munan Ning, Peng Jin, and Li Yuan. 2023. Video-llava: Learning united visual representation by alignment before projection. *arXiv preprint arXiv:2311.10122*.

Yijie Lin, Jie Zhang, Zhenyu Huang, Jia Liu, Zujie Wen, and Xi Peng. 2024. Multi-granularity correspondence learning from long-term noisy videos. In *Proceedings of the International Conference on Learning Representations*.

Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. 2024a. Improved baselines with visual instruction tuning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 26296–26306.

Haotian Liu, Chunyuan Li, Yuheng Li, Bo Li, Yuanhan Zhang, Sheng Shen, and Yong Jae Lee. 2024b. Llava-next: Improved reasoning, ocr, and world knowledge.

Ruyang Liu, Chen Li, Yixiao Ge, Thomas H. Li, Ying Shan, and Ge Li. 2024c. Bt-adapter: Video conversation is feasible without video instruction tuning. In *2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 13658–13667.

Fan Ma, Xiaojie Jin, Heng Wang, Yuchen Xian, Jiashi Feng, and Yi Yang. 2024. Vista-llama: Reducing hallucination in video language models via equal distance to visual tokens. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 13151–13160.

Muhammad Maaz, Hanoona Rasheed, Salman Khan, and Fahad Khan. 2024. Video-ChatGPT: Towards detailed video understanding via large vision and language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 12585–12602, Bangkok, Thailand. Association for Computational Linguistics.

Richard E. Mayer and Roxana Moreno. 2003. Nine ways to reduce cognitive load in multimedia learning. *Educational Psychologist*, 38(1):43–52.

Allen Newell and Herbert A. Simon. 1972. *Human Problem Solving*. Prentice-Hall, Englewood Cliffs, NJ.

Fred Paas, Alexander Renkl, and John Sweller. 2003. Cognitive load theory and instructional design: Recent developments. *Educational Psychologist*, 38(1):1–4.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. 2021. Learning transferable visual models from natural language supervision. *Preprint*, arXiv:2103.00020.

Chuyi Shang, Amos You, Sanjay Subramanian, Trevor Darrell, and Roei Herzig. 2024. TraveLER: A modular multi-LMM agent framework for video question-answering. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 9740–9766, Miami, Florida, USA. Association for Computational Linguistics.

John Sweller. 1988. Cognitive load during problem solving: Effects on learning. *Cognitive Science*, 12(2):257–285.

Anne M. Treisman and Garry Gelade. 1980. A feature-integration theory of attention. *Cognitive Psychology*, 12(1):97–136.

Xiaohan Wang, Yuhui Zhang, Orr Zohar, and Serena Yeung-Levy. 2024a. Videoagent: Long-form video understanding with large language model as agent. *European Conference on Computer Vision (ECCV)*.

Ziyang Wang, Shoubin Yu, Elias Stengel-Eskin, Jaehong Yoon, Feng Cheng, Gedas Bertasius, and Mohit Bansal. 2024b. Videotree: Adaptive tree-based video representation for llm reasoning on long videos. *Preprint*, arXiv:2405.19209.

Jeremy M. Wolfe. 1994. Guided search 2.0: A revised model of visual search. *Psychonomic Bulletin & Review*, 1(2):202–238.

Penghao Wu and Saining Xie. 2024. V?: Guided visual search as a core mechanism in multimodal llms. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 13084–13094.

Junbin Xiao, Xindi Shang, Angela Yao, and Tat-Seng Chua. 2021. Next-qa: Next phase of question-answering to explaining temporal actions. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 9777–9786.

Junbin Xiao, Angela Yao, Yicong Li, and Tat-Seng Chua. 2024. Can i trust your answer? visually grounded video question answering. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 13204–13214.

Huijuan Xu, Kun He, Bryan A. Plummer, Leonid Sigal, Stan Sclaroff, and Kate Saenko. 2019. Multilevel language and vision integration for text-to-clip retrieval. In *AAAI*.

Lin Xu, Yilin Zhao, Daquan Zhou, Zhijie Lin, See Kiong Ng, and Jiashi Feng. 2024a. Pllava : Parameter-free llava extension from images to videos for video dense captioning. *ArXiv*, abs/2404.16994.

Yifang Xu, Yunzhuo Sun, Zien Xie, Benxiang Zhai, and Sidan Du. 2024b. Vtg-gpt: Tuning-free zero-shot video temporal grounding with gpt. *Applied Sciences*, 14(5):1894.

Zhou Yu, Dejing Xu, Jun Yu, Ting Yu, Zhou Zhao, Yueting Zhuang, and Dacheng Tao. 2019. Activitynet-qa: A dataset for understanding complex web videos via question answering. In *AAAI*, pages 9127–9134.

Yitian Yuan, Tao Mei, and Wenwu Zhu. 2019. To find where you talk: temporal sentence localization in video with attention based location regression. In *Proceedings of the Thirty-Third AAAI Conference*

on Artificial Intelligence and Thirty-First Innovative Applications of Artificial Intelligence Conference and Ninth AAAI Symposium on Educational Advances in Artificial Intelligence, AAAI'19/IAAI'19/EAAI'19. AAAI Press.

Jeffrey M. Zacks, Nicole K. Speer, Khena M. Swallow, Todd S. Braver, and Jeremy R. Reynolds. 2007. Event perception: A mind/brain perspective. *Psychological Bulletin*, 133(2):273–293.

Hao Zhang, Aixin Sun, Wei Jing, and Joey Tianyi Zhou. 2020. Span-based localizing network for natural language video localization. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 6543–6554, Online. Association for Computational Linguistics.

Yuji Zhang, Sha Li, Cheng Qian, Jiateng Liu, Pengfei Yu, Chi Han, Yi R Fung, Kathleen McKeown, Chengxiang Zhai, Manling Li, and 1 others. 2025. The law of knowledge overshadowing: Towards understanding, predicting, and preventing llm hallucination. *arXiv preprint arXiv:2502.16143*.

Minghang Zheng, Xinhao Cai, Qingchao Chen, Yuxin Peng, and Yang Liu. 2024a. Training-free video temporal grounding using large-scale pre-trained models. *Preprint*, arXiv:2408.16219.

Minghang Zheng, Xinhao Cai, Qingchao Chen, Yuxin Peng, and Yang Liu. 2024b. Training-free video temporal grounding using large-scale pre-trained models. *Preprint*, arXiv:2408.16219.

Luowei Zhou, Chenliang Xu, and Jason J Corso. 2018. Towards automatic learning of procedures from web instructional videos. In *AAAI Conference on Artificial Intelligence*, pages 7590–7598.

Xingyi Zhou, Anurag Arnab, Shyamal Buch, Shen Yan, Austin Myers, Xuehan Xiong, Arsha Nagrani, and Cordelia Schmid. 2024. Streaming dense video captioning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 18243–18252.

A Viewer Implementation Details

Keyframe Extraction and Captioning. We utilize a two-stage keyframe extraction process combined with frame captioning. In the first stage, we implement the MPEG-4 compression technique (Le Gall, 1991) to extract all I-frames as candidate keyframes. I-frames typically contain rich visual content and clarity, or represent scene transitions.

In the second stage, we apply a modified Isodata clustering algorithm to the visual features of these I-frames, selecting cluster centers as final keyframes. This algorithm adaptively determines the number of clusters, unlike KNN-based clustering (Wang et al., 2024b; Zhou et al., 2024), which requires a pre-defined number of clusters or external supervision. Our approach ensures generalizability and robustness for diverse video types.

After clustering, we utilize an off-the-shelf vision-language model (VLM) to generate frame captions for the selected keyframes. The overall process is denoted by:

$$C = prep(start, end)$$

where C is the set of frame captions between the given timestamps.

Scanning. Given a timestamp range $(start, end)$, the Viewer calls an external LLM with C to produce an overview caption. It may query additional frames via a captioning tool to refine its summary, mimicking how users drag to specific timestamps for clarification. The process is:

$$Cap = Scanner(prep(start, end), t)$$

where t is the task prompt.

Localizing. To identify the timestamp range matching a textual description, we propose a lightweight three-stage search process:

Stage 1: We feed an external LLM the set of keyframe captions to let it acquire an overall capture of the video content. At the same time, we instruct the LLM to output five most possible timestamps that depicts the texture query. The LLM is able to call frame caption tool to acquire extra captions at arbitrary timestamps, before it's confident enough to output the answer. Formally:

$$P = stage_1(prep(0, d), e, t)$$

where e are extra captions and t is the prompt. P gives the resulting list of five timestamps which depicts the language query the best.

Stage 2: We initialize the conversation and feed it the frame captions at these five timestamps, while instructing it to pick the one timestamp that best depicts the language query, out of the five candidates. Also, the LLM is able to call frame caption tool to acquire extra captions at arbitrary timestamps before it's confident enough to output the answer.

$$t_{best} = stage_2(P, e, t)$$

where P is the output of the previous step, and t is the task prompt.

Stage 3: Last, we initialize the conversation again, and instruct the external LLM to expand the single timestamp t_{best} from the last step to a

Method	Temporal Relational				Timepoint Indexed				Multifaceted Integrative				Average			
	mIoU	Pre.	Cov.	F1	mIoU	Pre.	Cov.	F1	mIoU	Pre.	Cov.	F1	mIoU	Pre.	Cov.	F1
VTG-GPT (Xu et al., 2024b)	0.17	0.26	0.32	0.29	0.15	0.22	0.30	0.26	0.16	0.23	0.31	0.24	0.16	0.27	0.31	0.27
Zheng et al. (2024a)	0.11	0.18	0.21	0.19	0.04	0.08	0.09	0.08	0.06	0.10	0.11	0.10	0.07	0.12	0.13	0.12
ReSimplifyIt (Ours)	**0.23**	**0.36**	**0.39**	**0.37**	**0.98**	**1.0**	**0.98**	**0.99**	**0.47**	**0.60**	**0.69**	**0.64**	**0.56**	**0.65**	**0.69**	**0.67**

(a) more results on stage 1 video output

Table 4: More results on Stage-1 evaluation on YouCookII-TVS dataset. 'Pre.' and 'Cov.' stands for 'precision' and 'coverage'.

timestamp range. The frame caption at t_{best} is provided, and the LLM is still able to acquire more captions by tool calling to confirm the boundary. Considering the difficulty in dealing with dynamic transitions of events, as explored by some previous work (Zheng et al., 2024b), we simply apply a hard value of 5 seconds on the output. Formally:

$$(t'_{start}, t'_{end}) = stage_3(t_{best}, e, t)$$
$$(t_{start}, t_{end}) = (t'_{start} - 5, t'_{end} + 5)$$

This three-stage process balances precision and efficiency by minimizing frame access while ensuring robust temporal grounding. For visual clarity of the Isodata clustering, refer to Algorithm 1 for details.

B Details on the YouCookII-TVS benchmark

We constructed a synthetic question-answering dataset named **YouCookII-TVS**, based on the YouCookII dataset, to support fine-grained temporal and semantic understanding of cooking videos.

B.1 Source Data Preparation

The original YouCookII dataset (Zhou et al., 2018) contains temporally annotated instructional videos. Each annotation includes a segment $[s_i, e_i]$ representing start and end times (in seconds), along with a natural language description of the cooking step.

To ensure video consistency and avoid duplications, we have verified that each video clip name is unique across the dataset source.

B.2 Annotation Grouping via Temporal Connectivity

We define a temporal connectivity criterion to group sequential cooking steps into higher-level event triplets. Given two segments $[s_1, e_1]$ and $[s_2, e_2]$, we define their overlap ratio as:

$$\text{overlap\_ratio} = \frac{|\min(e_1, e_2) - \max(s_1, s_2)|}{\max(e_1, e_2) - \min(s_1, s_2)}$$

Two segments are considered *connectable* if:

$$s_2 > s_1, \quad e_2 > e_1, \quad \text{and} \quad \text{overlap\_ratio} \leq \theta$$

We set $\theta = 0.1$ in our experiments. Using this rule, we perform a greedy grouping of annotations into connected segments, and extract all valid length-3 subsequences (triplets) from each group.

B.3 Triplet-Based Question Generation

Each triplet $T = \{t_1, t_2, t_3\}$ consists of three temporally ordered steps. For each T, we generate nine different types of question-answer pairs by instantiating predefined templates. The question types are categorized into three groups:

Temporal Relational Reasoning (TRR)

- trr1: What is the cooking step after of $[description]$?

- trr2: What is the cooking step before $[description]$?

- trr3: What is the cooking step between $[description]$ and $[description]$?

Timepoint Indexed Reasoning (TIR)

- tir1: What is the step between timestamps s_2 and e_2?

- tir2: What is the step between frame indices $f_{s_2} = s_2 \cdot r$ and $f_{e_2} = e_2 \cdot r$?

- tir3: What step appears within $f_d = (e_2 - s_2) \cdot r$ frames after s_2 seconds?

Here, r denotes the video frame rate.

Multifaceted Integrative Reasoning (MIR)

- mir1: What is the first step after timestamp s_2?

- mir2: What is the last step before timestamp e_2?

Method	ActivityNetQA	
	w/tvs	w/o
Video-ChatGPT (Maaz et al., 2024)	58.5	50.5
Video-LLaVA (Lin et al., 2023)	61.2	52.1
ChatUniVi (Jin et al., 2023)	63.2	52.0
LLaVA-NExT (Liu et al., 2024b)	67.8	62.5
VideoAgent (Wang et al., 2024a)	61.5	60.2
VideoTree (Wang et al., 2024b)	59.0	63.6

Method	YouCookII-TVS							
	TRR.		TIR.		MIR.		Avg.	
	w/tvs	w/o	w/tvs	w/o	w/tvs	w/o	w/tvs	w/o
Video-ChatGPT (Maaz et al., 2024)	31.7	30.5	45.2	26.5	39.8	29.73	38.9	28.91
Video-LLaVA (Lin et al., 2023)	39.3	37.4	46.8	28.2	43.5	31.6	43.2	32.4
ChatUniVi (Jin et al., 2023)	54.4	39.8	57.4	52.8	58.7	49.6	56.5	47.4
LLaVA-NExT (Liu et al., 2024b)	46.5	44.1	65.9	33.4	62.2	38.3	58.2	48.6
VideoAgent (Wang et al., 2024a)	30.2	48.7	46.1	55.2	38.9	57.8	38.4	53.9
VideoTree (Wang et al., 2024b)	59.3	64.0	59.2	72.2	52.8	72.0	57.1	69.4

Method	NExT-QA							
	Tem.		Cau.		Des.		Avg.	
	w/tvs	w/o	w/tvs	w/o	w/tvs	w/o	w/tvs	w/o
Video-ChatGPT (Maaz et al., 2024)	45.5	23.7	45.5	56.7	45.6	43.0	45.5	44.2
Video-LLaVA (Lin et al., 2023)	42.8	42.8	50.4	48.9	55.1	44.5	52.2	46.3
ChatUniVi (Jin et al., 2023) -	-	-	-	-	-	-	5	28
LLaVA-NExT (Liu et al., 2024b)	57.5	52.3	62.0	59.0	61.4	56.5	60.5	56.6
VideoAgent (Wang et al., 2024a)	49.2	47.3	43.6	41.9	51.7	51.1	47.0	45.0
VideoTree (Wang et al., 2024b)	62.4	59.9	57.7	66.1	66.8	72.3	60.0	65.2

Method	NExT-OE							
	Tem.		Des.		Cau.		Avg.	
	w/tvs	w/o	w/tvs	w/o	w/tvs	w/o	w/tvs	w/o
Video-ChatGPT (Maaz et al., 2024)	49.6	40.8	51.2	43.2	46.9	38.6	49.8	41.5
Video-LLaVA (Lin et al., 2023)	37.5	37.5	53.2	46.7	47.6	43.4	48.0	43.3
ChatUniVi (Jin et al., 2023)	30.8	30.8	36.9	23.1	34.0	26.4	34.5	25.9
LLaVA-NExT (Liu et al., 2024b)	41.4	39.11	59.7	46.0	50.1	44.6	52.3	43.7
VideoAgent (Wang et al., 2024a)	44.1	53.4	48.8	46.0	50.4	52.6	47.8	49.6
VideoTree (Wang et al., 2024b)	52.1	61.1	58.0	60.7	64.4	65.6	57.7	61.9

Table 5: Evaluation results of TVS-guided inference on four benchmark: ActivityNetQA, YouCookII-TVS, NExT-QA, and NExT-OE, with the sub-categories presented in each benchmark.

Figure 3: More examples of the TVS task.

- mir3: Within s_1 and e_3, what is (are) the cooking step(s) apart from $[description]$ and $[description]$?

Template instantiation is performed by replacing placeholders with actual sentences and timestamps (framestamps) from the triplet.

B.4 Data Structuring and Metadata

Each generated data point is stored with the following fields:

- vid_name, vid_fname: Video ID and filename.

- vid_duration, vid_frame_rate: Metadata from video parsing.

- type: One of the nine QA types.

- question: Instantiated natural language query.

- answer: Corresponding ground-truth step description, serving as the ground-truth label for the VideoQA task.

- gt_timestamp: Temporal segment(s) serving as the ground-truth label for our TVS task on video trimming.

- gt_rewritten_query: Natural language query serving as the ground-truth label for our TVS task on query re-writing.

We generated a total of $N = 2754$ QA samples, covering all types evenly.

Algorithm 1 *ISODATA Clustering*

Require: Data matrix $\mathbf{X} \in \mathbb{R}^{n \times d}$, Candidate frames $\mathbf{F} \in \mathbb{R}^{n \times c \times w \times h}$, frame feature extractor $Enc()$, initial cluster count k, max iterations T, minimum intra-cluster similarity θ_{split}, maximum inter-cluster similarity θ_{merge}, max clusters k_{max}, min clusters k_{min}, max center shift δ_{max}, min elements per cluster n_{min}

Ensure: Cluster assignments $\mathbf{C}$, Final cluster centers $\mathbf{M}$

  1: $\mathbf{X} \leftarrow \text{Enc}(\mathbf{F})$

  2: $\mathbf{X}_{norm} \leftarrow \text{normalize}(\mathbf{X}, \ell_2)$

  3: $\mathbf{M} \leftarrow \text{random\_sample}(\mathbf{X}, k)$

  4: $t \leftarrow 0$

  5: **repeat**

  6:     Compute cosine similarity matrix $\mathbf{S} = \mathbf{X}_{norm}\mathbf{M}_{norm}^T$

  7:     $\mathbf{C} \leftarrow \arg\max(\mathbf{S}, \text{axis} = 1)$ $\triangleright$ Assign points to nearest clusters

  8:     **for** each cluster i **do**

  9:         Update center: $\mathbf{m}_i \leftarrow \text{mean}(\mathbf{X}[\mathbf{C} == i])$

10:     **end for**

11:     **if** any cluster size $< n_{min}$ **then**

12:         Merge smallest cluster with nearest neighbor $\triangleright$ Minimum elements enforcement

13:     **end if**

14:     **for** each cluster i **do**

15:         **if** intra-cluster similarity$(\mathbf{X}[\mathbf{C} == i], \mathbf{m}_i) < \theta_{split}$ **and** $k < k_{max}$ **then**

16:            Split cluster i into two new clusters $\triangleright$ Splitting phase

17:            $k \leftarrow k + 1$

18:         **end if**

19:     **end for**

20:     **for** all cluster pairs (i, j) **do**

21:         **if** inter-cluster similarity$(\mathbf{m}_i, \mathbf{m}_j) > \theta_{merge}$ **and** $k > k_{min}$ **then**

22:            Merge clusters i and j $\triangleright$ Merging phase

23:            $k \leftarrow k - 1$

24:         **end if**

25:     **end for**

26:     Compute center shifts $\Delta\mathbf{M} = \|\mathbf{M}_{new} - \mathbf{M}_{old}\|$

27:     $t \leftarrow t + 1$

28: **until** $t \geq T$ **or** $\max(\Delta\mathbf{M}) < \delta_{max}$

29: **return** $\mathbf{C}, \mathbf{M}$

Algorithm 2 *ReSimplifyIt*

Require: Video v, question q

Ensure: Screened video V', screened question q'

1: $V\_copy, q\_copy \leftarrow V, q$

2: $success\_history, failure\_history \leftarrow$ SuccessHistory(), FailureHistory()

3: **while** true **do**

4:      $launcher, validator, viewer \leftarrow$ Launcher(), Validator(), Viewer()

5:      $decision, q', trimming\_instruction \leftarrow$ launcher($q\_copy, success\_history, failure\_history$)

6:      **if** $decision == "proceed"$ **then**

7:          $judgement, request, result, reason \leftarrow$ validator($q\_copy, q', trimming\_instruction$)

8:          **while** $judgement == "view"$ **do**

9:              $response \leftarrow$ viewer($V', request$)

10:             validator.read_response($response$)

11:          **end while**

12:          **if** $judgement == "succeeded"$ **then**

13:             $V' \leftarrow result$

14:             $success\_history.append([q\_copy, q', trimming\_instruction])$

15:             $failure\_history.empty()$

16:             $V\_copy, q\_copy \leftarrow V', q'$

17:          **else**

18:             $failure\_history.append([q\_copy, q', trimming\_instruction])$

19:          **end if**

20:      **else**

21:          **return** V_copy, q_copy

22:      **end if**

23: **end while**

B.5 Dataset Splitting

To support evaluation, we partition the dataset into training, validation, and test splits. For each question type, we allocated:

$$\text{train: } 1926, \quad \text{val: } 270, \quad \text{test: } 558$$

This roughly follows 7:1:2.

More details about the dataset statistics can be found in Figure 4.

C Ablation Study

C.1 Experiment Settings

We first ablate the modular design—responsible for facilitating structured reasoning—by proposing the **ReSimplifyIt-simple** variant. In this setting, all underlying interfaces for handling textual and visual inputs, such as ISODATA-clustering (Algorithm 1) and frame-caption querying, are preserved. However, the entire reasoning pipeline is collapsed into a single, universal agent. Specifically, we initialize an external agentic LLM with task descriptions and operational instructions, and expose the aforementioned interfaces either through conversational context or tool invocation. This unified agent is then responsible for all reasoning procedures—functionally covering the roles of the Launcher, Validator, and Viewer modules, as well as memory tracking—in the original ReSimplifyIt framework, and ultimately produces the final output.

Then, we further ablate the video access completely, i.e. No access to the video content is provided throughout the *entire* reasoning process of the external agent. As the multi-turn interaction (feedback) are all essentially from the reference to video information to refine text input, disabling video access also renders multi-turn interactions unnecessary. To reflect this, we introduce the **ReSimplifyIt-blind** variant, in which a tool-calling LLM generates a rewritten query and a fixed sequence of tool invocations within a single-turn conversation. This sequence is subsequently executed by a separate executor module to produce the video output.

Refer to Figure 5 for an illustrations of these frameworks.

C.2 Evaluation Results

Evaluation results are presented in Table 6. Although the removal of modular design yields comparable video outputs, the modular architecture still demonstrates advantages—particularly on the *Multifaceted Integrative* subset, which involves more complex multi-hop reasoning, demonstrating the effectiveness of modular design and structured reasoning in more complex and intricate reasoning scenario. In comparison, the ablation of video access brings notable performance drop, underscoring the critical role of cooperative, feedback-driven multi-turn interaction. This aligns with the interdependency of the vision and text modality, which lies at the core of our TVS task formulation, reflecting the essence of the task initiative.

C.3 Full list of tools for ReSimplifyIt-blind framework

```
1. get_duration():
   Return the duration of the video as a
    floating point value.

2. get_resolution():
   Return the resolution of the video, as a
    tuple.

3. get_total_frame_num():
   Return total number of the frames of the
    video, as an integer.

4. grounding_select(obj_name,
    concerned_indices_input):
   Return, in the form of a list of integers,
    the indices of all frames
   containing the object given by obj_name,
    after taking the intersection
   of indices provided by
    concerned_indices_input. If None is passed,
   selects all frames.

5. indices_list_intersect(list1, list2):
   Return the intersection of two lists of
    indices.

6. indices_list_union(list1, list2):
   Return the union of two lists of indices.

7. indices_concat_and_fill(list1, list2):
   Return the sorted union of list1 and list2,
    then fill in missing
   values to make the sequence continuous.

8. indices_concat(list1, list2):
   Return the concatenation of the two lists.

9. timestamp_to_single_index(timestamp):
   Return the frame index corresponding to the
    given timestamp (in seconds).

10. single_timestamp_to_index_range(timestamp):
    Return indices of 60 consecutive frames
     centered at the timestamp.

11. range_timestamp_to_index_range(start, end):
    Return all frame indices between the start
     and end timestamps.
```

Figure 4: YouCookII-TVS statistics.

Method	Temporal Relational		Timepoint Indexed		Multifaceted Integrative		Average	
	mIoU	F1	mIoU	F1	mIoU	F1	mIoU	F1
ReSimplifyIt (Ours)	0.23	**0.37**	**0.98**	**0.99**	**0.47**	**0.64**	**0.56**	**0.67**
ReSimplifyIt-simple (Ours)	**0.24**	**0.37**	**0.98**	**0.99**	0.42	0.57	0.55	0.64
ReSimplifyIt-blind (Ours)	0.12	0.20	0.97	**0.99**	0.38	0.55	0.49	0.58

(a) Results on video output.

Method	Temporal Relational	Timepoint Indexed	Multifaceted Integrative	Average
ReSimplifyIt (Ours)	66.8	78.5	72.8	**72.7**
ReSimplifyIt-simple (Ours)	66.2	81.9	68.1	72.0
ReSimplifyIt-blind (Ours)	65.0	80.5	70.7	72.1

(b) Results on query rewriting.

Table 6: Ablation studies on our ReSimplifyIt framework. ReSimplifyIt-simple and ReSimplifyIt-blind represent ablations on modular design and feedback from video access, respectively.

D Implementation details of ReSimplifyIt framework

The Launcher module is based on single-turn conversation with GPT-4o. The Validator and Viewer module, including the scanner and localizer, are primarily based on multi-turn conversation with GPT-4o. For ISODATA frame clustering, we use CLIP (Radford et al., 2021) to obtain the visual features of the I-frames. We adopt the off-the-shelf LLaVA-1.5 (Liu et al., 2024a) for frame captioning.

E Prompts

E.1 Prompt used for evaluation of query rewriting of TVS

```
You are a helpful assistant to evaluate the
    quality of an output of a special type of
    sentence compression, which sentence is in
    the form of a question.

You will be given an output of such compression
    process and the ground truth answer, and the
    original input question sentence before the
    compression. Please evaluate the output
    based on the following three criterias:

1. Relevance: to minimize unwanted
information
- in this criteria, a candidate output gets
full mark if it doesn't contain any
information (phrases, concepts, etc.) out of
    the scope of the original input question.
- the more information it contains that is
not mentioned in the original input question
, the more marks are deducted.

2. Simplicity: to minimize tangential
information
- in this criteria, a candidate output gets
full mark if doesn't contain any information
```

Figure 5: Workflow of *ReSimplifyIt-simple* (left) and *ReSimplifyIt-blind* (right).

```
        (phrases, concepts, etc.) that is included
    in the original input question but not
    included in the ground truth compressed
    question. In other words, whether the
    question sentence is fully compressed.
    - the more information it contains that is
    included in the original input question but
    not included in the ground truth question,
    the more marks will be deducted.

    3. Completeness: to minimize over-
    compression
    - in this criteria, a candidate output gets
    full mark if it contains all information
    included in the ground truth compressed
    question.
    - the more information contained in the
    ground truth output question is found
    missing in the output compressed question,
    the more marks will be deducted.

    Here is the original input question: [
    original_question_flag], and
    here is the ground truth compressed question:
      [ground_truth_screened_question_flag], and
    here is the output compressed question: [
    output_screened_question_flag].

    Please rate the output compressed question
    on a scale from 0 to 100, with 0 being the
    worst and 100 being the best (full mark).
    Now, rate the quality of the output
    compressed question based on all the
    information above.
    Return your answer in this json format: {"
    score": [your score, from 0 to 100]}.
```

E.2 Prompts used for ReSimplifyIt framework

Prompt for the Launcher module:

```
Given a video question answering case, i.e. a
    video, a question, and an answer, sometimes
    it is possible to cut the video by only
    keeping a sub-clip or several sub-clips (
    concatenate if so) to be the video output
    and simultaneously modify the text question
    to be the paired text output while keeping
    the answer consistent and unchanged, so that
     the answer is still completely compatible
    to the modified question and the obtained
    video clip.
We define this action as "screening". By doing
    screening, the video becomes shorter, and
    therefore introduces lower cost to the
    downstream video question answering model.
    When modifying the question, note that the
    downstream video question answering model
    will only be seeing the sub-clip and think
    that the shown sub-clip is the whole video,
    so make sure the modified question is
    perfectly paired and aligned with and
    adapted to the modification.

[In context examples flag 1]

Sometimes, such screening can be repeatedly
    applied sequentially by several rounds,
    where the input in each round is the output
    video clip and the output modified question
    of its preceeding round. As mentioned, the
    answer consistency should be always ensured
    throughout the whole process, and is always
    completely compatible to the resulting video
     clip and modified question of every round.
    If succeeded, each round would make the
    video shorter and making the situation
    closer to the optimal case.

[In context examples flag 2]

Your duty is to help complete the screening. Due
     to some limit, you are only provided with
    the text question but not the video input.
Your task is to initiate an immediate plan for
    the screening operation, including a natural
     language instruction telling which video
```

clip(s) to keep (similar to examples above)
and the paired modified text question. If
you think the screening may compose more
than one round, you only need to perform one
round next.
As you cannot see the actual video, your plan
might fail, if the downstream video editting
agent taking and executing your instruction
on video clipping finds it infeasible.
Therefore, your plan is refered to as a '
trial'.
In your current situation, some rounds or trials
of the screening process might have already
been conducted, and privided as following
information:
1, the 'failure history': it is about the
history of failed previous trials of the
screening of your current round. Here is the
failure history for you (an empty indicates
that you are making the first trial of this
round): [failure_history_flag];
2, the 'success history': it is about the
history of the one success trial of all
previous round. Here is the failure history
for you (an empty indicates that you are at
the first round): [success_history_flag].

Now, here is the original question of this round
for video question answering: "[
quesion_flag]"
Again, please tell your plan which describes
what part of the video should be kept. Also,
give the modified question under the
assumption that the video is processed
smoothly according to your plan.

If you feel that there is no room to make such
screening (e.g. when the question is being
general like "what is this video about") so
you feel that you shouldn't make any plan,
you should decide to terminate the process.

Hints:
1. Before processing, remember to take a look in
the 'failure history' and 'success history'
information;
2. If you find that the success history contains
a case whose modified_question and the
description both significantly overlap with
the ones you are about to make, then you
should avoid making the same plan again. In
this case, you should switch to a clear
reasonable sensible alternative plan, or
make a decision to terminate the
modification process if you can't
confidently find one;
3. If you find that the failure history contains
a case whose modified_question and the
description both significantly overlap with
the ones you are about to make, or that any
of the "reason" in the failure history
records is going to make your attempt fail,
then you should avoid making the same plan
again. In this case, you should switch to a
clear reasonable sensible alternative plan,
or make a decision to terminate the
modification process if you can't
confidently find one.

Return your plan in this json format (keep in
mind here, that your response should be in
json format):
{"decision": [your decision, either "process" or
"terminate"], "modified_question": [the
modified question, or "N/A" if your previous
decision is "terminate"], "description": [
Description of what part of the video should
be kept as wanted sub-clip. The description
will be passed to downstream processer to
validate. Return "N/A" if your decision is "
terminate".]}

"""

Prompt for the Validator module:

You will be given a natural language instruction
telling you to trim a video, which
instruction itself might be infeasible. The
reason it might be infeasible is because the
agent who gave the instruction had no
access to the actual video content, so it
might be infeasible if take the actual video
contenet into consideration.

Therefore, I need you to be a helpful assistant
to confirm if the trimming plan is feasible.
Specifically, your job is to act as a validator
to validate whether it is feasible (whether
the video content really supports the plan).
If it is feasible, you will need to implement
the plan and return the resulting sub-clip
of the plan in the form of a two-layer list.
[In context example flag 1]
If it is not feasible, you will need to tell the
reason.

Here are some examples and explanations for
infeasible trimming instructions:

[start of examples]

[In context examples flag 2]

[end of examples]

You can invoke a viewer multiple times to
acquire the video content (partial content
each time), which viewer is a downstream
module prepared to assist you.

Note that the viewer is capable to deal with two
type of questions:

1. snippet rough scanning, e.g. "what is the
video about from xxx second to xxx second"?
2. localizing, e.g. "which segment contains xxx
(event/object)?"

Therefore, if [your decision] is "view", [your
message] should follow one of the above two
example templates.

Here is the trimming instruction you need to
validate: [plan_flag].
The video length is [video_length_flag] seconds,
and its frame rate is [frame_rate_flag] fps
.

```
Now, in each following turn of this conversation,
    you need to give your response in this json
    format: {"decision": [your decision], "
    message": [your message]}. This works as
    follows:
[your decision]: either "succeeded", "failed",
    or "view". "succeeded" means that the plan
    is successfully implemented, "failed" means
    that it is not, and by "view" you invoke the
    viewer to provide partial video content for
    you. If you choose "view", the viewer will
    take your message and return as you
    requested, and the conversation will
    continue. If you choose "succeeded" or "
    failed", it will be your final decision and
    the conversation will end.
[your message]: if you choose "succeeded" as
    your decision, then it should be the two-
    layer list as mentioned before, as the video
    edit result of the plan. If you choose "
    failed", this should be a brief reason on
    the failure (e.g. requested timestamp
    exceeds video length, video doesnt have the
    object/event needed, etc.). If you choose "
    view", this should be the question to ask
    the viewer about the video content.

Hint: it is not always necessary to invoke the
    viewer. [In context example flags 3]

For your ease of decision, here are some initial
    frame captions and their timestamps for you
    (in the form of key value pairs, where the
    value is the frame caption and the key is
    its corresponding timestamp, in the unit of
    second): [initial_captions_flag].
[sys_usr_split]

Now let's start!
```

Prompt for Viewer module:

```
You are a helpful and smart assistant that can
    respond to an upstream request a video by
    invoking tools. The length of this video is
    [video_length_flag].

Here is the content of the request: [
    validator_request_flag].

Here are the tools you can access (you might
    access them multiple times if you want):

1. scan(start, end): Return the overall caption
    of the video snippet (clip) between start
    and end timestamp, which are the parameters
    with the unit of second.
2. localize(query): Return the video location,
    in the form of a timestamp range given by
    the start and end timestamp, which contains
    the visual content of the query (which query
    might be an object, event, etc.)
3. get_image_cap(timestamp): parameter "
    timestamp" is an integer in the unit of
    second. Return the caption of the video
    frame at the given timestamp (regard the
    frame as an image).
```

```
Now, in each turn of the following conversation,
    your response should be in the following
    json format: {"decision": [your decision], "
    message": [your message]}. This works as
    follows:
[your decision]: either "tool" (if you wish to
    call tool in this round) or "respond" (if
    you feel that you are able to respond to the
    upstream module's request by comprehending
    your current knowledge acquired about the
    video.).
[your message]: if your decision is "tool", then
    this should only contain tool calling
    following given format, e.g. 'get_image_cap
    (10)', 'scan(21, 35)', 'localize("kicking
    the ball")'. If your decision is "respond",
    then this should be your response to the
    upstream request.

[sys_usr_split]

Now let's start!
```

E.3 Prompt used for ReSimplifyIt-simple framework

```
You are a assistant for the video question
    answering process, in which a candidate is
    presented with a video and a question for
    them to answer.\
Your objective is to help the candidate so that
    they will be able to give the answer with
    watching the shortest posible sub-clip(s) of
    the video. \
Your task is to cut the video to acquire this
    sub-clip(s) and also to modify the question,
    so that the candidate directly answering
    your modified question with presented only
    this sub-clip(s) of the video would be
    equivalent to answering the original
    question with presented the original whole
    uncut video. \

[In context examples flag 1]

You will need to cut the video in the form of
    providing me the timestamps, which is a list
    of [start, end] unit clips in the unit of
    second. \
A tool (python function) will be helping you to
    get the frame caption of at a certain
    timestamp (in the unit of second). Whenever
    you need to call this tool, send a message
    in this json format: {"decision": "tool", "
    parameter": [timestamp you need]}. [In
    context example flag 2] \
Whenever you think you are confident enough to
    provide the timestamp, return {"decision": "
    end", "timestamps": [your result timestamps
    ], "revised_question": [your revised
    question]}. [In context example flag 3].

Before we formally begin, here is a set of
    original captions with their timestamps
    provided for you to have an overall rough
    understanding of the video: [
    initial_captions_flag].
```

```
Also, the frame rate of this video is [
    frame_rate_flag] frames per second, and the
    total duration is [duration_flag].

[sys_usr_split]Now let's begin! and the original
    question is "[original_question_flag]".
```

E.4 Prompt used for ReSimplifyIt-blind framework

```
You are a assistant for the video question
    answering process, in which a candidate is
    presented with a video and a question for
    them to answer.\
Your objective is to help the candidate so
    thattheywill be able to give the answer with
     watching the shortest posible sub-clip(s)
    of the video. \
Your task is to cut the video to acquire this
    sub-clip(s) and also to modify the question,
     so that the candidate directly answering
    your modified question with presented only
    this sub-clip(s) of the video would be
    equivalent to answering the original
    question with presented the original whole
    uncut video. \

[In context examples flag 1]

You will be provided with a list of tools to
    process the video, and the original question
     to be answered by the candidate based on
    which to select the frames. Here is the list
     of tools you have access to, with the
    description (content in the brackets are the
    arguments needed):
[1]: get_duration(): return the duration of the
    video as a floating point value.
[2]: get_resolution(): return the resolution of
    the video, as a tuple.
[3]: get_total_frame_num(): return total number
    of the frames of the video, as an integer.
[4]: grounding_select(obj_name,
    concerned_indices_input): return, in the
    form of a list of integers, the indices of
    all frames containing the object given by
    obj_name, after taking the intersection of
    indices provided by the argument '
    concerned_indices_input'. '
    concerned_indices_input' is also a list of
    indices, and will be set to indices of all
    frames in the video if 'None' is passed.
[5]: indices_list_intersect(frame_indices_list_1,
     frame_indices_list_2): return, in the form
    of a list of integers, the intersection of
    the two arguments as list. Both argument '
    frame_indices_list_1' and '
    frame_indices_list_2' are a list of indices.
[6]: indices_list_union(frame_indices_list_1,
    frame_indices_list_2): return, in the form
    of a list of integers, the union of the two
    arguments as list. Both argument '
    frame_indices_list_1' and '
    frame_indices_list_2' are a list of indices.
[7]: indices_concat_and_fill(
    frame_indices_list_1, frame_indices_list_2):
     first take the sorted union of the two
    lists given by the arguments, and then fill
    in all the missing values so that every two
```

```
adjacent element only differ by 1. Both
    argument 'frame_indices_list_1' and '
    frame_indices_list_2' are a list of indices.
[8]: indices_concat(frame_indices_list_1,
    frame_indices_list_2): return, in the form
    of a list, the concatenation of the two
    lists provided by the arguments.
[9]: timestamp_to_single_index(timestamp):
    return a list with a single integer, which
    integer is the index of the frame at the
    given timestamp. The argument timestamp is a
     floating point value, whose unit is second.
[10]: single_timestamp_to_index_range(timestamp):
     return, in the form of a list, the indices
    of 60 consecutive frames, the midpoint of
    which is at the given timestamp. The
    argument timestamp is a floating point value
    , whose unit is second.
[11]: range_timestamp_to_index_range(start, end):
     return, in the form of a list, the indices
    of all frames which are between the two
    timestamps which are provided by the
    arguments. The argument start and end are
    both floating point values, whose unit are
    both second.

Above are all the tools to have access to.
    Please note that selecting frames out of all
     the frames of the original video is being
    cut and clipped, therefore you will also
    need to modify the aforementioned prompt, to
     make it align well with the reduced video
    frames.
[sys_usr_split]
Now the original question is: [question_flag].
    Having access to the information of all the
    tools mentioned above, provide me the python
     code which could achieve the selection of
    frames. You may define variables to store
    intermediate result, and determine the value
     of some arguments when necessary, but you
    should not require the downstream task
    operator to replace any of your assumption
    on arguments, as no more information but the
     original video is provided to the
    downstream task. Please use the variable
    name 'final_frames' to store your final list
     of frame index. Please only provide the
    code and revised question in this format: {"
    Code:[your whole paragraph of code] Revised
    question:[your revised prompt]"}, where [
    your whole paragraph of code] should be an
    empty string if you think no tools need to
    be called and the whole original video
    should be passed to the downstream task.
```

F More on Related Work

Video-LLMs for VideoQA   Video-LLMs have spurred a wave of models aimed at enhancing video understanding by leveraging the language capabilities of large language models (LLMs) (Lin et al., 2023; Ma et al., 2024; Li et al., 2024a, 2023b; Liu et al., 2024b; Xu et al., 2024a). Some approaches (Chen et al., 2023; Li et al., 2024b, 2023a) utilize dedicated video encoders such as video

transformers (Bertasius et al., 2021) or convolution networks. However, these designs often demand large-scale annotated video-text data and significant computational resources. To address this, alternative methods adapt pre-trained image-domain MLLMs to video inputs (Liu et al., 2024c; Maaz et al., 2024), offering improved practicality. Nonetheless, the sparsity and query-invariant nature of video encoding in existing models limits their ability to capture fine-grained spatial-temporal details effectively, especially under token budget constraints. This work addresses such inefficiencies by introducing a query-adaptive processing mechanism inspired by the principle of information screening, aiming to reconcile the trade-off between token efficiency and representational fidelity.

LLM-assisted Agentic Reasoning for VideoQA Another line of research for video question answering lies in building pure-text LLM assisted frameworks or multi-agent systems for VideoQA (Wang et al., 2024b; Shang et al., 2024; Wang et al., 2024a). Compared to Video-LLMs, which represents end-to-end single-pass approaches, these methods adopt traditional or LLM-based methods to proactively sample relevant video frames. VideoAgent (Wang et al., 2024a) and TravLER (Shang et al., 2024) utilized LLM's planning ability to conduct iterative keyframe searching, while VideoTree (Wang et al., 2024b) presented query-adaptive hierarchical tree-based keyframe selection.

Temporal Sentence Grounding for Videos Temporal sentence grounding (TSG) aims to localize the video segment best matching a language query. Early sliding-window methods (e.g., TALL (Gao et al., 2017), MCN (Hendricks et al., 2017)) were costly, while later proposal-based (Xu et al., 2019; Chen and Jiang, 2019) and proposal-free methods (Yuan et al., 2019; Zhang et al., 2020) improved efficiency via query-guided proposals or direct boundary prediction. All these methods take a video and a query as input and predict a matching temporal span. In contrast, our proposed TVS generalizes beyond TSG by supporting inter-frame reasoning and joint adaptation over both video and query, rather than retrieving only frames directly mentioned in the query.

Grounded videoQA Another seemly-similar line of research lies in integrating grounding techniques into VideoQA pipelines (Xiao et al., 2024; Chen et al., 2024a). Grounded VideoQA seeks to enhance model faithfulness by explicitly linking a model's textual output to "visual cues" or "evidence" within the video. This approach is effective at mitigating hallucinations for descriptive queries by enforcing *perceptual* alignment. descriptive tasks, the approach suffers from a fundamental conceptual incongruity with the nature of complex video reasoning. The semantics of a query and its corresponding video segment are often holistically entangled; for example, a high-level question about intent, causality, procedure, or even a simple temporal relational reasoning does not map to an atomic piece of visual evidence but is inferred from a continuous temporal context. The attempt to impose a discrete justification framework onto this intertwined semantic space leads to an inherently brittle and ill-defined notion of a "visual cue".

TVS naturally sidesteps this ambiguity by fundamentally reframing the objective, turning from *"what to answer"* to *"what to ask"*. More fundamentally, TVS introduces a more principled paradigm that respects this intrinsic entanglement. Rather than seeking to atomize evidence for a given answer, TVS reformulates the task itself through a priori contextual simplification. It isolates the minimal, self-contained $(video, query)$ sub-problem through an **endomorphic transformation** that keeps with the original task space unchanged and preserves the necessary holistic context for reasoning. This approach is not merely a circumvention of the definitional challenge; it establishes a more fundamentally sound and cognitively aligned task. By first reducing the problem space to a manageable and semantically coherent unit—mirroring the human strategy of simplifying a problem before attempting to solve it—TVS offers a more robust foundation for complex video-language understanding.