Inverse Game Theory for Stackelberg Games: the Blessing of Bounded Rationality

Abstract

Optimizing strategic decisions (a.k.a. computing equilibrium) is key to the success of many non-cooperative multi-agent applications. However, in many real-world situations, we may face the exact opposite of this game-theoretic problem — instead of prescribing equilibrium of a given game, we may directly observe the agents' equilibrium behaviors but want to infer the underlying parameters of an unknown game. This research question, also known as *inverse game theory*, has been studied in multiple recent works in the context of Stackelberg games. Unfortunately, existing works exhibit quite negative results, showing statistical hardness [27, 37] and computational hardness [24, 25, 26], assuming follower's perfectly rational behaviors. Our work relax such behavior assumption to *bounded* rationality, a more realistic yet more difficult setting as typically perceived. Perhaps surprisingly, we show that such complication in follower behaviors actually leads to provably more efficient learning of the follower utility parameters in general Stackelberg games. Systematic empirical experiments on synthesized games confirm our theoretical results and further suggest its robustness beyond the strict quantal response model.

1 Introduction

One primary objective of game theory is to predict the behaviors of agents through equilibrium concepts in a given game. In practice, however, we may observe some equilibrium behaviors of agents, but the game itself turns out to be unknown. For example, an online shopping platform can observe the shoppers' purchase decisions on different sale prices, but the platform has limited knowledge of the exact utilities of the shoppers. Similarly, while the policymaker could observe the market reactions to its policy announcement, the exact motives behind traders' reactions are usually unclear. In various security domains, the defender may want to understand the intentions or incentives of the attackers from their responses to different defense strategies so as to improve her future defense strategy. As such, recovering the underlying game parameters would not only lead us to better strategic decisions but also improve our explications of the motives and rationale in the dark.

These potentials and prospects motivate a class of research problems known as the inverse game theory [26]: *given the agents' equilibrium behaviors, what are possible utilities that induce these behaviors?* In this paper, we specifically target the sequential game setting from the perspective of the first-moving agent (e.g., Internet platform, policymaker, or defender) whose different strategies (e.g., price, regulation, or defense scheme) would induce different equilibrium behaviors of the following agent (e.g., Internet users, traders or attacker). The studies of such game settings have seen broad impacts and extensive applications ranging from the principal-agent problems in contract design [21, 19], the AI Economist [42] to the security games modeled for social good [16]. We formalize our problem under the standard Stackelberg game, where a leader has the commitment power of a randomized strategy, and a follower accordingly decides his response. It is known that

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

the optimal commitment of the leader can be efficiently computed in a single linear program, given full knowledge of the game [14]. However, the inverse learning problem to determine the underlying game from the follower's responses is more challenging: Letchford et al. [27], Peng et al. [37] show that learning optimal leader strategy from the follower's best responses requires number of samples that is a high-degree polynomial in the game size and may be exponential in the worst cases. This significantly limits the practicality of these algorithms, as the leader usually cannot afford the time or cost to gather feedback from so many interactions.

More concerning is the inconvenient reality that we can hardly expect the agents' optimal equilibrium responses assumed in existing work. In fact, these shoppers, traders or attackers themselves hardly know their exact utilities and are naturally unable to determine the expected-utility maximizing strategy. Extensive behavioral economics and psychology studies [23, 5, 32, 11, 10] have pinpointed the cognitive limitations that make human decisions prone to the noisy perception of their utilities. Among various models for quantifying irrational agent behaviors, one of the most popular ones is perhaps the *quantal response* (QR) model [32], which adopts the well-known logit choice model to capture agents' probabilistic selection of actions. This will also be the bounded rationality model of our focus in this paper. While our quantitative results do rely on the form of this model, we believe the insight revealed from our model generalizes to most problems of learning from boundedly rational agent behaviors.

The Blessing of Bounded Rationality. The key insight revealed from this paper is that the extra layer of behavioral complexity due to bounded rationality, while complicating the modeling and computation, provides more informative source for us to learn the underlying utilities of agents. To understand the intuitions and motivations behind our results, consider a case where the follower has a dominated action j_1 as shown in Table 1, where the leader's and follower's utility of action profile (i, j) is specified by $u_{i,j}, v_{i,j}$ respectively. Conventionally, such instance is treated as a degenerated instance, because the leader could ignore such action j_1 that a perfectly rational follower would never play. Then, the optimal leader strategy is clearly to always play the action i_2. However, when facing a

$u_{i,j}, v_{i,j}$	j_1	j_2
i_1	$100, 0.9$	$0.9, 1$
i_2	$-99, 0.9$	$1.1, 1$

Table 1: An example of dangerously "degenerated" Stackelberg game.

boundedly rational follower, it becomes possible to observe the response j_1 and estimate the utilities regarding this dominated action. For example, if the follower plays his action j_1 and j_2 at almost the same frequency, the follower's expected utility on the two actions should be close. Although such dominated action has no effect on the leader's optimal strategy against a perfectly rational follower, it could be a potentially damaging (or beneficial) action that leader want to avoid (or encourage) a bounded rational follower to play. That is, in the game instance above, if a somewhat irrational follower plays action j_1, it would be dangerous for the leader to play action i_2 yet be rewarding to play action i_1; hence, a more robust leader strategy should randomize by assigning some probability to play action i_1. We remark that in general, even without such extreme case of dominated actions, the extra payoff information are now available on how much worse (or better) using the empirical frequency of actions from the boundedly rational responses, which has been overlooked due to the assumption of perfectly rational follower.

Our Results. We present a set of tight analysis on the number of strategies and sample complexity sufficient and necessary to learn the follower's utility, for both the situations that the leader can observe the follower's full mixed strategies or only the follower's sampled pure strategies. In the former situation of observing follower's mixed strategies, our algorithm can recover the follower utility parameters using m follower mixed strategy responses in any general Stackelberg game where m is the number of leader actions. Surprisingly, the required number of queries is independent of follower actions! This is due to the fact that the randomness introduced by bounded rationality carries much more information about follower payoffs, compared to the perfect best response. In the later (more realistic) situation of only observing follower's sampled pure strategy, our algorithm learns the follower utility parameters within precision ϵ with probability at least δ using $\Theta(\frac{m \log(mn/\delta)}{\rho \epsilon^2})$ carefully chosen queries, where n is the number of follower actions and ρ depends on agent's bounded rationality level and is of order $\Theta(1/n)$ for typical boundedly rational agents. Interestingly, the additional challenge of only observing sampled actions only deteriorates the sample complexity

by a factor of $\log(mn)/\rho$.[1] These sample completexity results should be compared with that of [37, 27], which study similar learning questions but from perfectly rational follower responses. The $m\log(mn)/\rho$ order in our sample complexity is in sharp contrast to their complexity with *exponential* dependence in m or n in the worst case. Our experimental results empirically confirm the tightness of our sample complexity analysis.

At the conceptual level, our work illustrates that noises due to bounded rational behaviors could be leveraged as additional information sources to learn the follower utility. This intuition also drives the design of our analytic tools to explain how efficient and effective learning of the follower's utility is possible in real situations, in complementing the previous negative results developed under the idealized perfect rational behavior models [27, 37].

2 Related Work

Learning in Stackelberg Game. The learning problem in sequential game has been studied in several different setups. Marecki et al. [30], Balcan et al. [7] consider the online learning problem in Stackelberg security game with adversarially chosen follower types. Bai et al. [6] consider a bandit learning setting that one could query any entry of the followers' utility under noise, and use the estimation of utility is to approximate the optimal leader strategy; however, this learning process assumes *centralization*, i.e., the learner can control both leader's and follower's actions. More similar to ours is the strategic learning setup in Stackelberg games studied by [27, 37, 9], where the leader adaptively chooses her strategies based on the observation of the follower's best response and eventually recovers the follower's utility up to some precision level.

Bounded Rationality. McKelvey and Palfrey [32] introduced the quantal response equilibrium (QRE) by adopting the logit choice model [15, 31]. QRE serves as a strict generalization of Nash equilibrum (NE) — when the agents become perfectly rational, QRE converges to the NE. The modeling success of QR model attributes to the nice mathematical and statistical properties of the logit function that can capture a variety of boundedly rational behaviors under different parameter λ. QRE is widely adopted especially in Stackelberg (security) games [41, 35, 16, 20, 12] and zero-sum games [29] and notably has been deployed in various real world application [2, 17]. Moreover, the model structure of QR has been also used in various other contexts, such as the softmax activation in neural network [18], multinomial logistic regression [8] and the multiplicative weight update algorithm for no-regret learning [3].

As an initial attempt to our general learning problem, we also adopt the QR model to capture our agent's bounded rational behavior, for its modeling success in practice and being the most common choice of prior work [41, 35, 16, 20, 12, 29, 2, 17]. We acknowledge that there do exist other models of bounded rational behaviors beyond the QR model. For example, Kahneman [23] introduced the prospect theory to model the bounded rationality of agents in games under risk; Camerer et al. [11] proposed the cognitive hierarchy theory that classifies the agents according to their degree of reasoning in forming expectations of others. We anticipate that the message of our paper — i.e., the observation of suboptimal responses could provide additional information to learn the follower's preferences — generally applies to many of these bounded rationality models.

Inverse Game Theory. Vorobeychik et al. [39] considered the payoff function learning problem using the strategy profiles and corresponding utility through regression. Kuleshov and Schrijvers [26] introduced the concept of inverse game theory, and the authors showed that the problem of computing the agents' utilities from a set of correlated equilibrium is NP-Hard, unless the game is known to have special structures. More recently, the inverse game theory problem is studied under the QR model and leads to a few positive results: Haghtalab et al. [20] proves only three strategies are sufficient to recover linear follower payoff functions in security games; Ling et al. [29] presents an end-to-end learning framework that learns the zero-sum game payoff from its QRE. Following their success, our paper is the first work that provides theoretical guarantee of payoff recovery in *general* Stackelberg game. Finally, inverse problems have received significantly much more attention in single-agent decision making problems; The most notable problem is the inverse reinforcement learning pioneered by Ng et al. [34], Abbeel and Ng [1].

---

[1]Note that the $\frac{\log(\delta)}{\epsilon^2}$ term comes from concentration bound and is natural when observations (i.e., observed follower actions) have randomness.

3 Problem Formulation

Game Setup We consider the Stackelberg game between a single leader (she) and follower (he). We let $U \in \mathbb{R}^{m \times n}$ (resp. $V \in \mathbb{R}^{m \times n}$) be the leader's (resp. follower's) utility matrix, where m, n are the number of actions for the leader (resp. follower). We use $\mathcal{G}(U, V)$ to denote the game instance. Each entry $u_{i,j}$ (resp. $v_{i,j}$) of the utility matrix denotes the leader's utility (resp. follower's utility) when leader plays action i and follower plays action j. Without loss of generality, let $u_{i,j}, v_{i,j} \in [0, 1]$. Let $V_j \in \mathbb{R}^m$ be the jth column of the matrix V. We denote the set of the leader's (resp. follower's) action set by $[m] := \{1, \ldots, m\}$ (resp. $[n] := \{1, \ldots, n\}$).

In this sequential game, the leader moves first by committing to a (possibly randomized) strategy, $\boldsymbol{x} = (x_1, \cdots, x_m) \in \Delta_m$, where the simplex $\Delta_m = \{\boldsymbol{x} : \sum_{i \in [m]} x_i = 1 \text{ and } 0 \leq x_i \leq 1\}$ and each x_i represents the probability the leader playing action i. Similarly, let Δ_n denote the follower's strategy space. Under perfect rationality, given the leader's committed strategy, the follower would in turns chooses the best response action j^* that maximizes his utility, i.e., $j^* = \operatorname{argmax}_{j \in [n]} \{\boldsymbol{x}^\top V_j\}$. In our problem, we use the QR model instead to capture the follower's bounded rational behavior. That is, the follower would respond to the leader's committed strategy by choosing a strategy $\boldsymbol{y}^*$ that maximizes his utility up to a Gibbs entropic regularizer, i.e., $\boldsymbol{y}^* = \operatorname{argmax}_{\boldsymbol{y} \in \Delta_n} \{\lambda \boldsymbol{x}^\top V \boldsymbol{y} - \boldsymbol{y} \ln \boldsymbol{y}\}$. This is shown to be equivalent to the setting where the follower is best responding according to the payoff perturbed by noises from a Gumbel distribution [22]. And we know the close form solution of follower's optimal strategy for this convex optimization program is exactly the logit choice model on the true payoff, i.e., for each $j \in [n]$, $y_j^* = \frac{\exp(\lambda \boldsymbol{x}^\top V_j)}{\sum_{k \in [n]} \exp(\lambda \boldsymbol{x}^\top V_k)}$ [33].

We refer to λ as the bounded rationality constant that is given in each specific problem, as several existing work have already determined its empirical value in practice: the human behavior experiments in [38, 40] compute $\lambda = 7.6$; the experiments [28, 36, 32] show λ is in the range of 4 to 16.[2]

Learning Problem We consider the inverse game theory problem in sequential game with unknown follower utility and seek to quantify how much the leader can learn about a bounded rational follower's utility. We frame this problem under an *active* and *strategic* learning setup, where the leader can interactively choose a randomized strategy and observe follower's strategic responses. Specifically, at each round $t \in [T]$, the leader commits to a strategy $\boldsymbol{x}(t)$. The follower observes the committed $\boldsymbol{x}(t)$ and responds based on the QR strategy $\boldsymbol{y}(t)$. Below we will consider both feedback settings based on whether the leader is able to observe the exact distribution $\boldsymbol{y}(t)$ or merely its samples.

We set our primary learning objective as to recover a full characterization of the follower's utility; the results below shall explain how it is unnecessary and almost unrealistic to expect an exact recovery of the follower's utility. And we show in Proposition 1 and Theorem 1 that such utility characterization can be used to compute the optimal leader strategy under both perfect rationality, known as strong Stackelberg equilibrium (SSE), and bounded rationality, known as quantal Stackelberg equilibrium (QSE). And besides developing the optimal (or robust) leader strategies, we believe the recovered utilities are generally useful for our better understanding and reasoning of the followers' motives. However, given the limited scope of the paper, we focus on the inverse game theory problems and defer the problems regarding how to strategize using the knowledge of game (i.e., the typical game-theoretical problems) to related and future work.

4 Theoretical Results

4.1 Learning from Mixed Strategies

As a warm-up, we first consider a rather ideal case where the leader can directly observe the follower's mixed strategy $\boldsymbol{y}(t)$. In this case, it turns out that the leader would be able to perfectly recover the follower's payoff matrix from his responses to m different strategies and thereby determine the her optimal strategy. Despite a seemingly intuitive result, its underlying rationale is actually not as straightforward. Specifically, many would raise the following doubt: the logit transformation is not bijective and thus its inverse mapping is not injective; in particular, it only gives us a system of at most $n - 1$ different linear equations w.r.t. the follower's utility; one can check that if we add a

---

[2]The λ estimations are normalized to the utility scale in $[0, 1]$.

constant to all entries of the utility matrix, the resulting probability distribution stays the same after the logit transformation. Thus, it should require more than m such linear equation systems to recover a utility matrix with $m \times n$ unknown parameters. However, thanks to the observation in Proposition 1, it happens that the follower's utility matrix can be fully characterized by $m \times (n-1)$ parameters that is essentially the different of each column in the utility matrix. This somewhat coincidentally compensates the missing information on follower utility due to the logit transformation.

Knowing that m strategies is the lower bound of this learning problem in general, below we will explicitly construct a learning algorithm that have the matching upper bound. We start by formalizing a characterization of the follower utilities that provably induce the same leader and follower policies.

Proposition 1 (Policy Invariance under Payoff Transformation). *For any $\widetilde{V} \in \{V + \boldsymbol{c} \otimes 1_n | \boldsymbol{c} \in \mathbb{R}^m\}$, i.e., a row-wise shifted matrix of V, the follower's quantal response (resp. best response) policy to leader's committed strategy remains the same, and thus the optimal leader strategy in SSE or QSE remains the same.*

Proof. First, pick any leader strategy $\boldsymbol{x}$, we show with any utility matrix V, the follower has the same action probability under quantal response model for any of its row-shifted utility matrices $\widetilde{V} := V + \boldsymbol{c} \otimes 1_n$[3]. To verify this claim, we pick any of follower's action $j \in [n]$,

$$p_j = \frac{\exp(\lambda \boldsymbol{x}^\top \widetilde{V}_j)}{\sum_{k \in [n]} \exp(\lambda \boldsymbol{x}^\top \widetilde{V}_k)} = \frac{\exp(\lambda \boldsymbol{x}^\top [V_j + \boldsymbol{c}])}{\sum_{k \in [n]} \exp(\lambda \boldsymbol{x}^\top [V_k + \boldsymbol{c}])} = \frac{\exp(\boldsymbol{x}^\top V_j)\cancel{\exp(\lambda \boldsymbol{x}^\top \boldsymbol{c})}}{\sum_{k \in [n]} \exp(\lambda \boldsymbol{x}^\top V_k)\cancel{\exp(\lambda \boldsymbol{x}^\top \boldsymbol{c})}},$$

where the first and second equality is by definition; the last equality is by separating and canceling out the same terms.

Second, we show the follower's best response remains the same for any of its row-shifted utility matrices $\widetilde{V} := V + \boldsymbol{c} \otimes 1_n$. Specifically, for any $\boldsymbol{x}$, for any V and $\widetilde{V} := V + \boldsymbol{c} \otimes 1_n$, we have,
$$\forall j, k \in [n], \boldsymbol{x}^\top \widetilde{V}_j \geq \boldsymbol{x}^\top \widetilde{V}_k \iff \boldsymbol{x}^\top [V_j + \boldsymbol{c}] \geq \boldsymbol{x}^\top [V_k + \boldsymbol{c}] \iff \boldsymbol{x}^\top V_j \geq \boldsymbol{x}^\top V_k$$

Finally, since the follower's quantal response (resp. best response) policy to leader's committed strategy remains the same under any of its row-shifted utility matrices $\widetilde{V} := V + \boldsymbol{c} \otimes 1_n$, pick any strategy $\boldsymbol{x}$, the leader utility in face of quantal response (resp. best response) must remain the same. This means the leader's equilibrium strategy in SSE or QSE also remains the same for any follower utility $\widetilde{V} := V + \boldsymbol{c} \otimes 1_n$. $\qquad\square$

Proposition 1 suggests that the row-wise shifted payoff matrix is just as good as the ground-truth payoff matrix in our setting. This essentially means only the difference between action payoffs matters for the follower's policy. As such, we introduce a row-wise distance metric that accommodates such policy invariant transformation to empirically measure the quality of the recovered follower utility.

Definition 1 (Logit Distance). *We define a* logit distance *between the ground truth follower utility V and the recovered follower utility $\widetilde{V} \in \mathbb{R}^{m \times n}$, $\Phi(V, \widetilde{V}) = \frac{1}{mn} \sum_{i \in [m]} \min_z \left\| V_i - \widetilde{V}_i - z \right\|_1$.*

Whenever the distance $\Phi(V, \widetilde{V}) = 0$, we say the recovered follower utility is perfect.

Proposition 2 (m Strategies to Success). *There exists a learning algorithm that can always perfectly recover the follower strategy from m queries of the follower's mixed strategies.*

Proof Sketch. We pick m linearly independent basis vectors for each $\boldsymbol{x}(t)$ in m rounds and argue that the following optimization program can perfectly recover the follower's utility matrix $\widetilde{V}$.

$$\begin{aligned} \text{minimize} \quad & \sum_{t \in [m]} \left[\log \sum_{j \in [n]} \exp z_j(t) - \widehat{\boldsymbol{y}}(t) \cdot \boldsymbol{z}(t) \right] \\ & \boldsymbol{z}(t) = \lambda \boldsymbol{x}(t)^\top \widetilde{V}, \qquad\qquad\qquad \text{for } t \in [m]. \end{aligned} \tag{4.1}$$

We can see that the objective of the optimization program is a log-sum-exp function w.r.t. variables $\{\boldsymbol{z}(t)\}_{t \in [m]}$, which is convex. This means we can determine its minimizer set of $\{\boldsymbol{z}(t)\}_{t \in [m]}$. Meanwhile, the constraints of the optimization program gives a system of linear equation between $\{\boldsymbol{z}(t), \boldsymbol{x}(t)\}_{t \in [m]}$ and the variable $\widetilde{V}$. But the solution of $\widetilde{V}$ are not unique, as minimizer set of

---

[3] $1_n = (1, 1, \cdots, 1)$ denotes the 1-vector of size n

229 $\{z(t)\}_{t\in[m]}$ contain infinitely many elements. But it turns out that when $\{x(t)\}_{t\in[m]}$ forms an
230 linearly independent basis of $\mathbb{R}^m$, any solution $\widetilde{V}$ to the linear system given by any minimizer
231 $\{z(t)\}_{t\in[m]}$ are guaranteed to have $\Phi(V,\widetilde{V})=0$. We defer the full proof to Appendix A.

232   □

4.2 Learning from Realized Actions

234 In this section, we consider the more common scenario, where the leader is able to observe a single
235 action from follower at each round, i.e., the best response w.r.t his perceived utility under the Gumbel
236 noise, or equivalently the realized action of the follower's quantal response strategy. It turns out that
237 the intuitions from Section 4.1 still apply, and we are able to prove a strict generalization of these
238 results. In particular, Theorem 1 strengthens Proposition 1 in that learning the follower's utility up to
239 some logit distance could also lead to an approximation of the optimal leader strategy under some
240 mild condition given by Definition 2 in general Stackelberg game. Theorem 2 generalizes Proposition
241 2, as we showcase the sample complexity of our learning framework to recover the follower's utility
242 in face of the follower's stochastic responses.

243 **Definition 2** (Inducibility Gap). *For any follower utility V, we define its inducibility gap as*

$$\sigma(V) := \min_{j\in[n]} \max_{x\in\Delta_m} \min_{j'\neq j} x^\top V[e_j - e_{j'}]$$

244 *That is, the maximum constant $\sigma(V)$ such that for any follower actions $j \in [n]$, there exists a*
245 *leader strategy x^j that makes j dominates any other action j' by a margin of at least $\sigma(V)$, i.e.,*
246 $x^j V e_j \geq x^j V e_{j'} + \sigma(V), \forall j' \neq j \in [n]$.

247 **Theorem 1.** *Given a follower utility $\widetilde{V}$ with inducibility gap $\sigma(\widetilde{V}) > 5\epsilon$, we can construct an*
248 $O(\epsilon/\sigma(\widetilde{V}))$-*optimal leader strategy for any game $\mathcal{G}(U,V)$ with $\Phi(\widetilde{V},V) \leq \frac{\epsilon}{mn}$.*

249 *Proof Sketch.* We prove through an explicit construction. That is, given the estimation of the
250 follower's utility $\widetilde{V}$, we construct a ϵ-robust strategy $x = (1 - \frac{3\epsilon}{\sigma(V)})\widetilde{x}^* + \frac{3\epsilon}{\sigma(V)}x^{\widetilde{j}^*}$ based on the SSE
251 $(\widetilde{x}^*, \widetilde{j}^*)$ of $\mathcal{G}(U,\widetilde{V})$ and the strategy x^{j^*} such that $(x^{\widetilde{j}^*})^\top V e_j \geq (x^{\widetilde{j}^*})^\top V e_{j'} + \sigma(V), \forall j' \neq j$. We
252 show this strategy is guaranteed to be an $(\frac{6\epsilon}{\sigma(\widetilde{V})-2\epsilon})$-SSE of the Stackelberg game $\mathcal{G}(U,V)$. The proof
253 then relies on two key observations stated in Lemma 1.1 and 1.2: First, given that $\Phi(\widetilde{V},V) \leq \frac{\epsilon}{mn}$
254 and $\sigma(V) > 3\epsilon$, the best response of an robust strategy x in game $\mathcal{G}(U,V)$ remain the same from
255 that in a game $\mathcal{G}(U,\widetilde{V})$, and so is the leader utility. This means x gets at least $(1 - \frac{3\epsilon}{\sigma(V)})$ portion of
256 SSE utility in $\mathcal{G}(U,\widetilde{V})$. Second, the difference between the SSE utility in $\mathcal{G}(U,V)$ and $\mathcal{G}(U,\widetilde{V})$ are
257 bounded by $\frac{3\epsilon}{\sigma(V)}$. Meanwhile, despite V is unknown to us, Lemma 1.3 shows that we can bound
258 $\sigma(V) \geq \sigma(\widetilde{V}) - 2\epsilon$, so we can use $\sigma(\widetilde{V}) - 2\epsilon$ to substitute $\sigma(V)$. And this requires $\sigma(\widetilde{V}) \geq 5\epsilon$.   □

259 Due to space limit, we defer to the full statement of the lemmas and proofs to Appendix B. After
260 restoring the connections between the logit distance and leader's optimal equilibrium utility, we now
261 show the relationship between the logit distance and sample complexity in the learning problem.

262 **Theorem 2.** *It takes $\Theta(\frac{m\log(mn/\delta)}{\rho\epsilon^2})$ queries of the follower's quantal response to recover the*
263 *follower's utility $\widetilde{V}$ within the logit distance $\Phi(V,\widetilde{V}) = \frac{\epsilon}{\lambda}$ with probability at least $1 - \delta$, where ρ is*
264 *the least non-zero measure in the induced follower's strategies.*

265 This theorem is a strict generalization of Proposition 2 and we defer the full proof to Appendix
266 C due to space limit. The high level intuition comes from the fact that $(1 - \epsilon)$-multiplicative
267 approximation guarantee is translated to ϵ additive error after the logarithmic transformation using
268 the approximation that for small positive ϵ close to zero, we have $\ln(\frac{1}{1-\epsilon}) = O(\epsilon)$. And to obtain
269 such $(1 - \epsilon)$-multiplicative approximation of an mixed strategy, we use standard concentration results
270 for a tight sample complexity bound. We formalize these statements and proofs in Lemma 2.1, 2.2.

271 **Lemma 2.1.** *There exists a learning algorithm that can recover the follower's utility $\widetilde{V}$ within the*
272 *logit distance $\Phi(V,\widetilde{V}) = O(\frac{\epsilon}{\lambda})$ from m queries of the $(1 - \epsilon)$-multiplicative approximation of the*
273 *follower's mixed strategies.*

Lemma 2.2. *For any discrete distribution $\boldsymbol{y}$ with support size n and the least non-zero measure $\min_{i \in [n], y_i > 0}\{y_i\} \geq \rho$, with $\Theta(\frac{\log(n/\delta)}{\rho \epsilon^2})$ samples, the corresponding empirical distribution $\widehat{\boldsymbol{y}}$ is an $(1 - \epsilon)$-multiplicative approximation to $\boldsymbol{y}$, with probability at least $1 - \delta$.*

4.3 A Learning Framework of Practicality

PURE, Less is More   The results above lead us to a simple but provably effective method, PURE; the name comes from the fact that it only uses the m different pure strategies in Δ_m, $\{\boldsymbol{x}(t)\}_{t \in [m]}$. As specified in the proof of Theorem 2, it gathers the follower's sampled quantal responses of these pure strategies to estimate the corresponding empirical distributions $\{\widetilde{\boldsymbol{y}}(t)\}_{t \in [m]}$ and solves for the $\widetilde{V}$ through the optimization program 4.1. While it is a seemingly naive learning algorithm, we would like to make a few crucial points on its unique advantages from both theoretical and practical perspectives.

Theoretically, we know PURE is guaranteed to perfectly recover the follower utility in the setting of Section 4.1. More importantly, when randomness presents, PURE guarantees that the estimation error measured by the logit distance is always bounded as $O(\frac{\epsilon}{\lambda})$; the Equation (C.1) in the proof of Theorem 2 suggests that the inverse of a general row-stochastic matrix X and the error matrix β could otherwise lead to possibly unbounded estimation error.

Meanwhile, we anticipate the simplicity of PURE would be especially valuable to its applicability in practice. First, the randomized leader strategies in many applications are difficult to be implemented precisely, because the followers may not have the perfect estimation of the leader's distributions of randomization. This means that observing the follower's responses to randomized leader strategies could be more noisy in nature. Second, it might be inappropriate and possibly forbidden for the learner (e.g., a Internet platform or policy marker) to frequently change its strategies (e.g., prices or policies). Instead, the deployment of PURE only requires the learner to observe the responses of only a small number of simplified, pure strategies at the population level.

PURE for Structured Games   We remark that the learning framework of PURE could be tailored to the special structures in Stackelberg game. For example, let us consider a celebrated variant, known as the Stackelberg security game. Namely, a leader (defender) commits to a randomized allocation of security resources to defend a set of $n(= m)$ targets from a follower (attacker). In turn, the follower observes this randomized allocation and picks a target to attack. Both the leader and the follower receive payoffs depending on the target that was attacked and the probability that it was defended. So in this case the follower utility can be expressed as linear functions, where each entry in vector $\boldsymbol{w}, \boldsymbol{b} \in \mathbb{R}^n$ denotes respectively the attacker's cost and reward on each target. When the leader defends each target with the randomized strategy $\boldsymbol{x} \in \Delta_n$, if the follower attacks the target j, he receives utility based on the cost w.r.t. the chance target j is defended, and the reward for the attack, i.e., $V(\boldsymbol{x}, j) = w_j x_j + b_j$. Then, we can use the learning framework of PURE that only solves for the linear utility function parameters using the optimization program 4.2. This not only reduces the number of parameters to be learnt but also directly gives the reward and cost parameters of each targets. Our empirical experiments below suggest significantly faster error convergence rate once the structure insights is brought into the learning framework.

$$\begin{aligned} \text{minimize} \quad & \sum_{t \in [d]} \left[\log \sum_{j \in [n]} \exp z_j(t) - \widehat{\boldsymbol{y}}(t) \cdot \boldsymbol{z}(t) \right] \\ & \boldsymbol{z}_j(t) = \lambda(w_j x_j(t) + b_j), \qquad \text{for } j \in [n], t \in [T]. \end{aligned} \tag{4.2}$$

PURE-Exp for the Worst Cases   In certain situations however the followers could be more rational and the parameter λ is larger than the standard estimation. Then, the follower's stochastic quantal response becomes rather deterministic, and the least non-zero measure ρ decreases. Lemma 2.2 suggests that querying through the simple pure strategies could become much less inefficient in obtaining the $(1 - \epsilon)$-multiplicative approximation of the actual strategy. Nevertheless, it turns out that we can introduce the "exploration and exploitation" principle here for the remedy, and we thus name such variant of PURE algorithm as PURE-Exp. Specifically, we introduce an exploration procedure to search for better strategies if an empirical estimation of the follower strategy tends to concentrate on a single action. We knew such strategy would contain more noise than information, as the error introduced by its multiplicative approximation ratio can be significant; reversing a one-hot distribution from logit transformation provides no information about the follower utility. In this case, we carefully replace it by a perturbed strategy from the original strategy. This ensures that the resulting strategy set after replacement still forms a full rank matrix that ensures the invertibility

necessary for provably more effective recovery of V in Theorem 2. The algorithm would otherwise keep exploiting the leader strategies for the better estimation of the follower responses. Our empirical experiments show substantial performance improvement by PURE-Exp in those extreme cases.

Algorithm 1 PURE-Exp

1: **Input:** Game parameters m, n, λ, QR oracle $\mathcal{O} : \Delta_m \to [n]$ and optimization program $\mathcal{Q}$ based on the game structure.
2: **Initialization:** $\mathcal{X}$, a list of leader strategies where the i-th strategy $\boldsymbol{x}^{(i)} \leftarrow [e_i]_{i \in [m]}$; $\mathcal{Y}$, a list of empirical estimation of follower strategies w.r.t. $\boldsymbol{x}^{(i)}$; set $i \leftarrow 0$.
3: **for** $t = 0, 1, \ldots, T$ **do**
4:     Use leader strategy $\boldsymbol{x}^{(i)}$ from $\mathcal{X}$ to query for follower response $j \leftarrow \mathcal{O}(\boldsymbol{x}^{(i)})$.
5:     Update empirical estimation $\boldsymbol{y}^{(i)}$ of the follower's QR strategy to $\boldsymbol{x}^{(i)}$.
6:     **if** Probability mass of $\boldsymbol{y}^{(i)}$ concentrates on a single action **then**
7:         Sample a random perturbation $\widetilde{\boldsymbol{x}}$ from simplex Δ_m.
8:         Replace $\boldsymbol{x}^{(i)}$ in list $\mathcal{X}$ by the new strategy $\boldsymbol{x}^{(i)} \leftarrow \frac{1}{2}\widetilde{\boldsymbol{x}} + \frac{1}{2}e_i$.
9:         Reset the empirical estimator $\boldsymbol{y}^{(i)}$ in $\mathcal{Y}$.
10:     **end if**
11:     Update $i \leftarrow (i+1) \mod m$.
12: **end for**
13: Solve the optimization program $\mathcal{Q}$ for the best game parameters using $\mathcal{X}, \mathcal{Y}$.

---

5 Experiment

In this section, we seek to further understand the empirical implications of our learnability results. A major challenge when evaluating the learning performance is that the measures rely on the underlying ground truth utility. While there are several real world data collected in particular to understand the human behaviors and QR model [32, 38, 40, 35], they are sensitive, proprietary datasets in security domains that we are unfortunately unable to access. Moreover, these offline data only offers limited number of offline samples that can hardly be used in our active learning setup. Therefore, our experiments have to rely on synthesized game instances, from which we can construct oracles to respond to the active learning queries and accurately evaluate for the learning performance. As motivated in the previous section, we will use the logit distance in Definition 1 to empirically measure the quality of recovered follower utilities.[4] We start by investigating the empirical performance of PURE in games synthesized using several sets of different parameters below.

- **The number of leader and follower actions** m, n**:** We compare the learning performance in game of varying sizes, while fixing the number of query $T = 10^7$. In the left plot of Figure 1, the first trend to notice is that the error grows almost linear to m, exactly as Theorem 2 predicts. Meanwhile, the error also grows as n increases, as the error bound depends on $1/\rho \geq n$. In Appendix, we shows that $1/\rho$ in average among those randomized generated game instances grows linearly with n, which justifies the almost linear relation between the logit distance and n.

- **The level of bounded rationality** λ**:** We consider different λ ranging from 0.5 to 16 estimated in prior human behavior experiments [32, 38, 40]. In the middle plot of Figure 1, we display the convergence trend of logit distance in the number of queries. The PURE algorithm shows consistently good performance among these different λ. On one hand, in games with the smaller λ, the error tends to converge slower, as bounded by the $\frac{1}{\lambda\sqrt{t}}$ convergence rate implied by Theorem 2. On the other hand, the variance of error increases especially in the initial half of the timeline in games with larger λ. This is explained by the fact that sample complexity of learning distribution up to $(1 - \epsilon)$-multiplicative factor increases as the distribution concentrates when λ increase.

- **The payoff margin** α**:** We generate the follower's utility matrix, $V = \alpha I + (1 - \alpha)\Xi$, as a convex combination of diagonal matrix $I \in \mathbb{R}^{m \times n}$ and Gaussian random noise Ξ normalized to $[0, 1]^{m \times n}$ such that the larger α, the follower are likely to have higher margin for his best response

---

[4]Except the varying parameters, we control the parameters as $m = n = 10, \alpha = 0.2, \lambda = 8$ by default, and plot their average performance across 5 different randomly generated instances with the standard deviation illustrated in the error bars or the lightly shaded regions.

Figure 1: Recovering payoffs under varying parameters $m \times n$ (left), λ (middle), α (right)

Figure 2: Comparision of `PURE` v.s. offline data (left), `PURE` with or without structure insights (middle), `PURE` v.s. `PURE-Exp` (right).

against each of the leader's action. In the right plot of Figure 1, we can see a consistent trend of improving estimation of the follower's utility as query number increases across different level of α. Interestingly, as the utility matrix becomes closer to the simple diagonal matrix, and the follower easily becomes less irrational, the convergence rate slows down; this again suggests our message on the *blessing of bounded rationality* that provides the stochasticity in follower's responses used as our additional information source.

We also compare the performance `PURE` and its variants introduced in Section 4.3, and the results closely match with our theoretical insights. In the left plot of Figure 2, we compare `PURE` using only 10 leader strategies with the standard offline learning setup using $10^2, 10^3$ or 10^4 leader strategies with less samples in average and less accurate estimation of follower response for each leader strategy. We can see that the `PURE` significantly outperforms these offline learning setups, especially when λ is smaller such that the response of follower tends to be more irrational and thus "noisy". In the middle plot of Figure 2, we study the learning performance of `PURE` in various security games with or without using the optimization program specialized for the game structure (in dotted or straight lines). The result suggests that the structure insights can be used for fast recovery of follower utility. In the right plot of Figure 2, we found that `PURE-Exp`, with the principle of exploration and exploitation, are able to improve the learning performance in the case when the follower appears to be more rational. However, its performance also degrades as λ further increases and the problem becomes almost the perfect rationality setting that are proved to be statistically hard to learn [27, 37]. In the limit of space, please check out Appendix D for more descriptions and analysis of our experiments.

6 Conclusion

Two common assumptions of a typical game theory problem: (1) The agents know the game parameters; (2) The agents are perfectly rational. While these assumptions have enabled elegant mathematical models and fundamental theoretical insights, they could be limiting in some real world scenarios. Our paper tackle the particular problem in sequential game-theoretical interactions without these two common assumptions. While similar inverse game theory problems under perfect rationality are shown to be statistically or computationally intractable, we made an intriguing finding in which relaxing us from these idealistic settings in turns lead us to a provably efficient learning guarantee. We accordingly proposed the learning framework of `PURE` intended for less usage restrictions in real world applications. In future work, we wish to extend our analysis and insights to more general game settings and other models of bounded rationality.

References

[1] Pieter Abbeel and Andrew Y Ng. Apprenticeship learning via inverse reinforcement learning. In *Proceedings of the twenty-first international conference on Machine learning*, page 1, 2004.

[2] Bo An, Fernando Ordóñez, Milind Tambe, Eric Shieh, Rong Yang, Craig Baldwin, Joseph DiRenzo III, Kathryn Moretti, Ben Maule, and Garrett Meyer. A deployed quantal response-based patrol planning system for the us coast guard. *Interfaces*, 43(5):400–420, 2013.

[3] Sanjeev Arora, Elad Hazan, and Satyen Kale. The multiplicative weights update method: a meta-algorithm and applications. *Theory of computing*, 8(1):121–164, 2012.

[4] Patrice Assouad. Deux remarques sur l'estimation. *Comptes rendus des séances de l'Académie des sciences. Série 1, Mathématique*, 296(23):1021–1024, 1983.

[5] Robert J Aumann. Rationality and bounded rationality. In *Cooperation: Game-Theoretic Approaches*, pages 219–231. Springer, 1997.

[6] Yu Bai, Chi Jin, Huan Wang, and Caiming Xiong. Sample-efficient learning of stackelberg equilibria in general-sum games. *Advances in Neural Information Processing Systems*, 34, 2021.

[7] Maria-Florina Balcan, Avrim Blum, Nika Haghtalab, and Ariel D Procaccia. Commitment without regrets: Online learning in stackelberg security games. In *Proceedings of the sixteenth ACM conference on economics and computation*, pages 61–78, 2015.

[8] Christopher M Bishop and Nasser M Nasrabadi. *Pattern recognition and machine learning*, volume 4. Springer, 2006.

[9] Avrim Blum, Nika Haghtalab, and Ariel D Procaccia. Learning optimal commitment to overcome insecurity. *Advances in Neural Information Processing Systems*, 27, 2014.

[10] Colin F Camerer. *Behavioral game theory: Experiments in strategic interaction*. Princeton university press, 2011.

[11] Colin F Camerer, Teck-Hua Ho, and Juin-Kuan Chong. A cognitive hierarchy model of games. *The Quarterly Journal of Economics*, 119(3):861–898, 2004.

[12] Jakub Černỳ, Viliam Lisỳ, Branislav Bošanskỳ, and Bo An. Computing quantal stackelberg equilibrium in extensive-form games. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 5260–5268, 2021.

[13] Herman Chernoff. A measure of asymptotic efficiency for tests of a hypothesis based on the sum of observations. *The Annals of Mathematical Statistics*, pages 493–507, 1952.

[14] Vincent Conitzer. On stackelberg mixed strategies. *Synthese*, 193(3):689–703, 2016.

[15] Gerard Debreu. Individual choice behavior: A theoretical analysis, 1960.

[16] Fei Fang, Peter Stone, and Milind Tambe. When security games go green: Designing defender strategies to prevent poaching and illegal fishing. In *Twenty-fourth international joint conference on artificial intelligence*, 2015.

[17] Fei Fang, Thanh H Nguyen, Rob Pickles, Wai Y Lam, Gopalasamy R Clements, Bo An, Amandeep Singh, Brian C Schwedock, Milin Tambe, and Andrew Lemieux. Paws—a deployed game-theoretic application to combat poaching. *AI Magazine*, 38(1):23–36, 2017.

[18] Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep learning*. MIT press, 2016.

[19] Sanford J Grossman and Oliver D Hart. An analysis of the principal-agent problem. In *Foundations of insurance economics*, pages 302–340. Springer, 1992.

[20] Nika Haghtalab, Fei Fang, Thanh Hong Nguyen, Arunesh Sinha, Ariel D Procaccia, and Milind Tambe. Three strategies to success: Learning adversary models in security games. 2016.

[21] Bengt Holmström. Moral hazard and observability. *The Bell journal of economics*, pages 74–91, 1979.

[22] Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with gumbel-softmax. *arXiv preprint arXiv:1611.01144*, 2016.

[23] Daniel Kahneman. Econ ometrica i ci. *Econometrica*, 47(2):263–291, 1979.

[24] Shankar Kalyanaraman and Christopher Umans. The complexity of rationalizing matchings. In *International Symposium on Algorithms and Computation*, pages 171–182. Springer, 2008.

[25] Shankar Kalyanaraman and Christopher Umans. The complexity of rationalizing network formation. In *2009 50th Annual IEEE Symposium on Foundations of Computer Science*, pages 485–494. IEEE, 2009.

[26] Volodymyr Kuleshov and Okke Schrijvers. Inverse game theory: Learning utilities in succinct games. In *International Conference on Web and Internet Economics*, pages 413–427. Springer, 2015.

[27] Joshua Letchford, Vincent Conitzer, and Kamesh Munagala. Learning and approximating the optimal strategy to commit to. In *International symposium on algorithmic game theory*, pages 250–262. Springer, 2009.

[28] Bernhardt Lieberman. Human behavior in a strictly determined 3×3 matrix game. *Behavioral Science*, 5(4):317–322, 1960.

[29] Chun Kai Ling, Fei Fang, and J Zico Kolter. What game are we playing? end-to-end learning in normal and extensive form games. *arXiv preprint arXiv:1805.02777*, 2018.

[30] Janusz Marecki, Gerry Tesauro, and Richard Segal. Playing repeated stackelberg games with unknown opponents. In *Proceedings of the 11th International Conference on Autonomous Agents and Multiagent Systems-Volume 2*, pages 821–828, 2012.

[31] Daniel L McFadden. Quantal choice analaysis: A survey. *Annals of economic and social measurement, volume 5, number 4*, pages 363–390, 1976.

[32] Richard D McKelvey and Thomas R Palfrey. Quantal response equilibria for normal form games. *Games and economic behavior*, 10(1):6–38, 1995.

[33] Panayotis Mertikopoulos and William H Sandholm. Learning in games via reinforcement and regularization. *Mathematics of Operations Research*, 41(4):1297–1324, 2016.

[34] Andrew Y Ng, Stuart J Russell, et al. Algorithms for inverse reinforcement learning. In *Icml*, volume 1, page 2, 2000.

[35] Thanh Nguyen, Rong Yang, Amos Azaria, Sarit Kraus, and Milind Tambe. Analyzing the effectiveness of adversary modeling in security games. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 27, pages 718–724, 2013.

[36] Barry O'Neill. Nonmetric test of the minimax theory of two-person zerosum games. *Proceedings of the national academy of sciences*, 84(7):2106–2109, 1987.

[37] Binghui Peng, Weiran Shen, Pingzhong Tang, and Song Zuo. Learning optimal strategies to commit to. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 2149–2156, 2019.

[38] James Pita, Manish Jain, Milind Tambe, Fernando Ordóñez, and Sarit Kraus. Robust solutions to stackelberg games: Addressing bounded rationality and limited observations in human cognition. *Artificial Intelligence*, 174(15):1142–1171, 2010.

[39] Yevgeniy Vorobeychik, Michael P Wellman, and Satinder Singh. Learning payoff functions in infinite games. *Machine Learning*, 67(1):145–168, 2007.

[40] Rong Yang, Christopher Kiekintveld, Fernando Ordonez, Milind Tambe, and Richard John. Improving resource allocation strategy against human adversaries in security games. In *Twenty-Second International Joint Conference on Artificial Intelligence*, 2011.

[41] Rong Yang, Fernando Ordonez, and Milind Tambe. Computing optimal strategy against quantal response in security games. In *AAMAS*, pages 847–854, 2012.

[42] Stephan Zheng, Alexander Trott, Sunil Srinivasa, Nikhil Naik, Melvin Gruesbeck, David C Parkes, and Richard Socher. The ai economist: Improving equality and productivity with ai-driven tax policies. *arXiv preprint arXiv:2004.13332*, 2020.