Single Layer Predictive Normalized Maximum Likelihood for Out-of-Distribution Detection

Abstract

Detecting out-of-distribution (OOD) samples is vital for developing machine learning based models for critical safety systems. Common approaches for OOD detection assume access to some OOD samples during training which may not be available in a real-life scenario. Instead, we utilize the *predictive normalized maximum likelihood* (pNML) learner, in which no assumptions are made on the tested input. We derive an explicit expression of the pNML and its generalization error, denoted as the *regret*, for a single layer neural network (NN). We show that this learner generalizes well when (i) the test vector resides in a subspace spanned by the eigenvectors associated with the large eigenvalues of the empirical correlation matrix of the training data, or (ii) the test sample is far from the decision boundary. Furthermore, we describe how to efficiently apply the derived pNML regret to any pretrained deep NN, by employing the explicit pNML for the last layer, followed by the softmax function. Applying the derived regret to deep NN requires neither additional tunable parameters nor extra data. Our method surpasses the existing state-of-the-art methods on 60 OOD detection benchmarks using DenseNet-BC-100, ResNet-34, and WideResNet-40 models trained with CIFAR-100, CIFAR-10, and SVHN by a remarkable 15.2%.

1 Introduction

An important concern that limits the adoption of deep neural networks (DNN) in critical safety systems is how to assess our confidence in their predictions, i.e, quantifying their *generalization capability* (Willers et al., 2020). Take, for instance, a machine learning model for medical diagnosis. It may produce (wrong) diagnoses in the presence of inputs that are different from the training set rather than flagging them for human intervention (Singh et al., 2021). Detecting such unexpected inputs had been formulated as the OOD detection task (Hendrycks and Gimpel, 2017), as flagging test inputs that lie outside the training classes, i.e., are not *in-distribution* (IND).

Previous learning methods that designed to offer such generalization measures, include VC-dimension (Zhong et al., 2017; Vapnik and Chervonenkis, 2015) and norm based bounds (Neyshabur et al., 2018; Bartlett et al., 2017). As a whole, these methods characterized the generalization ability based on the properties of the parameters. However, they do not consider the test sample that is presented to the model (Jiang et al., 2020), which makes them useless for OOD detection. Other approaches build heuristics over the *empirical risk minimization* (ERM) learner, by post-processing the model output (Sastry and Oore, 2020) or modifying the training process (Papadopoulos et al., 2021; Vyas et al., 2018). Regardless of the approach, these methods choose the learner that minimizes the loss over the *training set*. This may lead to a large generalization error because the ERM estimate may be wrong on unexpected inputs; especially with large models such as DNN (Belkin et al., 2019).

To produce a useful generalization measure, we exploit the *individual setting* framework (Merhav and Feder, 1998). In the individual setting, there is no assumption about how the training and the test data are generated, nor about their probabilistic relationship. Moreover, the relationship between the labels and data is deterministic and can therefore be determined by an adversary. The generalization error in this setting is often referred to as the *regret* (Merhav and Feder, 1998). This regret is defined by the log-loss difference between a learner and the *genie*: a learner that knows the specific test label, yet is constrained to use an explanation from a set of possible models. The individual setting is the most general framework and so the result holds for a wide range of scenarios. Specifically, the results hold to OOD detection where the distribution of the OOD inputs is unknown.

The pNML learner (Fogel and Feder, 2018) was proposed as the min-max solution of the regret, where the minimum is over the learner choice and the maximum is for any possible test label value. Intuitively, the pNML assign a probability for a potential outcome as follows: Add the test sample to the training set with an arbitrary label, find the ERM solution of this new set, and take the probability it gives to the assumed label. Follow this procedure for every label and normalize to get a valid probability assignment. The pNML was developed before for linear regression (Bibas et al., 2019b) and was evaluated empirically for DNN (Fu and Levine, 2021; Bibas et al., 2019a).

We derive an analytical solution of the pNML learner and its generalization error (the regret) for a single layer NN. We analyze the derived regret and show it obtains low values when the test input either (i) lies in a subspace spanned by the eigenvectors associated with the large eigenvalues of the training data empirical correlation matrix or (ii) is located far from the decision boundary. Crucially, although our analysis focuses on a single layer NN, our results are applicable to the last layer of DNNs *without changing the network architecture or the training process*: We treat the pretrained DNN as a feature extractor with the last layer as a single layer NN classifier. We can therefore show the usage of the pNML regret as a confidence score for the OOD detection task.

To summarize, we make the following contributions.

1. **Analytical derivation of the pNML regret.** We derive an analytical expression of the pNML regret, which is associated with the generalization error, for a single layer NN.

2. **Analyzing the pNML regret.** We explore the pNML regret characteristic as a function of the test sample data, training data, and the corresponding ERM prediction. We provide a visualization on low dimensional data and demonstrate the situations in which the pNML regret is low and the prediction can be trusted.

3. **DNN adaptation.** We propose an adaptation of the derived pNML regret to any pretrained DNN that uses the softmax function with neither additional parameters nor extra data.

Applying our derived pNML regret to DNN does not require additional data, it is efficient and can be easily implemented. The derived regret is theoretically justified for OOD detection since it is the individual setting solution for which we do not require any knowledge on the test input distribution. Our pNML regret based score suppresses recent state-of-the-art methods in nearly all 60 IND-OOD detection benchmarks using ResNet-34, DenseNet-BC-100, and WideResNet-40 trained with CIFAR-100, CIFAR-10, and SVHN up to a remarkable $+15.2\%$.

2   Related work

OOD detection. A well-known method for OOD detection, named *ODIN*, manipulates the input image based on the gradient of the loss function (Liang et al., 2018). This input manipulation increases the margin between the maximum probability of images with known classes and images with unknown objects. However, the manipulation strength is defined by OOD data, which might be unavailable or different from the OOD samples in inference.

Different approaches propose to manipulate the loss function in the training phase. Lee et al. (2018) proposed to use the Mahalanobis distance between the test input representations and the class conditional distribution in the intermediate layers to train a logistic regression classifier to determine if the input sample is OOD. The *Energy* method (Liu et al., 2020) adds a cost function to the training phase to shape the energy surface explicitly for OOD detection. Papadopoulos et al. (2021) suggested the *outlier exposure with confidence control* (OECC) method in which a regularization term is added to the loss function such that the model produces a uniform distribution for OOD samples.

All mentioned methods require manipulating the DNN architecture or adding additional data. The *Baseline* method is one of the earliest approaches designed to identify whether a test input is IND and does not require changing the pretrained model (Hendrycks and Gimpel, 2017). This method uses the maximum probability of the DNN output as the OOD score. The *Gram* method (Sastry and Oore, 2020) detects OODs based on feature representations obtained in intermediate layers. Given a test sample, the Gram matrices of the test sample features are compared with those of the training samples known to belong to the estimated class of the test sample. However, this method require IND validation set and does not have a theoretical motivation.

The pNML learner. The pNML learner is the min-max solution of the supervised batch learning in the individual setting (Fogel and Feder, 2018) and is termed also the conditional normalized maximum likelihood (Rissanen and Roos, 2007; Roos and Rissanen, 2008).

Several methods deal with obtaining the pNML learner for different hypothesis sets: Bibas et al. (2019b) and Bibas and Feder (2021) showed the pNML solution for linear regression. Rosas et al. (2020) proposed an NML based decision strategy for supervised classification problems and showed it attains heuristic PAC learning. Fu and Levine (2021) used the pNML for model optimization based on learning a density function by discretizing the space and fitting a distinct model for each value.

For the DNN hypothesis set, Bibas et al. (2019a) estimated the pNML distribution with DNN by fine-tuning the last layers of the network for every test input and label combination. This approach is computationally expensive since training is needed for every test input. Zhou and Levine (2020) suggested a way to accelerate the pNML computation in DNN by using approximate Bayesian inference techniques to produce a tractable approximation to the pNML distribution.

3 Notation and preliminaries

In the supervised machine learning scenario, a training set consisting of N pairs of examples is given

$$\mathcal{D}_N = \{(x_n, y_n)\}_{n=1}^N, \quad x_n \in \mathcal{X}, \quad y_n \in \mathcal{Y}, \tag{1}$$

where x_n is the n-th data instance and y_n is its corresponding label. The goal of a learner is to predict the unknown test label y given a new test data x by assigning probability distribution $q(\cdot|x)$ to the unknown label. The performance is evaluated using the log-loss function

$$\mathcal{L}(q; x, y) = -\log q(y|x). \tag{2}$$

For the problem to be well-posed, we must make further assumptions on the class of possible models or *hypothesis set* that is used to find the relation between x and y. Denote Θ as a general index set, this class is a set of conditional probability distributions

$$P_\Theta = \{p_\theta(y|x), \ \theta \in \Theta\}. \tag{3}$$

The ERM is the learner from the hypothesis set that attains the minimal log-loss on the training set.

The individual setting. An additional assumption required to solve the problem is related to how the data and the labels are generated. In this work we consider the individual setting (Merhav and Feder, 1998; Fogel and Feder, 2018; Bibas et al., 2019b,a), where the data and labels, both in the training and test, are specific individual quantities: We do not assume any probabilistic relationship between them, the labels may even be assigned in an adversarial manner.

The genie. In the individual setting the goal is to compete with a reference learner, a genie, that has to following properties: (i) knows the test label value, (ii) is restricted to use a model from the given hypotheses set P_Θ, and (iii) does not know which of the samples is the test. This reference learner then chooses a model that attains the minimum loss over the training set and the test sample

$$\hat{\theta}(\mathcal{D}_N; x, y) = \arg\min_{\theta \in \Theta} \left[\mathcal{L}\left(p_\theta; x, y\right) + \sum_{n=1}^N \mathcal{L}\left(p_\theta; x_n, y_n\right) \right]. \tag{4}$$

The regret is the log-loss difference between a learner q and this genie:

$$R(q; \mathcal{D}_N; x, y) = -\log q(y|x) - \left[-\log p_{\hat{\theta}(\mathcal{D}_N; x, y)}(y|x) \right]. \tag{5}$$

Theorem 1 (Fogel and Feder (2018)). *The universal learner, denoted as the pNML, minimizes the regret for the worst case scenario*

$$\Gamma = R^*(\mathcal{D}_N, x) = \min_q \max_{y \in \mathcal{Y}} R(q; \mathcal{D}_N; x, y). \tag{6}$$

The pNML probability assignment and regret are

$$q_{pNML}(y|\mathcal{D}_N; x) = \frac{p_{\hat{\theta}(\mathcal{D}_N;x,y)}(y|x)}{\sum_{y' \in \mathcal{Y}} p_{\hat{\theta}(\mathcal{D}_N;x,y')}(y'|x)}, \quad \Gamma = \log \sum_{y' \in \mathcal{Y}} p_{\hat{\theta}(\mathcal{D}_N;x,y')}(y'|x). \tag{7}$$

Proof. The regret is equal for all choices of y. If we consider a different probability assignment, it should assign a smaller probability for at least one of the outcomes. If the true label is one of those outcomes it will lead to a higher regret. For more information see Fogel and Feder (2018). $\square$

The pNML regret is associated with the model complexity (Zhang, 2012). This complexity measure formalizes the intuition that a model that fits almost every data pattern very well would be much more complex than a model that provides a relatively good fit to a small set of data. Thus, the pNML incorporates a trade-off between goodness of fit and model complexity as measured by the regret.

Online update of a neural network. Let X_N and Y_N be the data and label matrices of N training points respectively

$$X_N = [x_1 \quad x_2 \quad \dots \quad x_N]^\top \in \mathcal{R}^{N \times M}, \quad Y_N = [y_1 \quad y_2 \quad \dots \quad y_N]^\top \in \mathcal{R}^{N \times C}, \tag{8}$$

such that the number of input features and model outputs are M and C respectively. Denote X_N^+ as the Moore–Penrose inverse of the data matrix

$$X_N^+ = \begin{cases} (X_N^\top X_N)^{-1} X_N^\top & Rank(X_N^\top X_N) = M \\ X_N^\top (X_N X_N^\top)^{-1} & otherwise, \end{cases} \tag{9}$$

$f(\cdot)$ and $f^{-1}(\cdot)$ as the activation and inverse activation functions, and $\theta \in \mathcal{R}^{M \times C}$ as the learnable parameters. The ERM, that minimizes the training set mean squared error (MSE), is

$$\hat{\theta}_N = X_N^+ f^{-1}(Y_N) = \arg\min_\theta ||Y_N - f(X_N \theta)||_2^2. \tag{10}$$

Recently, Zhuang et al. (2020) suggested a recursive formulation of the DNN weights. Using their scheme only one training sample is processed at a time: Denote the projection of a sample x onto the orthogonal subspace of the training set correlation matrix as

$$x_\perp = \left(I - X_N^+ X_N\right) x, \tag{11}$$

the update rule when receiving a new training sample with data x with label y is

$$\hat{\theta}(\mathcal{D}_N; x, y) = \hat{\theta}_N + g\left(f^{-1}(y) - x^\top \hat{\theta}_N\right), \quad g \triangleq \begin{cases} x_\perp, & x_\perp \neq 0 \\ \frac{1}{1 + x^\top X_N^+ X_N^{+\top} x} X_N^+ X_N^{+\top} x, & x_\perp = 0 \end{cases}. \tag{12}$$

where $\hat{\theta}_N$ is the ERM solution (the learned parameters based on N training samples $\mathcal{D}_N$). In their paper, Zhuang et al. (2020) applied this formulation for a DNN, layer by layer.

4   The pNML for a single layer NN

Intuitively, the pNML as stated in (7) can be described as follows: To assign a probability for a potential outcome, (i) add it to the training set with an arbitrary label, (ii) find the best-suited model, and (iii) take the probability it gives to the assumed label. Follow this procedure for every label and normalize to get a valid probability assignment. Use the log normalization factor as the confidence measure. This method can be extended to any general learning procedure that generates a prediction based on a training set. One such method is a single layer NN.

A single layer NN maps an input $x \in \mathcal{R}^M$ using the softmax function $\sigma(\cdot)$ to a probability vector which represents the probability assignment to one of C classes:

$$p_\theta(i|x) = \sigma(x^\top \theta)_i = \frac{e^{\theta_i^\top x}}{\sum_{j=1}^C e^{\theta_j^\top x}}, \quad i \in \{1, \ldots, C\}. \tag{13}$$

To align with the recursive formulation of (12), the label y is a one-hot vector with C elements and is represented by a row vector in the standard base $\{e_i\}_{i=1}^C$ (the i-th element is 1 and all others are 0). c stands for the true test label such that e_c is the one-hot vector of the true label. Also, the learnable parameters $\{\theta_i\}_{i=1}^C$ are the columns of the parameter matrix of (10).

We would like that the probability assignment of the true label to be 1. we define the following MSE minimization objective which is also known as the Brier score (Roulston, 2007)

$$\min_{\theta \in \Theta} \sum_{n=1}^N \left(1 - y_n \sigma\left(\theta^\top x_n\right)\right)^2. \tag{14}$$

This minimization is equivalent to minimizing the log-loss for a specific hypothesis set (see appendix A). The activation function and its inverse are

$$f(x^\top \theta, e_c) = e_c \sigma\left(\theta^\top x\right) = \sigma\left(\theta^\top x\right)_c, \quad z \triangleq f^{-1}\left(p_\theta(c|x)\right) = \ln p_\theta(c|x) + \ln \sum_{j=1}^C e^{\theta_j^\top x}. \tag{15}$$

To compute the genie, we assume that the label of the test sample is known and add it to the training set. We fit the model by optimizing the learnable parameters to minimize the loss of this new set.

Lemma 1. *Given test data x with label $y = e_c$, the genie prediction of the true label is*

$$p_{\hat{\theta}(\mathcal{D}_N; x, y = e_c)}(c|x) = \frac{p_c}{p_c + p_c^{x^\top g}(1 - p_c)} \tag{16}$$

where p_c is the probability assignment of the ERM model of the label c, and g is as defined in (12).

Proof. Using (12), the probability assignment of the genie can be written as follows.

$$p_{\hat{\theta}(\mathcal{D}_N; x, y = e_c)}(c|x) = \frac{e^{\hat{\theta}(\mathcal{D}_N; x, y = e_c)^\top x}}{\sum_{\substack{j=1 \\ j \neq c}}^C e^{\theta_j^\top x} + e^{\hat{\theta}(\mathcal{D}_N; x, y = e_c)^\top x}} = \frac{e^{x^\top[\theta_c + g(z - \theta_c^\top x)]}}{\sum_{j=1}^C e^{\theta_j^\top x} - e^{\theta_c^\top x} + e^{x^\top[\theta_c + g(z - \theta_c^\top x)]}} \tag{17}$$

The genie knows that that the true test label is e_c. The inverse activation function can be written as $z = \ln S$ where $S \triangleq \sum_{j=1}^C e^{\theta_j^\top x}$. The simplified numerator is

$$e^{\theta_c^\top x} e^{x^\top g(z - \theta_c^\top x)} = e^{\theta_c^\top x} \left[S e^{-\theta_c^\top x}\right]^{x^\top g} = S p_c^{-x^\top g} p_c. \tag{18}$$

Substituting to (17) and divide the numerator and denominator by S provides the result. □

The true test label is not available to a legit learner, therefore, in the pNML process, every possible label is taken into account. The pNML regret is the logarithm of the sum of models, each one trained with a different test label value.

Theorem 2. *Denote p_i as the ERM prediction of label i, the pNML regret of a single layer NN is*

$$\Gamma = \log \sum_{i=1}^C \frac{p_i}{p_i + p_i^{x^\top g}(1 - p_i)}. \tag{19}$$

Proof. The normalization factor is the sum of the probabilities assignment of models that were trained with a specific value of the test sample $K = \sum_{i=1}^C p_{\hat{\theta}(\mathcal{D}_N; x, y = e_i)}(i|x)$. Using Theorem 1, the log normalization factor is the pNML regret. With lemma 1, we get the explicit expression. □

The pNML probability assignment of label $i \in \{1, \ldots, C\}$ is the probability assignment of a model that was trained with that label divided by the normalization factor $q_{pNML}(i|x) = \frac{1}{K} p_{\hat{\theta}(\mathcal{D}_N;x,y)}(y|x)$.

Let u_m and h_m be the m-th eigenvector and eigenvalue of the training set data matrix such that for $r = rank\left(X_N^\top X_N\right)$ and $x_\perp = 0$, the quantity $x^\top g$ is

$$x^\top g = \frac{x^\top X_N^+ X_N^{+\top} x}{1 + x^\top X_N^+ X_N^{+\top} x} = \frac{\frac{1}{N} \sum_{m=1}^r \frac{1}{h_m^2} \left(x^\top u_m\right)^2}{1 + \frac{1}{N} \sum_{i=1}^r \frac{1}{h_m^2} \left(x^\top u_m\right)^2}, \quad \frac{1}{N} X_N^\top X_N \triangleq \sum_{i=1}^r h_m^2 u_m u_m^\top. \quad (20)$$

We make the following remarks.

1. If the test sample x lies mostly in the subspace spanned by the eigenvectors with large eigenvalues, $x^\top g$ is small and the corresponding regret is low $\lim_{x^\top g \to 0} \Gamma = 0$. In this case, the pNML prediction is similar to the genie and can be trusted.

2. Test input that resides is in the subspace that corresponds to the small eigenvalues produces a large $x^\top g$ and the maximal regret is obtained $\lim_{x^\top g \to \infty} \Gamma = \log C$. The prediction for this test sample cannot be trusted.

3. As the training set size (N) increases $x^\top g$ becomes smaller and the regret decreases.

4. If the ERM model assigns to one of the labels probability 1, then the regret is 0 no matter in which subspace the test vector lies.

4.1 Deep neural network adaptation

In the previous section, we derived the pNML for a single layer NN. We next show that our derivations can, in fact, be applied to *any pretrained NN*, without requiring additional parameters or extra data.

First extract the embeddings of the training set: Denote $\phi(\cdot)$ as the embedding creation (feature extraction) using a pretrained ERM model, propagate the training samples through the DNN up to the last layer and compute the inverse of the data matrix $\phi(X_N)^+ \phi(X_N)^{+\top}$. Then, given a specific test example x, extract its embedding $\phi(x)$ and its ERM probability assignment $\{p_i\}_{i=1}^C$. Finally calculate the regret as described in Theorem 1 using the training set and test embedding vectors.

We empirically found that norms of OOD embeddings are lower than those of IND samples. The regret depends on the norm of the test sample: For $0 < a < b$, the regret of ax is lower than the regret of bx. Hence, we normalize all embeddings (training, IND, and OOD) to have L^2 norms equal to 1.0.

Samples with a high regret value are considered samples with a large distance from the genie, the learner that knows the true label, and therefore the prediction cannot be trusted. Our proposed method utilizes this regret value to determine whether a test data item represents a known or an unknown.

The limitation of our approach is that we derived the pNML regret for a single layer NN. This means we reduce the hypothesis set that the genie can choose from. We believe that extending the analytical result to more layers would improve the performance. In addition, we derive the regret for the Brier score and not the log loss that is used in practice. In appendix A we show that minimizing the Brier score is equivalent to minimizing the log loss of a specific hypothesis set (the Gaussian family).

Figure 1: A single layer NN fitted to low dimensional data (the Iris flower set (Fisher, 1936)). (Left) The ERM probability assignment of class c_2 of the fitted model. (Right) The pNML regret. The training data of class c_1 and c_2 are marked with red circles and red crosses respectively.

5 Low dimension data simulation

In this section, we provide a visualization of the pNML regret on a low-dimensional dataset. We demonstrate the characteristic of the derived regret and show in what situations the prediction of the test sample can be trusted. We use the Iris flower data set (Fisher, 1936) with two classes and two features and name them c_1, c_2, and feature 1, feature 2 respectively.

Figure 1a shows the ERM probability assignment of class c_2 for a single layer NN that was fitted to the training data, which are marked in red. At the top left and bottom right, the model predicts with high probability that a sample from these areas belongs to class c_1 and c_2 respectively.

Figure 1b presents the analytical pNML regret. At the upper left and lower right, the regret is low: Although there are no training samples there, these regions are far from the decision boundary, adding one sample would not alter the probability assignment significantly, thus the pNML prediction is close to the genie. At the top right and bottom left, there are no training points therefore the regret is relatively high and the confidence in the prediction is low. In the next section, we show that these test samples, which are associated with high regret, can be classified as OOD samples.

6 Application to out-of-distribution detection

In this section, we show the effectiveness of the pNML regret for OOD detection. The motivation for using the individual setting and the pNML as its solution for OOD detection is that in the individual setting there is no assumption on the way the data is generated. The absence of assumption means that the result holds for a wide range of scenarios (PAC, stochastic, and even adversary) and specifically to OOD detection, where the OOD samples are drawn from an unknown distribution.

Table 1: OOD detection AUROC comparison for DenseNet-BC-100. We build upon the pretrained models of the compared methods. Our pNML regret (marked +pNML) improves all IND-OOD combinations, up to 69.4%, 49.4%, 3.1%, 2.2% for Baseline, ODIN, Gram, and OECC respectively.

IND	OOD	Baseline/+pNML	ODIN/+pNML	Gram/+pNML	OECC/+pNML
CIFAR-100	iSUN	69.7 / **96.4**	84.5 / **96.7**	99.0 / **99.5**	99.2 / **99.5**
	LSUN (R)	70.8 / **96.6**	86.0 / **96.9**	99.3 / **99.7**	99.4 / **99.6**
	LSUN (C)	80.1 / **93.1**	91.5 / **93.1**	91.4 / **94.5**	93.9 / **96.1**
	Imagenet (R)	71.6 / **97.4**	85.5 / **97.6**	99.0 / **99.5**	99.0 / **99.5**
	Imagenet (C)	76.2 / **95.7**	88.8 / **96.0**	97.7 / **98.7**	98.2 / **99.0**
	Uniform	43.3 / **100**	83.7 / **100**	100 / **100**	99.9 / **100**
	Gaussian	30.6 / **100**	50.6 / **100**	100 / **100**	100 / **100**
	SVHN	82.6 / **96.2**	92.5 / **96.2**	97.3 / **98.4**	97.0 / **97.5**
CIFAR-10	iSUN	94.8 / **98.7**	98.9 / **98.9**	99.8 / **100**	99.9 / **100**
	LSUN (R)	95.5 / **98.9**	99.2 / **99.2**	99.9 / **100**	99.9 / **100**
	LSUN (C)	93.0 / **96.4**	95.8 / **96.4**	97.5 / **98.7**	98.9 / **99.9**
	Imagenet (R)	94.1 / **98.8**	98.5 / **99.0**	99.7 / **99.9**	99.8 / **99.9**
	Imagenet (C)	93.8 / **97.7**	97.6 / **97.9**	99.3 / **99.7**	99.5 / **99.9**
	Uniform	96.6 / **100**	100 / **100**	100 / **100**	100 / **100**
	Gaussian	97.6 / **100**	100 / **100**	100 / **100**	100 / **100**
	SVHN	89.9 / **98.4**	94.6 / **98.7**	99.1 / **99.6**	99.6 / **100**
SVHN	iSUN	94.4 / **98.7**	92.8 / **99.1**	99.8 / **99.9**	100 / **100**
	LSUN (R)	94.1 / **98.4**	92.5 / **98.9**	99.8 / **100**	100 / **100**
	LSUN (C)	92.9 / **98.0**	88.6 / **98.1**	98.6 / **99.4**	99.8 / **100**
	Imagenet (R)	94.8 / **98.6**	93.3 / **99.0**	99.7 / **99.9**	100 / **100**
	Imagenet (C)	94.6 / **98.6**	92.8 / **98.8**	99.4 / **99.8**	100 / **100**
	Uniform	93.2 / **99.8**	91.6 / **100**	99.9 / **100**	100 / **100**
	Gaussian	97.4 / **99.8**	98.9 / **99.9**	100 / **100**	100 / **100**
	CIFAR-10	91.8 / **96.7**	88.9 / **97.8**	95.4 / **97.3**	99.5 / **100**
	CIFAR-100	91.4 / **96.7**	88.2 / **97.8**	96.4 / **98.0**	99.6 / **100**

Table 2: OOD detection AUROC comparison for ResNet-34. We build upon the pretrained models of the compared methods. Our pNML regret (marked +pNML) improves nearly all IND-OOD combinations, up to 41.5%, 11.9%, 2.4%, 2.1% for Baseline, ODIN, Gram, and OECC respectively.

IND	OOD	Baseline/+pNML	ODIN/+pNML	Gram/+pNML	OECC/+pNML
CIFAR-100	iSUN	75.7 / **83.0**	85.6 / **87.6**	98.8 / **99.1**	99.0 / **99.3**
	LSUN (R)	75.6 / **83.8**	85.4 / **88.0**	99.2 / **99.4**	99.3 / **99.6**
	LSUN (C)	75.5 / **83.1**	82.6 / **88.1**	92.2 / **94.6**	95.7 / **97.8**
	Imagenet (R)	77.1 / **84.4**	87.7 / **88.5**	98.9 / **99.2**	98.7 / **98.9**
	Imagenet (C)	79.6 / **85.8**	85.6 / **88.6**	97.7 / **98.4**	97.9 / **98.1**
	Uniform	85.2 / **98.1**	99.0 / **99.4**	100 / **100**	100 / **100**
	Gaussian	45.0 / **86.5**	83.8 / **95.7**	100 / **100**	100 / **100**
	SVHN	79.3 / **90.9**	94.0 / **95.4**	96.0 / **97.9**	97.0 / **97.6**
CIFAR-10	iSUN	91.0 / **96.4**	94.0 / **97.5**	99.8 / **100**	99.9 / **99.9**
	LSUN (R)	91.1 / **96.6**	94.1 / **97.7**	99.9 / **100**	**100** / 99.9
	LSUN (C)	91.8 / **95.4**	93.6 / **95.6**	97.9 / **99.1**	99.1 / **99.5**
	Imagenet (R)	91.0 / **95.4**	93.9 / **96.6**	99.7 / **99.9**	99.9 / **99.9**
	Imagenet (C)	91.4 / **95.4**	93.3 / **96.2**	99.3 / **99.7**	99.7 / **99.8**
	Uniform	96.1 / **99.8**	99.9 / **100**	100 / **100**	100 / **100**
	Gaussian	97.5 / **100**	100 / **100**	100 / **100**	100 / **100**
	SVHN	89.9 / **95.1**	95.8 / **97.9**	99.5 / **99.8**	99.8 / **99.8**
SVHN	iSUN	92.2 / **97.1**	91.4 / **98.0**	99.8 / **99.9**	100 / **100**
	LSUN (R)	91.5 / **96.7**	90.6 / **97.7**	99.8 / **100**	100 / **100**
	LSUN (C)	92.8 / **97.0**	92.3 / **97.1**	98.8 / **99.6**	99.7 / **99.9**
	Imagenet (R)	93.5 / **97.5**	92.8 / **98.3**	99.8 / **99.9**	100 / **100**
	Imagenet (C)	94.2 / **97.5**	93.7 / **98.2**	99.5 / **99.9**	99.9 / **100**
	Uniform	96.0 / **98.5**	95.5 / **99.5**	100 / **100**	100 / **100**
	Gaussian	96.1 / **98.4**	96.1 / **99.6**	100 / **100**	100 / **100**
	CIFAR-10	93.0 / **97.4**	92.0 / **98.0**	97.4 / **99.3**	99.4 / **99.8**
	CIFAR-100	92.5 / **97.1**	91.7 / **97.8**	97.5 / **99.2**	99.4 / **99.8**

6.1 Experimental setup

We follow the standard experimental setup (Sastry and Oore, 2020; Lee et al., 2018). All the assets we used are open-sourced with either Apache-2.0 License or Attribution-NonCommercial 4.0 International licenses. We ran all experiments on NVIDIA K80 GPU.

IND sets. For datasets that represent known classes, we use CIFAR-100, CIFAR-10 (Krizhevsky et al., 2014) and SVHN (Netzer et al., 2011). These sets contain RGB images with 32x32 pixels.

OOD sets. The OOD sets are represented by TinyImageNet (Liang et al., 2018), LSUN (Yu et al., 2015), iSUN (Xu et al., 2015), Uniform noise images, and Gaussian noise images. We use two variants of TinyImageNet and LSUN sets: a 32x32 image crop that is represented by "(C)" and a resizing of the images to 32x32 pixels that termed by "(R)". We also used CIFAR-100, CIFAR-10, and SVHN as OOD for models that were not trained with them.

Evaluation methodology. We benchmark our approach by adopting the following metrics (Sastry and Oore, 2020; Lee et al., 2018): (i) AUROC: The area under the receiver operating characteristic curve of a threshold-based detector. A perfect detector corresponds to an AUROC score of 100%. (ii) TNR at 95% TPR: The probability that an OOD sample is correctly identified (classified as negative) when the true positive rate equals 95%. (iii) Detection accuracy: Measures the maximum possible classification accuracy over all possible thresholds.

6.2 Results

We build upon the existing leading methods: Baseline (Hendrycks and Gimpel, 2017), ODIN (Liang et al., 2018), Gram (Sastry and Oore, 2020), OECC (Papadopoulos et al., 2021), and Energy (Liu et al., 2020). We use the following pretrained models: ResNet-34 (He et al., 2016), DenseNet-BC-100 (Huang et al., 2017) and WideResNet-40 (Zagoruyko and Komodakis, 2016). Training was

Table 3: **WideResNet-40 performance**. The compared method is Energy (Liu et al., 2020)

IND	OOD	AUROC	TNR at TPR 95%	Detection Acc.
		Energy/+pNML		
CIFAR-100	iSUN	78.4 / **93.6**	30.7 / **62.5**	71.1 / **87.0**
	LSUN (R)	80.3 / **94.1**	31.2 / **65.5**	73.1 / **87.5**
	LSUN (C)	**95.9** / 95.5	**80.0** / 79.3	**89.3** / 89.1
	Imagenet (R)	71.4 / **87.0**	22.1 / **44.8**	66.1 / **79.9**
	Imagenet (C)	79.7 / **87.3**	36.9 / **49.4**	72.8 / **79.7**
	Uniform	97.9 / **99.8**	95.2 / **100**	95.8 / **99.6**
	Gaussian	92.0 / **99.8**	9.6 / **100**	92.3 / **99.8**
	SVHN	**96.5** / 96.4	79.2 / **82.8**	90.5 / **91.3**
CIFAR-10	iSUN	99.3 / **99.4**	98.3 / **98.7**	96.7 / **97.0**
	LSUN (R)	99.3 / **99.5**	98.6 / **99.0**	97.0 / **97.3**
	LSUN (C)	99.4 / **99.5**	98.6 / **98.6**	97.0 / **97.1**
	Imagenet (R)	98.1 / **98.1**	92.0 / **92.4**	94.0 / **94.0**
	Imagenet (C)	98.6 / **98.6**	94.4 / **94.6**	94.9 / **94.9**
	Uniform	99.0 / **99.9**	100 / **100**	98.7 / **99.8**
	Gaussian	99.1 / **99.9**	100 / **100**	98.7 / **99.8**
	SVHN	99.3 / **99.6**	98.3 / **98.9**	96.9 / **97.6**

performed using CIFAR-100, CIFAR-10 and SVHN, each training set used separately to provide a complete picture of our proposed method's capabilities. Notice that ODIN, OECC, and Energy methods use OOD sets during training and the Gram method requires IND validation samples.

Table 1 and Table 2 show the AUROC of different OOD sets for DenseNet and ResNet models respectively. Our approach improves all the compared methods in nearly all combinations of IND-OOD sets. The largest AUROC gain over the current state-of-the-art is of CIFAR-100 as IND and LSUN (C) as OOD: For the DenseNet model, we improve Gram and OECC method by 3.1% and 2.2% respectively. For the ResNet model, we improve this combination by 2.4% and 2.1% respectively. The additional metrics (TNR at 95% FPR and detection accuracy) are shown in appendix E.

The standard ERM model when combined with the pNML regret as seen in the Baseline+pNML column is comparable to the more sophisticated methods: Although it lacks tunable parameters, Baseline+pNML outperforms the ODIN method in most DenseNet IND-OOD set combinations.

Table 3 shows the results of the Energy and Energy+pNML methods with WideResNet-40 model on CIFAR-100 and CIFAR-10 set as IND. Our method improves the AUROC of the OOD detection task in most combinations of IND and OOD up to 15.2% in the CIFAR-100 and iSUN combination.

7 Conclusions

We derived the analytical expression of the pNML regret for a single layer NN. We showed that the model generalizes well when the test data resides in a subspace spanned by the eigenvectors associated with the large eigenvalues of the training data correlation matrix. We demonstrated how to apply the pNML for DNN with neither additional parameters nor extra data. For ODD detection, we showed that the pNML regret improves the absolute AUROC value of the recent leading methods Gram, OECC, and Energy up to 3.1%, 2.2%, 15.2% respectively.

As for future work, the derived regret can be used for various tasks: active learning, probability calibration, and adversarial attack. Also, we would like to extend the derived regret to DNN.

Societal impacts. The negative social impact of this work depends on the application. For instance, in a surveillance camera scenario, a person from a minority group can be flagged as OOD if the minority group was not included in the training set. We recommend that when OOD is flagged a human will intervene rather than algorithmic response since the nature of the OOD is unknown.

References

Bartlett, P. L., Foster, D. J., and Telgarsky, M. (2017). Spectrally-normalized margin bounds for neural networks. In *Neural Inform. Process. Syst.*, pages 6240–6249.

Belkin, M., Hsu, D., Ma, S., and Mandal, S. (2019). Reconciling modern machine-learning practice and the classical bias–variance trade-off. *Proceedings of the National Academy of Sciences*, 116(32):15849–15854.

Bibas, K. and Feder, M. (2021). The predictive normalized maximum likelihood for over-parameterized linear regression with norm constraint: Regret and double descent. *arXiv preprint arXiv:2102.07181*.

Bibas, K., Fogel, Y., and Feder, M. (2019a). Deep pnml: Predictive normalized maximum likelihood for deep neural networks. *arXiv preprint arXiv:1904.12286*.

Bibas, K., Fogel, Y., and Feder, M. (2019b). A new look at an old problem: A universal learning approach to linear regression. *Int. Symp. on Information Theory*.

Fisher, R. A. (1936). The use of multiple measurements in taxonomic problems. *Annals of eugenics*, 7(2):179–188.

Fogel, Y. and Feder, M. (2018). Universal batch learning with log-loss. In *Int. Symp. on Information Theory*, pages 21–25. IEEE.

Fu, J. and Levine, S. (2021). Offline model-based optimization via normalized maximum likelihood estimation. In *Int. Conf. on Learning Representations*.

He, K., Zhang, X., Ren, S., and Sun, J. (2016). Deep residual learning for image recognition. In *Proc. Conf. Comput. Vision Pattern Recognition*, pages 770–778.

Hendrycks, D. and Gimpel, K. (2017). A baseline for detecting misclassified and out-of-distribution examples in neural networks. *Int. Conf. on Learning Representations*.

Huang, G., Liu, Z., van der Maaten, L., and Weinberger, K. Q. (2017). Densely connected convolutional networks. In *Proc. Conf. Comput. Vision Pattern Recognition*.

Jiang, Y., Neyshabur, B., Mobahi, H., Krishnan, D., and Bengio, S. (2020). Fantastic generalization measures and where to find them. In *Int. Conf. on Learning Representations*.

Krizhevsky, A., Nair, V., and Hinton, G. (2014). The cifar-10 dataset. *online: http://www. cs. toronto. edu/kriz/cifar. html*.

Lee, K., Lee, K., Lee, H., and Shin, J. (2018). A simple unified framework for detecting out-of-distribution samples and adversarial attacks. In *Neural Inform. Process. Syst.*

Liang, S., Li, Y., and Srikant, R. (2018). Enhancing the reliability of out-of-distribution image detection in neural networks. In *Int. Conf. on Learning Representations*.

Liu, W., Wang, X., Owens, J., and Li, Y. (2020). Energy-based out-of-distribution detection. *Advances in Neural Information Processing Systems*.

Merhav, N. and Feder, M. (1998). Universal prediction. *Trans. on Inform. Theory*, 44(6):2124–2147.

Netzer, Y., Wang, T., Coates, A., Bissacco, A., Wu, B., and Ng, A. Y. (2011). Reading digits in natural images with unsupervised feature learning. In *Neural Inform. Process. Syst. Workshops*, volume 2011, page 5.

Neyshabur, B., Bhojanapalli, S., and Srebro, N. (2018). A pac-bayesian approach to spectrally-normalized margin bounds for neural networks. In *Int. Conf. on Learning Representations*.

Papadopoulos, A.-A., Rajati, M. R., Shaikh, N., and Wang, J. (2021). Outlier exposure with confidence control for out-of-distribution detection. *Neurocomputing*.

Rissanen, J. and Roos, T. (2007). Conditional nml universal models. In *2007 Information Theory and Applications Workshop*, pages 337–341. IEEE.

Roos, T. and Rissanen, J. (2008). On sequentially normalized maximum likelihood models. *Compare*, 27(31):256.

Rosas, F. E., Mediano, P. A., and Gastpar, M. (2020). Learning, compression, and leakage: Minimizing classification error via meta-universal compression principles. *arXiv preprint arXiv:2010.07382*.

Roulston, M. S. (2007). Performance targets and the brier score. *Meteorological Applications: A journal of forecasting, practical applications, training techniques and modelling*, 14(2):185–194.

Sastry, C. S. and Oore, S. (2020). Detecting out-of-distribution examples with Gram matrices. In *Int. Conf. Mach. Learning*.

Singh, A., Sengupta, S., Rasheed, M. A., Jayakumar, V., and Lakshminarayanan, V. (2021). Uncertainty aware and explainable diagnosis of retinal disease. In *Medical Imaging 2021: Imaging Informatics for Healthcare, Research, and Applications*, volume 11601, page 116010J. International Society for Optics and Photonics.

Vapnik, V. N. and Chervonenkis, A. Y. (2015). On the uniform convergence of relative frequencies of events to their probabilities. In *Measures of complexity*, pages 11–30. Springer.

Vyas, A., Jammalamadaka, N., Zhu, X., Das, D., Kaul, B., and Willke, T. L. (2018). Out-of-distribution detection using an ensemble of self supervised leave-out classifiers. In *European Conf. Comput. Vision*, pages 560–574.

Willers, O., Sudholt, S., Raafatnia, S., and Abrecht, S. (2020). Safety concerns and mitigation approaches regarding the use of deep learning in safety-critical perception tasks. In *International Conference on Computer Safety, Reliability, and Security*, pages 336–350. Springer.

Xu, P., Ehinger, K. A., Zhang, Y., Finkelstein, A., Kulkarni, S. R., and Xiao, J. (2015). Turkergaze: Crowdsourcing saliency with webcam based eye tracking. *arXiv preprint arXiv:1504.06755*.

Yu, F., Zhang, Y., Song, S., Seff, A., and Xiao, J. (2015). Lsun: Construction of a large-scale image dataset using deep learning with humans in the loop. *arXiv preprint arXiv:1506.03365*.

Zagoruyko, S. and Komodakis, N. (2016). Wide residual networks. In *Proc. British Mach. Vision Conf.*

Zhang, J. (2012). Model selection with informative normalized maximum likelihood: Data prior and model prior. In *Descriptive and normative approaches to human behavior*, pages 303–319. World Scientific.

Zhong, K., Song, Z., Jain, P., Bartlett, P. L., and Dhillon, I. S. (2017). Recovery guarantees for one-hidden-layer neural networks. In *Int. Conf. Mach. Learning*, pages 4140–4149.

Zhou, A. and Levine, S. (2020). Amortized conditional normalized maximum likelihood. *arXiv preprint arXiv:2011.02696*.

Zhuang, H., Lin, Z., and Toh, K.-A. (2020). Training a multilayer network with low-memory kernel-and-range projection. *Journal of the Franklin Institute*, 357(1):522–550.