Emergent Communication of Generalizations

Abstract

To build agents that can collaborate effectively with others, recent research has trained artificial agents to communicate with each other in Lewis-style referential games. However, this often leads to successful but uninterpretable communication. We argue that this is due to the game objective: communicating about a single object in a shared visual context is prone to overfitting and does not encourage language useful beyond concrete reference. In contrast, human language conveys a rich variety of abstract ideas. To promote such skills, we propose games that require communicating generalizations over *sets* of objects representing abstract visual concepts, optionally with separate contexts for each agent. We find that these games greatly improve systematicity and interpretability of the learned languages, according to several metrics in the literature. Finally, we propose a method for identifying logical operations embedded in the emergent languages by learning an approximate compositional reconstruction of the language.

1   Introduction

The communication systems that emerge when two agents are trained to cooperate offer a window on the evolution of human language, as well as a promising avenue for improving the collaboration abilities of artificial agents. Much recent work studies Lewis-style [20] signaling games (Figure 1a), where agents are trained to refer to a single object in a shared visual context. However, a general consensus of this work is that without careful environmental pressures, agents develop successful but uninterpretable communication schemes distinctly unlike human language [1, 4, 5, 13, 17].

We argue that the reference games typically used in these studies are ill-suited to drive linguistic systematicity for two reasons. One is perceptual: agents can exploit inscrutable patterns in single inputs, which leads to communication via spurious features [2]. The other reason is cognitive: human language can convey abstract ideas, such as kinds and causes, not only reference to specific objects. Simple reference games are unlikely to drive emergence of such abstract language. In particular, *generalizations* over categories are a crucial part of language [25], helping us transfer knowledge that may be useful in the future. For example, we would like to teach our kin not just to avoid one specific lion, but to avoid all lions, including those that have not yet been seen. Some have even argued that language emerged precisely from this need to teach hard-won generalizations to others [16]. With this idea in mind, can we design an experimental setting that better catalyzes these abilities?

In this paper, we propose extensions of Lewis-style signaling games to *sets*. In the *set reference* (setref) game, a teacher must communicate to a student not just a single object, but rather a group of objects belonging to a concept (Figure 1b). In the *concept* game, each agent sees different examples of the concept (Figure 1c). Inspired by human teaching [8], our core insight is that requiring generalization to combinatorially large sets of (possibly unseen) objects encourages agents to learn and communicate rich abstractions across inputs (e.g. *seagulls*), instead of low-level features (e.g. *color #FDA448*). These tasks are more difficult than traditional reference games, and we will show with a variety of metrics that the learned languages are more systematic, compositional, and interpretable. Finally, the

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

(a) reference   (b) set reference   (c) concept

Figure 1: Communication games for the concept *red triangle*. Given a set of targets (red borders) and distractors, a **teacher** must send a message to help a **student** identify the targets. In (a) reference games, targets are identical; in (b) set reference (setref) games, there are multiple targets; and in (c) concept games, the agents see different inputs.

rich compositional space of concepts explored in these games allows us to probe for specific logical operators in the emergent language. We propose a method for doing so, thereby demonstrating how the emergent languages reflect the compositional structure of their inputs.

2 Communication Games

First imagine a generic communication game between a teacher T and student S. Let $G = (c, X^T, Y^T, X^S, Y^S)$ be a communication game, where $c : \mathcal{X} \mapsto \{0, 1\}$ is a latent concept to be communicated, $X^T = \{x_1^T, \dots, x_n^T\}$ is a set of n inputs presented to the teacher, and $Y^T = \{y_1^T, \dots, y_n^T\}$ is a set of labels for the teachers' inputs, defined as $y_i^T = c(x_i^T)$. We call x_i^T a *target* if $y_i^T = 1$, which indicates that x_i^T is a member of the concept c; otherwise x_i^T is a *distractor* and $y_i^T = 0$. X^S and Y^S are defined similarly for the student. Given its targets and distractors (but not the latent concept c), the teacher must send a message m to a student that allows them to correctly identify their own targets, where $m = (m_1, \dots, m_n)$ is a discrete sequence over a fixed alphabet $m_i \in \mathcal{M}$. Now we can define variants of this communication game as follows:

Reference game. In basic reference games, the teacher and student see the same examples ($X^T = X^S$, $Y^T = Y^S$) and there is a single (repeated) target: $x_i^T = x_j^T$ for all i, j where $y_i^T = y_j^T = 1$.[1]

Set reference (setref) game. Now we extend our game to *sets*: the teacher and student see the same examples, but there are multiple target images encoding the concept (e.g. different *red triangles*).

Concept game. Finally, we propose the more abstract concept game, where the teacher and student see *different examples* ($X^T \neq X^S$, $Y^T \neq Y^S$) of the same concept. When X^T and Y^T contain a single positive and negative example, this is a reference game with separate inputs for each agent, a setup which has been shown to encourage linguistic systematicity in some settings [7, 18, 19].

3 Models

Now we will formalize our models of the teacher and student. Given a communication game G, a teacher is defined as a distribution over messages given inputs $p^T(m \mid X^T, Y^T)$, and a student is a distribution over targets given a message: $p^S(Y^S \mid X^S, m) = \prod_i p^S(y_i^S \mid x_i^S, m)$.

Teacher. The teacher encodes all inputs with a convolutional neural network (CNN) f_θ^T; embeddings for targets and distractors are averaged to form target and distractor *prototype* embeddings [24], which then conditions a recurrent neural network (RNN) used to produce the message. Let X_+^T and X_-^T denote the sets of targets and distractors in X^T; then define a prototype embedding

---

[1]For the most consistent comparison across games, we present an atypical formulation of a reference game with multiple identical targets and student target decisions made independently for each input, instead of the single-target forced-choice setting. Appendix D shows results with traditional games trained with cross entropy loss; qualitative conclusions remain unchanged.

Figure 2: Example games, with targets (red border) and distractors for the ShapeWorld concept *blue OR rectangle* (left) and the Birds concept *painted bunting* (right). Concepts are represented as intensional logical formulas (top) or extensional sets of boolean input features (bottom), where each vector is the binary representation of an individual member of the concept (e.g. *blue rectangle*, or the labeled attributes of one particular bird). See Figure S1 in Appendix A for additional game examples.

$\mathbf{x}_+^T = \frac{1}{|X_+^T|} \sum_{x_i \in X_+^T} f_\theta^T(x_i)$ (analogously for $\mathbf{x}_-^T$). Then $p^T(m \mid X^T, Y^T) = p_{\text{RNN-DECODE}}(m \mid \text{proj}([\mathbf{x}_+^T; \mathbf{x}_-^T]))$ where proj is a linear projection to the RNN hidden state.

Student. The student takes a message and makes predictions about the labels $\hat{y}_i^S$ independently for each input x_i^S. Given the teacher message and an input image, define $p^S(y_i^S \mid x_i^S, m) = \sigma(\text{RNN-ENCODE}(m) \cdot f_\phi^S(x_i^S))$, where f_ϕ^S is a separate CNN for the student.

We jointly train a teacher-student pair, including the vision modules and communication protocol, with stochastic gradient descent to maximize the student likelihood of selecting the correct target images. Formally, the loss for a single game is

$$\mathcal{L}(T, S, G) = -\sum_i \log p^S(y_i^S \mid x_i^S, \hat{m}), \quad \hat{m} \sim p^T(m \mid X^T, Y^T). \tag{1}$$

To maintain backwards differentiability, we use the straight-through Gumbel-Softmax [11] trick with $\tau = 1$, simulating samples from the teacher distribution over tokens via softmax and discretizing in the forward pass only. For full model and training details and a link to code, see Appendix A.

4 Tasks

We examine the languages developed for our proposed communication games over two datasets: first, an artificial shape dataset which allows us to evaluate communication over cleanly defined logical concepts; second, a dataset of birds to test agents' ability to learn concepts from realistic visual input.

ShapeWorld. We use the ShapeWorld visual reasoning dataset [15] (Figure 2, left). For reference games, target images are a single object, defined by a conjunction of a shape and a color (e.g. *red triangle*, *green square*); of the 30 possible shapes, we hold out 20% for testing. For setref and concept games, concepts include the conjunctions tested in reference games, but also primitive concepts (e.g. *blue shapes*) and arbitrary disjunctions or conjunctions of (possibly negated) shapes and/or colors. This produces 312 concepts, 20% of which are held out for testing. These more general concepts cannot be tested in reference games, since a single object is always identified by a shape and color. This rules out disjunctive concepts like *red OR blue* that only make sense across multiple objects. Similarly, since there are no reference game targets that have color but not shape, we can never guarantee that a message for a reference game only carries the semantics *blue* and not, for example, *blue circle*, if the target image is a blue circle. By looking at sets, setref and concept games allow us to more precisely control the semantics of the concepts in each game.

Each game consists of 10 targets depicting shapes satisfying the concept, and 10 distractors. We specifically sample "hard" targets and distractors to test understanding of conjunctions or disjunctions (see Appendix B for details). Finally, we specify an agent vocabulary of 14 tokens and maximum length 5, so that the communication channel has the same bandwidth as the true concept formulas;[2] see Appendix C for experiments varying these parameters for both this dataset and the next one.

Birds. We next use the Caltech-UCSD Birds dataset [28] which contains 200 classes of birds with 40–60 images (Figure 2, right). As before, reference games involve a single target; setref and concept

---

[2]In the true concept formulas there are 5 shapes, 6 colors, and the 3 AND/OR/NOT operators, i.e. 14 tokens; and the longest concept formulas have the form *NOT x AND NOT y*, i.e. length 5.

game targets are members of a specific bird class. We use 100 classes at train and 50 at test, sampling
5 targets and 5 distractors per game. The dataset contains boolean attributes (e.g. *beak*, *size*) for
individual birds and classes.[3] Thus, we represent reference game concepts as the feature vector of the
target bird, and setref/concept game concepts as the feature vector of the class. In our evaluation, we
will measure how well the languages capture these features. As there is no reference language for this
task, we set the vocabulary size to 20 and the message length to 8 (though again see Appendix C).

5 Evaluation

We first measure communication success, as defined by student accuracy on held-out games from
seen and unseen concepts, with the unseen concepts testing a language's ability to generalize
compositionally. Ultimately, however, we are interested in the systematicity of the learned languages,
which we evaluate via the following measures:

Information theoretic measures. We first ignore the specific content of messages and concepts,
and simply compute simple information theoretic quantities, by treating each distinct message and
concept as a unique value and imagining probability distributions over these values. First, we measure
the **conditional entropy** of teacher messages given concepts, $H(M \mid C)$, averaged across seen and
unseen games; lower entropy indicates that agents use more consistent language for a fixed concept.
However, $H(M \mid C)$ measures systematicity only in one direction; as a more symmetric measure,
we also use the **adjusted mutual information**

$$\text{AMI}(M, C) = (I(M, C) - \mathbb{E}(I(M, C))) / (\max(H(M), H(C)) - \mathbb{E}(I(M, C))). \quad (2)$$

Here, $\mathbb{E}(I(M, C))$ is evaluated with respect to a hypergeometric model of randomness, where M
and C are assumed to be random permutations subject to the number of unique values in either
set [27]. AMI $\in [0, 1]$ represents the mutual information between M and C, adjusted for chance
to maintain comparability across different distributions of messages and concepts. A higher score
indicates overall higher alignment between messages and concepts.

Topographic ρ. To more precisely measure the lexical compositionality of a language, a measure
often used in the literature is *topographic* ρ [3, 17, 19, 21], which quantifies the agreement between
two representational systems a la Representational Similarity Analysis [14]. We define a distance
metric between game concepts $d_C(c_i, c_j)$ and another between agent messages $d_M(m_i, m_j)$, compute
pairwise distances between concepts and between messages, and measure their alignment with
Spearman's ρ. A high ρ indicates that a teacher sends lexically similar messages for similar concepts.

For our distance function on messages, we use the **Edit** (i.e. Levenshtein) distance with equal
insert/delete/replace costs. For distances between game concepts, we define two distances based on
intensional and extensional representations of concepts (Figure 2). First, we use the word-level **Edit**
distance between string representations of logical formulas. Second, we use the **Hausdorff** distance
d_H, a distance function between sets of members of a concept. Let $Z^a = \{z_1^a, \ldots, z_n^a\}$ be the set
of feature-based boolean representations of inputs belonging to concept a. For ShapeWorld, these
are two-hot vectors denoting the color and shape of all objects belonging to a specific formula; for
example, for the concept *red*, we have vectors for *red triangle*, *red circle*, and so on. For Birds, these
are boolean vectors of the attributes of each individual bird of a species. Then the Hausdorff distance
d_H is the maximum distance from any point in one set to the closest point in the other: $d_H(Z^a, Z^b) =$
$\max(\sup_i d(z_i^a, Z^b), \sup_j d(z_j^b, Z^a))$, where $d(a, B) = \inf_{b \in B} \text{EditDistance}(a, b)$.

6 Results

Table 1 shows test accuracy on communication games over seen and unseen concepts for 5 models
trained in each conditions. Reference game performance is high across both datasets, and agents are
able to generalize well to unseen games at test time. Accuracy on setref and concept games are lower
for both datasets, with somewhat lower performance on novel games for both Birds and ShapeWorld.
Overall, communicating sets seems to be a much harder task than specific reference.

---

[3] Feature vectors for individual birds in a class vary due to the visibility of features in the image; class vectors
are averaged across all individual birds, then rounded to 1 or 0.

Table 1: Student accuracy (seen and unseen concepts, where chance accuracy is 50%), conditional entropy of messages given concepts (lower is better), and adjusted mutual information score (higher is better), with (SD) across 5 runs.

Dataset	Game	Acc (Seen)	Acc (Unseen)	$H(M \mid C)$	$\text{AMI}(M, C)$
ShapeWorld	Ref	**97** (0.4)	**98** (0.3)	7.3 (0.2)	0.04 (0.00)
	Setref	92 (2.2)	87 (1.6)	3.9 (0.6)	0.59 (0.08)
	Concept	88 (3.4)	75 (3.0)	**2.4** (0.2)	**0.66** (0.07)
Birds	Ref	**93** (0.3)	**89** (0.1)	5.9 (0.2)	0.05 (0.00)
	Setref	89 (0.2)	78 (0.2)	5.2 (0.1)	0.17 (0.02)
	Concept	88 (0.1)	73 (0.3)	**4.1** (0.2)	**0.26** (0.02)

The ability to communicate accurately, even on unseen concepts, is not necessarily indicative of more *systematic* communication; generalization without compositional language is a common finding in the literature [1, 5, 13, 19]. Instead, we find that the more difficult games produce more systematic language. For ShapeWorld, concept game entropy over messages is lower than reference game entropy (2.4 vs. 7.3), and AMI is higher (0.66 vs. 0.04), with setref in the middle; this pattern also occurs in Birds. Furthermore, Figure 3 shows that topographic ρ between the languages and the (Edit and Hausdorff) concept distances is higher for concept and setref than ref, throughout training.

Figure 4 (more examples in Appendix E) shows messages generated by agents for concepts in both games, where we arbitrarily assign letters to agent "words" to assist with interpretation. For example, for concept game teachers conveying the concept *red AND triangle*, the innermost circle is largely red, indicating that the majority of messages sent for this concept begin with d; proceeding outward, we see blue regions indicating the token e. Thus, concept agents consistently use the 5-token sequence deeee to refer to red triangles (less commonly, edeee). In contrast, for different red triangles, the language of reference game agents is strikingly inconsistent, as indicated by the extreme diversity of colors, while setref language is somewhere in the middle. The entropies over the message distributions for these concepts correlate with the "busyness" of the plots, reinforcing the idea that the setref and concept languages are more consistent.

6.1 Set Size

The difference between reference and setref/concept games can be interpreted as a continuum, ranging from referring to a single object (reference) to referring to a potentially infinite number of objects. With a small number of objects, it may still be possible to communicate only low-level, non-generalizeable features of the set, similar to the strategies adopted by our reference game agents. In contrast, increasingly large numbers of objects should put further pressures on the semantics of the messages to not refer to individual inputs, but rather entire categories.

In Figure 5, we confirm this hypothesis, showing how increasing the number of targets n (with equal numbers of distractors) increases language systematicity. n has a statistically significant effect on topographic ρ for ShapeWorld setref (Spearman $\rho = 0.39, p = 0.029$) and concept ($\rho = 0.75, p < 10^{-5}$) and Birds setref ($\rho = 0.90, p < 10^{-7}$) and concept ($\rho = 0.51, p = 0.024$). When $n = 1$, the setref game is equivalent to a reference game with 1 target and 1 distractor, and the concept game is similar, but with agents given separate inputs. Our results suggest that this decoupling, as proposed by Lazaridou et al. [18] and often used in the emergent communication literature, pro-

Figure 5: Topographic ρ (concept Edit distance) with varying number of targets (average over seen/unseen splits). Each point and Ref line is an independent run.

motes systematicity in some cases (Birds) *but not others* (ShapeWorld). We additionally show that (1) sets are an *alternative* way of encouraging systematicity without needing this separation, and (2) even with this separation, larger set sizes further improve the systematicity of the resulting language.

Figure 3: Topographic ρ between language and Edit (top) or Hausdorff (bottom) concept distances for training and test splits across both datasets. Results from 5 runs plotted, with averages in bold.

Figure 4: Distribution of 300 messages and entropies for game concepts in ref, setref, and concept settings. Messages start at the center and proceed outwards, with each colored section corresponding to a unique token and its frequency of occurrence at that position in the message. Empty spaces indicate end of sentence. For convenience, ShapeWorld plots are partially labeled with tokens.

6.2 Generalizing across game types

To measure the generality of the agents' strategies, we evaluate their ability to generalize zero-shot across game types. Table 2 shows accuracy and systematicity metrics for agents evaluated on games of a different type. Agents trained on the setref and concept games are able to generalize to reference games (yellow cells), producing systematic referring expressions, as they have already been biased towards generic language. Importantly, setref game agents can generalize to concept games with separate inputs (magenta cells), though to a lesser extent for Birds (75% vs 84%). This suggests that sets pressure agents to learn generalizable features *despite* the shared input. In contrast, we see little generalization ability from reference games to setref and concept games (orange cells).

7 Probing for compositionality

The richer set of concepts afforded by our setref and concept games allow for more detailed analyses of the emergent languages beyond the standard metrics presented above. Broadly, we are interested in whether the compositional structure of concepts is reflected in the language. For example, our agents produce messages for the primitive concepts *red* and *triangle*, as well as the conjunctive concept *red AND triangle*.[4] Natural language is equipped with a composition operator, $\text{AND}(m_1, m_2) = m_1 \text{ AND } m_2$, that operates solely on lexical forms and whose meaning is defined as the conjunction of the meanings of its arguments. Does a similar operator exist in the emergent language (Figure 6a)?

---

[4]We cannot do this analysis for reference games, since we cannot test primitive concepts; recall Section 4.

Table 2: Accuracy/AMI/Topographic ρ (concept Edit distance) for agents *trained* on different game types (columns), then *evaluated* (zero-shot) on different game types (rows). Chance accuracy is 50%. Gray shaded cells indicate standard test-time evaluation; other cell colors are explained in the text. Note that for ShapeWorld reference agents, we evaluate only on setref and concept games that use the 30 conjunctive concepts tested in reference games (e.g. *red triangle*, *blue square*).

	Train Ref	Train Setref	Train Concept
ShapeWorld			
Eval Ref	98 (0.4)/.04 (.00)/.00 (.00)	91 (4.3)/.43 (.09)/.42 (.11)	83 (5.6)/.60 (.04)/.63 (.08)
Eval Setref	56 (0.1)/.02 (.00)/.00 (.00)	90 (1.3)/.59 (.08)/.12 (.03)	83 (6.7)/.66 (.07)/.09 (.01)
Eval Concept	50 (0.0)/.02 (.00)/.00 (.00)	90 (4.6)/.59 (.08)/.12 (.03)	82 (3.0)/.66 (.07)/.09 (.01)
Birds			
Eval Ref	91 (0.8)/.05 (.00)/.04 (.01)	85 (1.1)/.14 (.02)/.16 (.02)	82 (0.9)/.20 (.02)/.15 (.01)
Eval Setref	64 (1.7)/.03 (.01)/.15 (.01)	84 (1.1)/.17 (.02)/.37 (.04)	78 (0.7)/.26 (.02)/.40 (.03)
Eval Concept	56 (0.9)/.03 (.01)/.15 (.01)	75 (0.9)/.17 (.02)/.37 (.04)	82 (0.6)/.26 (.02)/.40 (.03)

We propose to *learn* such an operator by training a model to compose messages in the emergent language to form their conjunctions. Like the English AND, this operator must be able to combine any of the concepts in the language, and must crucially *generalize* to novel combinations of features. If, given new concepts, we can reconstruct a message that induces the right behavior in the student, this suggests our model has learned some analog of AND in the language. The reconstruction accuracy of this model can then be interpreted as a much more explicit measure of compositionality than the measures explored above: it reveals the degree to which the syntax of the emergent language operationalizes the specific logical operations present in the underlying space of concepts.

Our method is inspired by the *Tree Reconstruction Error* (TRE) metric proposed by Andreas [1], which learns a compositional approximation to a representation space, assuming the latent compositional structure is known. However, there are several crucial differences in our method that are optimized for probing for linguistic structure. First, we *learn* a set of arbitrary composition operations, instead of imposing a predefined operation (e.g. elementwise addition). Moreover, these learned composition operators are actually valid and interpretable linguistic transformations on messages, rather than operations (like addition) that work only on internal representations of sub-concepts. And finally, we evaluate our operators on held-out concepts, examining how the reconstructed messages serve the ultimate communicative goal: inducing the correct generalization behavior in the student.

7.1 Learning an Approximate Compositional Reconstruction (ACRe)

Let us first formalize the learning problem: after training our agents, we have a dataset of message and concept pairs $\mathcal{T} = \{(m_i, c_i)\}$ generated by a teacher for each game. Each concept is one of a set of logical forms $\mathcal{L}(\mathcal{C})$ defined over a set of *primitive* concepts $\mathcal{C}$ (e.g. *red*, *triangle*) as follows:

1. Every primitive concept is in $\mathcal{L}(\mathcal{C})$: $\mathcal{C} \subseteq \mathcal{L}(\mathcal{C})$.

2. Every composition of concepts is a concept: let Ω_n be the set of n-ary composition operations. Then $\forall n, \ (c_1, c_2, \ldots, c_n) \in \mathcal{L}(\mathcal{C})^n, \ \omega \in \Omega_n$, we have $\omega(c_1, c_2, \ldots, c_n) \in \mathcal{L}(\mathcal{C})$.

$\mathcal{T}$ defines a probability distribution over messages given concepts: $p_{\mathcal{T}}(m \mid c)$. Our aim is to learn an **A**pproximate **C**ompositional **Re**construction to these messages $\hat{p}_\eta(m \mid c)$, composed of η-parameterized message distributions that factorize along the compositional structure of $\mathcal{L}(C)$:

$$\hat{p}_\eta(m \mid c) = \begin{cases} \hat{p}_\eta^c(m) & \text{if } c \in \mathcal{C}, \text{ i.e. } c \text{ is primitive} \\ \mathbb{E}_{\hat{m}_i \sim \hat{p}_\eta(m_i \mid c_i)} \left[\hat{p}_\eta^\omega(m \mid \hat{m}_1, \ldots, \hat{m}_n) \right] & \text{if } c = \omega(c_1, \ldots, c_n), \end{cases} \tag{3}$$

where $\hat{p}_\eta^c(m)$ is a model of the distribution of messages for primitive concept c, and $\hat{p}_\eta^\omega(m \mid m_1, \ldots, m_n)$ is a learned lexical analog to operation ω that takes in messages and outputs a distribution over composed messages. Given a concept c, we can sample a message from $\hat{p}_\eta(m \mid c)$ by either sampling directly from $\hat{p}_\eta^c$ (if c is primitive) or recursively sampling messages m_i from the constituents of c, then sampling from the corresponding $\hat{p}_\eta^\omega$.

We implement $\hat{p}_\eta^c$ and $\hat{p}_\eta^\omega$ as small 2-layer transformer-based language models (LMs) [26]. For each c, $\hat{p}_\eta^c$ is an unconditional LM (i.e. we have an LM for *red*, *triangle*, etc.). For n-ary operations ω,

(a) (b) (c)

Figure 6: Our ACRe procedure. (a) Does a lexical analog of AND exist in our emergent language? (b) We first train primitive LMs to mimic the distribution of agent messages given a fixed concept. (c) We then train composition operations by sampling arguments from primitive LMs, then training a seq2seq model to mimic the agent message produced for a higher-order concept.

Table 3: ACRe evaluation. (SD) across 5 runs. In the highlighted cells we conduct paired t-tests, comparing ACRe to Closest Concept; * indicates significance at $p < 0.05$.

Game	Language	Train BLEU-1	Train Student Acc	Test BLEU-1	Test Student Acc
Setref	Teacher	100 (0.0)	91 (2.7)	100 (0.0)	86 (5.1)
	ACRe	93 (1.6)	82 (3.5)	92 (3.3)	66 (3.4)*
	Closest Concept	78 (4.6)	48 (0.6)	88 (3.8)	56 (0.5)
	Random	71 (6.7)	50 (0.1)	73 (7.7)	50 (0.0)
Concept	Teacher	100 (0.0)	88 (4.1)	100 (0.0)	84 (4.3)
	ACRe	89 (4.3)	81 (3.2)	85 (6.2)	68 (5.5)*
	Closest Concept	64 (3.7)	48 (1.6)	76 (2.7)	54 (3.7)
	Random	54 (2.9)	50 (0.2)	56 (2.2)	50 (0.5)

$\hat{p}_\eta^\omega$ is a sequence-to-sequence (seq2seq) model decoding from the concatenated arguments: $\hat{p}_\eta^\omega(m \mid m_1, \ldots, m_n) = p_\eta^{\text{decode}}(m \mid m_1 \; \texttt{[SEP]} \; m_2 \; \ldots \; \texttt{[SEP]} \; m_n)$. Note that this formulation imposes few constraints on the mechanism of the composition operator: for example, we are not enforcing that there exists a token denoting conjunction (AND), or that the arguments must be copied verbatim into the output. These constraints, generally true of human languages, could be explored in future work.

To train ACRe, let $\mathcal{T}_c = \{(m_i, c_i) \in \mathcal{T} \mid c_i = c\}$ be the set of message-concept pairs with concept c, and $\mathcal{T}_\omega = \{(m_i, c_i) \in \mathcal{T} \mid c_i = \omega(\cdot)\}$ be the set of messages where c_i uses ω. Now, for each primitive $c \in \mathcal{C}$, train the LM $\hat{p}_\eta^c$ on $\mathcal{T}_c$ to approximate $p_\mathcal{T}(m \mid c)$. Then, freezing these models, for $n = 1, \ldots, N, \omega \in \Omega_n$, train the composition model $\hat{p}_\eta^\omega$ on $\mathcal{T}_\omega$. Specifically, given a pair $(m, \omega(c_1, \ldots, c_n))$, first sample messages for the sub-concepts c_i from our frozen models: $\hat{m}_i \sim \hat{p}_\eta(m_i \mid c_i)$.[5] Then, train the composition model to maximize $\hat{p}_\eta^\omega(m \mid \hat{m}_1, \ldots, \hat{m}_n)$. For example, given a message bca for the concept *red AND triangle*, we first sample messages for *red* and *triangle* from $\hat{p}_\eta^{\text{red}}$ and $\hat{p}_\eta^{\text{triangle}}$, then train $\hat{p}_\eta^{\text{AND}}$ to decode bca from these messages (Figure 6). Full training and model details are in Appendix F.

7.2 Evaluation and results

After training, each $\hat{p}_\eta^\omega$ is a learned lexical analog to the composition operation ω. To test whether our approximation has learned the semantics of the language, we hold out 10% of conjunctive and disjunctive concepts c_i' during training and sample messages for these concepts from the learned $\hat{p}_\eta(m \mid c_i')$ according to Equation 3. We evaluate how well these reconstructed messages encode the concepts via (1) lexical overlap with the true teacher messages (as measured by BLEU-1) and (2) student performance when given our language and a game for the corresponding concept.[6]

---

[5] As presented, this procedure is only possible if the composition models can be trained and frozen in a specific order without circular dependencies. For example, we cannot naively train $\hat{p}_\eta^\omega$ on concepts of the form $\omega(\omega(\cdot))$, since sampling from the inner ω requires an already-trained $\hat{p}_\eta^\omega$. Learning from arbitrary concepts is possible by backpropagating through samples (e.g. via Gumbel-Softmax), which we leave for future work.

[6] In these experiments, we run ACRe on agents trained on the full set of 312 concepts in ShapeWorld, since we are not testing compositional generalization of the agents, but of ACRe.

Figure 7: Composition in the emergent languages. A concept game teacher's messages for sample primitive concepts and conjunctions, and predicted messages according to ACRe (where *green AND triangle* is an unseen combination) and other baselines. Color key same as Figure 4.

Results are in Table 3. The upper bound on performance is given by the true **Teacher** language, $p_{\mathcal{T}}(m \mid c)$. We also use language sampled randomly from (1) teacher messages for *any* concept $p_{\mathcal{T}}(m)$ (**Random**) and (2) teacher messages for the **Closest Concept** as measured by Edit distance (breaking ties randomly). ACRe's performance is a measure of the degree of compositionality in the language, upper bounded by the teacher language and lower bounded by the random baseline. The results reveal some degree of compositional structure: ACRe reconstructs the training data well and crucially outperforms baselines in predicting messages for unseen concepts. Of course, our ACRe model trails Teacher language accuracy by 16–20 points. This gap could stem from a failure of ACRe to find the correct compositional generalization, or lack of compositionality in the language itself.

A qualitative analysis supports the interpretation that the compositional operations are not always interpretable. Figure 7 shows an example of message distributions for the primitive concepts *yellow*, *green*, and *triangle*, as well as distributions for the conjunctive concepts *yellow AND triangle* and *green AND triangle*, with predictions from ACRe and baseline models. The message for *yellow AND triangle* is intuitively composed out of tokens concatenated from both primitives similar to natural language [9]. However, the message *green AND triangle* uses tokens from *green*, but none from *triangle*, thereby violating the *mutual exclusivity* principle of language [22]. Regardless, in both cases our ACRe model is able to approximate such messages better than the other baselines. An exciting avenue for future work is encouraging models to develop operators more akin to human language, and evaluating their acquisition by searching among a more restricted class of ACRe models $\hat{p}_{\eta}^{\omega}$.

8 Conclusion

We have proposed extensions of referential games to sets of objects, and found that the need to convey generalizable categories leads to the development of more systematic languages, whether inputs are shared (setref) or unshared (concept) across agents. Moving forward, the richer space of concepts afforded by our setref and concept games are a promising testbed for studying the emergence of higher-level linguistic phenomena, such as quantifiers or probabilistic language. Finally, while ACRe reveals some compositional structure in the emergent languages as-is, the learned composition operations are not particularly interpretable. Future work should identify what kinds of environmental or architectural constraints might encourage more transparent composition in learned artificial languages.

9 Broader Impact

Our work investigates agents communicating in artificial and isolated environments, and thus has limited immediate societal impact. However, we can imagine that with future advances in research and compute, agents may learn linguistic strategies to collaborate on real-world problems in increasingly high-stakes domains, and it will be important to ensure that the learned languages are interpretable, safe, and reliable. Our work has potential positive benefits in these scenarios: our proposed games encourage agents to learn more human-like linguistic behavior, which might ease collaboration with humans; and ACRe is a tool for evaluating and interpreting learned languages. However, future work is needed to see whether these tools remain reliable as we scale up our agents and tasks.

References

[1] J. Andreas. Measuring compositionality in representation learning. In *International Conference on Learning Representations*, 2019.

[2] D. Bouchacourt and M. Baroni. How agents see things: On visual representations in an emergent language game. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 981–985, 2018.

[3] H. Brighton and S. Kirby. Understanding linguistic evolution by visualizing the emergence of topographic mappings. *Artificial Life*, 12(2):229–242, 2006.

[4] R. Chaabouni, E. Kharitonov, E. Dupoux, and M. Baroni. Anti-efficient encoding in emergent communication. In *Advances in Neural Information Processing Systems*, 2019.

[5] R. Chaabouni, E. Kharitonov, D. Bouchacourt, E. Dupoux, and M. Baroni. Compositionality and generalization in emergent languages. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4427–4442, 2020.

[6] K. Cho, B. van Merriënboer, C. Gulcehre, D. Bahdanau, F. Bougares, H. Schwenk, and Y. Bengio. Learning Phrase Representations using RNN Encoder–Decoder for Statistical Machine Translation. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing*, pages 1724–1734, 2014.

[7] E. Choi, A. Lazaridou, and N. de Freitas. Compositional obverter communication learning from raw visual input. In *International Conference on Learning Representations*, 2018.

[8] S. Chopra, M. H. Tessler, and N. D. Goodman. The first crank of the cultural ratchet: Learning and transmitting concepts through language. In *Proceedings of the 41st Annual Meeting of the Cognitive Science Society*, pages 226–232, 2019.

[9] J. Haiman. The iconicity of grammar: Isomorphism and motivation. *Language*, pages 515–540, 1980.

[10] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 770–778, 2016.

[11] E. Jang, S. Gu, and B. Poole. Categorical reparameterization with gumbel-softmax. In *International Conference on Learning Representations*, 2017.

[12] D. P. Kingma and J. Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations*, 2014.

[13] S. Kottur, J. Moura, S. Lee, and D. Batra. Natural language does not emerge 'naturally' in multi-agent dialog. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, 2017.

[14] N. Kriegeskorte, M. Mur, and P. A. Bandettini. Representational similarity analysis-connecting the branches of systems neuroscience. *Frontiers in Systems Neuroscience*, 2:4, 2008.

[15] A. Kuhnle and A. Copestake. ShapeWorld - a new test methodology for multimodal language understanding. *arXiv preprint arXiv:1704.04517*, 2017.

[16] K. N. Laland. The origins of language in teaching. *Psychonomic Bulletin & Review*, 24(1):225–231, 2017.

[17] A. Lazaridou and M. Baroni. Emergent multi-agent communication in the deep learning era. *arXiv preprint arXiv:2006.02419*, 2020.

[18] A. Lazaridou, A. Peysakhovich, and M. Baroni. Multi-agent cooperation and the emergence of (natural) language. In *International Conference on Learning Representations*, 2017.

[19] A. Lazaridou, K. M. Hermann, K. Tuyls, and S. Clark. Emergence of linguistic communication from referential games with symbolic and pixel input. In *International Conference on Learning Representations*, 2018.

[20] D. Lewis. *Convention: A Philosophical Study*. Harvard University Press, Cambridge, MA, 1969.

[21] F. Li and M. Bowling. Ease-of-teaching and language structure from emergent communication. In *Advances in Neural Information Processing Systems*, 2019.

[22] E. M. Markman and G. F. Wachtel. Children's use of mutual exclusivity to constrain the meanings of words. *Cognitive Psychology*, 20(2):121–157, 1988.

[23] O. Russakovsky, J. Deng, H. Su, J. Krause, S. Satheesh, S. Ma, Z. Huang, A. Karpathy, A. Khosla, M. Bernstein, et al. ImageNet large scale visual recognition challenge. *International Journal of Computer Vision*, 115(3):211–252, 2015.

[24] J. Snell, K. Swersky, and R. Zemel. Prototypical networks for few-shot learning. In *Advances in Neural Information Processing Systems*, pages 4077–4087, 2017.

[25] M. H. Tessler and N. D. Goodman. The language of generalization. *Psychological Review*, 126(3):395, 2019.

[26] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, L. Kaiser, and I. Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, 2017.

[27] N. X. Vinh, J. Epps, and J. Bailey. Information theoretic measures for clusterings comparison: Variants, properties, normalization and correction for chance. *Journal of Machine Learning Research*, 11:2837–2854, 2010.

[28] C. Wah, S. Branson, P. Welinder, P. Perona, and S. Belongie. The Caltech-UCSD Birds-200-2011 dataset. Technical report, California Institute of Technology, 2011.

[29] T. Wolf, J. Chaumond, L. Debut, V. Sanh, C. Delangue, A. Moi, P. Cistac, M. Funtowicz, J. Davison, S. Shleifer, et al. Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 38–45, 2020.