REGULARIZATION MATTERS IN POLICY OPTIMIZATION - AN EMPIRICAL STUDY ON CONTINUOUS CONTROL

ABSTRACT

Deep Reinforcement Learning (Deep RL) has been receiving increasingly more attention thanks to its encouraging performance on a variety of control tasks. Yet, conventional regularization techniques in training neural networks (e.g., L_2 regularization, dropout) have been largely ignored in RL methods, possibly because agents are typically trained and evaluated in the same environment, and because the deep RL community focuses more on high-level algorithm designs. In this work, we present the first comprehensive study of regularization techniques with multiple policy optimization algorithms on continuous control tasks. Interestingly, we find conventional regularization techniques on the policy networks can often bring large improvement, especially on harder tasks. Our findings are shown to be robust against training hyperparameter variations. We also compare these techniques with the more widely used entropy regularization. In addition, we study regularizing different components and find that only regularizing the policy network is typically the best. We further analyze why regularization may help generalization in RL from four perspectives - sample complexity, reward distribution, weight norm, and noise robustness. We hope our study provides guidance for future practices in regularizing policy optimization algorithms. Our code is available at https://github.com/anonymouscode114/iclr2021_rlreg.

1 INTRODUCTION

The use of regularization methods to prevent overfitting is a key technique in successfully training neural networks. Perhaps the most widely recognized regularization methods in deep learning are L_2 regularization (also known as weight decay) and dropout (Srivastava et al., 2014). These techniques are standard practices in supervised learning tasks across many domains. Major tasks in computer vision, e.g., image classification (Krizhevsky et al., 2012; He et al., 2016), object detection (Ren et al., 2015; Redmon et al., 2016), use L_2 regularization as a default option. In natural language processing, for example, the Transformer (Vaswani et al., 2017) uses dropout, and the popular BERT model (Devlin et al., 2018) uses L_2 regularization. In fact, it is rare to see state-of-the-art neural models trained without regularization in a supervised setting.

However, in deep reinforcement learning (deep RL), those conventional regularization methods are largely absent or underutilized in past research, possibly because in most cases we are maximizing the return on the same task as in training. In other words, there is no generalization gap from the training environment to the test environment (Cobbe et al., 2018). Heretofore, researchers in deep RL have focused on high-level algorithm design and largely overlooked issues related to network training, including regularization. For popular policy optimization algorithms like Trust Region Policy Optimization (TRPO) (Schulman et al., 2015), Proximal Policy Optimization (PPO) (Schulman et al., 2017), and Soft Actor Critic (SAC) (Haarnoja et al., 2018), conventional regularization methods were not considered. In popular codebases such as the OpenAI Baseline (Dhariwal et al., 2017), L_2 regularization and dropout were not incorporated. Instead, a commonly used regularization in RL is the entropy regularization which penalizes the high-certainty output from the policy network to encourage more exploration and prevent the agent from overfitting to certain actions. The entropy regularization was first introduced by (Williams & Peng, 1991) and now used by many contemporary algorithms (Mnih et al., 2016; Schulman et al., 2017; Teh et al., 2017; Farebrother et al., 2018).

In this work, we take an empirical approach to assess the conventional paradigm which omits common regularization when learning deep RL models. We study agent performance on current task (the environment which the agent is trained on), rather than its generalization ability to different environments as in many recent works (Zhao et al., 2019; Farebrother et al., 2018; Cobbe et al., 2018). We specifically focus our study on policy optimization methods, which are becoming increasingly popular and have achieved top performance on various tasks. We evaluate four popular policy optimization algorithms, namely SAC, PPO, TRPO, and the synchronous version of Advantage Actor Critic (A2C), on multiple continuous control tasks. Various conventional regularization techniques are considered, including L_2/L_1 weight regularization, dropout, weight clipping (Arjovsky et al., 2017) and Batch Normalization (BN) (Ioffe & Szegedy, 2015). We compare the performance of these regularization techniques to that without regularization, as well as the entropy regularization.

Surprisingly, even though the training and testing environments are the same, we find that many of the conventional regularization techniques, when imposed to the policy networks, can still bring up the performance, sometimes significantly. Among those regularizers, L_2 regularization tends to be the most effective overall. L_1 regularization and weight clipping can boost performance in many cases. Dropout and Batch Normalization tend to bring improvements only on off-policy algorithms. Additionally, all regularization methods tend to be more effective on more difficult tasks. We also verify our findings with a wide range of training hyperparameters and network sizes, and the result suggests that imposing proper regularization can sometimes save the effort of tuning other training hyperparameters. We further study which part of the policy optimization system should be regularized, and conclude that generally only regularizing the policy network suffices, as imposing regularization on value networks usually does not help. Finally we discuss and analyze possible reasons for some experimental observations. Our main contributions can be summarized as follows:

- To our best knowledge, we provide the first systematic study of common regularization methods in policy optimization, which have been largely ignored in the deep RL literature.
- We find conventional regularizers can be effective on continuous control tasks (especially on harder ones) with statistical significance, under randomly sampled training hyperparameters. Interestingly, simple regularizers (L_2, L_1, weight clipping) could perform better than entropy regularization, with L_2 generally the best. BN and dropout can only help in off-policy algorithms.
- We study which part of the network(s) should be regularized. The key lesson is to regularize the policy network but not the value network.
- We analyze why regularization may help generalization in RL through sample complexity, reward distribution, weight norm, and training noise robustness.

2 RELATED WORKS

Regularization in Deep RL. There have been many prior works studying the theory of regularization in policy optimization (Farahmand et al., 2009; Neu et al., 2017; Zhang et al., 2020). In practice, conventional regularization methods have rarely been applied in deep RL. One rare case of such use is in Deep Deterministic Policy Gradient (DDPG) (Lillicrap et al., 2016), where Batch Normalization is applied to all layers of the actor and some layers of the critic, and L_2 regularization is applied to the critic. Some recent studies have developed more complicated regularization approaches to continuous control tasks. Cheng et al. (2019) regularizes the stochastic action distribution $\pi(a|s)$ using a control prior and dynamically adjusts regularization weight based on the temporal difference (TD) error. Parisi et al. (2019) uses TD error regularization to penalize inaccurate value estimation and Generalized Advantage Estimation (GAE) (Schulman et al., 2016) regularization to penalize GAE variance. However, most of these regularizations are rather complicated (Cheng et al., 2019) or catered to certain algorithms (Parisi et al., 2019). Also, these techniques consider regularizing the output of the network, while conventional methods mostly directly regularize the parameters. In this work, we focus on studying these simpler but under-utilized regularization methods.

Generalization in Deep RL typically refers to how the model perform in a different environment from the one it is trained on. The generalization gap can come from different modes/levels/difficulties of a game (Farebrother et al., 2018), simulation vs. real world (Tobin et al., 2017), parameter variations (Pattanaik et al., 2018), or different random seeds in environment generation (Zhang et al., 2018b). There are a number of methods designed to address this issue, e.g., through training the agent over multiple domains/tasks (Tobin et al., 2017; Rajeswaran et al., 2017), adversarial training (Tobin

et al., 2017), designing model architectures (Srouji et al., 2018), adaptive training (Duan et al., 2016), etc. Meta RL (Finn et al., 2017; Gupta et al., 2018; Al-Shedivat et al., 2017) try to learn generalizable agents by training on many environments drawn from the same family/distribution. There are also some comprehensive studies on RL generalization with interesting findings (Zhang et al., 2018a;b; Zhao et al., 2019; Packer et al., 2018), e.g., algorithms performing better in training environment could perform worse with domain shift (Zhao et al., 2019).

Recently, several studies have investigated conventional regularization's effect on generalization across tasks. (Farebrother et al., 2018) shows that in Deep Q-Networks (DQN), L_2 regularization and dropout are sometime beneficial when evaluated on the same Atari game with mode variations. (Cobbe et al., 2018) shows that L_2 regularization, dropout, BN, and data augmentation can improve generalization performance, but to a less extent than entropy regularization and ϵ-greedy exploration. Different from those studies, we focus on regularization's effect in the same environment, yet on which conventional regularizations are under-explored.

3 EXPERIMENTS

3.1 SETTINGS

Regularization Methods. We study six regularization methods, namely, L_2 and L_1 weight regularization, weight clipping, Dropout (Srivastava et al., 2014), Batch Normalization (Ioffe & Szegedy, 2015), and entropy regularization. See Appendix A for detailed introduction. Note that we consider entropy as a separate regularization method because it encourages exploration and helps to prevent premature convergence (Mnih et al., 2016). In Appendix K, we show that in the presence of certain regularizers, adding entropy on top does not lead to significant performance difference.

Algorithms. We evaluate regularization methods on four popular policy optimization algorithms, namely, A2C (Mnih et al., 2016), TRPO (Schulman et al., 2015), PPO (Schulman et al., 2017), and SAC (Haarnoja et al., 2018). The first three algorithms are on-policy while the last one is off-policy. For the first three algorithms, we adopt the code from OpenAI Baseline (Dhariwal et al., 2017), and for SAC, we use the official implementation at (Haarnoja, 2018).

Tasks. The algorithms with different regularizers are tested on nine continuous control tasks: Hopper, Walker, HalfCheetah, Ant, Humanoid, and HumanoidStandup from MuJoCo (Todorov et al., 2012); Humanoid, AtlasForwardWalk, and HumanoidFlagrun from RoboSchool (OpenAI). Among the MuJoCo tasks, agents for Hopper, Walker, and HalfCheetah are easier to learn, while Ant, Humanoid, HumanoidStandup are relatively harder (larger state-action space, more training examples). The three Roboschool tasks are even harder than the MuJoCo tasks as they require more timesteps to converge (Klimov & Schulman, 2017). To better understand how different regularization methods work on different difficulties, we roughly categorize the first three environments as "easy" tasks and the last six as "hard" tasks. Besides continuous control, we provide results on randomly sampled Atari environments (Bellemare et al., 2012) in Appendix P, which have discrete action space and different reward properties. Our observations are mostly similar to those on continuous control tasks.

Training. On MuJoCo tasks, we keep all hyperparameters unchanged as in the codebase adopted. Since hyperparameters for the RoboSchool tasks are not included, we briefly tune the hyperparameters for each algorithm before we apply regularization (details in Appendix D). For details on regularization strength tuning, please see Appendix C. The results shown in this section are obtained by **only regularizing the policy network**, and a further study on this will be presented in Section 5. We run each experiment independently with five seeds, then use the average return over the last 100 episodes as the final result. Each regularization method is evaluated independently, with other regularizers turned off. We refer to the result without any regularization as the baseline. For BN and dropout, we use its training mode in updating the network, and test mode in sampling trajectories. During training, negligible computation overhead is induced when a regularizer is applied. Specifically, the increase in training time for BN is $\sim 10\%$, dropout $\sim 5\%$, while L_2, L_1, weight clipping, and entropy regularization are all $< 1\%$. We used up to 16 NVIDIA Titan Xp GPUs and 96 Intel Xeon E5-2667 CPUs, and all experiments take roughly 57 days with resources fully utilized.

Additional Notes. 1. Note that entropy regularization is still applicable for SAC, despite it already incorporates the maximization of entropy in the reward. In our experiments, we add the entropy

Figure 1: Reward vs. timesteps, for four algorithms (columns) and four environments (rows).

regularization term to the policy loss function in equation (12) of (Haarnoja et al., 2018). **2.** In our experiments, L_2 regularization loss is added to the training loss, which is then optimized using Adam (Kingma & Ba, 2015). (Loshchilov & Hutter, 2019) observes that L_2 regularization interacts poorly with Adam and proposes AdamW to decouple weight decay from the optimization steps. However, in policy optimization algorithms, we find that the performance of AdamW with decompled weight decay is slightly worse than the performance of Adam with L_2 loss directly added. Comparisons are shown in Appendix L. **3.** Policy network dropout is not applicable to TRPO because during policy updates, different neurons in the old and new policy networks are dropped out, causing different shifts in the old and new action distributions given the same state, which violates the trust region constraint. In this case, the algorithm fails to perform any update from network initialization.

3.2 RESULTS

Training curves. We plot the training curves from four environments (rows) in Figure 1, on four algorithms (columns). Figures for the rest five environments are deferred to Appendix M. In the figure, different colors are used to denote different regularization methods, e.g., black is the baseline method. Shades are used to denote ± 1 standard deviation range. Notably, these conventional regularizers can frequently boost the performance across different tasks and algorithms, demonstrating that a study on the regularization in deep RL is highly demanding. We observe that BN always significantly hurts the baseline for on-policy algorithms. The reason will be discussed later. For the off-policy SAC algorithm, dropout and BN sometimes bring large improvement on hard tasks like AtlasForwardWalk and RoboschoolHumanoid. Interestingly, in some cases where the baseline (with the default hyperparameters in the codebase) does not converge to a reasonable solution, e.g., A2C Ant, PPO Humanoid, imposing some regularization can make the training converge to a high level.

How often do regularizations help? To quantitatively measure the effectiveness of the regularizations on each algorithm across different tasks, we **define the condition when a regularization is said to "improve" upon the baseline** in a certain environment. Denote the baseline mean return over five seeds on an environment as $\mu_{\text{env},b}$, and the mean and standard deviation of the return obtained with a certain regularization method over five seeds as $\mu_{\text{env},r}$ and $\sigma_{\text{env},r}$. We say the performance is "improved" by the regularization if $\mu_{\text{env},r} - \sigma_{\text{env},r} > \max(\mu_{\text{env},b}, T(\text{env}))$, where $T(\text{env})$ is the minimum return threshold of an environment. The threshold serves to ensure the return is at least in a reasonable level. We set the threshold to be 10^5 for HumanoidStandup and 10^3 for all other tasks.

Table 1: Percentage (%) of environments where the final performance "improves" with regularization, by our definition in Section 3.2.

Reg \ Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total
Entropy	**33.3**	**100.0**	**77.8**	0.0	50.0	33.3	0.0	33.3	22.2	33.3	50.0	44.4	16.7	58.3	44.4
L_2	0.0	50.0	33.3	0.0	**66.7**	**44.4**	**33.3**	**83.3**	**66.7**	**66.7**	**66.7**	**66.7**	25.0	**66.7**	**52.8**
L_1	0.0	50.0	33.3	0.0	**66.7**	**44.4**	**33.3**	66.7	55.6	33.3	50.0	44.4	16.7	58.3	44.4
Weight Clip	0.0	16.7	11.1	**33.3**	33.3	33.3	**33.3**	66.7	55.6	33.3	16.7	22.2	25.0	33.3	30.6
Dropout	0.0	0.0	0.0	N/A	N/A	N/A	**33.3**	50.0	44.4	**66.7**	50.0	55.6	**33.3**	33.3	33.3
BatchNorm	0.0	0.0	0.0	0.0	0.0	0.0	0.0	16.7	11.1	33.3	50.0	44.4	8.3	16.7	13.9

The result is shown in Table 1. Perhaps the most significant observation is that L_2 regularization is the most often to improve upon the baseline. A2C algorithm is an exception, where entropy regularization is the most effective. L_1 regularization behaves similar to L_2 regularization, but is outperformed by the latter. Weight clipping's usefulness is highly dependent on the algorithms and environments. Despite in total it only helps at 30.6% times, it can sometimes outperform entropy regularization by a large margin, e.g., in TRPO Humanoid and PPO Humanoid as shown in Figure 1. BN is not useful at all in the three on-policy algorithms (A2C, TRPO, and PPO). Dropout is not useful in A2C at all, and sometimes helps in PPO. However, BN and dropout can be useful in SAC. All regularization methods generally improve more often when they are used on harder tasks, perhaps because for easier ones the baseline is often sufficiently strong to reach a high performance.

Note that under our definition, not "improving" does not indicate "hurting". If we define "hurting" as $\mu_{env,r} + \sigma_{env,r} < \mu_{env,b}$ (the reward minimum threshold is not considered here), then total percentage of hurting is 0.0% for L_2, 2.8% for L_1, 5.6% for weight clipping, 44.4% for dropout, 66.7% for BN, and 0.0% for entropy. In other words, under our parameter tuning range, L_2 and entropy regularization never hurt with appropriate strengths. For BN and dropout, we also note that almost all hurting cases are in on-policy algorithms, except one case for BN in SAC. In sum, all regularizations in our study very rarely hurt the performance except for BN/dropout in on-policy methods.

How much do regularizations improve? For each algorithm and environment (for example, PPO on Ant), we calculate a z-score for each regularization method and the baseline, by treating results produced by all regularizations (including baseline) and all five seeds together as a population, and calculate each method's average z-scores from its five final results (positively clipped). z-score is also known as "standard score", the signed fractional number of standard deviations by which the value of a data point is above the mean value. For each algorithm and environment, a regularizer's z-score roughly measures its relative performance among others. The z-scores are then averaged over environments of a certain difficulty (easy/hard), and the results are shown in Table 2. In terms of the average improved margin, we can draw mostly similar observations as the improvement frequency (Table 1): L_2 tops the average z-score most often, and by large margin in total; entropy regularization is best used with A2C; Dropout and BN are only useful in the off-policy SAC algorithm; the improvement over baseline is larger on hard tasks. Notably, for all algorithms, any regularization on average outperforms the baseline on hard tasks, except dropout and BN in on-policy algorithms. On hard tasks, L_1 and weight clipping also perform higher than entropy in total, besides L_2.

Besides the improvement percentage (Table 1) and the z-score (Table 2), we provide more metrics of comparison (e.g., average ranking, min-max scaled reward) to comprehensively compare the different regularization methods. We also conduct **statistical significance** tests on these metrics, and the improvement are mostly statistically significant ($p < 0.05$). We believe evaluating under a variety of metrics make our conclusions more reliable. Detailed results are in Appendix F, H, and I.

Table 2: Average z-scores. Note that a negative z-score does not necessarily mean the method hurts, because it could be higher than the baseline. The scores within 0.01 range from the highest are in **bold**.

Reg \Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total
Baseline	0.30	-0.17	-0.02	0.28	0.10	0.16	0.24	-0.54	-0.28	-0.22	-0.47	-0.39	0.15	-0.27	-0.13
Entropy	**1.14**	**1.01**	**1.06**	0.16	0.30	0.26	**0.43**	-0.25	-0.02	0.32	-0.16	0.00	**0.51**	0.23	0.32
L_2	0.53	0.93	0.80	**0.51**	0.39	0.43	0.30	**0.76**	**0.61**	**0.36**	0.25	0.28	0.43	**0.58**	**0.53**
L_1	0.15	0.43	0.34	0.31	**0.57**	**0.48**	0.27	**0.76**	**0.60**	0.19	-0.17	-0.05	0.23	0.40	0.34
Weight Clip	0.22	0.24	0.24	0.28	0.49	0.42	0.34	0.63	0.53	-0.36	-0.09	-0.18	0.12	0.32	0.25
Dropout	-1.16	-1.18	-1.17	N/A	N/A	N/A	-0.12	-0.47	-0.35	0.35	**0.49**	**0.44**	-0.31	-0.39	-0.36
BatchNorm	-1.19	-1.26	-1.24	-1.54	-1.85	-1.75	-1.47	-0.89	-1.08	-0.64	0.17	-0.10	-1.21	-0.96	-1.04

4 ROBUSTNESS WITH HYPERPARAMETER CHANGES

In the previous section, the experiments are conducted mostly with the default hyperparameters in the codebase we adopt, which are not necessarily optimized. For example, PPO Humanoid baseline performs poorly using default hyperparameters, not converging to a reasonable solution. Meanwhile, it is known that RL algorithms are very sensitive to hyperparameter changes (Henderson et al., 2018). Thus, our findings can be vulnerable to such variations. To further confirm our findings, we evaluate the regularizations under a variety of hyperparameter settings. For each algorithm, we sample five hyperparameter settings for the baseline and apply regularization on each of them. Due to the heavy computation cost, we only evaluate on five environments: Hopper, Walker, Ant, Humanoid, HumanoidStandup. Under our sampled hyperparameters, poor baselines are mostly significantly improved. See Appendix E/ N for details on sampling and curves. The z-scores are shown in Table 3. We note that our main findings in Section 3 still hold. Interestingly, compared to the previous section, L_2, L_1, and weight clipping all tend to be better than entropy regularization by larger margins. For the p-scores of statistical significance/improvement percentages, see Appendix F/G.

Table 3: The average z-score for each regularization method, under five sampled hyperparameter settings.

Reg \Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total
Baseline	0.49	-0.05	0.17	0.15	0.14	0.14	0.34	-0.27	-0.03	-0.01	-0.25	-0.15	0.24	-0.11	0.03
Entropy	0.42	0.52	0.48	0.19	0.26	0.24	0.14	-0.14	-0.03	**0.21**	-0.12	0.01	0.24	0.13	0.17
L_2	0.08	**0.82**	0.52	0.36	0.48	**0.43**	0.52	**0.86**	**0.72**	0.02	**0.27**	**0.17**	0.24	**0.61**	**0.46**
L_1	**0.53**	0.71	**0.64**	0.24	**0.51**	0.41	0.44	0.77	0.64	0.12	0.07	0.09	**0.33**	0.51	0.44
Weight Clip	0.45	0.50	0.48	**0.49**	0.41	**0.44**	0.23	0.52	0.40	-0.50	-0.00	-0.20	0.17	0.36	0.28
Dropout	-0.24	-1.07	-0.74	N/A	N/A	N/A	-0.92	-0.83	-0.87	0.01	-0.10	-0.06	-0.38	-0.67	-0.55
BatchNorm	-1.74	-1.42	-1.54	-1.43	-1.81	-1.66	-0.75	-0.91	-0.85	0.16	0.14	0.15	-0.94	-1.00	-0.98

To better visualize the robustness against change of hyperparameters, we show the result when a single hyperparameter is varied in Figure 2. We note that the certain regularizations can consistently improve the baseline with different hyperparameters. In these cases, proper regularizations can ease the hyperparameter tuning process, as they bring up performance of baselines with suboptimal hyperparameters to be higher than that with better ones.

Figure 2: Final reward vs. single hyperparameter change. "Rollout Timesteps" refers to the number of state-action samples used for training between policy updates.

5 POLICY AND VALUE NETWORK REGULARIZATION

Our experiments so far only impose regularization on policy network. To investigate the relationship between policy and value network regularization, we compare four options: 1) no regularization, and regularizing 2) policy network, 3) value network, 4) policy and value networks. For 2) and 3) we tune the regularization strengths independently and then use the appropriate ones for 4) (more details in Appendix C). We evaluate all four algorithms on the six MuJoCo tasks and present the improvement percentage in Table 4. Note that entropy regularization is not applicable to the value network. We observe that generally, only regularizing the policy network is the most often to improve almost all

Table 4: Percentage (%) of environments where performance "improves" when regularized on policy / value / policy and value networks.

Reg\Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Pol	Val	P+V	Pol	Val	P+V	Pol	Val	P+V	Pol	Val	P+V	Pol	Val	P+V
L_2	**50.0**	0.0	16.7	**50.0**	16.7	33.3	**66.7**	16.7	**66.7**	**66.7**	33.3	33.3	**58.3**	16.7	37.5
L_1	**50.0**	16.7	**50.0**	33.3	0.0	33.3	**66.7**	0.0	50.0	33.3	33.3	33.3	**45.8**	12.5	41.7
Weight Clip	16.7	0.0	**16.7**	**50.0**	33.3	16.7	**66.7**	0.0	**66.7**	33.3	16.7	16.7	**41.7**	8.3	29.2
Dropout	0.0	**16.7**	0.0	N/A	**33.3**	N/A	**66.7**	33.3	50.0	**50.0**	0.0	0.0	**38.9**	20.8	16.7
BatchNorm	**16.7**	**16.7**	**16.7**	0.0	**16.7**	0.0	16.7	0.0	**50.0**	**33.3**	16.7	0.0	**16.7**	12.5	**16.7**

algorithms and regularizations. Regularizing the value network alone does not bring improvement as often as other options. Though regularizing both is better than regularizing value network alone, it is worse than only regularizing the policy network. For detailed training curves, refer to Appendix O.

6 ANALYSIS AND CONCLUSION

Why does regularization benefit policy optimization? In RL, when we are training and evaluating on the same environment, there is no generalization gap across different environments. However, there is still generalization between samples: the agents is only trained on the limited trajectories it has experienced, which cannot cover the whole state-action space of the environment. A successful policy needs to generalize from seen samples to unseen ones, which potentially makes regularization necessary. This might also explain why regularization could be more helpful on harder tasks, which have larger state space, and the portion of the space that have appeared in training tends to be smaller. We study how regularization helps generalization through the following perspectives:

Sampling Complexity. We compare the reward with varying number of training samples/timesteps, since the performance of learning from fewer samples is closely related to generalization ability. From the results in Figure 3, we find that for regularized models to reach the same reward level as baseline, they need much fewer training samples. This suggests that certain regularizers can significantly reduce the sampling complexity of baseline and thus lead to better generalization.

Figure 3: Reward with different amount of training samples. Regularized models can reach similar performance as baseline with less data, showing their stronger generalization ability.

Reward Distribution. We evaluate agents trained with and without regularization on 100 different trajectories and plot the reward distributions over trajectories in Figure 4. These trajectories represent unseen samples during training, since the state space is continuous (so it is impossible to traverse identical trajectories). For baseline, some trajectories yield relatively high rewards, while others yield low rewards, demonstrating the baseline cannot stably generalize to unseen examples; for regularized models, the rewards are more concentrated at a high level, demonstrating they can more

Figure 4: Reward distribution (frequency vs. reward value) over 100 trajectories. Regularized models generalize to unseen samples more stably with high reward.

stably generalize to unseen samples. This suggests that certain conventional regularizers can improve the model's generalization ability to larger portion of unseen samples.

Weight Norm. We observe that on many tasks, smaller policy weight norm correlates with better generalization ability. An example is illustrated in Table 5. Even though both entropy-regularized model and L_2-regularized model have similar final policy entropy, L_2-regularized model have much higher final performance, possibly because L_2-encouraged small weight norm makes the network learn simpler models and less prone to overfitting. Similar observations can be made on CartPole-v1 (Figure 5), an easy toy environment. We train a single layer linear policy using PPO, and we observe that L_2 regularized model has a more stable performance over time. With time growing, baseline and entropy's weight norm increases, and the reward decreases, a sign of overfitting. L_2's performance is stable, with weight norm being smaller, which could benefit generalization.

Table 5: Comparison of performance, policy entropy, and policy weight norm on PPO Humanoid.

Reg	Reward	Entropy	Policy Norm
Baseline	3485±302	-10.32	30.73
Entropy	3914±334	10.70	30.91
L_2	8148±335	8.11	8.71

Table 6: Effect of data augmentation on final performance on PPO Humanoid.

	Baseline	L_2
w/ DA	3485±302	8148±335
w/o DA	3483±293	9006±145

Robustness to Training Noise. Recent works (Kostrikov et al., 2020; Laskin et al., 2020) have applied data augmentation (DA) to RL, mainly on image-based inputs, to improve data efficiency and generalization. Laskin et al. (2020) adds noise to state-based input observations by random scaling them, as a form of DA. We apply this technique to both baseline and L_2 regularization on PPO Humanoid and report results in Table 6. Interestingly, while DA cannot improve the baseline performance, it can significantly improve the performance of L_2-regularized model. This suggests $L_2$2 regularizer can make the model robust to, or even benefit from, noisy/augmented input during training.

Figure 5: Reward and policy network L_2 norm for cartpole trained with one-layer linear network.

Why do BN and dropout work only with off-policy algorithms? One finding in our experiments is BN and dropout can sometimes improve on the off-policy algorithm SAC, but mostly hurt on-policy algorithms. We hypothesize two possible reasons: 1) for both BN and dropout, training mode is used to train the network, and testing mode is used to sample actions during interaction with the environment, leading to a discrepancy between the sampling policy and optimization policy (the same holds if we always use training mode). For on-policy algorithms, if such discrepancy is large, it can cause severe "off-policy issues", which hurts the optimization process or even crashes it since their theory necessitates that the data is "on policy", i.e., data sampling and optimization policies are the same. For off-policy algorithms, this discrepancy is not an issue, since they sample data from replay buffer and do not require the two policies to be the same. 2) BN can be sensitive to input distribution shifts, since the mean and std statistics depend on the input, and if the input distribution changes too quickly in training, the mapping functions of BN layers can change quickly too, which can possibly destabilize training. One evidence for this is that in supervised learning, when transferring a ImageNet pretrained model to other vision datasets, sometimes the BN layers are fixed (Yang et al., 2017) and only other layers are trained. In off-policy algorithms, the sample distributions are relatively slow-changing since we always draw from the whole replay buffer which holds cumulative data; in on-policy algorithms, we always use the samples generated from the latest policy, and the faster-changing input distribution for on-policy algorithms could be harmful to BN. BN has also been shown to be useful in DDPG (Lillicrap et al., 2015), an off-policy algorithm.

In summary, we conducted the first systematic study of regularization methods on multiple policy optimization algorithms. We found that conventional regularizations (L_2, L_1, weight clipping) could be effective at improving performance, sometimes more than entropy regularization. BN and dropout could be useful but only on off-policy algorithms. Our findings were confirmed with multiple sampled hyperparameters. Further experiments have shown that generally, the best practice is to regularize the policy network but not the value network or both. Finally we analyze why regularization can help in RL with experiments and discussions.

REFERENCES

Maruan Al-Shedivat, Trapit Bansal, Yuri Burda, Ilya Sutskever, Igor Mordatch, and Pieter Abbeel. Continuous adaptation via meta-learning in nonstationary and competitive environments. *arXiv preprint arXiv:1710.03641*, 2017.

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein gan. *arXiv preprint arXiv:1701.07875*, 2017.

Marc G. Bellemare, Yavar Naddaf, Joel Veness, and Michael Bowling. The arcade learning environment: An evaluation platform for general agents. *CoRR*, abs/1207.4708, 2012. URL http://arxiv.org/abs/1207.4708.

Richard Cheng, Abhinav Verma, Gbor Orosz, Swarat Chaudhuri, Yisong Yue, and Joel Burdick. Control regularization for reduced variance reinforcement learning. *arXiv preprint arXiv:1905.05380*, 2019.

Karl Cobbe, Oleg Klimov, Chris Hesse, Taehoon Kim, and John Schulman. Quantifying generalization in reinforcement learning. *arXiv preprint arXiv:1812.02341*, 2018.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Prafulla Dhariwal, Christopher Hesse, Oleg Klimov, Alex Nichol, Matthias Plappert, Alec Radford, John Schulman, Szymon Sidor, Yuhuai Wu, and Peter Zhokhov. Openai baselines. https://github.com/openai/baselines, 2017.

Yan Duan, John Schulman, Xi Chen, Peter L Bartlett, Ilya Sutskever, and Pieter Abbeel. Rl2: Fast reinforcement learning via slow reinforcement learning. *arXiv preprint arXiv:1611.02779*, 2016.

Amir M. Farahmand, Mohammad Ghavamzadeh, Shie Mannor, and Csaba Szepesvári. Regularized policy iteration. In D. Koller, D. Schuurmans, Y. Bengio, and L. Bottou (eds.), *Advances in Neural Information Processing Systems 21*, pp. 441–448. Curran Associates, Inc., 2009. URL http://papers.nips.cc/paper/3445-regularized-policy-iteration.pdf.

Jesse Farebrother, Marlos C Machado, and Michael Bowling. Generalization and regularization in dqn. *arXiv preprint arXiv:1810.00123*, 2018.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 1126–1135. JMLR. org, 2017.

Scott Fujimoto, Herke van Hoof, and David Meger. Addressing function approximation error in actor-critic methods. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 1587–1596, Stockholmsmässan, Stockholm Sweden, 10–15 Jul 2018. PMLR.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pp. 2672–2680, 2014.

Abhishek Gupta, Russell Mendonca, YuXuan Liu, Pieter Abbeel, and Sergey Levine. Meta-reinforcement learning of structured exploration strategies. In *Advances in Neural Information Processing Systems*, pp. 5302–5311, 2018.

Tuomas Haarnoja. Soft actor-critic. https://github.com/haarnoja/sac, 2018.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International Conference on Machine Learning*, pp. 1856–1865, 2018.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Peter Henderson, Riashat Islam, Philip Bachman, Joelle Pineau, Doina Precup, and David Meger. Deep reinforcement learning that matters. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. *arXiv preprint arXiv:1502.03167*, 2015.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. 2015.

Oleg Klimov and John Schulman. Roboschool. https://openai.com/blog/roboschool, 2017.

Arno Knapitsch, Jaesik Park, Qian-Yi Zhou, and Vladlen Koltun. Tanks and temples: Benchmarking large-scale scene reconstruction. *ACM Trans. Graph.*, 36(4), July 2017. ISSN 0730-0301. doi: 10.1145/3072959.3073599. URL https://doi.org/10.1145/3072959.3073599.

Ilya Kostrikov, Denis Yarats, and Rob Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels, 2020.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pp. 1097–1105, 2012.

Michael Laskin, Kimin Lee, Adam Stooke, Lerrel Pinto, Pieter Abbeel, and Aravind Srinivas. Reinforcement learning with augmented data, 2020.

Timothy Lillicrap, Jonathan Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. In *International Conference on Learning Representations*, 2016.

Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *arXiv preprint arXiv:1509.02971*, 2015.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019.

Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International conference on machine learning*, pp. 1928–1937, 2016.

Gergely Neu, Anders Jonsson, and Vicenç Gómez. A unified view of entropy-regularized markov decision processes, 2017.

OpenAI. Open-source software for robot simulation, integrated with openai gym. https://github.com/openai/roboschool.

Charles Packer, Katelyn Gao, Jernej Kos, Philipp Krähenbühl, Vladlen Koltun, and Dawn Song. Assessing generalization in deep reinforcement learning. *arXiv preprint arXiv:1810.12282*, 2018.

Simone Parisi, Voot Tangkaratt, Jan Peters, and Mohammad Emtiyaz Khan. Td-regularized actor-critic methods. In *Machine Learning*, pp. 1–35, 2019.

Anay Pattanaik, Zhenyi Tang, Shuijing Liu, Gautham Bommannan, and Girish Chowdhary. Robust deep reinforcement learning with adversarial attacks. In *Proceedings of the 17th International Conference on Autonomous Agents and MultiAgent Systems*, pp. 2040–2042. International Foundation for Autonomous Agents and Multiagent Systems, 2018.

Aravind Rajeswaran, Kendall Lowrey, Emanuel V Todorov, and Sham M Kakade. Towards generalization and simplicity in continuous control. In *Advances in Neural Information Processing Systems*, pp. 6550–6561, 2017.

René Ranftl, Katrin Lasinger, David Hafner, Konrad Schindler, and Vladlen Koltun. Towards robust monocular depth estimation: Mixing datasets for zero-shot cross-dataset transfer. *arXiv:1907.01341*, 2019.

Joseph Redmon, Santosh Divvala, Ross Girshick, and Ali Farhadi. You only look once: Unified, real-time object detection. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 779–788, 2016.

Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster r-cnn: Towards real-time object detection with region proposal networks. In *Advances in neural information processing systems*, pp. 91–99, 2015.

John Schulman, Sergey Levine, Pieter Abbeel, Michael Jordan, and Philipp Moritz. Trust region policy optimization. In *International Conference on Machine Learning*, pp. 1889–1897, 2015.

John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. In *International Conference on Learning Representations*, 2016.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine learning research*, 15(1):1929–1958, 2014.

Mario Srouji, Jian Zhang, and Ruslan Salakhutdinov. Structured control nets for deep reinforcement learning. In *International Conference on Machine Learning*, pp. 4749–4758, 2018.

Richard S Sutton, David A McAllester, Satinder P Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. In *Advances in neural information processing systems*, pp. 1057–1063, 2000.

Yee Teh, Victor Bapst, Wojciech M Czarnecki, John Quan, James Kirkpatrick, Raia Hadsell, Nicolas Heess, and Razvan Pascanu. Distral: Robust multitask reinforcement learning. In *Advances in Neural Information Processing Systems*, pp. 4496–4506, 2017.

Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *2017 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 23–30. IEEE, 2017.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 5026–5033. IEEE, 2012.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Ronald J Williams and Jing Peng. Function optimization using connectionist reinforcement learning algorithms. *Connection Science*, 3(3):241–268, 1991.

Jianwei Yang, Jiasen Lu, Dhruv Batra, and Devi Parikh. A faster pytorch implementation of faster r-cnn. https://github.com/jwyang/faster-rcnn.pytorch, 2017.

Amy Zhang, Nicolas Ballas, and Joelle Pineau. A dissection of overfitting and generalization in continuous reinforcement learning. *ArXiv*, abs/1806.07937, 2018a.

Chiyuan Zhang, Oriol Vinyals, Remi Munos, and Samy Bengio. A study on overfitting in deep reinforcement learning. *arXiv preprint arXiv:1804.06893*, 2018b.

Kaiqing Zhang, Bin Hu, and Tamer Başar. Policy optimization for $\mathcal{H}_2$ linear control with $\mathcal{H}_\infty$ robustness guarantee: Implicit regularization and global convergence, 2020.

Chenyang Zhao, Olivier Sigaud, Freek Stulp, and Timothy M. Hospedales. Investigating generalisation in continuous deep reinforcement learning. *ArXiv*, abs/1902.07015, 2019.

Brian D. Ziebart, Andrew Maas, J. Andrew Bagnell, and Anind K. Dey. Maximum entropy inverse reinforcement learning. In *Proceedings of the 23rd National Conference on Artificial Intelligence - Volume 3*, AAAI'08, pp. 1433–1438. AAAI Press, 2008. ISBN 978-1-57735-368-3. URL http://dl.acm.org/citation.cfm?id=1620270.1620297.

APPENDIX

TABLE OF CONTENTS

A REGULARIZATION METHODS

There are in general two types of common approaches for imposing regularization. One is to discourage complex models (e.g., weight regularization, weight clipping), and the other is to inject certain noise in network activations (e.g., dropout and Batch Normalization). Here we briefly introduce the methods we investigate in our experiments.

L_2 / L_1 **Weight Regularization.** Suppose L is the original empirical loss we want to minimize. When applying L_2 regularization, we add an additional L_2-norm squared loss term $\frac{1}{2}\lambda||\theta||_2^2$ to L, where θ are model parameters and λ is a hyperparameter. Similarly, in the case of L_1 weight regularization, the additional loss term is $\lambda||\theta||_1$. In our experiments, the total loss is optimized using Adam (Kingma & Ba, 2015). Using L_2/L_1 regularization can encourage the model to be simpler/sparse. From a Bayesian view, they impose certain prior distributions on model weights.

Weight Clipping. Weight clipping is a simple operation: after each gradient update step, each individual weight is clipped to range $[-c, c]$, where c is a hyperparameter. This could be formally described as $\theta_i \leftarrow \max(\min(\theta_i, c), -c)$. In Wasserstein GANs (Arjovsky et al., 2017), weight clipping is used to enforce the constraint of Lipschitz continuity. This plays an important role in stabilizing the training of GANs (Goodfellow et al., 2014) Weight clipping can also be seen as a regularizor since it reduce the complexity of the model space, by preventing any weight's magnitude from being larger than c.

Dropout. Dropout (Srivastava et al., 2014) is one of the most successful regularization techniques developed specifically for neural networks. During training, a certain percentage of neurons is deactivated; during testing, all neurons in the neural network are kept, and rescaling is applied to ensure the scale of the activations is the same as training. One explanation for its effectiveness in reducing overfitting is they can prevent "co-adaptation" of neurons. In the policy optimization algorithms we investigate, when the policy or the value network performs updates using minibatches of trajectory data or replay buffer data, we use the training mode of dropout. When the policy network samples trajectories from the environment, we use the testing mode of dropout.

Batch Normalization. Batch Normalization (BN) (Ioffe & Szegedy, 2015) is invented to address the problem of "internal covariate shift", and it does the following transformation: $\hat{z} = \frac{z_{in}-\mu_\mathcal{B}}{\sqrt{\sigma_\mathcal{B}^2+\epsilon}}$; $z_{out} = \gamma\hat{z} + \beta$, where $\mu_\mathcal{B}$ and $\sigma_\mathcal{B}$ are the mean and standard deviation of input activations over $\mathcal{B}$, and γ and β are trainable affine transformation parameters. BN turns out to greatly accelerate the convergence and bring up the accuracy. It also acts as a regularizer (Ioffe & Szegedy, 2015): during training, the statistics $\mu_\mathcal{B}$ and $\sigma_\mathcal{B}$ depend on the current batch, and BN subtracts and divides different values in each iteration. This stochasticity can encourage subsequent layers to be robust against such input variation. In policy optimization algorithms, we switch between training and testing modes the same way as we do in dropout.

Entropy Regularization. In a policy optimization framework, the policy network is used to model a conditional distribution over actions, and entropy regularization is widely used to prevent the learned policy from overfitting to one or some of the actions. More specifically, in each step, the output distribution of the policy network is penalized to have a high entropy. Policy entropy is calculated at each step as $H_{s_i} = -\mathbb{E}_{a_i \sim \pi(a_i|s_i)} \log \pi(a_i|s_i)$, where (s_i, a_i) is the state-action pair. Then the per-sample entropy is averaged within the batch of state-action pairs to obtain the regularization term $L^H = \frac{1}{N}\sum_{s_i} H_{s_i}$. A coefficient λ is also needed, and λL^H is added to the policy objective $J(\theta)$. The sum is then maximized during policy updates. Entropy regularization also encourages exploration and prevents premature convergence due to increased randomness in actions, leading to better performance in the long run.

B POLICY OPTIMIZATION ALGORITHMS

The policy optimization family of algorithms is one of the most popular methods for solving reinforcement learning problems. It directly parameterizes and optimizes the policy to gain more cumulative rewards. Below, we give a brief introduction to the algorithms we evaluate in our work.

A2C. Sutton et al. (2000) developed a policy gradient to update the parametric policy in a gradient descent manner. However, the gradient estimated in this way suffers from high variance. Advantage

Actor Critic (A3C) (Mnih et al., 2016) is proposed to alleviate this problem by introducing a function approximator for values and replacing the Q-values with advantage values. A3C also utilizes multiple actors to parallelize training. The only difference between A2C and A3C is that in a single training iteration, A2C waits for parallel actors to finish sampling trajectories before updating the neural network parameters, while A3C updates in an asynchronous manner.

TRPO. Trust Region Policy Optimization (TRPO) (Schulman et al., 2015) proposes to constrain each update within a safe region defined by KL divergence to guarantee policy improvement during training. Though TRPO is promising at obtaining reliable performance, approximating the KL constraint is quite computationally heavy.

PPO. Proximal Policy Optimization (PPO) (Schulman et al., 2017) simplifies TRPO and improves computational efficiency by developing a surrogate objective that involves clipping the probability ratio to a reliable region, so that the objective can be optimized using first-order methods.

SAC. Soft Actor Critic (SAC) (Haarnoja et al., 2018) optimizes the maximum entropy objective in reward (Ziebart et al., 2008), which is different from the objective of the on-policy methods above. SAC combines soft policy iteration, which maximizes the maximum entropy objective, and clipped double Q learning (Fujimoto et al., 2018), which prevents overestimation bias, during actor and critic updates, respectively.

C REGULARIZATION IMPLEMENTATION & TUNING DETAILS

As mentioned in the paper, in Section 3 we only regularize the policy network; in Section 5, we investigate regularizing both policy and value networks.

For L_1 and L_2 regularization, we add $\lambda ||\theta||_1$ and $\frac{\lambda}{2} ||\theta||_2^2$, respectively, to the loss of policy network or value network of each algorithm (for SAC's value regularization, we apply regularization only to the V network instead of also to the two Q networks). L_1 and L_2 loss are applied to all the weights of the policy or value network. For A2C, TRPO, and PPO, we tune λ in the range of $[1e-5, 5e-5, 1e-4, 5e-4]$ for L_1 and $[5e-5, 1e-4, 5e-4, 1e-3]$ for L_2. For SAC, we tune λ in the range of $[5e-4, 1e-3, 5e-3, 1e-2]$ for L_1 and $[1e-3, 5e-3, 1e-2, 5e-2]$ for L_2.

For weight clipping, the OpenAI Baseline implementation of the policy network of A2C, TRPO, and PPO outputs the mean of policy action from a two-layer fully connected network (MLP). The log standard deviation of the policy action is represented by a standalone trainable vector. We find that when applied only to the weights of MLP, weight clipping makes the performance much better than when applied to only the logstd vector or both. Thus, for these three algorithms, the policy network weight clipping results shown in all the sections above come from clipping only the MLP part of the policy network. On the other hand, in the SAC implementation, both the mean and the log standard deviation come from the same MLP, and there is no standalone log standard deviation vector. Thus, we apply weight clipping to all the weights of the MLP. For all algorithms, we tune the policy network clipping range in $[0.1, 0.2, 0.3, 0.5]$. For value network, the MLP produces a single output of estimated value given a state, so we clip all the weights of the MLP. For A2C, TRPO, and PPO, we tune the clipping range in $[0.1, 0.2, 0.3, 0.5]$. For SAC, we only clip the V network and do not clip the two Q networks for simplicity. We tune the clipping range in $[0.3, 0.5, 0.8, 1.0]$ due to its weights having larger magnitude.

For BatchNorm/dropout, we apply it before the activation function of each hidden layer/immediately after the activation function. When the policy or the value network is performing update using minibatches of trajectory data or minibatches of replay buffer data, we use the train mode of regularization and update the running mean and standard deviation. When the policy is sampling trajectory from the environment, we use the test mode of regularization and use the existing running mean and standard deviation to normalize data. For Batch Normalization/dropout on value network, only training mode is applied since value network does not participate in sampling trajectories. Note that adding policy network dropout on TRPO causes the KL divergence constraint $\mathbb{E}_{s \sim \rho_{\theta_{old}}} [D_{KL} (\pi_{\theta_{old}}(\cdot|s) \| \pi_\theta(\cdot|s))] \leq \delta$ to be violated almost every time during policy network update. Thus, policy network dropout causes the training to fail on TRPO, as the policy network cannot be updated.

For entropy regularization, we add $-\lambda L^H$ to the policy loss. λ is tuned from $[5e-5, 1e-4, 5e-4, 1e-3]$ for A2C, TRPO, PPO and $[0.1, 0.5, 1.0, 5.0]$ for SAC. Note that for SAC, our entropy regularization is added directly on the optimization objective (equation 12 in Haarnoja et al. (2018)), and is different from the original maximum entropy objective inside the reward term.

Note that for the three on-policy algorithms (A2C, TRPO, PPO) we use the same tuning range, and the only exception is the off-policy SAC. The reason why SAC's tuning range is different is that SAC uses a hyperparameter that controls the scaling of the reward signal, while A2C, TRPO, and PPO do not. In the original implementation of SAC, the reward signals are pre-tuned to be scaled up by a factor ranging from 5 to 100, according to specific environments. Also, unlike A2C, TRPO, and PPO, SAC uses unnormalized reward because if the reward magnitude is small, then, according to the original paper, the policy becomes almost uniform. Due to the above reasons, the reward magnitude of SAC is much higher than the magnitude of rewards used by A2C, TRPO, and PPO. Thus, the policy network loss and the value network loss have larger magnitude than those of A2C, TRPO, and PPO, so the appropriate regularization strengths become higher. Considering the SAC's much larger reward magnitude, we selected a different range of hyperparameters for SAC before we ran the whole experiments.

The optimal policy network regularization strength we selected for each algorithm and environment used in Section 3 can be seen in the legends of Appendix O. In addition to the results with environment-specific strengths presented in Section 3, we also present the results when the regularization strength is fixed across all environments for the same algorithm. The results are shown in Appendix J.

In Section 5, to investigate the effect of regularizing both policy and value networks, we combine the tuned optimal policy and value network regularization strengths. The detailed training curves are presented in Appendix O.

As a side note, when training A2C, TRPO, and PPO on the HalfCheetah environment, the results have very large variance. Thus, for each regularization method, after we obtain the best strength, we rerun it for another five seeds as the final result in Table 1 and 2.

D DEFAULT HYPERPARAMETER SETTINGS

Training timesteps. For A2C, TRPO, and PPO, we run $5e6$ timesteps for Hopper, Walker, and HalfCheetah; $2e7$ timesteps for Ant, Humanoid (MuJoCo), and HumanoidStandup; $5e7$ timesteps for Humanoid (RoboSchool); and $1e8$ timesteps for AtlasForwardWalk and HumanoidFlagrun. For SAC, since its simulation speed is much slower than A2C, TRPO, and PPO (as SAC updates its policy and value networks using a minibatch of replay buffer data at every timestep), and since it takes fewer timesteps to converge, we run $1e6$ timesteps for Hopper and Walker; $3e6$ timesteps for HalfCheetah and Ant; $5e6$ timesteps for Humanoid and HumanoidStandup; and $1e7$ timesteps for the RoboSchool environments.

Hyperparameters for RoboSchool. In the original PPO paper (Schulman et al., 2017), hyperparameters for the Roboschool tasks are given, so we apply the same hyperparameters to our training, except that instead of linear annealing the log standard deviation of action distribution from -0.7 to -1.6, we let it to be learnt by the algorithm, as implemented in OpenAI Baseline (Dhariwal et al., 2017). For TRPO, due to its proximity to PPO, we copy PPO's hyperparameters if they exist in both algorithms. We then tune the value update step size in $[3e-4, 5e-4, 1e-3]$. For A2C, we keep the original hyperparameters and tune the number of actors in $[32, 128]$ and the number of timesteps for each actor between consecutive policy updates in $[5, 16, 32]$. For SAC, we tune the reward scale from $[5, 20, 100]$.

The detailed hyperparameters used in our baselines for both MuJoCo and RoboSchool are listed in Tables 7-10.

Table 7: Baseline hyperparameter setting for A2C MuJoCo and RoboSchool tasks.

Hyperparameter	Value
Hidden layer size	64×2
Sharing policy and value weights	False
Number of hidden layers	2
Rollout timesteps per actor	5
Number of actors	1
Step size	$7e - 4$, linear decay
Max gradient norm	0.5
Discount factor (γ)	0.99

Hyperparameter	Value
Hidden layer size	64×2
Number of hidden layers	2
Sharing policy and value weights	False
Rollout timesteps per actor	32
Number of actors	32 (Humanoid, Atlas) 128 (Flagrun)
Step size	$7e - 4$, linear decay
Max gradient norm	0.5
Discount factor (γ)	0.99

Table 8: Baseline hyperparameter setting for TRPO Mujoco and RoboSchool tasks. The original OpenAI implementation does not support multiple actors sampling trajectories at the same time, so we modified the code to support this feature and accelerate training.

Hyperparameter	Value
Hidden layer size	32×2
Number of hidden layers	2
Sharing policy and value weights	False
Rollout timesteps per actor	1024
Number of actors	1
Value network step size	$1e - 3$, constant
Max KL divergence	0.01
Discount factor (γ)	0.99
GAE parameter (λ)	0.98
Conjugate gradient damping	0.1
Conjugate gradient iterations	10
Value network optimization epochs	10
Value network update minibatch size	64
Probability ratio clipping range	0.2

Hyperparameter	Value
Hidden layer size	64×2
Number of hidden layers	2
Sharing policy and value weights	False
Rollout timesteps per actor	512
Number of actors	32 (Humanoid, Atlas) 128 (Flagrun)
value network step size	$1e - 3$, constant
Max KL divergence	0.01
Discount factor (γ)	0.99
GAE parameter (λ)	0.98
Conjugate gradient damping	0.1
Conjugate gradient iterations	10
Value network optimization epochs	15
Value network update minibatch size	4096
Probability ratio clipping range	0.2

Table 9: Baseline hyperparameter setting for PPO MuJoCo and RoboSchool tasks.

Hyperparameter	Value
Hidden layer size	64×2
Number of hidden layers	2
Sharing policy and value weights	False
Rollout timesteps per actor	2048
Number of actors	1
Number of minibatches	32
Step size	$3e - 4$, linear decay
Max gradient norm	0.5
Discount factor (γ)	0.99
GAE parameter (λ)	0.95
Number of optimization epochs	10
Probability ratio clipping range	0.2

Hyperparameter	Value
Hidden layer size	64×2
Number of hidden layers	2
Sharing policy and value weights	False
Rollout timesteps per actor	512
Number of actors	32 (Humanoid, Atlas) 128 (Flagrun)
Minibatch size	4096
Step size	$3e - 4$, linear decay
Max gradient norm	0.5
Discount factor (γ)	0.99
GAE parameter (λ)	0.95
Number of optimization epochs	15
Probability ratio clipping range	0.2

Table 10: Baseline hyperparameter setting for SAC.

Hyperparameter	Value
Hidden layer size	256×2
Number of hidden layers	2
Samples per batch	256
Replay buffer size	10^6
Learning rate	$3e - 4$ constant
Discount factor (γ)	0.99
Target smoothing coefficient (τ)	0.005
Target update interval	1
Reward Scaling	5 (Hopper, Walker, HalfCheetah, Ant) 20 (MuJoCo Humanoid and all RoboSchool tasks) 100 (HumanoidStandup)

E HYPERPARAMETER SAMPLING DETAILS

In Section 4, we present results based on five hyperparameter settings. To obtain such hyperparameter variations, we consider varying the learning rates and the hyperparameters that each algorithm is very sensitive to. For A2C, TRPO, and PPO, we consider a range of rollout timesteps between consecutive policy updates by varying the number of actors or the number of trajectory sampling timesteps for each actor. For SAC, we consider a range of reward scale and a range of target smoothing coefficient.

More concretely, for A2C, we sample the learning rate from $[2e - 4, 7e - 4, 2e - 3]$ linear decay, the number of trajectory sampling timesteps (nsteps) for each actor from $[3, 5, 16, 32]$, and the number of actors (nenvs) from $[1, 4]$. For TRPO, we sample the learning rate of value network (vf_stepsize) from $[3e - 4, 5e - 4, 1e - 3]$ and the number of trajectory sampling timesteps for each actor (nsteps) in $[1024, 2048, 4096, 8192]$. The policy update uses conjugate gradient descent and is controlled by the max KL divergence. For PPO, we sample the learning rate from $[1e - 4$ linear, $3e - 4$ constant$]$, the number of actors (nenvs) from $[1, 2, 4, 8]$, and the probability ratio clipping range (cliprange) in $[0.1, 0, 2]$. For SAC, we sample the learning rate from $[1e - 4, 3e - 4, 1e - 3]$ the target smoothing coefficient (τ) from $[0.001, 0.005, 0.01]$, and the reward scale from small, default, and large mode. The default reward scale of 5 is changed to $(3, 5, 20)$; 20 to $(4, 20, 100)$; 100 to $(20, 100, 400)$ for each mode, respectively. Sampled hyperparameters 1-5 for each algorithms are listed in Table 11-14.

Table 11: Sampled hyperparameter settings for A2C.

	Learning rate	Nsteps	Nenvs
Baseline	$7e - 4$	5	1
Hyperparam. 1	$2e - 3$	32	4
Hyperparam. 2	$2e - 3$	32	1
Hyperparam. 3	$7e - 4$	16	1
Hyperparam. 4	$7e - 4$	32	4
Hyperparam. 5	$2e - 4$	3	4

Table 12: Sampled hyperparameter settings for TRPO.

	Vf_stepsize	Nsteps
Baseline	$1e - 3$	1024
Hyperparam. 1	$5e - 4$	8192
Hyperparam. 2	$1e - 3$	4096
Hyperparam. 3	$3e - 4$	2048
Hyperparam. 4	$5e - 4$	1024
Hyperparam. 5	$5e - 4$	4096

Table 13: Sampled hyperparameter settings for PPO

	Learning rate	Nenvs	Cliprange
Baseline	$3e - 4$ linear	1	0.2
Hyperparam. 1	$3e - 4$ linear	8	0.2
Hyperparam. 2	$1e - 4$ constant	8	0.2
Hyperparam. 3	$3e - 4$ linear	4	0.1
Hyperparam. 4	$1e - 4$ constant	2	0.2
Hyperparam. 5	$3e - 4$ linear	1	0.1

Table 14: Sampled hyperparameter settings for SAC

	Learning rate	τ	Mode
Baseline	$3e-4$	0.005	default
Hyperparam. 1	$3e-4$	0.005	small
Hyperparam. 2	$1e-4$	0.001	large
Hyperparam. 3	$1e-3$	0.005	small
Hyperparam. 4	$3e-4$	0.01	small
Hyperparam. 5	$1e-3$	0.005	default

F   STATISTICAL SIGNIFICANCE TEST OF z-SCORES

For each regularization method, we collect the z-scores produced by all seeds and all environments of a certain difficulty (e.g. for L_2 on PPO and hard environments, we have 6 envs $\times$ 5 seeds = 30 z-scores), and perform Welch's t-test (two-sample t-test with unequal variance) with the corresponding z-scores produced by the baseline. The resulting p-values for Table 2 in Section 3 and Table 3 in Section 4 are presented in Table 15 and Table 16, respectively. Note that whether the significance indicates improvement or harm depends on the relative mean z-score in Table 2 and Table 3. For example, for BN and dropout in on-policy algorithms, the statistical significance denotes harm, and in most other cases it denotes improvement. From the results, we observe that the improvement is statistically significant ($p < 0.05$) for hard tasks in general, with only a few exceptions. In total, L_2, L_1, entropy and weight clipping are all statistically significantly better than baseline. For Welch's t-test between entropy regularization and other regularizers, see Appendix H.

Table 15: P-values from Welch's t-test comparing the z-scores of regularization methods and baseline.

Reg \Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total
Entropy	0.01	0.00	0.00	0.65	0.16	0.47	0.61	0.21	0.22	0.26	0.24	0.10	0.05	0.00	0.00
L_2	0.37	0.00	0.00	0.43	0.05	0.05	0.86	0.00	0.00	0.21	0.01	0.01	0.10	0.00	0.00
L_1	0.54	0.00	0.02	0.92	0.00	0.01	0.94	0.00	0.00	0.35	0.25	0.14	0.62	0.00	0.00
Weight Clip	0.78	0.02	0.09	0.99	0.02	0.07	0.79	0.00	0.00	0.76	0.21	0.41	0.87	0.00	0.00
Dropout	0.00	0.00	0.00	N/A	N/A	N/A	0.27	0.80	0.74	0.21	0.00	0.00	0.02	0.43	0.05
BatchNorm	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.10	0.00	0.38	0.02	0.25	0.00	0.00	0.00

Table 16: P-values from Welch's t-test comparing the z-scores of regularization and baseline, under five sampled hyperparameter settings.

Reg \Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total
Entropy	0.58	0.00	0.00	0.71	0.14	0.19	0.23	0.36	0.98	0.28	0.40	0.18	0.96	0.00	0.01
L_2	0.00	0.00	0.00	0.12	0.00	0.00	0.31	0.00	0.00	0.89	0.00	0.01	0.99	0.00	0.00
L_1	0.77	0.00	0.00	0.40	0.00	0.00	0.55	0.00	0.00	0.51	0.04	0.05	0.25	0.00	0.00
Weight Clip	0.77	0.00	0.00	0.01	0.01	0.00	0.51	0.00	0.00	0.02	0.14	0.69	0.37	0.00	0.00
Dropout	0.00	0.00	0.00	N/A	N/A	N/A	0.00	0.00	0.00	0.96	0.29	0.41	0.00	0.00	0.00
BatchNorm	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.39	0.05	0.03	0.00	0.00	0.00

G   IMPROVEMENT PERCENTAGE FOR HYPERPARAMETER EXPERIMENTS

We provide the percentage of improvement result in Table 17 as a complement with Table 3, for the experiments with multiple sampled hyperparameters.

Table 17: Percentage (%) of environments where the final performance "improves" when using regularization, under five randomly sampled training hyperparameters for each algorithm.

Reg \ Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total
Entropy	**20.0**	40.0	32.0	0.0	26.7	16.0	10.0	33.3	24.0	**60.0**	13.3	**32.0**	22.5	28.3	26.0
L_2	**20.0**	**60.0**	**44.0**	10.0	40.0	28.0	**20.0**	**86.7**	**60.0**	10.0	**40.0**	28.0	15.0	**56.7**	**40.0**
L_1	10.0	53.3	36.0	10.0	**46.7**	32.0	10.0	**86.7**	56.0	20.0	26.7	24.0	12.5	53.3	37.0
Weight Clip	0.0	46.7	28.0	**40.0**	**46.7**	**44.0**	10.0	73.3	48.0	0.0	33.3	20.0	12.5	50.0	35.0
Dropout	**20.0**	0.0	8.0	N/A	N/A	N/A	0.0	40.0	24.0	0.0	20.0	12.0	6.7	20.0	14.7
BatchNorm	0.0	0.0	0.0	10.0	0.0	4.0	10.0	33.3	24.0	20.0	20.0	20.0	10.0	13.3	12.0

H   STATISTICAL SIGNIFICANCE TEST OF z-SCORES (ENTROPY REGULARIZATION)

As a complement to Table 2 in Section 3 and Table 3 in Section 4, we present the p-value results from Welch's t-test comparing the z-scores of entropy regularization with other regularizers in Table 18 and Table 19. Note that whether the significance indicates improvement or harm over entropy regularization depends on the relative mean z-score in Table 2 under default hyperparameter setting and Table 3 under sampled hyperparameter setting. We observe that in total, L_2 has significant improvement over entropy in both default hyperparameter setting and sampled hyperparameter setting. L_1 and weight clipping are significantly better than entropy under sampled hyperparameter setting. In general, the improvement over entropy is statistically more significant for hard tasks.

Table 18: *P*-values from Welch's *t*-test comparing the z-scores of entropy regularization and other regularizers, under the default hyperparameter setting.

Reg \Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total
L_2	0.05	0.56	0.07	0.22	0.59	0.21	0.66	0.00	0.00	0.89	0.07	0.12	0.58	0.00	0.02
L_1	0.00	0.00	0.00	0.57	0.05	0.07	0.62	0.00	0.00	0.67	0.93	0.75	0.06	0.10	0.83
Weight Clip	0.01	0.00	0.00	0.64	0.27	0.25	0.79	0.00	0.00	0.05	0.81	0.37	0.02	0.42	0.42
Dropout	0.00	0.00	0.00	N/A	N/A	N/A	0.07	0.43	0.12	0.93	0.01	0.03	0.00	0.00	0.00
BatchNorm	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.16	0.60	0.00	0.00	0.00

Table 19: *P*-values from Welch's *t*-test comparing the z-scores of entropy regularization and other regularizers, under five sampled hyperparameter settings for each policy optimization algorithm.

Reg \Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total
L_2	0.01	0.00	0.59	0.25	0.00	0.01	0.02	0.00	0.00	0.33	0.01	0.17	0.96	0.00	0.00
L_1	0.41	0.04	0.04	0.69	0.00	0.01	0.07	0.00	0.00	0.63	0.20	0.53	0.23	0.00	0.00
Weight Clip	0.76	0.86	0.96	0.03	0.11	0.01	0.59	0.00	0.00	0.00	0.45	0.11	0.40	0.00	0.04
Dropout	0.00	0.00	0.00	N/A	N/A	N/A	0.00	0.00	0.00	0.31	0.85	0.56	0.00	0.00	0.00
BatchNorm	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.80	0.17	0.33	0.00	0.00	0.00

I   ADDITIONAL METRICS

I.1   RANKING ALL REGULARIZERS

We compute the "average ranking" metric to compare the relative effectiveness of different regularization methods. Note that the average ranking of different methods across a set of tasks/datasets has been adopted as a metric before, as in (Ranftl et al., 2019) and (Knapitsch et al., 2017). Here, we rank the performance of all the regularization methods, together with the baseline, for each algorithm and task, and present the average ranks in Table 20 and Table 21. The ranks of returns among different regularizers are collected for each environment (after averaging over 5 random seeds), and then the mean rank over all seeds is calculated. From Table 20 and Table 21, we observe that, except for BN and dropout in on-policy algorithms, all regularizations on average outperform baselines. Again, L_2 regularization is the strongest in most cases. Other similar observations can be made as in previous tables. For every algorithm, baseline ranks lower on harder tasks than easier ones; in total, it ranks 3.50 for easier tasks and 5.25 for harder tasks. This indicates that regularization is more effective when the tasks are harder.

Table 20: The average rank in the mean return for different regularization methods under default hyperparameter settings. L_2 regularization tops the ranking for most algorithms and environment difficulties.

Reg \ Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total
Baseline	3.33	4.50	4.11	3.33	4.67	4.22	3.00	6.00	5.00	4.33	5.83	5.33	3.50	5.25	4.67
Entropy	**1.00**	**1.50**	**1.33**	4.67	3.00	3.56	**3.00**	4.17	3.78	**3.00**	3.83	3.55	2.92	3.13	3.06
L_2	2.67	**1.50**	1.89	**1.33**	2.83	**2.33**	**3.00**	2.17	**2.45**	**3.00**	2.67	**2.78**	**2.50**	**2.29**	**2.36**
L_1	4.33	3.67	3.89	2.67	**2.17**	2.34	3.33	2.67	2.89	3.67	4.83	4.44	3.50	3.34	3.39
Weight Clip	3.67	3.83	3.78	3.00	2.33	2.55	**3.00**	2.50	2.67	4.33	4.17	4.22	3.50	3.21	3.31
Dropout	6.00	6.00	6.00	N/A	N/A	N/A	5.67	4.67	5.00	3.33	3.17	3.22	5.00	4.61	4.74
BatchNorm	7.00	7.00	7.00	6.00	6.00	6.00	7.00	5.83	6.22	6.33	3.50	4.44	6.58	5.58	5.92

Table 21: The average rank in the mean return for different regularization methods, under five randomly sampled training hyperparameters for each algorithm.

Reg \ Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total
Baseline	**2.70**	4.13	3.65	3.70	3.40	3.50	3.00	5.53	4.69	4.20	5.00	4.73	3.40	4.52	4.14
Entropy	3.50	2.93	3.12	3.60	3.47	3.51	4.30	4.40	4.37	**3.10**	4.47	4.01	3.63	3.82	3.75
L_2	4.40	**2.27**	2.98	2.50	2.53	**2.52**	1.90	1.80	1.83	3.50	**2.73**	2.99	**3.08**	2.33	**2.58**
L_1	**2.70**	2.53	**2.59**	3.10	**2.27**	2.55	2.80	2.20	2.40	3.70	4.00	3.90	**3.08**	2.75	2.86
Weight Clip	3.30	3.13	3.19	**2.20**	3.33	2.95	3.70	2.87	3.15	5.80	4.27	4.78	3.75	3.40	3.52
Dropout	4.40	6.07	5.51	N/A	N/A	N/A	6.10	5.33	5.59	4.20	4.27	4.25	4.90	5.22	5.12
BatchNorm	7.00	6.93	6.95	5.90	6.00	5.97	6.20	5.80	5.93	3.50	3.27	3.35	5.65	5.50	5.55

I.2   SCALED REWARDS

Min-max scaling is a linear-mapping operation to map values ranging from $[\min(x), \max(x)]$ to $[0, 1]$, using $x' = \frac{x - \min(x)}{\max(x) - \min(x)}$. For each environment and policy optimization algorithm (for example, PPO on Ant), we calculate a "scaled reward" for each regularization method and the baseline, using the maximum mean return obtained using any regularization method (including baseline) as $\max(x)$ and 0 as $\min(x)$, on positively clipped returns. We then average the scaled rewards of mean return over environments of a certain difficulty (easy/hard). We present the results under the default hyperparameter setting in Table 22-24 and the results under sampled hyperparameter settings in Table 25-27. To analyze whether regularization significantly improves over the baseline and whether conventional regularizers significantly improves over entropy, we perform Welch's t-test on the scaled rewards, using an identical approach to the one we used for z-score. Our observation is similar to the ones we made in Section 3 and Section 4.

Table 22: Scaled rewards for each regularization method under the default hyperparameter setting.

Reg \Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total
Entropy	**100.0**	**93.0**	**95.3**	86.2	84.3	85.0	**95.2**	57.2	69.9	94.9	89.0	91.0	**94.1**	80.9	85.3
L_2	74.8	90.2	85.1	**97.2**	87.2	90.6	88.0	93.2	91.5	**97.1**	92.4	93.9	89.3	**90.7**	**90.3**
L_1	58.8	70.6	66.7	91.9	**95.5**	**94.3**	90.0	**93.5**	92.3	95.0	89.7	91.5	83.6	87.3	86.2
Weight Clip	61.2	65.3	63.9	90.7	89.6	90.0	92.7	88.4	89.8	91.6	89.2	90.0	84.0	83.1	83.4
Dropout	0.85	9.05	6.32	N/A	N/A	N/A	76.2	42.5	53.7	97.0	**96.2**	**96.5**	58.0	49.3	52.2
BatchNorm	0.00	6.32	4.21	21.8	12.9	15.9	25.7	30.7	29.1	88.2	92.9	91.4	33.9	35.7	35.1
Baseline	64.1	48.9	54.0	91.8	77.9	82.5	89.3	47.9	61.7	90.5	86.4	87.8	83.9	65.3	71.5

Table 23: *P*-values from Welch's *t*-test comparing the scaled rewards of regularization and baseline, under the default hyperparmeter setting.

Reg \Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total
Entropy	0.01	0.00	0.00	0.64	0.33	0.66	0.67	0.34	0.36	0.23	0.54	0.25	0.07	0.00	0.00
L_2	0.38	0.00	0.00	0.50	0.16	0.14	0.92	0.00	0.00	0.11	0.07	0.02	0.27	0.00	0.00
L_1	0.62	0.01	0.06	0.99	0.00	0.03	0.95	0.00	0.00	0.26	0.26	0.12	0.99	0.00	0.00
Weight Clip	0.80	0.04	0.14	0.94	0.10	0.22	0.80	0.00	0.00	0.80	0.46	0.44	0.98	0.00	0.00
Dropout	0.00	0.00	0.00	N/A	N/A	N/A	0.29	0.56	0.34	0.12	0.00	0.00	0.00	0.00	0.00
BatchNorm	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.05	0.00	0.60	0.03	0.15	0.00	0.00	0.00

Table 24: *P*-values from Welch's *t*-test comparing the scaled rewards of entropy and other regularizers, under the default hyperparmeter setting.

Reg \Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total
L_2	0.07	0.58	0.07	0.25	0.70	0.29	0.49	0.00	0.00	0.70	0.30	0.28	0.42	0.00	0.07
L_1	0.00	0.00	0.00	0.63	0.07	0.09	0.66	0.00	0.00	0.74	0.73	0.86	0.05	0.05	0.77
Weight Clip	0.01	0.00	0.00	0.69	0.49	0.42	0.84	0.00	0.01	0.16	0.88	0.73	0.07	0.54	0.51
Dropout	0.00	0.00	0.00	N/A	N/A	N/A	0.09	0.14	0.05	0.72	0.02	0.03	0.00	0.00	0.00
BatchNorm	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.04	0.22	0.91	0.00	0.00	0.00

Table 25: Scaled rewards for each regularization method under the five sampled hyperparameter settings.

Reg \Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total
Baseline	86.8	60.8	71.2	87.9	88.3	88.1	93.7	66.6	77.4	92.8	86.8	89.2	90.3	75.6	81.5
Entropy	83.8	81.2	82.2	86.8	91.0	89.3	89.8	65.8	75.4	**97.5**	87.5	91.5	89.5	81.4	84.6
L_2	69.9	**92.8**	83.6	93.6	95.4	**94.7**	**96.4**	90.6	**92.9**	93.3	**95.5**	94.6	88.3	**93.6**	91.5
L_1	**89.1**	88.7	**88.8**	89.9	97.1	94.2	95.2	89.0	91.5	92.7	91.7	92.1	**91.7**	91.6	**91.7**
Weight Clip	85.5	81.3	83.0	96.4	96.6	96.5	91.3	84.1	87.0	86.7	91.6	89.6	90.0	88.4	89.0
Dropout	59.3	21.9	36.9	N/A	N/A	N/A	71.2	57.6	63.0	94.1	89.3	91.2	74.9	56.3	63.7
BatchNorm	0.00	14.9	8.96	41.7	47.9	45.4	70.6	53.0	60.0	96.1	92.6	94.0	52.1	52.1	52.1

Table 26: *P*-values from Welch's *t*-test comparing the scaled rewards of regularization and baseline, under five sampled hyperparameters.

Reg \Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total
Entropy	0.59	0.00	0.01	0.74	0.18	0.51	0.22	0.87	0.57	0.06	0.69	0.18	0.63	0.07	0.04
L_2	0.00	0.00	0.00	0.09	0.00	0.00	0.40	0.00	0.00	0.86	0.00	0.00	0.32	0.00	0.00
L_1	0.71	0.00	0.00	0.51	0.00	0.00	0.63	0.00	0.00	0.98	0.03	0.12	0.49	0.00	0.00
Weight Clip	0.80	0.00	0.00	0.01	0.00	0.00	0.47	0.00	0.00	0.08	0.05	0.83	0.86	0.00	0.00
Dropout	0.00	0.00	0.00	N/A	N/A	N/A	0.00	0.03	0.00	0.66	0.26	0.26	0.00	0.00	0.00
BatchNorm	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.19	0.02	0.01	0.00	0.00	0.00

Table 27: *P*-values from Welch's *t*-test comparing the scaled rewards of entropy and other regularizers, under five sampled hyperparameters.

Reg \Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total
L_2	0.01	0.00	0.69	0.07	0.01	0.00	0.03	0.00	0.00	0.07	0.00	0.05	0.57	0.00	0.00
L_1	0.37	0.05	0.04	0.36	0.00	0.00	0.08	0.00	0.00	0.10	0.06	0.72	0.24	0.00	0.00
Weight Clip	0.75	0.99	0.82	0.01	0.00	0.00	0.64	0.00	0.00	0.00	0.10	0.32	0.77	0.00	0.00
Dropout	0.00	0.00	0.00	N/A	N/A	N/A	0.00	0.07	0.00	0.17	0.47	0.87	0.00	0.00	0.00
BatchNorm	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.52	0.05	0.14	0.00	0.00	0.00

J   REGULARIZATION WITH A FIXED STRENGTH

In previous sections, we tune the strength of regularization for each algorithm and environment, as described in Appendix C. Now we restrict the regularization methods to a **single** strength for each algorithm, across different environments. The results are shown in Table 28 and 29. The selected strength are presented in Table 30. We see that the L_2 regularization is still generally the best performing one, but SAC is an exception, where BN is better. This can be explained by the fact that in SAC, the reward scaling coefficient is different for each environment, which potentially causes the optimal L_2 and L_1 strength to vary a lot across different environments, while BN does not have a strength parameter.

Table 28: Percentage (%) of environments that, when using a regularization, "improves". For each algorithm, one single strength for each regularization is applied to all environments.

Reg \ Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total
Entropy	**33.3**	**66.7**	**55.6**	0.0	33.3	22.2	0.0	16.7	11.1	0.0	16.7	11.1	8.3	33.3	25.0
L_2	0.0	50.0	33.3	0.0	**50.0**	**33.3**	**33.3**	**66.7**	**55.6**	33.3	33.3	33.3	16.7	**50.0**	**38.9**
L_1	0.0	33.3	22.2	0.0	**50.0**	**33.3**	**33.3**	50.0	44.4	33.3	33.3	33.3	16.7	41.7	33.3
Weight clipping	0.0	0.0	0.0	**33.3**	33.3	**33.3**	**33.3**	50.0	44.4	33.3	0.0	11.1	25.0	20.8	22.2
Dropout	0.0	0.0	0.0	N/A	N/A	N/A	**33.3**	50.0	44.4	**66.7**	16.7	33.3	**33.3**	22.2	25.9
BatchNorm	0.0	0.0	0.0	0.0	0.0	0.0	0.0	16.7	11.1	33.3	**50.0**	**44.4**	8.3	16.7	13.9

Table 29: The average z-score for different regularization methods. For each algorithm, one single strength for each regularization is applied to all environments.

Reg \ Alg	A2C			TRPO			PPO			SAC			TOTAL		
	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total	Easy	Hard	Total
Baseline	0.56	0.08	0.24	**0.38**	0.22	0.27	0.38	-0.39	-0.14	0.15	-0.14	-0.04	**0.37**	-0.06	0.08
Entropy	**1.07**	0.86	0.93	0.25	0.33	0.3	0.02	-0.25	-0.16	-0.03	-0.22	-0.16	0.33	0.18	0.23
L_2	0.82	**1.05**	**0.97**	0.33	0.44	0.40	**0.39**	**0.68**	**0.58**	-0.33	0.08	-0.06	0.30	**0.56**	**0.48**
L_1	0.39	-0.01	0.12	0.22	**0.63**	**0.49**	0.32	0.44	0.40	-0.14	-0.15	-0.15	0.20	0.23	0.22
Weight Clip	-0.87	0.14	-0.20	**0.38**	0.19	0.25	**0.39**	0.36	0.37	-0.19	-0.36	-0.30	-0.08	0.09	0.03
Dropout	-0.96	-1.01	-0.99	N/A	N/A	N/A	-0.05	-0.19	-0.15	**0.61**	0.33	**0.43**	-0.13	-0.29	-0.24
BatchNorm	-1.00	-1.11	-1.07	-1.54	-1.81	-1.72	-1.44	-0.64	-0.91	-0.08	**0.45**	0.27	-1.02	-0.78	-0.86

Table 30: The fixed single regularization strengths that are used in each algorithm to obtain results in Table 28 and Table 29.

Reg \ Alg	A2C	TRPO	PPO	SAC
Entropy	$5e-4$	$5e-4$	$5e-4$	1.0
L_2	$1e-4$	$5e-4$	$5e-4$	$5e-2$
L_1	$1e-4$	$1e-4$	$1e-4$	$5e-3$
Weight clipping	0.2	0.2	0.2	0.3
Dropout	0.05	0.05	0.05	0.2
BatchNorm	True	True	True	True

K   REGULARIZING WITH L_2 AND ENTROPY

We also investigate the effect of combining L_2 regularization with entropy regularization, given that both cases of applying one of them alone yield performance improvement. We take the optimal strength of L_2 regularization and entropy regularization together and compare with applying L_2 regularization or entropy regularization alone. From Figure 6, we find that the performance increases for PPO HumanoidStandup, approximately stays the same for TRPO Ant, and decreases for A2C HumanoidStandup. Thus, the regularization benefits are not always addable. This phenomenon is possibly caused by the fact that the algorithms already achieve good performance using only L_2 regularization or entropy regularization, and further performance improvement is restrained by the intrinsic capabilities of algorithms.

Figure 6: The effect of combining L_2 regularization with entropy regularization. For PPO HumanoidStandup, we use the third randomly sampled hyperparameter setting. For A2C HumanoidStandup and TRPO Ant, we use the baseline as in Section 3.

L L_2 REGULARIZATION VS. FIXED WEIGHT DECAY (ADAMW)

Figure 7: Comparison between L_2 regularization and weight decay. For PPO Humanoid and HumanoidStandup, we use the third randomly sampled hyperparameter setting.

For the Adam optimizer (Kingma & Ba, 2015), "fixed weight decay" (AdamW in Loshchilov & Hutter (2019)) differs from L_2 regularization in that the gradient of $\frac{1}{2}\lambda||\theta||^2$ is not computed with the gradient of the original loss, but the weight is "decayed" finally with the gradient update. For Adam these two procedures are very different (see Loshchilov & Hutter (2019) for more details). In this section, we compare the effect of adding L_2 regularization with that of using AdamW, with PPO on Humanoid and HumanoidStandup. The result is shown in Figure 7. Similar to L_2, we briefly tune the strength of weight decay in AdamW and the optimal one is used. We find that while both L_2 regularization and AdamW can significantly improve the performance over baseline, the performance of AdamW tends to be slightly lower than the performance of L_2 regularization.

M ADDITIONAL TRAINING CURVES (DEFAULT HYPERPARAMETERS)

Figure 8: Reward vs. timesteps, for four algorithms (columns) and five environments (rows).

As a complement with Figure 1 in Section 3, we plot the training curves of the other five environments in Figure 8.

N TRAINING CURVES FOR HYPERPARAMETER EXPERIMENTS

In this section, we plot the full training curves of the experiments in Section 4 with five sampled hyperparameter settings for each algorithm in Figure 9 to 12. The strength of each regularization is tuned according to the range in Appendix C.

O TRAINING CURVES FOR POLICY VS. VALUE EXPERIMENTS

We plot the training curves with our study in Section 5 on policy and value network regularizations in Figure 13-16.

Figure 9: Training curves of A2C regularizations under five randomly sampled hyperparameters.

Figure 10: Training curves of TRPO regularizations under five randomly sampled hyperparameters.

Figure 11: Training curves of PPO regularizations under five randomly sampled hyperparameters.

Figure 12: Training curves of SAC regularizations under five randomly sampled hyperparameters.

Figure 13: The interaction between policy and value network regularization for A2C. The optimal policy regularization and value regularization strengths are listed in the legends. Results of regularizing both policy and value networks are obtained by combining the optimal policy and value regularization strengths.

Figure 14: The interaction between policy and value network regularization for TRPO.

Figure 15: The interaction between policy and value network regularization for PPO.

Figure 16: The interaction between policy and value network regularization for SAC.

P ATARI EXPERIMENTS

We present results on 5 randomly sampled Atari environments (Asteroids, Pacman, Qbert, Roadrunner, Riverraid) in Table 31. Note that SAC not applicable here because it requires the environment to have continuous action space, while Atari environments have discrete action space. We find that L_2 regularization can still significantly improve over the baseline, while L_1 and weight clipping are slightly less effective. Interestingly, while BN still significantly harms performance on on-policy environments (A2C, TRPO, PPO), dropout can significantly outperform the baseline. We also observe that, different from continuous control tasks, entropy regularization can improve a lot on baseline, perhaps due to the action space being discrete.

Table 31: Average z-scores on Atari envs with p-values testing regularizers against baseline.

Reg \ Alg	A2C	TRPO	PPO	TOTAL	p-value
Baseline	0.10	0.07	0.03	0.07	N/A
Entropy	0.59	0.24	0.65	0.49	0.00
L_2	0.23	0.49	0.39	0.37	0.01
L_1	0.01	0.15	0.15	0.10	0.73
Weight Clip	0.14	-0.16	0.09	0.03	0.74
Dropout	0.43	N/A	0.55	0.49	0.00
BatchNorm	-1.51	-0.79	-1.86	-1.39	0.00