FEW-SHOT GRAPH LINK PREDICTION WITH DOMAIN ADAPTATION

ABSTRACT

Real world link prediction problem often deals with data coming from multiple imbalanced domains. Similar problems in computer vision are often referred to as Few-Shot Learning (FSL) problems. However, for graph link prediction, this problem has rarely been addressed and explored. In this work, we propose an adversarial training based modification to the current state-of-the-arts link prediction method to solve this problem. We introduce a domain discriminator on pairs of graph-level embedding. We then use the discriminator to improve the model in an adversarial way, such that the graph embeddings generated by the model are domain agnostic. We test our proposal on 3 benchmark datasets. Our results demonstrate that, when domain differences exist, our method creates better graph embeddings that are more evenly distributed across domains and generates better prediction outcomes.

1 INTRODUCTION

A very common problem in machine learning is that our data often comes from multiple domains and these domains are not balanced. Some domains may have abundant data while others may only have a few data instances. If a model is trained on data with imbalanced domains, the model may not perform well on the underrepresented domains because the limited amount of data would not be able to generate enough penalties. A typical example is the image classification problem for rare animal species. Research on how to improve model performance for those underrepresented domains gave rise to the field of few-shot learning (FSL). Originated in the computer vision (CV) domain, FSL (Fei-Fei et al. (2006); Fink (2005)) refers to the type of ML algorithms that work with very limited data. It was originally proposed to relieve the burden of having to collect large amount of labeled supervised data. Over the years, the definition has extended to improve model performances for rare domains where only "a few shot" of data is available (Wang et al. (2020)).

Research in the past decade has demonstrated the power of storing and modeling relational data in the form of graph (Wu et al. (2021); Kipf & Welling (2017)). The growing ubiquity of graphs, even for data that is not naturally connected, has spurred research in link prediction that aims to predict new connections based on existing ones. For example, in a purchase network, we can build a recommender system using link prediction (Ai et al. (2019)). If a link is predicted to exist between two nodes, these two items might be purchased together. Another example is the protein-protein interaction (PPI) network in the biological domain where every node is a protein. We could predict whether two proteins could react with each other in biological systems (Agrawal et al. (2017)).

The problem of few-shot learning with imbalanced domain exists for link prediction as well. For example, the purchase network may include both grocery items and luxury item. The subgraph involving grocery items is expected to be much bigger than the subgraph for luxury items. The purchase network may also include transactions from big cities and small towns. Depending on the data sources, it can even come from different countries or states. In the PPI network, the proteins may come from different types of tissues, or even different organisms. Despite the existence of this problem, most current researches on link prediction assume all nodes coming from the same domain and the distributions of data are often not in consideration. To the best of knowledge, the problem of few-shot link prediction with imbalanced domains has not been addressed in the literature.

In the CV domain, one possible route to solve the FSL problem with imbalanced domains is working through domain adaptation (DA) (Motiian et al. (2017)). Ultimately, both FSL and DA comes down

to the question of how to build better representations. In 2006, Ben-David showed that a good feature representation is the key to effective domain adaptation (Ben-David et al. (2007)). They proved that a good representation should minimize the differences between the source and target domains, and maximize the margin of the training set. Following the line of Ben-David's work, a family of methods have been proposed. These methods aim to use a strong learner to learn domain-invariant representations and use a weaker learner to achieve the downstream tasks. A representative work in CV is Deep Adaptation Networks (DAN) (Long & Wang (2015)), which consists of 5 convolutional layers followed by 3 fully connected layers. Another outstanding work in CV is the Domain-Adversarial Neural Network (DANN) (Ganin et al. (2016)), where they train a domain classifier acting as a discriminator. They use this discriminator to add penalty and force the encoder to generate domain-invariant representation vector.

Inspired by DANN, we propose to use adversarial networks to solve the few-shot link prediction problem with imbalanced domains in this paper. Specifically, we build domain-invariant graph level representations for the enclosing subgraphs and link prediction classifier on top of the graph embedding vector. We find that the use of the adversarial idea is even more meaningful for Graph Neural Networks (GNNs) because GNN layers do not have the general-to-specific features as Convolutional Neural Networks (CNNs) for vision tasks.

We summarize our main contributions as follows:

- We improve the current state-of-the-arts link prediction methods by adversarial training to build better domain-agnostic graph embeddings.
- We address the special issues of carrying out few-shot learning experiments with graph data, such as how to define shots for graphs, how to generate "shots" of data, and how to design experiments for imbalanced domains.
- We suggest using t-SNE plots as rule of thumb for practitioners to decide whether to incorporate the proposed method.
- We provide visual explanations of the source of improvements of the proposed method.

2 RELATED WORKS

2.1 LINK PREDICTION

Link prediction focuses on predicting future or missing links between a pair of nodes. The current state-of-the-arts link prediction method is SEAL (Zhang & Chen (2018)). The core idea of SEAL is to extract *enclosing subgraphs* for a set of sampled positive and negative links. To be more specific, a positive link is a pair of nodes that are connected with an edge and a negative link is a pair of nodes that are not connected. An enclosing subgraph is the union set of h-hop neighboring nodes of the pair of nodes. By doing this data-preprocessing step, SEAL transforms the link prediction problem to a (sub)graph classification problem. It uses graph neural networks (GNNs) to generate the graph embedding, which feeds into a classifier and generate new predictions. Other than SEAL, Graph Auto-Encoder (GAE, Kipf & Welling (2016)) is an alternative approach. GAE works by generating node embedding for all nodes and then model the link likelihood based on the concatenated node embedding vectors for any node pairs. However, recent researches have shown this method heavily relies on the assumption that similar nodes need to have similar connections. In addition to these GNN-based methods, traditional heuristic methods, such as common neighbor (CN), Adamic-Adar (AA) and Personalized PageRank (Zhang & Chen (2018); Brin & Page (2012)), provide a completely different alternative. Given a pair of nodes, these non-parametric methods describe the topological structure of the surrounding neighborhood with a score. The advantage is that these methods could be used directly without training but the trade-off is that it's difficult to utilize node/edge features with these methods.

2.2 FEW-SHOT LEARNING AND DOMAIN ADAPTATION

Few-shot learning is a special type of machine learning problem, which aims at obtaining good learning performances when supervised evidence information is limited (Wang et al. (2020)). Common FSL methods include data augmentation (cropping, rotating, generative models, etc) and meta

Figure 1: **Few-shot Link Prediction with Domain Adaptation.** Here we use colors to denote different domains. The positive/negative outcome is denoted by texture. Solid boxes are positive links and slash-textured boxes are negative links. Similar with SEAL, we start by extracting enclosing subgraphs around positive/negative links in graphs. A pair of enclosing subgraphs are sent to model g, which is composed with a Graph Neural Network and a graph pooling layer, to generate a pair of graph embeddings. A Discriminator (D) is set up on the side to determine whether this pair of graph embeddings come from the same domain. The pair of graph embeddings also enter in model c to classify link existence.

learning (Sun et al. (2019)). Domain Adaptation is a type of Transfer Learning (TL) technique. It focuses on transferring learned knowledge from one domain to another, while still maintain good performances. The core idea of domain adaptation is to learn a domain invariant representation, which are usually done by maximizing mutual information (Hjelm et al. (2019)) or training in an adversarial network (Goodfellow et al. (2014)).

Some recent works focus on the problem of few-shot learning with domain adaptation. The work from Motiian et al. (2017) also uses adversarial networks as the solution but it introduced a 4-class confusion matrix classifier as the discriminator. The work from Zhao et al. (2020) explicitly added source/target per-class separation before doing embedding feature learning with domain adaptation.

3 METHODOLOGY

In this section, we first formulate the few-shot link prediction problem with imbalanced domains. Then, we present the method we use to predict links in existing domains.

3.1 PROBLEM DEFINITION

We define the few-shot link prediction problem with imbalanced domains as follows: in a given graph space $\mathbb{S}$, we have access to graphs from m ($m \in \mathbb{N}, m \geq 2$) number of domains. Different domains may have variations in their marginal distributions. Among the m domains, $m-1$ ($k \in \mathbb{N}^+$) domains have k number of small graphs, which we define as graph "shots". The last domain only has 1 shot. Our objective is to learn a link prediction model that leverages the domain differences to improve the performance in the domain with 1 shot of data.

3.2 NOTATIONS

In terms of graph-related notations, each graph is denoted by $G = (V, E, d)$, where V is the set of vertices, E is the set of edges and d is the type of domain, which could be a one-hot encoded vector with one extra digit representing any unseen domain. In the adjacency matrix A of G, $A_{u,v} = 1$ if edge $(u, v) \in E$, and otherwise $A_{u,v} = 0$. For any node u, we use $\mathcal{N}(u)$ to denote the set of neighboring nodes of u. In addition, we use superscript as a short hand to denote the domain class. For example, for a graph from domain i, we would denote it as G^i.

3.3 DOMAINS

To be more precise, here we refer domain as a graph-level class attribute in a data set, which can be used to split the graphs into meaningful and distinguishable groups. If the domain class attribute in a dataset is on nodes, here we split the graph into domain-specific sub-graphs and focus on intra-domain link prediction.

3.4 LINK PREDICTION

Here is the general form of any link prediction models: given (u, v, G), where u and v are a pair of nodes in graph G, the likelihood of having a link between u and v, $y_{u,v}$, is modeled by function $f : (u, v, G) \to y_{u,v}$. This function could be trained with a union set of positive and negative samples. Positive samples are sampled from existing edges while negative samples are built with node pairs with u and v', $v' \notin \mathcal{N}(u)$.

Based on the ideas from the SEAL framework, the first step is to extract an h-hop enclosing subgraph around edge (u, v). We denote this subgraph as $S_{u,v}$ and the process of generating the enclosing subgraph as $s(u, v, G) = S_{u,v}$. Function f could be rewritten as $f : S_{u,v} \to y_{u,v}$.

In general, f is composed with two separated functions g and c and could be written as $f = g \circ c$. Function g generates the graph embedding vector $g : S_{u,v} \to h_{S_{u,v}}$. Function c takes in the graph embedding and generates the prediction $\hat{y_{u,v}}$.

Here we have the supervised loss function.

$$\mathcal{L}_{cls}(g, c) = \mathbb{E}[\ell(c(g(S_{u,v})), y_{u,v})] \tag{1}$$

$$= -\frac{1}{N} \sum y_{u,v} \cdot \log(c(g(S_{u,v}))) + (1 - y_{u,v}) \cdot \log(1 - c(g(S_{u,v}))) \tag{2}$$

, where $\mathbb{E}$ is the statistical expectation of any loss function ℓ. In this case, ℓ is the standard binary cross-entropy loss.

The input of the discriminator D is a pair of graph embedding h^i and h^j generated by g. As stated above, here we use superscript to denote the domain information. The objective is to determine whether these two subgraphs are from the same domain. Since we know from which graph G these subgraphs are generated and we know the domain information of each G, we can easily get the ground truth $d^{i,j}$. The loss function here could be binary cross-entropy as well. An alternative design is to let the discriminator predict the exact domain that the graph embedding is from. We select the current one because it is easier to apply it on novel domains.

$$\mathcal{L}_{dis}(D) = \mathbb{E}[\ell(D(g(S^i_{u,v}), g(S^j_{u',v'})), d^{i,j})] \tag{3}$$

Given the two loss functions above, we could get the total loss for the input of a pair of subgraphs from domain i and j. Since our objective is to make sure the graph embedding does not contain domain specific information, we would like to minimize the supervised training loss while maximizing the loss of the discriminator.

$$\mathcal{L}_{total}(g, c) = \mathbb{E}[\sum_{i=1}^{m} \ell(c(g(S^i_{u,v})), y^i_{u,v}) - \alpha \cdot \sum_{i=1}^{m} \sum_{j=1}^{m} \ell(D(g(S^i_{u,v}), g(S^j_{u',v'})), d^{i,j})] \tag{4}$$

, where α is hyperparameter to adjust the weight of the discrimination term compared to the supervised loss.

4 EXPERIMENTS

4.1 DATASETS

In this study, we compared the model performances using three different datasets, including ogbn-products, ogbg-ppa and the protein-protein interaction (PPI) dataset.

Both the ogbn-products and ogbg-ppa dataset comes from the Stanford Open Graph Benchmark (Hu et al. (2020)). There is a specific category of benchmark dataset on OGB for link prediction. However, they could not be used in this study because those link-prediction benchmark dataset do not contain domain information. Therefore, we select ogbn-products and ogbg-ppa from the node/graph property prediction task and convert them into link prediction tasks. The protein-protein interaction (PPI) dataset comes from the GNN benchmark dataset (Dwivedi et al. (2020)) and originally published together with the GraphSage paper(Hamilton et al. (2018)). Its original purpose is also node property prediction and we re-purpose it as a link-prediction problem.

ogbn-products The ogbn-products dataset is a single graph with 2,449,029 nodes and 61,859,140 edges, representing the Amazon product co-purchasing network in 47 categories. Node feature is a 100-dimension word embedding vector extracted from product description. During the data preprocessing, we select 23 domains with more than 10,000 nodes and split the nodes into 23 subgraphs, each of which represents a single domain. Then, within each domain, we randomly selected 40% of the nodes as the test data and use the remaining 60% to generate training "shots". To ensure the robustness of our results, we run the random sampling 10 times to generate 10 sets of independent experiment data. In each experiment, within each domain, we start with a random node, run Breadth-first search (BFS) until the cumulated amount of nodes exceed 5% of all the nodes in the training graph (in other words, 3% in the original domain subgraph). All the nodes visited by BFS are considered as a "shot". Then we start from another random node from the rest of the graph, repeat the BFS process until a total of 10 shots are generated for each domain. To build the few-shot learning with imbalanced domain setting, for 22 out of 23 domains, we arrange all 10 shots to the training set and for the last domain, we arrange 1 shot to the training set. The training set is then randomized and feed into the model. The evaluation is done for the imbalanced domain only.

ogbg-ppa The ogbg-ppa dataset include 158,100 graphs representing the protein-protein association network in 1581 different species that cover 37 broad taxonomic groups. The average number of nodes is 243.4 and the average number of edges is 2,266.1. Edges in this dataset are associated with a 7-dimensional feature vector and there is no node feature for this data. We chose to pick broad taxonomic groups as our criteria to separate domains. All the domains have enough data so all 37 domains are counted. Because the input is no longer a single graph, no graph splitting is necessary. We select 50 graphs from each domain as our test set. For our training set, we selected 10 graphs from each domain to build the data for one experiment and we created 10 independent experiments to keep our result robust. Similar with what we do for ogbn-products, to build the few-shot learning with imbalanced domain setting, we put 1-shot of data for the evaluation domain into the training set and 10-shot for all the other domains. Note that the graphs in ogbg-ppa do not have node feature data. Instead, only edge feature data is available.

PPI The PPI dataset is another protein-related dataset. It includes 24 graphs representing the human protein-protein interaction network in 24 types of human tissues. The average number of nodes is 2372.7 and the average number of edges is 68508.7. Each node has 50 features. We follow the same procedure as we use for the ogbn-products dataset to split test and train, generate shots and produce experiment data.

4.2 BASELINE METHODS

We compared the performances of our proposed methods with several commonly used link-prediction methods, including SEAL, Graph AutoEncoder (GAE) and heuristic methods including Common Neighbor (CN), Adamic-Adar (AA) and Personalized PageRank (PPR).

SEAL SEAL is the current state-of-the-arts method for link prediction and provides a lot of inspirations to this work. The core idea is to create enclosing subgraphs around a selections of positive and negative node pairs. The distance between the target pair of nodes and all the other nodes are calculated within each subgraph. Then, SEAL uses a GNN to compute graph-level embedding for

each subgraph and use the graph embedding to predict the probability of having a link between each node pair.

GAE GAE employs a standard GCN to generate updated node embedding. For each positive and negative node pair, the node embedding vectors for the pair of nodes are concatenated and then used to predict the probability of having a link.

CN As a heuristic method, there is no training process needed for CN. The common neighbor method computes the total number of common neighbors between any node pairs and uses the score to predict the probability of having a link. The mathematical formula for CN is usually denoted by

$$CN = |\mathcal{N}(x) \bigcap \mathcal{N}(y)|$$

AA Adamic-Adar is another heuristic method. Unlike CN, instead of looking into the first-order neighbor of a node pair, AA pays attention to the second-order neighbor of the node pair. Its mathematical formula could be denoted by

$$AA = \sum_{z \in \mathcal{N}(x) \bigcap \mathcal{N}(y)} \frac{1}{\log(|\mathcal{N}(z)|)}$$

PPR Personalize PageRank computes the stationary distribution of a random walker starting at x and ending at y with restarts. Here since we are focusing on bidirectional graphs, we need to compute the scores for both from x to y and from y to x. The mathematical formula is denoted by the following equation, where q stands for the stationary distribution.

$$PPR = q_{xy} + q_{yx}$$

4.3 EXPERIMENT CONFIGURATION

All the heuristic methods (CN, AA & PPR) can be used directly without training. To ensure the evaluation is fair, we tested all six methods on the same set of node pairs for evaluation.

All three NN-based methods (our method, SEAL & GAE) requires training on a selection of positive and negative node pairs. To ensure a fair comparison, we trained all these three methods on the same sets of node pairs. As mentioned before, we generated 10 sets of experiment data for training. The final results for these NN-based methods are average performances in all 10 experiments. In addition, it is impossible to include all node pairs in the training process. Therefore, we sample a proportion of positive node pairs and then sample the same amount of negative node pairs for each dataset. The exact proportions for each dataset is consistent across all three NN-based methods and is in-fact determined based on the number of edges and the size of features. After all, we want to keep a balance between the speed of carrying out each experiment and the amount of data the model can see.

In all three GNN-based methods, we use a three layers GCN with 32 neurons on each layers. Classic GCN models only takes node features and it is what we use for ogbn-products and PPI. However, as mentioned earlier, the ogbg-ppa dataset only has edge features. To utilizing edge features, we modified the message passing rule such that the message include the concatenated node feature, which in this case is the calculated distance value between each node and the target node pair, and edge features. In our method and SEAL, where a graph level pooling is needed, we use the pooling method proposed in DGCNN (Zhang et al. (2018)), which composes of a sort pooling layer followed by a two-layer convolution network. In this experiment, we use the sort pooling layer to pull out the sorted features from the top 10 nodes (sorted by the largest value of each node).

For our method and SEAL, the prediction of link probability starts with a 32-length long graph embedding vector. After the pooling layer, we send the graph embedding to a dense layer with 32 neurons and another dense layer to generate the output. For GAE, the prediction of link probability requires the node level features of the two target nodes. In our implementation, after the GNN step, we simply look up the node embedding vectors for the two target nodes and concatenate the two

Figure 2: **Comparison of average test ROC-AUC performances in each dataset.** The colored dots represent the mean performance of 10 experiments and the error bars represent the standard deviation.

vectors. The merged embedding is then send to the same MLP as described earlier to generate the prediction.

In our methods, we use a three layer MLP with 32 neurons as the discriminator for the graph embedding. The input of the discriminator is the concatenation of two random graph embedding and the target of the discriminator is to predict whether these two embedding come from the same domain. In the actual implementation, because we train the model using a mini-batch of 32, this could be easily done by separating one batch of 32 embedding vectors to two groups of 16 vectors and comparing between these two groups.

In addition, we implement a 20 iteration warm-up stage for both our method and SEAL. In the warm-up stage, the models are trained without discriminator. The purpose of setting up the warm-up stage is to make it easier to train the adversarial model. As reported in literature, adversarial models are harder to train. If we train the model and the discriminator together from the very beginning, a bad initialization on the model may make it too difficult for the model to confuse the discriminator, which will lead to the "model collapsing". A 20 step warm-up stage may not always bring the model to the best spot but it offers a good starting point in most cases.

All the models are trained with a learning rate at 0.0001 with L2 regularization at 0.001 for 250 epochs. The discriminators are trained with a learning rate at 0.00001. All the experiments are trained and tested on a NVIDIA V100 card on the Visa MLP platform.

4.4 Experiment Results

In our proposed method, α is an important hyperparameter because it controls the impact of the discriminator on the model. In this experiment, we select α from 1, 3 and 5 and we compare the results with all of our baseline methods. The results are displayed in Table 1 and Figure 2.

First, we observe that compared with the vanilla SEAL method, in most cases, the proposed adversarial methods yield better performances over underrepresented domains. The average improvement is around 1.5% but the levels of improvement vary across different datasets. In the ogbn-products and PPI dataset, we observe much better performance from the adversarial models but in the ogbg-ppa dataset, the improvement is not very significant. We think the reason is that the feature distributions in the ogbg-ppa dataset are highly similar across domains. In this case, the impact of the lack of training data for one specific domain is very small. Therefore, the discriminator here cannot generate any benefits. We will discuss the details of our reasoning later.

The GAE method did not do well under this experiment. Unlike SEAL, GAE lacks the key node feature to describe the distance between each node to the target link. Under this few-shot learning setting, the limited number of nodes for training further restricts GAE's ability to efficiently train the model.

The performances of the heuristic methods are low as well. One possible explanation is that link prediction task in these three experiment dataset heavily depends on node/edge features. Since all three heuristic methods only use graph topological structure data, they lack enough information to make good predictions.

Table 1: Comparison of Test ROC-AUC Scores with Baseline Methods

	Adversarial Methods			SEAL	GAE	CN	AA	PPR
	$\alpha = 1$	$\alpha = 3$	$\alpha = 5$					
ogbn-products								
Domain 1	88.8±3.8	89.7±3.6	**90.9±3.5**	88.4±4.0	52.0±4.0	45.4	45.9	44.6
Domain 2	89.8±4.4	89.9±2.5	**90.0±3.0**	87.7±3.9	58.4±4.0	33.4	30.1	43.6
ogbg-ppa								
Domain 1	**89.4±6.1**	87.8±6.6	86.2±10.8	88.5±5.9	52.7±6.8	39.2	39.1	38.2
Domain 2	**90.6±6.4**	**90.6±4.9**	87.2±3.4	**90.6±5.5**	65.1±5.4	53.7	52.2	57.3
PPI								
Domain 1	**79.1±4.2**	78.9±3.3	79.0±2.7	77.1±2.7	55.0±3.2	57.0	63.0	43.5
Domain 2	82.9±2.4	**83.0±3.9**	81.1±3.8	81.6±3.4	50.5±3.1	53.5	57.5	67.0

[1] Results from trainable NN models are averages (± standard deviation) of 10 experiments.

[2] Results from heuristic methods are direct output on the same test set.

Figure 3: **Comparison of t-SNE visualization of graph embedding for all 24 domains in the PPI dataset.** The distribution of graph embeddings generated by baseline SEAL vary across domains while the graph embeddings generated by the adversarial method are domain-invariant.

Impact of Adversarial Training on Graph Embedding

To understand the real impact of the adversarial training on graph embedding, we use t-SNE (van der Maaten & Hinton (2008)) to reduce the dimension of graph embedding and visualize them in 2-D space. Figure 3 shows the changes of graph embedding for all 24 domains in PPI. From the figure we can see the dots generated by the adversarial method are more evenly distributed across the 2-D space and this observation further confirms that our proposed method is working as expected. .

In addition, by inspecting the t-SNE plot (Figure 4) for the ogbg-ppa dataset, we find that with the baseline SEAL method, the distribution of embedding points among different domains in ogbg-ppa are already evenly distributed. It shows that there is little inter-domain differences in this dataset. Although the protein graphs come from different organisms, it could be the case that all the graphs are assembled in a similar way so they are topologically similar. It could also be possible that the 7-dimension edge feature extracted for this dataset are not reflecting domain differences.

In fact, comparing Figure 3 and Figure 4 shows that the t-SNE visualization of the graph embedding vector is a good tool for machine learning practitioners to decide when to adopt the proposed approach. If there are distinguishable domain differences across domain based on the t-SNE plot, the proposed method will likely yield some improvements.

Training Curves, Run time and Impact of α

Figure 4: Domains in the ogbg-ppa dataset are already similar with baseline SEAL

We also look into the impact of the adversarial design on the training curves. Figure 5 shows the smoothed training curves of 10 experiments with the ogbn-products dataset on domain 2. The shaded area represent the standard error. Note that we excluded the performances during the 20-step warm-up stage to zoom on the most important area. As presented in Figure 5, the baseline performance quickly drops after 50 iterations even with the use of L2 regularization. This is mostly due to the fact that the evaluation domain is underrepresented in training data (recall that in the training data, we have 1 shot of data in the evaluation domain and 10 shot of data for every other domain). By enforcing the graph embedding from different domains to be similar using adversarial training, the graph embedding generated by our method is more likely to work well with the evaluation domain. Therefore we see the performances from all three adversarial experiments reach better best performances comparing with the baseline SEAL method.

Smoothed Testing ROC-AUC Score over training

Figure 5: Comparison of Smoothed Training Curves over 10 Experiments

In addition, by increasing the value of α, we increase the impact of the discriminator of the target model. In this case, $\alpha = 3$ seems to provide the best performance. However, if we look at the average best performances, the best α is in fact 5. A closer look into each individual training curve tells us that some of the best models were trained when $\alpha = 5$. However, the large α value also makes the model less stable and it's more likely to see the model collapse during the training process. Therefore, we conclude that when domain differences exist, higher impact of the discriminator helps the model reach better performances but it makes it more difficult to train. Eventually, there is a sweet spot to keep the balance between performance and model stability.

Figure 5 also tells us that comparing with the baseline SEAL method, our method takes more steps to converge. Increasing the value of α increases the steps to converge as well. At the same time, it also takes more time to train the adversarial model because the computation of graph embedding

needs to happen two times to collect gradients to train the target model and the discriminator. On average, it takes 1.134s to finish one training step for the ogbn-products dataset using baseline SEAL on a NVIDIA V100 graphic card but it takes 1.406s (24.0 % increase) to train the network using adversarial method.

5 CONCLUSION

In this work, we propose an adversarial training based approach to solve the few-shot graph link prediction problem. Compared with the state-of-arts method and other baselines, our method achieves better performance on underrepresented domains, especially when domain variance is not trivial. We further examine the changes of the graph embeddings using t-SNE and reveal the root of this improvement. At the same time, by showing the t-SNE visualizations for cases when the proposed method doesn't provide benefits, we show that t-SNE is a very efficient tool for practitioners to decide when to adopt our method.

REFERENCES

Monica Agrawal, Marinka Zitnik, and Jure Leskovec. Large-scale analysis of disease pathways in the human interactome, 2017.

Jun Ai, Yayun Liu, Zhan Su, Hui Zhang, and Fengyu Zhao. Link prediction in recommender systems based on multi-factor network modeling and community detection. *EPL (Europhysics Letters)*, 126(3):38003, jun 2019. doi: 10.1209/0295-5075/126/38003. URL https://doi.org/10.1209/0295-5075/126/38003.

Shai Ben-David, John Blitzer, Koby Crammer, and Fernando Pereira. Analysis of representations for domain adaptation. In B. Schölkopf, J. Platt, and T. Hoffman (eds.), *Advances in Neural Information Processing Systems*, volume 19. MIT Press, 2007. URL https://proceedings.neurips.cc/paper/2006/file/b1b0432ceafb0ce714426e9114852ac7-Paper.pdf.

Sergey Brin and Lawrence Page. Reprint of: The anatomy of a large-scale hypertextual web search engine. *Computer Networks*, 56(18):3825–3833, 2012. ISSN 1389-1286. doi: https://doi.org/10.1016/j.comnet.2012.10.007. URL https://www.sciencedirect.com/science/article/pii/S1389128612003611. The WEB we live in.

Vijay Prakash Dwivedi, Chaitanya K Joshi, Thomas Laurent, Yoshua Bengio, and Xavier Bresson. Benchmarking graph neural networks. *arXiv preprint arXiv:2003.00982*, 2020.

Li Fei-Fei, R. Fergus, and P. Perona. One-shot learning of object categories. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 28(4):594–611, 2006. doi: 10.1109/TPAMI.2006.79.

Michael Fink. Object classification from a single example utilizing class relevance metrics. In L. Saul, Y. Weiss, and L. Bottou (eds.), *Advances in Neural Information Processing Systems*, volume 17. MIT Press, 2005. URL https://proceedings.neurips.cc/paper/2004/file/ef1e491a766ce3127556063d49bc2f98-Paper.pdf.

Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor Lempitsky. Domain-adversarial training of neural networks, 2016.

Ian J. Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial networks, 2014.

William L. Hamilton, Rex Ying, and Jure Leskovec. Inductive representation learning on large graphs, 2018.

R Devon Hjelm, Alex Fedorov, Samuel Lavoie-Marchildon, Karan Grewal, Phil Bachman, Adam Trischler, and Yoshua Bengio. Learning deep representations by mutual information estimation and maximization, 2019.

Weihua Hu, Matthias Fey, Marinka Zitnik, Yuxiao Dong, Hongyu Ren, Bowen Liu, Michele Catasta, and Jure Leskovec. Open graph benchmark: Datasets for machine learning on graphs. *arXiv preprint arXiv:2005.00687*, 2020.

Thomas N. Kipf and Max Welling. Variational graph auto-encoders, 2016.

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks, 2017.

Mingsheng Long and Jianmin Wang. Learning transferable features with deep adaptation networks. *CoRR*, abs/1502.02791, 2015. URL http://arxiv.org/abs/1502.02791.

Saeid Motiian, Quinn Jones, Seyed Mehdi Iranmanesh, and Gianfranco Doretto. Few-shot adversarial domain adaptation, 2017.

Qianru Sun, Yaoyao Liu, Tat-Seng Chua, and Bernt Schiele. Meta-transfer learning for few-shot learning, 2019.

Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of Machine Learning Research*, 9(86):2579–2605, 2008. URL http://jmlr.org/papers/v9/vandermaaten08a.html.

Yaqing Wang, Quanming Yao, James Kwok, and Lionel M. Ni. Generalizing from a few examples: A survey on few-shot learning, 2020.

Zonghan Wu, Shirui Pan, Fengwen Chen, Guodong Long, Chengqi Zhang, and Philip S. Yu. A comprehensive survey on graph neural networks. *IEEE Transactions on Neural Networks and Learning Systems*, 32(1):4–24, Jan 2021. ISSN 2162-2388. doi: 10.1109/tnnls.2020.2978386. URL http://dx.doi.org/10.1109/TNNLS.2020.2978386.

Muhan Zhang and Yixin Chen. Link prediction based on graph neural networks, 2018.

Muhan Zhang, Zhicheng Cui, Marion Neumann, and Yixin Chen. An end-to-end deep learning architecture for graph classification. In *AAAI*, 2018.

An Zhao, Mingyu Ding, Zhiwu Lu, Tao Xiang, Yulei Niu, Jiechao Guan, Ji-Rong Wen, and Ping Luo. Domain-adaptive few-shot learning, 2020.