AN EXPERIMENT DESIGN PARADIGM USING JOINT FEATURE SELECTION AND TASK OPTIMIZATION

ABSTRACT

This paper presents a subsampling-task paradigm for data-driven task-specific experiment design (ED) and a novel method in populationwide supervised feature selection (FS). Optimal ED, the choice of sampling points under constraints of limited acquisition-time, arises in a wide variety of scientific and engineering contexts. However the continuous optimization used in classical approaches depend on a-priori parameter choices and challenging non-convex optimization landscapes. This paper proposes to replace this strategy with a subsampling-task paradigm, analogous to populationwide supervised FS. In particular, we introduce JOFSTO, which performs JOint Feature Selection and Task Optimization. JOFSTO jointly optimizes two coupled networks: one for feature scoring, which provides the ED, the other for execution of a downstream task or process. Unlike most FS problems, e.g. selecting protein expressions for classification, ED problems typically select from highly correlated globally informative candidates rather than seeking a small number of highly informative features among many uninformative features. JOFSTO's construction efficiently identifies potentially correlated, but effective subsets and returns a trained task network. We demonstrate the approach using parameter estimation and mapping problems in quantitative MRI, where economical ED is crucial for clinical application. Results from simulations and empirical data show the subsampling-task paradigm strongly outperforms classical ED, and within our paradigm, JOFSTO outperforms state-of-the-art supervised FS techniques. JOFSTO extends immediately to wider image-based ED problems and other scenarios where the design must be specified globally across large numbers of acquisitions. Our code is available for reviewers Code (2022).

1 INTRODUCTION

Experiment design (ED) seeks an optimally informative sampling scheme within a budget of measurement time Antony (2003). The problem arises across a wide range of scientific disciplines and applications wherever mathematical models are fitted to real-world noisy measurements to estimate quantities that cannot be measured directly e.g. agriculture Gupta et al. (2015), civil engineering Lye (2002), economics Jacquemet & L'Haridon (2019), microbiology E.Vanot & Sergent (2005). In Magnetic Resonance Imaging (MRI), ED is choosing the acquisition parameters within limited scanning time, to then estimate and map clinically informative MRI model parameters. Classical approaches Frieden (2004); Montgomery (2001) optimize the design to minimize the uncertainty of parameter values of a prespecified model, often derived from the Fisher information matrix. For any non-linear model, these approaches require a-priori specification of model parameter values to optimize the design for, which leads to circularity, as parameter values are by definition unknown at application stage. Moreover the optimization itself is usually cumbersome over a high-dimensional and highly non-convex space.

This paper considers a new paradigm for ED, which we cast as a populationwide feature selection (FS) problem, instead of one of continuous optimization. The paradigm requires training data densely sampled over the space of possible measurements from a representative population of test cases. It identifies i) a subset of locations in the measurement space that allows high performance of a downstream task, and ii) a trained network to support this task. The problem differs from most FS problems, which typically aim to 'identify a small, highly discriminative subset' Kuncheva et al. (2020), insofar as the set of measurements are all informative, unlike for example protein-coding

genes 10x Genomics (2022) or noisy two-moons data Scikit-Learn (2022). Typically in ED each measurement individually offers similar amounts of information overall to support task performance, but informs different aspects of the task; ED seeks a combination that covers all important aspects. Accordingly, again unlike most FS problems, measurements are highly correlated (see figure 3).

Thus we propose JOFSTO: an approach for joint FS and task optimization, applied to task-driven ED. JOFSTO simultaneously trains two neural networks end-to-end; the first scores and ranks the features by relevance to optimize subsampling and the second uses a subset of measurements to perform a prespecified task, such as estimating ED model parameters. JOFSTO's subsampling coupled with downstream-supported task training outputs both an optimized ED and a network trained for optimal task performance given that design. A simple scoring mechanism enables JOFSTO to identify effective subsets of potentially highly correlated features efficiently, and joint training during subsampling maintains high task performance. Furthermore we put JOFSTO's novel approach to scoring and feature subsampling in a recursive feature elimination (RFE) framework, to reduce the full set of samples to a small subsample stepwise, which aids convergence to strong solutions.

We demonstrate the benefits of JOFSTO within applications in quantitative MRI, where the standard aim is "parameter mapping", which fits a model to multichannel measurements in each image voxel to obtain maps of biologically informative parameters Alexander et al. (2019). However, acquisition time is limited by factors of cost and the ability of subjects (often sick patients) to remain motionless in the noisy and claustrophobic environment of the MR scanner, thus optimal ED can be crucial to support the most accurate image-driven diagnosis, prognosis, or treatment choices. Furthermore, lengthy MRI acquisitions enabling our new ED paradigm can be made easily on a few subjects, but are not feasible in routine patient imaging. Experiments, using both simulations and real-world data, show that JOFSTO outperforms classical ED in clinically-relevant tasks. In particular, we demonstrate improved performance in biological parameter mapping and state-of-the-art results in a subsampling-reconstruction MRI challenge. Moreover, within the subsampling paradigm, results show that JOFSTO outperforms state-of-the-art feature-selection algorithms in each task.

2 RELATED WORK

Experiment Design (ED) The design of an experiment is a set $A = \{\mathbf{a}^1, ..., \mathbf{a}^C\}$ where each $\mathbf{a}^i \in A$ is a combination of acquisition-parameter settings, i.e. choices of independent variables under the control of the experimenter. Each data acquisition under ED A provides a set of measurements $\mathbf{x} = (x^1, ..., x^C)$, corresponding to the elements of A; $\mathbf{x}$ is a *sample* under design A. ED optimization seeks the A that maximally supports a task, such as estimating parameters $\boldsymbol{\theta}$ of model $f(\mathbf{x}; \boldsymbol{\theta})$, that relates measurements, $\mathbf{x}$, of a system to underlying properties of interest encapsulated in $\boldsymbol{\theta}$. Classical ED approaches typically aim to minimize the expected variance of model parameters e.g. encoded in the Fisher information matrix Pukelsheim (2006), using Bayesian techniques Chaloner & Verdinelli (1995); Kaddour et al. (2020) or indirectly via an operating characteristic curve Montgomery (2001). However, for non-linear models, parameter uncertainty depends strongly on parameter value, so the design-optimization requires pre-specification of parameter values of interest, leading to circularity. Moreover, the optimization often becomes cumbersome particularly as model complexity increases and C becomes large Alexander (2008). Our subsampling-task paradigm for ED avoids this circularity and replaces the challenging continous optimization problem with neural network training.

Quantitative Magnetic Resonance Imaging (qMRI) qMRI acquires multi-channel images where channels have distinct acquisition parameters, each providing particular sensitivity to tissue composition or function. Each combination of acquisition parameters, or element $\mathbf{a}$ of the ED A, produces a 3D grayscale image. Thus a full qMRI scan with ED $A = \{\mathbf{a}^1, ..., \mathbf{a}^C\}$ produces a 3D image with C channels; each image voxel is a separate sample, but the design is common to all samples/voxels. Mathematical models relate MRI data - a series of measurements with varying acquisition parameters - to underlying tissue properties Cercignani et al. (2018). By fitting a model to the set of measurements (channels) in each image voxel, we obtain "parameter maps" (images where each voxel quantifies a physical, chemical, or physiological property) over a region or organ of interest; see e.g. Alexander et al. (2019) for examples in the brain.

ED in qMRI In practice, clinicians often use heuristics to choose the ED A that best supports acquisition parameter estimates in limited acquisition time, although more systematic studies often use Fisher matrix optimization, see e.g. Alexander (2008); Zhang et al. (2012); Panagiotaki et al.

(2015b). However, such approaches typically optimize the design for just one or several representative model parameter combinations, even though those combinations vary substantially from voxel to voxel. Thus, the design can be far from optimal in large portions of the image. Recent work e.g. Pizzolato et al. (2020); Blumberg et al. (2022) raise the possibility of a subsampling approach to ED, but consider it only abstractly within the task of recovering the full dense sample of measurements from a subsample, whilst Grussu et al. (2021) does not densely-sample the measurement and spatial domains, instead arguing that this leads to a model-free ED. Here we uniquely couple the subsampling with specific downstream tasks to optimize jointly the execution of a parameter mapping or other downstream task with identification of the design that optimally supports it.

Supervised Feature Selection (FS) FS is the well-studied problem of identifying an informative subset of features Guyon et al. (2004); Liu & Motoda (1998), either at the instance level e.g. identifying different salient parts of different images; or at the population/global level selecting across all the instances. Populationwide supervised FS is of primary relevance here, since each combination of acquisition parameters, i.e. elements of A, is global to many samples (image voxels). State-of-the-art approaches Wojtas & Chen (2020); Lee et al. (2022) outperform classical approaches e.g. (original) RFE Guyon et al. (2002), BAHSIC Song et al. (2007; 2012), mRMR Peng et al. (2005), CCM Chen et al. (2017), RF Breiman (2002), DFS Li et al. (2016), LASSO Tibshirani (1996), L-Score He et al. (2005); and recently, DL-based Abid et al. (2019); Yamada et al. (2020); Lindenbaum et al. (2021).

Strategies for Supervised FS There are two strategies for populationwide supervised FS, which aim to 'identify a small, highly discriminative subset' Kuncheva et al. (2020). The first strategy e.g. Lee et al. (2022) first exploits elements of task-performance, self-supervision, additional unlabeled data, and correlated feature subsets, to score all features, then perform FS for chosen subset size C. In a second step, a network is trained on feature subset for the task. However, this step does not exploit global information – assumed to be unnecessary for e.g. classification on DNA/RNA/proteins, or even counterproductive when a large number of nuisance features masks the structured features e.g. noisy two-moons dataset. This differs from our ED paradigm, where such a discriminative subset may not exist, as data are globally informative and has large global correlation (figure 3). A second strategy combines training for FS and task optimization, and returns an optimal feature subset of pre-given size C and a trained task network. However, e.g. Wojtas & Chen (2020), which has dual feature scoring and task-prediction networks like JOFSTO, unnecessarily searches for the discriminative subset in the ED paradigm, which involves the NP hard problem of assessing input-target functional dependence Weston et al. (2003) and performing multiple task evaluations on different feature combinations. This may result in overfitting and long training times. This paper proposes to follow the second strategy with jointly optimized dual networks, but avoids searching for the highly-discriminative subset.

3 METHODS

Figure 1 outlines JOFSTO's variables and dependencies, together with the example tasks we demonstrate later. This section gives a conceptual overview of the procedure. Section A, in particular Algorithm 2, defines the details of the implementation.

Problem Specification Our subsampling ED paradigm requires an input data set $\bar{X} = \{\bar{\mathbf{x}}_1, ..., \bar{\mathbf{x}}_n\} \in \mathbb{R}^{n \times \bar{C}}$, which consists of n samples acquired under super-design $\bar{A} = \{\bar{\mathbf{a}}^1, ..., \bar{\mathbf{a}}^{\bar{C}}\}$ that densely-samples the measurement/feature space. We also require a target data set $Y = \{\mathbf{y}_1, ..., \mathbf{y}_n\} \in \mathbb{R}^{n \times M}$, which provides gold-standard output of the task driving the ED; each $\mathbf{y}_i$ is a vector of M targets (e.g. MRI model parameters) for the corresponding sample $\bar{\mathbf{x}}_i$. JOFSTO aims to subsample $C < \bar{C}$ acquisition-parameter combinations to obtain an economical design $A = \{\mathbf{a}^1, ..., \mathbf{a}^C\} \subset \bar{A}$, which corresponds to acquiring $X = \{\mathbf{x}_1, ..., \mathbf{x}_n\} \in \mathbb{R}^{n \times C}$ where the same C elements of each $\bar{\mathbf{x}}_i$ are in $\mathbf{x}_i$.

Outer Loop JOFSTO's novel approach to scoring and feature subsampling is in a recursive feature elimination (RFE) framework. Across an outer loop we implement a RFE procedure, to subsample progressively in steps from the full data set to the target size, C. Each step $t = 1, ..., T$ aims for an intermediate feature subset size C_t and to construct a sample-independent feature score $\bar{s}_t$, the corresponding binary mask to subsample features m_t so $X = m_t \cdot \bar{X}$ (use standard broadcasting rules in the $\cdot$ operation), and a trained task network $\mathcal{T}_t$ to estimate Y, with $\hat{Y} = \mathcal{T}_t(X \cdot \bar{s}_t)$.

Figure 1: JOFSTO trains two neural networks $\mathcal{S}, \mathcal{T}$ end-to-end, where gradients are passed through the black lines. The score s for each measurement is a combination of learnt score s^p, and an averaged score $\bar{s}$ that is not directly learnt. During training in step t, JOFSTO progressively sets s to $\bar{s}$ to construct $\bar{s}_t$, and progressively constructs the mask m_t to subsample the data, $\bar{X}$, based on the lowest scores. We use three tasks each with distinct target output, $\widehat{Y}$. The first maps each sample to a set of model parameters in section 4.1; the second reconstructs the full data set in section 4.2; the third estimates model parameters from the reconstructed full data set in section 4.3.

Progressive Network Modification JOFSTO's construction of $m_t, \bar{s}_t$ is motivated by previous work Karras et al. (2018); Blumberg et al. (2019). These approaches progressively modified neural network topology across training, from learning a simpler task to a more complicated task. We use this paradigm to construct the mask, where we progressively set entries of m to zero, so $||m_t||_1 = C_t$. We aim to learn $\bar{s}_t$. However, as DL training is on batches, we learn a sample-dependent score across the data first $s^p \in \mathbb{R}^{n \times \bar{C}}$, then average across batches to compute $\bar{s}$. The final learnt score s is a linear combination of s^p and $\bar{s}$, we progressively set $s = \bar{s}$ to construct $\bar{s}_t$ at the conclusion of step t.

Inner Loop: Main Training Procedure At each step, JOFSTO trains two coupled neural networks $\mathcal{S}, \mathcal{T}$ end-to-end. The first network $\mathcal{S}$ scores the features, learning s^p, and the second network $\mathcal{T}$ performs the task on the weighted subsampled data $X \cdot s$, where the multiplication allows gradients to flow backwards through $\mathcal{S}$. During training, JOFSTO first scores the features and, as described, constructs $\bar{s}_t$, so the computational graph is as shown in figure 1 (bottom). It then chooses features corresponding to the lowest scores of $\bar{s}_t$ to remove, where the progressive network modification heuristic is that a smaller alteration to the network topology results in less performance degradation, than making a larger alteration. JOFSTO then progressively constructs m_t to have C_t ones and $\bar{C} - C_t$ zeros during dual-network training, maintaining high task performance during subsampling.

4 EXPERIMENTS AND RESULTS

This section presents the experiments and results in the example application of qMRI. Results on four experiments show JOFSTO has enhanced capacity, compared to alternative approaches, for the ED problem of designing an efficient MRI acquisition scheme A underpinning clinically useful tasks. Section 4.1 examines, in a controlled simulated setting, estimation of ground truth model parameters from two widely used qMRI models that map histologic features of tumors, and complexity of neural dendrites and axons. Section 4.2 explores a MRI subsampling-reconstruction challenge. Section 4.3 focusses on estimating multiple clinically relevant downstream metrics, computed by fitting qMRI models on reconstructed data.

Data The experiments use four publicly available qMRI datasets. Each contains densely-sampled measurements in the acquisition parameter space, produced either by scanning in-vivo human brains,

Table 1: Mean-Squared-Error $\times 10^2$ between estimated model parameters and ground truth model parameters used to simulate data, comparing JOFSTO with classical Fisher Matrix ED from the literature.

	VERDICT		NODDI	
Classic ED	15.0	$C = 20$	8	$C = 99$
JOFSTO	**2.04**	$C = 20, \bar{C} = 220$	**4.51**	$C = 99, \bar{C} = 3612$

Table 2: Mean-Squared-Error $\times 10^2$, between estimated model parameters and ground truth model parameters used to simulate data, comparing JOFSTO against approaches in supervised feature selection, selecting C from $\bar{C}$ measurements

	VERDICT $\bar{C} = 220$				NODDI $\bar{C} = 3612$			
$C =$	110	55	28	14	1806	903	452	226
Random FS + DL	1.54	2.24	3.25	6.10	2.99	3.34	3.88	4.31
Lee et al. (2022)	1.06	1.28	1.89	4.58	2.95	3.39	3.73	4.39
Wojtas & Chen (2020)	2.22	2.14	3.09	4.05	4.21	4.61	4.96	5.14
JOFSTO	**1.03**	**1.18**	**1.80**	**2.64**	**2.59**	**2.92**	**3.33**	**3.85**

or via simulations using qMRI models. Data comprises 3D images with $\bar{C}$ channels acquired with a super-design sampling scheme within MR acquisition parameter space $\bar{A}$, various state-of-the-art scanner hardware platforms, pre-processing and post-processing steps. This produces datasets with varying numbers of measurements/channels/features $\bar{C}$, voxel resolution, and image statistics, further described and visualized in section D. As the statistical distribution of voxels in each measurement/channel is different, we normalize the data channel-wise at the input and output of all neural networks for more efficient training. Following standard practice in MR parameter estimation and mapping Cercignani et al. (2018); Alexander et al. (2019), the data samples $\mathbf{x}_i \in \mathbb{R}^{\bar{C}}$ are individual voxels, thus the $\bar{C}$ features are the measurements/channels.

Baselines Experiments evaluate against two levels of baseline. First, to evaluate the subsampling ED paradigm in general, we compare JOFSTO to classical qMRI ED techniques using the Fisher information matrix Alexander (2008). Then, within the subsampling paradigm, we consider three baseline supervised FS methods. Firstly, random FS then deep learning (DL) training – an off-the-shelf, simple approach; and two baselines described in section 2: Lee et al. (2022) – the state-of-the-art approach in supervised FS, and Wojtas & Chen (2020) which, like JOFSTO has dual feature scoring and task prediction networks. Each approach conducts a brief hyperparameter search, and for fairness, the same number of evaluations are used for each feature subset. We used the official code repository for the baselines when required. Further details are in supplementary section B.

4.1 JOFSTO PRODUCES BETTER PARAMETER ESTIMATES THAN BASELINES

This section shows JOFSTO outperforms classical approaches in ED and in supervised feature selection, in a controlled simulation setting, where the ED problem is to choose limited qMRI acquisition parameters / measurements, and estimate tissue-related parameters.

Recent trends in qMRI Palombo et al. (2020); Gyori et al. (2022) use DL to estimate ground truth model parameters. We adopt that idea with two qMRI models:

1. The VERDICT (Vascular, Extracellular and Restricted Diffusion for Cytometry in Tumors) model Panagiotaki et al. (2014), which maps histological features of solid-cancer tumors particularly for early detection and classification of prostate cancer Panagiotaki et al. (2015a); Johnston et al. (2019); Singh et al. (2022). The VERDICT model includes parameters: f_I the intra-cellular volume fraction, f_V the vascular volume fraction, D_v the vascular perpendicular diffusivity, R the mean cell radius, and $\mathbf{n}$ - a 3D vector defining mean local vascular orientation.

2. The NODDI (Neurite Orientation Dispersion and Density Imaging) model Zhang et al. (2012), maps parameters of the cellular composition of brain tissue and is widely used in neuroimaging studies in neuroscience such as the UK Biobank study Alfaro-Almagro et al. (2018), and neurology e.g. in Alzheimer's disease Kamiya et al. (2020) and multiple sclerosis Grussu et al. (2017). The

Table 3: Mean-squared-error between $\bar{C} = 1344$ reconstructed measurements and $\bar{C}$ ground-truth measurements, on same experimental settings as Blumberg et al. (2022).

	$C = 500$	250	100	50	40	30	20	10
Blumberg et al. (2022) Table 1 State-of-Art	0.49	0.61	0.89	1.35	1.53	1.87	2.50	3.48
JOFSTO	**0.22**	**0.43**	**0.88**	**1.34**	**1.52**	**1.76**	**2.12**	**2.88**

Table 4: Mean-squared-error between $\bar{C} = 1344$ reconstructed measurements and $\bar{C}$ ground-truth measurements, on MUlti-DIffusion (MUDI) challenge subjects.

	$C = 500$	250	100	50
Random FS + DL	0.93	1.41	2.12	5.23
Lee et al. (2022)	0.63	0.86	1.24	1.61
Wojtas & Chen (2020)	1.67	1.72	2.17	2.34
JOFSTO	**0.21**	**0.44**	**0.94**	**1.34**

NODDI model includes five tissue parameters: f_{ic} the intra-cellular volume fraction, f_{iso} the isotropic volume fraction, the *orientation dispersion index* (ODI) that reflects the level of variation in neurite orientation, and **n** - a 3D vector defining the mean local fibre orientation.

We use simulations with known ground truth parameters to evaluate the different ED approaches via accuracy of model-parameter estimation. For the classical ED approach, we use two published Fisher matrix-optimized acquisition schemes for the two models, for VERDICT from Panagiotaki et al. (2015b) where $C = 20$; and NODDI from Zhang et al. (2012) where $C = 99$. For the supervised feature selection approaches, we select features from model-specific densely-sampled acquisition schemes for VERDICT ($\bar{C} = 220$) Panagiotaki et al. (2015a); and NODDI ($\bar{C} = 3612$) Ferizi et al. (2017). Simulated input qMRI data is created with $\mathbf{x}_i = f_{\boldsymbol{\theta}_i}(\mathbf{a}) + noise$, for MRI model f with parameters $\boldsymbol{\theta}_i$ at sample/voxel $i = 1, ..., n$, Rician noise Gudbjartsson & Patz (1995) representative of clinical qMRI, where $\boldsymbol{\theta}_1, ..., \boldsymbol{\theta}_n$ is generated from a biologically plausible range, described in section D and are fixed across different experiments. The target data are the ground truth model parameters $Y = \{\boldsymbol{\theta}_1, ..., \boldsymbol{\theta}_n\}$. Performance is evaluated as the MSE between the true $\{\boldsymbol{\theta}_i\}_{i=1}^n$ and learnt parameters.

Table 1 compares the classical Fisher information matrix ED Alexander (2008) against the JOFSTO, where JOFSTO FS size C is set to the number of measurements produced by the classical ED acquisition scheme. Table 2 shows JOFSTO against alternative approaches in supervised FS, where $C = \frac{\bar{C}}{2}, \frac{\bar{C}}{4}, \frac{\bar{C}}{8}, \frac{\bar{C}}{16}$. Further details regarding the models, experimental settings, and data are in sections D. In both cases, JOFSTO outperforms the baselines.

4.2 JOFSTO PRODUCES STATE-OF-THE-ART PERFORMANCE IN THE MUDI RECONSTRUCTION CHALLENGE

This section shows that JOFSTO obtains state-of-the-art performance, and outperforms approaches in supervised FS, in a subsampling-reconstruction MRI challenge.

The aim of the MICCAI MUlti-DIffusion (MUDI) challenge Pizzolato et al. (2020) was to identify an informative subset of a densely sampled qMRI data set, then use the subset to reconstruct the full data set. This reconstruction task first provides a generic challenge that tests the ability of an ED or FS algorithm to identify a subset with maximal information content. The data come from a diffusion-relaxation MRI acquisition, a state-of-the art qMRI technique that acquires multiple MRI modalities simultaneously in a high-dimensional acquisition parameter space, yielding enhanced in-vivo sensitivity to microstructural tissue properties Slator et al. (2021). The MUDI data has $\bar{C} = 1344$ measurements/channels with $A \subset \mathbb{R}^6$, underscoring the particular importance of ED for diffusion-relaxation MRI, as adequately sampling this high-dimensional measurement space in a time budget that is realistic in clinical settings is difficult Slator et al. (2021).

Challenge participants were asked to reduce the acquisition time of the full dataset to a clinically feasible duration. The two linked tasks were: i) Select a subset of the full dataset of pre-defined size $C = \{500, 250, 100, 50\}$; ii) Given the chosen subset for unseen data, to reconstruct the entire

Table 5: Mean-squared-error between parametric maps (downstream metrics) estimated from $\bar{C} = 288$ ground truth measurements and $\tilde{C}$ from C reconstructed measurements.

$C = 36$	DTI				DKI			MSDKI	
	FA	MD	AD	RD	MK	AK	RK	MSD	MSK
Random FS + DL	1.17	3.13	9.3	3.75	6.37	6.28	13.3	**2.50**	4.15
Lee et al. (2022)	5.96	10.4	43.7	14.2	8.74	7.27	16.9	3.87	10.8
Wojtas & Chen (2020)	10.4	68.8	106	81.4	9.39	10.3	18.6	11.1	8.82
JOFSTO	**0.94**	**1.73**	**8.15**	**1.50**	**6.15**	**5.92**	**12.6**	2.75	**3.78**
$C = 18$	DTI				DKI			MSDKI	
	FA	MD	AD	RD	MK	AK	RK	MSD	MSK
Random FS + DL	2.23	6.09	22.7	6.97	9.03	7.83	15.3	6.82	7.59
Lee et al. (2022)	2.86	12.9	31.2	14.9	12.0	9.26	20.3	8.96	8.17
Wojtas & Chen (2020)	9.83	23.2	77.7	26.8	11.9	10.9	21.3	10.8	6.03
JOFSTO	**1.29**	**2.55**	**13.4**	**2.60**	**7.67**	**6.73**	**13.9**	**6.37**	**4.94**

Figure 2: Qualitative comparison of 2D slices from 3D parametric maps (downstream metrics), where gold standard is estimated from $\bar{C} = 288$ ground truth measurements, and baseline/ours is from $C = 18$ reconstructed measurements. JOFSTO's parametric maps are visually closer to the gold standard than those from the baseline.

densely-sampled data, used to evaluate the ED i.e $Y := \bar{X}$. Here we use the MUDI challenge data set for two experiments that highlight the benefits of JOFSTO for the subsampling-reconstruction challenge. The first experiment follows the setting in Blumberg et al. (2022), which has state-of-the-art performance on the data. The second experiment compares JOFSTO with the state-of-the-art techniques in supervised FS in the settings of the original challenge. Table 3 shows results from experiment 1 confirming that JOFSTO improves over the state-of-the-art. Table 4 also shows that JOFSTO outperforms competing techniques in supervised FS in the setting of the original challenge.

Table 6: Ablation study on JOFSTO's components, experimental settings in table 1.

$C =$	110	55	28	14
JOFSTO w/o Scoring Network S	7.23	10.7	11.5	11.5
JOFSTO w/o RFE	**1.03**	1.19	1.83	2.80
JOFSTO	**1.03**	**1.18**	**1.80**	**2.64**

Table 7: Standard deviation of performance $\times 10^2$ and mean Jaccard Index between chosen measurements, across 10 random seeds, experimental settings in table 1 VERDICT simulations.

	STD performance across 10 seeds				Mean Jaccard of Chosen Measurements %			
$C =$	500	250	100	50	500	250	100	50
Random FS + DL	0.11	0.23	0.37	0.76	32.8	15.2	6.82	2.87
Lee et al. (2022)	0.01	0.02	0.05	0.18	81.2	71.4	62.2	75.9
Wojtas & Chen (2020)	0.44	0.34	0.37	0.44	34.3	18.1	48.8	41.0
JOFSTO	0.01	0.02	0.01	0.12	74.3	82.1	84.6	59.1

4.3 JOFSTO IMPROVES ESTIMATION OF TISSUE MICROSTRUCTURE FROM WATER DIFFUSIVITY

This section shows JOFSTO outperforms approaches in supervised FS for the ED task of designing an efficient acquisition scheme to support reconstruction of a densely-sampled dataset and downstream in-vivo quantification of human tissue microstructure.

Diffusion tensor imaging (DTI) Basser (1994) and diffusion kurtosis imaging (DKI) Jensen & Helpern (2010) are two widely-used qMRI methods. Like NODDI and VERDICT, they use diffusion MRI to sensitise the image intensity to the Brownian motion of water molecules within the tissue to provide a window on tissue microstructure. However, whereas NODDI and VERDICT are designed specifically for application to brain tissue and cancer tumours, respectively, DTI and DKI are more general purpose techniques that provide indices of diffusivity (e.g. mean diffusivity - MD), diffusion anisotropy (e.g. fractional anisotropy Bassera & Pierpaoli (1996) - FA), and the deviation from Gaussianity, or kurtosis, (e.g. mean kurtosis Jensen & Helpern (2010) - MK) that can inform on tissue integrity or pathology. Mean signal diffusion kurtosis imaging (MSDKI) is a simplified version of DKI that quantifies kurtosis using a simpler model that is easier to fit Henriques (2018). These techniques show promise for extracting imaging biomarkers for a wide variety of medical applications, such mild brain trauma, epilepsy, stroke, and Alzheimer's disease Ranzenberger & Snyder (2022); Tae et al. (2018); Jensen & Helpern (2010).

The experiment use feature subset sizes $C = \frac{\bar{C}}{8}, \frac{\bar{C}}{16}$, with the aim of testing the ability of various subsampling strategies to reduce the acquisition requirements for these imaging techniques, thereby enabling their usage in a wider range of clinical application areas. MRI models and model fitting use standard techniques detailed in section C, further data and information are in section D. Quantitative and qualitative results are in table 5, figure 2, where the JOFSTO outperforms the baselines quantitatively in 17/18 comparisons on clinically useful downstream metrics (parameter maps) and JOFSTO's parametric maps are visually closer to the gold standard than those from the baseline.

4.4 ABLATION STUDY AND THE EFFECT ON RANDOMNESS ON PERFORMANCE

Table 6 examines the impact of removing JOFSTO's components on performance. First it considers JOFSTO without RFE i.e. without iteratively removing features in our optimization algorithm and fixing $t = 2$ and $C_1, C_2 = \bar{C}, C$, showing that iterative subsampling has better performance than subsampling all the features in a single iteration. As our approach to feature scoring is a key element of JOSFTO, we also consider the impact of removing the scoring network S, which results in extremely poor performance as training is destabilized when progressively setting the score s from sample-dependence to sample-independence. Table 7 examines how the choice of random seed that affects network initialization and data shuffling, impacts performance. Results show JOFSTO performs favourably compared to alternative approaches, and JOFSTO is mostly robust to randomness inherent in DL.

5 CONCLUSION AND LIMITATIONS

Conclusion This paper proposes to replace classic approaches in ED with a subsampling-task paradigm analogous to populationwide supervised FS, thereby avoiding complications in continuous optimization and dependence of the design on a-priori model parameter choices. We introduce JOFSTO, which performs JOint Feature Selection and Task Optimization, that takes advantage of the structure of ED data. Experiments address the clinically relevant ED problem of obtaining high-quality microstructural information in the limited time available in quantitative MRI scans. Results show JOFSTO outperforms classical ED and state-of-the-art approaches in populationwide supervised FS. JOFSTO also obtains state-of-the-art performance in a subsampling-reconstruction MRI challenge. The code is available to reviewers Code (2022).

Limitations Our paradigm assumes we can obtain densely-sampled data in the measurement space. This is possible in MRI, as only a few subjects are required to provide densely-sampled training data. They may be e.g. sedated, and remain motionless for the long acquisition times required. Whilst such data is acquirable in 1 hour in research studies, in extreme cases motivated researchers endured longer, e.g. 8 hours in Ferizi et al. (2017). Future work will need to study the size and diversity of densely sampled data needed to ensure strong generalizable design. Small dense data sets are also achievable in other ED scenarios, such as other imaging problems or cell populations, although the strategy may not extend to all. Unlike alternative approaches in supervised FS e.g. Lee et al. (2022); Wojtas & Chen (2020), JOFSTO does not purport to consistently identify a small, highly discriminative feature subset Kuncheva et al. (2020); it is not designed to ignore a large number of nuisance features masking the variability of structured features Lindenbaum et al. (2021) or to explicitly integrate the correlation structure between feature subsets for efficiency Lee et al. (2022). This is an advantage in the ED paradigm, but means that JOFSTO may perform less well supervised FS tasks with these requirements, e.g. classification on some (but not all) proteins/DNA/RNA datasets, or identifying structured features of the synthetic noisy two-moon dataset. As JOFSTO uses DL, it is likely to overfit when the number of samples n is limited, or n is less than the number of selected features C, as observed in Kuncheva et al. (2020); Wojtas & Chen (2020). This scenario is frequent in e.g. genomics and could potentially occur even in imaging tasks if the diversity of signals over the image is low or the image is small. For example, Ferizi et al. (2017) used only 8 voxels with $\bar{C} = 3612$ measurements, to conduct a (voxelwise) MRI model ranking competition. JOFSTO's use of RFE is to aid the challenging optimization by reducing to stepwise consideration of nested feature subsets across steps $t = 1, .., T$. However, this decreases the upper bound on performance as the optimal feature set for C_t may not be a subset of the optimal feature set for C_{t-1}; future work will consider alternative optimization strategies to seek more globally optimal designs.

ETHICS STATEMENT

This paper highlights direct impact of our novel approach to ED applied to MRI. By selecting few acquisition parameters which may be obtained in routine MRI scans, and performing a task that provides improved visual or microstructural information, a clinician may better analyze and diagnose a variety of pathologies, potentially improving public health. This of course depends on the specific acquisition platforms and site, which varies scan performance. Thus results should be thoroughly verified by clinical experts before deployment. This paper also used in-vivo human brain MRI scans and followed the respective guidelines, where the authors of the cited, respective papers completed appropriate ethical reviews.

REPRODUCIBILITY

The code for our method in this paper will be publicly available and is submitted to the reviewers Code (2022). All data are publicly available. Data acquired from MRI scans are described in section D, including processing, splits, and download links. Code to generate simulated data is in the code repository. Settings for the JOFSTO and baseline methods are in section B. Details on MRI model fitting is in section C and uses publicly available libraries.

REFERENCES

10x Genomics. Single cell gene expression datasets. `https://support.10xgenomics.com/`

`single-cell-gene-expression/datasets`, 2022.

Abubakar Abid, Muhammed Fatih Balın, and James Zou. Concrete autoencoders: Differentiable feature selection and reconstruction. *In: International Conference on Machine Learning (ICML)*, 2019.

Daniel Alexander. A general framework for experiment design in diffusion MRI and its application in measuring direct tissue-microstructure features. *Magnetic resonance in medicine*, 60(2):439–448, 2008.

Daniel C. Alexander, Tim B. Dyrby, Markus Nilsson, and Hui Zhang. Imaging brain microstructure with diffusion MRI: practicality and applications. *NMR in Biomedicine*, 32(4):e3841, 2019.

Fidel Alfaro-Almagro, Mark Jenkinson, Neal K Bangerter, Jesper L R Andersson, Ludovica Griffanti, Gwenaëlle Douaud, Stamatios N Sotiropoulos, Saad Jbabdi, Moises Hernandez-Fernandez, Emmanuel Vallee, Diego Vidaurre, Matthew Webster, Paul McCarthy, Christopher Rorden, Alessandro Daducci, Daniel C Alexander, Hui Zhang, Iulius Dragonu, Paul M Matthews, Karla L Miller, and Stephen M Smith. Image processing and quality control for the first 10,000 brain imaging datasets from UK biobank. *Neuroimage*, 166:400–424, 2018.

Jiju Antony. *Design of Experiments for Engineers and Scientists*. Oxford: Butterworth-Heinemann, 2003.

Mattiello J.- LeBihan D. Basser, P. J. Mr diffusion tensor spectroscopy and imaging. *Biophysical journal*, 66(1):259–267, 1994.

Peter J. Bassera and Carlo Pierpaoli. Microstructural and physiological features of tissues elucidated by quantitative-diffusion-tensor MRI. *Journal of Magnetic Resonance*, 111:209–219, 1996.

Stefano B. Blumberg, Marco Palombo, Can Son Khoo, Chantal M. W. Tax, Ryutaro Tanno, and Daniel C. Alexander. Multi-stage prediction networks for data harmonization. *In: Medical Image Computing and Computer Assisted Intervention (MICCAI)*, 2019.

Stefano B. Blumberg, Hongxiang Lin, Francesco Grussu, Yukun Zhou, Matteo Figini, and Daniel C. Alexander. Progressive subsampling for oversampled data – application to quantitative MRI. In: Medical Image Computing and Computer Assisted Intervention (MICCAI), 2022.

Leo Breiman. Random forests. *Machine Learning*, 45(1):1573–0565, 2002.

Mara Cercignani, Nicholas G. Dowell, and Paul S. Tofts. *Quantitative MRI of the Brain: Principles of Physical Measurement*. CRC Press, second edition, 2018.

Kathryn Chaloner and Isabella Verdinelli. Bayesian experimental design: A review. *Statistical Science*, 10(3):273–304, 1995.

J. Chen, M. Stern, M. Wainwright, and M. Jordan. Kernel feature selection via conditional covariance minimization. *In: Neural Information Processing Systems (NIPS)*, 2017.

Paper Code. Code for this paper. `https://www.dropbox.com/scl/fo/qe6vb1w6fuf869hx4ht0k/h?dl=0&rlkey=og8czcorurl57jbiixio7hcjt`, 2022.

David C Van Essen, Stephen M Smith, Deanna M Barch, Timothy E J Behrens, Essa Yacoub, Kamil Ugurbil, and WU-Minn HCP Consortium. The WU-Minn Human Connectome Project: an overview. *Neuroimage*, 80:62–79, 2013.

Guillaume E.Vanot and Michelle Sergent. *Experimental Design in Microbiology*. Humana Press, 2005.

Uran Ferizi, Benoit Scherrer, Torben Schneider, Mohammad Alipoor, Odin Eufracio, Rutger H J Fick, Rachid Deriche, Markus Nilsson, Ana K Loya-Olivas, Mariano Rivera, Dirk H J Poot, Alonso Ramirez-Manzanares, Jose L Marroquin, Ariel Rokem, Christian Pötter, Robert F Dougherty, Ken Sakaie, Claudia Wheeler-Kingshott, Simon K Warfield, Thomas Witzel, Lawrence L Wald, José G Raya, and Daniel C Alexander. Diffusion MRI microstructure models with in vivo human brain connectome data: results from a multi-group comparison. *NMR in biomedicine*, 30(9), 2017.

Rutger Fick, Demian Wassermann, and Rachid Deriche. The Dmipy toolbox: Diffusion MRI multi-compartment modeling and microstructure recovery made easy. *Frontiers in Neuroinformatics*, 13 (64), 2019.

B Roy Frieden. *Science from Fisher information: a unification*. Cambridge University Press, 2004.

Eleftherios Garyfallidis, Matthew Brett, Bagrat Amirbekian, Ariel Rokem, Stefan van der Walt, Maxime Descoteaux, Ian Nimmo-Smith, and Dipy Contributors. DIPY, a library for the analysis of diffusion MRI data. *Frontiers in Neuroinformatics*, 8(8), 2014.

Francesco Grussu, Torben Schneider, Carmen Tur, Richard L Yates, Mohamed Tachrount, Andrada Ianuş, Marios C Yiannakas, Jia Newcombe, Hui Zhang, Daniel C Alexander, Gabriele C DeLuca, and Claudia A M Gandini Wheeler-Kingshott. Neurite dispersion: a new marker of multiple sclerosis spinal cord pathology? *Annals of Clinical and Translational Neurology*, 4(9), 2017.

Francesco Grussu, Stefano B. Blumberg, Marco Battiston, Lebina S. Kakkar, Hongxiang Lin, Andrada Ianuş, Torben Schneider, Saurabh Singh, Roger Bourne, Shonit Punwani, David Atkinson, Claudia A. M. Gandini Wheeler-Kingshott, Eleftheria Panagiotaki, Thomy Mertzanidou, and Daniel C. Alexander. Feasibility of data-driven, model-free quantitative mri protocol design: Application to brain and prostate diffusion-relaxation imaging. *Frontiers in Physics*, 9:615, 2021.

HáKon Gudbjartsson and Samuel Patz. The rician distribution of noisy MRI data. *Magnetic Resonance in Medicine*, 34(6):910–914, 1995.

V K Gupta, Rajender Parsad, and B N Mandal. *Significance of Experimental Designs in Agricultural Research*. Indian Agricultural Statistics Research Institute (IASRI), 2015.

Isabelle Guyon, Jason Weston, Stephen Barnhill, and Vladimir Vapnik. Gene selection for cancer classification using support vector machines. *Journal of Machine Learning Research*, 46(1): 389–422, 2002.

Isabelle Guyon, Steve Gunn, Asa Ben-Hur, and Gideon Dror. Result analysis of the NIPS 2003 feature selection challenge. *In: Neural Information Processing System (NIPS)*, 2004.

Noemi G Gyori, Marco Palombo, Christopher A Clark, Hui Zhang, and Daniel C Alexander. Training data distribution significantly impacts the estimation of tissue microstructure with machine learning. *Magnetic Resonance in Medicine*, 87(2):932–947, 2022.

Xiaofei He, Deng Cai, and Partha Niyogi. Laplacian score for feature selection. *In: Neural Information Processing Systems (NIPS)*, 2005.

Rafael Neto Henriques. Advanced methods for diffusion MRI data analysis and their application to the healthy ageing brain. *Ph.D Thesis*, 2018.

Jana Hutter, Paddy J Slator, Daan Christiaens, Rui Pedro AG Teixeira, Thomas Roberts, Laurence Jackson, Anthony N Price, Shaihan Malik, and Joseph V Hajnal. Integrated and efficient diffusion-relaxometry using zebra. *Scientific reports*, 8(1):1–13, 2018.

Nicolas Jacquemet and Olivier L'Haridon. *Experimental Economics Method and Applications*. Cambridge University Press, 2019.

Jens H Jensen and Joseph A Helpern. MRI quantification of non-gaussian water diffusion by kurtosis analysis. *NMR in Biomedicine*, 23(7):698–710, 2010.

Edward W Johnston, Elisenda Bonet-Carne, Uran Ferizi, Ben Yvernault, Hayley Pye, Dominic Patel, Joey Clemente, Wivijin Piga, Susan Heavey, Harbir S Sidhu, Francesco Giganti, James O'Callaghan, Mrishta Brizmohun Appayya, Alistair Grey, Alexandra Saborowska, Sebastien Ourselin, David Hawkes, Caroline M Moore, Mark Emberton, Hashim U Ahmed, Hayley Whitaker, Manuel Rodriguez-Justo amd Alexander Freeman, David Atkinson, Daniel Alexander, Eleftheria Panagiotaki, and Shonit Punwani. VERDICT MRI for prostate cancer: Intracellular volume fraction versus apparent diffusion coefficient. *Radiology*, 291(2):391–397, 2019.

Jean Kaddour, Steindór Sæmundsson, and Marc Peter Deisenroth. Probabilistic active meta-learning. *In: Neural Information Processing Systems (NeurIPS)*, 2020.

Kouhei Kamiya, Masaaki Hori, and Shigeki Aoki. NODDI in clinical research. *Journal of Neuroscience Methods*, 346:108908, 2020. ISSN 0165-0270. doi: https://doi.org/10.1016/j.jneumeth.2020.108908. URL https://www.sciencedirect.com/science/article/pii/S0165027020303319.

Tero Karras, Timo Aila, Samuli Laine, and Jaakko Lehtinen. Progressive growing of gans for improved quality, stability, and variation. *In: International Conference on Learning Representations (ICLR)*, 2018.

Ludmila I. Kuncheva, Clare E. Matthews, Álvar Arnaiz-González, and Juan José Rodríguez Diez. Feature selection from high-dimensional data with very low sample size: A cautionary tale. *arXiv preprint arXiv:2008.12025*, 2020.

Changhee Lee. Code for self-supervision enhanced feature selection with correlated gates. *https://github.com/chl8856/SEFS, git commit 21fe6d97cd98612e3d0eb5ce204d2d0e2e9deb5a*, 2022.

Changhee Lee, Fergus Imrie, and Mihaela van der Schaar. Self-supervision enhanced feature selection with correlated gates. *International Conference on Learning Representations (ICLR)*, 2022.

Y Li, C Chen, and W Wasserman. Deep feature selection: Theory and application to identify enhancers and promoters. *J Comput Biol*, 23(5):322–336, 2016.

Ofir Lindenbaum, Uri Shaham, Erez Peterfreund, Jonathan Svirsky, Nicolas Casey, and Yuval Kluger. Differentiable unsupervised feature selection based on a gated laplacian. *In: Neural Information Processing Systems (NeurIPS)*, 2021.

Huan Liu and Hiroshi Motoda. *Feature Selection for Knowledge Discovery and Data Mining*. The Springer International Series in Engineering and Computer Science. Springer, 1998.

L. M. Lye. *Design of experiments in civil engineering: are we still in the 1920's ?* Dekker New York, 2002.

Douglas C Montgomery. *Design and analysis of experiments*. John Wiley & Sons, fifth edition, 2001.

MUDI Organizers. MUlti-dimensional DIffusion (MUDI) MRI challenge 2019 data. https://www.developingbrain.co.uk/data/, 2022.

Marco Palombo, Andrada Ianuş, Michele Guerreri, Daniel Nunes, Daniel C. Alexander, Noam Shemesh, and Hui Zhang. SANDI: A compartment-based model for non-invasive apparent soma and neurite imaging by diffusion MRI. *NeuroImage*, 215:116835, 2020.

Eleftheria Panagiotaki, Rachel W Chan, Nikolaos Dikaios, Hashim U Ahmed, James O'Callaghan, Alex Freeman, David Atkinson, Shonit Punwani, David J Hawkes, and Daniel C Alexander. Microstructural characterization of normal and malignant human prostate tissue with vascular, extracellular, and restricted diffusion for cytometry in tumours magnetic resonance imaging. *Investigative Radiology*, 50(4):218–227, 2015a.

Eleftheria Panagiotaki, Andrada Ianuş, Edward Johnston, Rachel W Chan, Nicola Stevens, David Atkinson, Shonit Punwani, David J Hawkes, and Daniel C Alexander. Optimised VERDICT MRI protocol for prostate cancer characterisation. *In: International Society for Magnetic Resonance in Medicine (ISMRM)*, 2015b.

Eletheria Panagiotaki, Simon Walker-Samuel, Bernard Siow, S. Peter Johnson, Vineeth Rajkumar, R. Barbara Pedley, Mark F. Lythgoe, and Daniel C. Alexander. Noninvasive quantification of solid tumor microstructure using VERDICT MRI. *Cancer research*, 74(7):1902–1912, 2014.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Köpf, Edward Yang, Zach DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Junjie Bai Lu Fang, and Soumith Chintala. PyTorch: An imperative style, high-performance deep learning library. *In: Neural Information Processing Systems (NEURips*, 2019.

H. Peng, F. Long, and C. Ding. Feature selection via dependence maximization. volume 27, pp. 1226–1238, 2005.

Marco Pizzolato, Marco Palombo, Elisenda Bonet-Carne, Francesco Grussu, Andrada Ianuş, Fabian Bogusz, Tomasz Pieciak, Lipeng Ning, Stefano B. Blumberg, Thomy Mertzanidou, Daniel C. Alexander, Maryam Afzali, Santiago Aja-Fernández, Derek K. Jones, Carl-Fredrik Westin, Yogesh Rathi, Steven H. Baete, Lucilio Cordero-Grande, Thilo Ladner, Paddy J. Slator, Daan Christiaens, Jean-Philippe Thiran, Anthony N Price, Farshid Sepehrband, Fan Zhang, and Jana Hutter. Acquiring and predicting MUlti-dimensional DIffusion (MUDI) data: an open challenge. *In: International Society for Magnetic Resonance in Medicine (ISMRM)*, 2020.

Friedrich Pukelsheim. *Optimal Design of Experiments*. Society for Industrial and Applied Mathematics, 2006.

Logan R. Ranzenberger and Travis Snyder. *Diffusion Tensor Imaging*. StatPearls Publishing, fifth edition, 2022.

Scikit-Learn. Scikit-learn make moons. `https://scikit-learn.org/stable/modules/generated/sklearn.datasets.make_moons.html`, 2022.

Saurabh Singh, Harriet Rogers, Baris Kanber, Joey Clemente, Hayley Pye, Edward W. Johnston, Tom Parry, Alistair Grey, Eoin Dinneen, Greg Shaw, Susan Heavey, Urszula Stopka-Farooqui, Aiman Haider, Alex Freeman, Francesco Giganti, David Atkinson, Caroline M. Moore, Hayley C. Whitaker, Daniel C. Alexander, Eleftheria Panagiotaki, and Shonit Punwani. Avoiding unnecessary biopsy after multiparametric prostate MRI with VERDICT analysis: The INNOVATE study. *Radiology*, pp. 212536, 2022.

Paddy J. Slator, Marco Palombo, Karla L. Miller, Carl-Fredrik Westin, Frederik Laun, Daeun Kim, Justin P. Haldar, Dan Benjamini, Gregory Lemberskiy, Joao P. de Almeida Martins, and Jana Hutter. Combined diffusion-relaxometry microstructure imaging: Current status and future prospects. *Magnetic resonance in medicine*, 86(6):2987–3011, 2021.

L. Song, A. Smola, A. Gretton, K. M. Borgwardt, and J. Bedo. Supervised feature selection via dependence estimation. In *In: International Conference on Machine learning (ICML)*, 2007.

L. Song, A. Smola, A. Gretton, J. Bedo, and K. Borgwardt. Feature selection via dependence maximization. volume 13, pp. 1393–1434, 2012.

Woo Suk Tae, Byung Joo Ham, Sung Bom Pyun, Shin Hyuk Kang, and Byung Jo Kim. Current clinical applications of diffusion-tensor imaging in neurological disorders. *Journal of Clinical Neurology*, 14(2):129–140, 2018.

Robert Tibshirani. Regression shrinkage and selection via the lasso. *Journal of the Royal Statistics Society. Series B (Methodological)*, pp. 267–288, 1996.

Jason Weston, André Elisseeff, Bernhard Schölkopf, and Michael E. Tipping. Use of the zero-norm with linear models and kernel methods. *Journal of Machine Learning Research*, 3:1439–1461, 2003.

Maksymilian A. Wojtas. Code for feature importance ranking for deep learning, git commit 836096edb9f822e509cadcf9cd2e7cc5fa2324cc. `https://github.com/maksym33/FeatureImportanceDL`, 2021.

Maksymilian A. Wojtas and Ke Chen. Feature importance ranking for deep learning. *In: Neural Information Processing System (NeurIPS)*, 2020.

Yutaro Yamada, Ofir Lindenbaum, Sahand Negahban, and Yuval Kluger. Feature selection using stochastic gates. *In: International Conference on Machine Learning (ICML*, 2020.

Hui Zhang, Torben Schneider, Claudia A Wheeler-Kingshott, and Daniel C Alexander. NODDI: practical in vivo neurite orientation dispersion and density imaging of the human brain. *NeuroImage*, 61(4):1000–1016, 2012.

A   JOFSTO'S OPTIMIZATION ALGORITHM

This section presents further details concerning JOFSTO's optimization algorithm, outlined in section 3. We first describe the computational graph, illustrated in figure 1. We then describe the optimization procedure in full, described in algorithm 2. For steps $t = 1, ..., T$ this procedure obtains $m_t, \bar{s}_t, \mathcal{T}_t$, which are $m, \bar{s}, \mathcal{T}$ at the completion of step t. Multiplication follows standard array broadcasting rules e.g. $\mathbf{z}_1 \in \mathbb{R}^d, Z_2 \in \mathbb{R}^{n \times d}$, then $\mathbf{z}_1 \cdot Z_2 \in \mathbb{R}^{n \times d}$ is element-wise multiplication broadcasted to the first dimension.

Computational Graph This describes JOFSTO's computational graph during training, illustrated in figure 1-top and described in algorithm 1. JOFSTO has two neural networks: a Scoring Network $\mathcal{S}$ and a Task Network $\mathcal{T}$. The final feature score s is a linear combination of a learnt score $s^p = \sigma(\mathcal{S}(\bar{X}))$ and a sample-independent (averaged) score $\bar{s}$, expressed as $s = \alpha^s \cdot s^p + (1 - \alpha^s) \cdot \bar{s}$, where $s^p \in \mathbb{R}^{n \times \bar{C}}, \bar{s} \in \mathbb{R}^{\bar{C}}$, and $\alpha^s \in [0, 1]$ is not learnt but used to progressively set $s = \bar{s}$, and $\sigma : \mathbb{R} \to [0, \infty)$ is an activation function to ensure positive scores. JOFSTO uses a mask $m \in [0, 1]^{\bar{C}}$ to subsample the measurements with $X = m \cdot \bar{X} + (1 - m) \cdot \bar{X}^{fill}$ where $\bar{X}^{fill} \in \mathbb{R}^{\bar{C}}$ is user-chosen (e.g. zeros or data median) and fills the locations of un-subsampled measurements. The second neural network, the Task Network $\mathcal{T}$ takes the weighted, subsampled measurements and estimates the target $\widehat{Y} = \mathcal{T}(s \cdot X)$, where multiplication here allows gradients to flow end-to-end. A supervised loss is calculated $L(\widehat{Y}, Y)$, for user-chosen L and is backpropagated to compute the gradients of $\mathcal{S}, \mathcal{T}$.

Recursive Feature Elimination (RFE) The user prespecifies the number of features to consider across steps $t = 1, ..., T$: $C_1, ..., C_T$ where $\bar{C} = C_1 > ... > C_T$, so $C_{t-1} - C_t$ features are removed in step $t > 2$. In step t JOFSTO uses its novel approach to score features with $\bar{s}_t$, and uses m_t to subsample the features, within a RFE framework.

Step t = 1 On the first step JOFSTO trains on full information and learns a sample-independent score. It sets $m = m_1 = [1]^{\bar{C}}, \alpha^s = 1$ and trains across epochs $e = 1, ..., E$. At completion, set the first sample-independent score $\bar{s}_1 = \bar{s}^p$ where $\bar{s}^p$ is the mean of s^p across samples/batches.

Steps t = 2,...,T For subsequent steps, JOFSTO splits the inner loop training procedure $1 <= E_1 < E_2 < E_3 < E$ for hyperparameters epochs E_1, E_2, E_3.

1. Across $e = 1, ..., E_1$ JOFSTO learns a sample-independent score for each measurement. It trains on a combination of (previous) sample-independent score and current learnt score, and at $e = E_1$ it sets the sample-independent score as a the mean of learnt scores. This is $\bar{s} = \bar{s}_{t-1}, \alpha^s = \frac{1}{2}, m = m_{t-1}$, at $e = E_1$ set $\bar{s}_t = \frac{1}{2}(\bar{s}_{t-1} + \bar{s}^p)$ where $\bar{s}^p$ is the mean of s^p across samples/batches.

2. Across $e = E_1 + 1, ..., E_2$ JOFSTO progressively sets the score to be sample-independent, by progressively setting α^s from 1 to 0 successively on these epochs, allowing training to go from sample-dependent ($s = s^p$) to sample-independent scores ($s = \bar{s}$).

3. Across $e = E_2 + 1, ..., E_3$ JOFSTO chooses the lowest-scored measurements to subsample, then progressively modifies mask elements to perform this subsampling. At epoch $e = E_2$ choose the measurements to subsample $D_t = \arg\min_{C_{t-1} - C_t} \{\bar{s}_t[i] : m_{t-1}[i] = 1\}$, with mask target $m_t = m_{t-1} - \mathbb{I}_{i \in D}$. Construct the mask progressively with $m = \alpha^m \cdot m_{t-1} + (1 - \alpha^m) \cdot m_t$ where $\alpha^m \in [0, 1]$ is set from 1 to 0 across these epochs.

4. Across $e = E_3 + 1, ..., E$ the Task Network $\mathcal{T}$ is trained. At the completion of step t, this process returns (trained) $\mathcal{T}$ and $m, \bar{s}$, denoted as $\mathcal{T}_t, m_t, \bar{s}_t$. Then use as $\widehat{Y} = \mathcal{T}_t(X \cdot \bar{s}_t)$ as figure 1 Test.

Using JOFSTO For C_t acquisition-parameter combinations, use $A^{C_t} = \{\mathbf{a}^c : m_t[c] = 1, c = 1, ..., \bar{C}\}$ to obtain new data, where $\mathbf{a}^c \in A^{C_t}$ produces the measurement $x_1^c, ..., x_n^c$. Then one fills un-acquired measurements with $\bar{X}^{fill}$ by setting $X_i^c = (x_i^c$ if $m[c] = 1$, else $\bar{X}^{fill}[c])$ producing $X \in \mathbb{R}^{n \times \bar{C}}$. Then estimate Y with $\widehat{Y} = \mathcal{T}_t(X \cdot \bar{s}_t)$, and compute a downstream metric on $\widehat{Y}$.

Implementation JOFSTO's code is in PyTorch Paszke et al. (2019) and is submitted anonymously Code (2022). We describe its hyperparameters in section B.

Algorithm 1 JOFSTO Forward and Backwards Pass: FPBP()

Input Input Data $\bar{X} \in \mathbb{R}^{n \times \bar{C}}$, Target Data Y, Subsampled Data Fill $\bar{X}^{fill}$, Scoring Network $\mathcal{S}$, Task Network $\mathcal{T}$, Final Feature Score Multiplier $\alpha^s \in [0, 1]$, Mask $m \in [0, 1]^{\bar{C}}$

1: $s^p = \sigma(\mathcal{S}(\bar{X}))$ ▷ Learn Sample-Dependent Feature Score
2: $s = \alpha^s \cdot s^p + (1 - \alpha^s) \cdot \bar{s}$ ▷ Final Feature Score
3: $X = m \cdot \bar{X} + (1 - m) \cdot \bar{X}^{fill}$ ▷ Measurement Subsampling with a Mask
4: $\widehat{Y} = \mathcal{T}(s \cdot X)$ ▷ Perform the Task
5: $L = L(\widehat{Y}, Y)$ ▷ Calculate Supervised Loss
6: Backpropagate on L, compute gradients of $\mathcal{S}, \mathcal{T}$ weights, update weights of $\mathcal{S}, \mathcal{T}$

Algorithm 2 JOFSTO Optimization

Input Input Data $\bar{X} \in \mathbb{R}^{n \times \bar{C}}$, Target Data Y, Subsampled Data Fill $\bar{X}^{fill}$, Feature Size Candidates and RFE Steps $\bar{C} = C_1 > ... > C_T$, Training Steps $1 <= E_1 < E_2 < E_3 < E$

1: **for** $t \leftarrow 1$ **do**
2:   $m \leftarrow m_1 \leftarrow [1]^{\bar{C}}, a^s \leftarrow 1$
3:   **for** $e \leftarrow 1, ..., E$ **do**   ▷ Train on Full Information
4:    FPBP()
5:   **end for**
6:   Calculate $\bar{s}^p$ the mean learnt score of s^p across data
7:   $\bar{s}_1 \leftarrow \bar{s}^p$ ▷ First Sample-Independent Score
8: **end for**
9: **for** $t \leftarrow 2, ..., T$ **do**
10:   $\bar{s} \leftarrow \bar{s}_{t-1}, \alpha^s \leftarrow \frac{1}{2}, m \leftarrow m_{t-1}$
11:   **for** $e \leftarrow 1, ..., E_1$ **do**   ▷ Joint Optimization
12:    FPBP()
13:   **end for**
14:   Calculate $\bar{s}^p$ the mean learnt score of s^p across data
15:   $\bar{s}_t \leftarrow \frac{1}{2}(\bar{s}_{t-1} + \bar{s}^p)$ ▷ Sample-Independent Score for step t
16:   **for** $e \leftarrow E_1 + 1, ..., E_2$ **do**
17:    $\alpha^s \leftarrow \max\{\alpha^s - \frac{2}{E_2 - E_1}, 0\}$ ▷ Progressively Set the Score to be Sample-Independent
18:    FPBP()
19:   **end for**
20:   $D_t \leftarrow \arg\min_{C_{t-1} - C_t}\{\bar{s}_t[i] : m_{t-1}[i] = 1\}$ ▷ Features to Subsample
21:   $m_t \leftarrow m_{t-1} - \mathbb{I}_{i \in D}$ ▷ Mask Target
22:   $\alpha^m \leftarrow 1$
23:   **for** $e \leftarrow E_2 + 1, ..., E_3$ **do**
24:    $\alpha^m \leftarrow \max\{\alpha^m - \frac{1}{E_3 - E_2}, 0\}$
25:    $m \leftarrow \alpha^m \cdot m_{t-1} + (1 - \alpha^m) \cdot m_t$ ▷ Progressively Construct the Mask
26:    FPBP()
27:   **end for**
28:   **for** $e \leftarrow E_3 + 1, ..., E$ **do**
29:    FPBP()
30:   **end for**
31:   Cache $T_t, m_t, \bar{s}_t$, then use as $\widehat{Y} = \mathcal{T}_t(X \cdot \bar{s}_t)$ ▷ See figure 1-Test
32: **end for**

B SETTINGS FOR DIFFERENT APPROACHES

This section describes the settings for the different approaches used in this paper.

We used the official code for all baselines when required, following the implementation carefully. For every approach, for fairness, we considered the same number of evaluations on the validation data, to choose the best model to apply to the test data, for each different feature set size C. Data are split in training, validation and test sets, described in section D. We normalize the data following Grussu et al. (2021), which divides each channel/measurement by it's $99th$ percentile value calculated from the training set, the input and output of the neural network are normalized by this value. Other general hyperparameters are batch size 1500, learning rate $1E-4$ ($1E-5$ in section 4.1) and $ADAM$ optimizer, default network weight initialization.

OURS: JOFSTO

We conducted a brief search for the hyperparameters, setting $E_1 = 25$, $E_2 = E_1 + 10$, $E_3 = E_2 + 10$, we do not set E, as like other approaches, we train on $e = E_3, ...$ until early stopping on the validation set. We linearly modify the values of α^s in epochs $e = E_1 + 1, ..., E_2$ and linearly modify m in epochs $e = E_2 + 1, ..., E_3$. The activation function $\sigma = 2 \times sigmoid$, so the feature scores are initialized to approximately 1. The subsampled data fill $\bar{X}^{fill} \in \mathbb{R}^{\bar{C}}$ is the median of the data, across each measurement/channel. These hyperparameters were constant across all experiments. For each experiment we chose C_i to be the subset sizes required for the task e.g. in table 1 we set $C_{1,2,3,4,5} = \bar{C}, \frac{\bar{C}}{2}, \frac{\bar{C}}{4}, \frac{\bar{C}}{8}, \frac{\bar{C}}{16}$.

We perform a grid search to find the optimal network architecture hyperparameters for each task. The Scoring Network $\mathcal{S}$ and Task Network $\mathcal{T}$ have the same number of hidden layers $\in \{1, 2, 3\}$, number of units $\in \{30, 100, 300, 1000, 3000\}$, for each combination we obtain task performance on the feature set sizes $C_1 > C_2 > ....$ The best performing network on the validation set is deployed on the test data.

RANDOM FEATURE SELECTION (FS) + DEEP LEARNING (DL)

For different C we repeat the following process. We randomly select C number of measurements on a fixed random seed and perform grid search on the task network (mapping subsampled data to full data), with number of hidden layers $\in \{1, 2, 3\}$, number of units $\in \{30, 100, 300, 1000, 3000\}$. Training is until early stopping on the validation set. The best trained model is evaluated on the test set.

LEE ET AL. (2022)

This approach has a three-stage procedure and four neural networks to exploit task-performance, self-supervision, additional unlabeled data, and correlated feature subsets. It scores the features then subsequently train a task-based network on subsampled data. We use the official repository Lee (2022). The optimization procedure is split into i) self-supervision phase, ii) supervision phase, iii) training on selected features only.

The self-supervision phase finds the optimal encoder network hyperparameters. We perform grid search, the encoder network, feature vector estimator network, gate vector estimator network, all have same number of hidden layers $\in \{1, 2, 3\}$ number of units, including hidden dimension $\in \{30, 100, 300, 1000, 3000\}$, following Lee et al. (2022)-table-S.1, other hyperparameters $\alpha \in \{0.01, 0.1, 1.0, 10, 100\}$, $\pi \in \{0.2, 0.4, 0.6, 0.8\}$. The self-supervisory dataset is training set X. On the best validation performance (with early stopping), this returns a trained encoder network, cached for the supervision phase.

The supervision phase scores the features. The pre-trained encoder is loaded from the previous phase. We then perform grid search, where the predictor network has number of hidden layers $\in \{1, 2, 3\}$, number of units $\in \{30, 100, 300, 1000, 3000\}$, following table S.1 $\beta \in \{0.01, 0.1, 1.0, 10, 100\}$. On the best validation performance with early stopping, the process returns a score for all features.

The final phase is repeated for different number of features subset sizes C. We extract the C highest scored features from the previous phase and perform grid search on the task network (mapping subsampled data to full data), with number of hidden layers $\in \{1, 2, 3\}$, number of units $\in \{30, 100, 300, 1000, 3000\}$. Training is until early stopping on the validation set. The best trained model is evaluated on the test set.

WOJTAS & CHEN (2020)

This approach has a complicated three-stage procedure and two neural networks that respectively performs the task, and scores masks, where the two networks are trained alternatively. This returns an optimal mask (analogous to m_t in our approach) and trained task-network (analogous to $\mathcal{T}_t$ in our approach). We use the official repository Wojtas (2021). The following process is repeated for different feature subset sizes C.

We perform a grid search to find the optimal hyperparameters. The operator network (analogous to task network $\mathcal{T}$ in this paper) and the selector network have the same number of hidden layers $\in \{1, 2, 3\}$, number of units $\in \{30, 100, 300, 1000, 3000\}$, $s_p = 5$, $E_1 = 15000$. The joint training uses early stopping on the validation set, and returns an optimal feature set size, of size C and a trained operator network. The best performing operator network on the validation set is deployed on the test data.

C   FITTING MRI MODELS AND COMPUTING DOWNSTREAM METRICS (PARAMETER MAPS)

This section provides an outline of the standard MRI model fitting approaches we used in section 4.3. To fit the DTI,DKI,MSDKI MRI models to the data, and obtain the downstream metrics (parameter maps), we employ the widely-used, open-source DIPY library Garyfallidis et al. (2014). We followed standard practice for model fitting in MRI and used the least-squares optimization approach and default fitting settings. To remove outliers, values were clamped where DTI FA $\in [0, 1]$, DTI MD,AD,RD $\in [0, 0.003]$, DKI MK,AK,RK $\in [0, 3]$, MSDKI MSD $\in [0, 0.003]$ MSDKI MSK $\in [0, 3]$.

D   DATA

This section describes the data used in this paper. We provide a summary in table 8. Visualizations of slices are in figure 4.

Table 8: Summary of data.

Name	Type	No. Measurements C	Resolution mm^3	Acquisition Parameter Dimension	Number of voxels (K) Train	Val	Test
MUDI	qMRI scan	1344	2.5	$A \subset \mathbb{R}^6$	321	132	105
HCP	qMRI can	288	1.25	$A \subset \mathbb{R}^4$	2182	774	674
VERDICT	Simulated qMRI	220	-	$A \subset \mathbb{R}^7$	1000	100	100
NODDI-WMC	Simulated qMRI	3612	-	$A \subset \mathbb{R}^7$	100	10	10

VERDICT AND NODDI MRI MODELS SIMULATED DATA

Table 9: Parameter ranges for simulating synthetic VERDICT and NODDI model data,

VERDICT			NODDI		
Parameter	Minimum	Maximum	Parameter	Minimum	Maximum
f_I	0.01	0.99	f_{ic}	0.01	0.99
f_V	0.01	0.99	f_{iso}	0.01	0.99
D_v (μms^2 s^{-1})	3.05	10	ODI	0.01	0.99
R (μm)	0.01	20	$\mathbf{n}$	[-1 -1 -1]	[1 1 1]
$\mathbf{n}$	[-1 -1 -1]	[1 1 1]			

To simulate synthetic data for the VERDICT and NODDI models we use a known, fixed, acquisition scheme in combination with a set of ground truth model parameters. We choose the ground truth model parameters by uniformly sampling parameter combinations from the bounds given in table 9. We choose these bounds as they approximate the physically feasible limits of the parameters.

The VERDICT data has number of samples $n = 1000K, 100K, 100K$ in the train, validation, test split, with target data $Y \in \mathbb{R}^{n \times 8}, \boldsymbol{\theta}_i \in \mathbb{R}^8, i = 1, ..., n$. The classical ED approach yields an acquisition scheme derived from the Fisher information matrix Panagiotaki et al. (2015b) and here $X \in \mathbb{R}^{n \times 20}, C = 20$. The approaches in supervised feature selection use a densely-sampled empirical acquisition scheme, designed specifically for the VERDICT protocol from Panagiotaki et al. (2015a) and here $\bar{X} \in \mathbb{R}^{n \times 220}, \bar{C} = 220$.

The NODDI data has number of samples $n = 100K, 10K, 10K$ in the train,validation,test split, with target data $Y \in \mathbb{R}^{n \times 7}, \boldsymbol{\theta}_i \in \mathbb{R}^7, i = 1, ..., n$. The classical ED approach yields an acquisition scheme derived from the Fisher information matrix Zhang et al. (2012) and so $X \in \mathbb{R}^{n \times 99}, C = 99$. The approaches in supervised feature selection use a densely-sampled empirical acquisition scheme from an extremely rich acquisition from Ferizi et al. (2017). This was designed for the ISBI 2015 White Matter Challenge, which aimed to collect the richest possible data to rank MRI models, and required a single subject to remain motionless for two uncomfortable back-to-back 4h scans. Here $\bar{X} \in \mathbb{R}^{n \times 3612}, \bar{C} = 3612$.

We used Rician noise, as appropriate for MRI data Gudbjartsson & Patz (1995). The signal to noise ratio of the unweighted signal is 50, which is representative of clinical qMRI.

To conduct the simulations we employ the widely-used, open-source dmipy toolbox Fick et al. (2019), and the code for the simulations is anonymously submitted. The results in table 5 are all scaled by: DTI-FA $\times 10^2$, DTI-MD $\times 10^9$, DTI-AD $\times 10^9$, DTI-RD $\times 10^9$, DKI-MK $\times 10^2$, DKI-AK $\times 10^2$, DKI-RK 10^2, MSDKI-MSD $\times 10^9$, MSDKI-MSK $\times 10^2$.

D.1 MUlti-DIffusion (MUDI) Challenge Data

Data used in section 4.2 are images from 5 in-vivo human subjects, and are publicly available MUDI Organizers (2022), and was acquired with the state-of-the-art ZEBRA sequence Hutter et al. (2018). Diffusion-relaxation MRI has a 6D acquisition parameter space $A \subset \mathbb{R}^6$: echo time (TE), inversion time (TI), b-value, and b-vector directions in 3 dimensions: b_x, b_y, b_z. Data has $2.5mm$ isotropic resolution and field-of-view $220 \times 230 \times 140mm$ and resulted in 5 3D bran images with $\bar{C} = 1344$ measurements/channels, which here are unique diffusion- $T2^*$ and $T1$- weighting contrasts. More information is in Hutter et al. (2018); Pizzolato et al. (2020). Each subject has an associated brain mask, after removing outlier voxels resulted in $104520, 110420, 105743, 132470, 105045$ voxels for respective subjects $11, 12, 13, 14, 15$. For the experiment in table 4, we followed the original MUDI challenge Pizzolato et al. (2020) and took subjects $11, 12, 13$ as the training and validation set, and subjects $14, 15$ as the unseen test set, where $90\% - 10\%$ of the training/validation set voxels are respectively, for training and validation.

D.2 Human Connectome Project (HCP) Test Retest Data

In section 4.3 we utilise WU-Minn Human Connectome Project (HCP) diffusion data, which is publicly available at `humanconnectome.org` (Test Retest Data Release, release date: Mar 01, 2017) Essen et al. (2013). The data comprises $\bar{C} = 288$ volumes (i.e. measurements/channels), with 18 $b = 0$ (i.e. non-diffusion weighted) volumes, 90 gradient directions for $b = 1000$ s mm^{-2}, 90 directions for b=2000 s mm^{-2}, and 90 directions for b=3000 s mm^{-2}. We used 3 scans for training $103818\_1, 105923\_1, 111312\_1$, one scan for validation 114823_1 and one scan for testing 115320_1, which produced number of samples $n = 708724 + 791369 + 681650 = 2181743, 774149, 674404$ for the respective splits. We only used voxels inside the provided brain mask and normalized the data voxelwise with a standard technique in MRI, by dividing all measurements by the mean signal in each voxel's $b = 0$ values. Undefined voxels were then removed.

Figure 3: Correlation coefficient between the measurements/features of the data, zero entries correspond to b0-values.

Figure 4: 2D brain slices from 3D MRI scans, for different measurements/features/channels for the MUDI (above) HCP (below) data.