SOLUTION: BYZANTINE CLUSTER-SENDING IN EXPECTED CONSTANT COST AND CONSTANT TIME

Abstract

Traditional resilient systems operate on fully-replicated fault-tolerant clusters, which limits their scalability and performance. One way to make the step towards resilient high-performance systems that can deal with huge workloads is by enabling independent fault-tolerant clusters to efficiently communicate and cooperate with each other, as this also enables the usage of high-performance techniques such as sharding. Recently, such inter-cluster communication was formalized as the *Byzantine cluster-sending problem*. Unfortunately, existing worst-case optimal protocols for cluster-sending all have *linear complexity* in the size of the clusters involved.

In this paper, we propose *probabilistic cluster-sending techniques* as a solution for the cluster-sending problem with only an *expected constant message complexity*, this independent of the size of the clusters involved and this even in the presence of highly unreliable communication. Depending on the robustness of the clusters involved, our techniques require only *two-to-four* message round-trips (without communication failures). Furthermore, our protocols can support worst-case linear communication between clusters. Finally, we have put our techniques to the test in an in-depth experimental evaluation that further underlines the exceptional low expected costs of our techniques in comparison with other protocols. As such, our work provides a strong foundation for the further development of resilient high-performance systems.

1 Introduction

The promises of *resilient data processing*, as provided by private and public blockchains [15, 22, 28], has renewed interest in traditional consensus-based Byzantine fault-tolerant resilient systems [5, 6, 25]. Unfortunately, blockchains and other consensus-based systems typically rely on fully-replicated designs, which limits their scalability and performance. Consequently, these systems cannot deal with the ever-growing requirements in data processing [30, 31].

One way to improve on these limitations is by building complex system designs that consist of *independently-operating* resilient clusters that can cooperate to provide certain services. To illustrate this, one can consider a sharded resilient design. In a traditional resilient systems, resilience is provided by a fully-replicated consensus-based Byzantine fault-tolerant cluster in which all replicas hold all data and process all requests. This traditional design has only limited performance,

even with the best consensus protocols, and lacks scalability. To improve on the design of traditional systems, one can employ the *sharded* design of Figure 1. In this sharded design, each cluster only holds part of the data. Consequently, each cluster only needs to process requests that affect data they hold. In this way, this sharded design improves performance by enabling *parallel processing* of requests by different clusters, while also improving storage scalability. To support *arbitrary general-purpose workloads* that can affect data in several clusters in such a sharded design, the clusters need to be able to *coordinate their operations*, however [1, 7, 16, 19].[1]

Central to such complex system designs is the ability to reliably and efficiently communicate between independently-operating resilient clusters. Recently, this problem of communication *between* Byzantine fault-tolerant clusters has been formalized as the *cluster-sending problem* [18, 20]. We believe that efficient solutions to this problem have a central role towards bridging *resilient* and *high-performance* data processing.

Figure 1: A *sharded* design in which each resilient cluster of four replicas holds only a part of the data. Local decisions within a cluster are made via *consensus* (⟷), whereas multi-shard coordination to process multi-shard transactions requires *cluster-sending* (⟺). This illustration is based on Hellings et al. [20, Figure 1].

Although the cluster-sending problem has received some attention (e.g., as part of the design of AHL [7],

---

[1] Strict ordering as provided by consensus is necessary to support arbitrary general-purpose workloads. There are classes of operations for which strict consensus-based ordering of (sharding) steps is unnecessary, however. Examples include balance changes and, more generally, operations on CRDTs [32].

BYSHARD [19], GEOBFT [16], and CHAINSPACE [1]), and cluster-sending protocols that solve the cluster-sending problem with worst-case optimal complexity are known [18, 20], we believe there is still much room for improvement.

In this paper, we introduce a new solution to the cluster-sending problem: we introduce cluster-sending protocols that use *probabilistic cluster-sending* techniques and are able to provide low *expected-case* message complexity (at the cost of higher communication latencies, a good trade-off in systems where inter-cluster network bandwidth is limited). To simplify presentation, we first show how probabilistic cluster-sending works when communication is reliable and synchronous. Then, we generalize these synchronous solutions to practical environments in which communication can be unreliable and asynchronous. Our main contributions are as follows:

1. First, in Section 3, we introduce the cluster-sending step CS-STEP that attempts to send a value from a replica in the sending cluster to a replica in the receiving cluster in a verifiable manner and with a constant amount of inter-cluster communication. This step is guaranteed to perform cluster-sending if communication is reliable and the step is performed by non-faulty replicas.

2. Then, in Section 4, we illustrate the working of a *basic probabilistic cluster-sending protocol* by introducing the *Synchronous Probabilistic Cluster-Sending protocol* CSP. CSP uses CS-STEP with randomly selected sending and receiving replicas to provide cluster-sending in *expected constant* steps. In addition, we show how *pruned-CSP (CSPP)*, a fine-tuned variant of CSP, can guarantee cluster-sending in *expected constant* steps while also guaranteeing termination.

3. Next, in Section 5, we propose the *Synchronous Probabilistic Linear Cluster-Sending protocol* CSPL. CSPL not only guarantees cluster-sending in *expected constant* steps, but also guarantees a *worst-case optimal* linear upper-bound on communication. To achieve this worst-case optimal upper-bound, we introuce a specialized randomized scheme via which CSPL selects replicas. To prove the complexity bounds of CSPL, we provide an in-depth analysis of the expected behavior of the randomized scheme we introduce.

4. Next, in Section 6, we generalize CSP, CSPP, and CSPL to practical environments in which communication can be *unreliable and asynchronous*.

5. Finally, in Section 7, we evaluate the behavior of the proposed probabilistic cluster-sending protocols via an in-depth evaluation. In this evaluation, we show that probabilistic cluster-sending protocols has exceptionally low communication costs in comparison with existing cluster-sending protocols, this even in the presence of communication failures.

A summary of our findings in comparison with existing techniques can be found in Figure 2. In Section 2, we introduce the necessary terminology and notation, in Section 8, we compare with related work, and in Section 9, we conclude on our findings.

2 The Cluster-Sending Problem

Before we present our probabilistic cluster-sending techniques, we first introduce all necessary terminology and notation. The formal model we use is based on the formalization of the cluster-sending problem provided by Hellings et al. [18, 20]. If S is a set of replicas, then $\mathsf{f}(S) \subseteq S$ denotes the *faulty replicas* in S, whereas $\mathsf{nf}(S) = S \setminus \mathsf{f}(S)$ denotes the *non-faulty replicas* in S. We write $\mathbf{n}_S = |S|$, $\mathbf{f}_S = |\mathsf{f}(S)|$, and $\mathbf{nf}_S = |\mathsf{nf}(S)| = \mathbf{n}_S - \mathbf{f}_S$ to denote the number of replicas, faulty replicas, and non-faulty replicas in S, respectively. A *cluster* $\mathcal{C}$ is a finite set of replicas. We consider clusters with *Byzantine replicas* that behave in arbitrary manners. In specific, if $\mathcal{C}$ is a cluster, then any malicious adversary can control the replicas in $\mathsf{f}(\mathcal{C})$ at any time, but adversaries cannot bring non-faulty replicas under their control.

Definition 2.1. Let $\mathcal{C}_1, \mathcal{C}_2$ be disjoint clusters. The *cluster-sending problem* is the problem of reliably sending a value v from $\mathcal{C}_1$ to $\mathcal{C}_2$ in the presence of failures and malicious behaviour: non-faulty replicas in $\mathcal{C}_2$ can only receive v if the non-faulty replicas in $\mathcal{C}_1$ reached agreement on sending v, and the non-faulty replicas in $\mathcal{C}_1$ receive a confirmation only if the non-faulty replicas in $\mathcal{C}_2$ received v.

We formalize the *cluster-sending problem* of sending a value v from $\mathcal{C}_1$ to $\mathcal{C}_2$ as a progression of replica states as follows:

1. Cluster-sending is initiated when the non-faulty replicas in $\mathcal{C}_1$ reach the state AGREE(v) indicating that the replicas in $\mathcal{C}_1$ have internally decided upon sending v to $\mathcal{C}_2$.

2. Only after all non-faulty replicas in $\mathcal{C}_1$ reach the state AGREE(v), the non-faulty replicas in $\mathcal{C}_2$ can reach the state RECEIVE(v).

3. Only after all non-faulty replicas in $\mathcal{C}_2$ reach the state RECEIVE(v), the replicas in $\mathcal{C}_1$ can reach the state CONFIRM(v).

Cluster-sending is succesfull if all non-faulty replicas in $\mathcal{C}_1$ reach the state CONFIRM(v).

We note that the value v sent by cluster $\mathcal{C}_1$ is a parameter of the cluster-sending problem. Typically, the value v originates from the resilient applications that are running on the clusters

Figure 2: A comparison of *cluster-sending protocols* that send a value from cluster C_1 with $\mathbf{n}_{C_1}$ replicas, of which $\mathbf{f}_{C_1}$ are faulty, to cluster C_2 with $\mathbf{n}_{C_2}$ replicas, of which $\mathbf{f}_{C_2}$ are faulty. For each protocol P, *Protocol* specifies its name; *Robustness* specifies the conditions P puts on the clusters; *Message Steps* specifies the number of messages exchanges P performs; *Optimal* specifies whether P is worst-case optimal; and *Unreliable* specifies whether P can deal with unreliable communication.

	Protocol	Robustness[a]	Message Steps (expected-case)	(worst-case)	Optimal	Unreliable
	PBS-CS [18, 20]	$\min(\mathbf{n}_{C_1}, \mathbf{n}_{C_2}) > \mathbf{f}_{C_1} + \mathbf{f}_{C_2}$	$\mathbf{f}_{C_1} + \mathbf{f}_{C_2} + 1$		✔	✘
	PBS-CS [18, 20]	$\mathbf{n}_{C_1} > 3\mathbf{f}_{C_1}, \mathbf{n}_{C_2} > 3\mathbf{f}_{C_2}$	$\max(\mathbf{n}_{C_1}, \mathbf{n}_{C_2})$		✔	✘
	GEOBFT [16]	$\mathbf{n}_{C_1} = \mathbf{n}_{C_2} > 3\max(\mathbf{f}_{C_1}, \mathbf{f}_{C_2})$	$\mathbf{f}_{C_2} + 1$[b]	$\Omega(\mathbf{f}_{C_1}\mathbf{n}_{C_2})$	✘	✔
	CHAINSPACE [1]	$\mathbf{n}_{C_1} > 3\mathbf{f}_{C_1}, \mathbf{n}_{C_2} > 3\mathbf{f}_{C_2}$	$\mathbf{n}_{C_1}\mathbf{n}_{C_2}$		✘	✘
This Paper	CSPP	$\mathbf{n}_{C_1} > 2\mathbf{f}_{C_1}, \mathbf{n}_{C_2} > 2\mathbf{f}_{C_2}$	4	$(\mathbf{f}_{C_1} + 1)(\mathbf{f}_{C_2} + 1)$	✘	✔
	CSPP	$\mathbf{n}_{C_1} > 3\mathbf{f}_{C_1}, \mathbf{n}_{C_2} > 3\mathbf{f}_{C_2}$	$\frac{9}{4} (= 2\frac{1}{4})$	$(\mathbf{f}_{C_1} + 1)(\mathbf{f}_{C_2} + 1)$	✘	✔
	CSPL	$\min(\mathbf{n}_{C_1}, \mathbf{n}_{C_2}) > \mathbf{f}_{C_1} + \mathbf{f}_{C_2}$	4	$\mathbf{f}_{C_1} + \mathbf{f}_{C_2} + 1$	✔	✔
	CSPL	$\min(\mathbf{n}_{C_1}, \mathbf{n}_{C_2}) > 2(\mathbf{f}_{C_1} + \mathbf{f}_{C_2})$	$\frac{9}{4} (= 2\frac{1}{4})$	$\mathbf{f}_{C_1} + \mathbf{f}_{C_2} + 1$	✔	✔
	CSPL	$\mathbf{n}_{C_1} > 3\mathbf{f}_{C_1}, \mathbf{n}_{C_2} > 3\mathbf{f}_{C_2}$	3	$\max(\mathbf{n}_{C_1}, \mathbf{n}_{C_2})$	✔	✔

[a]Protocols that have different message step complexities depending on the robustness assumptions have been included for each of the robustness assumptions.
[b]Complexity when the coordinating primary in C_1 is non-faulty and communication is reliable.

C_1, e.g., due to the application requiring communication with other clusters and agree upon initiation such communication via an internal consensus step.

We assume that there is no limitation on local communication within a cluster, while global communication between clusters is costly. This model is supported by practice, where communication between wide-area deployments of clusters is up-to-two orders of magnitude more expensive than communication within a cluster [7, 16].

We assume that each cluster can make *local decisions* among all non-faulty replicas, e.g., via a *consensus protocol* such as PBFT (when Byzantine fault tolerance is required) or PAXOS [6, 25] (when crash-fault tolerance suffices). Furthermore, we assume that the replicas in each cluster can certify such local decisions via a *signature scheme*. For example, a cluster C can certify a consensus decision on some message m by collecting a set of signatures for m of $\mathbf{f}_C + 1$ replicas in C, guaranteeing one such signature is from a non-faulty replica (which would only signs values on which consensus is reached). We write $\langle m \rangle_C$ to denote a message m certified by C. To minimize the size of certified messages, one can utilize a threshold signature scheme [33]. To enable decision making and message certification, we assume, for every cluster C, $\mathbf{n}_C > 2\mathbf{f}_C$, a minimal requirement [9, 26]. Lastly, we assume that there is a common source of randomness for all non-faulty replicas in the sending cluster C_1, e.g., via a distributed fault-tolerant random coin [3, 4].

3 The Cluster-Sending Step

As the first step toward a probabilistic cluster-sending protocol, we introduce the *cluster-sending step* that takes as input a value v and a choice of replicas $\mathtt{R}_1 \in C_1$ and $\mathtt{R}_2 \in C_2$, and tries to perform cluster-sending via communication between the pair of replicas $(\mathtt{R}_1, \mathtt{R}_2)$. The design of the cluster-sending step will ensure that cluster-sending succeeds if both $\mathtt{R}_1$ and $\mathtt{R}_2$ are non-faulty, but can detectably fail otherwise. In the following sections, we introduce cluster-sending protocols that *instantiate this cluster-sending step* via one-or-more pairs of replicas $(\mathtt{R}_1, \mathtt{R}_2)$ to ensure that eventually a cluster-sending step succeeds.

If communication is reliable and one knows non-faulty replicas $\mathtt{R}_1 \in \mathsf{nf}(C_1)$ and $\mathtt{R}_2 \in \mathsf{nf}(C_2)$, then cluster-sending a value v from C_1 to C_2 can be done via a straightforward *cluster-sending step*: one can simply instruct $\mathtt{R}_1$ to send v to $\mathtt{R}_2$. When $\mathtt{R}_2$ receives v, it can disperse v locally in C_2. Unfortunately, we do not know which replicas are faulty and which are non-faulty. Furthermore, it is practically impossible to reliably determine which replicas are non-faulty, as non-faulty replicas can appear faulty due to unreliable communication, while faulty replicas can appear well-behaved to most replicas, while interfering with the operations of only some non-faulty replicas.

To deal with faulty replicas when utilizing the above *cluster-sending step*, one needs a sufficient safeguards to detect *failure* of $\mathtt{R}_1$, of $\mathtt{R}_2$, or of the communication between them. To do so, we add receive and confirmation phases to the sketched cluster-sending step. During the *receive phase*, the receiving replica $\mathtt{R}_2$ must construct a proof P that it received and dispersed v locally in C_2 and then send this proof back to $\mathtt{R}_1$. Finally, during the *confirmation phase*, $\mathtt{R}_1$ can utilize P to prove to all other replicas in C_1 that the cluster-sending step was successful. The pseudo-code of this *cluster-sending step protocol* CS-STEP can be found in Figure 3. We have the following:

Proposition 3.1. *Let* C_1, C_2 *be disjoint clusters with* $\mathtt{R}_1 \in C_1$ *and* $\mathtt{R}_2 \in C_2$. *If* C_1 *satisfies the pre-conditions of* CS-STEP($\mathtt{R}_1$, $\mathtt{R}_2$, v), *then execution of* CS-STEP($\mathtt{R}_1$, $\mathtt{R}_2$, v) *satisfies the post-*

Protocol CS-STEP(R_1, R_2, v), with $R_1 \in \mathcal{C}_1$ and $R_2 \in \mathcal{C}_2$:

Pre: Each replica in $\mathsf{nf}(\mathcal{C}_1)$ decided AGREE(v) (and can construct $\langle \mathtt{send} : v,\ \mathcal{C}_2 \rangle_{\mathcal{C}_1}$).

Post: **(i)** If communication is reliable, $R_1 \in \mathsf{nf}(\mathcal{C}_1)$, and $R_2 \in \mathsf{nf}(\mathcal{C}_2)$, then R_2 decides RECEIVE(v). **(ii)** If a replica in $\mathsf{nf}(\mathcal{C}_2)$ decides RECEIVE(w) for any value w, then that must have been preceded by the non-faulty replicas in $\mathcal{C}_1$ deciding AGREE(w). **(iii)** If a non-faulty replica in $\mathsf{nf}(\mathcal{C}_2)$ decides RECEIVE(v), then all replicas in $\mathsf{nf}(\mathcal{C}_2)$ will decides RECEIVE(v) and all replicas in $\mathsf{nf}(\mathcal{C}_1)$ will decide CONFIRM(v) (whenever communication becomes reliable).

The *cluster-sending step* for R_1 and R_2:

1: Instruct R_1 to send $\langle \mathtt{send} : v,\ \mathcal{C}_2 \rangle_{\mathcal{C}_1}$ to R_2.

The *receive role* for $\mathcal{C}_2$:

2: **event** $R_2 \in \mathsf{nf}(\mathcal{C}_2)$ receives message $m := \langle \mathtt{send} : v,\ \mathcal{C}_2 \rangle_{\mathcal{C}_1}$
       from $R_1 \in \mathcal{C}_1$ **do**
3:    **if** R_2 does not have consensus on m **then**
4:       Use *local consensus* on m and construct $\langle \mathtt{proof} : m \rangle_{\mathcal{C}_2}$.
5:       {*Each replica in $\mathsf{nf}(\mathcal{C}_2)$ decides* RECEIVE(v).}
6:    Send $\langle \mathtt{proof} : m \rangle_{\mathcal{C}_2}$ to R_1.

The *confirmation role* for $\mathcal{C}_1$:

7: **event** $R_1 \in \mathsf{nf}(\mathcal{C}_1)$ receives message $m_p := \langle \mathtt{proof} : m \rangle_{\mathcal{C}_2}$
       with $m := \langle \mathtt{send} : v,\ \mathcal{C}_2 \rangle_{\mathcal{C}_1}$ from $R_2 \in \mathcal{C}_2$ **do**
8:    **if** R_1 does not have consensus on m_p **then**
9:       Use *local consensus* on m_p.
10:     {*Each replica in $\mathsf{nf}(\mathcal{C}_1)$ decides* CONFIRM(v).}

Figure 3: The cluster-sending step protocol CS-STEP(R_1, R_2, v). In this protocol, R_1 tries to send v to R_2, which will succeed if both R_1 and R_2 are non-faulty.

conditions and will exchange at most two messages between $\mathcal{C}_1$ and $\mathcal{C}_2$.

Proof. We prove the three post-conditions separately. **(i)** We assume that communication is reliable, $R_1 \in \mathsf{nf}(\mathcal{C}_1)$, and $R_2 \in \mathsf{nf}(\mathcal{C}_2)$. Hence, R_1 sends message $m := \langle \mathtt{send} : v,\ \mathcal{C}_2 \rangle_{\mathcal{C}_1}$ to R_2 (Line 1 of Figure 3). In the receive phase (Lines 2–6 of Figure 3), replica R_2 *receives* message m from R_1. Replica R_2 uses local consensus on m to replicate m among all replicas $\mathcal{C}_2$ and, along the way, to constructs a *proof of receipt* $m_p := \langle \mathtt{proof} : m \rangle_{\mathcal{C}_2}$. As all replicas in $\mathsf{nf}(\mathcal{C}_2)$ participate in this local consensus, all replicas in $\mathsf{nf}(\mathcal{C}_2)$ will decide RECEIVE on v from $\mathcal{C}_1$. Finally, the proof m_p is returned to R_1. In the confirmation phase (Lines 7–10 of Figure 3), replica R_1 receives the proof of receipt m_p. Next, R_1 uses local consensus on m_p to replicate m_p among all replicas in $\mathsf{nf}(\mathcal{C}_1)$, after which all replicas in $\mathsf{nf}(\mathcal{C}_1)$ decide CONFIRM on sending v to $\mathcal{C}_2$

(ii) A replica in $\mathsf{nf}(\mathcal{C}_2)$ only decides RECEIVE on v after consensus is reached on a message $m := \langle \mathtt{send} : v,\ \mathcal{C}_2 \rangle_{\mathcal{C}_1}$ (Line 5 of Figure 3). This message m not only contains the value v, but also the identity of the recipient cluster $\mathcal{C}_2$. Due

to the usage of certificates and the pre-condition, the message m cannot be created without the replicas in $\mathsf{nf}(\mathcal{C}_1)$ deciding AGREE on sending v to $\mathcal{C}_2$.

(iii) A replica in $\mathsf{nf}(\mathcal{C}_1)$ only decides CONFIRM on v after consensus is reached on a *proof of receipt* message $m_p := \langle \mathtt{proof} : m \rangle_{\mathcal{C}_2}$ (Line 10 of Figure 3). This consensus step will complete for all replicas in $\mathcal{C}_1$ whenever communication becomes reliable. Hence, all replicas in $\mathsf{nf}(\mathcal{C}_1)$ will eventually decide CONFIRM on v. Due to the usage of certificates, the message m_p cannot be created without cooperation of the replicas in $\mathsf{nf}(\mathcal{C}_2)$. The replicas in $\mathsf{nf}(\mathcal{C}_2)$ only cooperate in constructing m_p as part of the consensus step of Line 4 of Figure 3. Upon completion of this consensus step, all replicas in $\mathsf{nf}(\mathcal{C}_2)$ will decide RECEIVE on v. □

In the following sections, we show how to use the cluster-sending step in the construction of cluster-sending protocols. In Section 4, we introduce synchronous protocols that provide *expected constant message complexity*. Then, in Section 5, we introduce synchronous protocols that additionally provide *worst-case linear message complexity*, which is optimal. Finally, in Section 6, we show how to extend the presented techniques to asynchronous communication.

4 Probabilistic Cluster-Sending with Random Replica Selection

In the previous section, we introduced CS-STEP, the cluster-sending step protocol that succeeds whenever the participating replicas are non-faulty and communication is reliable. In this section, we introduce a basic probabilistic cluster-sending protocol that utilizes CS-STEP to perform cluster-sending with expected constant costs.

Using CS-STEP, we build a three-step protocol that cluster-sends a value v from $\mathcal{C}_1$ to $\mathcal{C}_2$:

1. First, the replicas in $\mathsf{nf}(\mathcal{C}_1)$ reach agreement and decide AGREE on sending v to $\mathcal{C}_2$.

2. Then, the replicas in $\mathsf{nf}(\mathcal{C}_1)$ perform a *probabilistic cluster-sending step* by electing replicas $R_1 \in \mathcal{C}_1$ and $R_2 \in \mathcal{C}_2$ fully at random, after which CS-STEP(R_1, R_2, v) is executed.

3. Finally, each replica in $\mathsf{nf}(\mathcal{C}_1)$ waits for the completion of CS-STEP(R_1, R_2, v). If the waiting replicas decided CONFIRM on v during this wait, then cluster-sending is successful. Otherwise, we repeat the previous step.

To simplify presentation, we first present the above protocol assuming *synchronous* inter-cluster communication: in this sectiom, we assume that messages sent by non-faulty replicas will be delivered within some known bounded delay. *Synchronous* systems can be modeled by *pulses* [10, 11]:

Protocol $\text{CSP}(\mathcal{C}_1, \mathcal{C}_2, v)$**:**

1: Use *local consensus* on v and construct $\langle\texttt{send}: v,\ \mathcal{C}_2\rangle_{\mathcal{C}_1}$.
2: {*Each replica in* $\text{nf}(\mathcal{C}_1)$ *decides* AGREE *on* v.}
3: **repeat**
4:     Choose replicas $(\text{R}_1, \text{R}_2) \in \mathcal{C}_1 \times \mathcal{C}_2$, fully at random.
5:     CS-STEP($\text{R}_1, \text{R}_2, v$)
6:     Wait *three* global pulses.
7: **until** $\mathcal{C}_1$ reaches consensus on $\langle\texttt{proof}: \langle\texttt{send}: v,\ \mathcal{C}_2\rangle_{\mathcal{C}_1}\rangle_{\mathcal{C}_2}$.

Figure 4: The Synchronous Probabilistic Cluster-Sending protocol $\text{CSP}(\mathcal{C}_1, \mathcal{C}_2, v)$ that cluster-sends a value v from $\mathcal{C}_1$ to $\mathcal{C}_2$.

Definition 4.1. A system is *synchronous* if all inter-cluster communication happens in *pulses* such that every message sent in a pulse will be received in the same pulse.

We refer to Section 6 on how to generalize the results of this section to practical environments with asynchronous and unreliable communication.

The pseudo-code of the resultant *Synchronous Probabilistic Cluster-Sending protocol* CSP can be found in Figure 4. Next, we prove that CSP is correct and has expected-case constant message complexity:

Theorem 4.2. *Let* $\mathcal{C}_1, \mathcal{C}_2$ *be disjoint clusters. If communication is synchronous, then* $\text{CSP}(\mathcal{C}_1, \mathcal{C}_2, v)$ *results in cluster-sending* v *from* $\mathcal{C}_1$ *to* $\mathcal{C}_2$. *The execution performs two local consensus steps in* $\mathcal{C}_1$, *one local consensus step in* $\mathcal{C}_2$, *and is expected to make* $(\mathbf{n}_{\mathcal{C}_1}\mathbf{n}_{\mathcal{C}_2})/(\mathbf{nf}_{\mathcal{C}_1}\mathbf{nf}_{\mathcal{C}_2})$ *cluster-sending steps.*[2]

Proof. Due to Lines 1–2 of Figure 4, $\text{CSP}(\mathcal{C}_1, \mathcal{C}_2, v)$ establishes the pre-conditions for any execution of CS-STEP(R_1, R_2, v) with $\text{R}_1 \in \mathcal{C}_1$ and $\text{R}_2 \in \mathcal{C}_2$. Using the correctness of CS-STEP (Proposition 3.1), we conclude that $\text{CSP}(\mathcal{C}_1, \mathcal{C}_2, v)$ results in cluster-sending v from $\mathcal{C}_1$ to $\mathcal{C}_2$ whenever the replicas $(\text{R}_1, \text{R}_2) \in \mathcal{C}_1 \times \mathcal{C}_2$ chosen at Line 4 of Figure 4 are non-faulty. As the replicas $(\text{R}_1, \text{R}_2) \in \mathcal{C}_1 \times \mathcal{C}_2$ are chosen fully at random, we have probability $p_i = \mathbf{nf}_{\mathcal{C}_i}/\mathbf{n}_{\mathcal{C}_i}$, $i \in \{1, 2\}$, of choosing $\text{R}_i \in \text{nf}(\mathcal{C}_i)$. The probabilities p_1 and p_2 are independent of each other. Consequently, the probability of choosing $(\text{R}_1, \text{R}_2) \in \text{nf}(\mathcal{C}_1) \times \text{nf}(\mathcal{C}_2)$ is $p = p_1 p_2 = (\mathbf{nf}_{\mathcal{C}_1}\mathbf{nf}_{\mathcal{C}_2})/(\mathbf{n}_{\mathcal{C}_1}\mathbf{n}_{\mathcal{C}_2})$. As such, each iteration of the loop at Line 3 of Figure 4 can be modeled as an independent *Bernoulli trial* with probability of success p, and the expected number of iterations of the loop is $p^{-1} = (\mathbf{n}_{\mathcal{C}_1}\mathbf{n}_{\mathcal{C}_2})/(\mathbf{nf}_{\mathcal{C}_1}\mathbf{nf}_{\mathcal{C}_2})$.

Finally, we prove that each local consensus step needs to be performed only once. To do so, we consider the local consensus steps triggered by the loop at Line 3 of Figure 4. These are the local consensus steps at Lines 4 and 9 of Figure 3. The local consensus step at Line 4 can be initiated

---

[2] Throughout this paper, the *number of consensus steps* in the presented cluster-sending protocols refers to the *single* consensus step necessary to reach agreement in the sending cluster on sending a value v and all consensus steps performed in all invocations of CS-STEP by the protocol.

by a faulty replica R_2. After this single local consensus step reaches consensus on message $m := \langle\texttt{send}: v,\ \mathcal{C}_2\rangle_{\mathcal{C}_1}$, each replica in $\text{nf}(\mathcal{C}_2)$ reaches consensus on m, decides RECEIVE on v, and can construct $m_p := \langle\texttt{proof}: m\rangle_{\mathcal{C}_2}$, this independent of the behavior of R_2. Hence, a single local consensus step for m in $\mathcal{C}_2$ suffices, and no replica in $\text{nf}(\mathcal{C}_2)$ will participate in future consensus steps for m. An analogous argument proves that a single local consensus step for m_p in $\mathcal{C}_1$, performed at Line 9 of Figure 3, suffices. $\square$

Remark 4.3. Although Theorem 4.2 indicates local consensus steps in clusters $\mathcal{C}_1$ and $\mathcal{C}_2$, these local consensus steps typically come for *free* as part of the protocol that uses cluster-sending as a building block. To see this, we consider a multi-shard transaction τ processed by clusters $\mathcal{C}_1$ and $\mathcal{C}_2$.

The decision of cluster $\mathcal{C}_1$ to send a value v to cluster $\mathcal{C}_2$ is a consequence of the execution of τ in $\mathcal{C}_1$. Before the replicas in $\mathcal{C}_1$ execute τ, they need to reach consensus on the order in which τ is executed in $\mathcal{C}_1$. As part of this consensus step, the replicas in $\mathcal{C}_1$ can also construct $\langle\texttt{send}: v,\ \mathcal{C}_2\rangle_{\mathcal{C}_1}$ without additional consensus steps. Hence, no consensus step is necessary in $\mathcal{C}_1$ to send value v. Likewise, if value v is received by replicas in $\mathcal{C}_2$ as part of some multi-shard transaction execution protocol, then the replicas in $\mathcal{C}_2$ need to perform their portion of the necessary transaction execution steps to execute τ as a *consequence* of receiving v. To do so, the replicas in $\mathcal{C}_2$ need to reach consensus on the order in which these transaction execution steps are performed. As part of this consensus step, the replicas in $\mathcal{C}_2$ can also constructing a proof of receipt for v.

In typical fault-tolerant clusters, more than half of the replicas are non-faulty (e.g., in synchronous systems with Byzantine failures that use digital signatures, or in systems that only deal with crashes) or more than two-third of the replicas are non-faulty (e.g., asynchronous systems). In these systems, CSP is expected to only performs a few cluster-sending steps:

Corollary 4.4. *Let* $\mathcal{C}_1, \mathcal{C}_2$ *be disjoint clusters. If communication is synchronous, then the expected number of cluster-sending steps performed by* $\text{CSP}(\mathcal{C}_1, \mathcal{C}_2, v)$ *is upper bounded by* 4 *if* $\mathbf{n}_{\mathcal{C}_1} > 2\mathbf{f}_{\mathcal{C}_1}$ *and* $\mathbf{n}_{\mathcal{C}_2} > 2\mathbf{f}_{\mathcal{C}_2}$; *and by* $\frac{9}{4}$ ($= 2\frac{1}{4}$) *if* $\mathbf{n}_{\mathcal{C}_1} > 3\mathbf{f}_{\mathcal{C}_1}$ *and* $\mathbf{n}_{\mathcal{C}_2} > 3\mathbf{f}_{\mathcal{C}_2}$.

In CSP, the replicas $(\text{R}_1, \text{R}_2) \in \mathcal{C}_1 \times \mathcal{C}_2$ are chosen fully at random and *with replacement*, as CSP does not retain any information on *failed* probabilistic steps. In the worst case, this prevents *termination*, as the same pair of replicas can be picked repeatedly. Furthermore, CSP does not prevent the choice of faulty replicas whose failure could be detected. We can easily improve on this, as the *failure* of a probabilistic step provides some information on the chosen replicas. In specific, we have the following technical properties:

Lemma 4.1. *Let* $\mathcal{C}_1, \mathcal{C}_2$ *be disjoint clusters. We assume synchronous communication and assume that each replica in* $\text{nf}(\mathcal{C}_1)$ *decided* AGREE *on sending* v *to* $\mathcal{C}_2$.

1. *Let* $(R_1, R_2) \in C_1 \times C_2$. *If* CS-STEP($R_1$, R_2, v) *fails to cluster-send* v, *then either* $R_1 \in f(C_1)$, $R_2 \in C_2$, *or both.*

2. *Let* $R_1 \in C_1$. *If* CS-STEP(R_1, R_2, v) *fails to cluster-send* v *for* $\mathbf{f}_{C_2} + 1$ *distinct replicas* $R_2 \in C_2$, *then* $R_1 \in f(C_1)$.

3. *Let* $R_2 \in C_2$. *If* CS-STEP(R_1, R_2, v) *fails to cluster-send* v *for* $\mathbf{f}_{C_1} + 1$ *distinct replicas* $R_1 \in C_1$, *then* $R_2 \in f(C_2)$.

Proof. The statement of this Lemma assumes that the pre-conditions for any execution of CS-STEP(R_1, R_2, v) with $R_1 \in C_1$ and $R_2 \in C_2$ are established. Hence, by Proposition 3.1, CS-STEP(R_1, R_2, v) will cluster-send v if $R_1 \in nf(C_1)$ and $R_2 \in nf(C_2)$. If the cluster-sending step fails to cluster-send v, then one of the replicas involved must be faulty, proving the first property. Next, let $R_1 \in C_1$ and consider a set $S \subseteq C_2$ of $\mathbf{n}_S = \mathbf{f}_{C_2} + 1$ replicas such that, for all $R_2 \in S$, CS-STEP(R_1, R_2, v) fails to cluster-send v. Let $S' = S \setminus f(C_2)$ be the non-faulty replicas in S. As $\mathbf{n}_S > \mathbf{f}_{C_2}$, we have $\mathbf{n}_{S'} \geq 1$ and there exists a $R_2' \in S'$. As $R_2' \notin f(C_2)$ and CS-STEP(R_1, R_2', v) fails to cluster-send v, we must have $R_1 \in f(C_1)$ by the first property, proving the second property. An analogous argument proves the third property. $\square$

We can apply the properties of Lemma 4.1 to actively *prune* which replica pairs CSP considers (Line 4 of Figure 4). Notice that pruning via Lemma 4.1(1) simply replaces choosing replica pairs *with replacement*, as done by CSP, by choosing replica pairs *without replacement*, this without further reducing the possible search space. Pruning via Lemma 4.1(2) does reduce the search space, however, as each replica in C_1 will only be paired with a subset of $\mathbf{f}_{C_2} + 1$ replicas in C_2. Likewise, pruning via Lemma 4.1(3) also reduces the search space. We obtain the *Pruned Synchronous Probabilistic Cluster-Sending protocol* (CSPP) by applying all three prune steps to CSP. By construction, Theorem 4.2, and Lemma 4.1, we conclude:

Corollary 4.5. *Let* C_1, C_2 *be disjoint clusters. If communication is synchronous, then* CSPP(C_1, C_2, v) *results in cluster-sending* v *from* C_1 *to* C_2. *The execution performs two local consensus steps in* C_1, *one local consensus step in* C_2, *is expected to make less than* $(\mathbf{n}_{C_1}\mathbf{n}_{C_2})/(\mathbf{nf}_{C_1}\mathbf{nf}_{C_2})$ *cluster-sending steps, and makes worst-case* $(\mathbf{f}_{C_1}+1)(\mathbf{f}_{C_2}+1)$ *cluster-sending steps.*

5 Worst-Case Linear-Time Probabilistic Cluster-Sending

In the previous section, we introduced CSP and CSPP, two probabilistic cluster-sending protocols that can cluster-send a value v from C_1 to C_2 with expected constant cost. Unfortunately, CSP does not guarantee termination, while CSPP has a worst-case *quadratic complexity*. In this section, we improve on this by presenting a probabilistic cluster-sending protocol that has expected constant cost and guarantees termination

with a worst-case *optimal linear complexity* [18,20]. We refer to Table 1 for an overview of the notation used in this section.

Table 1: Overview of the notation used in Section 5.

Notation	Description
P_1, P_2	Permutation of a list of replicas from C_1 and C_2, respectively.
m_1, m_2	Given a pair of lists of replicas (P_1, P_2), the number of faulty replicas in list P_1 and P_2, respectively.
b_1	The number 1-*faulty pairs* in a given pair of lists of replicas (P_1, P_2).
b_2	The number 2-*faulty pairs* in a given pair of lists of replicas (P_1, P_2).
$b_{1,2}$	The number of *both-faulty pairs* in a given pair of lists of replicas (P_1, P_2).
$\mathsf{list}(R)$	A list-representation of the replica set R.
$\mathsf{perms}(S)$	Permutation of list of replicas S.
$S^{:n}$	The first n elements in the list obtained by repeatedly concatenating list S.
$L\|_M$	Tthe list obtained from L by only keeping the values that also appear in list M.
$\mathbb{M}(v, w)$	The number of distinct ways in which two lists of v and w elements, respectively, can be merged together (without shuffling elements from their respective lists).
Φ	A list-pair function.
$\|P_1; P_2\|_{\mathbf{f}}$	The number of faulty positions in (P_1, P_2).
$\mathbb{F}(n, m_1, m_2, k)$	The number of permutations (P_1, P_2) with k faulty positions of two given lists of n replicas of which m_1 and m_2 replicas are faulty, respectively.
$\mathbb{E}(n, m_1, m_2)$	The non-faulty position trials problem with two lists of n replicas of which m_1 and m_2 replicas are faulty, respectively.

To improve on CSP and CSPP, we need to improve the scheme by which we select replica pairs $(R_1, R_2) \in C_1 \times C_2$ that we use in cluster-sending steps. The straightforward manner to guarantee a worst-case *linear complexity* is by using a scheme that can select only up-to-$n = \max(\mathbf{n}_{C_1}, \mathbf{n}_{C_2})$ distinct pairs $(R_1, R_2) \in C_1 \times C_2$. To select n replica pairs from $C_1 \times C_2$, we will proceed in two steps.

1. We generate list S_1 of n replicas taken from C_1 and list S_2 of n replicas taken from C_2.

2. Then, we choose permutations $P_1 \in \mathsf{perms}(S_1)$ and $P_2 \in \mathsf{perms}(S_2)$ fully at random, and interpret each pair $(P_1[i], P_2[i])$. $0 \leq i < n$, as one of the chosen replica pairs.

We use the first step to deal with any differences in the sizes of C_1 and C_2, and we use the second step to introduce sufficient randomness in our protocol to yield a low expected-case message complexity.

Next, we introduce some notations to simplify reasoning about the above list-based scheme. If R is a set of replicas, then $\mathsf{list}(R)$ is the list consisting of the replicas in R placed in a predetermined order (e.g., on increasing replica identifier). If S is a list of replicas, then we write $\mathsf{f}(S)$ to denote the faulty replicas in S and $\mathsf{nf}(S)$ to denote the non-faulty replicas in S, and we write $\mathbf{n}_S = |S|$, $\mathbf{f}_S = |\{i \mid (0 \leq i < \mathbf{n}_S) \wedge S[i] \in \mathsf{f}(S)\}|$, and $\mathbf{nf}_S = \mathbf{n}_S - \mathbf{f}_S$ to denote the number of positions in S with replicas, faulty replicas, and non-faulty replicas, respectively. If (P_1, P_2) is a pair of equal-length lists of $n = |P_1| = |P_2|$ replicas, then we say that the i-th position is a *faulty position* if either $P_1[i] \in \mathsf{f}(P_1)$ or $P_2[i] \in \mathsf{f}(P_2)$. We write $\|P_1; P_2\|_{\mathbf{f}}$ to denote the number of *faulty positions* in (P_1, P_2). As faulty positions can only be constructed out of the $\mathbf{f}_{P_1}$ faulty replicas in P_1 and the $\mathbf{f}_{P_2}$ faulty replicas in P_2, we must have $\max(\mathbf{f}_{P_1}, \mathbf{f}_{P_2}) \leq \|P_1; P_2\|_{\mathbf{f}} \leq \min(n, \mathbf{f}_{P_1} + \mathbf{f}_{P_2})$.

Example 5.1. Consider clusters $\mathcal{C}_1, \mathcal{C}_2$ with

$$S_1 = \mathsf{list}(\mathcal{C}_1) = [\mathsf{R}_{1,1}, \dots, \mathsf{R}_{1,5}], \quad \mathsf{f}(\mathcal{C}_1) = \{\mathsf{R}_{1,1}, \mathsf{R}_{1,2}\};$$
$$S_2 = \mathsf{list}(\mathcal{C}_2) = [\mathsf{R}_{2,1}, \dots, \mathsf{R}_{2,5}], \quad \mathsf{f}(\mathcal{C}_2) = \{\mathsf{R}_{2,1}, \mathsf{R}_{2,2}\}.$$

The set $\mathsf{perms}(S_1) \times \mathsf{perms}(S_2)$ contains $5!^2 = 14400$ list pairs. Now, consider the list pairs $(P_1, P_2), (Q_1, Q_2), (R_1, R_2) \in \mathsf{perms}(S_1) \times \mathsf{perms}(S_2)$ with

$$P_1[\mathsf{R}_{1,1}, \mathsf{R}_{1,5}, \mathsf{R}_{1,2}, \mathsf{R}_{1,4}, \mathsf{R}_{1,3}],$$
$$P_2[\mathsf{R}_{2,1}, \mathsf{R}_{2,3}, \mathsf{R}_{2,2}, \mathsf{R}_{2,5}, \mathsf{R}_{2,4}];$$
$$Q_1[\mathsf{R}_{1,1}, \mathsf{R}_{1,3}, \mathsf{R}_{1,5}, \mathsf{R}_{1,4}, \mathsf{R}_{1,2}],$$
$$Q_2[\mathsf{R}_{2,5}, \mathsf{R}_{2,4}, \mathsf{R}_{2,3}, \mathsf{R}_{2,2}, \mathsf{R}_{2,1}];$$
$$R_1[\mathsf{R}_{1,5}, \mathsf{R}_{1,4}, \mathsf{R}_{1,3}, \mathsf{R}_{1,2}, \mathsf{R}_{1,1}],$$
$$R_2[\mathsf{R}_{2,1}, \mathsf{R}_{2,2}, \mathsf{R}_{2,3}, \mathsf{R}_{2,4}, \mathsf{R}_{2,5}].$$

We have underlined the faulty replicas in each list, and we have $\|P_1; P_2\|_{\mathbf{f}} = 2 = \mathbf{f}_{S_1} = \mathbf{f}_{S_2}$, $\|Q_1; Q_2\|_{\mathbf{f}} = 3$, and $\|R_1; R_2\|_{\mathbf{f}} = 4 = \mathbf{f}_{S_1} + \mathbf{f}_{S_2}$.

In the following, we will use a *list-pair function* Φ to compute the initial list-pair (S_1, S_2) of n replicas taken from $\mathcal{C}_1$ and $\mathcal{C}_2$, respectively. We build a cluster-sending protocol that uses Φ to compute S_1 and S_2, uses randomization to choose n replica pairs from $S_1 \times S_2$, and, finally, performs cluster-sending steps using only these n replica pairs. The pseudo-code of the resultant *Synchronous Probabilistic Linear Cluster-Sending protocol* CSPL can be found in Figure 5. Next, we prove that CSPL is correct and has a worst-case linear message complexity:

Proposition 5.1. *Let $\mathcal{C}_1, \mathcal{C}_2$ be disjoint clusters and let Φ be a list-pair function with $(S_1, S_2) := \Phi(\mathcal{C}_1, \mathcal{C}_2)$ and $n = \mathbf{n}_{S_1} = \mathbf{n}_{S_2}$. If communication is synchronous and $n > \mathbf{f}_{S_1} + \mathbf{f}_{S_2}$, then $\mathrm{CSPL}(\mathcal{C}_1, \mathcal{C}_2, v, \Phi)$ results in cluster-sending v from $\mathcal{C}_1$ to $\mathcal{C}_2$. The execution performs two local consensus steps in $\mathcal{C}_1$, one local consensus step in $\mathcal{C}_2$, and makes worst-case $\mathbf{f}_{S_1} + \mathbf{f}_{S_2} + 1$ cluster-sending steps.*

Protocol $\mathrm{CSPL}(\mathcal{C}_1, \mathcal{C}_2, v, \Phi)$**:**

1: Use *local consensus* on v and construct $\langle \mathtt{send} : v, \mathcal{C}_2 \rangle_{\mathcal{C}_1}$.
2: {*Each replica in* $\mathsf{nf}(\mathcal{C}_1)$ *decides* AGREE *on* v.}
3: Let $(S_1, S_2) := \Phi(\mathcal{C}_1, \mathcal{C}_2)$.
4: Choose $(P_1, P_2) \in \mathsf{perms}(S_1) \times \mathsf{perms}(S_2)$ fully at random.
5: $i := 0$.
6: **repeat**
7:     CS-STEP$(P_1[i], P_2[i], v)$
8:     Wait *three* global pulses.
9:     $i := i + 1$.
10: **until** $\mathcal{C}_1$ reaches consensus on $\langle \mathtt{proof} : \langle \mathtt{send} : v, \mathcal{C}_2 \rangle_{\mathcal{C}_1} \rangle_{\mathcal{C}_2}$.

Figure 5: The Synchronous Probabilistic Linear Cluster-Sending protocol $\mathrm{CSPL}(\mathcal{C}_1, \mathcal{C}_2, v, \Phi)$ that cluster-sends a value v from $\mathcal{C}_1$ to $\mathcal{C}_2$ using list-pair function Φ.

Proof. Due to Lines 1–2 of Figure 5, $\mathrm{CSPL}(\mathcal{C}_1, \mathcal{C}_2, v, \Phi)$ establishes the pre-conditions for any execution of CS-STEP$(\mathsf{R}_1, \mathsf{R}_2, v)$ with $\mathsf{R}_1 \in \mathcal{C}_1$ and $\mathsf{R}_2 \in \mathcal{C}_2$. Now let $(P_1, P_2) \in \mathsf{perms}(S_1) \times \mathsf{perms}(S_2)$, as chosen at Line 4 of Figure 5. As P_i, $i \in \{1, 2\}$, is a permutation of S_i, we have $\mathbf{f}_{P_i} = \mathbf{f}_{S_i}$. Hence, we have $\|P_1; P_2\|_{\mathbf{f}} \leq \mathbf{f}_{S_1} + \mathbf{f}_{S_2}$ and there must exist a position j, $0 \leq j < n$, such that $(P_1[j], P_2[j]) \in \mathsf{nf}(\mathcal{C}_1) \times \mathsf{nf}(\mathcal{C}_2)$. Using the correctness of CS-STEP (Proposition 3.1), we conclude that $\mathrm{CSPL}(\mathcal{C}_1, \mathcal{C}_2, v, \Phi)$ results in cluster-sending v from $\mathcal{C}_1$ to $\mathcal{C}_2$ in at most $\mathbf{f}_{S_1} + \mathbf{f}_{S_2} + 1$ cluster-sending steps. Finally, the bounds on the number of consensus steps follow from an argument analogous to the one in the proof of Theorem 4.2. $\square$

Proposition 5.1 only shows that CSPL will perform cluster-sending when specific conditions are met on the list-pair function. Next, we proceed in two steps to arrive at practical list-pair functions for CSPL that can be used in combination with CSPL to guarantee an expected constant cost. First, in Section 5.1, we study the probabilistic nature of CSPL. Then, in Section 5.2, we propose practical list-pair functions and show that these functions yield instances of CSPL with expected constant message complexity.

5.1 The Expected-Case Complexity of CSPL

The expected-case analysis of CSP and CSPP was rather straightforward, as the sending and receiving replicas used by these protocols are chosen fully at random and independent of each other. Hence, the random choices made by both protocols can be modelled via well-known independent Bernoulli trials (see the proof of Theorem 4.2). In CSPL, the choice of sending and receiving replicas are dependent, as they are chosen from a list of possible replica pairs. As such, the random choices made by CSPL can no longer be modelled via independent Bernoulli trials. Hence, the expected-case analysis of CSPL requires a further analysis of the probabilistic nature of the randomized scheme used by CSPL.

As the first step toward this analysis, we solve the following abstract problem that captures the probabilistic argument at the core of the expected-case complexity of CSPL:

Problem 5.2 (non-faulty position trials)**.** Let S_1 and S_2 be lists of $|S_1| = |S_2| = n$ replicas. Choose permutations $(P_1, P_2) \in \mathsf{perms}(S_1) \times \mathsf{perms}(S_2)$ fully at random. Next, we inspect positions in P_1 and P_2 fully at random (with replacement). The *non-faulty position trials problem* asks how many positions one expects to inspect to find the first non-faulty position.

Let S_1 and S_2 be lists of $|S_1| = |S_2| = n$ replicas. To answer the non-faulty position trials problem, we first look at the combinatorics of *faulty positions* in pairs $(P_1, P_2) \in \mathsf{perms}(S_1) \times \mathsf{perms}(S_2)$. Let $m_1 = \mathbf{f}_{S_1}$ and $m_2 = \mathbf{f}_{S_2}$. By $\mathbb{F}(n, m_1, m_2, k)$, we denote the number of distinct pairs (P_1, P_2) one can construct that have exactly k faulty positions, hence, with $\|P_1; P_2\|_{\mathbf{f}} = k$. As observed, we have $\max(m_1, m_2) \leq \|P_1; P_2\|_{\mathbf{f}} \leq \min(n, m_1 + m_2)$ for any pair (P_1, P_2). Hence, we have $\mathbb{F}(n, m_1, m_2, k) = 0$ for all $k < \max(m_1, m_2)$ and $k > \min(n, m_1 + m_2)$.

Now consider the step-wise construction of any permutation $(P_1, P_2) \in \mathsf{perms}(S_1) \times \mathsf{perms}(S_2)$ with k faulty positions. First, we choose $(P_1[0], P_2[0])$, the pair at position 0, after which we choose pairs for the remaining $n - 1$ positions. For $P_i[0]$, $i \in \{1, 2\}$, we can choose n distinct replicas, of which m_i are faulty. If we pick a non-faulty replica, then the remainder of P_i is constructed out of $n - 1$ replicas, of which m_i are faulty. Otherwise, the remainder of P_i is constructed out of $n - 1$ replicas of which $m_i - 1$ are faulty. If, due to our choice of $(P_1[0], P_2[0])$, the first position is faulty, then only $k - 1$ out of the $n - 1$ remaining positions must be faulty. Otherwise, k out of the $n - 1$ remaining positions must be faulty. Combining this analysis yields four types for the first pair $(P_1[0], P_2[0])$:

1. A *non-faulty pair* $(P_1[0], P_2[0]) \in \mathsf{nf}(P_1) \times \mathsf{nf}(P_2)$. We have $(n - m_1)(n - m_2)$ such pairs, and we have $\mathbb{F}(n - 1, m_1, m_2, k)$ different ways to construct the remainder of P_1 and P_2.

2. A *1-faulty pair* $(P_1[0], P_2[0]) \in \mathsf{f}(P_1) \times \mathsf{nf}(P_2)$. We have $m_1(n - m_2)$ such pairs, and we have $\mathbb{F}(n - 1, m_1 - 1, m_2, k - 1)$ different ways to construct the remainder of P_1 and P_2.

3. A *2-faulty pair* $(P_1[0], P_2[0]) \in \mathsf{nf}(P_1) \times \mathsf{f}(P_2)$. We have $(n - m_1)m_2$ such pairs, and we have $\mathbb{F}(n - 1, m_1, m_2 - 2, k - 1)$ different ways to construct the remainder of P_1 and P_2.

4. A *both-faulty pair* $(P_1[0], P_2[0]) \in \mathsf{f}(P_1) \times \mathsf{f}(P_2)$. We have $m_1 m_2$ such pairs, and we have $\mathbb{F}(n - 1, m_1 - 1, m_2 - 1, k - 1)$ different ways to construct the remainder of P_1 and P_2.

Hence, for all k, $\max(m_1, m_2) \leq k \leq \min(n, m_1 + m_2)$, $\mathbb{F}(n, m_1, m_2, k)$ is recursively defined by:

$$\mathbb{F}(n, m_1, m_2, k) = (n - m_1)(n - m_2)\mathbb{F}(n - 1, m_1, m_2, k)$$
$$\text{(non-faulty pair)}$$
$$+ m_1(n - m_2)\mathbb{F}(n - 1, m_1 - 1, m_2, k - 1)$$
$$\text{(1-faulty pair)}$$
$$+ (n - m_1)m_2\mathbb{F}(n - 1, m_1, m_2 - 1, k - 1)$$
$$\text{(2-faulty pair)}$$
$$+ m_1 m_2 \mathbb{F}(n - 1, m_1 - 1, m_2 - 1, k - 1),$$
$$\text{(both-faulty pair)}$$

and the base case for this recursion is $\mathbb{F}(0, 0, 0, 0) = 1$.

Example 5.3. Reconsider the list pairs (P_1, P_2), (Q_1, Q_2), and (R_1, R_2) from Example 5.1. In (P_1, P_2), we have both-faulty pairs at positions 0 and 2 and non-faulty pairs at positions 1, 3, and 4. In (Q_1, Q_2), we have a 1-faulty pair at position 0, non-faulty pairs at positions 1 and 2, a 2-faulty pair at position 3, and a both-faulty pair at position 4. Finally, in (R_1, R_2), we have 2-faulty pairs at positions 0 and 1, a non-faulty pair at position 2, and 1-faulty pairs at positions 3 and 4.

Using the combinatorics of faulty positions, we formalize an exact solution to the *non-faulty position trials problem*:

Lemma 5.1. *Let S_1 and S_2 be lists of $n = \mathbf{n}_{S_1} = \mathbf{n}_{S_2}$ replicas with $m_1 = \mathbf{f}_{S_1}$ and $m_2 = \mathbf{f}_{S_2}$. If $m_1 + m_2 < n$, then the non-faulty position trials problem $\mathbb{E}(n, m_1, m_2)$ has solution*

$$\frac{1}{n!^2}\left(\sum_{k=\max(m_1, m_2)}^{m_1 + m_2} \frac{n}{n - k}\mathbb{F}(n, m_1, m_2, k)\right).$$

Proof. We have $|\mathsf{perms}(S_1)| = |\mathsf{perms}(S_2)| = n!$. Consequently, we have $|\mathsf{perms}(S_1) \times \mathsf{perms}(S_2)| = n!^2$ and we have probability $1/(n!^2)$ to choose any pair $(P_1, P_2) \in \mathsf{perms}(S_1) \times \mathsf{perms}(S_2)$. Now consider such a pair $(P_1, P_2) \in \mathsf{perms}(S_1) \times \mathsf{perms}(S_2)$. As there are $\|P_1; P_2\|_{\mathbf{f}}$ faulty positions in (P_1, P_2), we have probability $p(P_1, P_2) = (n - \|P_1; P_2\|_{\mathbf{f}})/n$ to inspect a non-faulty position. Notice that $\max(m_1, m_2) \leq \|P_1; P_2\|_{\mathbf{f}} \leq m_1 + m_2 < n$ and, hence, $0 < p(P_1, P_2) \leq 1$. Each of the inspected positions in (P_1, P_2) is chosen fully at random. Hence, each inspection is a *Bernoulli trial* with probability of success $p(P_1, P_2)$, and we expect to inspect a first non-faulty position in the $p(P_1, P_2)^{-1} = n/(n - \|P_1; P_2\|_{\mathbf{f}})$-th attempt. We conclude that the non-faulty position trials problem $\mathbb{E}(n, m_1, m_2)$ has solution

$$\frac{1}{n!^2}\left(\sum_{(P_1, P_2) \in \mathsf{perms}(S_1) \times \mathsf{perms}(S_2)} \frac{n}{n - \|P_1; P_2\|_{\mathbf{f}}}\right).$$

Notice that there are $\mathbb{F}(n, m_1, m_2, k)$ distinct pairs $(P_1, P_2) \in \mathsf{perms}(S_1) \times \mathsf{perms}(S_2)$ with $\|P_1'; P_2'\|_{\mathbf{f}} = k$ for each k, $\max(m_1, m_2) \leq k \leq m_1 + m_2 < n$. Hence, in the above expression for $\mathbb{E}(n, m_1, m_2)$, we can group on these pairs (P_1', P_2') to obtain the searched-for solution. $\square$

To further solve the non-faulty position trials problem, we work towards a *closed form* for $\mathbb{F}(n, m_1, m_2, k)$. Consider any pair $(P_1, P_2) \in \text{perms}(S_1) \times \text{perms}(S_2)$ with $\|P_1; P_2\|_{\mathbf{f}} = k$ obtained via the outlined step-wise construction. Let b_1 be the number of 1-*faulty pairs*, let b_2 be the number of 2-*faulty pairs*, and let $b_{1,2}$ be the number of *both-faulty pairs* in (P_1, P_2). By construction, we must have $k = b_1 + b_2 + b_{1,2}$, $m_1 = b_1 + b_{1,2}$, and $m_2 = b_2 + b_{1,2}$ and by rearranging terms, we can derive

$$b_{1,2} = (m_1 + m_2) - k, \quad b_1 = k - m_2, \quad b_2 = k - m_1.$$

Example 5.4. Consider

$$\begin{aligned} S_1 &= [\text{R}_{1,1}, \ldots, \text{R}_{1,5}], & \mathbf{f}(S_1) &= \{\text{R}_{1,1}, \text{R}_{1,2}, \text{R}_{1,3}\}; \\ S_2 &= [\text{R}_{2,1}, \ldots, \text{R}_{2,5}], & \mathbf{f}(S_2) &= \{\text{R}_{2,1}\}. \end{aligned}$$

Hence, we have $n = 5$, $m_1 = \mathbf{f}_{S_1} = 3$, and $m_2 = \mathbf{f}_{S_2} = 1$. If we want to create a pair $(P_1, P_2) \in \text{perms}(S_1) \times \text{perms}(S_2)$ with $k = \|P_1; P_2\|_{\mathbf{f}} = 3$ faulty positions, then (P_1, P_2) must have two non-faulty pairs, two 1-faulty pairs, no 2-faulty pairs, and one both-faulty pair. Hence, we have $n - k = 2$, $b_1 = 2$, $b_2 = 0$, and $b_{1,2} = 1$.

The above analysis only depends on the choice of m_1, m_2, and k, and not on our choice of (P_1, P_2). Next, we use this analysis to express $\mathbb{F}(n, m_1, m_2, k)$ in terms of the number of distinct ways in which one can *construct*

(A) lists of b_1 1-faulty pairs out of faulty replicas from S_1 and non-faulty replicas from S_2,

(B) lists of b_2 2-faulty pairs out of non-faulty replicas from S_1 and faulty replicas from S_2,

(C) lists of $b_{1,2}$ both-faulty pairs out of the remaining faulty replicas in S_1 and S_2 that are not used in the previous two cases, and

(D) lists of $n - k$ non-faulty pairs out of the remaining (non-faulty) replicas in S_1 and S_2 that are not used in the previous three cases;

and in terms of the number of distinct ways one can *merge* these lists. As the first step, we look at how many distinct ways we can merge two lists together:

Lemma 5.2. *For any two disjoint lists S and T with $|S| = v$ and $|T| = w$, there exist $\mathbb{M}(v, w) = (v + w)!/(v!w!)$ distinct lists L with $L|_S = S$ and $L|_T = T$, in which $L|_M$, $M \in \{S, T\}$, is the list obtained from L by only keeping the values that also appear in list M.*

Next, we look at the number of distinct ways in which one can construct lists of type A, B, C, and D. Consider the construction of a list of type A. We can choose $\binom{m_1}{b_1}$ distinct sets of b_1 faulty replicas from S_1 and we can choose $\binom{n - m_2}{b_1}$ distinct sets of b_1 non-faulty replicas from S_2. As we

can order the chosen values from S_1 and S_2 in $b_1!$ distinct ways, we can construct $b_1!^2 \binom{m_1}{b_1} \binom{n - m_2}{b_1}$ distinct lists of type A. Likewise, we can construct $b_2!^2 \binom{n - m_1}{b_2} \binom{m_2}{b_2}$ distinct lists of type B.

Example 5.5. We continue from the setting of Example 5.4: we want to create a pair $(P_1, P_2) \in \text{perms}(S_1) \times \text{perms}(S_2)$ with $k = \|P_1; P_2\|_{\mathbf{f}} = 3$ faulty positions. To create (P_1, P_2), we need to create $b_1 = 2$ pairs that are 1-faulty. We have $\binom{m_1}{b_1} = \binom{3}{2} = 3$ sets of two faulty replicas in S_1 that we can choose, namely the sets $\{\text{R}_{1,1}, \text{R}_{1,2}\}$, $\{\text{R}_{1,1}, \text{R}_{1,3}\}$, and $\{\text{R}_{1,2}, \text{R}_{1,3}\}$. Likewise, we have $\binom{n - m_2}{b_1} = \binom{4}{2} = 6$ sets of two non-faulty replicas in S_2 that we can choose. Assume we choose $T_1 = \{\text{R}_{1,1}, \text{R}_{1,3}\}$ from S_1 and $T_2 = \{\text{R}_{2,4}, \text{R}_{2,5}\}$ from S_2. The two replicas in T_1 can be ordered in $\mathbf{n}_{T_1}! = 2! = 2$ ways, namely $[\text{R}_{1,1}, \text{R}_{1,3}]$ and $[\text{R}_{1,3}, \text{R}_{1,1}]$. Likewise, the two replicas in T_2 can be ordered in $\mathbf{n}_{T_2}! = 2! = 2$ ways. Hence, we can construct $2 \cdot 2 = 4$ distinct lists of type A out of this single choice for T_1 and T_2, and the sequences S_1 and S_2 provide us with $\binom{m_1}{b_1} \binom{n - m_2}{b_1} = 18$ distinct choices for T_1 and T_2. We conclude that we can construct 72 distinct lists of type A from S_1 and S_2.

By construction, lists of type A and type B cannot utilize the same replicas from S_1 or S_2. After choosing $b_1 + b_2$ replicas in S_1 and S_2 for the construction of lists of type A and B, the remaining $b_{1,2}$ faulty replicas in S_1 and S_2 are all used for constructing lists of type C. As we can order these remaining values from S_1 and S_2 in $b_{1,2}!$ distinct ways, we can construct $b_{1,2}!^2$ distinct lists of type C (per choice of lists of type A and B). Likewise, the remaining $n - k$ non-faulty replicas in S_1 and S_2 are all used for constructing lists of type D, and we can construct $(n - k)!^2$ distinct lists of type D (per choice of lists of type A and B).

As the final steps, we merge lists of type A and B into lists of type AB. We can do so in $\mathbb{M}(b_1, b_2)$ ways and the resultant lists have size $b_1 + b_2$. Next, we merge lists of type AB and C into lists of type ABC. We can do so in $\mathbb{M}(b_1 + b_2, b_{1,2})$ ways and the resultant lists have size k. Finally, we merge list of type ABC and D together, which we can do in $\mathbb{M}(k, n - k)$ ways. From this construction, we derive that $\mathbb{F}(n, m_1, m_2, k)$ is equivalent to

$$b_1!^2 \binom{m_1}{b_1} \binom{n - m_2}{b_1} b_2!^2 \binom{n - m_1}{b_2} \binom{m_2}{b_2} \cdot$$
$$\mathbb{M}(b_1, b_2) b_{1,2}!^2 \mathbb{M}(b_1 + b_2, b_{1,2})(n - k)!^2 \mathbb{M}(k, n - k),$$

which can be simplified to the following (see Appendix B):

Lemma 5.3. *Let $\max(m_1, m_2) \le k \le \min(n, m_1 + m_2)$ and let $b_1 = k - m_2$, $b_2 = k - m_1$, and $b_{1,2} = (m_1 + m_2) - k$. We have*

$$\mathbb{F}(n, m_1, m_2, k) = \frac{m_1! m_2! (n - m_1)! (n - m_2)! n!}{b_1! b_2! b_{1,2}! (n - k)!}.$$

Proof. We write $f(n,m_1,m_2,k)$ for the closed form in the statement of this lemma and we prove the statement of this lemma by induction. First, the base case $\mathbb{F}(0,0,0,0)$. In this case, we have $n = m_1 = m_2 = k = 0$ and, hence, $b_1 = b_2 = b_{1,2} = 0$, and we conclude $f(0,0,0,0) = 1 = \mathbb{F}(0,0,0,0)$.

Now assume $\mathbb{F}(n',m_1',m_2',k') = f(n',m_1',m_2',k')$ for all $n' < n$ and all k' with $\max(m_1',m_2') \leq k' \leq \min(n',m_1' + m_2')$. Next, we prove $\mathbb{F}(n,m_1,m_2,k) = f(n,m_1,m_2,k)$ with $\max(m_1,m_2) \leq k \leq \min(n,m_1 + m_2)$. We use the shorthand $\mathbb{G} = \mathbb{F}(n,m_1,m_2,k)$ and we have

$$\mathbb{G} = (n-m_1)(n-m_2)\mathbb{F}(n-1,m_1,m_2,k)$$
$$\text{(non-faulty pair)}$$
$$+ m_1(n-m_2)\mathbb{F}(n-1,m_1-1,m_2,k-1)$$
$$\text{(1-faulty pair)}$$
$$+ (n-m_1)m_2\mathbb{F}(n-1,m_1,m_2-1,k-1)$$
$$\text{(2-faulty pair)}$$
$$+ m_1 m_2 \mathbb{F}(n-1,m_1-1,m_2-1,k-1).$$
$$\text{(both-faulty pair)}$$

Notice that if $n = k$, then the non-faulty pair case does not apply, as $\mathbb{F}(n-1,m_1,m_2,k) = 0$, and evaluates to zero. Likewise, if $b_1 = 0$, then the 1-faulty pair case does not apply, as $\mathbb{F}(n-1,m_1-1,m_2,k-1) = 0$, and evaluates to zero; if $b_2 = 0$, then the 2-faulty pair case does not apply, as $\mathbb{F}(n-1,m_1,m_2-1,k-1) = 0$, and evaluates to zero; and, finally, if $b_{1,2} = 0$, then the both-faulty pair case does not apply, as $\mathbb{F}(n-1,m_1-1,m_2-1,k-1) = 0$, and evaluates to zero.

First, we consider the case in which $n > k$, $b_1 > 0$, $b_2 > 0$, and $b_{1,2} > 0$. Hence, each of the four cases apply and evaluate to non-zero values. We directly apply the induction hypothesis on $\mathbb{F}(n-1,m_1,m_2,k)$, $\mathbb{F}(n-1,m_1-1,m_2,k-1)$, $\mathbb{F}(n-1,m_1,m_2-1,k-1)$, and $\mathbb{F}(n-1,m_1-1,m_2-1,k-1)$, and obtain

$$\mathbb{G} = (n-m_1)(n-m_2) \cdot$$
$$\frac{m_1!m_2!(n-1-m_1)!(n-1-m_2)!(n-1)!}{b_1!b_2!b_{1,2}!(n-1-k)!}$$
$$+ m_1(n-m_2) \cdot$$
$$\frac{(m_1-1)!m_2!(n-m_1)!(n-1-m_2)!(n-1)!}{(b_1-1)!b_2!b_{1,2}!(n-1-(k-1))!}$$
$$+ (n-m_1)m_2 \cdot$$
$$\frac{m_1!(m_2-1)!(n-1-m_1)!(n-m_2)!(n-1)!}{b_1!(b_2-1)!b_{1,2}!(n-1-(k-1))!}$$
$$+ m_1 m_2 \cdot$$
$$\frac{(m_1-1)!(m_2-1)!(n-m_1)!(n-m_2)!(n-1)!}{b_1!b_2!(b_{1,2}-1)!(n-1-(k-1))!}.$$

We apply $x! = x(x-1)!$ and further simplify and obtain

$$\mathbb{G} = \frac{m_1!m_2!(n-m_1)!(n-m_2)!(n-1)!}{b_1!b_2!b_{1,2}!(n-1-k)!}$$
$$+ \frac{m_1!m_2!(n-m_1)!(n-m_2)!(n-1)!}{(b_1-1)!b_2!b_{1,2}!(n-k)!}$$
$$+ \frac{m_1!m_2!(n-m_1)!(n-m_2)!(n-1)!}{b_1!(b_2-1)!b_{1,2}!(n-k)!}$$
$$+ \frac{m_1!m_2!(n-m_1)!(n-m_2)!(n-1)!}{b_1!b_2!(b_{1,2}-1)!(n-k)!}$$
$$= (n-k)\frac{m_1!m_2!(n-m_1)!(n-m_2)!(n-1)!}{b_1!b_2!b_{1,2}!(n-k)!}$$
$$+ b_1\frac{m_1!m_2!(n-m_1)!(n-m_2)!(n-1)!}{b_1!b_2!b_{1,2}!(n-k)!}$$
$$+ b_2\frac{m_1!m_2!(n-m_1)!(n-m_2)!(n-1)!}{b_1!b_2!b_{1,2}!(n-k)!}$$
$$+ b_{1,2}\frac{m-1!m_2!(n-m_1)!(n-m_2)!(n-1)!}{b_1!b_2!b_{1,2}!(n-k)!}.$$

We have $k = b_1 + b_2 + b_{1,2}$ and, hence, $n = (n-k) + b_1 + b_2 + b_{1,2}$ and we conclude

$$\mathbb{G} = ((n-k) + b_1 + b_2 + b_{1,2}) \cdot$$
$$\frac{m_1!m_2!(n-m_1)!(n-m_2)!(n-1)!}{b_1!b_2!b_{1,2}!(n-k)!}$$
$$= n\frac{m_1!m_2!(n-m_1)!(n-m_2)!(n-1)!}{b_1!b_2!b_{1,2}!(n-k)!}$$
$$= \frac{m_1!m_2!(n-m_1)!(n-m_2)!n!}{b_1!b_2!b_{1,2}!(n-k)!}.$$

Next, in all other cases, we can repeat the above derivation while removing the terms corresponding to the cases that evaluate to 0. By doing so, we end up with the expression

$$\mathbb{G} = \frac{((\sum_{t \in T} t)m_1!m_2!(n-m_1)!(n-m_2)!(n-1)!}{b_1!b_2!b_{1,2}!(n-k)!}.$$

in which T contains the term $(n-k)$ if $n > k$ (the non-faulty pair case applies), the term b_1 if $b_1 > 0$ (the 1-faulty case applies), the term b_2 if $b_2 > 0$ (the 2-faulty case applies), and the term $b_{1,2}$ if $b_{1,2} > 0$ (the both-faulty case applies). As each term $(n-k)$, b_1, b_2, and $b_{1,2}$ is in T whenever the term is non-zero, we have $\sum_{t \in T} t = (n-k) + b_1 + b_2 + b_{1,2} = n$. Hence, we can repeat the steps of the above derivation in all cases, and complete the proof. $\square$

We combine Lemma 5.1 and Lemma 5.3 to conclude

Proposition 5.2. *Let S_1 and S_2 be lists of $n = \mathbf{n}_{S_1} = \mathbf{n}_{S_2}$ replicas with $m_1 = \mathbf{f}_{S_1}$, $m_2 = \mathbf{f}_{S_2}$, $b_1 = k - m_2$, $b_2 = k - m_1$, and $b_{1,2} = (m_1 + m_2) - k$. If $m_1 + m_2 < n$, then the non-faulty*

position trials problem $\mathbb{E}(n, m_1, m_2)$ *has solution*

$$\frac{1}{n!^2}\left(\sum_{k=\max(m_1,m_2)}^{m_1+m_2}\frac{n}{n-k}\frac{m_1!m_2!(n-m_1)!(n-m_2)!n!}{b_1!b_2!b_{1,2}!(n-k)!}\right).$$

Finally, we use Proposition 5.2 to derive

Proposition 5.3. *Let* C_1, C_2 *be disjoint clusters and let* Φ *be a list-pair function with* $(S_1, S_2) := \Phi(C_1, C_2)$ *and* $n = \mathbf{n}_{S_1} = \mathbf{n}_{S_2}$. *If communication is synchronous and* $\mathbf{f}_{S_1} + \mathbf{f}_{S_2} < n$, *then the expected number of cluster-sending steps performed by* CSPL(C_1, C_2, v, Φ) *is less than* $\mathbb{E}(n, \mathbf{f}_{S_1}, \mathbf{f}_{S_2})$.

Proof. Let $(P_1, P_2) \in \mathsf{perms}(S_1) \times \mathsf{perms}(S_2)$. We notice that CSPL inspects positions in P_1 and P_2 in a different way than the non-faulty trials problem: at Line 7 of Figure 5, positions are inspected one-by-one in a predetermined order and not fully at random (with replacement). Next, we will argue that $\mathbb{E}(n, \mathbf{f}_{S_1}, \mathbf{f}_{S_2})$ provides an upper bound on the expected number of cluster-sending steps regardless of these differences. Without loss of generality, we assume that S_1 and S_2 each have n distinct replicas. Consequently, the pair (P_1, P_2) represents a set R of n distinct replica pairs taken from $C_1 \times C_2$. We notice that each of the $n!$ permutations of R is represented by a single pair $(P_1', P_2') \in \mathsf{perms}(S_1) \times \mathsf{perms}(S_2)$.

Now consider the selection of positions in (P_1, P_2) fully at random, but without replacement. This process will yield a list $[j_0, \ldots, j_{n-1}] \in \mathsf{perms}([0, \ldots, n-1])$ of positions fully at random. Let $Q_i = [P_i[j_0], \ldots, P_i[j_{n-1}]]$, $i \in \{1, 2\}$. We notice that the pair (Q_1, Q_2) also represents R and we have $(Q_1, Q_2) \in \mathsf{perms}(S_1) \times \mathsf{perms}(S_2)$. Hence, by choosing a pair $(P_1, P_2) \in \mathsf{perms}(S_1) \times \mathsf{perms}(S_2)$, we choose set R fully at random and, at the same time, we choose the order in which replica pairs in R are inspected fully at random.

Finally, we note that CSPL inspects positions without replacement. As the number of expected positions inspected in the non-faulty position trials problem decreases if we choose positions without replacement, we have proven that $\mathbb{E}(n, \mathbf{f}_{S_1}, \mathbf{f}_{S_2})$ is an upper bound on the expected number of cluster-sending steps. $\square$

5.2 Practical Instances of CSPL

As the last step in providing practical instances of CSPL, we need to provide practical list-pair functions to be used in conjunction with CSPL. We provide two such functions that address most practical environments. Let C_1, C_2 be disjoint clusters, let $n_{\min} = \min(\mathbf{n}_{C_1}, \mathbf{n}_{C_2})$, and let $n_{\max} = \max(\mathbf{n}_{C_1}, \mathbf{n}_{C_2})$. We provide list-pair functions

$$\Phi_{\min}(C_1, C_2) \mapsto (\mathsf{list}(C_1)^{:n_{\min}}, \mathsf{list}(C_2)^{:n_{\min}}),$$
$$\Phi_{\max}(C_1, C_2) \mapsto (\mathsf{list}(C_1)^{:n_{\max}}, \mathsf{list}(C_2)^{:n_{\max}}),$$

in which $L^{:n}$ denotes the first n values in the list obtained by repeating list L. Next, we illustrate usage of these functions:

Example 5.6. Consider clusters C_1, C_2 with

$$S_1 = \mathsf{list}(C_1) = [\mathsf{R}_{1,1}, \ldots, \mathsf{R}_{1,9}];$$
$$S_2 = \mathsf{list}(C_2) = [\mathsf{R}_{2,1}, \ldots, \mathsf{R}_{2,4}].$$

We have

$$\Phi_{\min}(C_1, C_2) = ([\mathsf{R}_{1,1}, \ldots, \mathsf{R}_{1,4}], \mathsf{list}(C_2));$$
$$\Phi_{\max}(C_1, C_2) = (\mathsf{list}(C_1), [\mathsf{R}_{2,1}, \ldots, \mathsf{R}_{2,4}, \mathsf{R}_{2,1}, \ldots, \mathsf{R}_{2,4}, \mathsf{R}_{2,1}]).$$

Next, we combine $\Phi_{\min}$ and $\Phi_{\max}$ with CSPL, show that in practical environments $\Phi_{\min}$ and $\Phi_{\max}$ satisfy the requirements put on list-pair functions in Proposition 5.1 to guarantee termination and cluster-sending, and use these results to determine the expected constant complexity of the resulting instances of CSPL.

Theorem 5.7. *Let* C_1, C_2 *be disjoint clusters with synchronous communication.*

1. *If* $n = \min(\mathbf{n}_{C_1}, \mathbf{n}_{C_2}) > 2\max(\mathbf{f}_{C_1}, \mathbf{f}_{C_2})$, *then the expected number of cluster-sending steps performed by* CSPL$(C_1, C_2, v, \Phi_{\min})$ *is upper bounded by* 4. *For every* $(S_1, S_2) := \Phi_{\min}(C_1, C_2)$, *we have* $n = \mathbf{n}_{S_1} = \mathbf{n}_{S_2}$, $n > 2\mathbf{f}_{S_1}$, $n > 2\mathbf{f}_{S_2}$, *and* $n > \mathbf{f}_{S_1} + \mathbf{f}_{S_2}$

2. *If* $n = \min(\mathbf{n}_{C_1}, \mathbf{n}_{C_2}) > 3\max(\mathbf{f}_{C_1}, \mathbf{f}_{C_2})$, *then the expected number of cluster-sending steps performed by* CSPL$(C_1, C_2, v, \Phi_{\min})$ *is upper bounded by* $\frac{9}{4}$ $(= 2\frac{1}{4})$. *For every* $(S_1, S_2) := \Phi_{\min}(C_1, C_2)$, *we have* $n = \mathbf{n}_{S_1} = \mathbf{n}_{S_2}$, $n > 3\mathbf{f}_{S_1}$, $n > 3\mathbf{f}_{S_2}$, *and* $n > \mathbf{f}_{S_1} + \mathbf{f}_{S_2}$.

3. *If* $\mathbf{n}_{C_1} > 3\mathbf{f}_{C_1}$ *and* $\mathbf{n}_{C_2} > 3\mathbf{f}_{C_2}$, *then the expected number of cluster-sending steps performed by* CSPL$(C_1, C_2, v, \Phi_{\max})$ *is upper bounded by* 3. *For every* $(S_1, S_2) := \Phi_{\max}(C_1, C_2)$, *we have* $n = \mathbf{n}_{S_1} = \mathbf{n}_{S_2} = \max(\mathbf{n}_{C_1}, \mathbf{n}_{C_2}) > \mathbf{f}_{S_1} + \mathbf{f}_{S_2}$ *and either we have* $\mathbf{n}_{C_1} \geq \mathbf{n}_{C_2}$, $n > 3\mathbf{f}_{S_1}$, *and* $n > 2\mathbf{f}_{S_2}$; *or we have* $\mathbf{n}_{C_2} \geq \mathbf{n}_{C_1}$, $n > 2\mathbf{f}_{S_1}$, *and* $n > 3\mathbf{f}_{S_2}$.

Each of these instance of CSPL *results in cluster-sending* v *from* C_1 *to* C_2.

Proof. First, we prove the properties of $\Phi_{\min}$ and $\Phi_{\max}$ claimed in the three statements of the theorem. In the first and second statement of the theorem, we have $\min(\mathbf{n}_{C_1}, \mathbf{n}_{C_2}) > c\max(\mathbf{f}_{C_1}, \mathbf{f}_{C_2})$, $c \in \{2, 3\}$. Let $(S_1, S_2) := \Phi_{\min}(C_1, C_2)$ and $n = \mathbf{n}_{S_1} = \mathbf{n}_{S_2}$. By definition of $\Phi_{\min}$, we have $n = \min(\mathbf{n}_{C_1}, \mathbf{n}_{C_2})$, in which case S_i, $i \in \{1, 2\}$, holds n distinct replicas from C_i. Hence, we have $\mathbf{f}_{C_i} \geq \mathbf{f}_{S_i}$ and, as $n > c\max(\mathbf{f}_{C_1}, \mathbf{f}_{C_2}) \geq c\mathbf{f}_{C_i}$, also $n > c\mathbf{f}_{S_i}$. Finally, as $n > 2\mathbf{f}_{S_1}$ and $n > 2\mathbf{f}_{S_2}$, also $2n > 2\mathbf{f}_{S_1} + 2\mathbf{f}_{S_2}$ and $n > \mathbf{f}_{S_1} + \mathbf{f}_{S_2}$ holds.

In the last statement of the theorem, we have $\mathbf{n}_{C_1} > 3\mathbf{f}_{C_1}$ and $\mathbf{n}_{C_2} > 3\mathbf{f}_{C_2}$. Without loss of generality, we assume $\mathbf{n}_{C_1} \geq \mathbf{n}_{C_2}$. Let $(S_1, S_2) := \Phi_{\max}(C_1, C_2)$ and $n = \mathbf{n}_{S_1} = \mathbf{n}_{S_2}$. By definition of $\Phi_{\max}$, we have $n = \max(\mathbf{n}_{C_1}, \mathbf{n}_{C_2}) = \mathbf{n}_{C_1}$. As $n = \mathbf{n}_{C_1}$, we have $S_1 = \mathsf{list}(C_1)$. Consequently, we also have

$\mathbf{f}_{S_1} = \mathbf{f}_{C_1}$ and, hence, $\mathbf{n}_{S_1} > 3\mathbf{f}_{C_1}$. Next, we will show that $\mathbf{n}_{S_2} > 2\mathbf{f}_{S_2}$. Let $q = \mathbf{n}_{C_1}$ div $\mathbf{n}_{C_2}$ and $r = \mathbf{n}_{C_1}$ mod $\mathbf{n}_{C_2}$. We note that $\mathsf{list}(C_2)^{:n}$ contains q full copies of $\mathsf{list}(C_2)$ and one partial copy of $\mathsf{list}(C_2)$. Let $T \subset C_2$ be the set of replicas in this partial copy. By construction, we have $\mathbf{n}_{S_2} = q\mathbf{n}_{C_2} + r > q3\mathbf{f}_{C_2} + \mathbf{f}_T + \mathbf{n}\mathbf{f}_T$ and $\mathbf{f}_{S_2} = q\mathbf{f}_{C_2} + \mathbf{f}_T$ with $\mathbf{f}_T \leq \min(\mathbf{f}_{C_2}, r)$. As $q > 1$ and $\mathbf{f}_{C_2} \geq \mathbf{f}_T$, we have $q\mathbf{f}_{C_2} \geq \mathbf{f}_{C_2} \geq \mathbf{f}_T$. Hence, $\mathbf{n}_{S_2} > 3q\mathbf{f}_{C_2} + \mathbf{f}_T + \mathbf{n}\mathbf{f}_T > 2q\mathbf{f}_{C_2} + \mathbf{f}_{C_2} + \mathbf{f}_T + \mathbf{n}\mathbf{f}_T \geq 2(q\mathbf{f}_{C_2} + \mathbf{f}_T) + \mathbf{n}\mathbf{f}_T \geq 2\mathbf{f}_{S_2}$. Finally, as $n > 3\mathbf{f}_{S_1}$ and $n > 2\mathbf{f}_{S_2}$, also $2n > 3\mathbf{f}_{S_1} + 2\mathbf{f}_{S_2}$ and $n > \mathbf{f}_{S_1} + \mathbf{f}_{S_2}$ holds.

Now, we prove the upper bounds on the expected number of cluster-sending steps for $\mathsf{CSPL}(C_1, C_2, v, \Phi_{\min})$ with $\min(\mathbf{n}_{C_1}, \mathbf{n}_{C_2}) > 2\max(\mathbf{f}_{C_1}, \mathbf{f}_{C_2})$. By Proposition 5.3, the expected number of cluster-sending steps is upper bounded by $\mathbb{E}(n, \mathbf{f}_{S_1}, \mathbf{f}_{S_2})$. In the worst case, we have $n = 2f + 1$ with $f = \mathbf{f}_{S_1} = \mathbf{f}_{S_2}$. Hence, the expected number of cluster-sending steps is upper bounded by $\mathbb{E}(2f + 1, f, f)$, $f \geq 0$. We claim that $\mathbb{E}(2f + 1, f, f)$ simplifies to $\mathbb{E}(2f + 1, f, f) = 4 - 2/(f + 1) - f!^2/(2f)!$. Hence, for all S_1 and S_2, we have $\mathbb{E}(n, \mathbf{f}_{S_1}, \mathbf{f}_{S_2}) < 4$. An analogous argument can be used to prove the other upper bounds. □

Note that the third case of Theorem 5.7 corresponds to cluster-sending between arbitrary-sized resilient clusters that each operate using Byzantine fault-tolerant consensus protocols.

Remark 5.8. The upper bounds on the expected-case complexity of instances of CSPL presented in Theorem 5.7 match the upper bounds for CSP presented in Corollary 4.4. This does not imply that the expected-case complexity for these protocols is the same, however, as the probability distributions that yield these expected-case complexities are very different. To see this, consider a system in which all clusters have n replicas of which f, $n = 2f + 1$, are faulty. Next, we denote the expected number of cluster-sending steps of protocol P by $\mathbf{E}_P$, and we have

$$\mathbf{E}_{\mathsf{CSP}} = \frac{(2f + 1)^2}{(f + 1)^2} = 4 - \frac{4f + 3}{(f + 1)^2};$$

$$\mathbf{E}_{\mathsf{CSPL}} = \mathbb{E}(2f + 1, f, f) = 4 - \frac{2}{(f + 1)} - \frac{f!^2}{(2f)!}.$$

In Figure 6, we have illustrated this difference by plotting the expected-case complexity of CSP and CSPL for systems with equal-sized clusters. In practice, we see that the expected-case complexity for CSP is slightly lower than the expected-case complexity for CSPL.

5.3 Practical Considerations

The results in this paper address the worst-case use-case of cluster-sending: the exchange of a *single* value between clusters in complete isolation without *any* knowledge on the likelihood of specific replicas to be faulty. Practical use-cases

typically provide additional knowledge that can be used to further fine-tune the cluster-sending protocols. E.g., if multiple values are to be exchanged in consecutive steps, then one can start the cluster-sending of the *next* value by first attempting to cluster-send via the previously-successful replica pair and by skipping any replica pairs that have failed (in preceding rounds). Likewise, if the likelihood of replicas to be faulty is known to be skewed, then one can incorporate the skew in the *fully at random* selection of replica pairs to maximize the likelihood of selection non-faulty replica pairs.

The cluster-sending problem we consider here only considers sending a value from one cluster to another cluster. The cluster-sending problem can be generalized in two ways toward a multi-cluster-sending protocol:

1. Cluster C_1 sends a value v to multiple other clusters $C_{2,1}, \ldots, C_{2,n}$, and the success of sending v to any of the clusters $C_{2,i}$ is independent of the success of sending v to any of the other clusters $C_{2,j}$, $1 \leq i \neq j \leq n$. In this case, the cluster-sending steps to each cluster are independent of each other. Hence, the solutions we present in this paper can be applied in a straightforward manner.

2. Cluster C_1 sends a value v to multiple other clusters $C_{2,1}, \ldots, C_{2,n}$ and these clusters only successfully receive v if all clusters do so. This problem is much more akin the traditional *commit problem* as solved by two-phase commit protocols and three-phase commit protocols in the non-resilient setting [14, 29, 34]. One can use cluster-sending as a fundamental *resilient communication primitive* on top of which one can implement resilient versions of these commit protocols (see, e.g., as is the focus of BYSHARD [19]).

6 Asynchronous Communication

In the previous sections, we introduced CSP, CSPP, and CSPL, three probabilistic cluster-sending protocols with expected constant message complexity. To simplify presentation, we have presented their design with respect to a synchronous environment. Next, we consider their usage in environments with asynchronous inter-cluster communication due to which messages can get arbitrary delayed, duplicated, or dropped.

We notice that the presented protocols *only* depend on synchronous communication to minimize communication: at the core of the correctness of CSP, CSPP, and CSPL is the cluster-sending step performed by CS-STEP, which does not make any assumptions on communication (Proposition 3.1). Consequently, CSP, CSPP, and CSPL can easily be generalized to operate in environments with asynchronous communication.

First, we observe that message duplication and out-of-order delivery have no impact on the cluster-sending step performed by CS-STEP. Hence, we do not need to take precautions

Figure 6: Comparison of the expected-case complexity of CSPL and CSP as a function of the number of faulty replicas.

against such asynchronous behavior. Furthermore, if communication is asynchronous, but reliable (messages do not get lost, but can get duplicated, be delivered out-of-order, or get arbitrarily delayed), both CSPP and CSPL will be able to always perform cluster-sending in a finite number of steps.

If communication is asyncrhonous and unreliable (messages sent between non-faulty replicas can get lost and all cluster-sending steps can fail), then the presented *syncrhonous* protocols can fail and, hence, need to be adjusted to the asyncrhonous environment in which they are deployed. The best way in which a probabilistic cluster-sending solution can deal with *unreliable* asynchronous communication depends on the model of asynchronous communication one is optimizing for.

As an example, we illustrate cluster-sending with a basic model of unreliable communication in which each communication step can independently fail with a probability of p_{fail}. In this setting, replicas in $\mathcal{C}_1$ can simply continue cluster-sending steps until a step succeeds, which will eventually happen. Similar to the proof of Theorem 4.2, we can prove the following:

Theorem 6.1. *Let $\mathcal{C}_1, \mathcal{C}_2$ be disjoint clusters. If each communication step can independently fail with a probability of p_{fail}, then $\text{CSP}(\mathcal{C}_1, \mathcal{C}_2, v)$ is expected to result in cluster-sending v from $\mathcal{C}_1$ to $\mathcal{C}_2$ in $(\mathbf{n}_{\mathcal{C}_1} \mathbf{n}_{\mathcal{C}_2})/(\mathbf{nf}_{\mathcal{C}_1} \mathbf{nf}_{\mathcal{C}_2}) \cdot \frac{1}{(1 - p_{\text{fail}})^2}$ cluster-sending steps.*

Sketch. There are two communication steps between $\text{R}_1 \in \mathcal{C}_1$ and $\text{R}_2 \in \mathcal{C}_2$. With a message loss of p_{fail} between the clusters, the probability q that no communication failure happens during a cluster-sending step between two non-faulty replicas is $(1 - p_{\text{fail}})^2$. □

Not all models of asynchronous communication allow for such a precise characterization of the expected-case complexity for cluster-sending: often, communication steps are not fully independent as the communication model allows for *periods* in which no communication will succeed. This is the

case for the *partial synchrony model*, which is often employed by primary-backup consensus protocols such as PBFT. In the partial synchrony model, *unreliable periods of communication* are followed by *sufficiently-long periods of reliable communication*, during which cluster-sending with the presented algorithms will always succeed. During arbitrary-length periods of unreliable of communication, a cluster-sending attempt can perform an arbitrary number of cluster-sending steps.

Although the partial synchrony model and many other asynchronous communication models do not allow for a precise characterization of the expected-case complexity, we can still use our protocols to provide cluster-sending eventually: running the algorithms until successful cluster-sending is performed, by simply continuing until a step succeeds (CSP) or by rerunning the protocol until a step succeeds (CSPP, and CSPL), will assure success as soon as communication becomes reliable.

We note that if communication is asynchronous, then messages can get arbitrarily delayed. Fortunately, practical environments operate with large periods of reliable communication in which the majority of the messages arrive within some bounded delay unknown to $\mathcal{C}_1$ and $\mathcal{C}_2$. Hence, replicas in $\mathcal{C}_1$ can simply assume some delay δ. If this delay is too short, then a cluster-sending step can *appear to fail* simply because the proof of receipt is still under way. In this case, cluster-sending will still be achieved when the proof of receipt arrives, but spurious cluster-sending steps can be initiated in the meantime. To reduce the number of such spurious cluster-sending steps, all non-faulty replicas in $\mathcal{C}_1$ can use *exponential backoff* to increase the message delay δ toward some reasonable upper bound (e.g., 100 s).

Finally, asynchronous environments often necessitate rather high assumptions on the message delay δ. Consequently, the duration of a single failed cluster-sending step performed by CS-STEP will be high. Here, a trade-off can be made between *message complexity* and *duration* by starting several rounds of the cluster-sending step at once, which will

sharply reduce the duration of the protocol with only a constant increase in expected message complexity. For example, if CSP is expected to perform *four* cluster-sending steps, then one can reduce the expected-case duration of cluster-sending from the duration of *four cluster-sending steps* to the duration of *one cluster-sending step* by simply performing four cluster-sending steps in parallel (of which one is expected to succeed). In the presence of unreliable communication, one can increase the number of parallel cluster-sending steps in accordance with Theorem 6.1 to keep the duration of cluster-sending low.

7 Performance evaluation

In the previous sections, we introduced probabilistic cluster-sending protocols with expected-case constant message complexity. To gain further insight in the performance attainable by these protocols, especially in environments with unreliable communication, we implemented these protocols in a simulated sharded resilient environment that allows us to control the faulty replicas and the message loss rates.[3] As a baseline of comparison, we also evaluated three cluster-sending protocols from the literature:

1. The *worst-case optimal cluster-sending protocol* PBS-CS of Hellings et al. [18, 20] that can perform cluster-sending using only $\mathbf{f}_{C_1} + \mathbf{f}_{C_2} + 1$ messages, which is worst-case optimal. This protocol requires reliable communication.

2. The *broadcast-based cluster-sending protocol* of CHAINSPACE [1] that can perform cluster-sending using $\mathbf{n}_{C_1}\mathbf{n}_{C_2}$ messages. This protocol requires reliable communication.

3. The *global sharing protocol* of GEOBFT [16], an optimistic cluster-sending protocol that assumes that each cluster uses a primary-backup consensus protocol (e.g., PBFT [6]) and optimizes for the case in which the coordinating primary of C_1 is non-faulty. In this optimistic case, GEOBFT can perform cluster-sending using only $\mathbf{f}_{C_2} + 1$ messages. To deal with faulty primaries and unreliable communication, GEOBFT employs a costly remote view-change protocol, however.

We refer to Figure 2 for an analytical comparison between these three cluster-sending protocols and our three probabilistic cluster-sending protocols.

In each experiment, we measured the number of messages exchanged in 10000 runs of the cluster-sending protocol under consideration. In specific, in each run we measure the number of messages exchanged when sending a value v from a cluster C_1 to a cluster C_2 with $\mathbf{n}_{C_1} = \mathbf{n}_{C_2} = 3\mathbf{f}_{C_1} + 1 = 3\mathbf{f}_{C_2} + 1$, and we aggregate this data over 10000 runs. The messages

exchanged is an objective measure of the performance of the cluster-sending protocols under consideration that is independent of the environment (e.g., network bandwidth, message delays) and the application use-case for which cluster-sending is used. As we use equal-sized clusters, we have $\Phi_{\min}(C_1, C_2) = \Phi_{\max}(C_1, C_2)$ and, hence, we use a singe instance of CSPL.

Next, we detail the two experiments we performed and look at their results.

7.1 Performance of Cluster-Sending Protocols

In our first experiment, we measure the number of messages exchanged as a function of the number of faulty replicas. In this case, we assumed reliable communication, due to which we could include all six protocols. The results of this experiment can be found in Figure 7.

As is clear from the results, our probabilistic cluster-sending protocols are able to perform cluster-sending with only a constant number of messages exchanged. Furthermore, we see that the performance of our cluster-sending protocols matches the theoretical expected-case analysis in this paper and closely follows the expected performance illustrated in Figure 6 (note that Figure 6 plots cluster-sending steps and each cluster-sending step involves the exchange of *two* messages between clusters).

As all other cluster-sending protocols have a linear (PBS-CS and GEOBFT) or quadratic (CHAINSPACE) message complexity, our probabilistic cluster-sending protocols outperform the other cluster-sending protocols. This is especially the case when dealing with bigger clusters, in which case the expected-case constant message complexity of our probabilistic cluster-sending protocols shows the biggest advantage. Only in the case of the smallest clusters can the other cluster-sending protocols outperform our probabilistic cluster-sending protocols, as PBS-CS, GEOBFT, and CHAINSPACE use reliable communication to their advantage to eliminate any acknowledgment messages send from the receiving cluster to the sending cluster. We believe that the slightly higher cost of our probabilistic cluster-sending protocols in these cases is justified, as our protocols can effectively deal with unreliable communication.

7.2 Message Loss

In our second experiment, we measure the number of messages exchanged as a function of the number of faulty replicas and as a function of the message loss (in percent) *between the two clusters*. We only focus on message loss between clusters, and we assume that consensus steps *within a cluster* always succeed. In this case, we only included our probabilistic cluster-sending protocols, as PBS-CS and CHAINSPACE both assume reliable communication and GEOBFT is only able to perform recovery via remote view-changes in periods

---

[3]The full implementation of this experiment is available at `anonymized`.

Figure 7: A comparison of the number of message exchange steps as a function of the number of faulty replicas in both clusters by our probabilistic cluster-sending protocols CSP, CSPP, and CSPL, and by three protocols from the literature. For each protocol, we measured the number of message exchange steps to send a value between two equally-sized clusters (average of 10 000 runs), each cluster having $n = 3\mathbf{f} + 1$ replicas. †The results for GEOBFT are a plot of the best-case optimistic phase of that protocol.

of reliable communication. The results of this experiment can be found in Figure 8.

Theorem 6.1 can be used to derive the expected-case complexity of CSP in each of the cases. For example, with a message loss of $p_{\text{fail}} = 30\%$, the probability q that no communication failure happens during a cluster-sending step is $q = 0.49$. Hence, when compared to the case without message loss, we expect an increase in the message complexity by a factor $1/q \approx 2$. Our measurements on CSP show that this expected increase also happens in practice. For CSPP and CSPL, we did not provide a theoretical analysis of the expected-case complexity. Still, in practice we see a similar behavior as with CSP: we see an increase in the message complexity by a factor $1/q \approx 2$ for all protocols.

This observation extends to other probabilities of message loss. Although the probabilistic arguments underpinning the expected-case cost of, on the one hand, CSP and CSPP and, on the other hand, CSPL are vastly different, the results of these experiments show that across the board, the practical performance of the three protocols is similar.

These results further underline the practical benefits of each of the probabilistic cluster-sending protocols, especially for larger clusters: even in the case of high message loss rates, each of our probabilistic cluster-sending protocols are able to outperform the cluster-sending protocols PBS-CS, CHAINSPACE, and GEOBFT, which can only operate with reliable-communication.

8 Related Work

Although there is abundant literature on distributed systems and on consensus-based resilient systems (e.g., [2, 5, 8, 15, 17, 29, 35]), there is only limited work on communication

between resilient systems [1, 16, 18, 20]. In the previous section, we have already compared CSP, CSPP, and CSPL with the worst-case optimal cluster-sending protocols of Hellings et al. [18, 20], the optimistic cluster-sending protocol of GEOBFT [16], and the broadcast-based cluster-sending protocols of CHAINSPACE [1]. Furthermore, we notice that *cluster-sending* can be solved using well-known Byzantine primitives such as consensus, interactive consistency, and Byzantine broadcasts [6, 9, 26]. These primitives are much more costly than cluster-sending protocols, however, and require huge amounts of communication between all involved replicas.

In parallel to the development of traditional resilient systems and permissioned blockchains, there has been promising work on sharding in permissionless blockchains such as BITCOIN [27] and ETHEREUM [36]. Examples include techniques for enabling reliable cross-chain coordination via sidechains, blockchain relays, atomic swaps, atomic commitment, and cross-chain deals [12, 13, 21, 23, 24, 37, 38]. Unfortunately, these techniques are deeply intertwined with the design goals of permissionless blockchains in mind (e.g., cryptocurrency-oriented), and are not readily applicable to traditional consensus-based Byzantine clusters.

9 Conclusion

In this paper, we presented probabilistic cluster-sending protocols that each provide highly-efficient solutions to the cluster-sending problem. Our probabilistic cluster-sending protocols can facilitate communication between Byzantine fault-tolerant clusters with expected constant communication between clusters. For practical environments, our protocols can support worst-case linear communication between clusters,

Figure 8: A comparison of the number of message exchange steps as a function of the number of faulty replicas in both clusters and of the message loss by our probabilistic cluster-sending protocols CSP, CSPP, and CSPL. For each protocol, we measured the number of message exchange steps to send $10\,000$ values between two equally-sized clusters, each cluster having $n = 3\mathbf{f} + 1$ replicas, after which we aggregated the measurements to obtain a summary of the distribution of messages exchanged.

which is optimal, and deal with asynchronous and unreliable communication. The low practical cost of our cluster-sending protocols further enables the development and deployment of high-performance systems that are constructed out of Byzantine fault-tolerant clusters, e.g., fault-resilient geo-aware sharded data processing systems.

References

[1] Mustafa Al-Bassam, Alberto Sonnino, Shehar Bano, Dave Hrycyszyn, and George Danezis. Chainspace: A sharded smart contracts platform, 2017. URL: http://arxiv.org/abs/1708.03778.

[2] Christian Berger and Hans P. Reiser. Scaling byzantine consensus: A broad analysis. In *Proceedings of the 2nd Workshop on Scalable and Resilient Infrastructures for Distributed Ledgers*, pages 13–18. ACM, 2018. https://doi.org/10.1145/3284764.3284767.

[3] Gabi Bracha and Ophir Rachman. Randomized consensus in expected $O((n^2 \log n))$ operations. In *Distributed Algorithms*, pages 143–150. Springer Berlin Heidelberg, 1992. https://doi.org/10.1007/BFb0022443.

[4] Christian Cachin, Klaus Kursawe, Frank Petzold, and Victor Shoup. Secure and efficient asynchronous broadcast protocols. In *Advances in Cryptology — CRYPTO 2001*, pages 524–541. Springer Berlin Heidelberg, 2001. https://doi.org/10.1007/3-540-44647-8_31.

[5] Christian Cachin and Marko Vukolic. Blockchain consensus protocols in the wild (keynote talk). In *31st International Symposium on Distributed Computing*,

volume 91 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 1:1–1:16. Schloss Dagstuhl–Leibniz-Zentrum fuer Informatik, 2017. https://doi.org/10.4230/LIPIcs.DISC.2017.1.

[6] Miguel Castro and Barbara Liskov. Practical byzantine fault tolerance and proactive recovery. *ACM Transactions on Computer Systems*, 20(4):398–461, 2002. https://doi.org/10.1145/571637.571640.

[7] Hung Dang, Tien Tuan Anh Dinh, Dumitrel Loghin, Ee-Chien Chang, Qian Lin, and Beng Chin Ooi. Towards scaling blockchain systems via sharding. In *Proceedings of the 2019 International Conference on Management of Data*, pages 123–140. ACM, 2019. https://doi.org/10.1145/3299869.3319889.

[8] Tien Tuan Anh Dinh, Rui Liu, Meihui Zhang, Gang Chen, Beng Chin Ooi, and Ji Wang. Untangling blockchain: A data processing view of blockchain systems. *IEEE Trans. Knowl. Data Eng.*, 30(7):1366–1385, 2018. https://doi.org/10.1109/TKDE.2017.2781227.

[9] D. Dolev and H. Strong. Authenticated algorithms for byzantine agreement. *SIAM Journal on Computing*, 12(4):656–666, 1983. https://doi.org/10.1137/0212045.

[10] Danny Dolev, Cynthia Dwork, and Larry Stockmeyer. On the minimal synchronism needed for distributed consensus. *Journal of the ACM*, 34(1):77—-97, 1987. https://doi.org/10.1145/7531.7533.

[11] Cynthia Dwork, Nancy Lynch, and Larry Stockmeyer. Consensus in the presence of partial synchrony. *Journal of the ACM*, 35(2):288—323, 1988. https://doi.org/10.1145/42282.42283.

[12] Muhammad El-Hindi, Carsten Binnig, Arvind Arasu, Donald Kossmann, and Ravi Ramamurthy. BlockchainDB: A shared database on blockchains. *Proc. VLDB Endow.*, 12(11):1597–1609, 2019. https://doi.org/10.14778/3342263.3342636.

[13] Ethereum Foundation. BTC Relay: A bridge between the bitcoin blockchain & ethereum smart contracts, 2017. URL: http://btcrelay.org.

[14] Jim Gray. Notes on data base operating systems. In *Operating Systems, An Advanced Course*, pages 393–481. Springer-Verlag, 1978. https://doi.org/10.1007/3-540-08755-9_9.

[15] Suyash Gupta, Jelle Hellings, and Mohammad Sadoghi. *Fault-Tolerant Distributed Transactions on Blockchain*. Synthesis Lectures on Data Management. Morgan & Claypool, 2021. https://doi.org/10.2200/S01068ED1V01Y202012DTM065.

[16] Suyash Gupta, Sajjad Rahnama, Jelle Hellings, and Mohammad Sadoghi. ResilientDB: Global scale resilient blockchain fabric. *Proceedings of the VLDB Endowment*, 13(6):868—-883, 2020. https://doi.org/10.14778/3380750.3380757.

[17] Suyash Gupta and Mohammad Sadoghi. *Blockchain Transaction Processing*, pages 1–11. Springer International Publishing, 2018. https://doi.org/10.1007/978-3-319-63962-8_333-1.

[18] Jelle Hellings and Mohammad Sadoghi. Brief announcement: The fault-tolerant cluster-sending problem. In *33rd International Symposium on Distributed Computing (DISC 2019)*, volume 146 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 45:1–45:3. Schloss Dagstuhl–Leibniz-Zentrum fuer Informatik, 2019. https://doi.org/10.4230/LIPIcs.DISC.2019.45.

[19] Jelle Hellings and Mohammad Sadoghi. Byshard: Sharding in a byzantine environment. *Proceedings of the VLDB Endowment*, 14(11):2230–2243, 2021. https://doi.org/10.14778/3476249.3476275.

[20] Jelle Hellings and Mohammad Sadoghi. The fault-tolerant cluster-sending problem. In *Foundations of Information and Knowledge Systems*, pages 168–186. Springer, 2022. https://doi.org/10.1007/978-3-031-11321-5_10.

[21] Maurice Herlihy. Atomic cross-chain swaps. In *Proceedings of the 2018 ACM Symposium on Principles of Distributed Computing*, pages 245—254. ACM, 2018. https://doi.org/10.1145/3212734.3212736.

[22] Maurice Herlihy. Blockchains from a distributed computing perspective. *Communications of the ACM*, 62(2):78–85, 2019. https://doi.org/10.1145/3209623.

[23] Maurice Herlihy, Barbara Liskov, and Liuba Shrira. Cross-chain deals and adversarial commerce. *The VLDB Journal*, 2021. https://doi.org/10.1007/s00778-021-00686-1.

[24] Jae Kwon and Ethan Buchman. Cosmos whitepaper: A network of distributed ledgers, 2019. URL: https://cosmos.network/cosmos-whitepaper.pdf.

[25] Leslie Lamport. Paxos made simple. *ACM SIGACT News, Distributed Computing Column 5*, 32(4):51–58, 2001. https://doi.org/10.1145/568425.568433.

[26] Leslie Lamport, Robert Shostak, and Marshall Pease. The byzantine generals problem. *ACM Transactions on Programming Languages and Systems*, 4(3):382–401, 1982. https://doi.org/10.1145/357172.357176.

[27] Satoshi Nakamoto. Bitcoin: A peer-to-peer electronic cash system. URL: https://bitcoin.org/en/bitcoin-paper.

[28] Arvind Narayanan and Jeremy Clark. Bitcoin's academic pedigree. *Communications of the ACM*, 60(12):36–45, 2017. https://doi.org/10.1145/3132259.

[29] M. Tamer Özsu and Patrick Valduriez. *Principles of Distributed Database Systems*. Springer, 2020. https://doi.org/10.1007/978-3-030-26253-2.

[30] Michael Pisa and Matt Juden. Blockchain and economic development: Hype vs. reality. Technical report, Center for Global Development, 2017. URL: https://www.cgdev.org/publication/blockchain-and-economic-development-hype-vs-reality.

[31] David Reinsel, John Gantz, and John Rydning. Data age 2025: The digitization of the world, from edge to core. Technical report, IDC, 2018. URL: https://www.seagate.com/files/www-content/our-story/trends/files/idc-seagate-dataage-whitepaper.pdf.

[32] Marc Shapiro, Nuno Preguiça, Carlos Baquero, and Marek Zawirski. Conflict-free replicated data types. In *Stabilization, Safety, and Security of Distributed Systems*, pages 386–400. Springer, 2011. https://doi.org/10.1007/978-3-642-24550-3_29.

[33] Victor Shoup. Practical threshold signatures. In *Advances in Cryptology — EUROCRYPT 2000*, pages 207–220. Springer Berlin Heidelberg, 2000. https://doi.org/10.1007/3-540-45539-6_15.

[34] Dale Skeen. A quorum-based commit protocol. Technical report, Cornell University, 1982.

[35] Gerard Tel. *Introduction to Distributed Algorithms*. Cambridge University Press, 2nd edition, 2001.

[36] Gavin Wood. Ethereum: a secure decentralised generalised transaction ledger. EIP-150 revision. URL: https://gavwood.com/paper.pdf.

[37] Gavin Wood. Polkadot: vision for a heterogeneous multi-chain framework, 2016. URL: https://polkadot.network/PolkaDotPaper.pdf.

[38] Victor Zakhary, Divyakant Agrawal, and Amr El Abbadi. Atomic commitment across blockchains. *Proc. VLDB Endow.*, 13(9):1319–1331, 2020. https://doi.org/10.14778/3397230.3397231.

A The proof of Lemma 5.2

To get the intuition behind the closed form of Lemma 5.2, we take a quick look at the combinatorics of *list-merging*. Notice that we can merge lists S and T together by either first taking an element from S or first taking an element from T. This approach towards list-merging yields the following recursive solution to the list-merge problem:

$$
\mathbb{M}(v,w) = \begin{cases} \mathbb{M}(v-1,w) + \mathbb{M}(v,w-1) & \text{if } v > 0 \text{ and } w > 0; \\ 1 & \text{if } v = 0 \text{ or } w = 0. \end{cases}
$$

Consider lists S and T with $|S| = v$ and $|T| = w$ distinct values. We have $|\mathsf{perms}(S)| = v!$, $|\mathsf{perms}(T)| = w!$, and $|\mathsf{perms}(S \cup T)| = (v+w)!$. We observe that every list-merge of $(P_S, P_T) \in \mathsf{perms}(S) \times \mathsf{perms}(T)$ is a unique value in $\mathsf{perms}(S \cup T)$. Furthermore, every value in $\mathsf{perms}(S \cup T)$ can be constructed by such a list-merge. As we have $|\mathsf{perms}(S) \times \mathsf{perms}(T)| = v!w!$, we derive the closed form

$$
\mathbb{M}(v,w) = \frac{(v+w)!}{(v!w!)}
$$

of Lemma 5.2. Next, we formally prove this closed form.

Proof. We prove this by induction. First, the base cases $\mathbb{M}(0,w)$ and $\mathbb{M}(v,0)$. We have

$$
\mathbb{M}(0,w) = \frac{(0+w)!}{0!w!} = \frac{w!}{w!} = 1;
$$
$$
\mathbb{M}(v,0) = \frac{(v+0)!}{v!0!} = \frac{v!}{v!} = 1.
$$

Next, we assume that the statement of the lemma holds for all non-negative integers v', w' with $0 \le v' + w' \le j$. Now consider non-negative integers v, w with $v + w = j + 1$. We assume that $v > 0$ and $w > 0$, as otherwise one of the base cases applies. Hence, we have

$$
\mathbb{M}(v,w) = \mathbb{M}(v-1,w) + \mathbb{M}(v,w-1).
$$

We apply the induction hypothesis on the terms $\mathbb{M}(v-1,w)$ and $\mathbb{M}(v,w-1)$ and obtain

$$
\mathbb{M}(v,w) = \left(\frac{((v-1)+w)!}{(v-1)!w!} \right) + \left(\frac{(v+(w-1))!}{v!(w-1)!} \right).
$$

Next, we apply $x = x(x-1)!$ and simplify the result to obtain

$$
\begin{aligned}
\mathbb{M}(v,w) &= \left(\frac{v(v+w-1)!}{v!w!} \right) + \left(\frac{w(v+w-1)!}{v!w!} \right) \\
&= \left(\frac{(v+w)(v+w-1)!}{v!w!} \right) = \frac{(v+w)!}{v!w!},
\end{aligned}
$$

which completes the proof. $\square$

B The simplification of $\mathbb{F}(n,m_1,m_2,k)$

Let g be the expression

$$b_1!^2 \binom{m_1}{b_1}\binom{n-m_2}{b_1}b_2!^2\binom{n-m_1}{b_2}\binom{m_2}{b_2}\cdot$$
$$\mathbb{M}(b_1,b_2)b_{1,2}!^2\mathbb{M}(b_1+b_2,b_{1,2})(n-k)!^2\mathbb{M}(k,n-k),$$

as stated right above Lemma 5.3. We will show that g is equivalent to the closed form of $\mathbb{F}(n,m_1,m_2,k)$, as stated in Lemma 5.3.

Proof. We use the shorthands $\mathbf{T}_1 = \binom{m_1}{b_1}\binom{n-m_2}{b_1}$ and $\mathbf{T}_2 = \binom{n-m_1}{b_2}\binom{m_2}{b_2}$, and we have

$$g = b_1!^2\mathbf{T}_1 b_2!^2\mathbf{T}_2\cdot$$
$$\mathbb{M}(b_1,b_2)b_{1,2}!^2\mathbb{M}(b_1+b_2,b_{1,2})(n-k)!^2\mathbb{M}(k,n-k).$$

We apply Lemma 5.2 on terms $\mathbb{M}(b_1,b_2)$, $\mathbb{M}(b_1+b_2,b_{1,2})$, and $\mathbb{M}(k,n-k)$, apply $k = b_1+b_2+b_{1,2}$, and simplify to derive

$$g = b_1!^2\mathbf{T}_1 b_2!^2\mathbf{T}_2\cdot$$
$$\frac{(b_1+b_2)!}{b_1!b_2!}b_{1,2}!^2\frac{(b_1+b_2+b_{1,2})!}{(b_1+b_2)!b_{1,2}!}(n-k)!^2\frac{(k+n-k)!}{k!(n-k)!}$$
$$= b_1!\mathbf{T}_1 b_2!\mathbf{T}_2 b_{1,2}!(n-k)!n!.$$

Finally, we expand the binomial terms $\mathbf{T}_1$ and $\mathbf{T}_2$, apply $b_{1,2} = m_1-b_1 = m_2-b_2$ and $k = m_1+b_2 = m_2+b_1$, and simplify to derive

$$g = b_1!\frac{m_1!}{b_1!(m_1-b_1)!}\frac{(n-m_2)!}{b_1!(n-m_2-b_1)!}\cdot$$
$$b_2!\frac{(n-m_1)!}{b_2!(n-m_1-b_2)!}\frac{m_2!}{b_2!(m_2-b_2)!}\cdot$$
$$b_{1,2}!(n-k)!n!$$
$$= \frac{m_1!}{b_{1,2}!}\frac{(n-m_2)!}{b_1!(n-k)!}\frac{(n-m_1)!}{b_2!(n-k)!}\frac{m_2!}{b_{1,2}!}b_{1,2}!(n-k)!n!$$
$$= \frac{m_1!m_2!(n-m_1)!(n-m_2)!n!}{b_1!b_2!b_{1,2}!(n-k)!},$$

which completes the proof. □

C The Closed Form of $\mathbb{E}(2f+1,f,f)$

Here, we shall prove that

$$\mathbb{E}(2f+1,f,f) = 4 - \frac{2}{(f+1)} - \frac{f!^2}{(2f)!}.$$

Proof. By Proposition 5.2 and some simplifications, we have

$$\mathbb{E}(2f+1,f,f) = \frac{1}{(2f+1)!^2}\cdot$$
$$\left(\sum_{k=f}^{2f}\frac{2f+1}{2f+1-k}\frac{f!^2(f+1)!^2(2f+1)!}{(k-f)!^2(2f-k)!(2f+1-k)!}\right).$$

First, we apply $x! = x(x-1)!$, simplify, and obtain

$$\mathbb{E}(2f+1,f,f) = \frac{f!^2(2f+1)}{(2f+1)!}\cdot$$
$$\left(\sum_{k=f}^{2f}\frac{(f+1)!^2}{(k-f)!^2(2f+1-k)!^2}\right)$$
$$= \frac{f!^2}{(2f)!}\left(\sum_{k=0}^{f}\frac{(f+1)!^2}{k!^2(f+1-k)!^2}\right)$$
$$= \frac{f!^2}{(2f)!}\left(\sum_{k=0}^{f}\binom{f+1}{k}^2\right).$$

Next, we apply $\binom{m}{n} = \binom{m}{m-n}$, extend the sum by one term, and obtain

$$\mathbb{E}(2f+1,f,f) = \frac{f!^2}{(2f)!}\cdot$$
$$\left(\left(\sum_{k=0}^{f+1}\binom{f+1}{k}\binom{f+1}{f+1-k}\right) - \binom{f+1}{f+1}\binom{f+1}{0}\right).$$

Then, we apply Vandermonde's Identity to eliminate the sum and obtain

$$\mathbb{E}(2f+1,f,f) = \frac{f!^2}{(2f)!}\left(\binom{2f+2}{f+1} - 1\right).$$

Finally, we apply straightforward simplifications and obtain

$$\mathbb{E}(2f+1,f,f) = \frac{f!^2}{(2f)!}\frac{(2f+2)!}{(f+1)!(f+1)!} - \frac{f!^2}{(2f)!}$$
$$= \frac{f!^2}{(2f)!}\frac{(2f)!(2f+1)(2f+2)}{f!^2(f+1)^2} - \frac{f!^2}{(2f)!}$$
$$= \frac{(2f+1)(2f+2)}{(f+1)^2} - \frac{f!^2}{(2f)!}$$
$$= \frac{(2f+2)^2}{(f+1)^2} - \frac{2f+2}{(f+1)^2} - \frac{f!^2}{(2f)!}$$
$$= \frac{4(f+1)^2}{(f+1)^2} - \frac{2(f+1)}{(f+1)^2} - \frac{f!^2}{(2f)!}$$
$$= 4 - \frac{2}{f+1} - \frac{f!^2}{(2f)!},$$

which completes the proof. □

Response to the Reviewers' comments
"Solution: Byzantine Cluster-Sending in Expected Constant Cost and Constant Time"

Anonymous authors

March 1, 2023

We would like to tank the chairs and the reviewers for providing us the opportunity to revise our work. We have detailed below our rebuttal to reviewers comments and, where applicable, the corresponding changes we made to the paper (highlighted in the paper in blue). Before we continue, we like to thank each of the *four* reviewers for their careful review and their detailed feedback.

1 Metareview

We have addressed all concerns of the individual reviewers, which covers the main concerns raised in the meta-review.

2 Review #1 (Reviewer RyEC)

Review: The problem is defined by the following properties:

[should be Def 2.1, part (3)] Agreement-Send(C1): all non-faulty replicas in C1 agrees to send v.

[should be Def 2.1, part (1)] Agreement-Receive(C2): all non-faulty replicas in C2 receive v. (I believe "receive" here is a state where each replica reaches.)

[should be Def 2.1, part (2)] Agreement-Confirm(C1): all non-faulty replicas in C1 confirm v. ("confirm" here seems to be another halting state.)

Validity&Integrity (C2): if a non-faulty replica in C2 receives v, then v must be sent from some replica in C1.

Validity&Integrity (C1): a non-faulty replica in C1 confirms v iff a non-faulty replica in C2 receives v.

We have changed the wording of Definition 2.1 to further clarify the cluster-sending problem.

Review: ... Both clusters must agree on the same random order, as the clusters should initially agree on the same random source via a distributed fault-tolerant random coin [3, 4].

The receiving cluster does not have to know the random order, that is a fact only relevant to the sending cluster. We have clarified this in the paper.

Review: This paper does not mention the lower bound on the expected inter-cluster messages to this model. Why 4 and 9/4 is the best?

The only lower-bounds proven for the cluster-sending problem are for the worst-case setting. For the expected-case complexity, no such lower bounds are known. We do conjecture that our protocols (for which we have provided exact bounds on their complexity) achieve an optimal expected-case complexities, however.

To get an exact inter-cluster message complexity, we have to choose a specific failure model. For simple asynchronous communication models (e.g., each message is independently likely to get lost with some probability p), the exact inter-cluster message complexity is easy to obtain (e.g., we can include an added probability of failure p onto the two messages exchanged in each step).

For other failure models, e.g., failure models that allow arbitrary durations of failure, as long as eventually communication recovers, there is no straightforward way to formalize an expected complexity.

To further clarify this, we have reworked Section 6.

We have reduced the size of Figure 8 by removing some of the data points (namely 20%, 40%, 60%, and 80% message loss). Furthermore, we have changed the description of the experiment to clarify its purpose and included a discussion that relates the experiment with the newly-introduced results of Section 6.

We have added the following discussion regarding multi-cluster cluster-sending to the end of Section 5.3.

The cluster-sending problem we consider here only considers sending a value from one cluster to another cluster. The cluster-sending problem can be generalized in two ways toward a multi-cluster-sending protocol:

1. Cluster $\mathcal{C}_1$ sends a value v to multiple other clusters $\mathcal{C}_{2,1}, \dots, \mathcal{C}_{2,n}$, and the success of sending v to any of the clusters $\mathcal{C}_{2,i}$ is independent of the success of sending v to any of the other clusters $\mathcal{C}_{2,j}$, $1 \le i \ne j \le n$. In this case, the cluster-sending steps to each cluster are independent of each other. Hence, the solutions we present in this paper can be applied in a straightforward manner.

2. Cluster $\mathcal{C}_1$ sends a value v to multiple other clusters $\mathcal{C}_{2,1}, \dots, \mathcal{C}_{2,n}$ and these clusters only successfully receive v if all clusters do so. This problem is much more akin the traditional *commit problem* as solved by two-phase commit protocols and three-phase commit protocols in the non-resilient setting. One can use cluster-sending as a fundamental *resilient communication primitive* on top of which one can implement resilient versions of these commit protocols (see, e.g., as is the focus of BYSHARD).

Our work will provide cluster-sending even when dealing with adaptive full-information adversaries as long as their potential to corrupt replicas is limited (which is the usual assumption). To deal with an adversary that can fully influence the distributed fault-tolerant coin used to make decisions would indeed reduce the protocols to the worst-case message complexity.

Done.

We prefer the integer-fractions ourselves: it shows the integer part directly. We have added the fraction-only notation too.

> **Review:** Definition 2.1 (1), each non-faulty replica "in " seems duplicated.

Fixed.

> **Review:** Theorem 4.2 and its proof: the denominator nfC1 seems incorrect (typo?). The same typo also occurs in Corollary 4.5.

The double term $(\mathbf{nf}_{\mathcal{C}_1}\mathbf{nf}_{\mathcal{C}_1})$ was indeed a typo. It should have been $(\mathbf{nf}_{\mathcal{C}_1}\mathbf{nf}_{\mathcal{C}_2})$.

> **Review:** The ɪs still case sensitive. Some part of your CSp is written as Csp. This occurs in page 2 item 2 in the main contribution.

We found two occurrences of this issue, both are fixed now.

3 Review #2 (Reviewer WwWS)

The reviewer did not have remaining concerns.

4 Review #3 (Reviewer gpss)

> **Review:** I have just one comment on this work. This problem has real-life applications; therefore, deriving some more realistic bounds on the message complexity would help the system designers who are concerned with latency. The estimation of message complexity under synchrony is too idealistic a scenario; therefore, the author can consider a performance analysis on the expected message complexity if they assume some upper bound on the max latency T for the message delivery, but the algorithm should not use this parameter or should not be aware of it. They can also make some assumptions on the actual consensus protocol, failure model (crash or recovery), and upper and lower bound time on message delivery [T1, T2] to derive the result.

In an asynchronous setting, one needs *some* mechanism to determine whether a communication step was not performed (either due to malicious behavior or due to unreliable communication). To do so without using any timing assumption would yield a completely different approach as taken in this paper (if possible). As such, our outline of the asynchronous versions of the cluster-sending protocols utilize exponential backoff to reach a sensible latency for message delivery (if the message is not dropped). In practice, one can trade latency in the asynchronous setting for message complexity by performing multiple cluster-sending steps in parallel. We have further clarified this approach in the paper.

We already study the behavior of the cluster-sending protocols in terms of the message complexity as a function of unreliable communication in Section 7.2 and Figure 8. We have improved the description of this experiment and the analysis of its results with regards to unreliable communication. Furthermore, we have expanded the analysis in Section 6 of asynchronous communication to provide expected complexities under certain models of asynchronous communication.

5 Review #4 (Reviewer kHhH)

> **Review:** Variable (set) R shows up in the definition undefined.

Throughout the paper, ʀ, ʀ₁, ʀ₂, ... all refer to replicas. Due to our rewording of Definition 2.1, we no longer refer to specific replicas in the definition. At other places, we have ensured that replicas are always taken from the set of all replicas or all non-faulty replicas in a cluster.

> **Review:** It is unclear what it means to decide "RECEIVE / CONFIRM / AGREE".

These terms refer to conceptual states the clusters $\mathcal{C}_1$ and $\mathcal{C}_2$ can reach. The progression of conceptual states is as follows:

1. The replicas in $\mathcal{C}_1$ reach the state AGREE(v) indicating that the replicas in $\mathcal{C}_1$ have internally decided upon sending v to $\mathcal{C}_2$.

   The cause of such agreement is outside of the scope of cluster-sending (e.g., the consequence of a prior consensus decision made while operating cluster $\mathcal{C}_1$).

2. After the replicas in $\mathcal{C}_1$ reach the state AGREE(v), the replicas in $\mathcal{C}_2$ can reach the state RECEIVE(v) indicating that the replicas in $\mathcal{C}_2$ have received value v from $\mathcal{C}_1$ in a resilient manner.

   The cause of reaching RECEIVE is one-or-more steps of the communication protocol that is used to perform cluster-sending.

3. Finally, after the replicas in $\mathcal{C}_2$ reach the state RECEIVE(v), the replicas in $\mathcal{C}_1$ can reach the state CONFIRM(v) indicating that the replicas in $\mathcal{C}_1$ have confirmed that the value v was received by $\mathcal{C}_2$ in a resilient manner.

   The cause of reaching RECEIVE is one-or-more steps of the communication protocol that is used to perform cluster-sending.

We have reformulated Definition 2 to clarify the usage of the terns agree, receive, and confirm.

> **Review:** Requirement (i) says that non-faulty replicas in C2 decide RECEIVE, no matter what. Requirement (iii) then says non-faulty replicas in C2 decide DECEIVE only if non-faulty replicas in C1 decided AGREE. That immediately implies that non-faulty replicas must decide AGREE, no matter what. This immediately collapses the three requirements to a very simple requirement: no matter what happens, C2 decide on RECEIVE, and C1 decide on CONFIRM and AGREE. I am not confident this is what the authors had in mind. (If this is what you have in mind, why over-complicate it?)
>
> If the above is indeed what you mean, what is the difference between CONFIRM and AGREE? We can simply treat them to be the same action since they must always happen together.
>
> It seems that replicas in C1 already agreed on some action called "sending". Then, we can simply equate "sending" with CONFIRM and AGREE. The problem is solved trivially.

The reviewer is right that *if* the value v is known a-priori by both cluster $\mathcal{C}_1$ and $\mathcal{C}_2$, then the cluster-sending problem is trivial.

We have reformulated Definition 2.1 and Section 2 to clarify that the cluster-sending problem is parameterized with respect to some value v that $\mathcal{C}_1$ wants to send, however. Hence, as explained above, the decisions RECEIVE(v), CONFIRM(v), and AGREE(v) are with respect to some value v that $\mathcal{C}_1$ wants to send: the decision AGREE(v) indicates the initial step made by $\mathcal{C}_1$ to initiate cluster-sending, and the decision CONFIRM(v) finishes the cluster-sending step by informing all replicas in $\mathcal{C}_1$ that all replicas in $\mathcal{C}_2$ have received v. As such, we are not interested in trivial solutions in which an a-priori known value is shared.

> **Review:** What is more confusing is that the beginning of Figure 3 gives another set of "pre" and "post" conditions that seem very different from Definition 2.1.
>
> Post (i) introduces R1 and R2, whose purposes are again unclear. R2 is not used at all in that paragraph. R1, without any constraint, seems synonymous to "every replica in C1".

Figure 3 was not intended as a definition: we intended Figure 3 as a protocol that is used as a building block within cluster-sending protocols. Both replicas R_1 and R_2 are inputs of this protocol, as defined in the first line of Figure 3. To further clarify this intent, we have changed the wording in Section 3.

> **Review:** Why are R1 and R2 part of the input to the protocol? Definition 2.1 did not specify these inputs.
>
> Post (ii) states "then C1 agrees on sending", but C1 already agrees on sending according to the "pre" part, making this bullet vacuous.

We have reworded this part of the protocol in line with our changes to Definition 2.1. The intended meaning was that *if* any replicas in $\mathcal{C}_2$ reach the RECEIVE(w) state for any value w, then that must have been preceded by the replicas in $\mathcal{C}_1$ reaching AGREE(w). Hence, $\mathcal{C}_2$ can only receive w from $\mathcal{C}_1$ if the non-faulty replicas actually intended to send w (otherwise, faulty replicas in $\mathcal{C}_1$ would be able to send arbitrary messages).

> **Review:** Post (iii) is situated on a condition "If one replica in C1 decides CONFIRM". If we go by Definition 2.1, this is bound to happen, making the bullet vacuous. If we ignore what is said in Definition 2.1, then it is unclear under what conditions CONFIRM needs to happen, allowing trivial solutions that never decide CONFIRM.
>
> It is also problematic that the properties in Figure 3 rely on communication being reliable". It is not a good idea to conflate the problem statement with the model.

We have address this concern as part of our reformulation of Definition 2.1 when defining the receive, confirm, and agree wording

> **Review:** Instruct R1 to ... Who is instructing R1 to do things?

Instructing R_1 is done by the cluster-sending protocols that use CS-STEP as part of their invocation of CS-STEP, e.g., the protocol CSP in Figure 4 will choose replica R_1 and *then* invoke CS-STEP. We have further clarified this usage of the cluster-sending step in the introduction of Section 3.

> **Review:** Is local consensus guaranteed to succeed on any value? Or are there constraints are what values can be agreed upon? If there is no constraint, then all replicas can simply agree on all possible values, leading to a trivial solution.

The reviewer is right that we do not specify the normal operations of clusters. Instead, we provide the value v that needs to be sent as parameter of the cluster-sending problem (and the cluster-sending protocols we present). These values v typically originate from whichever resilient applications are running on the clusters $\mathcal{C}_1$ and from whichever communication requirements they have. For example, in a sharded system, cluster $\mathcal{C}_1$ can operate a shard and send information to the shard operated by $\mathcal{C}_2$ to perform multi-shard transaction execution. We have added clarification to Section 2.