DYNAMICAL SYSTEMS EMBEDDING WITH A PHYSICS-INFORMED CONVOLUTIONAL NETWORK

ABSTRACT

Dynamical systems are found in innumerable forms across the physical and biological sciences, yet all these systems fall naturally into universal equivalence classes: conservative or dissipative, stable or unstable, compressible or incompressible. Predicting these classes from data remains an essential open challenge in computational physics at which existing time-series classification methods struggle. Here, we propose, `phase2vec`, an embedding method that learns high-quality, physically-meaningful representations of dynamical systems without supervision. Our embeddings are produced by a convolutional backbone that extracts geometric features from flow data and is trained to minimize a physically-informed vector field reconstruction loss. The trained architecture can not only predict the equations of unseen data, but also, crucially, learns embeddings that respect the underlying semantics of the embedded physical systems. We first validate the quality of these learned embeddings by showing that the dynamical features they encode can be used to denoise corrupted testing data. Next, we examine the extent to which the underlying physical categories of input data can be decoded from embeddings compared to standard blackbox classifiers and state-of-the-art time series classification techniques. We find that our embeddings encode important physical properties of the underlying data, including the stability of fixed points, conservation of energy, and the incompressibility of flows, with greater fidelity than competing methods. We finally apply our embeddings to the analysis of meteorological data, showing we can detect climatically meaningful features. Collectively, our results demonstrate the viability of embedding approaches for the discovery of dynamical features in physical systems.

1 INTRODUCTION

The application of deep neural networks to the prediction (Lusch et al., 2018), control Haluszczynski & Räth (2021), and basic understanding (Raissi et al., 2019) of dynamical systems has spurred important advances across the sciences, from neuroscience Sussillo et al. (2016) to physics Karniadakis et al. (2021), and from earth system science Reichstein et al. (2019) and climate Fresca et al. (2020) to computational biology Sapoval et al. (2022). However, while deep learning has already contributed significantly to the analysis of single systems, its role in understanding the principles of dynamical systems *in general* remains somewhat limited. The ability to predict or control one system, after all, tells us little about how to do so with another. Crucially, without the ability to see the general design principles underlying the behavior of numerous dynamical systems, the problem of constructing new systems is quite difficult, and most current attempts rely on exhaustive search through system parameters (Hart et al., 2012; Scholes et al., 2019).

A machine learning framework that could elucidate the physical similarity among numerous systems having different governing equations and parameters would be an important first step in this direction. But progress has been limited, largely because representations of even a single dynamical system are necessarily high-dimensional (many initial conditions over time) and the problem of understanding single systems in detail is already both daunting and useful. The few existing approaches to this problem focus mostly on the limited setting of rapid adaptation to new parameter regimes for governing equations Kirchmeyer et al. (2022) as opposed to learning representations that generalize widely among different systems.

To address this challenge, we propose `phase2vec`, a dynamical systems embedding model which learns high-quality, low-dimensional representations of dynamical systems which encode meaningful physical properties of the underlying system. Similarly to many word embeddings approaches (Mikolov et al., 2013), which approximate the meaning of words using statistical regularity instead of formal semantics, our dynamical embeddings seek to model the "semantics" of dynamical systems from data instead of via analytical investigation. `phase2vec` is so-called since it is based on convolutional features extracted from the vector field representing the dynamics in phase space of input data. Like other embedding methods, we train our system on an auxiliary task, in our case involving equation reconstruction. We show that this auxiliary task, combined with a physics-informed loss, forces the network to learn dynamically meaningful embeddings.

The main contributions of this paper are:

1. The proposal of `phase2vec`, a novel neural network and unsupervised loss which can be used to learn low-dimensional representations of dynamical systems.

2. A demonstration that these embeddings can be used to decode the governing equations of testing data, recover sparse underlying models, and denoise input data in a way that preserves dynamical characteristics.

3. A series of experiments showing that important physical properties (conservation of energy, incompressibility, class of dynamical stability) can be decoded from `phase2vec` embeddings with much greater accuracy than both blackbox classifiers and contemporary time series classification approaches.

4. An application of `phase2vec` to the analysis of atmospheric data, demonstrating that the embeddings capture meaningful structure in real data, such as the characteristics of distinct temperature zones.

2   RELATED WORK

Data-driven discovery of governing equations   There is a large body of work concerning the discovery of governing equations of single systems from time series data (reviewed in Timme & Casadiego (2014)). Early work by Bongard & Lipson (2007); Schmidt & Lipson (2009) fit the coefficients of an explicit basis of polynomials to time series data using least squares, an approach which was modernized in the sparse reconstruction method of SINDy Brunton et al. (2016) and its autoencoder formulation in Champion et al. (2019). Applied Koopman theory, on the other hand, uses time series data to approximate the action of a non-linear dynamical system on its phase space as a linear operator (the Koopman operator) acting on a potentially infinite space of measurement functions Brunton et al. (2021). Other approaches eschew the explicit modeling of dynamical equations in favor of implicitly representing the dynamical transition as the discrete-time action of an autoencoder on state samples. For example, Lusch et al. (2018) approximated the action of the Koopman operator in such a set-up, while Bramburger et al. (2021) used an autoencoder to learn topologically conjugate representations of unseen equations. Instead of learning a discrete-time representation of a dynamical system in the form of a feedforward neural network, other approaches have explicitly modeled continuous-time dynamics with recurrent neural networks Sussillo et al. (2016); Raza & Alam (2016) or neural ODEs Chen et al. (2018).

Generalization of physical systems   While there has been some progress in the estimation of equations for single systems, inferring the dynamics of multiple systems simultaneously has proven more challenging. Brown & Sethna (2003). The manifold boundary approximation (MBA) method of Quinn et al. (2021) has been used in numerous cases Transtrum & Qiu (2014) to estimate the minimal mechanisms underlying behavioral archetypes within a single parameterized dynamical family (e.g. a family Ising models parameterized by coupling strength Teoh et al. (2020)). A more recent line of work Clavera et al. (2019); Lee et al. (2020); Yin et al. (2021); Kirchmeyer et al. (2022); Wang et al. (2022) has taken an adaptation approach whereby the representation of dynamics observed during a training period can be quickly updated to a new setting in which the parameters of the underlying system have changed. Here, too, the focus is the generalization to new parameter regimes of the same underlying equation. To our knowledge, the problem of learning generalizable representations of dynamical models whose functional forms vary widely (e.g. $> 1 \times 10^7$ equations modulo parameter values) has not been systematically addressed.

Vector-field-based approaches All of the above approaches have taken time series as their input data. Vector-fields representations can be generated by underlying models or equations, or estimated from time series, either by naive binning of many trajectories associated with different initial conditions Sneed & Komaee (2021) or by fitting a statistical model (e.g. Qiu et al. (2022)). Among the approaches which rely on vector field data is Kastrati & Imran (2019), which provided theoretical guarantees for the performance of vector field classifiers. Others sought to design vector fields subject to the constraints on the number, location, and stability of fixed points which are mathematically imposed by Conley index theoryConley (1978), later applying these designed fields in computer graphics and computational biology Zhang et al. (2006); Chen et al. (2008).

Data-driven coarse-graining The existence of high-dimensionality in many problems in exact sciences motivated the development of data-driven coarse-grained models. Such approaches aim at constructing a lower-dimensional model which is practical to integrate in time and can adequately encode meaningful features and predict the outputs of interest, such as future dynamics or response to perturbations. Data-driven strategies use simulations of the original, fine-grained, or full-order system of equations in order to learn (or infer) the correct coarse-grained representation of the data Krumscheid et al. (2015); Nicolaou et al. (2021); Bakarji & Tartakovsky (2021). Many of these are model-based predictions looking to recover the dynamical governing equations of the system. A generalization of this includes adding a model selection step prior to the fit of parameters Krumscheid et al. (2015).

Model reduction across systems In many real-world systems, there exists a low-dimensional representation of the data, a model, which captures essential properties of its behavior. The fact that most complex models exhibit a hierarchy of parameter importance was termed as *sloppiness* Brown & Sethna (2003), and the hierarchical model manifold of predictions is deemed a *hyperribbon* Amari & Nagaoka (2000); Amari (2016); Nielsen (2020). The emergent simplicity as represented by the effectively low dimensional *hyperribbon* explains why only a few parameter combinations matter for the behavior of complex systems. This understanding has broad implications in a variety of fields. For example, in Biology the implications of sloppiness were studied for evolvability and robustness of complex biological systems Draghi et al. (2010), and more recent work has examined similar connections in neuroscience O'Leary et al. (2013). Here, we take a machine learning approach for the extraction of reduced dynamical model encodings.

3 METHODOLOGY

Let $\mathcal{D} = \{F_i\}_{i=1}^m$ be a set of continuously differentiable, parameterized vector fields on the $\mathbb{R}^2$ each with parameter vector Ξ. Each $F \in \mathcal{D}$ is associated to a planar dynamical system via

$$\dot{X} = F(X; \Xi). \tag{1}$$

When F is identified with a dynamical system in this manner, we refer to $\mathbb{R}^2$ as the system's *phase space* and the value $X(t)$ of a solution to Eq. 1 as the *state* of the system at time t.

Our goal is to learn a γ-parameterized embedding map $z_i = \psi(F_i; \gamma)$ for each $F_i \in \mathcal{D}$ so that the $z_i \in \mathbb{R}^d$ capture the principal factors of variation in the underlying physical system given by Eq. 1 (Fig. 1). We reason that a good map, ψ, is one that produces embeddings, z_i, of testing data from which governing equations can be faithfully decoded. Much in the way word embeddings are learned by optimizing an embedding map on a self-supervised auxiliary task of context prediction (Mikolov et al., 2013), we train our embedding map on a self-supervised auxiliary task of governing equation prediction.

3.1 ARCHITECTURE

In practice, we evaluate each F on a (potentially different) $n \times n$ lattice on the phase space so that $\mathcal{D}$ is a set of $2 \times n \times n$ arrays whose components indicate the two-dimensional velocity of equation 1 at a discrete locaiton. We instantiate the map, ψ, as three-layer convolutional architecture terminating in one fully-connected layer mapping convolutional features to the d-dimensional phase2vec embedding space (for architectural details, see Sec. A.1).

Figure 1: *phase2vec pipeline*. `phase2vec` learns high-quality embeddings of dynamical systems from phase space data. An input vector field (here represented as a stream plot) is first passed through a series of convolutional, rectification, and downsampling layers. Terminal convolutional features are aggregated in a relatively low-dimensional ($d = 100$) layer before being mapped to a set of estimated coefficients $\hat{\Xi}$. These coefficients are used as weight for a dictionary of polynomials in two variables and the resulting linear combination (depicted transposed above) comprises the estimated governing equation, $\hat{f}(x, \hat{\Xi})$, which results in the corresponding reconstructed vector field.

To compute predicted equations, embeddings are passed through a two-layer multi-layer perceptron which maps the embedding space to a vector of estimated coefficients for Eq. 1, Ξ_{recon}. These coefficients are used to form linear combinations with a set of basis functions $\Phi(X) = [\Phi_1(X), \ldots, \Phi_p(X)]$. The reconstructed equation is taken as

$$\dot{X}_{recon} = \Phi(X)\Xi_{recon} = F_{recon}(X, \Xi_{recon}) \tag{2}$$

For a multi-index, $0 \leq |\alpha| \leq 3$, we set $\Phi_\alpha(X) = X^\alpha$ so that the dictionary comprises the ten possible unit-coefficient monomials of two variables up to cubic degree. These are predicted for each of the two phase dimensions so that $\hat{\Xi} \in \mathbb{R}^{10 \times 2}$ (Fig. 1).

3.2 Loss and Training

Following Champion et al. (2019), we train our system with a loss that balances reconstruction fidelity with sparsity of the underlying equation. However, we also normalize our reconstruction loss in a manner that emphasizes special "skeletal" points of the dynamics. In particular, we take our reconstruction loss to be

$$\mathcal{L}_1(\dot{X}, \dot{X}_{recon}) = \frac{\|\dot{X} - \dot{X}_{recon}\|_2}{\|\dot{X}\|_2 + \epsilon}, \tag{3}$$

for a small corrective constant, ϵ. Here, $\mathcal{L}_1$ is especially large where $\dot{X}$ vanishes, lending special emphasis to fixed points and "slow" regions in the dynamics, which are often the locus of important dynamical phenomena (Tredicce & Lippi, 2004). We use a simple sparsity loss $\mathcal{L}_2(\dot{X}) = \|\Xi_{recon}(\dot{X})\|_1$ and train $\psi(\dot{X}, \gamma)$ by computing

$$\gamma^* = \arg\min_{\gamma} \mathbb{E}_{F \in \mathcal{D}}\left[\mathcal{L}(\dot{X}, \dot{X}_{recon})\right] \tag{4}$$

for $\mathcal{L} = \mathcal{L}_1 + \beta\mathcal{L}_2$ with sparsity regularizer β. Note that the loss measures the discrepancy between the true and reconstructed vector fields and not between the true and reconstructed parameters.

The training set $\mathcal{D}$ was a collection of polynomial ODEs generated from the dictionary Φ with coefficients that were 0 with probability .75 and were otherwise sampled uniformly on $[-3, 3]$. Network hyperparameters were selected to minimize validation loss on two data sets, one measuring generalization to new parameter regimes for the training set and another measuring generalization to new functional forms not observed during training. For the former, we simply used a set of equations sampled from the same distribution generating $\mathcal{D}$ but having a disjoint set of coefficients, and for the latter, we used a collection of real-world systems ranging from the FitzHugh-Nagumo neuron

(FitzHugh, 1955) to the Lotka Volterra model (Freedman, 1980). The functional form of equations from this latter set were systematically excluded from the training set. For example, if a testing system had the form $\dot{x}_1 = a + bx_1^2$; $\dot{x}_2 = cx_1x_2$, then this equation was never used generate a training datum for any a, b, c (see Sec. A.2).

4 RESULTS

Generalization to held-out systems On the auxiliary task of equation prediction, we found `phase2vec` performance was comparable to that of a traditional, per-equation, sparse fitting method, LASSO (Tibshirani, 1996), even on testing data (Table 1). Again, none of the functional forms of the testing systems were observed during training. One system, the simple oscillator, is not even expressible by a finite combination of elements in Φ and is nevertheless where `phase2vec` has its largest performance advantage. We also confirmed that we could decode the classes of testing equations from `phase2vec` by training a cross-validated logistic regressor on embeddings, which achieved an F1 score of .814 (see Sec. A.3 for details).

	Saddle-Node (1)	Pitchfork (1)	Transcritical (1)	Simple Oscillator (1)	Lotka-Volterra (1)
LASSO	4.34×10^{-1}	7.55×10^{-4}	4.13×10^{-4}	5.33×10^{0}	4.31×10^{-1}
Phase2Vec	8.00×10^{-2}	9.64×10^{-2}	9.84×10^{-1}	4.36×10^{-1}	4.89×10^{-1}
	Homoclinic (1)	**Van Der Pol** (1)	**Selkov** (2)	**FitzHugh-Nagumo** (4)	**Polynomial** (20)
LASSO	9.40×10^{-4}	2.61×10^{0}	1.02×10^{0}	2.04×10^{-2}	5.26×10^{-1}
Phase2Vec	1.55×10^{-1}	8.93×10^{-1}	5.12×10^{-1}	9.11×10^{-1}	1.47×10^{-1}

Table 1: Reconstruction loss according to Eq. 3 of vector fields generated from either LASSO Tibshirani (1996) or `phase2vec`. The systems comprise well-known, two-dimensional dynamical models used across the sciences (see Sec. A.2 for equations, parameters and generated trajectories). `phase2vec` and LASSO both used the same sparse regularization parameter of $\beta = 1 \times 10^{-3}$.

Moreover, we found that fixed-point normalization was crucial for accurate vector field reconstruction of testing data, especially for systems with complex dynamical features such as cohabitating fixed points and cycles (Fig. 2a). For example, we compared the quality of reconstruction of the normalized and un-normalized models of a dynamical system exhibiting a homoclinic bifurcation in which a limit cycle collides with a saddle point as one if its coefficients is tuned from $\xi = -1.2$ to about .8645 (see Sec. A.2). We found that un-normalized reconstruction error was, naturally, lower for the model trained with the un-normalized loss. However, the ability of the normalized model to predict the ground truth system behavior near dynamical key points (such as fixed points) was much greater than the un-normalized model.

To observe the necessity of the normalization more closely, we generated 20 reconstructions for each of the normalized and un-normalized model corresponding to 20 evenly spaced parameters, ξ, in the interval $[-1.2, -.8645]$. We then simulated 1000 trajectories from all of these systems with initial conditions sampled from a circle of radius .1 surrounding the fixed point at the origin. As the trajectories advanced in time, we measured the euclidean deviation, averaged across all initial conditions (Fig. 2a). We found that trajectories starting near the fixed point diverged much more rapidly from their true course when simulated based on the un-normalized compared to those of the normalized model. This is especially noticeable when the reconstructions are viewed as streamplots (Fig. 2a: ground truth, black border inset); blue border inset, un-normalized reconstruction, and red border inset, normalized-reconstruction). In this sense, the normalized loss is critical for inferring meaningful dynamical features while ignoring irrelevant details which influence the pure euclidean loss (details in Supp. A.1).

Furthermore, we expect meaningful and useful representations of dynamical systems to correspond to the simplest (but not too simple) system that generates the underlying input dynamics. This requirement can be translated in our case to sparse parameter representations. Therefore, we next investigated the role of sparsity in the auxiliary equation prediction task by measuring parameter reconstruction error on a new version of the classical system testing set (i.e. the systems of Table. 1) whose underlying parameters, Ξ_{pert}, were perturbed by spatially-independent, zero-mean gaussian noise with standard deviation $\sigma = .1$. We varied β from 1×10^{-3} to 1×10^{-1} in 20 steps and for each β measured the average euclidean distance between the inferred parameters and the true

(a) (b)

Figure 2: *Fixed-point normalization and sparsity. (a)* We compared the euclidean distance between trajectories simulated by a `phase2vec` model trained with (red) or without (blue) physically-informed normalization, and the ground truth model, in the case of a homoclinic oscillator (Sec. A.2). In both cases, we used the same set of 100 initial conditions spaced evenly around a circle of radius .1 surrounding the fixed point at the origin. Error for the unnormalized model was found to diverge at a much faster rate than the normalized model. Relative performance near the fixed point is evident from stream plot reconstructions (black inset: ground true; blue inset: unnormalized; red inset: normalized.) *(b)* We compared parameter prediction error, $\mathcal{P}$, to the proportion of ground truth (noisy) parameters sparsified, $\mathcal{S}$, over numerous settings of the sparsity regularizer, β. For $\beta \in [1e-3, 1e-2]$ (green box), reconstruction error was relatively low despite sparsification up to 25%.

(unperturbed) parameters

$$\mathcal{P} = \mathbb{E}_\mu \left[\|\Xi_{recon} - \Xi\|_2 \right] \tag{5}$$

versus the average proportion of the perturbed parameters which were sparsified

$$\mathcal{S} = \mathbb{E}_\mu \left[\frac{\|\Xi_{recon}\|_1}{\|\Xi_{pert}\|_1} \right]. \tag{6}$$

for $\Xi_{pert} \sim \mu$. We found that the perturbed parameters could be substantially sparsified (approximately over the range $\beta \in [1e-3, 1e-2]$) without incurring a large reconstruction error (Fig. 2, green box). This provides evidence that the model has learned to distinguish between parameters that contribute significantly to dynamical structures observed in the vector field and irrelevant nuisance parameters.

Dynamically-informed reconstruction of test data The applicability of our model to real data depends strongly on our ability to produce meaningful embeddings from noisy data since vector fields are typically acquired by binning derivatives from time series datasets which can be sparse or corrupted. To evaluate this ability, we measured reconstruction performance on testing data subjected to two types of noise: one applied to the vector fields themselves and another applied to the underlying coefficients used to generate the vector fields. For the first, we used gaussian noise (.1, .2 or .3 times the ground-truth standard deviation of each vector field, F_i) or random zero-masking (10, 20 or 30% of vectors in the lattice were randomly set to the 0 vector). For the second, we used the noisy parameters Ξ_{pert} discussed above.

We found that `phase2vec` reconstructions degraded gracefully with noise and in most cases recovered the major dynamical structures of the uncorrupted data (Fig. 3). Crucially, as these were testing data, reconstruction is only possible if the embedding map, ψ, has acquired a robust and general notion of how the geometry of vectors in phase space relate to governing equations (for more reconstructions, see Sec. A.4).

Decoding the physics of embedded data Having ensured that governing equations for testing data could be decoded from `phase2vec` embeddings with performance comparable to a per-equation fitting method including during noisy conditions, we next sought to validate the quality of these embeddings on a battery of physics classification tasks. We compared `phase2vec` to three other

Figure 3: *Dynamically-informed denoising.* We examined the ability of `phase2vec` to reconstruct noisy testing data in three cases. *Column 1*: gaussian noise applied to the input vector field (depicted: $\sigma = .3$). *Column 2*: random zero masking applied to the input vector field (depicted: 10% masked). *(Column 3)*: gaussian noise applied to the true parameter vector (depicted: $\sigma = .01$).

Figure 4: *Classification performance of `phase2vec` vs. alternative representations.* We compared the ability of `phase2vec` vs alternative representations to decode meaningful physical properties of input vector fields. In classification of conservative dynamics, incompressible flows, and fixed-point stability class (see main text and Sec. A.3), `phase2vec` (green) outperformed competing representations: (1) the raw 20-dimensional parameter vector of the true equation (red), (2) the first $d = 100$ PCA eigenvalues of the input vector field (blue), and (3) features extracted using the attentional time series model TapNet (purple). Bars depict weighted F1 score and errors represent standard deviation across classes.

representations: (1) the raw parameter vector of the underlying equation, (2) the first d PCA eigenvalues of the raw vector fields where d is set to be the dimension of the embedding space, and (3) time series features extracted by TapNet (Zhang et al., 2020), a state-of-the-art time series classifier. For all representations, except for TapNet (which has a built-in MLP classifier), we trained a logistic regressor with a cross-validated ℓ_2 penalty to predict the true classes of the underlying dynamics. In this setting, we ran three experiments with classes delineated according to: (1) whether or not the dynamics respected the conservation of energy (Conservatvity; two classes), (2) whether or not the

dynamics represented an incompressible flow (Incompressibility; two classes) or (3) which type of fixed-point stability a linear system exhibited (Linear stability; five classes: stable node, unstable node, stable spiral, unstable spiral or saddle point). TapNet classifications came from voting over classifications made from 10 length-64 time-series. For training details, see Sec. A.3.

On all classification tasks, we found that `phase2vec` embeddings outperformed the competing representations (Fig. 4), achieving an F1 score of over .9. The largest comparative advantage for `phase2vec` was achieved on the five-class linear stability task, where the otherwise high-performing TapNet achieved an F1 score of under .3. The relative advantage of `phase2vec` over TapNet specifically in the cases of conservation of energy and incompressiblity demonstrates one of the important advantages of a vector-field-based approach. Namely, these are global properties of the whole system which are naturally captured by the extensive coverage of phase space a vector field provides as well as the aggregation of phase information which can be detected by convolutional features.

Embeddings of atmospheric data To investigate whether our embeddings could identify meaningful structure in real data, we computed representations of two types of meteorological data. For a first, qualitative demonstration, we computed embeddings for global wind vectors taken from Blumenthal et al. (2005). Measurements were indexed by month and by year, from 1960 to 2022, as well as by pressure (Kb). We used wind vector measurements from a fixed spatial grid comprising roughly the entire eastern hemisphere which exhibits distinct visual patterns in the form of horizontal streamlines that emerge at low pressures (Fig. 5; brown inset for .07 Kb and green inset for .01 Kb). We found that `phase2vec` embeddings could easily identify these pressure-dependent bands in the form of the red, brown, and green clusters (Fig. 5).

Figure 5: *Emergent clusters in wind vector data.* Each point is a `phase2vec` embedding of a vector field measuring wind velocity in a fixed spatial grid covering the eastern hemisphere. Different points correspond to different times and pressures. Points are colored by pressure from .01 to 1.0 Kb. Three clusters emerge, corresponding to the appearance of circumglobal streamlines (insets) as a function of pressure.

For a second, quantitative experiment, we computed embeddings for world average temperature data taken from Fick & Hijmans (2017) which were accompanied by so-called Köppen labels which indicate to which of five coarse temperature zones (tropical, arid, temperate, cold and polar) a given spatial location belongs Köppen (1884); Beck et al. (2018). The ability to make quantitative predictions about these data is especially important since they have been recently shown to produce accurate forecasts of changing climate zones as a result of global warming Beck et al. (2018).

To demonstrate the ability of `phase2vec` to classify data taken from a real physical system, we generated embeddings of random spatial crops ($153° \times 153°$ latitude by longitude) of synthesized temperature gradient fields and used them to predict each crop's expected Köppen label. As these fields were indexed by month and labels were not, we used month-averaged embeddings as our representation of a given location (much as word embedding are often averaged to make a representation of a paragraph). We found that `phase2vec` month-averaged embeddings of these data (first two PCs, Fig. 6, left) were significantly more predictive of the expected Köppen label than the raw vector field (Fig. 6 right, VF F1 testing score: $.484 \pm .011$ vs `phase2vec` F1 testing score: $.627 \pm .079$), indicating that `phase2vec` had extracted dynamical structure relevant to climate annotations.

Figure 6: *Temperature gradient embeddings and Köppen label prediction.* We computed temperature gradient embeddings over 2000 global, spatial crops over 12 months. Points are colored according to a coarse Köppen label indicating the general climatic zone which predominates in the crop. We found that these labels were more easily predicted from `phase2vec` than from raw vector fields matched for dimensionality by PCA.

5 CONCLUSION

We introduced `phase2vec`, a physics-informed convolutional network for high-quality, low-dimensional representations of dynamical systems. `phase2vec` is capable of finding meaningful, low-dimensional representations which encode dynamical features that can be used to learn governing equations and denoise dynamical data. Importantly, `phase2vec` can generalize to held-out systems and learn the underlying semantics of dynamical systems, which can be used to decode general physical characteristics from data with greater fidelity than competing methods.

A clear area for future work is the extension of our framework from the planar to the n-dimensional case. This could be accomplished in a straightforward way with the use of higher-dimensional convolutions, which have been used up to several tens of dimensions Choy et al. (2020). For higher dimensional real-world systems, like neural circuits or chemical signaling pathways, potential approaches could include other machine learning architectures which could take advantage of sparse measurements in phase space, such as graph neural networks.

The ability of `phase2vec` to encode meaningful dynamical features from data makes it a useful and promising model for the recovery of minimal physical systems and the design of new dynamical systems across biological and engineering applications.

6 REPRODUCIBILITY STATEMENT

We use the described architecture (Methods, Fig. 1) in all of our experiments with consistent random seeds allowing for reproducibility. Datasets used in the experiments are detailed in Sec. A.2.

REFERENCES

Shun-ichi Amari. *Information geometry and its applications*, volume 194. Springer, 2016.

Shun-ichi Amari and Hiroshi Nagaoka. *Methods of information geometry*, volume 191. American Mathematical Soc., 2000.

Joseph Bakarji and Daniel M Tartakovsky. Data-driven discovery of coarse-grained equations. *Journal of Computational Physics*, 434:110219, 2021.

Hylke E Beck, Niklaus E Zimmermann, Tim R McVicar, Noemi Vergopolan, Alexis Berg, and Eric F Wood. Present and future köppen-geiger climate classification maps at 1-km resolution. *Scientific data*, 5(1):1–12, 2018.

MB Blumenthal, E Grover-Kopec, M Bell, and J del Corral. The iri/ldeo climate data library: Helping people use climate data. In *AGU Fall Meeting Abstracts*, volume 2005, pp. IN32A–05, 2005.

Josh Bongard and Hod Lipson. Automated reverse engineering of nonlinear dynamical systems. *Proceedings of the National Academy of Sciences*, 104(24):9943–9948, 2007.

Jason J Bramburger, Steven L Brunton, and J Nathan Kutz. Deep learning of conjugate mappings. *Physica D: Nonlinear Phenomena*, 427:133008, 2021.

Kevin S Brown and James P Sethna. Statistical mechanical approaches to models with many poorly known parameters. *Phys. Rev. E Stat. Nonlin. Soft Matter Phys.*, 68(2 Pt 1):021904, 2003.

Steven L Brunton, Joshua L Proctor, and J Nathan Kutz. Discovering governing equations from data by sparse identification of nonlinear dynamical systems. *Proc. Natl. Acad. Sci. U. S. A.*, 113(15): 3932–3937, 2016.

Steven L Brunton, Marko Budišić, Eurika Kaiser, and J Nathan Kutz. Modern koopman theory for dynamical systems. *arXiv preprint arXiv:2102.12086*, 2021.

Kathleen Champion, Bethany Lusch, J Nathan Kutz, and Steven L Brunton. Data-driven discovery of coordinates and governing equations. *Proc. Natl. Acad. Sci. U. S. A.*, 116(45):22445–22451, 2019.

Guoning Chen, Konstantin Mischaikow, Robert S Laramee, and Eugene Zhang. Efficient morse decompositions of vector fields. *IEEE Transactions on Visualization and Computer Graphics*, 14 (4):848–862, 2008.

Ricky TQ Chen, Yulia Rubanova, Jesse Bettencourt, and David K Duvenaud. Neural ordinary differential equations. *Advances in neural information processing systems*, 31, 2018.

Christopher Choy, Junha Lee, René Ranftl, Jaesik Park, and Vladlen Koltun. High-dimensional convolutional networks for geometric pattern recognition. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 11227–11236, 2020.

Ignasi Clavera, Anusha Nagabandi, Simin Liu, Ronald S. Fearing, Pieter Abbeel, Sergey Levine, and Chelsea Finn. Learning to adapt in dynamic, real-world environments through meta-reinforcement learning. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=HyztsoC5Y7.

Charles C Conley. *Isolated invariant sets and the Morse index*. American Mathematical Soc., 1978.

Jeremy A Draghi, Todd L Parsons, Günter P Wagner, and Joshua B Plotkin. Mutational robustness can facilitate adaptation. *Nature*, 463(7279):353–355, 2010.

Stephen E Fick and Robert J Hijmans. Worldclim 2: new 1-km spatial resolution climate surfaces for global land areas. *International journal of climatology*, 37(12):4302–4315, 2017.

Richard FitzHugh. Mathematical models of threshold phenomena in the nerve membrane. *The bulletin of mathematical biophysics*, 17(4):257–278, 1955.

Herbert I Freedman. *Deterministic mathematical models in population ecology*, volume 57. Marcel Dekker Incorporated, 1980.

Stefania Fresca, Andrea Manzoni, Luca Dedè, and Alfio Quarteroni. Deep learning-based reduced order models in cardiac electrophysiology. *PloS one*, 15(10):e0239416, 2020.

Alexander Haluszczynski and Christoph Räth. Controlling nonlinear dynamical systems into arbitrary states using machine learning. *Scientific reports*, 11(1):1–8, 2021.

Yuval Hart, Yaron E Antebi, Avraham E Mayo, Nir Friedman, and Uri Alon. Design principles of cell circuits with paradoxical components. *Proceedings of the National Academy of Sciences*, 109 (21):8346–8351, 2012.

George Em Karniadakis, Ioannis G Kevrekidis, Lu Lu, Paris Perdikaris, Sifan Wang, and Liu Yang. Physics-informed machine learning. *Nature Reviews Physics*, 3(6):422–440, 2021.

Zenun Kastrati and Ali Shariq Imran. Performance analysis of machine learning classifiers on improved concept vector space models. *Future Generation Computer Systems*, 96:552–562, 2019.

Matthieu Kirchmeyer, Yuan Yin, Jeremie Dona, Nicolas Baskiotis, Alain Rakotomamonjy, and Patrick Gallinari. Generalizing to new physical systems via context-informed dynamics model. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 11283–11301. PMLR, 17–23 Jul 2022. URL https://proceedings.mlr.press/v162/kirchmeyer22a.html.

Wladimir Köppen. Die wärmezonen der erde, nach der dauer der heissen, gemässigten und kalten zeit und nach der wirkung der wärme auf die organische welt betrachtet. *Meteorologische Zeitschrift*, 1(21):5–226, 1884.

S Krumscheid, M Pradas, GA Pavliotis, and S Kalliadasis. Data-driven coarse graining in action: Modeling and prediction of complex systems. *Physical Review E*, 92(4):042139, 2015.

Kimin Lee, Younggyo Seo, Seunghyun Lee, Honglak Lee, and Jinwoo Shin. Context-aware dynamics model for generalization in model-based reinforcement learning. In *International Conference on Machine Learning*, pp. 5757–5766. PMLR, 2020.

Bethany Lusch, J Nathan Kutz, and Steven L Brunton. Deep learning for universal linear embeddings of nonlinear dynamics. *Nat. Commun.*, 9(1):4950, 2018.

Tomás Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space. In *1st International Conference on Learning Representations, ICLR 2013, Scottsdale, Arizona, USA, May 2-4, 2013, Workshop Track Proceedings*, 2013. URL http://arxiv.org/abs/1301.3781.

Zachary Nicolaou, Matthew Kafker, Steven Brunton, and J Nathan Kutz. Data-driven coarse graining of many-body systems. In *APS Division of Fluid Dynamics Meeting Abstracts*, pp. M31–004, 2021.

Frank Nielsen. An elementary introduction to information geometry. *Entropy*, 22(10):1100, 2020.

Timothy O'Leary, Alex H Williams, Jonathan S Caplan, and Eve Marder. Correlations in ion channel expression emerge from homeostatic tuning rules. *Proceedings of the National Academy of Sciences*, 110(28):E2645–E2654, 2013.

Xiaojie Qiu, Yan Zhang, Jorge D Martin-Rufino, Chen Weng, Shayan Hosseinzadeh, Dian Yang, Angela N Pogson, Marco Y Hein, Kyung Hoi Joseph Min, Li Wang, et al. Mapping transcriptomic vector fields of single cells. *Cell*, 185(4):690–711, 2022.

Katherine N Quinn, Michael C Abbott, Mark K Transtrum, Benjamin B Machta, and James P Sethna. Information geometry for multiparameter models: New perspectives on the origin of simplicity. *arXiv preprint arXiv:2111.07176*, 2021.

Maziar Raissi, Paris Perdikaris, and George E Karniadakis. Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational physics*, 378:686–707, 2019.

Khalid Raza and Mansaf Alam. Recurrent neural network based hybrid model for reconstructing gene regulatory network. *Computational biology and chemistry*, 64:322–334, 2016.

Markus Reichstein, Gustau Camps-Valls, Bjorn Stevens, Martin Jung, Joachim Denzler, Nuno Carvalhais, et al. Deep learning and process understanding for data-driven earth system science. *Nature*, 566(7743):195–204, 2019.

Nicolae Sapoval, Amirali Aghazadeh, Michael G Nute, Dinler A Antunes, Advait Balaji, Richard Baraniuk, CJ Barberan, Ruth Dannenfelser, Chen Dun, Mohammadamin Edrisi, et al. Current progress and open challenges for applying deep learning across the biosciences. *Nature Communications*, 13(1):1–12, 2022.

Michael Schmidt and Hod Lipson. Distilling free-form natural laws from experimental data. *science*, 324(5923):81–85, 2009.

Natalie S Scholes, David Schnoerr, Mark Isalan, and Michael PH Stumpf. A comprehensive network atlas reveals that turing patterns are common but not robust. *Cell systems*, 9(3):243–257, 2019.

Terry-Ann Sneed and Arash Komaee. Nonparametric reconstruction of vector fields from noisy observations of their flow curves. In *2021 American Control Conference (ACC)*, pp. 3969–3974. IEEE, 2021.

David Sussillo, Rafal Jozefowicz, LF Abbott, and Chethan Pandarinath. Lfads-latent factor analysis via dynamical systems. *arXiv preprint arXiv:1608.06315*, 2016.

Han Kheng Teoh, Katherine N Quinn, Jaron Kent-Dobias, Colin B Clement, Qingyang Xu, and James P Sethna. Visualizing probabilistic models in minkowski space with intensive symmetrized kullback-leibler embedding. *Physical Review Research*, 2(3):033221, 2020.

Robert Tibshirani. Regression shrinkage and selection via the lasso. *Journal of the Royal Statistical Society: Series B (Methodological)*, 58(1):267–288, 1996.

Marc Timme and Jose Casadiego. Revealing networks from dynamics: an introduction. *Journal of Physics A: Mathematical and Theoretical*, 47(34):343001, 2014.

Mark K Transtrum and Peng Qiu. Model reduction by manifold boundaries. *Phys. Rev. Lett.*, 113 (9):098701, 2014.

J.R. Tredicce and G.L. Lippi. Critical slowing down at a bifurcation. *American Journal of Physics*, 72(799), 2004.

Jindong Wang, Cuiling Lan, Chang Liu, Yidong Ouyang, Tao Qin, Wang Lu, Yiqiang Chen, Wenjun Zeng, and Philip Yu. Generalizing to unseen domains: A survey on domain generalization. *IEEE Transactions on Knowledge and Data Engineering*, 2022.

Yuan Yin, Ibrahim Ayed, Emmanuel de Bézenac, Nicolas Baskiotis, and Patrick Gallinari. Leads: Learning dynamical systems that generalize across environments. *Advances in Neural Information Processing Systems*, 34:7561–7573, 2021.

Eugene Zhang, Konstantin Mischaikow, and Greg Turk. Vector field design on surfaces. *ACM Transactions on Graphics (ToG)*, 25(4):1294–1326, 2006.

Xuchao Zhang, Yifeng Gao, Jessica Lin, and Chang-Tien Lu. Tapnet: Multivariate time series classification with attentional prototypical network. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 6845–6852, 2020.

A APPENDIX

All experiments were carried out using `pytorch` v. 1.12 using an NVIDIA RTX 3060 GPU.

A.1 ARCHITECTURE

The convolutional part of the `phase2vec` embedding pipeline consisted of three convolutional blocks, each with kernel size 3×3, stride 2×2 and 128 channels. Convolutional blocks were interleaved by `ReLU` non-lineararities and batch norm layers. The final convolutional activations were mapped by a single linear layer to a $d = 100$-dimensinoal embedding space.

To compute predicted coefficients, these embeddings were mapped by a 2-layer MLP whose hidden layers had 128 units to 20-dimensional vectors representing the 10 coefficients possible for each of the two dimensions in the ODE. MLP layers were alternated with batch norm layers as well as dropout layers whose rate we set to $p = .1$ during training.

A.2 Data, training and evaluation

A.2.1 Synthetic data

The training set $\mathcal{D}$ was a collection of polynomial ODEs generated from the dictionary Φ with coefficients that were 0 with probability $.75$ and were otherwise sampled uniformly on $[-3, 3]$ and consisted of 10k examples. For evaluation in all settings, a test set of 1000 samples was used.

Network hyperparameters were selected to minimize validation loss on two data sets:

1. *Polynomial equations*: For generalization to new parameter regimes. A set of equations sampled from the same distribution generating $\mathcal{D}$ but having a disjoint set of coefficients.

2. *Real-world systems*: For generalization to new functional forms not observed during training. The real-world systems are given by Table A.2. Parameter ranges used to generate the data are in Table A.3

All equations were recentered to be on the square $[-1, 1]^2$ on the phase plane and discrete vector fields were computed by measuring the continuous system on an evenly-spaced grid of 64×64 points.

Name	Equation	Class labels
Saddle-node	$\dot{x_1} = a - x^2 \; \dot{x_2} = -1$	0 if $a < 0$; 1 if $a \geq 0$
Pitchfork	$\dot{x_1} = ax_1 - x_1^3; \dot{x_2} = -1$	2 if $a < 0$; 3 if $a \geq 0$
Transcritical	$\dot{x_1} = ax_1 - x_1^2; \dot{x_2} = -1$	4 if $a < 0$; 5 if $a \geq 0$
Simple Oscillator	$\dot{r} = r(a - r^2); \dot{\theta} = -1$ (polar)	6 if $a < 0$; 7 if $a \geq 0$
Lotka-Volterra	$\dot{x_1} = x_1(1 - x_2); \dot{x_2} = ax_2(x_1 - 1)$	8 for all a
Homoclinic	$\dot{x_1} = x_2; \dot{x_2} = ax_2 + x_1 - x_1^2 + x_1 x_2$	9 if $a < -.8645$; 10 if $a \geq -.8645$
Van Der Pol	$\dot{x_1} = x_2; \dot{x_2} = a(1 - x_1^2)x_2 - x_1$	11 for all a
Selkov	$\dot{x_1} = x_1 + ax_2 + x_1^2 x_2; \dot{x_2} = b - ax_2 - x_1^2 x_2$	12 if $a < .3$; 13 if $a \geq .3$
FitzHugh-Nagumo	$\dot{x_1} = x_1 - \frac{x_1^3}{3} - x_2 + a; \dot{x_2} = \frac{1}{b}(x_1 + c - dx_2)$	14 if $a < .35$; 15 if $a \geq .35$

Table A.2: Real-world systems, their equations and class boundaries. Systems having two classes exhibit a bifurcation (i.e. the emergence of a new topological structure in the dynamics: a fixed point, limit cycle, etc.)

Name	Ranges
Saddle-node	$a \in [-1, 1]$
Pitchfork	$a \in [-1, 1]$
Transcritical	$a \in [-1, 1]$
Simple Oscillator	$a \in [-1, 1]$
Lotka-Volterra	$[-1,1]$
Homoclinic	$a \in [-1.2, -.7]$
Van Der Pol	$a \in [.1, .4]$
Selkov	$a \in [.05, .15]; b \in [.2, 1.0]$
FitzHugh-Nagumo	$a \in [.1, .5]; b \in [10, 15]; c \in [.6, .7]; d \in [.7, .8]$

Table A.3: Parameter ranges used for generating the data.

A.2.2 Real data

Global wind vectors Data was downloaded from IRI/LDEO Climate Data Library (https://iridl.ldeo.columbia.edu/). Measurements were indexed by month and by year, from 1960 to 2022, as well as by pressure (Kb). We used wind vector measurements from a fixed spatial grid comprising roughly the entire eastern hemisphere. A set of 2000 samples was used for testing.

World climate data   We took climate data from WorldClim V2 (`http://www.worldclim.org`). We used monthly temperature averages, taken over a temporal span of 1970–2000 at a spatial resolution of $0.083 \deg$. Corresponding Köppen labels were downloaded from GloH2O, Köppen-Geiger (`http://www.gloh2o.org/koppen/`). We used a coarse-grained level of the labels amounting to five temperature zones (tropical, arid, temperate, cold and polar). A set of 2000×12 (per month) samples was used for testing.

A.3   PHYSICS CLASSIFICATION

All data sets had 1000 samples with equal numbers of class exemplars. Embeddings were acquired for all data using the model trained on polynomials systems as described above. We considered three problems:

Conservativity   A conservative system represents a physical system which respects conservation of energy. Every conservative system can be represented as the gradient of a scalar field. To generate conservative systems, we first generated scalar fields by sampling the coefficients of a single polynomial equation with basis functions in Φ according to the same distribution as used to generate training coefficients. We then manually calculated gradients of these scalar fields. The opposing class were 500 samples from the training set which we ensured were not conservative. We did so by calculating the curl of each counter datum and checking it was nonzero: as for a simply connected domain, conservative system is equivalent to a system's being irrotational, i.e., having zero curl.

Incompressibility   A system is incompressible if it represents the flow of a fluid which cannot be "compressed" into or out of the phase plane. In other words, the divergence of the field is zero. To generate divergence-free fields, we first identified the phase plane with $\mathbb{C}$ so that each point (x_1, x_2) was identified with $z = x_1 + ix_2$. We again created a (holomorophic) polynomial using the same distribution on parameters given by

$$f(z) = f(x_1 + ix_2) = a + ib \tag{7}$$

Define the vector field $\frac{df}{dz} = v - iw$ where

$$v = \frac{\partial a}{\partial x_1} \tag{8}$$

and

$$w = \frac{\partial a}{\partial x_2} \tag{9}$$

The component b automatically satisfies the equivalence of mixed partials:

$$\frac{\partial^2 b}{\partial x_1 \partial x_2} = \frac{\partial^2 b}{\partial x_2 \partial x_1} \tag{10}$$

which gives $\nabla \dot{v} = 0$ and so v was taken as our divergence-free, incompressible system.

Linear stability   A linear planar system $\dot{x} = Ax$ exhibits a stable node, unstable node, stable spiral, unstable spiral or saddle point as a function of the trace and determinant of A. We randomly sampled A until 200 exemplars of each stability class were acquired.

For each task we computed the relevant embeddings and then trained a logistic regressor on 80% of the data, the rest of which was held out for testing, using a stratified train-test split. An ℓ_2 penalty was cross-validated using leave-one-out cross-validation on validation data split from the training set. We searched for an optimal regularizer over 11 values spread logarithmically between 1×10^{-5} and 1×10^5. For multi-class settings, we used a one-versus-rest scheme.

A.4   VECTOR FIELD RECONSTRUCTIONS

We provide `phase2vec` reconstructions over test data. Starting with a demonstration of the different classes, (1) Conservative (Fig. A.7) (2) Incompressible (Fig. A.8) and (3) Linear (Fig. A.9).

Next, we assess the reconstruction with added noise of two types: (1) addition of gaussian noise to the vector field (Fig. A.10) and (2) random zero masking of vectors in the lattice (Fig. A.11).

Figure A.7: Conservative dynamics, ground truth vs. reconstruction

Figure A.8: Incompressible dynamics, ground truth vs. reconstruction

Figure A.9: Linear stability dynamics, ground truth vs. reconstruction

Figure A.10: Added gaussian noise of order of .3 times the ground-truth standard deviation of each vector field, ground truth dynamics vs reconstruction

Figure A.11: Random zeroing out of 30% of the vectors, ground truth dynamics vs reconstruction