Hierarchical Lattice Layer for Partially Monotone Neural Networks

Abstract

Partially monotone regression is a regression analysis in which the target values are monotonically increasing with respect to a subset of input features. The TensorFlow Lattice library is one of the standard machine learning libraries for partially monotone regression. It consists of several neural network layers, and its core component is the lattice layer. One of the problems of the lattice layer is its requirement for a special training algorithm to satisfy monotonicity constraints. Another problem is that it cannot receive a high-dimensional input vector due to the resultant memory consumption. We propose a novel neural network layer, the hierarchical lattice layer (HLL), as an extension of the lattice layer so that we can use a standard neural network algorithm to train HLL while satisfying monotonicity constraints and so that it can receive a high-dimensional input vector. Our experiments demonstrate that HLL did not sacrifice its prediction performance on real datasets compared with the lattice layer.

1 Introduction

In regression analysis, we often have prior knowledge that the target values are monotonically increasing (or decreasing) with respect to a subset of input features. For example, when we estimate house prices from house data (e.g., the area size, the number of rooms, and the distance to the nearest supermarket), we know that the target value (i.e., the house price) is monotonically increasing with respect to some of the input features (e.g., the area size) if the other features are equal Potharst and Feelders [2002].

Partially monotone regression is a regression analysis that exploits such prior knowledge. The input of this regression is a feature vector $x \in \mathbb{R}^d$, which can be partitioned into $x = (p, q)$ such that $p \in \mathbb{R}^{d-m}$ is non-monotone features and $q \in \mathbb{R}^m$ is monotone features. The goal of this regression is to find a function f such that $f(x) = f(p, q) \in \mathbb{R}$ is monotonically increasing on q. Partially monotone regression models have advantages over the standard regression models. For example, they have a better regularization capability Dugas *et al.* [2000]; Fard *et al.* [2016]; You *et al.* [2017] and better interpretability Gupta *et al.* [2016], and they can be used for fair machine learning Wang and Gupta [2020].

Many machine learning models have been developed for partially monotone regression. For example, there are decision-tree based models Potharst and Feelders [2002], SVM models Lauer and Bloch [2008], boosting models Bartley *et al.* [2018], and random forest models Bartley *et al.* [2019]. Many popular open source libraries for gradient boosting can handle partial monotonicity (e.g., CatBoost, LightGBM, and XGBoost). See a survey paper Cano *et al.* [2019] and the references in Gupta *et al.* [2016] for comprehensive surveys.

As for neural network models, the TensorFlow Lattice library Canini *et al.* [2016]; Gupta *et al.* [2016]; You *et al.* [2017] is a standard model for partially monotone regression, and it is publicly available

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

as an open source library. It consists of several neural network layers, and its core component is the lattice layer Gupta *et al.* [2016]. Hereafter, we call this layer TL Lattice. TL Lattice constructs a hypercube with k^d vertices as an internal structure, where $k \geq 2$ is an integer hyperparameter for specifying the granularity of the hypercube, and d is the dimension of the input vector $x \in \mathbb{R}^d$. One of its problems is its memory consumption in storing k^d parameters, and therefore, it cannot receive a high-dimensional input vector with a large d. This means that we need to combine multiple neural network layers to handle an input vector with a large d (e.g., by using small lattices Canini *et al.* [2016]; You *et al.* [2017]). Another problem is its requirement for a special algorithm to train it to handle monotonicity constraints, which means that we cannot use a standard neural network algorithm to train it. The details of the special training algorithms used for the TensorFlow Lattice library are described in Gupta *et al.* [2016]; You *et al.* [2017].

In this paper, we propose a novel neural network layer, the *hierarchical lattice layer* (HLL), as an extension of TL Lattice. The internal structure of HLL is similar to that of TL Lattice in that both layers construct hypercube structures. However, they are different in several aspects. For example, HLL constructs an m-dimensional hypercube, whereas TL Lattice constructs a d-dimensional hypercube, where d and m are the dimensions of the input vector $x \in \mathbb{R}^d$ and its monotone feature $q \in \mathbb{R}^m$, respectively. Since m is usually a small integer in practice, the number of vertices k^m in HLL is significantly smaller than that of TL Lattice (i.e., k^d). Therefore, HLL can receive a high-dimensional input vector as long as m is small. For another example, the parameterization of HLL is designed to represent a class of partially monotone functions (i.e., HLL cannot represent a function $f(p, q)$ that is not monotonic on q) by using the hierarchical relationship between the vertices of the hypercube. Therefore, the internal structure of HLL ensures partial monotonicity regardless of the training algorithm used. In contrast, the internal structure of TL Lattice is a lookup table, and the table itself can represent any function $f(p, q)$, which means that the parameterization of TL Lattice is not designed to satisfy monotonicity constraints. Therefore, TL Lattice requires a special algorithm to train its parameters to ensure these constraints.

In our experiments, we demonstrate that HLL did not sacrifice its prediction performance compared with TL Lattice. Note that HLL is designed to satisfy monotonicity constraints and is not designed to improve the prediction performance compared with TL Lattice. Therefore, the purpose of our experiments was not to show improvements in prediction performance compared with TL Lattice but to show that HLL did not sacrifice the prediction performance to satisfy the constraints. In addition, we also demonstrate that we could use HLL for high-dimensional input vectors with a small m.

2 Partially Monotone Regression

Regression analysis is a method for finding a function $f : \mathbb{R}^d \to \mathbb{R}$ such that $f(x_i)$ approximates y_i for a given dataset $D = \{(x_i, y_i)\}_{i=1}^{n}$, where $x_i \in \mathbb{R}^d$ is a feature vector, and $y_i \in \mathbb{R}$ is a target value. In partially monotone regression, we assume that we can partition a feature vector $x \in \mathbb{R}^d$ into $x = (p, q) \in \mathbb{R}^{d-m} \times \mathbb{R}^m$, where $0 < m < d$, such that $f(x) \in \mathbb{R}$ is monotonic on q. A function $f(x)$ for $x = (p, q)$ is *monotonic* on q if this inequality holds:

$$f(p, q) \leq f(p, q'), \ \forall p, \ \forall q \leq q',$$

where $q \leq q'$ denotes the inequality for all the elements (i.e., $q[i] \leq q'[i]$ for all $1 \leq i \leq m$, where $q[i]$ denotes the i-th element of q).

Partially monotone regression has many applications in various fields, and it has important applications even if $m = 1$. An example of such application with $m = 1$ is quantile regression Koenker and Bassett [1978]; Zhou *et al.* [2020], which is used to estimate the conditional quantiles of a target variable distribution. We show that the output $q(x) = q(x', \tau)$ of the quantile regression for an input $x = (x', \tau)$ is monotonic on τ, where $x' \in \mathbb{R}^{d-1}$ is a feature vector, and $\tau \in [0, 1]$ is a quantile level. In quantile regression, we estimate the quantile value $q(x', \tau)$ defined by

$$q(x', \tau) = \inf\{y \mid F(y|X = x') \geq \tau\},$$

where $F(y|X = x')$ is the conditional cumulative distribution function of Y given $X = x'$:

$$F(y|X = x') = \Pr(Y \leq y|X = x').$$

Since the function $q(x', \tau)$ is monotonically increasing on τ, this problem can be modeled as partially monotone regression with $m = 1$.

86 Another example of partially monotone regression with $m = 1$ is survival analysis, which is also
87 known as time-to-event analysis Wang *et al.* [2019]; Rindt *et al.* [2022]. We show that the output
88 $f(x) = f(x', t)$ of the survival analysis for an input $x = (x', t)$ is monotonic on t, where $x' \in \mathbb{R}^{d-1}$
89 is a feature vector of a patient, and $t \in \mathbb{R}$ is the time of an event of interest of this patient. In survival
90 analysis, the event of interest typically corresponds to the death of a patient. The goal of the analysis
91 is to estimate a survival function $S(x', t)$ for patient x', which represents the probability that the
92 event does not occur until time t for patient x'. By setting $f(x', t) = 1 - S(x', t)$, we can model the
93 survival analysis as a partially monotone regression with $m = 1$, where the value $f(x', t)$ shows the
94 mortality rate of patient x' at time t, and $f(x', t)$ is monotonically increasing on t.

3 Hierarchical Lattice Layer

96 In this section, we explain our new *hierarchical lattice layer* (HLL) for neural network models for
97 partially monotone regression. It can be seen as an extension of TL Lattice Gupta *et al.* [2016]. Note
98 that the input of HLL is a d-dimensional vector $x \in [0, 1]^d$, and its output $f(x)$ is in $[0, 1]$, where the
99 input vector x can be partitioned into two subvectors $p \in [0, 1]^{d-m}$ and $q \in [0, 1]^m$ such that $f(x)$ is
100 monotonic on q.

3.1 Hypercube Structure

102 In HLL, we create the m-dimensional unit hypercube $[0, 1]^m$, and we decompose it into $(k_1 - 1) \times$
103 $(k_2 - 1) \times \cdots \times (k_m - 1)$ subhypercubes by dividing the interval $[0, 1]$ of the i-th dimension into
104 $k_i - 1$ subintervals, where each $k_i \geq 2$ is an integer hyperparameter that specifies the granularity of
105 the hypercube. Unless otherwise stated, we assume that $k_1 = k_2 = \cdots = k_m = k$, and the interval
106 $[0, 1]$ is divided into $k - 1$ equal-length subintervals just for simplicity. This means that the length of
107 an edge of a subhypercube is $1/(k-1)$, and we have the k^m vertices in the unit hypercube. We denote
108 the set of the vertices in the unit hypercube by V_m. In this paper, we do not distinguish between a
109 vertex $v \in V_m$ and its coordinate $q_v \in \mathbb{R}^m$. This means that the value $f(p, q_v)$ for coordinate q_v is
110 written as $f(p, v)$.

111 To construct HLL, we assume that there is a total order $\sigma = (v_0, v_1, \ldots, v_{|V_m|-1})$ of vertices in
112 V_m. We can use any total order σ to construct HLL, but unless otherwise stated, we assume that
113 σ is determined by the increasing order of the Manhattan distance (i.e., L_1 distance) from the
114 origin vertex $v_0 = (0, 0, \ldots, 0) \in [0, 1]^m$ of the unit hypercube with an arbitrary tie-breaker. See
115 Figure 1 for an example of a decomposed unit hypercube with $m = 2$ and $k = 4$ and the total order
116 $\sigma = (v_0, v_1, \ldots, v_{15})$ determined by the Manhattan distance.

117 We define the *domination* relationship between vertices in V_m, and we define the minimal dominated
118 and dominating sets based on σ.

Definition 3.1 *(Domination.) A vertex $v \in \mathbb{R}^m$ is said to dominate another vertex $u \in \mathbb{R}^m$ if and
120 only if $u[i] \leq v[i]$ holds for all $i \in \{1, 2, \ldots, m\}$ and there exists an index $i' \in \{1, 2, \ldots, m\}$ such
121 that $u[i'] < v[i']$.*

Definition 3.2 *(Minimal dominated set.) The set of vertices $L_{v,\sigma}$ denotes the minimal set of vertices
123 that satisfy three conditions (i) every vertex $u \in L_{v,\sigma}$ is dominated by v, (ii) vertex u precedes v in σ,
124 and (iii) no other vertex $w \in L_{v,\sigma}$ dominates u.*

Definition 3.3 *(Minimal dominating set.) The set of vertices $U_{v,\sigma}$ denotes the minimal set of vertices
126 that satisfy three conditions (i) every vertex $u \in U_{v,\sigma}$ dominates v, (ii) vertex u precedes v in σ, and
127 (iii) no other vertex $w \in U_{v,\sigma}$ is dominated by u.*

128 Note that the domination relation means that $f(p, u) \leq f(p, v)$ holds for any $p \in \mathbb{R}^{d-m}$ if vertex v
129 dominates vertex u. Regarding the minimal dominated and dominating sets, there can be multiple
130 minimal sets that satisfy the conditions. Throughout this paper, we fix an (arbitrary) minimal
131 dominated set $L_{v,\sigma}$ and an (arbitrary) minimal dominating set $U_{v,\sigma}$ for each $v \in \sigma$. Note also that we
132 have $|L_{v,\sigma}| \leq m$ and $|U_{v,\sigma}| = 0$ if σ is determined by the Manhattan distance. This is why we use
133 the Manhattan distance to determine σ, because we have weaker upper bounds $|L_{v,\sigma}| \leq |V_m|$ and
134 $|U_{v,\sigma}| \leq |V_m|$ if σ is an arbitrary ordering.

$v_9 = (0, 1)$ $v_{15} = (1, 1)$

$v_0 = (0, 0)$ $v_6 = (1, 0)$

Figure 1: Example of vertices in unit hypercube in HLL with $m = 2$ and $k = 4$.

Example. In the hypercube shown in Figure 1, vertex v_8 dominates the vertices in $\{v_0, v_1, v_2, v_4, v_5\}$ and is dominated by the vertices in $\{v_{11}, v_{12}, v_{13}, v_{14}, v_{15}\}$. By the definition of the minimal dominated set, we have $L_{v_8, \sigma} = \{v_4, v_5\}$ because vertices v_0, v_1, and v_2 are dominated by v_4 or v_5. By the definition of the minimal dominating set, we have $U_{v_8, \sigma} = \emptyset$ because all the vertices that dominate v_8 appear after v_8 in ordering σ.

3.2 Auxiliary Neural Network

For HLL, we construct an auxiliary neural network $g_\theta(p, v)$. To explain its construction, we define two functions $l(p, v)$ and $u(p, v)$ for $p \in \mathbb{R}^{d-m}$ and a vertex $v \in V_m$ as

$$
l(p, v) = \begin{cases} \max\limits_{v' \in L_{v, \sigma}} f(p, v') & \text{if } L_{v, \sigma} \neq \emptyset, \\ 0 & \text{if } L_{v, \sigma} = \emptyset, \end{cases} \tag{1}
$$

$$
u(p, v) = \begin{cases} \min\limits_{v' \in U_{v, \sigma}} f(p, v') & \text{if } U_{v, \sigma} \neq \emptyset, \\ 1 & \text{if } U_{v, \sigma} = \emptyset, \end{cases} \tag{2}
$$

where $L_{v, \sigma}$ and $U_{v, \sigma}$ are the minimal dominated and dominating sets, respectively. Note that $l(p, v)$ and $u(p, v)$ are defined so as to satisfy the inequality $l(p, v) \leq f(p, v) \leq u(p, v)$. By using this inequality, we define a third function $g(p, v)$ as a function that satisfies

$$
f(p, v) = (1 - g(p, v))l(p, v) + g(p, v)u(p, v). \tag{3}
$$

Since we have $l(p, v) \leq f(p, v) \leq u(p, v)$, there always exists $0 \leq g(p, v) \leq 1$ that satisfies Eq. (3). We show an example of the definitions of the three functions for a simple case with $m = 1$ and $k = 3$ in Appendix A.

The auxiliary neural network $g_\theta(p, v)$ in HLL is trained to learn the function $g(p, v)$. To satisfy the constraint $0 \leq g(p, v) \leq 1$, we use the sigmoid function in the last layer of $g_\theta(p, v)$ as the activation function. Note that, by the definitions of the three functions $l(p, v)$, $u(p, v)$, and $g(p, v)$, we can compute $f(p, v)$ for any p and v by using $g_\theta(p, v)$.

3.3 Inference and Training Algorithms

The inference algorithm of HLL is similar to TL Lattice, and Figure 2 illustrates it. Given an input $x = (p, q)$, we first calculate $f(p, v)$ for all $v \in V_q$ by using $g_\theta(p, v)$, where $V_q \subseteq V_m$ is the set of the vertices that surround q in the hypercube. Then, we estimate $f(p, q)$ as an interpolation of the values $f(p, v)$ for $v \in V_q$. As for the interpolation algorithm, we can use multilinear interpolation or simplex interpolation Gupta *et al.* [2016]. Note that the size of V_q depends on the interpolation algorithm (i.e., $|V_q| = 2^m$ if we use multilinear interpolation, and $|V_q| = O(m \log m)$ if we use simplex interpolation).

The training algorithm of HLL is the same as that of the standard neural network layer. For example, if we train a neural network model that consists of a single HLL, the parameters of HLL (i.e. the parameters θ of the auxiliary neural network g_θ) are trained to minimize the empirical loss

$$
\min_{g_\theta} \sum_{i=1}^{n} \ell(y_i, f(x_i)),
$$

Figure 2: Illustration of inference algorithm of HLL for case with $m = 3$, and q is surrounded by vertices $V_q = \{v_1, v_2, \ldots, v_8\}$.

where $\{(x_i, y_i)\}_{i=1}^n$ is a dataset, $f(x_i)$ is the output of the inference algorithm of HLL for input x_i, and ℓ is a loss function.

3.4 Partial Monotonicity

As already proven in Gupta *et al.* [2016], the function $f(p, q)$ computed by an interpolation algorithm satisfies monotonicity constraints if the values corresponding to the vertices of the hypercube satisfy the constraints. Therefore, we show that we have $f(p, u) \leq f(p, v)$ for any pair of vertices $u, v \in V_m$ such that u is dominated by v. Note that this lemma holds for any vertex ordering σ and is not restricted to the vertex ordering determined by the Manhattan distance.

Lemma 3.4 *In HLL, $f(p, u) \leq f(p, v)$ holds for any $p \in \mathbb{R}^{d-m}$ and any pair of vertices $u, v \in V_m$ such that u is dominated by v*

Proof. Suppose that u precedes v in the total ordering σ. By the definition of the minimal dominated set, there exists a sequence of vertices $u_0(= u), u_1, u_2, \ldots, u_J(= v)$ such that $u_{j-1} \in L_{u_j, \sigma}$ holds for $j = 1, 2, \ldots, J$. Since $u_{j-1} \in L_{u_j, \sigma}$, we have $f(p, u_{j-1}) \leq l(p, u_j) \leq f(p, u_j)$ by Eq. (1). Hence, we have $f(p, u) = f(p, u_0) \leq f(p, u_1) \leq \cdots \leq f(p, u_J) = f(p, v)$.

Similarly, suppose that v precedes u in the total ordering σ. By the definition of the minimal dominating set, there exists a sequence of vertices $v_0(= v), v_1, v_2, \ldots, v_J(= u)$ such that $v_{j-1} \in U_{v_j, \sigma}$ holds for $j = 1, 2, \ldots, J$. Since $v_{j-1} \in U_{v_j, \sigma}$, we have $f(p, v_{j-1}) \geq u(p, v_j) \geq f(p, v_j)$ by Eq. (2). Hence, we have $f(p, v) = f(p, v_0) \geq f(p, v_1) \geq \cdots \geq f(p, v_J) = f(p, u)$. $\qquad\square$

3.5 Complexity Analysis

We show that the time complexity of the inference algorithm of HLL is $O((T(g_\theta) + m)|V_m|)$, where $T(g_\theta)$ is the time complexity of computing $g_\theta(p, v)$ for an input $(p, v) \in \mathbb{R}^{d-m} \times \mathbb{R}^m$. First, the time complexity to compute $f(p, v)$ for all vertices $v \in V_m$ is $O((T(g_\theta) + m)|V_m|)$ since it takes $O(T(g_\theta) + |L_{v,\sigma}| + |U_{v,\sigma}|)$ time to compute $f(p, v)$ for a single vertex $v \in V_m$, and we have $|L_{v,\sigma}| + |U_{v,\sigma}| \leq m$. Then, the time complexity for the interpolation algorithm is $O(2^m)$ if we use multilinear interpolation and $O(m \log m)$ if we use simplex interpolation Gupta *et al.* [2016]. Since we have $2^m \leq |V_m|$, the time complexity for the interpolation algorithm is smaller than that for the computation of $f(p, v)$. Hence, the overall time complexity remains $O((T(g_\theta) + m)|V_m|)$. If we can assume that m is a small integer (i.e., m is a constant), the computation time for inference can be written simply as $O(T(g_\theta))$. Note that, if the time complexity $T(g_\theta)$ is a linear function on d, the time complexity of the inference algorithm for HLL is smaller than that for TL Lattice because the inference algorithm of TL Lattice takes $O(2^d)$ and $O(d \log d)$ times if we use multilinear interpolation and simplex interpolation, respectively Gupta *et al.* [2016].

The space complexity of HLL is $O(|g_\theta| + m|V_m|)$ if the vertex ordering σ is determined by the Manhattan distance, where we denote the size of the auxiliary neural network $g_\theta(p, v)$ by $|g_\theta|$, and the $O(m|V_m|)$ term is the space required to store $L_{v,\sigma}$ and $U_{v,\sigma}$ for all $v \in V_m$. Note that, if we use an arbitrary vertex ordering σ, we require $O(|V_m|^2)$ space to store $L_{v,\sigma}$ and $U_{v,\sigma}$ for all $v \in V_m$ because we know only that $|L_{v,\sigma}| \leq |V_m|$ and $|U_{v,\sigma}| \leq |V_m|$. Since $|V_m|^2$ is much larger than $m|V_m|$, we recommend using the Manhattan distance to determine σ in HLL.

4 Experiments

In our experiments, we demonstrate that HLL did not sacrifice its prediction performance compared with TL Lattice. Note that HLL is designed to satisfy monotonicity constraints and is not designed to improve the prediction performance compared with TL Lattice. Therefore, the purpose of our experiments was not to show such improvements but to show that HLL did not sacrifice the prediction performance to satisfy the constraints. In addition, we also demonstrate that we could use HLL for high-dimensional input vectors with a small m. All our experiments were conducted on a virtual machine with an Intel Xeon CPU (3.30 GHz) processor without any GPU and 64 GB of memory running Red Hat Enterprise Linux Server 7.6.

4.1 Neural Network Models

In our experiments, we compared these four neural network models.

- **MLP**. A multi-layer perceptron model with three hidden layers. We used the ReLU activation layer for the hidden layers and the sigmoid function for the output layer. Note that this neural network is not designed for partially monotone regression and cannot handle monotonicity constraints.

- **HLL**. A neural network model consisting of a single hierarchical lattice layer. We used an MLP model with three hidden layers for the auxiliary neural network $g_\theta(p, v)$, and we used multilinear interpolation in the inference algorithm.

- **TL Lattice**. A neural network model consisting of a single TL Lattice layer Gupta *et al.* [2016]. This layer uses $O(k^d)$ space, and therefore, it can be used only for low-dimensional inputs (i.e., d is a small integer). We used multilinear interpolation in the inference algorithm.

- **TL RTL.** A neural network model consisting of a single RTL layer Canini *et al.* [2016] from the TensorFlow Lattice library, which is a random ensemble of tiny lattices (i.e., TL Lattices). This layer consists of $\lceil d/r \rceil$ tiny lattices, and each tiny lattice receives an r-dimensional input vector, where r is an integer hyperparameter. Hence, this layer uses $O((d/r)k^r)$ space, which is significantly smaller than that of TL Lattice when $r \ll d$. Note that a theoretical analysis in Canini *et al.* [2016] shows that TL RTL with d/r tiny lattices is equivalent to the single d-dimensional TL Lattice. We used this model for datasets with high-dimensional inputs (i.e., d is a large integer).

We used Python 3.8.12 and PyTorch 1.8.1 to implement MLP and HLL. As for TL Lattice and TL RTL, we used TensorFlow 2.3.0 and TensorFlow Lattice 2.0.10, which is the implementation provided by the authors Canini *et al.* [2016]; Gupta *et al.* [2016] and available as an open source library under Apache License 2.0 at `https://www.tensorflow.org/lattice`. The TensorFlow Lattice library also provides an implementation of the Kronecker-Factored lattice layer Morioka *et al.* [2021], which uses a smaller amount of memory than TL Lattice. However, we did not include the experimental results for this layer because TL RTL significantly outperformed it for the datasets we used in terms of prediction performance.

Throughout our experiments, all problems were solved as regression problems, and we used mean squared error (MSE) for the evaluation metric. For the training of the neural network models, we used the Adam optimizer Kingma and Ba [2015]. In HLL, TL Lattice, and TL RTL, the number of vertices in each dimension of the hypercube was set to k by default. However, the numbers of the vertices in the dimensions that correspond to small categorical values were set to the numbers of the categories. For example, if the i-th dimension corresponds to a binary feature, then we set $k_i = 2$ (instead of $k_i = k$).

4.2 Real Datasets

We used 12 real datasets taken from the UCI Machine Learning Repository Dua and Graff [2017] in our experiments. We used six small datasets: Energy Efficiency Tsanas and Xifara [2012], QSAR Aquatic Toxicity Cassotti *et al.* [2014], Concrete Compressive Strength Yeh [1998], Contraceptive Method Choice Lim *et al.* [2000], Abalone Nash *et al.* [1994], and Shill Bidding Alzahrani and Sadaoui [2020], and six large datasets: Online Shoppers Purchasing Intention Sakar *et al.* [2019], Adult, Online News Popularity Fernandes *et al.* [2015], Facebook Comment Volume Singh *et al.*

Table 1: Datasets obtained from UCI Machine Learning Repository.

Name	n	d	Monotone features
Energy Efficiency	768	8	X3, X5, X7
QSAR Aquatic Toxicity	908	6	MLOGP, SM1_Dz(Z)
Concrete Compressive Strength	1 030	8	*Water*
Contraceptive Method Choice	1 473	12	Number of children ever born, *wife age*
Abalone	4 176	10	Shell, *shucked*, *viscera*, and whole weights
Shill Bidding	6 321	9	Winning_Ratio
Online Shoppers Purchasing	12 330	74	*BounceRates*, *ExitRates*
Adult	30 162	88	Age
Online News Popularity	39 644	58	n_tokens_content, n_tokens_title
Facebook Comment Volume	40 949	52	Column 37
Bank Marketing	41 188	63	cons.conf.idx
Blog Feedback	46 864	276	Columns 51–53

[2015], Bank Marketing Moro *et al.* [2014], and Blog Feedback Buza [2014]. We confirmed that none of these datasets contained any personally identifiable data points nor any offensive content.

Table 1 shows a summary of these 12 datasets. Some of the datasets were already split into training and test data, and the others were unsplit (i.e., a single dataset was given). Column n of this table shows the number of data points in the training dataset for the split datasets and the number of data points for the unsplit datasets. In our experiments, we removed all the data points that had missing feature values.

Column d of Table 1 shows the number of features after our feature encoding. We briefly explain our feature encoding here. We normalized all the continuous values (including the target values) to a range between 0 and 1 by using the min-max scaling algorithm (i.e. a simple linear transformation). We used label encoding to encode the ordinal categorical values. For example, we replaced the ordinal categorical values $\{low, med, high\}$ with $low = 0$, $med = 0.5$, and $high = 1$ so that the replaced values were in the range between 0 and 1. We used one-hot encoding for the other categorical values. When we used TL Lattice and TL RTL, we renormalized the input feature vectors from $[0, 1]^d$ to $[0, k-1]^d$, where k is a hyperparameter, to conform to the input specifications of these two models.

The last column of Table 1 shows the monotone features we used in our experiments. The *italic* feature names represent monotonically decreasing features, and the others represent monotonically increasing features. We should choose monotone features by using domain knowledge for each dataset, but we used the SHAP values Lundberg and Lee [2017] to find candidates of monotone features for the datasets for which we had little domain knowledge. We expected that there would be an almost monotonic relationship between the SHAP value and the i-th feature value (i.e., $x[i]$) if the target value was monotonic on the i-th feature. In our experiments, we constructed an MLP model for each dataset and computed its SHAP values. Then, we checked for each feature if the SHAP values were monotonically increasing (or decreasing) with respect to the feature values by using Spearman's rank correlation coefficients. Note that such correlation between SHAP values and feature values does not mean a monotone relationship, but we found this approach helpful to find candidates of monotone features for datasets with little domain knowledge.

4.3 Experimental Results

In our experiments, we split the data points into training, validation, and test data points. For the unsplit datasets, we divided the data points into training (60%), validation (20%), and test (20%). We used a single random split to search for the best hyperparameters and five random splits to obtain the average prediction performance. For the datasets that were already split into training and test datasets, we further divided the data points in the training dataset into training (80%) and validation (20%) and kept the test dataset unchanged. We used a single random split to search for the best hyperparameters and five random splits to obtain the average prediction performance without changing the test dataset.

Regarding the hyperparameters, we chose the best hyperparameters for each combination of a neural network and a dataset; the learning rate was chosen from $\{1, 10^{-1}, 10^{-2}, 10^{-3}, 10^{-4}, 10^{-5}\}$, the

Figure 3: MSE (lower is better) of the neural network models with various k on small datasets.

batch size was chosen from $\{8, 16, 32, ..., 4096\}$, the number of neurons in the hidden layers was chosen from $\{16, 32, 64, ..., 512\}$ for MLP and HLL, and the hyperparameter r was chosen from $\{4, 5, 6, 7\}$ for TL RTL. We used only the training and validation datasets to determine the best hyperparameters, and we used Optuna Akiba *et al.* [2019] to search for the best hyperparameters.

Results for Small Datasets. We compared the prediction performances of MLP, HLL, and TL Lattice by using the six small datasets (i.e., d was small). We trained these neural network models for 1000 epochs with certain early stopping criteria, and Figure 3 shows the results for various k. The red lines show the average of the MSEs for five runs of MLP, and we regard these values as baselines of the prediction performance. The blue and orange lines show the average MSEs together with their standard deviations for five runs of HLL and TL Lattice, respectively. These results showed that our HLL performed comparably to MLP for all six datasets. Somewhat surprisingly, we note that using a finer-grained lattice (i.e., increasing k) did not necessarily improve the MSEs. This phenomenon was already mentioned in Gupta *et al.* [2016] for TL Lattice, and we confirmed this phenomenon both for TL Lattice and HLL in our experiments. Figure 3 also shows that the prediction performance of HLL were also comparable with TL Lattice. Although TL Lattice showed worse MSEs than MLP and HLL for some datasets, these differences in prediction performance were supposed to come from two factors. One was the difference of the parameterization; HLL used a hypercube of size k^m, whereas TL Lattice used a hypercube of size k^d. The other one was the difference of the neural network training algorithm; MLP and HLL used the standard training algorithm, whereas TL Lattice used its own special training algorithm.

Results for Large Datasets. For the datasets with a large d, we could not use TL Lattice due to its space complexity $O(k^d)$, so we used TL RTL instead. TL Lattice requires that at least 2^{52} parameters be stored even if $k = 2$ since $d \geq 52$, but we cannot store such a large number of parameters in memory. In contrast, we could use HLL since m is small in the datasets we used.

We compared the prediction performance of MLP, HLL, and TL RTL by using the six large datasets. We trained these neural network models for 100 epochs with certain early stopping criteria, and Figure 4 shows the results for various k. The red lines show the average MSEs for five runs of MLP, and we regard these values as baselines of the prediction performance. The blue and green lines show the average MSEs together with their standard deviations for five runs of HLL and TL RTL, respectively. Note that the result for TL RTL with $k = 5$ on the Blog Feedback dataset was missing due to a memory limitation in our computer environment. These results showed that our HLL performed comparably to MLP and TL RTL regardless of k for the six large datasets. We think

Figure 4: MSE (lower is better) of the neural network models with various k on large datasets.

that HLL performed better than MLP for some datasets thanks to the regularization effects coming from the monotonicity constraints.

5 Related Work

There are some neural networks for partially monotone regression other than the TensorFlow Lattice library. One of the simplest approaches is to enforce non-negativity constraints on neural network weights that are related to monotone inputs (e.g., Daniels and Velikova [2010]; You *et al.* [2017]). Another simple approach is to use a regularization term to enforce monotonicity Gupta *et al.* [2019]; Monteiro *et al.* [2021], but a prediction model that uses this approach may not always satisfy the monotonicity constraints. More complex approaches are proposed in Liu *et al.* [2020]; Sivaraman *et al.* [2020]. These approaches use a mixed integer linear programming solver or a satisfiability modulo theories (SMT) solver to ensure the monotonicity of the neural network. The disadvantages of these approaches are their computational complexity and the costs of using the solvers.

6 Conclusion

We proposed the hierarchical lattice layer (HLL) for partially monotone neural networks as an extension of TL Lattice Gupta *et al.* [2016]. We demonstrated that HLL resolved two problems with TL Lattice: the requirement for a special training algorithm and the memory consumption. In our experiments, we showed that HLL did not sacrifice prediction performances to resolve these problems. Note that our experiments were limited to a comparison between single layers (i.e., HLL and TL Lattice). The prediction performance of these models might be able to be improved by combining multiple layers (e.g., You *et al.* [2017]) or any other techniques (e.g., changing feature encoding and increasing the number of layers in MLP) and the memory consumption might also be reduced by using smaller lattices, but note that the requirement for a special training algorithm remains for TL Lattice.

A limitation of our HLL is that it cannot be used for the applications with a large m. If m is large, we need to combine small HLL layers to construct a large neural network as demonstrated in Canini *et al.* [2016]; You *et al.* [2017] for TL Lattice.

References

T. Akiba, S. Sano, T. Yanase, T. Ohta, and M. Koyama. Optuna: A next-generation hyperparameter optimization framework. In *Proceedings of KDD 2019*, pages 2623–2631, 2019.

A. Alzahrani and S. Sadaoui. Clustering and labeling auction fraud data. *Data Management, Analytics and Innovation*, pages 269–283, 2020.

C. Bartley, W. Liu, and M. Reynolds. A novel framework for constructing partially monotone rule ensembles. In *Proceedings of ICDE 2018*, 2018.

C. Bartley, W. Liu, and M. Reynolds. Enhanced random forest algorithms for partially monotone ordinal classification. In *Proceedings of AAAI-19*, pages 3224–3231, 2019.

K. Buza. Feedback prediction for blogs. *Data Analysis, Machine Learning and Knowledge Discovery*, pages 145–152, 2014.

K. Canini, A. Cotter, M. R. Gupta, M. Milani Fard, and J. Pfeifer. Fast and flexible monotonic functions with ensembles of lattices. In *Proceedings of NIPS 2016*, pages 2927–2935, 2016.

J.-R. Cano, P. A. Gutiérrez, B. Krawczyk, M. Woźniak, and S. García. Monotonic classification: An overview on algorithms, performance measures and data sets. *Neurocomputing*, 341:168–182, 2019.

M. Cassotti, D. Ballabio, V. Consonni, A. Mauri, I. V. Tetko, and R. Todeschini. Prediction of acute aquatic toxicity towards Daphnia magna using GA-kNN method. *Alternatives to Laboratory Animals*, 42(1):31–41, 2014.

H. Daniels and M. Velikova. Monotone and partially monotone neural networks. *IEEE Transactions on Neural Networks*, 21(6):906–917, 2010.

D. Dua and C. Graff. UCI Machine Learning Repository, 2017.

C. Dugas, Y. Bengio, F. Bélisle, C. Nadeau, and R. Garcia. Incorporating second-order functional knowledge for better option pricing. In *Proceedings of NIPS 2000*, pages 472–478, 2000.

M. Milani Fard, K. Canini, A. Cotter, J. Pfeifer, and M. Gupta. Fast and flexible monotonic functions with ensembles of lattices. In *Proceedings of NIPS 2016*, pages 2927–2935, 2016.

K. Fernandes, P. Vinagre, and P. Cortez. A proactive intelligent decision support system for predicting the popularity of online news. In *Proceedings of EPIA 2015*, pages 535–546, 2015.

M. Gupta, A. Cotter, J. Pfeifer, K. Voevodski, K. Canini, A. Mangylov, W. Moczydlowski, and A. van Esbroeck. Monotonic calibrated interpolated look-up tables. *Journal of Machine Learning Research*, 17(1):3790–3836, 2016.

A. Gupta, N. Shukla, L. Marla, A. Kolbeinsson, and K. Yellepeddi. How to incorporate monotonicity in deep networks while preserving flexibility? In *Proceedings of NeurIPS 2019 Workshop on Machine Learning with Guarantees*, 2019.

D. P. Kingma and J. Ba. Adam: A method for stochastic optimization. In *Proceedings of ICLR 2015*, 2015.

R. Koenker and B. Bassett, Jr. Regression quantiles. *Econometrica*, 46(1):33–50, 1978.

F. Lauer and G. Bloch. Incorporating prior knowledge in support vector regression. *Machine Learning*, 70:89–118, 2008.

T.-S. Lim, W.-Y. Loh, and Y.-S. Shih. A comparison of prediction accuracy, complexity, and training time of thirty-three old and new classification algorithms. *Machine Learning*, 40:203–228, 2000.

X. Liu, X. Han, N. Zhang, and Q. Liu. Certified monotonic neural networks. In *Proceedings of NeurIPS 2020*, pages 15427–15438, 2020.

S. M. Lundberg and S.-I. Lee. A unified approach to interpreting model predictions. In *Proceedings of NIPS 2017*, pages 4768–4777, 2017.

J. Monteiro, M. O. Ahmed, H. Hajimirsadeghi, and G. Mori. Not too close and not too far: Enforcing monotonicity requires penalizing the right points. In *Proceedings of XAI for Debugging Workshop at NeurIPS 2021*, 2021.

N. Morioka, E. Louidor, and W. T. Bakst. Monotonic Kronecker-factored lattice. In *Proceedings of ICLR 2021*, 2021.

S. Moro, P. Cortez, and P. Rita. A data-driven approach to predict the success of bank telemarketing. *Decision Support Systems*, 62:22–31, 2014.

W. J. Nash, T. L. Sellers, S. R. Talbot, A. J. Cawthorn, and W. B. Fort. The population biology of Abalone (Haliotis species) in Tasmania. I. Blacklip Abalone (H. rubra) from the north coast and islands of bass strait. Technical report, Sea Fisheries Division, 1994.

R. Potharst and A. J. Feelders. Classification trees for problems with monotonicity constraints. *ACM SIGKDD Explorations Newsletter*, 4(1):1–10, 2002.

D. Rindt, R. Hu, D. Steinsaltz, and D. Sejdinovic. Survival regression with proper scoring rules and monotonic neural networks. In *Proceedings of AISTATS 2022*, 2022.

C. O. Sakar, S. O. Polat, M. Katircioglu, and Y. Kastro. Real-time prediction of online shoppers' purchasing intention using multilayer perceptron and LSTM recurrent neural networks. *Neural Computing and Applications*, 31:6893–6908, 2019.

K. Singh, R. Kaur Sandhu, and D. Kumar. Comment volume prediction using neural networks and decision trees. In *Proceedings of UKSIM 2015*, pages 15–20, 2015.

A. Sivaraman, G. Farnadi, T. Millstein, and G. Van den Broeck. Counterexample-guided learning of monotonic neural networks. In *Proceedings of NeurIPS 2020*, pages 11936–11948, 2020.

A. Tsanas and A. Xifara. Accurate quantitative estimation of energy performance of residential buildings using statistical machine learning tools. *Energy and Buildings*, 49:560–567, 2012.

S. Wang and M. Gupta. Deontological ethics by monotonicity shape constraints. In *Proceedings of AISTATS 2020*, pages 2043–2054, 2020.

P. Wang, Y. Li, and C. K. Reddy. Machine learning for survival analysis: A survey. *ACM Computing Surveys*, 51(6):1–36, 2019.

I.-C. Yeh. Modeling of strength of high performance concrete using artificial neural networks. *Cement and Concrete Research*, 28(12):1797–1808, 1998.

S. You, D. Ding, K. Canini, J. Pfeifer, and M. R. Gupta. Deep lattice networks and partial monotonic functions. In *Proceedings of NIPS 2017*, pages 2985–2993, 2017.

F. Zhou, J. Wang, and X. Feng. Non-crossing quantile regression for deep reinforcement learning. In *Proceedings of NeurIPS 2020*, pages 15909–15919, 2020.

Figure 5: Illustration of parameterization of HLL for $m = 1$ and $k = 3$ with $\sigma = (v_0, v_1, v_2)$.

A   Parameterization of HLL for Simple Case

We show an example of the functions $l(p, v)$, $u(p, v)$, and $g(p, v)$ for a simple case with $m = 1$ and $k = 3$. In this case, the hypercube has three vertices $V_m = \{v_0, v_1, v_2\}$, and we use the total ordering $\sigma = (v_0, v_1, v_2)$ here. Recall that HLL is constructed to satisfy the monotonicity constraint $0 \leq f(p, v_0) \leq f(p, v_1) \leq f(p, v_2) \leq 1$ for any $p \in [0, 1]^{d-1}$. See Figure 5 for an illustration of the definitions of $g(p, v_0)$, $g(p, v_1)$, and $g(p, v_2)$.

The three functions $l(p, v)$, $u(p, v)$, and $g(p, v)$ are defined to satisfy $l(p, v) \leq f(p, v) \leq u(p, v)$ and $0 \leq g(p, v) \leq 1$ for any $p \in [0, 1]^{d-1}$ and any $v \in V_m$. For the first element v_0 of σ, we have $l(p, v_0) = 0$ and $u(p, v_0) = 1$ because $L_{v_0, \sigma} = U_{v_0, \sigma} = \emptyset$ and $g(p, v_0) = f(p, v_0)$, which satisfies $l(p, v_0) \leq f(p, v_0) \leq u(p, v_0)$ and $0 \leq g(p, v_0) \leq 1$. For the second element v_1 of σ, we have $l(p, v_1) = f(p, v_0)$ and $u(p, v_1) = 1$ because $L_{v_1, \sigma} = \{v_0\}$ and $U_{v_1, \sigma} = \emptyset$. The function $g(p, v_1)$ is defined as a function that satisfies

$$f(p, v_1) = (1 - g(p, v_1))l(p, v_1) + g(p, v_1) \cdot u(p, v_1).$$

Note that this definition satisfies $l(p, v_1) \leq f(p, v_1) \leq u(p, v_1)$ and $0 \leq g(p, v_1) \leq 1$, which means that the monotonicity constraint $f(p, v_0) \leq f(p, v_1) \leq 1$ is satisfied. Similarly, for the third element v_2 in σ, we have $l(p, v_2) = f(p, v_1)$ and $u(p, v_2) = 1$ because $L_{v_2, \sigma} = \{v_1\}$ and $U_{v_2, \sigma} = \emptyset$. The function $g(p, v_2)$ is defined as a function that satisfies

$$f(p, v_2) = (1 - g(p, v_2))l(p, v_2) + g(p, v_2) \cdot u(p, v_2).$$

Note that this definition satisfies $l(p, v_2) \leq f(p, v_2) \leq u(p, v_2)$ and $0 \leq g(p, v_2) \leq 1$, which means that the monotonicity constraint $f(p, v_1) \leq f(p, v_2) \leq 1$ is satisfied.

B   Multilinear Interpolation

For the completeness of this paper, we briefly describe multilinear interpolation algorithm Gupta *et al.* [2016] here. For simplicity, we assume that we are given a vector $q \in [0, 1]^m$, and the set of vertices that surround q is the set of vertices of the (undivided) unit hypercube $V_q = \{v \mid v \in \{0, 1\}^m\}$. Assuming that we know the value $f(p, v)$ for any $v \in V_q$ and $p \in \mathbb{R}^{d-m}$, we can compute the multilinear interpolation by

$$f(p, q) = \sum_{v \in V_q} f(p, v) \prod_{i=1}^{m} q[i]^{v[i]}(1 - q[i])^{1-v[i]},$$

where $q[i]$ and $v[i]$ represent the i-th dimension of vectors q and v, respectively.

Example.   We can compute $f(p, q)$ for $q = (0.3, 0.6)$ by

$$
\begin{aligned}
f(p, q) &= f(p, v_{(0,0)})(1 - 0.3)(1 - 0.6) + f(p, v_{(0,1)}) \cdot ((1 - 0.3) \cdot 0.6) \\
&\quad + f(p, v_{(1,0)}) \cdot (0.3 \cdot (1 - 0.6)) + f(p, v_{(1,1)}) \cdot (0.3 \cdot 0.6)
\end{aligned}
$$

when $m = 2$ and $V_q = \{v_{(0,0)}, v_{(0,1)}, v_{(1,0)}, v_{(1,1)}\}$.

C   Experiments on Synthetic Datasets

1D Synthetic Datasets.   We show our experimental results on one-dimensional synthetic datasets $D_{\text{square1}} = \{(x_i, y_i)\}_{i=1}^n$ such that $y_i = x_i^2$ and $D_{\text{sqrt1}} = \{(x_i, y_i)\}_{i=1}^n$ such that $y_i = \sqrt{x_i}$. Figures 6 and 7 show the prediction results with various k for these two datasets. The blue lines show the predictions by HLL, and the black lines show the ground truth. Both figures show that increasing k yields better prediction results on these synthetic datasets.

Figure 6: Prediction results of HLL with various k for dataset D_{square1}.

Figure 7: Prediction results of HLL with various k for dataset D_{sqrt1}.

2D Synthetic Datasets.   We show our experimental results on two-dimensional synthetic datasets $D_{\text{square2}} = \{(x_i, y_i)\}_{i=1}^n$ such that $y_i = (x_i[1]^2 + x_i[2]^2)/2$ and $D_{\text{sqrt2}} = \{(x_i, y_i)\}_{i=1}^n$ such that $y_i = (\sqrt{x_i[1]} + \sqrt{x_i[2]})/2$ (recall that the i-th element of vector x is denoted as $x[i]$). Figures 8 and 9 show the prediction results of HLL, TL Lattice, and TL RTL with $k = 4$ against the ground truth. These prediction models show similar prediction results on these synthetic datasets.

Figure 8: Comparison of predictions for D_{square2}.

Figure 9: Comparison of predictions for D_{sqrt2}.

D Experiments on Training Time

We compared the training times of HLL and TL Lattice on the small datasets. In these experiments, we fixed the hyperparameters; k was set to 2, the learning rate was set to 0.001, and the batch size was set to 128. The number of epochs was set to 100, and we did not use any early stopping. Figure 10 shows the results, where we varied the number of neurons in the auxiliary neural network $g_\theta(p, v)$ from 16 to 512 for HLL, and the execution times were the averages of five runs. These results show that the training times of HLL were shorter than those of TL Lattice for these six small datasets.

Figure 10: Comparison of training times (in sec.) of neural network models for various numbers of neurons of HLL on small datasets.