Response Modeling of Hyper-Parameters for Deep Convolutional Neural Networks

Abstract

Hyper-parameter optimization (HPO) is critical in training high performing Deep Neural Networks (DNN). Current methodologies fail to define an analytical *response surface* (Bergstra & Bengio, 2012) and remain a training bottleneck due to their use of additional internal hyper-parameters and lengthy evaluation cycles. We demonstrate that the low-rank factorization of the convolution weights of intermediate layers of a CNN can define an analytical response surface. We quantify how this surface acts as an auxiliary to optimizing training metrics. We introduce a dynamic tracking algorithm – autoHyper– that performs HPO on the order of hours for various datasets including ImageNet and requires no manual tuning. Our method – using a single RTX2080Ti – is able to select a learning rate within 59 hours for AdaM (Kingma & Ba, 2014) on ResNet34 applied to ImageNet and improves in testing accuracy by 4.93% over the default learning rate. In contrast to previous methods, we empirically prove that our algorithm and response surface generalize well across model, optimizer, and dataset selection removing the need for extensive domain knowledge to achieve high levels of performance.

1 Introduction

The choice of Hyper-Parameters (HP) – such as initial learning rate, batch size, and weight decay – has shown to greatly impact the generalization performance of Deep Neural Network (DNN) training (Keskar et al., 2017; Wilson et al., 2017; Li et al., 2019; Yu & Zhu, 2020). By increasing the complexity of network architectures (from high to low parameterized models) and training datasets (class number and samples), the manual intervention to tune these parameters for optimization becomes a practically expensive and highly challenging task. Therefore, the problem of Hyper-Parameter Optimization (HPO) becomes central to developing highly efficient training workflows.

Recent studies shift the gear toward development of a meaningful *metric measure* to explain effective HP tuning for DNN training. This is done in several behavioural studies, including changes in loss surfaces (Keskar et al., 2017), input perturbation analysis (Novak et al., 2018), and the energy norm of the covariance of gradients (Jastrzebski et al., 2020), just to name a few. In fact, the abstract formulation of the HPO problem, as highlighted by Bergstra & Bengio (2012), can be modelled by

$$\lambda^* \leftarrow \underset{\lambda \in \Lambda}{\arg\min} \{\mathbb{E}_{x \sim M}[\mathcal{L}(x; \mathcal{A}_\lambda(X^{(\text{train})})]\}, \tag{1}$$

where, $X^{(\text{train})}$ and x are random variables, modelled by some natural distribution M, that represent the train and validation data, respectively, $\mathcal{L}(\cdot)$ is some expected loss and $\mathcal{A}_\lambda(X^{(\text{train})})$ is a learning algorithm that maps $X^{(\text{train})}$ to some learned function, conditioned on the hyper-parameter set λ. Note that this learned function, denoted as $f(\theta; \lambda; X^{(\text{train})})$, involves its own inner optimization problem. The HPO in (1) highlights two optimization problems of which optimization over λ cannot occur until complete training and optimization over $f(\theta; \lambda; X^{(\text{train})})$ is complete. This fact applies heavy computational burden for HPO. Bergstra & Bengio (2012) reduce this burden by attempting to solve the following

$$\lambda^* \leftarrow \underset{\lambda \in \Lambda}{\arg\min} \tau(\lambda), \tag{2}$$

where τ is called the *hyper-parameter response function* or *response surface*, and Λ is some set of choices for λ (*i.e.* the search space). The goal of the response surface is to introduce an auxiliary

function parameterized by λ of which its minimization is directly correlated to minimization of the objective function $f(\theta)$. Little advancements in an analytical model of the response surface has led to estimating it by (a) running multiple trials of different HP configurations (*e.g.* grid searching), using evaluation against validation sets as an estimate to τ; or (b) characterizing the distribution model of a configuration's performance metric (*e.g.* cross-validation performances) to numerically define a relationship between τ and λ.

An important shift occurred when Bergstra & Bengio (2012) showed that random searching is more efficient to grid searching, particularly when optimizing high-dimensional HP sets. To mitigate the time complexity and increase overall performance, subsequent methods attempted to characterize the distribution model for such random configurations (Snoek et al., 2012; Eggensperger et al., 2013; Feurer et al., 2015a;b; Klein et al., 2017; Falkner et al., 2018) or employed population control (Young et al., 2015; Jaderberg et al., 2017) or early-stopping (Karnin et al., 2013; Li et al., 2017; 2018). However, these methods suffer from (a) additional internal HPs that require manual tuning facilitated by extensive domain knowledge; (b) heavy computational overhead whereby the optimization process takes days to weeks in most cases (Li et al., 2017; Falkner et al., 2018; Yu & Zhu, 2020); (c) poor generalization across model selection, datasets, and general experimental configurations (*e.g.* optimizers); and (d) strong dependence on a manually defined search ranges that heavily influences results (Choi et al., 2020; Sivaprasad et al., 2020).

In this paper, we employ the notion of knowledge gain (Hosseini & Plataniotis, 2020) to model a response surface, solvable with low computational overhead. We restrict our response surface to consider a single HP, namely the initial learning rate η, and support this choice by noting that the initial learning rate is the most sensitive and important HP towards final model performance (Goodfellow et al., 2016; Bergstra & Bengio, 2012; Yu & Zhu, 2020). We demonstrate how our method's optimization directly correlates to optimizing model performance. Finally, we provide empirical measures of the computational requirements of our algorithm and present thorough experiments on a diverse set of Convolutional Neural Network (CNN) and Computer Vision dataset that demonstrate the generalization of our response surface.

The main contributions of this work are as follows:

1. Inspired by knowledge gain in the intermediate layers of a CNN, we introduce a well-defined, analytical response surface using the low-rank-factorization of convolution weights (Equation 5).

2. We propose a dynamic tracking algorithm of low computational overhead on the order of minutes and hours, dubbed autoHyper, to optimize our response surface and conduct HPO.

3. This algorithm requires no domain knowledge, human intuition, or manual intervention, and is not bound by a manually set searching space, allowing for completely automatic setting of the initial learning rate; a novelty for deep learning practitioners

1.1 RELATED WORKS

We leave extensive analysis of the related works to established surveys (Luo, 2016; He et al., 2019; Yu & Zhu, 2020) but present a general overview here. Grid searching and manual tuning techniques that require extensive domain knowledge trial various configurations and retain the best. Random search (Bergstra & Bengio, 2012) was proven to be more efficient, particularly in high-dimensional cases, but these methods suffer from redundancy and high computational overhead. Bayesian optimization (Snoek et al., 2012; Eggensperger et al., 2013; Feurer et al., 2015a;b; Klein et al., 2017) techniques attempt to characterize the distribution model of the random HP configurations. They fail to properly define the response surface τ and resolve to estimating it by rationalizing a Gaussian process over sampling points. The use of neural networks over Gaussian to model the generalization performance was shown to have better computational performance (Snoek et al., 2015; Springenberg et al., 2016). Furthermore, the early stopping methods (Karnin et al., 2013; Li et al., 2017; 2018) spawn various configurations with equal resource distributions, successively stopping poorperforming configurations and reassigning resources dynamically. Population-based training (PBT) methods (Young et al., 2015; Jaderberg et al., 2017) follow an evolutionary approach by spawning various experimental configurations and adapting poor-performing trials to warm restart with inherited learnable parameters and HPs. In addition, other methods such as orthogonal array tuning (Zhang et al., 2019), box-constrained derivative-free optimization (Diaz et al., 2017), reverse

dynamics algorithm for SGD optimization (Maclaurin et al., 2015), and hybrid methods (Swersky et al., 2013; 2014; Domhan et al., 2015; Falkner et al., 2018; Kandasamy et al., 2016) exist but demonstrate no significant benefits over the previous techniques. Generally, each of these methods suffer from high computational overheads – on the order of days to weeks to converge – as well as additional internal HPs that heavily influence performance and generalization. In recent years, many Python libraries have also been developed that include these optimization methods (Bergstra et al., 2013; Kotthoff et al., 2017; Akiba et al., 2019).

2 A NEW RESPONSE SURFACE MODEL

In this section, we motivate and develop a new response surface model $\tau(\lambda)$ based on low-rank factorization of convolutional weights in a CNN. Unlike the common approach of cross-validation performance measures, we define a new measure on the well-posedness of the intermediate layers of a CNN and relate this measure to the general performance of the network. We first start adopting the low-rank measure of convolution weights.

2.1 KNOWLEDGE GAIN VIA LOW-RANK FACTORIZATION

Consider a four-way array (4-D tensor) $\mathsf{W} \in \mathbb{R}^{N_1 \times N_2 \times N_3 \times N_4}$ as the convolution weights of an intermediate layer of a CNN (N_1 and N_2 being the height and width of kernel size, and N_3 and N_4 corresponding to the input and output channel size, respectively). Under the convolution operation, the input feature maps $\mathsf{F}^I \in \mathbb{R}^{W \times H \times N_3}$ are mapped into an arbitrary output feature map $\mathsf{F}^O \in \mathbb{R}^{W \times H \times N_4}$ by

$$\mathsf{F}^O_{:,:,i_4} = \sum_{i_3=1}^{N_3} \mathsf{F}^I_{:,:,i_3} * \mathsf{W}_{:,:,i_3,i_4}.$$

Importantly, following Hosseini & Plataniotis (2020), we can decompose (e.g. by singular value decomposition) this 4-D tensor along a given dimension d as follows:

$$\mathsf{W} \xrightarrow{\text{unfold}} W_d \xrightarrow{\text{factorize + decompose}} \underbrace{\widehat{U}_d \widehat{\Sigma}_d \widehat{V}_d^T}_{\widehat{W}_d} + E_d$$

We note the importance of factorizing the unfolded matrix W_d using a low-rank factorization. Without this factorization, the presence of noise will inhibit proper analysis. This noise E_d will "capture" the randomness of initialization and allow us to better analyze our unfolded matrices. In this case, the low-rank factorization is achieved by the Variational Bayesian Matrix Factorization (VBMF) (Nakajima et al., 2013).

Following the definition of *Knowledge Gain (KG)* from Hosseini & Plataniotis (2020), one can now define a metric for each network layer using the norm energy of the low-rank factorization as

$$\mathcal{G}_d(\widehat{W}_d) = \frac{1}{N_d \cdot \sigma_1(\widehat{W}_d)} \sum_{i=1}^{N'_d} \sigma_i(\widehat{W}_d) \tag{3}$$

where, $\sigma_1 \geq \sigma_2 \geq \ldots \geq \sigma_{N'_d}$ are the associated low-rank singular values in descending order. Here $N'_d = \text{rank}\{\widehat{W}_d\}$ and the unfolding can be done in either input or output channels i.e. $d \in \{3, 4\}$. For more information on KG as well as its efficient algorithmic computation, we refer the reader to Hosseini & Plataniotis (2020).

The metric defined in (3) is normalized such that $\mathcal{G}_d \in [0, 1]$ and can be used to probe CNN layers to monitor their efficiency in the carriage of information from input to output feature maps. We further define the KG, averaged across input and output channels, parameterized by the HP set λ, epoch t and network layer ℓ as

$$\bar{\mathcal{G}}_\lambda(t, \ell) = [\mathcal{G}_3(\widehat{W}_3) + \mathcal{G}_4(\widehat{W}_4)]/2.$$

A perfect network and set of HPs would yield $\bar{\mathcal{G}}_\lambda(T, \ell) = 1 \quad \forall \ell \in [L]$ where L is the number of layers in the network and each network layer functions as a better autoencoder through iterative training. In this scenario, the carriage of information throughout the network is maximized. Conversely, $\bar{\mathcal{G}}_\lambda(T, \ell) = 0$ indicates that the information flow is very weak such that mapping is effectively random (The noise matrix E_d is full).

2.2 DEFINITION OF NEW RESPONSE FUNCTION

Interestingly, if $\bar{\mathcal{G}}_\lambda(T, \ell) = 0$ in early stages of training, it is evidence that no learning has occurred, indicative of an initial learning rate that is too small. It then becomes useful to track the zero-valued KGs within a network's intermediate layers' input and output channels, which effectively becomes a measure of channel rank. We denote this rank per epoch as follows:

$$\mathcal{Z}_t(\lambda) \leftarrow \frac{1}{L} \sum_{\ell \in [L]} \lfloor 1 - \bar{\mathcal{G}}_\lambda(t, \ell) \rfloor$$

where $\mathcal{Z}_t(\lambda) \in [0, 1)$. Finally, we define the average rank across T epochs as

$$\mathcal{Z}(\lambda) \leftarrow \frac{1}{T} \sum_{t \in [T]} \mathcal{Z}_t(\lambda). \tag{4}$$

Note that $\mathcal{Z}(\lambda) \in [0, 1)$. The average rank measure in (4) is therefore a normalized summation of the zero-valued singular values of the low-rank factorization across all layers' input and output unfolded tensor arrays.

Relating to the notion of HPO and the response surface, we return to (1) and (2). Where previously the nature of these two optimization problems was poorly understood or practically unsolvable, we propose a new problem that is well understood and practically solvable (on the computational order of hours). To solve for the optimal HP set λ, we look at the following optimization problem

$$\lambda^* \leftarrow \arg\min_\lambda 1 - \mathcal{Z}(\lambda), \text{ subject to } \| \nabla_\lambda \mathcal{Z}(\lambda) \|_2^2 \leq \epsilon \tag{5}$$

where $\epsilon \in [0, 1)$ is some small conditioning error. Returning to equation 2, our response surface is therefore defined as $\tau = 1 - \mathcal{Z}(\lambda)$ subject to $\| \nabla_\lambda \mathcal{Z}(\lambda) \|_2^2 \leq \epsilon$. Note that we now simplify our problem to only consider $\lambda = \eta$. To explain this somewhat counterintuitive formulation, we analyze Figures 1(a) & 2, which demonstrate that as learning rates increase, $\mathcal{Z}(\eta)$ plateaus to zero. Specifically, we notice that optimal learning rates lie towards the inception of the plateau of $\mathcal{Z}(\eta)$, before $\mathcal{Z}(\eta) = 0$. This can also be seen in Figures 8 & 7 in Appendix A. Therefore, we wish to design our response surface such that the solution lies at the inception of the plateau-ing region. In this case, our constraint $\| \nabla_\lambda \mathcal{Z}(\lambda) \|_2^2 \leq \epsilon$ promotes learning rates that lie along this plateau-ing region, while $\arg\min_\lambda 1 - \mathcal{Z}(\lambda)$ promotes, of those learning rates in the plateau-ing region, a learning rate that lies towards the inception of this plateau-ing region. It is important to note that we do not explicitly calculate the gradient $\nabla_\lambda \mathcal{Z}(\lambda)$, but rather use this constraint to guide our dynamic tracking algorithm (see section 3)

(a) Auxiliary Behaviour   (b) Histogram of $\mathcal{Z}(\eta)$

Figure 1: (a) Auxiliary representation of $\mathcal{Z}(\eta)$ to training loss and training accuracy. The red dot indicates the learning rate chosen by our method with corresponding metrics drawn in red lines. Lines and scatter points in grayscale show various trialled learning rates. (b) Distribution of $\mathcal{Z}(\eta)$ over numerous experimental configurations applied on CIFAR10 and CIFAR100 (see subsection 4.1).

More generally, high $\mathcal{Z}(\eta)$ indicates a learning rate that is too small, as intermediate layers do not make sufficient progress in early stages of learning and therefore their KGs remain very low. This observation follows that of Li et al. (2019) in which larger initial learning rates result in better generalization performance. Promotion of this behaviour is achieved by our gradient constraint in Equation 5. Conversely, too large of a learning rate can over-regulate a network and, therefore, we

wish not to minimize $\mathcal{Z}(\eta)$ completely but tune it to be sufficiently small to arrive at the inception of its plateau, creating a sort of kick-start if you will. This is achieved by the balance between our minimization and constraint in. Equation 5.

| (a) AdaBound | (b) AdaGrad | (c) AdaM |

Figure 2: $\mathcal{Z}(\eta)$ for various learning rates using AdaBound, AdaGrad, and AdAM on ResNet34 applied to CIFAR10. The author-suggested initial learning rate is indicated by the red markers, and the autoHyper suggested learning rate is indicated by the green markers.

Finally, we choose $T = 5$ in our experiment. The early phase of training has been shown to be an important criterion in optimal model performance (Jastrzebski et al., 2020; Li et al., 2019) and we therefore wish to only consider 5-epochs to ensure optimization within this phase. Additionally, Figure 2 and Figures 8 & 7 in Appendix A tell us that $\mathcal{Z}(\eta)$ stabilizes after 5 epochs.

2.3 EMPIRICAL EVALUATION OF NEW RESPONSE MODEL

Figure 1(a) visualizes results of our method on ResNet34 on CIFAR10 optimized with AdaM. The learning rate selected by our method results in lowest training loss and highest top-1 training accuracy over the 5-epoch range we consider. We note the importance of stopping at the inception of this plateau region as even though higher learning rates, highlighted by the gray-scale lines/markers, result in potentially lower $\mathcal{Z}(\eta)$, they do not guarantee lower training losses or higher training accuracies. We conclude that our response surface is a strong auxiliary to training loss, and optimizing HPs relative to our response surface will in fact optimize towards training loss and accuracy.

Figure 1(b) displays the histogram of $\mathcal{Z}(\eta)$ values over various experimental configurations (see subsection 4.1). We highlight the presence of a multimodal distribution that peaks at low $\mathcal{Z}(\eta)$ but importantly not zero. This visualizes our method's tendency to converge to a consistent range of values irrespective of the experimental configuration, demonstrating the generalization of our response surface.

3 AUTOHYPER: AUTOMATIC TUNING OF INITIAL LEARNING RATE

The pseudo-code for autoHyper is presented in Algorithm 1. Analyzing equation 5, we state that the optimal solution lies within the inception of the plateauing region of $\mathcal{Z}(\eta)$. To find this region, autoHyper first initializes a logarithmic grid space, from $\eta_{min} = 1 \times 10^{-4}$ to $\eta_{max} = 0.1$ of $S = 20$ step sizes, denoted by Ω. It iterates through each $\eta_i \in \Omega; i \in \{0, \dots, 19\}$, and computes $\mathcal{Z}(\eta)$, until a plateau is reached. Once a plateau is reached, Ω is reset such that η_{min} and η_{max} "zoom" towards the learning rates at the plateau. This process is repeated recursively until no significant difference between η_{min} and η_{max} exists. On average, this recursion occurs 3 to 4 times and as shown in Figure 3, the number of trialled learning rates remains very low (between 10-30 on average). Importantly, our algorithm is not constrained by its initial grid space. As it tracks $\mathcal{Z}(\eta)$ over trialed learning rates, it may grow and shrink its search bounds dynamically. This permits our method to be fully autonomous and require no human intuition in setting of initial grid space or other algorithmic settings.

Algorithm 1 autoHyper

Require: grid space function Ψ, learning rate significant difference delta $\alpha = 5 \times 10^{-5}$, and rate of change function ζ
1: **procedure** RESTART( )
2:     learning rate index $i = 0$
3:     $\mathbf{\Omega} = \Psi(\eta_{min}, \eta_{max}, S)$
4: **end procedure**
5: RESTART( )
6: **while** True **do**
7:     **if** $i = |\Omega|$ **then**   // increase search space since no plateau has been found yet
8:         set $\eta_{min} = \eta_{max}$, increase η_{max} and RESTART( )
9:     **end if**
10:     **if** $\eta_{max} - \eta_{min} < \alpha$ **then**   // limits of search space are not significantly different
11:         **return** η_{max}
12:     **end if**
13:     with $\eta_i \leftarrow \Omega_i$, train for 5 epochs
14:     compute rank: $\mathcal{Z}(\eta_i)$ per equation 4
15:     **if** $\mathcal{Z}(\eta_i) = 1.0$ **then**   // all KG is zero-valued, η_{min} is too small
16:         increase η_{min} and RESTART( )
17:     **end if**
18:     **if** $i = 0$ and $\mathcal{Z}(\eta_i) < 0.5$ and this is the first run **then**   // initial η_{min} is too large
19:         reduce η_{min} and RESTART( )
20:     **else**
21:         **if** $\mathcal{Z}(\eta_i) = 0.0$ **then**   // all KG is non-zero, don't search further, perform "zoom"
22:             set $\eta_{min} = \Omega_{i-2}$, $\eta_{max} = \Omega_i$ and RESTART( )
23:         **end if**
24:         compute rate of change of $\mathcal{Z}(\eta_i)$: $\delta \leftarrow \zeta(\{\mathcal{Z}(\eta_0), \ldots, \mathcal{Z}(\eta_i)\})$
25:         **if** rate of change plateaus **then**   // perform "zoom"
26:             set $\eta_{min} = \Omega_{i-1}$, $\eta_{max} = \Omega_i$ and RESTART( )
27:         **end if**
28:     **end if**
29:     $i += 1$
30: **end while**

Figure 3: Computational analysis of autoHyper over various setups (number of learning rates autoHyper trialled before converging). ResNet34 trials take 3 minutes, 3 minutes, 18 minutes, and 220 minutes for CIFAR10, CIFAR100, TinyImageNet and, ImageNet, respectively. ResNet18, ResNeXt50, and DenseNet121 trials take 2 minutes, 3 minutes, and 3 minutes respectively for both CIFAR10 and CIFAR100.

We note here that the choice of Ψ and ζ mentioned in Algorithm 1 (*i.e.* grid space and rate of change functions, respectively) will have a significant affect on the final generated learning rate. We make use of numpy's *geomspace* function for the logarithmic grid spacing, and calculate the rate of change in $\mathcal{Z}(\eta)$ by taking the cumulative product of the sequence of $\mathcal{Z}(\eta_i)$, to the power of 0.8. A logarithmic grid space is used as our response surface is more sensitive to smaller learning rates (see Figure 2).

(a) ResNet34/Adam   (b) EffNetB0/AdaS$^{\beta = 0.8}$

Figure 4: $\mathcal{Z}(\eta)$ (blue) vs. cumprod$(\mathcal{Z}(\eta))^{0.8}$ (orange) for (a) a stable and (b) an unstable architecture on CIFAR10.

Note that initial grid bounds are not important as our algorithm can shift those bounds dynamically, however the successive increments between learning rates in the grid must be sufficiently small (on the order of 1×10^{-4} as in our initialization). Since our response surface itself is not guaranteed to monotonically decreased, as shown in Figure 4(b), we employ the cumulative product of $\mathcal{Z}(\eta_i)$, which is a monotonically decreasing function, since $\mathcal{Z}(\eta_i) \in [0, 1)$, and is therefore always guaranteed to converge. The cumulative product (to the power of 0.8) is a good choice because it (a) is always guaranteed to plateau (since $0 \leq \mathcal{Z}(\eta_i) < 1$), which removes the need for some manually tuned threshold and (b) because it dampens noise well. Because the cumulative product on its own degrades to zero rather quickly in many scenarios, raising it to the power of 0.8 regulates this effect. This power is technically tune-able, however we show empirically in Figure 4(a) and 4(b) that 0.8 behaves well for both stable and unstable architectures. Refer to Figure 9 in Appendix C for the performance results of EfficientNetB0.

4   EXPERIMENTS

In this section, we empirically evaluate our algorithm autoHyper and response surface on various network architectures trained using various optimizers and applied to image classification datasets.

4.1   EXPERIMENTAL SETUPS

All experiments are run using an RTX2080Ti, 3 cores of an Intel Xeon Gold 6246 processor, and 64 gigabytes of RAM. We run experiments on CIFAR10 (Krizhevsky et al., 2009), CIFAR100 (Krizhevsky et al., 2009), TinyImageNet (Li et al.), and ImageNet (Russakovsky et al., 2015). On CIFAR10 and CIFAR100, we apply ResNet18 (He et al., 2015), ResNet34 (He et al., 2015), ResNeXt50 (Xie et al., 2016), and DenseNet121 (Huang et al., 2017). On TinyImageNet and ImageNet, we apply ResNet34. For architectures applied to CIFAR10 and CIFAR100, we train using AdaM (Kingma & Ba, 2014), AdaBound (Luo et al., 2019), AdaGrad (Duchi et al., 2011), RMSProp (Tieleman & Hinton, 2012), AdaS$^{(\beta = \{0.8, 0.9, 0.95, 0.975\})}$ (Hosseini & Plataniotis, 2020) (with early-stop), and SLS (Vaswani et al., 2019). For ResNet34 applied to TinyImageNet, we train using AdaM, AdaBound, AdaGrad, and AdaS$^{(\beta = \{0.8, 0.9, 0.95, 0.975\})}$. For ResNet34 applied to ImageNet, we train using AdaM and AdaS$^{(\beta = \{0.9, 0.95, 0.975\})}$. Note that the β in AdaS-variants is known as the *gain factor* and trades between performance and convergence rate : a low β converges faster but at the cost of performance and vice-versa. For each experimental setup we ran one training sequence using suggested learning rates (baseline) and one training sequence using learning rates generated by autoHyper (see Tables 1-4 in Appendix B). Refer to Appendix B for additional setup details.

4.2   RESULTS

Consistent performance across architectures, datasets, and optimizers. We visualize the primary results of each experiment in Figure 5 (additional results are shown in Figure 11 in Appendix C). From these figures we see how well our method generalizes to experimental configurations by noting the consistency in top-1 test accuracies when training using the autoHyper generated initial learning rate vs. the baseline. Further, we note that if there is loss of performance when using an initial learning rate generated by autoHyper, we identify that this loss is $< 1\%$ in all experiments except three: On CIFAR100, the baselines of ResNeXt50 trained using AdaM, ResNext50 trained using RMSProp, and DenseNet121 trained using AdaBound achieve 1.2%, 2.28% and 1.9% better top-1 test accuracy, respectively. We note importantly however that when accounting for the standard deviation of each of these results, only the DenseNet121 experiement maintains its $> 1\%$ improvement. Refer to Appendix C (Tables 5-8) to see the tabulated results of each experiment.

Performance improvement over increased epoch budgets. In reference to Table 6 in Appendix C, we highlight how, of the 29 experimental configurations, when trained using the initial learning rate suggested by autoHyper, only 12 of them outperform the baseline. However, as training progresses, we note that by the end of the fixed epoch budget, 18 of the 29 experiments trained using the initial learning rate suggested by autoHyper outperform the baselines. Further, in many of the cases where baselines perform better, they remain within the standard deviation of trials, and are therefore not significantly better. These results are surprising as our goal with this method was to achieve competitive results in tuning the initial learning rate however, in more than half the cases, our method results in increased performance at a significantly smaller computational cost.

Large deviation from the suggested initial learning rates. Referring to Tables 1-4, we notice the variation in learning rates suggested by autoHyper as compared to the author-suggested learning rates. The learning rates generated by our method reveal the "blind spots" that the authors originally overlooked in their HPO. Interestingly, however, we note the similarity in initial learning for ResNet34 trained using AdaM on CIFAR10. As was reported in Wilson et al. (2017), 0.0003 was proven to be a superior learning rate for AdaM applied to CIFAR10, and our method confirms this. Importantly, our method requires significantly less time than the grid searching technique employed by Wilson et al. (2017) to arrive at this conclusion.

Drastic improvements in AdaM applied to TinyImageNet and ImageNet. ResNet34 trained using AdaM and applied to TinyImageNet and ImageNet achieves final improvements of 3.14% and 4.93% in top-1 test accuracy, respectively (see Table 5 in Appendix C). Such improvements come at a minimal cost using our method, requiring 13 trials (4 hours) and 16 trials (59 hours) for TinyImageNet and ImageNet, respectively (see Figure 3).

Extremely fast and consistent convergence rates. We visualize the convergence rates of our method in Figure 3. Importantly, we identify the consistency of required trials per optimizer across architecture and dataset selection as well as the low convergence times. We identify that the longest convergence time for our method is on ResNet34 trained using $AdaS^{\beta = 0.95}$ applied to ImageNet, which took 31 trials and a total of 114 hours. We note that our method exhibits less consistent results when optimizing using SLS and attribute this to the fact that SLS tends to result in extremely high $\mathcal{Z}(\eta)$ for extended iterations (beyond 20 epochs) and initial learning rates. Despite this, our model still converges by design and results in competitive performance.

Observations on the generalization characteristics of optimizers. Figure 5 identifies the poor generalization characteristics of AdaM, AdaBound, AdaGrad, and SLS where they consistently achieve low training losses, but do not exhibit equivalently high top-1 test accuracies. We note that these observations are similar to those made by Wilson et al. (2017); Li et al. (2019); Jastrzeb-ski et al. (2020). We additionally contribute that AdaS does generalize well. We also highlight SLS' multi-order-of-magnitude tolerance to initial learning rate as well as the stability of the AdaS optimizer, particularly when applied on TinyImageNet.

5 CONCLUSION

Figure 6: $\mathcal{Z}(\eta, \gamma)$ for learning rate (η) and mini-batch size (γ).

In this work we proposed an analytical response surface that acts as auxiliary to training metrics and generalizes well. We proposed an algorithm, autoHyper, that solves this surface and quickly generates learning rates that are competitive to author- suggested values and in some cases, drastically superior. We note that our method only trials learning rates once and is therefore susceptible to random initialization variations, and we leave investigation of multiple trialling to future work. Figure 6 visualizes our response surface over a multi-dimension HP set and highlights how our response surface remains solvable. We identify that autoHyper could be adapted to simultaneously optimize multiple HPs by tracking tangents across this surface towards the minimum, but leave this to future work.

Figure 5: Top-1 test accuracies for each experiment as well as training loss results for CIFAR10 experiments and top-1 training accuracies for TinyImageNet and ImageNet experiments. Titles below plots indicate what experiment the above plots refers to. Legend labels marked by '*' (solid lines) show results for autoHyper generated learning rates and dotted lines are the baselines.

REFERENCES

Takuya Akiba, Shotaro Sano, Toshihiko Yanase, Takeru Ohta, and Masanori Koyama. Optuna: A next-generation hyperparameter optimization framework. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 2623–2631, 2019.

James Bergstra and Yoshua Bengio. Random search for hyper-parameter optimization. *The Journal of Machine Learning Research*, 13(1):281–305, 2012.

James Bergstra, Dan Yamins, and David D Cox. Hyperopt: A python library for optimizing the hyperparameters of machine learning algorithms. In *Proceedings of the 12th Python in science conference*, volume 13, pp. 13–19. Citeseer, 2013.

Dami Choi, Christopher J. Shallue, Zachary Nado, Jaehoon Lee, Chris J. Maddison, and George E. Dahl. On empirical comparisons of optimizers for deep learning, 2020.

Gonzalo I Diaz, Achille Fokoue-Nkoutche, Giacomo Nannicini, and Horst Samulowitz. An effective algorithm for hyperparameter optimization of neural networks. *IBM Journal of Research and Development*, 61(4/5):9–1, 2017.

Tobias Domhan, Jost Tobias Springenberg, and Frank Hutter. Speeding up automatic hyperparameter optimization of deep neural networks by extrapolation of learning curves. In *Twenty-Fourth International Joint Conference on Artificial Intelligence*, 2015.

John Duchi, Elad Hazan, and Yoram Singer. Adaptive subgradient methods for online learning and stochastic optimization. *Journal of machine learning research*, 12(7), 2011.

Katharina Eggensperger, Matthias Feurer, Frank Hutter, James Bergstra, Jasper Snoek, Holger Hoos, and Kevin Leyton-Brown. Towards an empirical foundation for assessing bayesian optimization of hyperparameters. In *NIPS workshop on Bayesian Optimization in Theory and Practice*, volume 10, pp. 3, 2013.

Stefan Falkner, Aaron Klein, and Frank Hutter. Bohb: Robust and efficient hyperparameter optimization at scale, 2018.

Matthias Feurer, Aaron Klein, Katharina Eggensperger, Jost Springenberg, Manuel Blum, and Frank Hutter. Efficient and robust automated machine learning. In *Advances in neural information processing systems*, pp. 2962–2970, 2015a.

Matthias Feurer, Jost Tobias Springenberg, and Frank Hutter. Initializing bayesian hyperparameter optimization via meta-learning. In *Twenty-Ninth AAAI Conference on Artificial Intelligence*, 2015b.

Ian J. Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep Learning*. MIT Press, Cambridge, MA, USA, 2016. http://www.deeplearningbook.org.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition, 2015.

Xin He, Kaiyong Zhao, and Xiaowen Chu. Automl: A survey of the state-of-the-art. *arXiv preprint arXiv:1908.00709*, 2019.

Mahdi S. Hosseini and Konstantinos N. Plataniotis. Adas: Adaptive scheduling of stochastic gradients, 2020.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4700–4708, 2017.

Max Jaderberg, Valentin Dalibard, Simon Osindero, Wojciech M Czarnecki, Jeff Donahue, Ali Razavi, Oriol Vinyals, Tim Green, Iain Dunning, Karen Simonyan, et al. Population based training of neural networks. *arXiv preprint arXiv:1711.09846*, 2017.

Stanislaw Jastrzebski, Maciej Szymczak, Stanislav Fort, Devansh Arpit, Jacek Tabor, Kyunghyun Cho*, and Krzysztof Geras*. The break-even point on optimization trajectories of deep neural networks. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=r1g87C4KwB.

Kirthevasan Kandasamy, Gautam Dasarathy, Junier B Oliva, Jeff Schneider, and Barnabás Póczos. Gaussian process bandit optimisation with multi-fidelity evaluations. In *Advances in Neural Information Processing Systems*, pp. 992–1000, 2016.

Zohar Karnin, Tomer Koren, and Oren Somekh. Almost optimal exploration in multi-armed bandits. In *International Conference on Machine Learning*, pp. 1238–1246, 2013.

Nitish Shirish Keskar, Dheevatsa Mudigere, Jorge Nocedal, Mikhail Smelyanskiy, and Ping Tak Peter Tang. On large-batch training for deep learning: Generalization gap and sharp minima. In *International Conference on Learning Representations*, 2017. URL https://openreview.net/forum?id=H1oyRlYgg.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization, 2014.

Aaron Klein, Stefan Falkner, Simon Bartels, Philipp Hennig, and Frank Hutter. Fast bayesian optimization of machine learning hyperparameters on large datasets. In *Artificial Intelligence and Statistics*, pp. 528–536, 2017.

Lars Kotthoff, Chris Thornton, Holger H Hoos, Frank Hutter, and Kevin Leyton-Brown. Auto-weka 2.0: Automatic model selection and hyperparameter optimization in weka. *The Journal of Machine Learning Research*, 18(1):826–830, 2017.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Fei-Fei Li, Andrej Karpathy, and Justin Johnson. URL `https://tiny-imagenet.herokuapp.com/`.

Liam Li, Kevin Jamieson, Afshin Rostamizadeh, Ekaterina Gonina, Moritz Hardt, Benjamin Recht, and Ameet Talwalkar. Massively parallel hyperparameter tuning. *arXiv preprint arXiv:1810.05934*, 2018.

Lisha Li, Kevin Jamieson, Giulia DeSalvo, Afshin Rostamizadeh, and Ameet Talwalkar. Hyperband: A novel bandit-based approach to hyperparameter optimization. *The Journal of Machine Learning Research*, 18(1):6765–6816, 2017.

Yuanzhi Li, Colin Wei, and Tengyu Ma. Towards explaining the regularization effect of initial large learning rate in training neural networks. In *Advances in Neural Information Processing Systems*, pp. 11674–11685, 2019.

Gang Luo. A review of automatic selection methods for machine learning algorithms and hyperparameter values. *Network Modeling Analysis in Health Informatics and Bioinformatics*, 5(1):18, 2016.

Liangchen Luo, Yuanhao Xiong, Yan Liu, and Xu Sun. Adaptive gradient methods with dynamic bound of learning rate, 2019.

Dougal Maclaurin, David Duvenaud, and Ryan Adams. Gradient-based hyperparameter optimization through reversible learning. In *International Conference on Machine Learning*, pp. 2113–2122, 2015.

Shinichi Nakajima, Masashi Sugiyama, S Derin Babacan, and Ryota Tomioka. Global analytic solution of fully-observed variational bayesian matrix factorization. *Journal of Machine Learning Research*, 14(Jan):1–37, 2013.

Roman Novak, Yasaman Bahri, Daniel A. Abolafia, Jeffrey Pennington, and Jascha Sohl-Dickstein. Sensitivity and generalization in neural networks: an empirical study. In *International Conference on Learning Representations*, 2018. URL `https://openreview.net/forum?id=HJC2SzZCW`.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision (IJCV)*, 115(3):211–252, 2015. doi: 10.1007/s11263-015-0816-y.

Prabhu Teja Sivaprasad, Florian Mai, Thijs Vogels, Martin Jaggi, and François Fleuret. Optimizer benchmarking needs to account for hyperparameter tuning, 2020.

Jasper Snoek, Hugo Larochelle, and Ryan P Adams. Practical bayesian optimization of machine learning algorithms. In *Advances in neural information processing systems*, pp. 2951–2959, 2012.

Jasper Snoek, Oren Rippel, Kevin Swersky, Ryan Kiros, Nadathur Satish, Narayanan Sundaram, Mostofa Patwary, Mr Prabhat, and Ryan Adams. Scalable bayesian optimization using deep neural networks. In *International conference on machine learning*, pp. 2171–2180, 2015.

Jost Tobias Springenberg, Aaron Klein, Stefan Falkner, and Frank Hutter. Bayesian optimization with robust bayesian neural networks. In *Advances in neural information processing systems*, pp. 4134–4142, 2016.

Kevin Swersky, Jasper Snoek, and Ryan P Adams. Multi-task bayesian optimization. In *Advances in neural information processing systems*, pp. 2004–2012, 2013.

Kevin Swersky, Jasper Snoek, and Ryan Prescott Adams. Freeze-thaw bayesian optimization. *arXiv preprint arXiv:1406.3896*, 2014.

Tijmen Tieleman and Geoffrey Hinton. Lecture 6.5-rmsprop: Divide the gradient by a running average of its recent magnitude. *COURSERA: Neural networks for machine learning*, 4(2):26–31, 2012.

Sharan Vaswani, Aaron Mishkin, Issam H. Laradji, Mark Schmidt, Gauthier Gidel, and Simon Lacoste-Julien. Painless stochastic gradient: Interpolation, line-search, and convergence rates. *CoRR*, abs/1905.09997, 2019. URL http://arxiv.org/abs/1905.09997.

Ashia C. Wilson, Rebecca Roelofs, Mitchell Stern, Nathan Srebro, and Benjamin Recht. The marginal value of adaptive gradient methods in machine learning, 2017.

Saining Xie, Ross Girshick, Piotr Dollár, Zhuowen Tu, and Kaiming He. Aggregated residual transformations for deep neural networks, 2016.

Steven R Young, Derek C Rose, Thomas P Karnowski, Seung-Hwan Lim, and Robert M Patton. Optimizing deep learning hyper-parameters through an evolutionary algorithm. In *Proceedings of the Workshop on Machine Learning in High-Performance Computing Environments*, pp. 4. ACM, 2015.

Tong Yu and Hong Zhu. Hyper-parameter optimization: A review of algorithms and applications. *arXiv preprint arXiv:2003.05689*, 2020.

Xiang Zhang, Xiaocong Chen, Lina Yao, Chang Ge, and Manqing Dong. Deep neural network hyperparameter optimization with orthogonal array tuning. In *International Conference on Neural Information Processing*, pp. 287–295. Springer, 2019.

A   RANK BEHAVIOUR OVER MULTIPLE EPOCHS

(a) AdaM   (b) AdaGrad

(c) AdaS $\beta = 0.8$ (d) RMSProp

Figure 7: Rank ($\mathcal{Z}(\eta)$) for various learning rates on VGG16 trained using AdaM, AdaGrad, AdaS $\beta = 0.8$, and RMSProp and applied to CIFAR10. A fixed epoch budget of 20 was used. We highlight how across these 20 epochs, very little progress is made beyond the first first epochs. It is from this analysis that we choose our epoch range of $T = 5$.

(a) AdaM   (b) AdaGrad

(c) AdaS $\beta = 0.8$ (d) RMSProp

Figure 8: ($\mathcal{Z}(\eta)$) for various learning rates on ResNet34 trained using AdaM, AdaGrad, AdaS $\beta = 0.8$, and RMSProp and applied to CIFAR10. A fixed epoch budget of 20 was used. We highlight how across these 20 epochs, very little progress is made beyond the first first epochs. It is from this analysis that we choose our epoch range of $T = 5$.

B   ADDITIONAL EXPERIMENTAL DETAILS FOR SUBSECTION 4.1

We note the additional configurations for our experimental setups.

Datasets: For CIFAR10 and CIFAR100, we perform random cropping to 32×32 and random horizontal flipping on the training images and make no alterations to the test set. For TinyImageNet,

we perform random resized cropping to 64×64 and random horizontal flipping on the training images and center crop resizing to 64×64 on the test set. For ImageNet, we follow He et al. (2015) and perform random resized cropping to 224×244 and random horizontal flipping and 256×256 resizing with 224×224 center cropping on the test set.

Additional Configurations: Experiments on CIFAR10, CIFAR100, and TinyImageNet used mini-batch sizes of 128 and ImageNet experiments used mini-batch sizes of 256. For weight decay, 5×10^{-4} was used for AdaS-variants on CIFAR10 and CIFAR100 experiments and 1×10^{-4} for all optimizers on TinyImageNet and ImageNet experiments, with the exception of AdaM using a weight decay of 7.8125×10^{-6}. For AdaS-variant, the momentum rate for momentum-SGD was set to 0.9. All other hyper-parameters for each respective optimizer remained default as reported in their original papers. For CIFAR10 and CIFAR100, we use the manually tuned suggested learning rates as reported in Wilson et al. (2017) for AdaM, RMSProp, and AdaGrad. For TinyImageNet and ImageNet, we use the suggested learning rates as reported in each optimizer's respective paper. Refer to Tables 1-4 to see exactly which learning rates were used, as well as the learning rates generated by autoHyper. CIFAR10, CIFAR100, and TinyImageNet experiments were trained for 5 trials with a maximum of 250 epochs and ImageNet experiments were trained for 3 trials with a maximum of 150 epochs. Due to AdaS' stable test accuracy behaviour as demonstrated by Hosseini & Plataniotis (2020), an early-stop criteria, monitoring testing accuracy, was used for CIFAR10, CIFAR100, and ImageNet experiments. For CIFAR10 and CIFAR100, a threshold of 1×10^{-3} for AdaS$^{\beta = 0.8}$ and 1×10^{-4} for AdaS$^{\beta = \{0.9, 0.95\}}$ and patience window of 10 epochs. For ImageNet, a threshold of 1×10^{-4} for AdaS$^{\beta = \{0.8, 0.9, 0.95\}}$ and patience window of 20 epochs. No early stop is used for AdaS$^{\beta = 0.975}$.

Learning Rates: We report every learning rate in Tables 1-4.

Table 1: Learning rates for ResNet34 experiments. Left inner columns show suggested, right inner columns show autoHyper generated. Note that the superscript for AdaS-variants indicates their β gain factor.

Optimizer	CIFAR10		CIFAR100		TinyImageNet		ImagetNet	
AdaM	0.0003	0.000333	0.0003	0.000241	0.001	0.0001965	0.001	0.0001965
AdaBound	0.001	0.000347	0.001	0.000347	0.001	0.0000944	-	-
AdaGrad	0.01	0.002861	0.01	0.002236	0.01	0.0022359	-	-
AdaS$^{(0.8)}$	0.03	0.012374	0.03	0.010401	0.03	0.010185	-	-
AdaS$^{(0.9)}$	0.03	0.012374	0.03	0.010190	0.03	0.0085857	0.02	0.011479
AdaS$^{(0.95)}$	0.03	0.015336	0.03	0.015025	0.03	0.0085857	0.02	0.011479
AdaS$^{(0.975)}$	0.03	0.012374	0.03	0.010190	0.03	0.0085857	0.02	0.011479
RMSProp	0.0003	0.000168	0.0003	0.000197	-	-	-	-
SLS	1.0	0.034191	1.0	0.034191	-	-	-	-

Table 2: Learning rates for ResNet18 experiments. Left inner columns show suggested, right inner columns show autoHyper generated.

Optimizer	CIFAR10		CIFAR100	
AdaM	0.0003	0.0006756	0.0003	0.0006756
AdaBound	0.001	0.00036040	0.001	0.00024896
AdaGrad	0.01	0.0049724	0.01	0.0049724
AdaS$^{(\beta = 0.8)}$	0.03	0.0126594	0.03	0.0126594
AdaS$^{(\beta = 0.9)}$	0.03	0.0104254	0.03	0.0126594
AdaS$^{(\beta = 0.95)}$	0.03	0.01042544	0.03	0.01042543
AdaS$^{(\beta = 0.975)}$	0.03	0.0104254	0.03	0.007071
RMSProp	0.0003	0.0004697	0.0003	0.0004697
SLS	1.0	0.03419134	1.0	0.0341913

C ADDITIONAL RESULTS FOR SUBSECTION 4.2

Table 3: Learning rates for ResNeXt50 experiments. Left inner columns show suggested, right inner columns show autoHyper generated.

Optimizer	CIFAR10		CIFAR100	
AdaM	0.0003	0.0006756	0.0003	0.0006756
AdaBound	0.001	0.00036040	0.001	0.00024896
AdaGrad	0.01	0.0049724	0.01	0.0049724
AdaS$^{(\beta = 0.8)}$	0.03	0.0126594	0.03	0.0126594
AdaS$^{(\beta = 0.9)}$	0.03	0.0104254	0.03	0.0126594
AdaS$^{(\beta = 0.95)}$	0.03	0.023134	0.03	0.022666
AdaS$^{(\beta = 0.975)}$	0.03	0.0104254	0.03	0.007071
RMSProp	0.0003	0.0004697	0.0003	0.0004697
SLS	1.0	0.03419134	1.0	0.0341913

Table 4: Learning rates for DenseNet121 experiments. Left inner columns show suggested, right inner columns show autoHyper generated.

Optimizer	CIFAR10		CIFAR100	
AdaM	0.0003	0.0020109	0.0003	0.00093162
AdaBound	0.001	0.0030176	0.001	0.003147979
AdaGrad	0.01	0.01537206	0.01	0.01537206
AdaS$^{(\beta = 0.8)}$	0.03	0.06107176	0.03	0.03978104
AdaS$^{(\beta = 0.9)}$	0.03	0.0598363	0.03	0.050414
AdaS$^{(\beta = 0.95)}$	0.03	0.0492772	0.03	0.0357048479
AdaS$^{(\beta = 0.975)}$	0.03	0.0598363	0.03	0.0504143
RMSProp	0.0003	0.00201093	0.0003	0.00067564
SLS	1.0	0.0031184	1.0	0.087943

Figure 9: Test accuracy and trianing loss for EfficientNetB0 applied to CIFAR100. Importantly, EfficientNetB0 is an unstable network architecture in relation to our response surface and yet our method, autoHyper, is still able to converge and achieve competitive performance.

Figure 10: Full results of CIFAR100, TinyImageNet, and ImageNet experiments. Top-1 test accuracy and training losses are reported for CIFAR100 experiments and top-1 and top-5 test and training accuracies are reported for TinyImageNet and ImageNet. Titles below the figures indicate to which experiments the above figures belong to. As before, lines indicated by the '*' (solid lines), are results using initial learning rate as suggested by autoHyper.

Figure 11: Demonstration of the importance of initial learning rate in scheduled learning rate case, for ResNet18 applied on CIFAR10, using Step-Decay method with step-size = 25 epochs and decay rate = 0.5. As before, the dotted line represents the baseline results, with initial learning rate = 0.1, and the solid line represents the results using autoHyper's suggested learning rate of 0.008585. These results highlight the importance of initial learning rate, even when using a scheduled learning rate heuristic, and demonstrates the importance of the additional step-size and decay rate hyper-parameters. Despite better initial performance from the autoHyper suggest learning rate, the step-size and decay rate choice cause the performance to plateau too early.

Table 5: List of ResNet34 top-1 test accuracy using various optimizers and applied to various datasets. Note that each cell reports the average accuracy over each experimental trial, sub-scripted by the standard deviation over the trials. Values on the left are from trials trained using the initial learning rate as generated by autoHyper. Values on the right are from trials trained using the suggested initial learning rate. Note a '*' indicates that early-stop has been activated.

Dataset	Optimizer	Epoch 50	Epoch 100	Epoch 150	Epoch 200	Epoch 250
CIFAR10	AdaBound	$\mathbf{91.66}_{\pm 0.33}/90.84_{\pm 0.17}$	$\mathbf{92.37}_{\pm 0.25}/92.03_{\pm 0.44}$	$\mathbf{92.78}_{\pm 0.20}/92.67_{\pm 0.14}$	$\mathbf{92.79}_{\pm 0.42}/92.59_{\pm 0.13}$	$\mathbf{93.24}_{\pm 0.17}/92.74_{\pm 0.16}$
	AdaGrad	$89.41_{\pm 0.39}/\mathbf{90.17}_{\pm 0.61}$	$90.30_{\pm 0.33}/\mathbf{91.10}_{\pm 0.25}$	$90.77_{\pm 0.35}/\mathbf{91.34}_{\pm 0.37}$	$90.67_{\pm 0.30}/\mathbf{91.40}_{\pm 0.15}$	$90.94_{\pm 0.14}/\mathbf{91.50}_{\pm 0.24}$
	AdaM	$91.44_{\pm 0.19}/\mathbf{91.54}_{\pm 0.35}$	$\mathbf{92.72}_{\pm 0.15}/92.71_{\pm 0.27}$	$92.93_{\pm 0.21}/\mathbf{93.07}_{\pm 0.33}$	$93.06_{\pm 0.34}/\mathbf{93.17}_{\pm 0.30}$	$\mathbf{93.39}_{\pm 0.31}/93.22_{\pm 0.36}$
	AdaS$^{0.8}$	$\mathbf{93.35}_{\pm 0.14}/93.04_{\pm 0.13}$	$\mathbf{93.40}_{\pm 0.15}/93.03_{\pm 0.16}$	$\mathbf{93.40}^{*}_{\pm 0.15}/93.00_{\pm 0.17}$	$\mathbf{93.40}^{*}_{\pm 0.15}/93.02_{\pm 0.16}$	$\mathbf{93.40}^{*}_{\pm 0.15}/93.02_{\pm 0.13}$
	AdaS$^{0.9}$	$94.00_{\pm 0.13}/\mathbf{94.35}_{\pm 0.22}$	$94.25^{*}_{\pm 0.22}/\mathbf{94.48}_{\pm 0.13}$	$94.25^{*}_{\pm 0.22}/\mathbf{94.45}_{\pm 0.11}$	$94.25^{*}_{\pm 0.22}/\mathbf{94.47}_{\pm 0.13}$	$94.2^{*}5_{\pm 0.22}/\mathbf{94.46}_{\pm 0.12}$
	AdaS$^{0.95}$	$91.90_{\pm 0.25}/\mathbf{92.03}_{\pm 0.33}$	$94.91_{\pm 0.16}/\mathbf{95.14}_{\pm 0.16}$	$95.08^{*}_{\pm 0.18}/\mathbf{95.20}_{\pm 0.11}$	$95.08^{*}_{\pm 0.18}/\mathbf{95.20}_{\pm 0.11}$	$95.08^{*}_{\pm 0.18}/\mathbf{95.20}_{\pm 0.11}$
	AdaS$^{0.975}$	$87.68_{\pm 0.95}/\mathbf{88.91}_{\pm 1.30}$	$92.92_{\pm 0.32}/\mathbf{93.09}_{\pm 0.52}$	$94.75_{\pm 0.12}/\mathbf{94.99}_{\pm 0.23}$	$95.01_{\pm 0.13}/\mathbf{95.14}_{\pm 0.34}$	$95.13_{\pm 0.11}/\mathbf{95.24}_{\pm 0.15}$
	RMSProp	$90.69_{\pm 0.47}/\mathbf{90.86}_{\pm 0.58}$	$91.41_{\pm 0.55}/\mathbf{91.59}_{\pm 0.77}$	$92.22_{\pm 0.68}/\mathbf{92.69}_{\pm 0.33}$	$\mathbf{92.94}_{\pm 0.33}/92.88_{\pm 0.30}$	$\mathbf{93.03}_{\pm 0.23}/92.90_{\pm 0.29}$
	SLS	$\mathbf{93.30}_{\pm 0.16}/93.28_{\pm 0.10}$	$93.41_{\pm 0.09}/\mathbf{93.48}_{\pm 0.09}$	$93.39_{\pm 0.10}/\mathbf{93.49}_{\pm 0.09}$	$93.34_{\pm 0.13}/\mathbf{93.41}_{\pm 0.08}$	$93.33_{\pm 0.06}/\mathbf{93.45}_{\pm 0.16}$
CIFAR100	AdaBound	$\mathbf{69.21}_{\pm 0.59}/68.02_{\pm 0.75}$	$\mathbf{71.38}_{\pm 0.44}/70.57_{\pm 0.40}$	$\mathbf{72.39}_{\pm 0.27}/71.67_{\pm 0.49}$	$\mathbf{72.83}_{\pm 0.16}/72.08_{\pm 0.27}$	$\mathbf{73.15}_{\pm 0.24}/71.94_{\pm 0.66}$
	AdaGrad	$\mathbf{65.35}_{\pm 0.46}/65.15_{\pm 0.27}$	$\mathbf{66.72}_{\pm 0.34}/66.58_{\pm 0.38}$	$\mathbf{67.03}_{\pm 0.50}/66.91_{\pm 0.31}$	$\mathbf{67.16}_{\pm 0.50}/66.97_{\pm 0.25}$	$\mathbf{67.43}_{\pm 0.59}/67.02_{\pm 0.23}$
	AdaM	$68.31_{\pm 0.48}/\mathbf{68.66}_{\pm 0.46}$	$69.71_{\pm 0.63}/\mathbf{69.78}_{\pm 0.27}$	$70.43_{\pm 0.29}/\mathbf{70.45}_{\pm 0.42}$	$\mathbf{70.98}_{\pm 0.43}/70.61_{\pm 0.33}$	$\mathbf{71.43}_{\pm 0.28}/71.11_{\pm 0.37}$
	AdaS$^{0.8}$	$73.58_{\pm 0.31}/\mathbf{74.18}_{\pm 0.32}$	$73.58^{*}_{\pm 0.36}/\mathbf{74.21}_{\pm 0.35}$	$73.58^{*}_{\pm 0.36}/\mathbf{74.22}_{\pm 0.35}$	$73.58^{*}_{\pm 0.36}/\mathbf{74.19}_{\pm 0.24}$	$73.58^{*}_{\pm 0.36}/\mathbf{74.21}_{\pm 0.26}$
	AdaS$^{0.9}$	$75.54_{\pm 0.25}/\mathbf{75.64}_{\pm 0.25}$	$75.78^{*}_{\pm 0.21}/\mathbf{76.02}_{\pm 0.10}$	$75.78^{*}_{\pm 0.21}/\mathbf{76.00}_{\pm 0.13}$	$75.78^{*}_{\pm 0.21}/\mathbf{76.05}_{\pm 0.11}$	$75.78^{*}_{\pm 0.21}/\mathbf{75.99}_{\pm 0.09}$
	AdaS$^{0.95}$	$71.25_{\pm 0.90}/\mathbf{71.57}_{\pm 1.00}$	$77.48^{*}_{\pm 0.37}/\mathbf{77.53}_{\pm 0.18}$	$77.48^{*}_{\pm 0.37}/\mathbf{77.60}_{\pm 0.22}$	$77.48^{*}_{\pm 0.37}/\mathbf{77.60}_{\pm 0.22}$	$77.48^{*}_{\pm 0.37}/\mathbf{77.60}_{\pm 0.22}$
	AdaS$^{0.975}$	$62.11_{\pm 2.01}/\mathbf{62.49}_{\pm 1.60}$	$\mathbf{75.15}_{\pm 0.26}/74.48_{\pm 0.53}$	$\mathbf{78.44}_{\pm 0.34}/77.81_{\pm 0.23}$	$\mathbf{78.15}_{\pm 0.22}/77.76_{\pm 0.38}$	$\mathbf{78.26}_{\pm 0.35}/78.00_{\pm 0.28}$
	RMSProp	$67.17_{\pm 1.00}/\mathbf{67.69}_{\pm 0.62}$	$68.78_{\pm 1.29}/\mathbf{69.28}_{\pm 0.29}$	$\mathbf{70.23}_{\pm 0.50}/69.96_{\pm 0.48}$	$70.20_{\pm 0.49}/\mathbf{70.39}_{\pm 0.50}$	$\mathbf{70.57}_{\pm 0.40}/70.25_{\pm 0.29}$
	SLS	$\mathbf{66.81}_{\pm 1.25}/64.88_{\pm 1.23}$	$\mathbf{73.48}_{\pm 0.24}/73.02_{\pm 0.20}$	$\mathbf{73.78}_{\pm 0.19}/73.14_{\pm 0.21}$	$\mathbf{73.74}_{\pm 0.32}/73.24_{\pm 0.11}$	$\mathbf{73.77}_{\pm 0.12}/73.22_{\pm 0.11}$
TinyImageNet	AdaBound	$\mathbf{55.07}_{\pm 1.06}/54.15_{\pm 1.13}$	$\mathbf{55.75}_{\pm 0.34}/55.37_{\pm 0.15}$	$\mathbf{56.66}_{\pm 0.30}/55.00_{\pm 0.85}$	$\mathbf{56.06}_{\pm 0.04}/55.05_{\pm 0.58}$	$\mathbf{56.22}_{\pm 0.17}/55.48_{\pm 0.67}$
	AdaGrad	$52.01_{\pm 0.43}/\mathbf{52.75}_{\pm 0.60}$	$54.01_{\pm 0.39}/\mathbf{54.27}_{\pm 0.77}$	$54.46_{\pm 0.68}/\mathbf{54.94}_{\pm 0.60}$	$54.69_{\pm 0.30}/\mathbf{55.12}_{\pm 0.27}$	$55.04_{\pm 0.54}/\mathbf{55.81}_{\pm 0.84}$
	AdaM	$\mathbf{53.98}_{\pm 1.14}/47.43_{\pm 1.60}$	$\mathbf{54.67}_{\pm 0.93}/48.97_{\pm 1.86}$	$\mathbf{55.86}_{\pm 0.26}/52.22_{\pm 0.51}$	$\mathbf{54.81}_{\pm 0.73}/50.14_{\pm 1.20}$	$\mathbf{54.46}_{\pm 1.14}/52.13_{\pm 1.14}$
	AdaS$^{0.8}$	$\mathbf{58.06}_{\pm 0.54}/57.85_{\pm 0.55}$	$\mathbf{58.20}_{\pm 0.42}/58.06_{\pm 0.48}$	$\mathbf{58.13}_{\pm 0.34}/57.99_{\pm 0.36}$	$\mathbf{58.18}_{\pm 0.43}/58.16_{\pm 0.40}$	$\mathbf{58.02}_{\pm 0.42}/57.98_{\pm 0.44}$
	AdaS$^{0.9}$	$54.45_{\pm 0.91}/\mathbf{58.95}_{\pm 0.45}$	$58.99_{\pm 0.25}/\mathbf{59.97}_{\pm 0.33}$	$\mathbf{60.08}_{\pm 0.40}/59.97_{\pm 0.40}$	$\mathbf{61.38}_{\pm 0.49}/60.01_{\pm 0.30}$	$\mathbf{61.56}_{\pm 0.58}/59.91_{\pm 0.45}$
	AdaS$^{0.95}$	$56.18_{\pm 1.36}/\mathbf{57.41}_{\pm 0.71}$	$\mathbf{60.83}_{\pm 0.10}/60.29_{\pm 0.30}$	$\mathbf{61.17}_{\pm 0.28}/60.72_{\pm 0.06}$	$\mathbf{61.10}_{\pm 0.38}/61.03_{\pm 0.14}$	$\mathbf{61.28}_{\pm 0.44}/60.74_{\pm 0.20}$
	AdaS$^{0.975}$	$54.87_{\pm 1.22}/\mathbf{55.19}_{\pm 0.74}$	$58.91_{\pm 0.57}/\mathbf{59.19}_{\pm 0.49}$	$\mathbf{60.62}_{\pm 0.69}/60.22_{\pm 0.27}$	$\mathbf{61.70}_{\pm 0.39}/61.13_{\pm 0.37}$	$\mathbf{61.81}_{\pm 0.45}/61.44_{\pm 0.27}$
ImageNet	AdaM	$\mathbf{66.22}_{\pm 0.08}/62.14_{\pm 0.29}$	$\mathbf{68.17}_{\pm 0.07}/63.17_{\pm 0.21}$	$\mathbf{68.68}_{\pm 0.24}/63.75_{\pm 0.08}$	-	-
	AdaS$^{0.9}$	$\mathbf{71.61}_{\pm 0.10}/71.48_{\pm 0.35}$	$71.87^{*}_{\pm 0.20}/\mathbf{72.11}_{\pm 0.16}$	$71.87^{*}_{\pm 0.20}/\mathbf{72.11}_{\pm 0.16}$	-	-
	AdaS$^{0.95}$	$67.52_{\pm 0.47}/\mathbf{68.15}_{\pm 0.21}$	$\mathbf{72.88}_{\pm 0.03}/72.75_{\pm 0.34}$	$\mathbf{73.09}_{\pm 0.23}/73.05_{\pm 0.17}$	-	-
	AdaS$^{0.975}$	$\mathbf{58.25}_{\pm 0.34}/58.09_{\pm 0.36}$	$69.17_{\pm 0.09}/\mathbf{69.42}_{\pm 0.24}$	$72.42_{\pm 0.15}/\mathbf{72.52}_{\pm 0.03}$	-	-

Table 6: List of ResNet18 top-1 test accuracies using various optimizers and applied to various datasets. Note that each cell reports the average accuracy over each experimental trial, sub-scripted by the standard deviation over the trials. Values on the left are from trials trained using the initial learning rate as generated by autoHyper. Values on the right are from trials trained using the suggested initial learning rate. Note a '*' indicates that early-stop has been activated.

Dataset	Optimizer	Epoch 50	Epoch 100	Epoch 150	Epoch 200	Epoch 250
CIFAR10	AdaBound	$\mathbf{91.24}_{\pm0.21}/90.35_{\pm0.51}$	$\mathbf{92.25}_{\pm0.21}/91.64_{\pm0.42}$	$\mathbf{92.69}_{\pm0.14}/92.05_{\pm0.25}$	$\mathbf{92.79}_{\pm0.24}/92.20_{\pm0.26}$	$\mathbf{92.85}_{\pm0.06}/92.35_{\pm0.18}$
	AdaGrad	$89.42_{\pm0.22}/\mathbf{89.67}_{\pm0.40}$	$90.39_{\pm0.18}/\mathbf{90.79}_{\pm0.30}$	$90.55_{\pm0.14}/\mathbf{91.16}_{\pm0.23}$	$90.75_{\pm0.13}/\mathbf{91.20}_{\pm0.26}$	$90.87_{\pm0.14}/\mathbf{91.23}_{\pm0.25}$
	AdaM	$\mathbf{91.43}_{\pm0.42}/91.29_{\pm0.45}$	$\mathbf{92.17}_{\pm0.36}/92.16_{\pm0.13}$	$\mathbf{92.63}_{\pm0.15}/92.37_{\pm0.17}$	$\mathbf{92.88}_{\pm0.32}/92.65_{\pm0.21}$	$\mathbf{92.95}_{\pm0.24}/92.93_{\pm0.22}$
	AdaS$^{0.8}$	$92.81_{\pm0.13}/\mathbf{92.87}_{\pm0.23}$	$92.80^{*}_{\pm0.16}/\mathbf{92.92}_{\pm0.19}$	$92.80^{*}_{\pm0.16}/\mathbf{92.92}_{\pm0.19}$	$92.80^{*}_{\pm0.16}/\mathbf{92.92}_{\pm0.19}$	$92.80^{*}_{\pm0.16}/\mathbf{92.92}_{\pm0.19}$
	AdaS$^{0.9}$	$93.71_{\pm0.04}/\mathbf{94.09}_{\pm0.14}$	$93.75^{*}_{\pm0.12}/\mathbf{94.05}_{\pm0.10}$	$93.75^{*}_{\pm0.12}/\mathbf{94.05}_{\pm0.10}$	$93.75^{*}_{\pm0.12}/\mathbf{94.05}_{\pm0.10}$	$93.75^{*}_{\pm0.12}/\mathbf{94.05}_{\pm0.10}$
	AdaS$^{0.95}$	$\mathbf{91.96}_{\pm0.35}/91.89_{\pm1.10}$	$94.69_{\pm0.15}/\mathbf{94.81}_{\pm0.16}$	$94.74^{*}_{\pm0.16}/\mathbf{94.93}_{\pm0.11}$	$94.74^{*}_{\pm0.16}/\mathbf{94.93}_{\pm0.11}$	$94.74^{*}_{\pm0.16}/\mathbf{94.93}_{\pm0.11}$
	AdaS$^{0.975}$	$87.99_{\pm1.18}/\mathbf{88.05}_{\pm1.19}$	$93.35_{\pm0.43}/\mathbf{93.46}_{\pm0.12}$	$94.74_{\pm0.10}/\mathbf{94.77}_{\pm0.22}$	$94.88_{\pm0.07}/\mathbf{95.07}_{\pm0.22}$	$94.94_{\pm0.04}/\mathbf{95.14}_{\pm0.20}$
	RMSProp	$90.35_{\pm1.21}/\mathbf{90.98}_{\pm0.36}$	$91.85_{\pm0.19}/\mathbf{91.88}_{\pm0.47}$	$\mathbf{92.26}_{\pm0.16}/92.25_{\pm0.16}$	$\mathbf{92.66}_{\pm0.12}/92.39_{\pm0.38}$	$\mathbf{92.69}_{\pm0.33}/92.62_{\pm0.30}$
	SLS	$\mathbf{93.30}_{\pm0.16}/93.28_{\pm0.10}$	$93.41_{\pm0.09}/\mathbf{93.48}_{\pm0.09}$	$93.39_{\pm0.10}/\mathbf{93.49}_{\pm0.09}$	$93.34_{\pm0.13}/\mathbf{93.41}_{\pm0.08}$	$93.33_{\pm0.06}/\mathbf{93.45}_{\pm0.16}$
CIFAR100	AdaBound	$\mathbf{70.15}_{\pm0.31}/68.75_{\pm0.42}$	$\mathbf{72.29}_{\pm0.21}/70.89_{\pm0.26}$	$\mathbf{72.91}_{\pm0.24}/71.60_{\pm0.40}$	$\mathbf{73.10}_{\pm0.38}/71.86_{\pm0.18}$	$\mathbf{73.16}_{\pm0.25}/72.04_{\pm0.30}$
	AdaGrad	$66.07_{\pm0.36}/\mathbf{66.12}_{\pm0.53}$	$\mathbf{67.39}_{\pm0.48}/67.37_{\pm0.39}$	$\mathbf{67.62}_{\pm0.52}/67.50_{\pm0.57}$	$\mathbf{67.85}_{\pm0.57}/67.72_{\pm0.31}$	$67.75_{\pm0.56}/\mathbf{67.76}_{\pm0.50}$
	AdaM	$68.32_{\pm0.65}/\mathbf{68.51}_{\pm0.39}$	$69.33_{\pm0.42}/\mathbf{69.56}_{\pm0.29}$	$69.60_{\pm0.18}/\mathbf{70.07}_{\pm0.31}$	$69.72_{\pm0.22}/\mathbf{70.49}_{\pm0.45}$	$70.09_{\pm0.35}/\mathbf{70.34}_{\pm0.27}$
	AdaS$^{0.8}$	$73.32_{\pm0.30}/\mathbf{73.48}_{\pm0.12}$	$73.38^{*}_{\pm0.28}/\mathbf{73.59}_{\pm0.09}$	$73.38^{*}_{\pm0.28}/\mathbf{73.59}_{\pm0.09}$	$73.38^{*}_{\pm0.28}/\mathbf{73.59}_{\pm0.09}$	$73.38^{*}_{\pm0.28}/\mathbf{73.59}_{\pm0.09}$
	AdaS$^{0.9}$	$\mathbf{75.24}_{\pm0.27}/74.98_{\pm0.15}$	$75.27^{*}_{\pm0.28}/75.15_{\pm0.17}$	$75.27^{*}_{\pm0.28}/75.15_{\pm0.17}$	$75.27^{*}_{\pm0.28}/75.15_{\pm0.17}$	$\mathbf{75.27}^{*}_{\pm0.28}/75.15_{\pm0.17}$
	AdaS$^{0.95}$	$\mathbf{74.40}_{\pm0.17}/73.86_{\pm0.17}$	$76.44_{\pm0.30}/76.32_{\pm0.33}$	$76.44_{\pm0.34}/\mathbf{76.47}_{\pm0.31}$	$76.49^{*}_{\pm0.37}/\mathbf{76.53}_{\pm0.30}$	$76.49^{*}_{\pm0.37}/\mathbf{76.53}_{\pm0.30}$
	AdaS$^{0.975}$	$63.62_{\pm1.70}/\mathbf{64.44}_{\pm0.99}$	$\mathbf{74.21}_{\pm0.25}/73.79_{\pm0.54}$	$76.59_{\pm0.19}/\mathbf{77.05}_{\pm0.10}$	$76.62_{\pm0.14}/\mathbf{77.15}_{\pm0.19}$	$76.68_{\pm0.18}/\mathbf{77.23}_{\pm0.09}$
	RMSProp	$66.29_{\pm0.42}/\mathbf{66.52}_{\pm1.41}$	$68.48_{\pm0.31}/\mathbf{68.89}_{\pm0.43}$	$68.88_{\pm0.20}/\mathbf{69.10}_{\pm0.36}$	$69.29_{\pm0.55}/\mathbf{69.78}_{\pm0.46}$	$69.28_{\pm0.50}/\mathbf{70.08}_{\pm0.23}$
	SLS	$\mathbf{66.81}_{\pm1.25}/64.88_{\pm1.23}$	$\mathbf{73.48}_{\pm0.24}/73.02_{\pm0.20}$	$\mathbf{73.78}_{\pm0.19}/73.14_{\pm0.21}$	$\mathbf{73.74}_{\pm0.32}/73.24_{\pm0.11}$	$\mathbf{73.77}_{\pm0.12}/73.22_{\pm0.11}$

Table 7: List of ResNeXt50 top-1 test accuracies using various optimizers and applied to various datasets. Note that each cell reports the average accuracy over each experimental trial, sub-scripted by the standard deviation over the trials. Values on the left are from trials trained using the initial learning rate as generated by autoHyper. Values on the right are from trials trained using the suggested initial learning rate. Note a '*' indicates that early-stop has been activated.

Dataset	Optimizer	Epoch 50	Epoch 100	Epoch 150	Epoch 200	Epoch 250
CIFAR10	AdaBound	$88.71_{\pm1.28}/\mathbf{89.01_{\pm0.55}}$	$\mathbf{90.90_{\pm0.25}}/90.75_{\pm0.39}$	$90.76_{\pm0.65}/\mathbf{91.23_{\pm0.24}}$	$\mathbf{91.63_{\pm0.30}}/91.55_{\pm0.29}$	$\mathbf{91.69_{\pm0.33}}/91.42_{\pm0.42}$
	AdaGrad	$87.80_{\pm1.32}/\mathbf{87.85_{\pm0.91}}$	$89.25_{\pm0.33}/\mathbf{89.37_{\pm0.23}}$	$\mathbf{89.79_{\pm0.27}}/89.63_{\pm0.69}$	$\mathbf{90.07_{\pm0.27}}/89.80_{\pm0.11}$	$\mathbf{90.13_{\pm0.19}}/90.07_{\pm0.27}$
	AdaM	$\mathbf{90.11_{\pm0.59}}/89.74_{\pm0.89}$	$91.15_{\pm0.19}/\mathbf{91.28_{\pm0.45}}$	$91.68_{\pm0.26}/\mathbf{91.82_{\pm0.27}}$	$91.61_{\pm0.24}/\mathbf{92.07_{\pm0.17}}$	$92.12_{\pm0.07}/\mathbf{92.18_{\pm0.31}}$
	AdaS$^{0.8}$	$91.51_{\pm0.22}/\mathbf{91.56_{\pm0.13}}$	$91.49^*_{\pm0.16}/\mathbf{91.56_{\pm0.07}}$	$91.49^*_{\pm0.16}/\mathbf{91.56_{\pm0.07}}$	$91.49^*_{\pm0.16}/\mathbf{91.56_{\pm0.07}}$	$91.49^*_{\pm0.16}/\mathbf{91.56_{\pm0.07}}$
	AdaS$^{0.9}$	$93.31_{\pm0.15}/\mathbf{93.37_{\pm0.11}}$	$93.51^*_{\pm0.12}/\mathbf{93.60_{\pm0.16}}$	$93.51^*_{\pm0.12}/\mathbf{93.60_{\pm0.16}}$	$93.51^*_{\pm0.12}/\mathbf{93.60_{\pm0.16}}$	$93.51^*_{\pm0.12}/\mathbf{93.60_{\pm0.16}}$
	AdaS$^{0.95}$	$89.03_{\pm0.45}/\mathbf{90.49_{\pm0.24}}$	$94.57_{\pm0.13}/\mathbf{94.61_{\pm0.15}}$	$94.59_{\pm0.14}/\mathbf{94.62_{\pm0.10}}$	$94.61^*_{\pm0.11}/\mathbf{94.62_{\pm0.10}}$	$94.61^*_{\pm0.11}/\mathbf{94.62_{\pm0.10}}$
	AdaS$^{0.975}$	$\mathbf{87.65_{\pm0.55}}/85.33_{\pm1.38}$	$92.07_{\pm0.48}/\mathbf{92.29_{\pm0.54}}$	$\mathbf{94.93_{\pm0.07}}/94.86_{\pm0.11}$	$\mathbf{95.03_{\pm0.09}}/94.98_{\pm0.13}$	$95.02_{\pm0.06}/\mathbf{95.03_{\pm0.12}}$
	RMSProp	$\mathbf{89.26_{\pm0.42}}/89.11_{\pm0.89}$	$89.65_{\pm0.89}/\mathbf{90.17_{\pm0.30}}$	$91.02_{\pm0.36}/\mathbf{91.63_{\pm0.13}}$	$90.96_{\pm0.45}/\mathbf{91.80_{\pm0.17}}$	$91.34_{\pm0.59}/\mathbf{92.15_{\pm0.20}}$
	SLS	$93.05_{\pm0.31}/\mathbf{93.18_{\pm0.11}}$	$\mathbf{93.52_{\pm0.12}}/93.40_{\pm0.10}$	$\mathbf{93.51_{\pm0.20}}/93.50_{\pm0.12}$	$\mathbf{93.54_{\pm0.22}}/93.47_{\pm0.12}$	$\mathbf{93.56_{\pm0.20}}/93.49_{\pm0.14}$
CIFAR100	AdaBound	$66.66_{\pm0.64}/\mathbf{66.75_{\pm0.31}}$	$69.92_{\pm0.40}/\mathbf{70.13_{\pm0.40}}$	$70.63_{\pm0.23}/\mathbf{71.06_{\pm0.51}}$	$71.02_{\pm0.28}/\mathbf{71.35_{\pm0.26}}$	$71.20_{\pm0.34}/\mathbf{71.43_{\pm0.30}}$
	AdaGrad	$\mathbf{63.75_{\pm0.57}}/62.97_{\pm0.54}$	$\mathbf{65.27_{\pm0.46}}/65.01_{\pm0.64}$	$\mathbf{65.36_{\pm0.48}}/65.30_{\pm0.41}$	$\mathbf{65.75_{\pm0.41}}/65.65_{\pm0.37}$	$\mathbf{66.03_{\pm0.56}}/65.66_{\pm0.36}$
	AdaM	$\mathbf{66.74_{\pm0.46}}/66.47_{\pm0.45}$	$68.40_{\pm0.28}/\mathbf{68.87_{\pm0.50}}$	$68.37_{\pm0.53}/\mathbf{69.59_{\pm0.26}}$	$69.04_{\pm0.18}/\mathbf{70.14_{\pm0.35}}$	$69.12_{\pm0.16}/\mathbf{70.32_{\pm0.46}}$
	AdaS$^{0.8}$	$72.06_{\pm0.41}/\mathbf{72.39_{\pm0.21}}$	$72.00^*_{\pm0.44}/\mathbf{72.41_{\pm0.16}}$	$72.00^*_{\pm0.44}/\mathbf{72.41_{\pm0.16}}$	$72.00^*_{\pm0.44}/\mathbf{72.41_{\pm0.16}}$	$72.00^*_{\pm0.44}/\mathbf{72.41_{\pm0.16}}$
	AdaS$^{0.9}$	$74.23_{\pm0.28}/\mathbf{74.30_{\pm0.11}}$	$74.41^*_{\pm0.26}/\mathbf{74.43_{\pm0.14}}$	$74.41^*_{\pm0.26}/\mathbf{74.43_{\pm0.14}}$	$74.41^*_{\pm0.26}/\mathbf{74.43_{\pm0.14}}$	$74.41^*_{\pm0.26}/\mathbf{74.43_{\pm0.14}}$
	AdaS$^{0.95}$	$\mathbf{72.78_{\pm0.09}}/72.29_{\pm0.37}$	$75.47_{\pm0.10}/\mathbf{76.03_{\pm0.34}}$	$75.74_{\pm0.03}/\mathbf{75.95_{\pm0.26}}$	$75.63^*_{\pm0.12}/\mathbf{75.95_{\pm0.26}}$	$75.63^*_{\pm0.12}/\mathbf{75.95_{\pm0.26}}$
	AdaS$^{0.975}$	$63.16_{\pm1.84}/\mathbf{63.67_{\pm1.48}}$	$74.42_{\pm0.47}/\mathbf{74.52_{\pm0.44}}$	$76.12_{\pm0.17}/\mathbf{76.27_{\pm0.23}}$	$76.45_{\pm0.16}/\mathbf{76.47_{\pm0.18}}$	$\mathbf{76.58_{\pm0.21}}/76.46_{\pm0.24}$
	RMSProp	$63.69_{\pm0.66}/\mathbf{63.96_{\pm1.40}}$	$66.24_{\pm0.28}/\mathbf{67.82_{\pm0.82}}$	$66.35_{\pm0.26}/\mathbf{67.97_{\pm1.16}}$	$66.83_{\pm0.39}/\mathbf{69.31_{\pm0.27}}$	$67.17_{\pm0.70}/\mathbf{69.45_{\pm1.17}}$
	SLS	$55.34_{\pm4.77}/\mathbf{58.80_{\pm3.56}}$	$70.10_{\pm1.18}/\mathbf{70.75_{\pm0.98}}$	$71.51_{\pm0.31}/\mathbf{71.73_{\pm0.38}}$	$71.89_{\pm0.09}/\mathbf{72.03_{\pm0.40}}$	$71.82_{\pm0.22}/\mathbf{72.08_{\pm0.43}}$

Table 8: List of DenseNet121 top-1 test-accuracies using various optimizers and applied to various datasets. Note that each cell reports the average accuracy over each experimental trial, sub-scripted by the standard deviation over the trials. Values on the left are from trials trained using the initial learning rate as generated by autoHyper. Values on the right are from trials trained using the suggested initial learning rate. Note a '*' indicates that early-stop has been activated.

Dataset	Optimizer	Epoch 50	Epoch 100	Epoch 150	Epoch 200	Epoch 250
CIFAR10	AdaBound	$88.57_{\pm0.49}/\mathbf{89.73_{\pm0.32}}$	$90.09_{\pm0.23}/\mathbf{90.64_{\pm0.23}}$	$90.65_{\pm0.24}/\mathbf{91.20_{\pm0.09}}$	$90.59_{\pm0.46}/\mathbf{91.32_{\pm0.12}}$	$90.96_{\pm0.48}/\mathbf{91.65_{\pm0.20}}$
	AdaGrad	$\mathbf{88.57_{\pm0.29}}/88.31_{\pm0.45}$	$\mathbf{89.20_{\pm0.23}}/89.03_{\pm0.27}$	$\mathbf{89.36_{\pm0.09}}/89.26_{\pm0.25}$	$\mathbf{89.47_{\pm0.12}}/89.33_{\pm0.25}$	$\mathbf{89.85_{\pm0.19}}/89.52_{\pm0.16}$
	AdaM	$\mathbf{90.75_{\pm0.28}}/89.42_{\pm0.72}$	$\mathbf{91.39_{\pm0.32}}/90.28_{\pm0.49}$	$\mathbf{91.75_{\pm0.27}}/90.84_{\pm0.16}$	$\mathbf{91.72_{\pm0.28}}/91.29_{\pm0.26}$	$\mathbf{91.86_{\pm0.26}}/91.32_{\pm0.43}$
	AdaS$^{0.8}$	$\mathbf{91.61_{\pm0.20}}/91.28_{\pm0.26}$	$\mathbf{91.59^*_{\pm0.25}}/91.28_{\pm0.23}$	$\mathbf{91.59^*_{\pm0.25}}/91.28_{\pm0.23}$	$\mathbf{91.59^*_{\pm0.25}}/91.28_{\pm0.23}$	$\mathbf{91.59^*_{\pm0.25}}/91.28_{\pm0.23}$
	AdaS$^{0.9}$	$92.91_{\pm0.08}/92.89_{\pm0.20}$	$92.97^*_{\pm0.18}/\mathbf{93.06_{\pm0.14}}$	$92.97^*_{\pm0.18}/\mathbf{93.06_{\pm0.14}}$	$92.97^*_{\pm0.18}/\mathbf{93.06_{\pm0.14}}$	$92.97^*_{\pm0.18}/\mathbf{93.06_{\pm0.14}}$
	AdaS$^{0.95}$	$91.59_{\pm0.36}/\mathbf{91.59_{\pm0.23}}$	$93.33_{\pm0.35}/\mathbf{93.45_{\pm0.18}}$	$93.33^*_{\pm0.24}/\mathbf{93.51_{\pm0.20}}$	$93.33^*_{\pm0.24}/\mathbf{93.51_{\pm0.20}}$	$93.33^*_{\pm0.24}/\mathbf{93.51_{\pm0.20}}$
	AdaS$^{0.975}$	$\mathbf{86.96_{\pm1.15}}/86.17_{\pm0.80}$	$91.87_{\pm0.26}/\mathbf{92.06_{\pm0.51}}$	$93.17_{\pm0.20}/\mathbf{93.53_{\pm0.19}}$	$93.40_{\pm0.22}/\mathbf{93.72_{\pm0.15}}$	$93.47_{\pm0.24}/\mathbf{93.83_{\pm0.20}}$
	RMSProp	$\mathbf{88.80_{\pm0.93}}/88.19_{\pm1.18}$	$\mathbf{90.95_{\pm0.85}}/89.76_{\pm1.15}$	$\mathbf{91.54_{\pm0.52}}/90.77_{\pm0.64}$	$\mathbf{91.65_{\pm0.36}}/90.95_{\pm0.48}$	$\mathbf{91.83_{\pm0.30}}/91.29_{\pm0.20}$
	SLS	$\mathbf{92.95_{\pm0.28}}/92.78_{\pm0.07}$	$\mathbf{93.35_{\pm0.20}}/93.14_{\pm0.16}$	$\mathbf{93.40_{\pm0.17}}/93.12_{\pm0.15}$	$\mathbf{93.38_{\pm0.15}}/93.16_{\pm0.11}$	$\mathbf{93.36_{\pm0.18}}/93.16_{\pm0.13}$
CIFAR100	AdaBound	$63.87_{\pm0.25}/\mathbf{65.30_{\pm0.28}}$	$65.61_{\pm0.18}/\mathbf{68.00_{\pm0.30}}$	$66.66_{\pm0.22}/\mathbf{68.65_{\pm0.21}}$	$66.69_{\pm0.37}/\mathbf{68.46_{\pm0.32}}$	$67.00_{\pm0.20}/\mathbf{68.90_{\pm0.36}}$
	AdaGrad	$\mathbf{61.62_{\pm0.46}}/61.08_{\pm0.28}$	$\mathbf{62.01_{\pm0.29}}/61.43_{\pm0.31}$	$\mathbf{62.40_{\pm0.50}}/61.86_{\pm0.50}$	$\mathbf{62.91_{\pm0.46}}/62.09_{\pm0.22}$	$\mathbf{62.79_{\pm0.35}}/62.14_{\pm0.15}$
	AdaM	$\mathbf{66.53_{\pm0.30}}/64.50_{\pm0.33}$	$\mathbf{67.64_{\pm0.35}}/65.69_{\pm0.29}$	$\mathbf{68.32_{\pm0.27}}/66.42_{\pm0.57}$	$\mathbf{68.46_{\pm0.28}}/66.89_{\pm0.53}$	$\mathbf{69.05_{\pm0.49}}/67.48_{\pm0.17}$
	AdaS$^{0.8}$	$\mathbf{70.90_{\pm0.11}}/70.59_{\pm0.39}$	$\mathbf{71.01^*_{\pm0.28}}/70.63_{\pm0.33}$	$\mathbf{71.01^*_{\pm0.28}}/70.63_{\pm0.33}$	$\mathbf{71.01^*_{\pm0.28}}/70.63_{\pm0.33}$	$\mathbf{71.01^*_{\pm0.28}}/70.63_{\pm0.33}$
	AdaS$^{0.9}$	$73.11_{\pm0.49}/\mathbf{73.13_{\pm0.30}}$	$73.13_{\pm0.44}/\mathbf{73.25_{\pm0.25}}$	$73.13^*_{\pm0.44}/\mathbf{73.25_{\pm0.25}}$	$73.13^*_{\pm0.44}/\mathbf{73.25_{\pm0.25}}$	$73.13_{\pm0.44}/\mathbf{73.25_{\pm0.25}}$
	AdaS$^{0.95}$	$72.62_{\pm0.50}/\mathbf{72.90_{\pm0.72}}$	$73.98_{\pm0.21}/\mathbf{74.09_{\pm0.30}}$	$73.98^*_{\pm0.33}/\mathbf{74.22_{\pm0.24}}$	$73.98^*_{\pm0.33}/\mathbf{74.22_{\pm0.24}}$	$73.98^*_{\pm0.33}/\mathbf{74.22_{\pm0.24}}$
	AdaS$^{0.975}$	$61.85_{\pm1.59}/\mathbf{63.44_{\pm1.90}}$	$72.16_{\pm0.56}/\mathbf{72.65_{\pm0.85}}$	$73.81_{\pm0.44}/\mathbf{73.92_{\pm0.52}}$	$73.88_{\pm0.42}/\mathbf{73.99_{\pm0.45}}$	$73.97_{\pm0.36}/\mathbf{74.10_{\pm0.47}}$
	RMSProp	$\mathbf{64.73_{\pm0.00}}/62.80_{\pm0.54}$	$\mathbf{66.22_{\pm0.00}}/64.85_{\pm0.28}$	$\mathbf{67.57_{\pm0.00}}/65.74_{\pm0.40}$	$\mathbf{67.35_{\pm0.00}}/66.30_{\pm0.42}$	$\mathbf{68.13_{\pm0.00}}/66.61_{\pm0.58}$
	SLS	$52.01_{\pm7.25}/\mathbf{55.66_{\pm6.26}}$	$\mathbf{65.96_{\pm1.20}}/62.29_{\pm5.97}$	$\mathbf{69.88_{\pm0.24}}/67.28_{\pm1.15}$	$\mathbf{70.12_{\pm0.45}}/68.63_{\pm1.61}$	$\mathbf{70.25_{\pm0.19}}/69.44_{\pm0.61}$