Kernel Functional Optimisation

Abstract

Traditional methods for kernel selection rely on parametric kernel functions or a combination thereof and although the kernel hyperparameters are tuned, these methods often provide sub-optimal results due to the limitation induced by the parametric forms. In this paper, we propose a novel formulation for kernel selection using efficient Bayesian optimisation to find the best fitting non-parametric kernel. The kernel is expressed using a linear combination of functions sampled from a prior Gaussian Process (GP) defined by a hyperkernel. We also provide a mechanism to ensure the positive definiteness of the Gram matrix constructed using the resultant kernels. Our experimental results on GP regression and Support Vector Machine (SVM) classification tasks involving both synthetic functions and several real-world datasets show the superiority of our approach over the state-of-the-art.

1 Introduction

In most kernel machines, the kernel function is chosen from the standard bag of popular kernels (Genton, 2001, Stein, 2015) such as Squared Exponential kernel (SE), Matérn kernel and Periodic kernel, or a weighted combination thereof (Aiolli and Donini, 2015, Gönen and Alpaydın, 2011, Rakotomamonjy et al., 2007). Recent developments (Jang et al., 2017, Wilson and Adams, 2013) in kernel learning parameterise the kernel function to boost the expressiveness of the kernel. However, the expressiveness of such kernels remains limited by the chosen parametric form and thus they often fall short in providing the best kernel function for complex data distributions. There have been some early attempts to design an optimal non-parametric kernel to remove the limitations associated with the parametric forms. For example, Ong et al. (2003, 2005) proposed a hyperkernel framework by defining a Reproducing Kernel Hilbert Space (RKHS) on the space of kernels *i.e.*, a kernel on kernels to support kernel learning. They formulate a semidefinite programming (Vandenberghe and Boyd, 1996) based optimisation problem using the representer theorem (Steinwart and Christmann, 2008, Vapnik, 1999) to find the best kernel. However, their method suffers from two key limitations: **(i)** their way of enforcing the positive definiteness property produces a restrictive search space, resulting in a sub-optimal solution, and **(ii)** the computational complexity of their method scales with the dataset size, making it infeasible for larger datasets. Benton et al. (2019) proposed Functional Kernel Learning (FKL), which extends the function space view of the Gaussian Process (GP) for kernel learning. FKL uses a transformed GP over a spectral density to define a distribution over kernels. However, the formulation of kernel functionals using the spectral densities induces strong assumptions on the properties such as periodicity, stationarity, *etc.* and thus are not generally applicable.

In this paper, we propose a generic framework called Kernel Functional Optimisation (KFO) to address the aforesaid shortcomings. First, it provides a flexible form of kernel learning whose computational complexity is decoupled from dataset size. Next, it allows us to use a computationally efficient Bayesian optimisation method to find the best kernel. We incorporate hyperkernels into our Bayesian framework that allows us to search for the optimal kernel in a Hilbert space of kernels spanned by the hyperkernel (Ong et al., 2005). We draw kernel functionals from a (hyper) GP

distribution fitted using a hyperkernel. As the kernel drawn from the hyper-GP may be indefinite, we provide ways to ensure positive definiteness by transforming indefinite, or Kreĭn (Oglic and Gärtner, 2019, Ong et al., 2004) kernel space into a positive definite kernel space. The optimisation of kernel functionals necessitates solving larger covariance matrices and thus adds to the computational burden of the overall process. To speed up the computations, we perform a low-rank decomposition of the covariance matrix. Further, we provide a theoretical analysis of our method showing that it converges efficiently as in its cumulative regret grows only sub-linearly and eventually vanishes.

We evaluate the performance of our proposed method on both synthetic and real-world datasets using SVM classification (Diehl and Cauwenberghs, 2003, Scholkopf and Smola, 2001, Burges, 1998) and GP regression tasks. Comparison of predictive performance against the state-of-the-art baselines demonstrates the superiority of our method. Further, we compare with the state-of-the-art performance reported in the latest survey paper on classifier comparison (Zhang et al., 2017) and find that our method provides the best performance on most of the datasets. Our main contributions in this paper are as follows: **(i)** we propose a novel approach for finding the best non-parametric kernel using hyperkernels and Bayesian functional optimisation (Section 3), **(ii)** we provide methods to ensure positive definiteness of the kernels optimised (Section 3), **(iii)** we derive the convergence guarantees to demonstrate that the regret grows sublinearly for our proposed method (Section 4), **(iv)** we provide empirical results on both synthetic and real-world datasets to prove the usefulness (Section 5).

2 Background

Notations. We use lower case bold fonts $\mathbf{v}$ for vectors and v_i for each element in $\mathbf{v}$. $\mathbf{v}^\intercal$ is the transpose. We use upper case bold fonts $\mathbf{M}$ (and bold greek symbols) for matrices and M_{ij} for each element in $\mathbf{M}$. $|\cdot|$ for the absolute value. $\mathbb{N}_n = \{1, 2, \cdots, n\}$. $\mathbb{R}$ for Reals. $\mathcal{X}$ is a non-empty (index) set and $\mathbf{x} \in \mathcal{X}$. $\tilde{\mathcal{X}}$ is a non-empty (compounded index) set and $\tilde{\mathbf{x}} \in \tilde{\mathcal{X}}, \tilde{\mathcal{X}} = \mathcal{X}^2$. $(\cdot)_+$ clips a negative value to zero. $[\![\cdot]\!]$ is the Iverson bracket (Iverson, 1962) defined for any boolean value I as $[\![I]\!] = 1$, if I is True, 0 otherwise. Matrix $\mathbf{M} = [M_{ij}]_{i,j \in \mathbb{N}}$ and $\|\mathbf{M}\|_\mathrm{F}$ is the Frobenius Norm of $\mathbf{M}$.

2.1 Bayesian Optimisation

Bayesian Optimisation (BO) (Brochu et al., 2010, Shahriari et al., 2015, Frazier, 2018) offers an elegant framework for finding the global extrema of an unknown, expensive and noisy function $f(\mathbf{x})$, represented as $\mathbf{x}^* = \mathrm{argmax}_{\mathbf{x} \in \mathcal{X}} f(\mathbf{x})$, where $\mathcal{X}$ is a compact search space. Bayesian optimisation is comprised of two main components **(i)** A Gaussian Process (GP) (Williams and Rasmussen, 2006) model of f, and **(ii)** an Acquisition function (u) (Kushner, 1964, Močkus, 1975, Wilson et al., 2018) to guide optimisation. Let $\mathcal{D} = \{\mathbf{x}_{1:t}, \mathbf{y}_{1:t}\}$ denote a set of obervations of f, where $y = f(\mathbf{x}) + \epsilon'$ is the noisy observation corrupted with white Gaussian noise $\epsilon' \in \mathcal{N}(0, \sigma_{noise}^2)$. Then the predictive distribution at any point $\mathbf{x}_*$ is given as $f(\mathbf{x}_*)|\mathcal{D} \sim \mathcal{N}(\mu(\mathbf{x}_*), \sigma^2(\mathbf{x}_*))$, where $\mu(\mathbf{x}_*) = \mathbf{k}^\intercal[\mathbf{K} + \sigma_{noise}^2\mathbf{I}]^{-1}\mathbf{y}_{1:t}$, $\sigma^2(\mathbf{x}_*) = k(\mathbf{x}_*, \mathbf{x}_*) - \mathbf{k}^\intercal[\mathbf{K} + \sigma_{noise}^2\mathbf{I}]^{-1}\mathbf{k}$, $\mathbf{k} = [k(\mathbf{x}_*, \mathbf{x}_1) \cdots k(\mathbf{x}_*, \mathbf{x}_t)]$, $k : \mathcal{X} \times \mathcal{X} \to \mathbb{R}$ and $\mathbf{K} = [k(\mathbf{x}_i, \mathbf{x}_j)]_{i,j \in \mathbb{N}_t}$. The negative log-likelihood for a GP distribution is

$$-\log p(y_*|\mathcal{D}, \mathbf{x}_*) = \tfrac{1}{2}\log(2\pi\sigma^2(\mathbf{x}_*)) + \tfrac{(y_* - \mu(\mathbf{x}_*))^2}{2\sigma^2(\mathbf{x}_*)} \tag{1}$$

The acquisition function (u) guides the search by balancing between exploitation (searching known high-value regions) and exploration (searching high-variance regions). GP-UCB acquisition function (Srinivas et al., 2012, Brochu et al., 2010) is the commonly used acquisition function, given as

$$u_t(\mathbf{x}) = \mu(\mathbf{x}) + \sqrt{\beta_t}\,\sigma(\mathbf{x}) \tag{2}$$

where β_t grows as $O(\log t)$ with iteration t. Further, it can be shown that the average regret $(\triangleq \frac{1}{t}\sum_{t'=1}^{t'=t}|f(\mathbf{x}^*) - f(\mathbf{x}_{t'})|)$ grows as $O(\sqrt{\log t / t})$, and hence the average regret vanishes as $t \to \infty$. An algorithm for standard Bayesian optimisation is provided in the supplementary material.

The aforementioned standard Bayesian optimisation procedure often suffers from scaling issues, originating from the curse of dimensionality. Wang et al. (2016) proposed REMBO - Random EMbedding Bayesian Optimisation - to address these scaling issues. REMBO works by projecting the

objective function onto a lower-dimensional subspace prior to optimisation. LINEBO (Kirschner et al., 2019) builds on the same idea but instead of a fixed subspace, it decomposes the given black-box optimisation problem into a sequence of one-dimensional subproblems. Further, our method builds upon the priniciples of Bayesian functional optimisation methodologies (Vien et al., 2018, Vellanki et al., 2019, Shilton et al., 2020) in the literature to find a function to optimise a given process.

2.2 RKHS and Hyper-RKHS

The kernel functions used in the Gaussian process uniquely define an associated Reproducing Kernel Hilbert Space (RKHS) (Aronszajn, 1950). Formally:

Definition 1: *Let $\mathcal{H}_k$ be a Hilbert space of functions $f : \mathcal{X} \to \mathbb{R}$ on a non-empty set $\mathcal{X}$. A function $k : \mathcal{X} \times \mathcal{X} \to \mathbb{R}$ is a reproducing kernel of $\mathcal{H}_k$, and $\mathcal{H}_k$ a* **Reproducing Kernel Hilbert Space (RKHS)**, *if the following properties are satisfied.*

- k spans $\mathcal{H}_k$ *i.e.,* $\mathcal{H}_k = \overline{\text{span}\{k(\cdot, \mathbf{x}) | \mathbf{x} \in \mathcal{X}\}}$
- $\forall \mathbf{x} \in \mathcal{X}, \forall f \in \mathcal{H}_k, \langle f(\cdot), k(\cdot, \mathbf{x}) \rangle_{\mathcal{H}_k} = f(\mathbf{x})$ *(the reproducing property)*
- $\forall \mathbf{x}, \mathbf{x}' \in \mathcal{X}, k(\mathbf{x}, \mathbf{x}') = \langle k(\cdot, \mathbf{x}), k(\cdot, \mathbf{x}') \rangle_{\mathcal{H}_k},$

Next, we consider the Reproducing Kernel Hilbert Spaces (RKHS) of kernels by introducing a compounded index set $\tilde{\mathcal{X}} : \mathcal{X} \times \mathcal{X}$ and a hyperkernel κ (Ong and Smola, 2003, Ong et al., 2003). Analogous to the RKHS (Aronszajn, 1950) associated with the kernel function, a hyperkernel defines an associated Hyper-Reproducing Kernel Hilbert Spaces (Hyper-RKHS) (Ong et al., 2003).

Definition 2: *Let $\mathcal{X}$ be a nonempty set and $\tilde{\mathcal{X}}$ denote $\mathcal{X} \times \mathcal{X}$. The Hilbert space $\mathcal{H}_\kappa$ of functions $k : \tilde{\mathcal{X}} \to \mathbb{R}$ is called a* **Hyper-Reproducing Kernel Hilbert Space (Hyper-RKHS),** *if there exists a hyperkernel $\kappa : \tilde{\mathcal{X}} \times \tilde{\mathcal{X}} \to \mathbb{R}$ that satisfies the following properties:*

- κ spans $\mathcal{H}_\kappa$ *i.e.,* $\mathcal{H}_\kappa = \overline{\text{span}\{\kappa(\cdot, \tilde{\mathbf{x}}) \mid \tilde{\mathbf{x}} \in \tilde{\mathcal{X}}\}}$
- $\forall \tilde{\mathbf{x}} \in \tilde{\mathcal{X}}, \forall k \in \mathcal{H}_\kappa, \langle k(\cdot), \kappa(\cdot, \tilde{\mathbf{x}}) \rangle_{\mathcal{H}_\kappa} = k(\tilde{\mathbf{x}})$ *(the reproducing property)*
- $\forall \tilde{\mathbf{x}}, \tilde{\mathbf{x}}' \in \tilde{\mathcal{X}}, \kappa(\tilde{\mathbf{x}}, \tilde{\mathbf{x}}') = \langle \kappa(\cdot, \tilde{\mathbf{x}}), \kappa(\cdot, \tilde{\mathbf{x}}') \rangle_{\mathcal{H}_\kappa}$
- $\kappa(\mathbf{x}', \mathbf{x}'', \mathbf{x}''', \mathbf{x}'''') = \kappa(\mathbf{x}'', \mathbf{x}', \mathbf{x}''', \mathbf{x}'''') \ \forall \mathbf{x}', \mathbf{x}'', \mathbf{x}''', \mathbf{x}'''' \in \mathcal{X}$

The GP distribution defined by a hyperkernel κ is a distribution on the space of kernels. This Hyper-RKHS is a hilbert space comprised of positive definite, negative definite and indefinite kernels. A *Kreĭn* kernel k (Oglic and Gärtner, 2018, Ong et al., 2004) is an indefinite kernel with a positive decomposition *i.e.*, there exist positive kernels $k_+ \in \mathcal{H}_+$ and $k_- \in \mathcal{H}_-$, such that $k = k_+ - k_-$. From Definition 2, we see that $\kappa(\tilde{\mathbf{x}}, \tilde{\mathbf{x}}') = \kappa(\mathbf{x}', \mathbf{x}'', \mathbf{x}''', \mathbf{x}'''')$ is a kernel, where $\tilde{\mathbf{x}} = (\mathbf{x}', \mathbf{x}'')$. Generally, the samples drawn from $\mathcal{GP}(0, k)$ do not lie in the corresponding RKHS $\mathcal{H}_k$, but in a larger RKHS $\mathcal{H}_{k' \neq k}$ (see discussion in Kanagawa et al. (2018), Remark 3.8 and section 4). We also note that the posterior mean of $\mathcal{GP}(0, k)$ lies in the RKHS $\mathcal{H}_k$. Similarly, with hyper-GP, the samples drawn from $\mathcal{GP}_\kappa(0, \kappa)$ lie in RKHS $\mathcal{H}_{\kappa' \neq \kappa}$, whereas its posterior mean (μ) lies in $\mathcal{H}_\kappa$. Further, μ can be decomposed with positive and negative weights as $\mu = \mu_+ - \mu_- = \sum_i \alpha_{i_+} \kappa(\cdot, \tilde{\mathbf{x}}_{i_+}) - \sum_i \alpha_{i_-} \kappa(\cdot, \tilde{\mathbf{x}}_{i_-})$, where $\alpha_{i_+}, \alpha_{i_-} > 0$; and $\mu_\pm = \sum_i \alpha_{i_\pm} \kappa(\cdot, \tilde{\mathbf{x}}_{i_\pm})$ is a kernel (Definition 2 and Ong et al. (2004)). Thus, $\mu = \mu_+ - \mu_-$ is a *Kreĭn* kernel (Oglic and Gärtner, 2019).

3 Framework

In this paper, we address the global optimisation problem formulated as $K^* = \text{argmax}_{K \in \mathcal{H}_\kappa} f(K)$, where $f : \mathcal{H}_\kappa \to \mathbb{R}$ is an expensive objective functional and κ is a hyperkernel. In particular, we are interested in finding the best kernel $K^* \in \mathcal{H}_\kappa$ to maximise the model performance represented by the objective functional f (for example, f can be the leave-one-out classification performance of a SVM classifier). First, we describe the construction of valid kernel functionals using hyperkernel, followed by a discussion on the kernel functional optimisation using Bayesian optimisation. A

process flowchart describing the overall optimisation process of kernel functionals is shown in Figure 1. A complete algorithm for Kernel Functional Optimisation (KFO) is given by Algorithm 1.

3.1 Construction of Kernel Functionals from Hyper-Gaussian Process

Ong and Smola (2003) and Ong et al. (2003, 2005) have discussed the general guidelines to design a hyperkernel. We follow the same strategy to formulate *Matérn Harmonic Hyperkernel* (κ):

$$\kappa(\mathbf{x}, \mathbf{x}', \mathbf{x}'', \mathbf{x}''') = \frac{1 - \lambda_h}{1 - \left(\lambda_h \, \overline{c}_1 \, \overline{c}_2 \, \exp\left(-\frac{\sqrt{3}}{l}(r_1 + r_2)\right)\right)} \tag{3}$$

where λ_h and l correspond to the hyperparameters of the hyperkernel, $r_1 = \|\mathbf{x} - \mathbf{x}'\|$, $r_2 = \|\mathbf{x}'' - \mathbf{x}'''\|$, $\overline{c}_1 = \left(1 + \frac{\sqrt{3}}{l}r_1\right)$, and $\overline{c}_2 = \left(1 + \frac{\sqrt{3}}{l}r_2\right)$. The derivation of Matérn Harmonic Hyperkernel is provided in the supplementary material. In our proposed method, we use the draws from a (hyper) Gaussian process $\mathcal{GP}_\kappa(0, \kappa)$ to construct finite-dimensional subspaces of our kernel space on which we perform optimisation. As discussed in Section 2.2, the kernel samples drawn from $\mathcal{GP}_\kappa(0, \kappa)$ do not lie in $\mathcal{H}_\kappa$, hence we approximate the draws using the posterior mean of $\mathcal{GP}_\kappa(0, \kappa)$ lying in $\mathcal{H}_\kappa$.

In practice, when sampling from $\mathcal{GP}_\kappa(0, \kappa)$, we assume a grid $\mathcal{G}$ with N^2 points $\{\tilde{\mathbf{x}}_1, \tilde{\mathbf{x}}_2, \cdots \mid \tilde{\mathbf{x}}_i \in \tilde{\mathcal{X}} : \mathcal{X} \times \mathcal{X}, \forall i \in \mathbb{N}_{N^2}\}$ for placing a GP distribution on kernels using a hyperkernel κ mentioned in Eq. (3). The sample set $\mathbf{k} \sim \mathcal{GP}_\kappa(0, \kappa)$ is essentially a set of noiseless observations of the kernel K on the grid-points $\tilde{\mathbf{x}}_1, \tilde{\mathbf{x}}_2, \cdots$ lying in $\mathcal{H}_{\kappa' \neq \kappa}$. The number of points in the grid is chosen such that the resulting grid is sufficiently fine to represent the kernel K everywhere on $\tilde{\mathcal{X}}$. Therefore, for any point $\tilde{\mathbf{x}}_i \in \tilde{\mathcal{X}}$, the posterior variance of the kernel K given the observations $\{(\tilde{\mathbf{x}}_i, k_i) \mid i \in \mathbb{N}_{N^2}\}$ is negligible and thus the kernel K can be approximated using the posterior mean of $\mathcal{GP}_\kappa(0, \kappa)$ as,

$$K(\tilde{\mathbf{x}}) \approx [\kappa(\tilde{\mathbf{x}}, \tilde{\mathbf{x}}_1) \, \kappa(\tilde{\mathbf{x}}, \tilde{\mathbf{x}}_2) \, \kappa(\tilde{\mathbf{x}}, \tilde{\mathbf{x}}_3) \cdots] \, \boldsymbol{\kappa}^{-1} \, \mathbf{k} = \sum_i \alpha_i \, \kappa(\tilde{\mathbf{x}}, \tilde{\mathbf{x}}_i), \text{where } \boldsymbol{\alpha} = \boldsymbol{\kappa}^{-1} \, \mathbf{k} \tag{4}$$

3.2 Kernel Functional Optimisation

We adopt the ideas from Bayesian optimisation method - LINEBO (Kirschner et al., 2019) for the optimisation of non-parametric kernel functionals via a sequence of one-dimensional projections. First, we discuss the construction of low-dimensional subspaces. The key challenge here is to address the computational burden with the use of large grid. Next, we describe the Bayesian functional optimisation for each of the subspace and across many such subspaces. Since the best kernel obtained is a Kreĭn kernel, we transform it to ensure the positive definiteness of the Gram matrix.

Construction of Low-dimensional Spaces. We start with the construction of low-dimensional search space spanned by randomly chosen basis vectors drawn from the hyper-GP $\mathcal{GP}_\kappa(0, \kappa)$. The hyper-GP surrogate modelling requires the computation of covariance matrix $\boldsymbol{\kappa} \in \mathbb{R}^{N^2 \times N^2}$ using κ for the predefined grid $\mathcal{G}$. Further, the accuracy of the kernel functional to represent the kernel K is directly proportional to the assumed grid size N^2. To avoid the computational burden arising from the larger grid size N^2, we perform Principal Component Analysis (PCA) (Wold et al., 1987) and choose N' principal components. Mathematically, we represent $\boldsymbol{\kappa} = (\boldsymbol{E}\sqrt{\boldsymbol{\Lambda}})(\boldsymbol{E}\sqrt{\boldsymbol{\Lambda}})^\mathsf{T}$, where i^{th} column $\boldsymbol{e}_i$ in $\boldsymbol{E} \in \mathbb{R}^{N^2 \times N'}$ corresponds to the i^{th} principal component and $\boldsymbol{\Lambda} \in \mathbb{R}^{N' \times N'}$ is the diagonal matrix containing top N' eigenvalues. The outer-loop in Algorithm 1 iterates through a

Figure 1: A complete flowchart for Kernel Functional Optimisation

162 sequence of S d-dimensional subspaces by drawing d random basis vectors in each subspace from
163 $\mathcal{GP}_\kappa(0, \kappa)$ *i.e.*, $\mathbf{k}^{(1)}, \mathbf{k}^{(2)}, \cdots, \mathbf{k}^{(d)} \sim \mathcal{GP}_\kappa(0, \kappa)$, where $\mathbf{k}^{(\cdot)} = \boldsymbol{E}\sqrt{\boldsymbol{\Lambda}} \cdot \beta^{(\cdot)}$ and $\beta^{(\cdot)} \sim \mathcal{N}(0, I_{N'})$.

Kernel Optimisation Observation Model. As discussed earlier, we construct kernel functionals
165 $K(\cdot, \cdot)$ from the hyper-GP distribution $\mathcal{GP}_\kappa(0, \kappa)$ as per Eq. (4) using

$$\mathbf{k} = K^{\#} + \lambda^{(1)}\mathbf{k}^{(1)} + \cdots + \lambda^{(d)}\mathbf{k}^{(d)} \tag{5}$$

166 where $\lambda^{(\cdot)} \in [0, 1]$, $\mathbf{k}^{(\cdot)}$ are the random basis vectors drawn and $K^{\#}$ corresponds to the best kernel
167 found in all the previous subspaces. The optimal kernel in the given subspace s is obtained by
168 optimising $\boldsymbol{\lambda}$ using a Bayesian optimisation procedure with another GP distribution $\mathcal{GP}(0, k_{\text{SE}})$. The
169 observation model for $\mathcal{GP}(0, k_{\text{SE}})$ is considered as $\mathcal{D}'_s = \{(K, y = f(K))\}$, where K is the kernel
170 functional constructed and y is a measure signifying the ability of the latent kernel to represent the
171 given data. For example, log-likelihood can be used as the measure y in our observation model.

Building GP for Kernel Optimisation. We fit a GP distribution $\mathcal{GP}(0, k_{\text{SE}})$ on the observed kernel
173 functionals using Squared Exponential (SE) kernel (k_{SE}) given by,

$$k_{\text{SE}}(K_1, K_2) = \sigma_f^2 \exp\left(\frac{-1}{2\Upsilon^2} \|K_1 - K_2\|^2_{\mathcal{H}_{\kappa' \neq \kappa}} \right) \tag{6}$$

174 where σ_f^2 and Υ correspond to the signal variance and lengthscale parameters of k_{SE}. Although there
175 is no restriction on the kernel choice here, we consider the commonly used SE kernel. As mentioned
176 earlier, we approximate K using the posterior mean (μ), therefore we compute the similarity between
177 the kernel functionals using RKHS norm ($\|\cdot\|_{\mathcal{H}_\kappa}$) estimated as,

$$\|K_1 - K_2\|_{\mathcal{H}_{\kappa' \neq \kappa}} \approx \|\mu_1 - \mu_2\|_{\mathcal{H}_\kappa} = \sqrt{\boldsymbol{\alpha}_1^\mathsf{T}\boldsymbol{\kappa}\boldsymbol{\alpha}_1 + \boldsymbol{\alpha}_2^\mathsf{T}\boldsymbol{\kappa}\boldsymbol{\alpha}_2 - 2\boldsymbol{\alpha}_1^\mathsf{T}\boldsymbol{\kappa}\boldsymbol{\alpha}_2} \tag{7}$$

178 where μ_1 and μ_2 are the posterior mean approximations of K_1 and K_2, respectively. We refer to the
179 supplementary material for the details of similarity formulations using L_2-Norm.

Kernel Optimisation. We find the best kernel functional in the given low-dimensional subspace using
181 GP-UCB acquisition function (Eq. (2)) with $\beta_t = 2\log(t^{2+\frac{\hat{n}}{2}}\pi^2/3\hat{\delta})$, where $\hat{n}$ corresponds to the
182 total number of kernel functional observations and $\hat{\delta}$ is a value in $[0, 1]$. The best kernel found ($K^{\#}$)
183 across all the previous subspaces acts as a subspace bias, guiding the optimisation in the next random
184 subspaces as per Eq. (5). The selection of S d-dimensional subspaces (outer-loop) and optimising
185 the kernel (for T iterations) in each of the subspace (inner-loop) continues until the search budget
186 is exhausted. The hyperparameters $\theta = \{\sigma_f^2, \Upsilon\}$ in k_{SE} are tuned by maximising the log marginal
187 likelihood. In addition to that, the hyperparameters of the hyperkernel ($\Theta = \{\lambda_h, l\}$) mentioned in Eq.
188 (3) are tuned using another standard Bayesian optimisation procedure. The observation model for the
189 hyperparameter tuning of hyperkernel is constructed as $\mathfrak{D} = \{(\Theta, y' = \Gamma(\Theta))\}$, where Γ maps the
190 model performance y' with the corresponding hyperparameter set Θ. We refer to the supplementary
191 material for the detailed discussion on tuning the hyperparameters of both kernel and hyperkernel.

From Kreĭn kernels to Positive Definite Gram Matrix

193 As the kernel approximated by Eq. (4) is an indefinite, or Kreĭn kernel (K), the Gram matrix (C)
194 constructed for the datapoints using K is also indefinite. We use the following matrix post-processing
195 methods to ensure the positive definiteness of Gram matrix constructed.

196 The Eigen Value Decomposition (EVD) based matrix post-processing involves the decomposition of
197 the Gram matrix $C = Z\Delta Z^\mathsf{T}$, where Z is the square matrix containing eigenvectors corresponding
198 to the eigenvalues in the diagonal matrix Δ. The Eigen spectrum clip ($\Delta_{ii} = (\Delta_{ii})_+$) ensures
199 positive definiteness of the given training and test covariance matrix, but in isolation, without
200 considering the transformation of the underlying kernel function, thus resulting in inconsistency (see
201 discussion 2.2 in (Chen et al., 2009)). Therefore, to consistently transform both the training and
202 test points, the Eigen spectrum clip is treated as a linear transformation on the training points first
203 *i.e.*, $\widehat{C}_{\text{train}} = \boldsymbol{\vartheta}_{\text{clip}}C_{\text{train}}$, where $\boldsymbol{\vartheta}_{\text{clip}}$ is the spectrum transformation matrix and then, apply the same
204 transformation on $\mathbf{c}_{\text{test}} = [K(\mathbf{x}_{\text{test}}, \mathbf{x}_1)\, K(\mathbf{x}_{\text{test}}, \mathbf{x}_2) \cdots]^\mathsf{T}$ as $\widehat{\mathbf{c}}_{\text{test}} = \boldsymbol{\vartheta}_{\text{clip}}\mathbf{c}_{\text{test}}$, where $\boldsymbol{\vartheta}_{\text{clip}} = Z\Delta_{\text{clip}}Z^\mathsf{T}$

Algorithm 1 Kernel Functional Optimisation

Input: N^2 - Number of points in the grid $\mathcal{G}$

1. Initialise $(K^\#, y_{\text{best}}) \leftarrow (\mathbf{0}, 0)$, $\mathcal{D}_0 \leftarrow \emptyset$
2. Compute $\boldsymbol{\kappa}$ for N^2 grid points $\tilde{\mathbf{x}}_1, \tilde{\mathbf{x}}_2, \cdots$ using Eq. (3)
3. Perform PCA of $\boldsymbol{\kappa}$ as $\boldsymbol{\kappa} = (\boldsymbol{E}\sqrt{\boldsymbol{\Lambda}})(\boldsymbol{E}\sqrt{\boldsymbol{\Lambda}})^\intercal$
4. **for** subspace $s = 1, 2, \cdots, S$ **do** (subspace loop)
5.   Sample $\mathbf{k}^{(1)}, \mathbf{k}^{(2)}, \cdots, \mathbf{k}^{(d)} \sim \mathcal{GP}_\kappa(0, \kappa)$
6.   Generate random initial observations in the current subspace s
   $$\mathcal{D}'_s = \{(K, y) \mid K \xleftarrow{\text{Eq. (4)}} K^\# + \lambda^{(1)}\mathbf{k}^{(1)} + \cdots + \lambda^{(d)}\mathbf{k}^{(d)}, y = f(K), \lambda_{i \in \mathbb{N}_d} \sim U(0, 1)\}$$
7.   **for** each iteration $t = 1, 2, \cdots, T$ **do**
8.   Solve $\boldsymbol{\lambda}_* = \arg\max_{\boldsymbol{\lambda} \in [0,1]^d} u_t(\mu(K(\boldsymbol{\lambda})) + \sqrt{\beta_t}\,\sigma(K(\boldsymbol{\lambda})))$
9.   Compute the new kernel K_{new} as $K_{\text{new}} \xleftarrow{\text{Eq. (4)}} K^\# + \lambda_*^{(1)}\mathbf{k}^{(1)} + \cdots + \lambda_*^{(d)}\mathbf{k}^{(d)}$
10.   Use the kernel K_{new} and $\widehat{C}$ to measure the fitting quality y as $y_{\text{new}} = f(K_{\text{new}})$
11. $\mathcal{D}'_s \leftarrow \mathcal{D}'_s \cup \{(K_{\text{new}}, y_{\text{new}})\}$
12.   **end for**
13. $\mathcal{D}_s \leftarrow \mathcal{D}_{s-1} \cup \mathcal{D}'_s$
14. $(K^\#, y_{\text{best}}) = \arg\max_{(K,y) \in \mathcal{D}_s} y$
15. **end for**
16. $K^* \leftarrow K^\#$
17. return (K^*, y_{best})

---

and $\boldsymbol{\Delta}_{\text{clip}} = \text{diag}(\llbracket \Delta_{11} \geq 0 \rrbracket, \llbracket \Delta_{22} \geq 0 \rrbracket, \cdots)$. The magnitude of change in the transformed matrix ($\widehat{C}$) from the given indefinite kernel matrix (C) is minimum with the spectrum clip transformations *i.e.*, $\widehat{C}_{\text{clip}} = \arg\min_{\widehat{C} \succ 0} \|C - \widehat{C}\|_{\text{F}}$. We note that, it is possible to use the original optimised kernel for specialised SVMs (Ying et al., 2009), but we consider this as part of the future work.

The aforestated post-processing gets complicated for GP. The GP predictive distribution involves the calculation of mean $\mu(\cdot)$ and variance $\sigma^2(\cdot)$ for the test samples. The variance requires the computation of $[K(\mathbf{x}_{\text{text}}, \mathbf{x}_{\text{text}})]$. Although the linear transformation $\boldsymbol{\vartheta}_{\text{clip}}$ on C_{train} ensures positive definiteness of $\mathbf{c}_{\text{test}} = [K(\mathbf{x}_{\text{test}}, \mathbf{x}_1)\, K(\mathbf{x}_{\text{test}}, \mathbf{x}_2) \cdots]^\intercal$, it does not consistently transform $[K(\mathbf{x}_{\text{text}}, \mathbf{x}_{\text{text}})]$. Thus for GP, to ensure positive definiteness of the kernel approximated, we clip the values of $\boldsymbol{\alpha}$ in Eq. (4) *i.e.*, $\boldsymbol{\alpha} = [(\alpha)_+]$ by visualising Eq. (4) in terms of representer theory mentioned in Ong et al. (2005).

4 Theoretical Analysis

4.1 Inner-Loop

The cumulative regret for the optimisation in the inner-loop is calculated as $R_T = \sum_{t=1}^{T} f(K^*) - f(K_t)$, where K^* is the best kernel found across all the subspaces. In the inner-loop, our goal is to derive the upper bound for cumulative regret (R_T) in terms of the total number of iterations T.

In conventional BO algorithms, the variables being optimised are directly used in the model construction. In contrast, the inner-loop in our proposed method constructs the model using the projection of the variables being optimised ($\boldsymbol{\lambda}_*$) in the functional space *i.e.*, $\mathbf{k} = K^\# + \sum_i \lambda^{(i)}\mathbf{k}^{(i)}$.

Proposition 1 : *Let $\mathbb{S}_s$ be the subspace constructed in each instance s of the outer loop. Then, at each iteration t in the inner-loop, the maximum information gain (γ_t) of the kernel $\widehat{k} : \mathbb{S}_s \times \mathbb{S}_s \rightarrow \mathbb{R}$ is same as that of the information gain (γ_t) of the standard kernel in euclidean space $k : \mathcal{X} \times \mathcal{X} \rightarrow \mathbb{R}$.*

The proof of proposition 1 is deferred to the supplementary material.

It is important to note that the model for f in the inner-loop is constructed with the observations obtained from the current and previous subspaces search and not just the observations from the current search. Therefore, the bounds on the overall regret for the inner-loop can be derived as follows.

Theorem 1 : *Let $f(K)|\mathcal{D}_{s-1}$ be the posterior of f in subspace s before entering the inner-loop and $f(K)|\mathcal{D}_{s-1} \cup \mathcal{D}'_s$ be the posterior at iteration t of the inner-loop. Then, the updated posterior $f(K)|\mathcal{D}_{s-1} \cup \mathcal{D}'_s$ is equivalent to the posterior of the biased GP with prior covariance $K_{\mathcal{D}_{s-1}}$ and the inner-loop regret grows sublinearly as $\mathcal{O}^*(\sqrt{dt\gamma_{\mathcal{D}_{s-1},t}})$, where $\gamma_{\mathcal{D}_{s-1},t}$ is the maximum information gain for prior covariance $K_{\mathcal{D}_{s-1}}$ and $\mathcal{O}^*$ notation is a variation of $\mathcal{O}$ with log factors suppressed.*

The proof of Theorem 1 is provided in the supplementary material.

4.2 Outer-Loop

We provide theoretical analysis of the outer-loop based on the notion of *effective dimension* (Kirschner et al., 2019, Wang et al., 2016). As we deal with functionals in our method, the standard definition of *effective dimension* is slightly modified as follows:

Definition 3: *A function f is said to have effective dimensionality $d' \in \mathbb{N}$, such that there exists $\underline{\mathbf{k}}^{(1)}, \underline{\mathbf{k}}^{(2)}, \cdots, \underline{\mathbf{k}}^{(d')} \in \mathcal{H}_\kappa$ such that $\|f(K + K_\perp) - f(K)\|_{\mathcal{H}_\kappa} = 0, \forall K \in \mathbb{K}, \forall K_\perp \in \mathbb{K}^\perp$, where $\mathbb{K} = \mathrm{span}(\underline{\mathbf{k}}^{(1)}, \underline{\mathbf{k}}^{(2)}, \cdots, \underline{\mathbf{k}}^{(d')})$ and $\mathbb{K}^\perp = \{\tilde{K} \in \mathcal{H}_\kappa \mid \langle K, \tilde{K} \rangle_{\mathcal{H}_\kappa} = 0, \forall K \in \mathbb{K}\}$*

Following Kirschner et al. (2019), we derive the regret bounds for the outer-loop.

Theorem 2: *Given a twice Frechet-differentiable kernel $k : \mathcal{H}_\kappa \times \mathcal{H}_\kappa \to \mathbb{R}$, let $0 < \delta < 1$, $f \sim \mathcal{GP}(0, k)$ with effective dimension d' and maxima $K^* = \mathrm{argmax}_{K \in \mathcal{H}_\kappa} f(K)$. Then, after s subspaces search (s outer-loop iterations), with probability at least $1 - \delta$, the regret $f(K^*) - f(K^\#) \in \mathcal{O}(\llbracket d < d' \rrbracket (\frac{1}{s} \log(\frac{1}{\delta}))^{\frac{2}{d'-d}} + \epsilon_{d,\delta})$, where $K^\#$ is the best kernel found across all the previous subspaces search and $\epsilon_{d,\delta}$ is the regret bound for the inner-loop and $\llbracket \cdot \rrbracket$ is the Iverson bracket.*

The proof of Theorem 2 is provided in the supplementary material.

4.3 Overall Convergence

In LINEBO, one-dimensional subspaces (or the lines) are optimised upto $\mathrm{err}(K^+) < \epsilon$ for some fixed ϵ (Lemma 4 of Kirschner et al. (2019)) and $K^+ = \mathrm{argmax}_{K_i \in K_{1:t}} f(K_i)$. In our method, for a given subspace s, we terminate after T iterations with accuracy $\mathrm{err}(K^+) \leq \epsilon_{d,\delta}$. In our setup with $d = 1$, given a fixed budget (T iterations) for the inner-loop, we get $\epsilon_{1,\delta} \in \mathcal{O}(T^{c-\frac{1}{2}})$, where $c \in (0, 0.5)$ (Assumption 2 in Kirschner et al. (2019)). On the other hand, if the number of vectors (d) spanning the random basis is same as the effective dimensionality (d'), then our convergence is analogous to REMBO (Wang et al., 2016), with the regret imposed only by $\epsilon_{d',\delta}$. Further, the order of regret bound in such cases remains unchanged even if we consider only one subspace search ($S = 1$).

Alternatively, simple regret measure implemented as a terminating condition in the inner-loop results in the regret bound $\epsilon_{d,\delta} = \epsilon$. If we consider one-dimensional spaces ($d = 1$) and use $\mathrm{err}(K^+) < \epsilon$ as the terminating condition for the inner-loop, the convergence guarantee of our algorithm is exactly same as that of LINEBO with $\epsilon_{d,\delta} = \epsilon$. Thus, the inner-loop of our algorithm is expected to complete in $T \in \mathcal{O}(\epsilon^{\frac{2}{1-2c}})$ iterations for some $c \in (0, 0.5)$ (see discussion around Assumption 2 in Kirschner et al. (2019)), resulting in $\mathcal{O}(S\epsilon^{\frac{2}{1-2c}})$ total number of function evaluations overall.

5 Experiments

We evaluate the performance of our proposed algorithm (KFO) on synthetic benchmark functions and also apply our method on real-world datasets for SVM classification and GP regression tasks. We have considered the following experimental settings for KFO. We have used Matérn Harmonic Hyperkernel (Eq. (3)) to define the space of kernel functionals. To express the kernel as kernel functional in Hyper-RKHS, we consider $N^2 \gtrsim 10 \times n$ for a given n dimensional problem. The outer-loop representing the number of low-dimensional subspace searches (S) to find the best kernel function is restricted to $S = 5$ and the number of iterations (T) in each of the subspace (inner-loop) is restricted to $T = 20$. We use GP-UCB acquisition function to guide the search for optimum in

all our experiments and at all levels. The hyperparameters λ_h and l of the hyperkernel (Eq. (3)) are
tuned in the interval $(0, 1]$ using a standard BO procedure mentioned in the supplementary material.

5.1 Synthetic Experiments

In this experiment, we test our algorithm (KFO) with the following synthetic functions: **(i)** Triangular
wave **(ii)** a mixture of three Gaussian distributions (G_{mix}), and **(iii)** SINC function. We compare with
the following stationary and non-stationary kernels **(i)** SE kernel **(ii)** Matérn kernel with $\nu = 3/2$
(Mat3/2) **(iii)** Multi-Kernel Learning (MKL) as a linear combination of SE, Mat3/2 and Linear kernel.
The kernel hyperparameters Υ, σ_f^2 and weights $\mathbf{w}$ (in the case of MKL) are tuned by maximising
the log marginal likelihood. We compute posterior distribution and maximum log-likelihood for the
aforesaid synthetic functions. The maximum log-likelihood (and the standard deviation) is computed
over 10 repeated runs. We show the posterior distribution and the maximum log-likelihood estimates
obtained for Triangular wave function in Figure 2. We refer to the supplementary material for the
results on other synthetic functions. It is evident that the posterior distribution computed using the
standard kernels has poor predictions in the held-out test region. By contrast, kernel suggested by
KFO has better predictive mean and variance in the held-out test region. Especially note that the
KFO optimised kernel was able to find the correct periodicity even without explicit enforcement.

likelihood$_{\text{SE}} = -173 \pm 1.2$ likelihood$_{\text{MAT}} = 81.8 \pm 1.9$ likelihood$_{\text{MKL}} = 82.1 \pm 0.4$ likelihood$_{\text{KFO}} = 89.8 \pm 1.6$

Figure 2: Posterior distributions and maximum log-likelihood computed for Triangular wave function
using KFO and other baselines. The solid blue line shows the true function. The green shaded area
covers two standard deviations above and below the posterior mean shown by a green dashed line.

5.2 Real-world Experiments

We compare the performance of our proposed algorithm in SVM classification and GP regression
tasks against the state-of-the-art baselines. In our classification and regression experiments, we use
the publicly available multi-dimensional real-world datasets from the UCI repository (Dua and Graff,
2017). In SVM classification problems, we use C-SVM in conjunction with KFO to minimise the test
classification error (E_r). We perform 10-fold cross-validation on the training data set containing 80%
of the total instances and tune the Cost parameter (C) of the SVM in the exponent space of $[-3, 3]$.

We compare our results with Radial Basis Function (RBF) based traditional C-SVM classifier (SVM-
RBF) and MKL based SVM classifier (SVM-MKL). We also compare with ν parameterised Linear
SVM ($\nu-$SVM) adhering to the definition of the hyperkernel optimisation problems using the results
mentioned in Ong and Smola (2003). The classification error percentage obtained for the test sets
consisting of 20% of the total instances using different classification algorithms are shown in Table 1.
To demonstrate the efficiency of our approach, we also present the best test classification error (last
column of Table 1) reported by state-of-the-art classifiers in the literature Zhang et al. (2017). To the
best of our knowledge, Zhang et al. (2017) is the most recent work that surveyed numerous classifiers
and reported their performance on UCI datasets. Additionally, we also construct a SVM classifier
(KFO-MKL) with its kernel formulated as a weighted combination of KFO tuned kernel and standard
kernels (analogous to MKL), we refer to the supplementary material for the results.

In GP regression tasks on UCI datasets, we compute negative log-likelihood (Eq. (1)) on the test set
as the measure of performance. We compare our results with the standard parametric kernels such as

RBF and Automatic Relevance Determination (ARD) Matérn kernel and the non-parametric kernels such as Functional Kernel Learning (FKL-Shared and FKL-Separate) kernel mentioned in Benton et al. (2019). In FKL-Separate, the functional kernel learning is achieved by formulating a product of one-dimensional kernels, each of which has its own GP and hyperparameters. In contrast, FKL-Shared uses a GP with unique set of hyperparameters to draw one-dimensional kernels. The results of our GP regression tasks are shown in Table 2, with each cell containing the negative log-likelihood and the standard deviation averaged over 10 repeated runs with random $80/20$ train/test splits. Evidently, our method outperformed the state-of-the-art baselines in both the SVM classification and GP regression experiments, demonstrating the significant improvement in generalisation performance. We refer to the supplementary material for the other experimental results and the code base used.

Table 1: SVM classification results (test classification error and the standard deviation) for the real-world datasets using KFO and other baselines for the test set consisting of 20% of the total instances. Bold indicates the best performance among all the columns. The last column shows the best performance reported among all the other classifiers[†] mentioned in Zhang et al. (2017).

Dataset	KFO	SVM-RBF	SVM-MKL	$\nu-$SVM	Other Classifiers[†]
Ionosphere	$\mathbf{3.06 \pm 1.6}$	6.1 ± 1.8	9.31 ± 0.4	6.7 ± 1.8	5.56
Glass	9.3 ± 0.19	$\mathbf{7.2 \pm 2.7}$	20.86 ± 0.7	8.9 ± 2.6	9.52
Sonar	6.6 ± 1.2	15.3 ± 4.1	20.99 ± 4.4	15.3 ± 3.7	$\mathbf{4.76}$
Heart	$\mathbf{11.47 \pm 0.2}$	23.2 ± 3.7	15	19.3 ± 2.4	14.14
Wine	$\mathbf{0}$	0.01 ± 0.01	$\mathbf{0}$	$\mathbf{0}$	$\mathbf{0}$
Credit	28.19 ± 3.57	15.3 ± 2.0	13.62 ± 1.8	$\mathbf{13.8 \pm 3.1}$	24.00
Biodeg	12.12 ± 1.29	26.39 ± 2.5	12.33 ± 1.5	14.4 ± 4.4	$\mathbf{11.32}$
Hayes-Roth	$\mathbf{14.18 \pm 0.1}$	35.81 ± 6.2	18.69 ± 0.9	16.1 ± 6.9	21.43
WDBC	$\mathbf{0.68 \pm 0.84}$	5.2 ± 1.4	2.05 ± 1.6	3.8 ± 1.2	1.59
Contraceptive	$\mathbf{30.1 \pm 2.71}$	35.49 ± 1.6	32.86 ± 2.3	36.95 ± 3.7	44.59
Car	$\mathbf{0}$	5.30 ± 0.5	2.54 ± 0.4	2.22 ± 0.05	$\mathbf{0}$
Phoneme	22.74 ± 2.31	22.85 ± 1.6	20.12 ± 0.3	17.58 ± 0.5	$\mathbf{10.17}$
Ecoli	$\mathbf{0.96 \pm 0.7}$	3.99 ± 0.7	2.58 ± 1.3	3.99 ± 0.7	12.12
Seeds	$\mathbf{1.2 \pm 0.2}$	8.74 ± 0.4	3.96 ± 0.5	10.32 ± 4.8	4.55
Summary	$9/14$	$1/14$	$1/14$	$2/14$	$5/14$

Table 2: GP Regression results (negative log-likelihood and the standard deviation) for the real-world datasets using KFO and other baselines. Bold indicates the best performance among all the columns.

Dataset	KFO	RBF	ARD Matérn	FKL-Shared	FKL-Seperate
Fertility	5.15 ± 2.95	-3.90 ± 1.76	$\mathbf{-4.40 \pm 2.58}$	-2.7 ± 1.25	-1.83 ± 3.3
Yacht	$\mathbf{-34.6 \pm 1.6}$	1.65 ± 76.47	-19.49 ± 14.0	-14.52 ± 4.7	-15.7 ± 8.2
Slump	$\mathbf{-3.01 \pm 1.7}$	36.302 ± 7.93	26.33 ± 7.48	4.38 ± 1.33	59.4 ± 12.87
Boston	$\mathbf{-24.7 \pm 4.2}$	139.61 ± 11.5	130.8 ± 10.50	122.6 ± 3.91	143.7 ± 5.71
Auto	$\mathbf{-8.78 \pm 1.2}$	96.18 ± 8.02	94.01 ± 5.03	101.7 ± 19.3	98.94 ± 6.1
Airfoil	$\mathbf{-204.1 \pm 4.5}$	358.93 ± 8.93	305.88 ± 7.46	270.0 ± 28.4	284.8 ± 48.7

6 Conclusion

We present a novel formulation for kernel selection via the optimisation of kernel functionals using Bayesian functional optimisation. The kernel functional learnt is a non-parametric kernel capable of capturing the intricate stationary and non-stationary variations. Our algorithm iteratively searches through a sequence of random kernel functional subspaces where the best kernel obtained from all the previous subspaces search biases the next search. The resultant kernel is an indefinite, or Kreĭn kernel, thus we use matrix post-processing techniques to ensure the positive definiteness of the resulting Gram matrix. The theoretical analysis shows a fast convergence rate of our algorithm. The experimental results show that our method outperforms the other state-of-the-art baselines.

References

F. Aiolli and M. Donini. EasyMKL: a scalable Multiple Kernel Learning algorithm. *Neurocomputing*, 169:215–224, 2015.

N. Aronszajn. Theory of reproducing kernels. *Transactions of the American Mathematical Society*, 68(3):337–404, 1950.

G. Benton, W. J. Maddox, J. Salkey, J. Albinati, and A. G. Wilson. Function-space distributions over kernels. In *Advances in Neural Information Processing Systems (NeurIPS 2019)*, pages 14965–14976, 2019.

E. Brochu, V. M. Cora, and N. De Freitas. A tutorial on Bayesian optimisation of expensive cost functions, with application to active user modeling and hierarchical reinforcement learning. *arXiv preprint arXiv:1012.2599*, 2010.

C. J. Burges. A tutorial on support vector machines for pattern recognition. *Data Mining and Knowledge Discovery*, 2(2):121–167, 1998.

Y. Chen, E. K. Garcia, M. R. Gupta, A. Rahimi, and L. Cazzanti. Similarity-based classification: concepts and algorithms. *Journal of Machine Learning Research*, 10(3), 2009.

C. P. Diehl and G. Cauwenberghs. SVM incremental learning, adaptation and optimisation. In *Proceedings of the International Joint Conference on Neural Networks, (IJCNN 2003)*, volume 4, pages 2685–2690. IEEE, 2003.

D. Dua and C. Graff. UCI machine learning repository, 2017. URL `http://archive.ics.uci.edu/ml`.

P. I. Frazier. A tutorial on Bayesian optimisation. *arXiv preprint arXiv:1807.02811*, 2018.

M. G. Genton. Classes of kernels for machine learning: a statistics perspective. *Journal of Machine Learning Research*, 2(Dec):299–312, 2001.

M. Gönen and E. Alpaydın. Multiple kernel learning algorithms. *Journal of Machine Learning Research*, 12:2211–2268, 2011.

K. E. Iverson. *A programming language*. John Wiley & Sons, USA, 1962. ISBN 0471430145.

P. A. Jang, A. Loeb, M. Davidow, and A. G. Wilson. Scalable Lévy process priors for spectral kernel learning. In *Advances in Neural Information Processing Systems (NeurIPS 2017)*, pages 3940–3949, 2017.

M. Kanagawa, P. Hennig, D. Sejdinovic, and B. K. Sriperumbudur. Gaussian processes and kernel methods: a review on connections and equivalences. *arXiv preprint arXiv:1807.02582*, 2018.

J. Kirschner, M. Mutný, N. Hiller, R. Ischebeck, and A. Krause. Adaptive and safe Bayesian optimisation in high dimensions via one-dimensional subspaces. *arXiv preprint arXiv:1902.03229*, 2019.

H. J. Kushner. A new method of locating the maximum point of an arbitrary multipeak curve in the presence of noise. *Journal of Basic Engineering*, 86:97–106, 1964.

J. Močkus. On Bayesian methods for seeking the extremum. In *Optimisation Techniques IFIP Technical Conference*, pages 400–404. Springer, 1975.

D. Oglic and T. Gärtner. Learning in reproducing kernel Kreĭn spaces. In *Proceedings of the 35th International Conference on Machine Learning (ICML 2018)*, 2018.

D. Oglic and T. Gärtner. Scalable learning in reproducing kernel Kreĭn spaces. In *Proceedings of the 36th International Conference on Machine Learning (ICML 2019)*, pages 4912–4921, 2019.

C. S. Ong and A. J. Smola. Machine learning with hyperkernels. In *Proceedings of the 20th International Conference on Machine Learning (ICML 2003)*, pages 568–575, 2003.

C. S. Ong, R. C. Williamson, and A. J. Smola. Hyperkernels. In *Advances in Neural Information Processing Systems (NeurIPS 2003)*, pages 495–502, 2003.

C. S. Ong, X. Mary, S. Canu, and A. J. Smola. Learning with non-positive kernels. In *Proceedings of the 21st International Conference on Machine Learning (ICML 2004)*, page 81, 2004.

C. S. Ong, A. J. Smola, and R. C. Williamson. Learning the kernel with hyperkernels. *Journal of Machine Learning Research*, 6(Jul):1043–1071, 2005.

A. Rakotomamonjy, F. Bach, S. Canu, and Y. Grandvalet. More efficiency in multiple kernel learning. In *Proceedings of the 24th International Conference on Machine Learning (ICML 2007)*, pages 775–782, 2007.

B. Scholkopf and A. J. Smola. *Learning with kernels: support vector machines, regularisation, optimisation, and beyond*. MIT Press, Cambridge, MA, USA, 2001. ISBN 0262194759.

B. Shahriari, K. Swersky, Z. Wang, R. P. Adams, and N. De Freitas. Taking the human out of the loop: a review of Bayesian optimisation. *Proceedings of the IEEE*, 104(1):148–175, 2015.

A. Shilton, S. Rana, S. Gupta, and S. Venkatesh. Sequential subspace search for functional Bayesian optimisation incorporating experimenter intuition. *arXiv preprint arXiv:2009.03543*, 2020.

N. Srinivas, A. Krause, S. M. Kakade, and M. W. Seeger. Information-theoretic regret bounds for Gaussian process optimisation in the bandit setting. *IEEE Transactions on Information Theory*, 58 (5):3250–3265, 2012.

M. Stein. *Interpolation of spatial data: some theory for kriging*. Springer, 02 2015. doi: 10.1007/ 978-1-4612-1494-6.

I. Steinwart and A. Christmann. *Support vector machines*. Springer Science & Business Media, 2008.

L. Vandenberghe and S. Boyd. Semidefinite programming. *SIAM Rev.*, 38(1):49–95, Mar. 1996. ISSN 0036-1445. doi: 10.1137/1038003. URL https://doi.org/10.1137/1038003.

V. N. Vapnik. An overview of statistical learning theory. *IEEE Transactions on Neural Networks*, 10 (5):988–999, 1999.

P. Vellanki, S. Rana, S. Gupta, D. R. de Celis Leal, A. Sutti, M. Height, and S. Venkatesh. Bayesian functional optimisation with shape prior. In *Proceedings of the 33rd AAAI Conference on Artificial Intelligence (AAAI 2019)*, volume 33, pages 1617–1624, 2019.

N. A. Vien, H. Zimmermann, and M. Toussaint. Bayesian functional optimisation. In *Proceedings of the 32nd AAAI Conference on Artificial Intelligence (AAAI 2018)*, pages 4171–4178, 2018.

Z. Wang, F. Hutter, M. Zoghi, D. Matheson, and N. de Feitas. Bayesian optimisation in a billion dimensions via random embeddings. *Journal of Artificial Intelligence Research*, 55:361–387, 2016.

C. K. Williams and C. E. Rasmussen. *Gaussian processes for machine learning*, volume 2. MIT press Cambridge, MA, 2006.

A. Wilson and R. Adams. Gaussian process kernels for pattern discovery and extrapolation. In *Proceedings of the 30th International Conference on Machine Learning (ICML 2013)*, pages 1067–1075, 2013.

J. Wilson, F. Hutter, and M. Deisenroth. Maximising acquisition functions for Bayesian optimisation. In *Advances in Neural Information Processing Systems (NeurIPS 2018)*, pages 9884–9895, 2018.

413   S. Wold, K. Esbensen, and P. Geladi. Principal component analysis. *Chemometrics and Intelligent*
414   *Laboratory Systems*, 2(1-3):37–52, 1987.

415   Y. Ying, C. Campbell, and M. Girolami. Analysis of SVM with indefinite kernels. In *Advances in*
416   *Neural Information Processing Systems (NeurIPS 2003)*, volume 22. Curran Associates, Inc., 2009.

417   C. Zhang, C. Liu, X. Zhang, and G. Almpanidis. An up-to-date comparison of state-of-the-art
418   classification algorithms. *Expert Systems with Applications*, 82:128–150, 2017.