Graph Coloring via Neural Networks for Haplotype Assembly and Viral Quasispecies Reconstruction

Abstract

Understanding genetic variation, e.g., through mutations, in organisms is crucial to unravel their effects on the environment and human health. A fundamental characterization can be obtained by solving the haplotype assembly problem, which yields the variation across multiple copies of chromosomes. Variations among fast evolving viruses that lead to different strains (called quasispecies) are also deciphered with similar approaches. In both these cases, high-throughput sequencing technologies that provide oversampled mixtures of large noisy fragments (reads) of genomes, are used to infer constituent components (haplotypes or quasispecies). The problem is harder for polyploid species where there are more than two copies of chromosomes. State-of-the-art neural approaches to solve this NP-hard problem do not adequately model relations among the reads that are important for deconvolving the input signal. We address this problem by developing a new method, called `NeurHap`, that combines graph representation learning with combinatorial optimization. Our experiments demonstrate substantially better performance of `NeurHap` in real and synthetic datasets compared to competing approaches.

1   Introduction

Our genetic material is organized as sequences of DNA or RNA molecules (nucleotides) which form three-dimensional structures (chromosomes) within our cells. Most organisms have multiple highly similar copies of chromosomes in their cells (e.g., humans have 2). Variations in genetic sequences lead to the emergence of new species during evolution and are also known to be associated with many diseases (e.g., cancer). There are many possible ways in which such variations can occur; the simplest among them is a *mutation* or a change in the nucleotide at a specific location in the DNA or RNA sequence. A Single Nucleotide Polymorphism (SNP) refers to a mutation in at least one of the copies which renders the copies nonidentical at that point. An ordered list of SNPs on a single chromosome is called a haplotype [Schwartz, 2010]. Haplotypes provide a signature of genetic variability and thus inform us about disease susceptibilities and evolutionary patterns (e.g., of viruses). These studies in turn pave the way for personalized medicine and effective drug development against viruses.

The problem of inferring haploytypes from high-throughput sequencing data is called haplotype assembly or phasing, and is done in multiple stages (see Figure 1). Sequencing data yields multiple copies of short fragments of the entire genomic sequence (called reads, Figure 1b). These reads are noisy due to sequencing errors and their short lengths may span across limited number of SNPs. This makes the problem of haplotype phasing challenging. The reads are first aligned to a reference genome. This step indicates positions that are different across reads and thus infers the potential locations of SNPs. All other positions are discarded to obtain the SNP matrix (Figure 1c). This matrix may be viewed as an oversampled mixture of noisy reads (restricted to SNPs). Each mixture component represents a single haplotype and thus should have SNPs at the same locations.

Figure 1: The pipeline of reference-based polyploid haplotypes reconstruction and `NeuralHap`.

In diploid species, containing two copies of chromosomes, there are two haplotypes to be inferred. This problem has been studied extensively [Browning and Browning, 2011]. In polyploid species, containing more than two copies of chromosomes (and thus more than two haplotypes), the problem is more challenging due to dramatic increase in search space [Van de Peer et al., 2017, Abou Saada et al., 2022, Jablonski and Beerenwinkel, 2021]. In reconstruction of virus strains, called viral quasispecies, from viral populations, similar challenges arise. Moreover, unknown population sizes and imbalanced abundances pose additional difficulties [Jablonski and Beerenwinkel, 2021].

Existing approaches for haplotype phasing of polyploid species and viral quasispecies often group reads in the SNP matrix into clusters that correspond to different haplotypes, respectively. In an ideal case, all reads from the same cluster should be consistent with respect to SNPs as they all belong to the same haplotype. In reality inconsistencies occur due to sequencing errors in reads. Therefore, a minimum error correction (MEC) score [Lippert et al., 2002b] is used to measure the discrepancy between the consensus haplotypes and their associated reads within each cluster (see Figure 1e). It is NP-hard to optimize the MEC score [Zhang et al., 2006], and a number of combinatorial optimization heuristics have been proposed to approximate the optimal MEC score [Zhang et al., 2020].

More recently, the first neural network-based learning framework, named GAEseq [Ke and Vikalo, 2020b], was proposed to phase haplotype for polyploid species and viral quasispecies. CAECseq was later developed using a convolutional auto-encoder which captures spatial relationship between SNPs and enables clustering reads obtained from highly similar genomic regions [Ke and Vikalo, 2020a]. Both GAEseq and CAECseq showed improved results compared to previous approaches. A major limitation of both CAECseq and GAEseq is that they cannot capture implicit relations among different reads. These methods have two independent steps (embedding and clustering) which makes the haplotype phasing results unstable. Besides, sparsity of the SNP matrix makes haplotype phasing for polyploids more challenging for these methods as well.

In this paper, we propose an approach based on graph representation learning for haplotype phasing of polyploid species and viral quasispecies. We formulate the haplotype phasing problem as a graph coloring problem, where the colors indicate haplotypes. The graph is constructed from the SNP matrix where vertices are reads and two edge types are defined based on pairwise consistency and conflicts with respect to SNPs in the reads. Message passing-based neural networks are trained to minimize a loss designed to obtain a color assignment that maximizes consistent edges and minimizes conflicting edges. The network learns vertex representations and through them, an initial color assignment. A local refinement strategy is then applied to adjust node colors in order to minimize MEC scores. Thus, in contrast to previous neural approaches that first learn representations and then cluster, our approach models the problem requirements in all steps. As a result, our model achieves better MEC scores, is more stable and also performs well on the challenging cases of polyploids and viral quasispecies. In summary, our contributions are:

- We provide a unique formulation of the haplotype phasing problem as a graph coloring problem, and develop an algorithm based on graph representation learning and combinatorial optimization.

- Our approach consists of `NeurHap`-search, a graph neural network to learn vertex representations and color assignments followed by `NeurHap`-refine, a local refinement strategy to adjust colors and optimize MEC scores.
- Extensive experiments on synthetic and real datasets demonstrate that our new method `NeuralHap` significantly outperforms state-of-the-art phasing methods for both polyploid species and viral quasispecies.

2   Related Work

Haplotype Phasing. The aim of haplotype phasing of polyploid species and viral quasispecies is to group reads into homogeneous clusters that corresponds to different haplotypes, respectively. The minimum error correction (MEC) score [Lippert et al., 2002b] is introduced to measure the total discrepancy of reads in all clusters but is NP-hard to be optimised [Zhang et al., 2006]. Haplotype phasing for diploid species (i.e., reconstructing two haplotypes) has been extensively studied in the last two decades and a number of combinatorial optimization heuristics have been proposed to approximate the optimal MEC score, such as BNB [Wang et al., 2005], HapCUT [Bansal and Bafna, 2008], HASH [Bansal et al., 2008], RefHap [Duitama et al., 2012] ProbHap [Kuleshov, 2014], HapCUT2 [Edge et al., 2017] and others, and refer to [Zhang et al., 2020] for a recent review on phasing diploid species.

Haplotype phasing for polyploid species (i.e., reconstructing more than two haplotypes) becomes more computationally challenging as it requires a much larger search space compared to phasing two haplotypes for diploids species. A limited number of phasing methods work for ployploid species, e.g., HapCompass [Aguiar and Istrail, 2012], SDhaP [Das and Vikalo, 2015], H-PoP [Xie et al., 2016], AltHap [Hashemi et al., 2018], refer to [Abou Saada et al., 2022] for a recent review. Haplotype phasing for viral quasispecies is very similar to the problem of phasing polyploid species. While haplotypes in polyploid species typically have uniform abundances, the different haplotypes (strains) in viral quasispecies may have varying abundances. Quite a few tools have also been proposed for haplotype phasing of viral quasispecies, such as ViSpA [Astrovskaya et al., 2011], ShoRAH [Zagordi et al., 2011], QuRe [Prosperi and Salemi, 2012], QuasiRecomb[Töpfer et al., 2013], PredictHaplo [Prabhakaran et al., 2014], aBayesQR [Ahn and Vikalo, 2018], TenSQR [Ahn et al., 2018], refer to [Jablonski and Beerenwinkel, 2021] for a recent review.

More recently, deep learning models have been introduced into haplotype phasing for polyploid species and viral quasispecies. GAEseq [Ke and Vikalo, 2020b] uses a graph auto-encoder model on the constructed reads-SNPs bipartite network to model the relations between reads and SNPs. CAECseq [Ke and Vikalo, 2020a] uses a convolutional auto-encoder model to represent reads as low-dimensional features and then employs a clustering algorithm to group these reads. Note that GAEseq and CAECseq can be directly used to phase haplotypes for both polyploid species and viral quasispecies. Experimental results on both simulated and real datasets showed the superior results of GAEseq and CAECseq (in terms of MEC scores) compared to previous approaches for haplotype phasing for both polyploid species and viral quasispecies [Ke and Vikalo, 2020b,a]. However, implicit relations among different reads have not been fully captured by GAEseq and CAECseq, especially when embedding and clustering are modelled separately and the SNP matrix is sparse.

Neural Networks on Graph. Most existing graph neural networks can be explained as a message-passing based graph learning model which recursively combines learned features/messages from their neighbors [Cui et al., 2019, Cai et al., 2018, Gilmer et al., 2017]. Popular methods include GCN [Kipf and Welling, 2017], GraphSAGE [Hamilton et al., 2017], GAT [Veličković et al., 2018] and GIN [Xu et al., 2019]. All these methods make the homophily assumption that similar nodes in the graph should be embedded close together. However, graph coloring aims to assign pairwise nodes with distinct colors for each edge of the graph, which is opposite to the homophily assumption. An intuitive way to integrate GNN models into the graph coloring challenge is to adjust the loss functionm, such as GNN-GCP [Lemos et al., 2019], RUN-CSP [Toenshoff et al., 2019], and PI-GNN [Schuetz et al., 2022]. However, existing GNN-based graph coloring models cannot be implemented to the read-overlap graph directly because they cannot handle conflict and consistent edges simultaneously.

3 Methodology

Overview. In this paper, we propose the model of neural networks for graph coloring optimization to solve the haplotype reconstruction problem, called `NeurHap`. `NeurHap` mainly contains three steps, i) constructing the *read-overlap graph*; ii) global coloring searching via iterative neural networks model, `NeurHap-search`; iii) local refinement to fine tune final coloring, `NeurHap-refine`.

Notations. Let k be the number of haplotypes in a cell of polyploid species (aka. *ploidy*) or the number of strains in viral quasispecies. For example, human and other mammals contain two haplotypes (diploid, *k=2*); plants have more than 2 haplotypes (e.g., California redwood has six copies of each chromosome, hexaploid, *k=6*). Viral quasispecies mixing 5 distinct HIV strains will have $k = 5$.

Figure 2: A toy example of constructing *read-overlap graph* with conflict edges (in grey) and consistent edge (in blue)

Single nucleotide polymorphisms (SNPs) refer to positions where not all haplotypes have the same alleles. Given the alignment of reads to a reference genome, the SNP columns can be identified by removing the columns with identical alleles. The remaining alignment is referred to as a $m \times n$ SNP matrix $\mathcal{R}$ where m denotes the number of reads and n is the number of SNPs. The haplotype reconstruction aims to group m reads into k clusters , $\{C_1, C_2, \ldots, C_k\}$, that correspond to k haplotypes, $\{\mathcal{H}_1, \mathcal{H}_2, \ldots, \mathcal{H}_k\}$ respectively. Once reads are grouped into clusters, the haplotype $\mathcal{H}_i$ can be reconstructed from reads in C_i using a simple consensus voting. In the ideal case, all the reads from the cluster C_i will be all consistent with $\mathcal{H}_i$. In reality, this is not the case and thus a minimum error correction (MEC) score [Lippert et al., 2002b] is introduced to measure the discrepancy between the reads in the cluster C_i and the consensus haplotypes $\mathcal{H}_i$ in all clusters. Given the grouping of reads into k clusters $\{C_1, C_2, \ldots, C_k\}$, the corresponding MEC score can be computed as

$$\text{MEC}(C_1, C_2, \ldots, C_k) = \sum_{i=1}^{k} \sum_{R_j \in C_i} HD(\mathcal{H}_i, R_j) \tag{1}$$

where $HD(\cdot)$ is the Hamming distance function. Note that $HD(\mathcal{H}_i, R_j)$ for $R_j \in C_i$ can only be computed when we know all the reads in the cluster C_i and use them to derive the consensus haplotype $\mathcal{H}_i$ of C_i. The main challenge in haplotype phasing is to find the grouping of reads into $\{C_1, C_2, \ldots, C_k\}$ such that the MEC score is minimized.

In order to minimize the MEC score, reads from the same cluster should be as consistent as possible. Two reads are called *overlapping* if they span over common SNP positions otherwise *non-overlapping*. Two overlapping read are called *consistent* if they have the same alleles at the overlapping SNP positions otherwise in *conflict*. Given any two reads, the relationship between them must be one of three cases, *non-overlapping*, *consistent*, *conflict*. For example, in figure 2, R_1 and R_7 are *non-overlapping*, R_1 and R_4 are *consistent* and R_1 and R_3 are in *conflict*. In an ideal case, all the overlapping reads in the same cluster must be *consistent*, i.e., if two reads are in *conflict*, they must belong to different clusters. This observation naturally motives us to build a read-overlap graph to model all reads as vertices and the important pairwise relationships (i.e., *consistent* and *conflict*) between overlapping reads as edges. Moreover, if we use k colors to represent the k clusters of reads, the problem of haplotype phasing is reduced to a graph coloring problem on the read-overlap graph. For example, in figure 2, the minimum MEC is achieved by grouping nine reads into three clusters, $C_1 = \{R_1, R_4, R_7\}$, $C2 = \{R_2, R_5, R_8\}$ and $C_3 = \{R_3, R_6, R_9\}$, which correspond to three distinct colors on corresponding vertices in the read-overlap graph, respectively.

3.1 Graph Coloring over Read-overlap Graphs.

The *read-overlap graph* $\mathcal{G} = (\mathcal{V}, \mathcal{E}_=, \mathcal{E}_{\neq})$ is constructed in this step. Here, the vertex set V denotes all reads, the edge set $\mathcal{E}_=$ represents all pairwise consistent relationships between overlapping reads, and the edge set $\mathcal{E}_{\neq}$ refers to the pairwise conflict relationships between overlapping reads. Moreover,

due to sequencing errors and alignment ambiguity, we further introduce two parameters p and q to define the relationship between two reads in the read-overlap graph. Two reads are *overlapping* if they overlap in at least p SNP positions otherwise *non-overlapping*. Two overlapping reads R_i and R_j are *consistent* if they have the same alleles over all SNP positions (i.e., $HD(R_i, R_j) = 0$), and are in *conflict* if they differ on at least q SNP positions (i.e., $HD(R_i, R_j) \geq t$), where $HD(R_i, R_j)$ represents the Hamming distance between two overlapping reads in the read-overlap graph.

Now we are ready to reduce the problem of haplotype phasing to the graph coloring problem on the read-overlap graph. Recall that the haplotype phasing problem aims to group reads into k clusters such that reads from the same cluster are as consistent as possible. If we employ $c(v)$ to represent one out of k colors assigned to a read v (i.e., one of the k clusters that v belongs to), two reads R_i and R_j are in the same cluster if and only if two corresponding vertices v_i and v_j have the same color, i.e., $c(v_i) = c(v_j)$. Now the graph coloring problem needs to assign a color to $c(v)$ for every vertex $v \in \mathcal{V}$ to minimise the MEC score under the constraints that any two conflicting reads have two different colors and any two consistent reads have the same color.

$$\min \ \text{MEC}(c(v_1), c(v_2), \ldots, c(v_n)) = \min \sum_{i=1}^{k} \sum_{c(v_j)=i} \text{HD}(\mathcal{H}_i, R_j)$$

$$\text{s.t.,} \ \begin{cases} \forall (v_i, v_j) \in \mathcal{E}_{\neq}, c(v_i) \neq c(v_j) \\ \forall (v_i, v_j) \in \mathcal{E}_{=}, c(v_i) = c(v_j) \end{cases} \tag{2}$$

Note that the above graph coloring problem is different from the classical graph coloring problem [Pardalos et al., 1998] in combinatorial optimization. While all the edges are conflicting edges in the classical graph coloring problem, the above problem formulation in the equation 2 has constraints for both conflicting and consistent edges. In the following section, we will show how to model these constraints using neural networks.

3.2 Network-based Global Search and Combinatorial Optimization-based Local Refinement

Satisfying Constraints. As the vertices of the read-overlap graph need to be colored to satisfy the constraints in the equation 2, we further reduce the graph coloring problem to a constraints satisfying problem inspired by RUN-CSP [Toenshoff et al., 2019]. Graph neural networks (GNNs) are designed to follow homophily constraints such that similar vertices in the graph are embedded close to each other (i.e., same colors). While this is true for consistent constraints in the read-overlap graph, the conflicting constraints impose heterozygous constraints, i.e., vertices connected by a conflicting edge should have very different embeddings (i.e., different colors). Therefore, given k distinct colors, we introduce two 0/1 metrics in $\mathbb{R}^{k \times k}$ for incorporating the above two different coloring constraints, $\mathcal{M}_{\neq}$ (for conflicting constraints) and $\mathcal{M}_{=}$ (for consistent constraints). The conflict-constraint matrix $\mathcal{M}_{\neq}$ denotes the binary conflict relationships among k colors, i.e., $\mathcal{M}_{\neq}(i, j) = 1$ if $i \neq j$ and 0 otherwise, for any $i, j \in \{1, ..., k\}$. The consistent-constraint matrix $\mathcal{M}_{=}$ denotes the consistent relationships between k colors, i.e., $\mathcal{M}_{=}(i, j) = 1$ if $i = j$ and 0 otherwise, for any $i, j \in \{1, ..., k\}$.

Assume that the coloring-assignment matrix $P \in \mathbb{R}^{|\mathcal{V}| \times k}$ is a matrix that represents the coloring assignment probability (over k colors) for each vertex v in its corresponding row $P(v)$. For any conflicting edge $(v_i, v_j) \in \mathcal{E}_{\neq}$ in the read-overlap graph, we aim to assign different colors to v_i and v_j and thus maximize the sum of joint-probabilities with different colors, i.e., $P(v_i)\mathcal{M}_{\neq}P(v_j)^{\mathsf{T}}$. Symmetrically, for any consistent edge $(v_i, v_j) \in \mathcal{E}_{=}$ in the read-overlap graph, we aim to assign the same colors to v_i and v_j and thus maximize the sum of joint-probabilities with same colors, i.e., $P(v_i)\mathcal{M}_{=}P(v_j)^{\mathsf{T}}$. In summary, the unsupervised objective function can be formulated as follows:

$$\mathcal{L} = -\frac{1}{|\mathcal{E}_{\neq}|} \sum_{(v_i, v_j) \in \mathcal{E}_{\neq}} \log(P(v_i)\mathcal{M}_{\neq}P(v_j)^{\mathsf{T}}) - \lambda \cdot \frac{1}{|\mathcal{E}_{=}|} \sum_{(v_i, v_j) \in \mathcal{E}_{=}} \log(P(v_i)\mathcal{M}_{=}P(v_j)^{\mathsf{T}}). \tag{3}$$

Here, λ controls the importance of consistent constraints compared to conflict constraints. We will now show how to use a representation learning to derive a coloring-assignment matrix P that optimizes the above objective function.

Global Search: `NeurHap`-search To derive a coloring-assignment matrix P, we propose to use an iterative message passing-based representation learning model to capture the structural information of the read-overlap graph. The message-passing learning model mainly contains three operation functions, message-learning, aggregation, and combine operator. Given trainable d-dimensional embeddings for every nodes $\{h(v_1), h(v_2), ..., h(v_n)\}, h(v_i) \in \mathbb{R}^d, v_i \in \mathcal{V}$, which are initialized by randomly sampling from a uniform distribution, the message passing model can be formulated as:

$$
\begin{aligned}
h(v_i) &= \text{COMBINE}(m(v_i), h(v_i)), \\
m(v_i) &= \text{AGGREGATE}(\{\text{MESSAGE}(h(v_i), h(v_j)) : v_j \in N(v_i)\}).
\end{aligned}
\tag{4}
$$

Here, $m(v_i)$ is the learned messages from the neighbors of v_i, and $N(v_i)$ is the neighbors of v_i with respect to conflict edges. $\text{COMBINE}(\cdot)$ is a learnable combine function, $\text{AGGREGATE}(\cdot)$ denotes an aggregation function, and $\text{MESSAGE}(\cdot)$ represents the learnable message function, e.g. $\text{MESSAGE}(h(v_i), h(v_j)) = \text{MLP}(h(v_i)||h(v_j))$. A simple MLP decoder can be used to map the learned node embeddings to the probability of colors: $P(v_i) = \text{DEC}(h(v_i))$. The message-passing model is iteratively trained for t times in each epoch to generate reliable features for each node.

The pseudocode for the global search process of `NeurHap` is as follows:

Algorithm 1: The Global Search Algorithm `NeurHap`-search

Data: SNP matrix $\mathcal{R}$; number of iteration t; number of polyploids k; dimension of hidden features d.
Result: Assignments $\mathcal{Y}$.
1   $\mathcal{E}_{\neq}, \mathcal{E}_{=} \leftarrow$ Equation 1   // Construct conflict and consistent edge set
2   $\mathcal{M}_{\neq}(k), \mathcal{M}_{=}(k)$ // Initialize coloring constraints
3   $h \leftarrow \mathbb{R}^d \sim [0, 1)$ // Initialize by a uniform distribution
4   **for** e epochs **do**
5   **for** t iterations **do**
6         $\overline{m}(v_j) = \text{msg}(h(v_i), h(v_j)) = \text{MLP}(h(v_i)||h(v_j))$ // Compute message from $h(v_i)$ and $h(v_j)$
7         $m(v_i) = \text{agg}(\overline{m}(v_j) : v_j \in N(v_i))$ // Aggregate messages from neighbors of v_i
8         $h(v_i) = \text{comb}(m(v_i), h(v_i))$ // Combine messages from $h(v_i)$ and $m(v_i)$
9   **end**
10     $P \leftarrow \text{dec}(h(v_i))$ // Compute coloring assignment probs
11     $\mathcal{L} \leftarrow$ Equation 3   // Compute conflict loss
12     $\mathcal{Y} \leftarrow P$ // Compute coloring assignment
13 **end**

After optimizing the objective function with `NeurHap`, we can obtain an initial coloring assignment for vertices that satisfy the constraints in the equation 2 in the read-overlap graph. However, the objective function in equation 2 (i.e., the MEC score) may not be optimized as there may exist multiple coloring assignments that satisfy all constraints. Therefore, we run an additional local refinement step to further optimise the objective function in equation 2.

Local refinement: `NeurHap`-refine This step mainly searches for possible color adjustments of individual vertices given their associated conflict and consistent constraints. More specifically, if an individual vertex can be assigned a color different from its current color without violating any of the associated conflict constraints with the neighboring vertices, the color is changed if a better MEC score is obtained by the change. The local refinement algorithm, `NeurHap`-refine, iteratively explores these possible color adjustments of individual vertices. Refer to Appendix A.1 for the pseudocode.

4 Experiments

Dataset. To evaluate the proposed method `NeurHap`, we compare `NeurHap` with state-of-the-art baselines for both polyploid species and viral quasispecies. i) *Polyploid species*: The Solanum Tuberosum is Tetraploid ($k=4$) and the datasets of Solanum Tuberosum contains both simulated

dataset **Sim-Potato** and real-world dataset **Real-Potato**, both downloaded from [Ke and Vikalo, 2020a,b]. **Sim-Potato** contains 40 sub-datasets, which contains ten different samples sequenced at four distinct coverages (5X, 10X, 20X, and 30X). **Real-Potato** is the Chromosome *5* capture-seq data of a small solanum tuberosum population available at NCBI (accession SRR6173308 [1]). Ten samples are generated by randomly selecting ten genomic regions as the reference genome. ii) *Viral Quasispecies*: Three viral quasispecies datasets are downloaded from SAVAGE[2] [Baaijens et al., 2017], including the human immunodeficiency virus (**5-strain HIV**, *k=5*), the hepatitis C virus (**10-strain HCV**, *k=10*), and the zika virus (**15-strain ZIKV**, *k=15*). Ten samples are generated by randomly sampling from each of the these three datasets. In this paper, we use BWA-MEM [Li, 2013] to align reads to the reference genome and use the same tool described in CAECseq and GAEseq [Ke and Vikalo, 2020a,b] to derive the SNP matrix from the above alignment to ensure a fair comparison.

Baseline algorithms. GAEseq [Ke and Vikalo, 2020b] and CAECseq [Ke and Vikalo, 2020a] are two state-of-the-art approaches that work on both haplotype assembly and viral quasispecies reconstruction. We included two additional methods, H-PoP [Xie et al., 2016], AltHap [Hashemi et al., 2018], that specifically work on haplotype assembly for polyploid species. We also included one additional method, TenSQR [Ahn et al., 2018], that specifically works on viral quasispecies reconstruction. Many other specific methods are not included in this study because GAEseq [Ke and Vikalo, 2020b] and CAECseq [Ke and Vikalo, 2020a] have recently demonstrated their superior performance against other baselines in both haplotype assembly and viral quasispecies reconstruction.

Experimental setup. The minimum error correction (MEC) score, given in equation 1, is adopted as the evaluation metric [Lippert et al., 2002a] for both haplotype assembly and viral quasispecies reconstruction. Following the experimental setup in [Ke and Vikalo, 2020a,b], all the algorithms run ten times on each input dataset and the lowest MEC score is reported. The initial number of polyploids k is known: $k = 4$ for both Sim-Potato and Real-Potato, $k = 5$ for 5-strain HIV, $k = 10$ for 10-strain HCV, and $k = 15$ for 15-strain ZIKV. The default settings of `NeurHap` hyperparameter are as follows. The representation dimensions are all empirically set to be 32. The number of iteration t in `NeurHap`-search is set to be 10 as default. The parameter λ chooses 0.01 as the default value. The default values for parameters p and q are 3 and 5, respectively. All codes, data and experimental settings for `NeurHap` model will be released after the double-blind review.

4.1 Performance on Polyploid Species data

Table 1 and 2 shows that `NeurHap` significantly outperforms state-of-the-art baselines, which achieving the lowest MEC scores on both the Sim-Potato and Real-Potato datasets. For Cov-5X of Sim-Potato, the MEC score obtained by `NeurHap` is 29.9 which is about 3x lower than the low-

Table 1: Performance comparison on Sim-Potato data.

Model	#Cov 5X	#Cov 10X	#Cov 20X	#Cov 30X
H-PoP	429.0±64.1	933.9±103.6	1782.2±161.8	2826.9±180.7
AltHap	610.9±259.3	722.3±179.1	649.3±369.4	1148.2±509.9
GAEseq	153.7±20.3	261.6±58.7	372.8±74.5	496.9±128.7
CAECseq	96.2±26.9	141.4±40.7	254.2±99.7	372.9±148.9
NeurHap	**29.9±5.7**	**51.9±8.2**	**92.6±10.6**	**142.0±23.6**

est scores achieved by baselines (96.2 for CAECseq). For Real-Potato, `NeurHap` also achieves the lowest MEC scores on all samples. The average MEC score achieved by `NeurHap` is 371.6 which is significantly lower than the second lowest MEC score obtained by CAECseq, 400. The gap between `NeurHap` and baselines demonstrates the superiority of our model in polyploids haplotype phasing.

4.2 Performance on Viral Quasispecies data

Table 3 shows the results obtained by `NeurHap` and baselines for reconstructing viral quasiqpecies on three datasets respectively, 5-strain HIV, 10-strain HCV, and 15-strain ZIKV. In Table 3, `NeurHap` significantly outperforms baselines on all 10 samples in these datasets. `NeurHap` achieves the lowest MEC score in 5-strain HIV (1371.4), which is about 160 lower than the MEC score obtained by

---

[1]https://www.ncbi.nlm.nih.gov/sra/SRR6173308

[2]https://bitbucket.org/jbaaijens/savage-benchmarks

Table 2: Performance comparison on Real-Potato data.

Sample	#1	#2	#3	#4	#5	#6	#7	#8	#9	#10	Avg.
Reads	240	389	274	115	141	398	295	284	489	449	-
SNPs	294	238	83	23	176	198	456	424	236	410	-
H-PoP	705	525	132	4	240	982	981	766	793	1413	654.1±435.6
AltHap	746	572	192	9	299	1295	1021	982	811	1311	723.8±451.1
GAEseq	231	406	97	2	180	873	558	441	592	712	409.2±266.6
CAECseq	229	393	103	1	172	859	522	430	593	698	400.0±260.9
NeurHap	**178**	**343**	**93**	**1**	**163**	**857**	**499**	**384**	**561**	**632**	**371.6±268.9**

CAECseq (1638.5). For 10-strain HCV data, `NeurHap` also achieves the lowest MEC score 1008.1 and the second lowest MEC score is 1144.3 obtained by TenSQR. With increase in the number of haplotypes (strains), performance of CAECseq and GAEseq deteriorates and while that of `NeurHap` improves. `NeurHap` significantly outperforms CAECseq and GAEseq on polyploid haplotypes.

Table 3: Performance comparison on three viral quasispecies datasets.

Dataset		#1	#2	#3	#4	#5	#6	#7	#8	#9	#10	Avg.
5-strain HIV	Reads	967	961	951	961	966	969	962	965	955	971	-
	SNPs	1617	1685	1595	1605	1615	1660	1619	1622	1580	1653	-
	TenSQR	1920	2324	1867	1896	2055	1793	2125	1754	1679	1757	1917.0±198.6
	GAEseq	1981	1953	1678	1806	1905	2007	1819	1746	1702	1747	1834.4±119.6
	CAECseq	1729	1750	1787	1552	1730	1622	1611	1529	1519	1556	1638.5±101.5
	NeurHap	**1307**	**1525**	**1385**	**1265**	**1410**	**1382**	**1393**	**1323**	**1274**	**1450**	**1371.4±81.2**
10-strain HCV	Reads	500	498	500	499	498	500	499	500	500	500	-
	SNPs	1770	1712	1794	1749	1741	1759	1786	1765	1743	1808	-
	TenSQR	1081	1037	1106	960	1115	1015	1365	1293	1396	1075	1144.3±151.8
	GAEseq	1270	1121	1301	1171	1245	1152	1371	1105	1152	1200	1208.8±85.8
	CAECseq	1490	1616	1347	1675	1475	1405	1563	1413	1436	1554	1497.4±103.1
	NeurHap	**1029**	**990**	**1097**	**956**	**1012**	**899**	**1014**	**1008**	**1079**	**997**	**1008.1±56.3**
15-strain ZIKV	Reads	500	500	500	500	500	499	498	497	499	500	-
	SNPs	2384	2358	2385	2360	2386	2383	2375	2373	2353	2353	-
	TenSQR	941	794	859	869	950	856	848	789	849	758	851.3±61.5
	GAEseq	1470	1585	1515	1590	1713	1363	1523	1348	1618	1393	1511.8±119.4
	CAECseq	2344	2248	2427	2338	2454	2406	2378	2496	2292	2309	2369.2±77.4
	NeurHap	**718**	**655**	**752**	**721**	**862**	**658**	**694**	**622**	**666**	**675**	**702.3±67.8**

4.3 Visualization

To better understand the phasing results, we use python-iGraph package to visualize the read-overlap graph of Sim-Potato-5X dataset with clustering results from `NeurHap`, CAECseq, and GAEseq (see Figure 3). Different colors denote distinct haplotypes (the number of haplotypes for Sim-Potato is 4). Grey edges are conflict edges and blue edges are consistent edges in the read-overlap graph. In Figure 3 b) and c), 89 and 133 conflict edges are violated (i.e., connecting two vertices with the same color) for CAECseq and GAEseq, respectively, while none of the conflicting edges are violated for `NeurHap`. `NeurHap` derives a coloring assignment that is most consistent with the conflict and consistent edges in the read-overlap graph.

Figure 4 shows the search process of `NeurHap` on the Sim-Potato-5X Sample 1 as an example. The sub-figure a) shows the grid layout of the initial coloring of the read-overlap graph violates significant number of conflict edges (in grey) and consistent edges (in blue). With the increasing number of epochs, the number of violating constraints (conflict and consistent edges) decrease significantly.

4.4 Experimental Analysis

a) NeurHap [MEC=27]   **b) CAECseq** [MEC=100]   **c) GAEseq** [MEC=156]

Figure 3: The visualization of `NeurHap`, CAECseq, and GAEseq on Sim-Potato-5X-Sample1 data.

a) epoch=0   **b) epoch=10**   **c) epoch=30**   **d) epoch=70**

Figure 4: The grid layout of read-overlap graph with the violating edges in the training of `NeurHap`.

Ablation study. To study the effectiveness of our proposed model, we conduct an ablation study to examine the two algorithmic components in `NeurHap`, a graph neural network-based algorithm `NeurHap-search` and a local combinatorial optimisation-based refinement algorithm `NeurHap-refine`. Figure 5 shows that `NeurHap-refine` is able to further optimize the MEC score, e.g., the MEC scores for 5-strain HIV by `NeurHap-search` and `NeurHap` are 1453.5 and 1371.4 respectively, demonstrating the complementary effectiveness of global search and local refinement algorithms on phasing haplotypes.

Figure 5: Results of `NeurHap-search` and `NeurHap` (`NeurHap-search` + `NeurHap-refine`) on all five datasets.

Parameter analysis & Running time. We investigate the importance of core parameters in model, including p and q for read-overlap graph, λ for consistent constraints, t for iterations, and d for feature dimension. The detailed parameters analysis is listed in the Appendix A.3. We benchmark the running time of `NeurHap` against two deep learning baselines CAECseq and GAEseq on the Sim-Potato-Cov30 data. `NeurHap` achieves the lowest MEC score (142.0) compared with CAECseq (372.9) and GAEseq (496.9). The running time of `NeurHap` is 387 seconds which is comparable to the fastest CAECseq (341 seconds). GAEseq is the slowest among the three and takes 492 seconds.

5 Conclusion

In this paper, we propose `NeurHap`, a graph representation learning approach to reconstruct haplotypes of polyploid species and viral quasispecies. We give a novel formulation of the haplotype phasing problem as a graph coloring problem. We design a message-passing based graph neural network search framework over a carefully constructed graph to assign colors (indicating haplotypes) to the reads, and a local refinement step to adjust colors to optimize MEC scores. Extensive experiments on both simulated and real-world datasets demonstrate the effectiveness of our proposed `NeurHap` model on phasing haplotypes from polyploid species and viral quasispecies. A limitation of our method is in its ability to handle long reads. Massive long reads in polyploids leads to an even larger search space that may be addressed by extensions to our approach in future work.

References

Omar Abou Saada, Anne Friedrich, and Joseph Schacherer. Towards accurate, contiguous and complete alignment-based polyploid phasing algorithms. *Genomics*, 114(3):110369, 2022.

D. Aguiar and Sorin Istrail. Hapcompass: A fast cycle basis algorithm for accurate haplotype assembly of sequence data. *Journal of computational biology*, 19 6:577–90, 2012.

Soyeon Ahn and Haris Vikalo. abayesqr: A bayesian method for reconstruction of viral populations characterized by low diversity. *Journal of computational biology*, 25:637–648, 2018.

Soyeon Ahn, Ziqi Ke, and Haris Vikalo. Viral quasispecies reconstruction via tensor factorization with successive read removal. *Bioinformatics*, 34:i23 – i31, 2018.

Irina Astrovskaya, Bassam Tork, Serghei Mangul, Kelly Westbrooks, Ion I. Măndoiu, Peter Balfe, and Alex Zelikovsky. Inferring viral quasispecies spectra from 454 pyrosequencing reads. *BMC Bioinformatics*, 12:S1 – S1, 2011.

Jasmijn A. Baaijens, Amal Zine El Aabidine, Eric Rivals, and Alexander Schönhuth. De novo assembly of viral quasispecies using overlap graphs. *Genome research*, 27 5:835–848, 2017.

Vikas Kumar Bansal and Vineet Bafna. Hapcut: an efficient and accurate algorithm for the haplotype assembly problem. *Bioinformatics*, 24 16:i153–9, 2008.

Vikas Kumar Bansal, Aaron L. Halpern, Nelson Axelrod, and Vineet Bafna. An mcmc algorithm for haplotype assembly from whole-genome sequence data. *Genome research*, 18 8:1336–46, 2008.

Sharon R Browning and Brian L Browning. Haplotype phasing: existing methods and new developments. *Nature Reviews Genetics*, 12(10):703–714, 2011.

HongYun Cai, Vincent W. Zheng, and Kevin Chen-Chuan Chang. A comprehensive survey of graph embedding: Problems, techniques, and applications. *TKDE*, 30:1616–1637, 2018.

Peng Cui, Xiao Wang, Jian Pei, and Wenwu Zhu. A survey on network embedding. *TKDE*, 31: 833–852, 2019.

Shreepriya Das and Haris Vikalo. Sdhap: haplotype assembly for diploids and polyploids via semi-definite programming. *BMC Genomics*, 16, 2015.

Jorge Duitama, Gayle K McEwen, Thomas Huebsch, Stefanie Palczewski, Sabrina Schulz, Kevin J. Verstrepen, Eun-Kyung Suk, and Margret R. Hoehe. Fosmid-based whole genome haplotyping of a hapmap trio child: evaluation of single individual haplotyping techniques. *Nucleic Acids Research*, 40:2041 – 2053, 2012.

Peter Edge, Vineet Bafna, and Vikas Kumar Bansal. Hapcut2: robust and accurate haplotype assembly for diverse sequencing technologies. *Genome research*, 27 5:801–812, 2017.

Justin Gilmer, Samuel S. Schoenholz, Patrick F. Riley, Oriol Vinyals, and George E. Dahl. Neural message passing for quantum chemistry. In *ICML*, 2017.

William L. Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. In *NeurIPS*, 2017.

Abolfazl Hashemi, Banghua Zhu, and Haris Vikalo. Sparse tensor decomposition for haplotype assembly of diploids and polyploids. *BMC Genomics*, 19(191), 2018.

Kim Philipp Jablonski and Niko Beerenwinkel. Computational methods for viral quasispecies assembly. In *Virus Bioinformatics*, pages 51–64. Chapman and Hall/CRC, 2021.

Ziqi Ke and Haris Vikalo. A convolutional auto-encoder for haplotype assembly and viral quasispecies reconstruction. In *NeurIPS*, 2020a.

Ziqi Ke and Haris Vikalo. A graph auto-encoder for haplotype assembly and viral quasispecies reconstruction. In *AAAI*, 2020b.

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *ICLR*, 2017.

Volodymyr Kuleshov. Probabilistic single-individual haplotyping. *Bioinformatics*, 30:i379 – i385, 2014.

Henrique Lemos, Marcelo O. R. Prates, Pedro H. C. Avelar, and L. Lamb. Graph colouring meets deep learning: Effective graph neural network models for combinatorial problems. *2019 IEEE 31st International Conference on Tools with Artificial Intelligence (ICTAI)*, pages 879–885, 2019.

Heng Li. Aligning sequence reads, clone sequences and assembly contigs with bwa-mem. *arXiv: Genomics*, 2013.

Ross Lippert, Russell Schwartz, Giuseppe Lancia, and Sorin Istrail. Algorithmic strategies for the single nucleotide polymorphism haplotype assembly problem. *Briefings in bioinformatics*, 3(1): 23—31, 2002a.

Ross Lippert, Russell Schwartz, Giuseppe Lancia, and Sorin Istrail. Algorithmic strategies for the single nucleotide polymorphism haplotype assembly problem. *Briefings in bioinformatics*, 3(1): 23–31, 2002b.

Panos M Pardalos, Thelma Mavridou, and Jue Xue. The graph coloring problem: A bibliographic survey. In *Handbook of combinatorial optimization*, pages 1077–1141. Springer, 1998.

Sandhya Prabhakaran, Mélanie Rey, Osvaldo Zagordi, Niko Beerenwinkel, and Volker Roth. Hiv haplotype inference using a propagating dirichlet process mixture model. *IEEE/ACM Transactions on Computational Biology and Bioinformatics*, 11:182–191, 2014.

Mattia C. F. Prosperi and Marco Salemi. Qure: software for viral quasispecies reconstruction from next-generation sequencing data. *Bioinformatics*, 28 1:132–3, 2012.

Martin J. A. Schuetz, J. Kyle Brubaker, and Helmut G. Katzgraber. Combinatorial optimization with physics-inspired graph neural networks. *ArXiv*, abs/2107.01188, 2022.

Russell Schwartz. Theory and algorithms for the haplotype assembly problem. *Communications in Information and Systems*, 10(1):23–38, 2010.

Jan Toenshoff, Martin Ritzert, Hinrikus Wolf, and Martin Grohe. Run-csp: Unsupervised learning of message passing networks for binary constraint satisfaction problems. *ArXiv*, abs/1909.08387, 2019.

Armin Töpfer, Osvaldo Zagordi, Sandhya Prabhakaran, Volker Roth, Eran Halperin, and Niko Beerenwinkel. Probabilistic inference of viral quasispecies subject to recombination. *Journal of computational biology : a journal of computational molecular cell biology*, 20 2:113–23, 2013.

Yves Van de Peer, Eshchar Mizrachi, and Kathleen Marchal. The evolutionary significance of polyploidy. *Nature Reviews Genetics*, 18(7):411–424, 2017.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph Attention Networks. In *ICLR*, 2018.

Rui-Sheng Wang, Ling-Yun Wu, Zhen-Ping Li, and Xiang-Sun Zhang. Haplotype reconstruction from snp fragments by minimum error correction. *Bioinformatics*, 21 10:2456–62, 2005.

Minzhu Xie, Qiong Wu, Jianxin Wang, and Tao Jiang. H-PoP and H-PoPG: heuristic partitioning algorithms for single individual haplotyping of polyploids. *Bioinformatics*, 32(24):3735–3744, 2016.

Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? In *ICLR*, 2019.

Osvaldo Zagordi, Arnab Bhattacharya, Nicholas Eriksson, and Niko Beerenwinkel. Shorah: estimating the genetic diversity of a mixed sample from next-generation sequencing data. *BMC Bioinformatics*, 12:119 – 119, 2011.

Xiang-Sun Zhang, Rui-Sheng Wang, Ling-Yun Wu, and Wei Zhang. Minimum conflict individual haplotyping from snp fragments and related genotype. *Evolutionary Bioinformatics*, 2: 117693430600200032, 2006.

Xingtan Zhang, Ruoxi Wu, Yibin Wang, Jiaxin Yu, and Haibao Tang. Unzipping haplotypes in diploid and polyploid genomes. *Computational and structural biotechnology journal*, 18:66–72, 2020.