Is Adversarial Training Really a Silver Bullet for Mitigating Data Poisoning?

Abstract

Indiscriminate data poisoning can decrease the clean test accuracy of a deep learning model by slightly perturbing its training samples. There is a consensus that such poisons can hardly harm adversarially-trained (AT) models when the adversarial training budget is no less than the poison budget, i.e., $\epsilon_{\mathrm{adv}} \geq \epsilon_{\mathrm{poi}}$. This consensus, however, is challenged in this paper based on our new attack strategy that induces *indiscriminative features* (INF). The existence of indiscriminative features makes the poisoned data become less useful for training a model, no matter if AT is applied or not. In contrast, existing methods are limited to using perturbations as *shortcuts*, which just override the actual image content during model training. We demonstrate that for attacking a CIFAR-10 AT model under a reasonable setting with $\epsilon_{\mathrm{adv}} = \epsilon_{\mathrm{poi}} = 8/255$, our INF yields an accuracy drop of 13.31%, which is $7\times$ better than existing methods and equal to discarding 83% training data. We further show the generalizability of INF to more challenging settings, e.g., higher AT budgets, partial poisoning, unseen model architectures, and stronger (ensemble or adaptive) defenses. We finally provide new insights into the distinct roles of non-robust vs. robust features in poisoning standard vs. AT models and confirm the effectiveness of INF in poisoning standard models.

1 Introduction

Indiscriminate data poisoning aims to degrade the overall prediction performance of a machine learning model at test time by manipulating its training data. It has been increasingly important to understand indiscriminate data poisoning as web scraping becomes a common approach to obtaining large-scale data for training advanced models (Brown et al., 2020; Dosovitskiy et al., 2021). Although slightly perturbing training samples has been shown to effectively poison deep learning models, there is a consensus that such poisons can hardly harm an adversarially-trained model when the perturbation budget in adversarial training, ϵ_{adv}, is no less than the poison budget, ϵ_{poi}, i.e., $\epsilon_{\mathrm{adv}} \geq \epsilon_{\mathrm{poi}}$ (Fowl et al., 2021a;b; Huang et al., 2021; Tao et al., 2021; Wang et al., 2021; Fu et al., 2022; Tao et al., 2022). In particular, Tao et al. (2021) have proved that in this setting, adversarial training can serve as a principled defense against existing poisoning methods.

However, in this paper, we challenge this consensus by rethinking data poisoning from a fundamentally new perspective. Specifically, we introduce a new poisoning approach that can substantially degrade adversarially-trained models by making the features of training samples from different classes become indiscriminative. In this way, the indiscriminative samples would hardly contribute to training the target (discriminative) model anymore no matter whether adversarial training is applied or not. Different from our attack strategy, existing methods commonly inject perturbations as shortcuts, which ensures that the model wrongly learns the shortcuts rather than the actual image content, leading to low test accuracy (Segura et al., 2022a; Evtimov et al., 2021; Yu et al., 2022).

Figure 1 illustrates the working mechanism of our new poisoning approach, with a comparison to a reverse operation that instead aims to eliminate indiscriminative features. Our new approach is also inspired by the conventional, noisy label-based poisoning approach (Biggio et al., 2012; 2011; Muñoz-González et al., 2017), where *indiscriminative labels* are introduced by directly flipping labels (e.g., assigning a "dog" (or "cat") label to both the "dog" and "cat" images) under a strong assumption that the labeling process of the target model can be manipulated. However, due to the imperceptibility constraint in the common clean-label setting, we instead propose to introduce

(a) Test Acc: 84.88%   (b) Test Acc: **72.99%** ↓   (c) Test Acc: **71.57%** ↓   (d) Test Acc: 88.72% ↑

Figure 1: The t-SNE visualizations of the feature representations for (a) clean CIFAR-10 vs. poisoned CIFAR-10 achieved by our (b) INF-pull and (c) INF-push, which aim to induce indiscriminative features. As a comparison, (d) uses a reverse objective of INF-push and instead increases the model accuracy. All representations are obtained from the same reference model. Different from our INF, existing methods lead to discriminative/well-separable features (see Appendix A).

indiscriminative features represented in the latent space. Our work mainly makes the following three contributions:

- We demonstrate that, contrary to the consensus view, indiscriminate data poisoning *can* actually decrease the clean test accuracy of adversarially-trained models to a substantial extent. Specifically, we propose INF, a new poisoning approach that is based on inducing indiscriminative features in the latent space of a pre-trained reference model.
- We conduct extensive experiments to demonstrate the effectiveness of INF against adversarial training the reasonable setting with $\epsilon_{\mathrm{adv}} = \epsilon_{\mathrm{poi}}$ and also its generalizability to a variety of more challenging settings, such as adversarial training with higher budgets, partial poisoning, unseen model architectures, and stronger (ensemble or adaptive) defenses.
- We further present a feature-based understanding of poisoning by analyzing the usefulness of non-robust vs. robust features in compromising standard vs. adversarially-trained models and also confirm the effectiveness of INF in the context of standard training.

2   RELATED WORK

Data poisoning. Data poisoning aims to compromise a model's performance at test time by manipulating its training data. Related work on poisoning DNNs has mainly investigated targeted, backdoor, and indiscriminate poisoning. Different from backdoor (Gu et al., 2017; Liu et al., 2018; Salem et al., 2022) and targeted poisoning (Muñoz-González et al., 2017; Shafahi et al., 2018; Geiping et al., 2021), which aim to degrade the model on specific (targeted) test samples, indiscriminate poisoning aims at arbitrary clean test samples. Traditional indiscriminate poisoning is based on injecting noisy labels (Biggio et al., 2012; 2011; Muñoz-González et al., 2017); however, they can be easily detected (Shafahi et al., 2018; Song et al., 2020). Recent methods instead pursue "clean-label" poisons by adding imperceptible perturbations. These methods mainly use the error-minimization (Huang et al., 2021; Tao et al., 2021; Fu et al., 2022) or error-maximization loss (Fowl et al., 2021b), with a pre-trained (Fowl et al., 2021b; Wang et al., 2021; Tao et al., 2021) or trained-from-scratch (Huang et al., 2021; Fu et al., 2022) reference model. However, these methods are known to be vulnerable to adversarial training (AT). Although two concurrent methods, ADVIN (Wang et al., 2021) and REM (Fu et al., 2022), also attempt to poison AT models, they are no longer effective under the reasonable setting with $\epsilon_{\mathrm{poi}} \leq \epsilon_{\mathrm{adv}}$ considered in our work (see results in Table 1). Generating poisons using a feature-space loss has also been explored (Shafahi et al., 2018; Zhu et al., 2019; Geiping et al., 2021), but without considering AT and in the field of targeted poisoning.

Adversarial training. Adversarial training (AT) was recognized as the only promising solution so far to provide robustness against (test-time) adversarial examples (Athalye et al., 2018; Tramèr et al., 2020). It was also recently proved to be a principled defense against indiscriminate poisoning (Tao et al., 2021). The general idea of AT is to simply augment training data with adversarial examples generated in each training step. The single-step approach, FGSM, was initially used by the seminal work of Goodfellow et al. (2015) but has been found to be ineffective against multi-step attacks (Tramèr et al., 2017; Kurakin et al., 2017). To address this limitation, Madry et al. (2018) have proposed the PGD-based AT, which uses the multi-step optimization to further enhance the robustness. Other state-of-the-art methods have been focused on improving this PGD-based AT by,

for example, training on both clean and adversarial examples (Zhang et al., 2019), incorporating an explicit differentiation of misclassified examples (Wang et al., 2020), identifying a bag of training tricks (Pang et al., 2021), or accelerating the training process via gradient recycling (Shafahi et al., 2019). In this paper, we consider three different state-of-the-art AT techniques that adopt the standard PGD and also varied adversarial training budget ϵ_{adv}.

3   INDISCRIMINATIVE FEATURES (INF) FOR POISONING AT MODELS

3.1   PROBLEM STATEMENT

We formulate the problem in the context of image classification DNNs. There are two parties involved, the *poisoner* and the *victim*. The poisoner has full access to the clean training dataset $\mathcal{D}_c = \{(\boldsymbol{x}_i, y_i)\}_{i=1}^n$ and is able to add perturbations $\boldsymbol{\delta}^{\mathrm{poi}}$ to each sample and release the poisoned version $\mathcal{D}_p = \{(\boldsymbol{x}_i', y_i)\}_{i=1}^n$, where $\boldsymbol{x}_i' = \boldsymbol{x}_i + \boldsymbol{\delta}_i^{\mathrm{poi}}$. Once the poisoned dataset is generated and released, the poisoner cannot further modify the dataset. Moreover, the poisoner has no control over the target model's training process and the labeling function of the victim. The victim only has access to the poisoned dataset and aims to train a well-generalized model using this dataset. As the victim is aware that the obtained dataset may be poisoned, they decide to deploy adversarial training to secure their model. **The goal of the poisoner is to decrease the clean test accuracy of the adversarially-trained model by poisoning its training dataset.**

When perturbing the clean dataset, the poisoner wants to ensure that the perturbation is imperceptible and can escape any detection from the victim. To this end, the poisoner constrains the generated perturbations $\boldsymbol{\delta}^{\mathrm{poi}}$ by a certain *poison budget* ϵ_{poi}, i.e., $\|\boldsymbol{\delta}^{\mathrm{poi}}\|_\infty \le \epsilon_{\mathrm{poi}}$. Take the widely-adopted adversarial training framework (Madry et al., 2018) as an example, the victim trains a target model F on the poisoned dataset $\mathcal{D}_p$ by a certain *adversarial training budget* ϵ_{adv} following the objective:

$$\arg\min_\theta \; \mathbb{E}_{(\boldsymbol{x}',y)\sim\mathcal{D}_p}\left[\max_{\boldsymbol{\delta}^{\mathrm{adv}}} \mathcal{L}(F(\boldsymbol{x}' + \boldsymbol{\delta}^{\mathrm{adv}}), y)\right] \;\; \text{s.t.} \;\; \|\boldsymbol{\delta}^{\mathrm{adv}}\|_\infty \le \epsilon_{\mathrm{adv}}, \tag{1}$$

where $\boldsymbol{x}'$ denotes the poisoned input, $\boldsymbol{\delta}^{\mathrm{adv}}$ denotes the adversarial perturbations, θ denotes the model parameters, and $\mathcal{L}$ is the classification loss (e.g., the commonly used cross-entropy loss).

In this paper, we focus on the reasonable setting with $\epsilon_{\mathrm{poi}} \le \epsilon_{\mathrm{adv}}$. In contrast, the two concurrent studies, ADVIN (Wang et al., 2021) and REM (Fu et al., 2022), focus on much easier settings with $\epsilon_{\mathrm{poi}} \ge 2\epsilon_{\mathrm{adv}}$, in which it is not surprising that AT would fail because the clean samples are already out of the ϵ_{adv}-ball of the poisoned samples (Tao et al., 2021).

3.2   METHODOLOGY

In this section, we introduce INF, our new poisoning approach to compromising adversarial training. The key intuition of INF is to cause samples from different classes to share indiscriminative features, which then become not useful for discriminative model training, including adversarial training. Specifically, we propose two different variants of INF, namely INF-push and INF-pull. For INF-push, all training samples in each of the original classes y are pushed away from the corresponding class centroid $\boldsymbol{\mu}_y$ in the latent feature space (i.e., output of the penultimate layer F_{L-1}^*) of a reference model F^*, which has totally L layers. The objective function can be formulated as:

$$\mathcal{L}_{\mathrm{push}} = \max_{\boldsymbol{\delta}^{\mathrm{poi}}} \|F_{L-1}^*(\boldsymbol{x} + \boldsymbol{\delta}^{\mathrm{poi}}) - \boldsymbol{\mu}_y\|_2 \;\; \text{s.t.} \;\; \|\boldsymbol{\delta}^{\mathrm{poi}}\|_\infty \le \epsilon_{\mathrm{poi}}. \tag{2}$$

For INF-pull, each training sample is pulled towards the centroid of its nearest class y':

$$\mathcal{L}_{\mathrm{pull}} = \min_{\boldsymbol{\delta}^{\mathrm{poi}}} \|F_{L-1}^*(\boldsymbol{x} + \boldsymbol{\delta}^{\mathrm{poi}}) - \boldsymbol{\mu}_{y'}\|_2 \;\; \text{s.t.} \;\; \|\boldsymbol{\delta}^{\mathrm{poi}}\|_\infty \le \epsilon_{\mathrm{poi}}. \tag{3}$$

The above class centroid is computed as the average features of all clean samples $\mathcal{X}$ in that class:

$$\boldsymbol{\mu} = \frac{1}{|\mathcal{X}|} \sum_{\boldsymbol{x}\in\mathcal{X}} F_{L-1}^*(\boldsymbol{x}). \tag{4}$$

We find this simple, average-based method works well in our case, and we leave the exploration of other, metric learning methods (Kaya and Bilge, 2019) to future work.

In order to learn a similar representation space to that of an AT target model, the reference model F^* is also adversarially trained (on the clean dataset) with a certain perturbation budget ϵ_{ref}. We provide more general discussions about the impact of ϵ_{ref} on the poisoning performance in Section 5. Following the common practice, we adopt the Projected Gradient Descent (PGD) (Madry et al., 2018) to solve the above poison optimization.

Why adversarial training can be compromised. Tao et al. (2021) have proved that adversarial training can serve as a principled defense against data poisoning based on the following theorem.

Theorem 1 *Given a classifier $f : \mathcal{X} \to \mathcal{Y}$, for any data distribution $\mathcal{D}$ and any perturbed distribution $\hat{\mathcal{D}}$ such that $\hat{\mathcal{D}} \in \mathcal{B}_{W_\infty}(\mathcal{D}, \epsilon)$, we have*

$$\mathcal{R}_{\text{nat}}(f, \mathcal{D}) \leq \max_{\mathcal{D}' \in \mathcal{B}_{W_\infty}(\hat{\mathcal{D}}, \epsilon)} \mathcal{R}_{\text{nat}}(f, \mathcal{D}') = \mathcal{R}_{\text{adv}}(f, \hat{\mathcal{D}}).$$

Theorem 1 guarantees that adversarial training on the poisoned data distribution $\hat{\mathcal{D}}$ optimizes an upper bound of natural risk on the original data distribution $\mathcal{D}$ if $\hat{\mathcal{D}}$ is within the ∞-Wasserstein ball of $\mathcal{D}$ (Tao et al., 2021). That is to say, achieving a low natural risk on $\mathcal{D}$ (i.e., high clean test accuracy) requires a low adversarial risk on $\hat{\mathcal{D}}$. This guarantee is based on an *implicit* assumption that adversarial training is capable of minimizing the adversarial risk on the poisoned data distribution $\hat{\mathcal{D}}$, which holds for existing attacks as they follow the shortcut-based attack strategy. However, for our INF, the poisoned data that share indiscriminative features become not useful even for adversarial training, and as a result, the assumption required for the proof is broken.

Important note on the cross-entropy loss. The key novelty of our INF over existing methods lies in not only the attack strategy (indiscriminative features vs. shortcuts) but also the specific loss (feature-level vs. output-level). Existing methods on poisoning standard models have commonly adopted the cross-entropy (CE) loss and concluded that the targeted optimization, either with an incorrect (Fowl et al., 2021b; Tao et al., 2021; Wang et al., 2021) or original (Huang et al., 2021) class as the target, is generally stronger than the untargeted CE. This conclusion somewhat leads to the fact that the two concurrent studies on poisoning AT models (i.e., ADVIN (Wang et al., 2021) and REM (Fu et al., 2022)) have completely ignored the untargeted CE as their baseline.

However, we find that the above conclusion does not hold for poisoning AT models. Specifically, we notice that the untargeted CE can also lead to indiscriminate features to some extent and as a result yield a substantial accuracy drop (12.02%), while its targeted counterpart (i.e, ADVIN (Wang et al., 2021) shown in our Table 1) completely fails. Note that the untargeted CE still performs worse than our INF-push, especially in the more complex tasks, i.e., CIFAR-100 and TinyImageNet (see Appendix B for details). This indicates that using the CE loss is not an ultimate solution in practice.

4 EXPERIMENTS

In this section, we first compare our INF to existing attacks under the basic setting and then validate its generalizability to more challenging settings. All experiments are performed on an NVIDIA DGX-A100 server. Our anonymous code can be found at `https://anonymous.4open.science/r/INF-C277`.

4.1 EXPERIMENTAL SETTINGS

We use three image classification benchmark datasets: CIFAR-10 (CIF), CIFAR-100 (CIF), and TinyImageNet (Tin). These datasets have been commonly used in the poisoning literature. We adopt the perturbation budget $\epsilon_{\text{ref}} = 4/255$ for adversarially training the reference model and find that other values also work well (see results in Section 5). PGD-300 with a step size of $0.4/255$ and differentiable data augmentation (Fowl et al., 2021b) is used for poison optimization. If not explicitly mentioned, we focus on the reasonable setting with $\epsilon_{\text{poi}} = \epsilon_{\text{adv}} = 8/255$ and adopt ResNet-18 for both the reference and target models. Additional experimental settings can be found in Appendix C.

Table 1: Comparison of different poisoning methods against adversarial training.

POISON METHOD	CLEAN TEST ACCURACY (%, ↓)
NONE (CLEAN)	84.88
HYPOCRITICAL[+] (TAO ET AL., 2022)	86.56
HYPOCRITICAL (TAO ET AL., 2021)	84.96
UNLEARNABLE (HUANG ET AL., 2021)	84.91
ADVPOISON (FOWL ET AL., 2021B)	83.11
ADVIN (WANG ET AL., 2021)	86.76
REM (FU ET AL., 2022)	84.21
INF-PULL (OURS)	72.99
INF-PUSH (OURS)	**71.57**

4.2 INF COMPARED TO EXISTING ATTACKS UNDER $\epsilon_{\text{adv}} = \epsilon_{\text{poi}}$

We first evaluate the performance of different state-of-the-art poisoning methods against adversarial training in the basic setting with $\epsilon_{\text{poi}} = \epsilon_{\text{adv}}$ on CIFAR-10. As can be seen from Table 1, all existing methods can hardly decrease the model accuracy. Specifically, although ADVIN (Wang et al., 2021) and REM (Fu et al., 2022) have claimed effectiveness in the unreasonable settings with $\epsilon_{\text{poi}} \geq 2\epsilon_{\text{adv}}$, they fail in our reasonable setting. In some cases, the poisons may even slightly increase the model accuracy, which is also noticed in the concurrent work (Tao et al., 2022).

In contrast to existing methods, both our INF-push and INF-pull can substantially decrease the model accuracy. Note that decreasing the model accuracy to 71.57% is dramatic because it equals to the performance achieved by directly discarding 83% of the original training data (see more relevant discussions in Section 4.5). In addition, INF-push and INF-pull achieve similar results but obviously, INF-pull is less efficient because it needs to calculate and then rank the distance between each sample and class centroid. Moreover, the class selection strategy in INF-pull may have an impact on the final performance (see more analysis in Section 6). For these reasons, if not specifically mentioned, we choose to use INF-push in the following experiments.

Table 2: Evaluating INF on different datasets.

POISON METHOD \ DATASET	CIFAR-10	CIFAR-100	TINYIMAGENET
NONE (CLEAN)	84.88	59.50	51.95
INF (OURS)	71.57	47.29	41.32

(a) Madry (Madry et al., 2018)   (b) TRADES (Zhang et al., 2019)   (c) MART (Wang et al., 2020)

Figure 2: Evaluating INF against three different well-known adversarial training frameworks.

4.3 INF FOR LARGER DATASETS AND OTHER AT FRAMEWORKS

The results shown in Table 2 further validate the general effectiveness of our INF on larger datasets, where the model accuracy consistently drops by more than 10%. We also evaluate INF against different widely-used AT frameworks. Figure 2 shows the learning curves of the poisoned AT target model that is trained with Madry (Madry et al., 2018), TRADES (Zhang et al., 2019), or

MART (Wang et al., 2020). As can be seen, our INF largely decreases the clean test accuracy in all cases. We can also observe that all the three frameworks exhibit a relatively steady learning process, i.e., the model accuracy monotonically increases over epochs, and finally reaches an accuracy that is still lower than that of the model trained on clean data. This pattern is different from that in poisoning standard models, where the model accuracy is found to increase at a few early epochs, and then start to decrease dramatically to the final low accuracy (Huang et al., 2021; Liu et al., 2021; Segura et al., 2022a). This fundamental difference indicates that early stopping cannot be used as an effective defense against poisoning for AT models.

Table 3: Evaluating INF under different ϵ_{poi} vs. ϵ_{adv}.

POISON BUDGET \ ADVTRAIN BUDGET	$\epsilon_{\mathrm{adv}} = 4/255$	$\epsilon_{\mathrm{adv}} = 8/255$	$\epsilon_{\mathrm{adv}} = 16/255$
NONE (CLEAN)	90.31	84.88	73.78
$\epsilon_{\mathrm{poi}} = 4/255$	84.37	79.25	69.35
$\epsilon_{\mathrm{poi}} = 8/255$	75.39	71.57	63.73
$\epsilon_{\mathrm{poi}} = 16/255$	50.27	60.29	53.03

4.4 INF UNDER HIGHER AT BUDGETS

We further test INF under higher adversarial training budgets and also consider different poison budgets. As can be seen from Table 3, even with an overwhelming budget, adversarial training can still be largely degraded by our INF. For example, when the AT budget is $\epsilon_{\mathrm{adv}} = 16/255$, which is $2\times$ larger than the poison budget $\epsilon_{\mathrm{poi}} = 8/255$, our INF still yields a substantial accuracy drop of 10.05%. In addition, under the same setting with $\epsilon_{\mathrm{adv}} = \epsilon_{\mathrm{poi}}$, a larger poison budget leads to a better poison performance. Specifically, for $\epsilon_{\mathrm{adv}} = \epsilon_{\mathrm{poi}} = 4/255$, model accuracy drops by 5.94% (90.31% → 84.37%), while for a larger poison budget, $8/255$ and $16/255$, the accuracy drops by 13.31% (84.88% → 71.57%) and 20.75% (73.78% → 53.03%), respectively.

Table 4: Effects of adjusting the poison proportion. "None (Clean)" shows the baseline results where the rest clean data is used without poisoning.

POISON METHOD \ POISON PROPORTION	0.2	0.4	0.6	0.8
NONE (CLEAN)	83.66	81.82	79.16	73.23
CLEAN+INF	81.41	78.67	75.84	73.56
CLEAN+INF (WORSE CASE)	81.84	78.83	75.92	74.01

Poison Proportion: 0.2   Poison Proportion: 0.4   Poison Proportion: 0.6   Poison Proportion: 0.8

Figure 3: The t-SNE visualizations for different poison proportions.

4.5 INF UNDER PARTIAL POISONING

We also examine INF in a more challenging scenario where only partial training data are allowed to be poisoned. We consider two different poisoning settings where different data are used for calculating the class centroids. Specifically, the first setting is based on the whole original (clean) dataset but the second, worse-case one is based on only the partial clean data that are allowed to be poisoned. As can be seen from Table 4, our INF is still effective in this challenging scenario. In comparison, other attacks can hardly decrease the model accuracy even when the whole dataset is poisoned (see Table 1). In particular, INF decreases the model accuracy from 84.88% to 81.41% by only poisoning 0.2 of the training data, and this result is also lower than the baseline that is achieved by directly discarding these poisoned data (83.66%).

We can also observe that the two different poisoning settings yield very similar results. This indicates that the calculation of class centroids in our INF is not sensitive to the amount of data, and as a result, its efficiency can be potentially improved by using less data for the centroid calculation. The fact that poisoning more data yields better performance can also be explained by Figure 3 where a larger poison proportion leads to a larger number of indiscriminative features.

Table 5: Transferability of INF poisons from ResNet-18 to other model architectures.

POISON METHOD \ TARGET	RESNET-18	RESNET-34	VGG-19	DENSENET-121	MOBILENETV2
NONE (CLEAN)	84.88	86.58	75.99	87.22	80.11
INF	71.57	73.05	64.66	74.35	67.21

4.6 Transferability of INF to unseen model architectures

The latent feature space that is used for generating poisons is specific to a certain reference model. For this reason, one natural question to ask is whether the poisons generated on one model architecture are still effective when the target model adopts a different architecture. Table 5 demonstrates that the poisoning effects of our INF optimized against a ResNet-18 reference model can transfer to other target model architectures. Specifically, for the four different (unseen) architectures, the generated poisons are able to degrade the model accuracy to almost the same extent, indicating that strong generalizability of our INF.

Table 6: Evaluating INF against defenses that apply both data augmentations and AT.

DEFENSE	CLEAN TEST ACCURACY (%)
NONE (CLEAN)	84.88
ADVERSARIAL TRAINING	71.57
+RANDOM NOISE	71.88
+JPEG COMPRESSION	70.40
+MIXUP (ZHANG ET AL., 2018)	71.84
+CUTOUT (DEVRIES AND TAYLOR, 2017)	69.81
+CUTMIX (YUN ET AL., 2019)	68.85
+GRAYSCALE (LIU ET AL., 2021)	68.67

4.7 INF against other defenses

Ensemble defenses with data augmentations. Applying additional data augmentations before stndard training has been shown to be able to mitigate the effects of perturbation-based poisons (Huang et al., 2021; Fowl et al., 2021b; Liu et al., 2021; Tao et al., 2021). Here we study if data augmentations can complement adversarial training when facing our INF. Following previous work, we test a diverse set of data augmentations, including random noise (with the same magnitude as our poisons), and three more advanced techniques, Mixup (Zhang et al., 2018), Cutmix (Yun et al., 2019), and Cutout (Devries and Taylor, 2017). We also test a recent technique that is based on gray-scale pre-filtering (Liu et al., 2021) and has shown effective performance in mitigating the unlearnable examples (Huang et al., 2021). Note that this technique is also applied to the test samples. As can be seen from Table 6, all the data augmentation methods fail to help AT to mitigate our INF but even often lead to slightly worse results.

Adaptive defenses by filtering out indiscriminative samples. In addition to the above existing defense methods, we also consider stronger, adaptive defenses that the victim may design based on a certain level of knowledge about our INF. It is worth noting that, in realistic scenarios, the victim can only leverage a poisoned model, and so it also has no access to a clean AT reference model, which is available to the poisoner, including our INF. This is reasonable because if it is indeed feasible for the victim to get a clean AT (reference) model, there is no need for dealing with the poisoned data in the first place, and that clean AT model can already be used as an effective target model.

When the victim knows that indiscriminative features have been introduced by INF, they would filter out the "overlapped samples", which are located close in the feature space but from different classes.

We test by removing different proportions of such "overlapped samples" and find that the best setting can only recover the accuracy from 71.57% to 72.43%. We go a step further by considering a stronger victim who even knows the specific algorithm of INF-push (i.e., Equation 2). In this case, the victim would recover the data by pulling the poisoned samples back towards their original class centroids. We find that this defense is stronger than the above but still can only recover the accuracy to 75.32% (about 10% lower than the clean AT accuracy).

Adaptive defenses through feature perturbation-based AT. We further test a new defense that uses Eq. 2 for for generating the adversarial examples in AT instead of the common, cross-entropy loss. When trained on clean data, this new AT variant yields an accuracy of 86.84%, similar to that achieved by the conventional AT. However, when trained on our poisoned data, the model accuracy still substantially drops to 72.99%, indicating that it is not a satisfying defense. This defense is even worse than the above one that is based on a pre-trained AT model (72.99% vs. 75.32%). This might be because the class centroids calculated when the model is not well trained (in the early AT training stage) cannot provide meaningful guidance compared to those based on the pre-trained model. As a sanity check, we also try another AT variant that uses a reverse loss of Eq. 2 and find that as expected, it causes the model accuracy to drop a lot (to 47.26%).

Figure 4: Impact of the robustness of the reference model on poisoning standard (ST, $\epsilon_{\text{ref}} = 0$) vs. adversarially-trained (AT) target model. (a) Clean test accuracy for both ST and AT; (b) Perturbation visualizations for different $\epsilon_{\text{ref}} = 0$. More visualizations can be found in Appendix E.

5 ROBUST VS. NON-ROBUST POISONS

All our experiments have so far been focused on poisoning AT models. However, it is also valuable to study the problem in the context of standard training and figure out the difference. To this end, we analyze the poisons against a standard (ST) model vs. an AT model. Specifically, we adjust the perturbation budget ϵ_{ref} for adversarially training the reference model and analyze the poisons in terms of both the poisoning strength and the visual characteristics of perturbations.

As can be seen from Figure 4a, for poisoning the AT model, the poisoning strength is gradually improved as the reference model becomes more robust (i.e., ϵ_{ref} is increased). In contrast, for poisoning the ST model, the poisoning is gradually degraded. Concurrent work (Tao et al., 2022) also discusses the impact of ϵ_{ref} on poisoning AT models but focuses on a fundamentally different task where the attack aims to degrade the adversarial robustness of AT models (rather than the clean accuracy here). It is also important to note that our INF can work well under different ϵ_{ref} between 2 and 8, where their approach is much more sensitive to the choice of ϵ_{ref} in their task (see their Figure 2(a)). We further visualize the perturbations generated with different ϵ_{ref} in 4b. As can be seen, when using a standard reference model (i.e., $\epsilon_{\text{ref}} = 0$), the perturbations exhibit noisy patterns, but as the ϵ_{ref} is gradually increased, the perturbations tend to be more aligned with image semantics.

These observations suggest that poisoning the ST and AT models require modifying different types of features. More specifically, modifying the robust (semantic) features is the key to poisoning the AT models, while modifying the non-robust features is the key to poisoning the ST models. This conclusion also supports the well-known perspective that *non-robust features can be picked up by models during standard training, even in the presence of robust features, while adversarial training*

tends to utilize robust features (Ilyas et al., 2019). Figure 4a also confirms that our INF is also effective is poisoning ST models since it can decrease the model accuracy to the random guess level (i.e., 10% for CIFAR-10).

| (a) Clean (84.88%) | (b) Pull-pair (78.21%) | (c) Pull (72.99%) | (d) Push (71.57%) |

Figure 5: The t-SNE visualizations for INF-pull-pair vs. our original INF (Pull and Push).

6 ADDITIONAL ANALYSIS OF INDISCRIMINATIVE FEATURES

The above experimental results have demonstrated the effectiveness of INF in various scenarios. Here we provide additional analysis to better understand the property of indiscriminative features. To this end, we adjust the class selection strategy in INF-pull to be simply based on pairwise indiscriminative features. Specifically, each pair consists of two classes that have the minimal centroid distance. For optimization, we calculate the centroids of each class pair and then minimize the distance between samples in one class and the centroid of the other class. We denote this attack variant targeting pairwise indiscriminative features as INF-pull-pair. We find that INF-pull-pair can decrease the model accuracy from 84.88% to 78.21%, which indicates that introducing pairwise indiscriminative features can already substantially compromise adversarial training. However, there is still a large performance gap between INF-pull-pair and our original INF. This can be explained by the fact that INF-pull exploits more diverse pulling directions based on the sample-class distance, and INF-push makes samples from multiple classes become overlapped. The visualizations in Figure 5 clearly confirm the above observation that INF-pull-pair yields indiscriminative features to some extent but still fewer than the original INF-pull and INF-push.

7 CONCLUSION

In this paper, we have proposed INF, a new poisoning approach to decreasing the deep learning classifier's accuracy even when adversarial training is applied. This approach is based on a new attack strategy that makes the features of training samples from different classes become indiscriminative. Extensive experiments demonstrate the effectiveness of INF against adversarial training in different scenarios, including those with more aggressive AT budgets, unseen model architectures, and adaptive defenses. We also discuss the distinct roles of the robust vs. non-robust features in poisoning standard vs. adversarially-trained models and confirm the effectiveness of INF in poisoning standard models.

We encourage future research to analyze INF in more comprehensive settings and compare it to the current, shortcut-based methods from different angles. In particular, it is important to come up with new defenses against INF, possibly based on advanced techniques of learning from noisy labels (Song et al., 2020). It is also worth noting that most of the current poisoning studies, including ours, have assumed that the poisoner has access to the training dataset of the target model. This assumption is realistic in specific threat models (e.g., secure dataset release (Fowl et al., 2021a)) but may not be plausible for sensitive/private data. Therefore, it would be promising to extend INF to addressing data-free poisons (Yu et al., 2022; Segura et al., 2022b).

On the one hand, data poisoning could be potentially leveraged by malicious parties as attacks. In this case, we hope our work can inspire the community to develop stronger defenses based on our comprehensive analysis. On the other hand, when data poisoning is directly used for social good, e.g., for protecting personal data from being misused (Fowl et al., 2021a; Huang et al., 2021; Wang et al., 2021; Liu et al., 2021; Fu et al., 2022), our new approach for generating stronger poisons lead to stronger protective effects.

REFERENCES

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language Models are Few-Shot Learners. In *Annual Conference on Neural Information Processing Systems (NeurIPS)*. NeurIPS, 2020. 1

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An Image is Worth 16x16 Words: Transformers for Image Recognition at Scale. In *International Conference on Learning Representations (ICLR)*, 2021. 1

Liam Fowl, Ping-Yeh Chiang, Micah Goldblum, Jonas Geiping, Arpit Bansal, Wojtek Czaja, and Tom Goldstein. Preventing Unauthorized Use of Proprietary Data: Poisoning for Secure Dataset Release. *CoRR abs/2103.02683*, 2021a. 1, 9

Liam Fowl, Micah Goldblum, Ping-Yeh Chiang, Jonas Geiping, Wojtek Czaja, and Tom Goldstein. Adversarial Examples Make Strong Poisons. In *Annual Conference on Neural Information Processing Systems (NeurIPS)*, pages 30339–30351. NeurIPS, 2021b. 1, 2, 4, 5, 7, 14

Hanxun Huang, Xingjun Ma, Sarah Monazam Erfani, James Bailey, and Yisen Wang. Unlearnable Examples: Making Personal Data Unexploitable. In *International Conference on Learning Representations (ICLR)*, 2021. 1, 2, 4, 5, 6, 7, 9

Lue Tao, Lei Feng, Jinfeng Yi, Sheng-Jun Huang, and Songcan Chen. Better Safe Than Sorry: Preventing Delusive Adversaries with Adversarial Training. In *Annual Conference on Neural Information Processing Systems (NeurIPS)*, pages 16209–16225. NeurIPS, 2021. 1, 2, 3, 4, 5, 7, 13

Zhirui Wang, Yifei Wang, and Yisen Wang. Fooling Adversarial Training with Inducing Noise. *CoRR abs/2111.10130*, 2021. 1, 2, 3, 4, 5, 9

Shaopeng Fu, Fengxiang He, Yang Liu, Li Shen, and Dacheng Tao. Robust Unlearnable Examples: Protecting Data Against Adversarial Learning. In *International Conference on Learning Representations (ICLR)*, 2022. 1, 2, 3, 4, 5, 9

Lue Tao, Lei Feng, Hongxin Wei, Jinfeng Yi, Sheng-Jun Huang, and Songcan Chen. Can Adversarial Training Be Manipulated By Non-Robust Features? In *Annual Conference on Neural Information Processing Systems (NeurIPS)*. NeurIPS, 2022. 1, 5, 8

Pedro Sandoval Segura, Vasu Singla, Liam Fowl, Jonas Geiping, Micah Goldblum, David Jacobs, and Tom Goldstein. Poisons that are learned faster are more effective. *CoRR abs/2204.08615*, 2022a. 1, 6, 13

Ivan Evtimov, Ian Covert, Aditya Kusupati, and Tadayoshi Kohno. Disrupting Model Training with Adversarial Shortcuts. *CoRR abs/2106.06654*, 2021. 1, 13

Da Yu, Huishuai Zhang, Wei Chen, Jian Yin, and Tie-Yan Liu. Availability Attacks Create Shortcuts. In *ACM Conference on Knowledge Discovery and Data Mining (KDD)*, pages 2367–2376. ACM, 2022. 1, 9, 13

Battista Biggio, Blaine Nelson, and Pavel Laskov. Poisoning Attacks against Support Vector Machines. In *International Conference on Machine Learning (ICML)*. icml.cc / Omnipress, 2012. 1, 2

Battista Biggio, Blaine Nelson, and Pavel Laskov. Support Vector Machines Under Adversarial Label Noise. In *Asian Conference on Machine Learning (ACML)*, pages 97–112. JMLR, 2011. 1, 2

Luis Muñoz-González, Battista Biggio, Ambra Demontis, Andrea Paudice, Vasin Wongrassamee, Emil C. Lupu, and Fabio Roli. Towards Poisoning of Deep Learning Algorithms with Back-gradient Optimization. In *Workshop on Security and Artificial Intelligence (AISec)*, pages 27–38. ACM, 2017. 1, 2

Tianyu Gu, Brendan Dolan-Gavitt, and Siddharth Grag. Badnets: Identifying Vulnerabilities in the Machine Learning Model Supply Chain. *CoRR abs/1708.06733*, 2017. 2

Yingqi Liu, Shiqing Ma, Yousra Aafer, Wen-Chuan Lee, Juan Zhai, Weihang Wang, and Xiangyu Zhang. Trojaning Attack on Neural Networks. In *Network and Distributed System Security Symposium (NDSS)*. Internet Society, 2018. 2

Ahmed Salem, Rui Wen, Michael Backes, Shiqing Ma, and Yang Zhang. Dynamic Backdoor Attacks Against Machine Learning Models. In *IEEE European Symposium on Security and Privacy (Euro S&P)*. IEEE, 2022. 2

Ali Shafahi, W Ronny Huang, Mahyar Najibi, Octavian Suciu, Christoph Studer, Tudor Dumitras, and Tom Goldstein. Poison Frogs! Targeted Clean-Label Poisoning Attacks on Neural Networks. In *Annual Conference on Neural Information Processing Systems (NeurIPS)*, pages 6103–6113. NeurIPS, 2018. 2

Jonas Geiping, Liam H. Fowl, W. Ronny Huang, Wojciech Czaja, Gavin Taylor, Michael Moeller, and Tom Goldstein. Witches' Brew: Industrial Scale Data Poisoning via Gradient Matching. In *International Conference on Learning Representations (ICLR)*, 2021. 2

Hwanjun Song, Minseok Kim, Dongmin Park, and Jae-Gil Lee. Learning from Noisy Labels with Deep Neural Networks: A Survey. *CoRR abs/2007.08199*, 2020. 2, 9

Chen Zhu, W Ronny Huang, Hengduo Li, Gavin Taylor, Christoph Studer, and Tom Goldstein. Transferable Clean-label Poisoning Attacks on Deep Neural Nets. In *International Conference on Machine Learning (ICML)*, pages 7614–7623. JMLR, 2019. 2

Anish Athalye, Nicholas Carlini, and David A. Wagner. Obfuscated Gradients Give a False Sense of Security: Circumventing Defenses to Adversarial Examples. In *International Conference on Machine Learning (ICML)*, pages 274–283. PMLR, 2018. 2

Florian Tramèr, Nicholas Carlini, Wieland Brendel, and Aleksander Madry. On Adaptive Attacks to Adversarial Example Defenses. In *Annual Conference on Neural Information Processing Systems (NeurIPS)*. NeurIPS, 2020. 2

Ian Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and Harnessing Adversarial Examples. In *International Conference on Learning Representations (ICLR)*, 2015. 2

Florian Tramèr, Alexey Kurakin, Nicolas Papernot, Ian Goodfellow, Dan Boneh, and Patrick McDaniel. Ensemble Adversarial Training: Attacks and Defenses. In *International Conference on Learning Representations (ICLR)*, 2017. 2

Alexey Kurakin, Ian J. Goodfellow, and Samy Bengio. Adversarial Machine Learning at Scale. In *International Conference on Learning Representations (ICLR)*, 2017. 2

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards Deep Learning Models Resistant to Adversarial Attacks. In *International Conference on Learning Representations (ICLR)*, 2018. 2, 3, 4, 5

Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric P. Xing, Laurent El Ghaoui, and Michael I. Jordan. Theoretically Principled Trade-off between Robustness and Accuracy. In *International Conference on Machine Learning (ICML)*, pages 7472–7482. PMLR, 2019. 3, 5

Yisen Wang, Difan Zou, Jinfeng Yi, James Bailey, Xingjun Ma, and Quanquan Gu. Improving Adversarial Robustness Requires Revisiting Misclassified Examples. In *International Conference on Learning Representations (ICLR)*, 2020. 3, 5, 6

Tianyu Pang, Xiao Yang, Yinpeng Dong, Hang Su, and Jun Zhu. Bag of Tricks for Adversarial Training. In *International Conference on Learning Representations (ICLR)*, 2021. 3

Ali Shafahi, Mahyar Najibi, Amin Ghiasi, Zheng Xu, John P. Dickerson, Christoph Studer, Larry S. Davis, Gavin Taylor, and Tom Goldstein. Adversarial training for free! In *Annual Conference on Neural Information Processing Systems (NeurIPS)*, pages 3353–3364. NeurIPS, 2019. 3

Mahmut Kaya and Hasan Sakir Bilge. Deep Metric Learning: A Survey. *Symmetry*, 2019. 4

https://www.cs.toronto.edu/~kriz/cifar.html. 4

https://www.kaggle.com/c/tiny-imagenet. 4

Zhuoran Liu, Zhengyu Zhao, Alex Kolmus, Tijn Berns, Twan van Laarhoven, Tom Heskes, and Martha A. Larson. Going Grayscale: The Road to Understanding and Improving Unlearnable Examples. *CoRR abs/2111.13244*, 2021. 6, 7, 9

Hongyi Zhang, Moustapha Cissé, Yann N. Dauphin, and David Lopez-Paz. mixup: Beyond Empirical Risk Minimization. In *International Conference on Learning Representations (ICLR)*, 2018. 7

Terrance Devries and Graham W. Taylor. Improved Regularization of Convolutional Neural Networks with Cutout. *CoRR abs/1708.04552*, 2017. 7

Sangdoo Yun, Dongyoon Han, Sanghyuk Chun, Seong Joon Oh, Youngjoon Yoo, and Junsuk Choe. CutMix: Regularization Strategy to Train Strong Classifiers With Localizable Features. In *IEEE International Conference on Computer Vision (ICCV)*, pages 6022–6031. IEEE, 2019. 7

Andrew Ilyas, Shibani Santurkar, Dimitris Tsipras, Logan Engstrom, Brandon Tran, and Aleksander Madry. Adversarial Examples Are Not Bugs, They Are Features. In *Annual Conference on Neural Information Processing Systems (NeurIPS)*, pages 125–136. NeurIPS, 2019. 9

Pedro Sandoval Segura, Vasu Singla, Jonas Geiping, Micah Goldblum, Tom Goldstein, and David W. Jacobs. Autoregressive Perturbations for Data Poisoning. In *Annual Conference on Neural Information Processing Systems (NeurIPS)*. NeurIPS, 2022b. 9

A DISCRIMINATIVE FEATURES IN EXISTING METHODS

Instead of introducing indiscriminative features, most existing poisoning methods rely on generating certain shortcut perturbations that can be more easily learned by the target model than the actual image content (Tao et al., 2021; Segura et al., 2022a; Evtimov et al., 2021; Yu et al., 2022). Figure 6 visualizes the poison representations of different existing methods on an adversarially-trained model. As can be seen, although there exist certain differences between the patterns of different methods (e.g., regarding the relative positions of different classes), all these methods indeed yield well separable data. This observation also confirms that causing indiscriminative features is a *sufficient condition* to degrade adversarial training.

| Hypocritical[+] | Hypocritical | Unlearnable | AdvPoison | ADVIN | REM |

Figure 6: The t-SNE visualizations of the feature representations for existing poisoning methods.

B DETAILED RESULTS FOR INF VS. THE CE LOSS

Table 7: INF vs. the CE loss using the same robust reference model.

POISON METHOD \ DATASET	CIFAR-10	CIFAR-100	TINYIMAGENET
ADVPOISON-UNTAR	72.86	50.45	45.47
INF-PUSH	**71.57**	**47.29**	**41.32**

C ADDITIONAL EXPERIMENTAL SETTINGS

All reference and target models are trained for 100 epochs using SGD optimizer with an initial learning rate of 0.1 that is decayed by a factor of 0.1 at the 75-th and 90-th training epochs. The optimizer is set with momentum 0.9 and weight decay 5×10^{-4}. The inner maximization (i.e., generation of adversarial examples) of the adversarial training is solved by 10-step PGD with a step size of $2/255$.

D ADDITIONAL EXPERIMENTAL RESULTS

(a) CIFAR-10   (b) CIFAR-100   (c) TinyImageNet

Figure 7: Learning curves of our INF on different datasets.

Clean (84.88%)   INF (71.57%)

Figure 8: Classification confusion metrics for clean vs. INF on CIFAR-10. Our INF causes misclassification from one true class to multiple wrong classes, while previous work causes misclassification from one true class to a dominant wrong class (see Figure 2 in (Fowl et al., 2021b)).

E   ADDITIONAL PERTURBATION VISUALIZATIONS

Clean $\epsilon_{\text{ref}} = 4$ $\epsilon_{\text{ref}} = 8$ Clean $\epsilon_{\text{ref}} = 4$ $\epsilon_{\text{ref}} = 8$

(a) CIFAR-100   (b) TinyImageNet

Figure 9: Perturbation (normalized to [0,1]) visualizations for CIFAR-100 and TinyImageNet.