Graph State Networks (GSNs): Persistent Nodewise Selective State Space Models

Abstract

Temporal graphs are often observed as streams of timestamped interactions, where accurate prediction requires retaining and selectively using historical information nodes. Existing temporal graph models either (i) recompute representations from a sliding neighborhood/history at query time, or (ii) maintain a memory module but offer limited control and limited theory for what is retained over long horizons. We propose **Graph State Networks (GSNs)**, a bucketed temporal-graph framework that maintains a persistent hidden state per node and updates it online using a content- and time-dependent selective state space update. Concretely, GSNs store node states in an explicit id-indexed state table and for each bucket, *read* the current state, *update* it with a time-aware Mamba-like mechanism, and *commit* the state back via an exponential moving average controlled by commit-rate α. This commit mechanism provides an explicit "retention dial" and enables a clean analysis of forgetting. We develop a **capacity/recall theory** for persistent node memory and show that, under a time-varying non-affine model assumption of *blank-bucket* dynamics, the influence of a single past event decays exponentially at a rate governed by some contraction factor and the induced update. Empirically, GSNs are competitive on standard dynamic link prediction benchmarks in terms of *average precision*. We validate these ideas with controlled synthetic write–wait–read probes. Under shared later blank sequences and a small nonzero state-noise blank update, the measured write-vs-zero-write relative influence decays approximately exponentially, and a Theorem 1-style contraction-with-disturbance bound tracks the empirical curve closely, including the nonzero floor at larger commit rates.

1 Introduction

Many real-world relational systems, e.g., communication networks, collaboration graphs, recommender systems, transaction ledgers, are naturally modeled as *temporal graphs*, where edges arrive as timestamped events. A core problem is **dynamic link prediction**: given past interactions, score which edges are likely to occur next. The challenge is not just modeling graph structure, but doing so *online* while handling long and irregular histories.

A common design choice is *where the history is stored*. In one family of methods, node representations are computed (or recomputed) from a window of recent interactions using message passing and/or attention over sampled temporal neighborhoods. This can be effective, but it inherits familiar limitations of deep message passing–difficulty propagating long-range signals due to bottlenecks ("over-squashing") and representation collapse in deep stacks ("over-smoothing"), while neighborhood retrieval can become expensive or brittle under distribution shift. A second family uses more global attention-style mechanisms (temporal Transformers and graph Transformers), which can capture long-range dependencies but often lead to quadratic costs in sequence length or require substantial positional/structural encoding machinery.

A different viewpoint is to treat each node as an **online state machine**: instead of rebuilding a node embedding from scratch at query time, a persistent state is updated as events arrive. This view is present in several temporal-graph architectures (e.g., memory module in Temporal Graph Networks), but two gaps remain in practice:

Figure 1: GSN Layer (*read–update–commit*) for a temporal graph snapshot. Here V is the set of nodes and m is the state dimension. Each node i has a persistent state $s_i \in \mathbb{R}^m$ stored in an ID-indexed persistent state table $S \in \mathbb{R}^{|V| \times m}$ that carries across buckets (hence persistent). At snapshot start, the layer reads s_i, then uses incoming messages/events $m_{j \to i}$ and elapsed time Δt in a time-aware selective state-space update to produce features x_i for the task head $g_\gamma(x_i)$ and a proposed new state s'_i. After scoring, the new states are committed to the table via an Exponential Moving Average (EMA) with commit rate α using (1).

1. **Update mechanism:** Many memory updates are hand-designed (GRU-style) or tied closely to specific neighborhood aggregation schemes. Recent progress in **selective state-space models (SSMs)**, notably Mamba (Gu & Dao, 2023), suggests that content-dependent, gated state updates can provide strong long-range modeling with favorable scaling.

2. **Controllability and interpretability of forgetting:** Even when a model maintains memory, it is often unclear *what* information persists and how *quickly* it decays as time passes without a new signal. For deployment, this matters: some applications need long retention; others need rapid adaptation.

This work proposes **Graph State Networks (GSNs)** as a step toward addressing both gaps. GSNs make a simple but strict architectural commitment: every node i owns a persistent hidden state $s_i \in \mathbb{R}^m$ that is **not reinitialized per batch or per forward call**, but evolves over the temporal stream. Concretely, we maintain an explicit state table S indexed by global node IDs. For each temporal bucket/snapshot, we:

- **Read** the current persistent state for nodes present in the bucket;

- **Update** it using a time-aware Mamba-like block;

- **Write/commit** the new state back to the table using an Exponential Moving Average (EMA) with commit rate $\alpha \in (0, 1]$:

$$S[\text{ids}(i)] \leftarrow (1 - \alpha)S[\text{ids}(i)] + \alpha s_i, \tag{1}$$

where s_i is the calculated *new state* of the node i, and ids(i) is the ID of node i as a tuple of (a, b) indexing the row and column of S.

This design cleanly separates (i) *how* information is integrated into a node's memory (the selective SSM update) from (ii) *how aggressively* that memory is refreshed (the commit rule). It also matches our implementation setting: we intentionally use bucketed processing where node states persist across buckets and are

advanced via explicit commit steps at bucket boundaries, rather than strict event-by-event constant-time streaming updates (though it must be noted that streaming updates can be achieved by using a bucket size = 1).

Beyond architecture, our second goal is to make node retention mechanism measurable. We develop a capacity/recall theory for persistent node states: because a fixed-dimensional state must compress history, it cannot reproduce arbitrary query-time retrieval, but its retention can be characterized in terms of what remains recoverable after many events. A key object is the model's behavior during **blank buckets**, i.e., periods with no new informative input, where the system's intrinsic dynamics determine whether old information decays, persists, or is overwritten by drift. Under incremental stability assumptions for time-varying blank-bucket dynamics, we obtain geometric forgetting bounds for state differences. For the learned blank operator used in experiments, we additionally fit a simple empirical stepwise recursion to summarize observed influence decay.

Contributions. In summary, this work:

- introduces **Graph State Networks**, a persistent node-state architecture updated by a time-aware selective SSM and committed via an EMA rule with rate α;

- develops **blank-bucket forgetting theory** that yields closed-form convergence behavior and quantitative bounds on single-event influence decay;

- proposes and evaluates **synthetic write–wait–read probes** that diagnose what the node state retains and show that short-horizon measurements extrapolate to long-horizon predictions;

- demonstrates that **state persistence is compatible with strong predictive performance** on standard temporal link prediction benchmarks, while offering an explicit retention dial.

2 Related Work

A large body of literature studies representation learning on temporal interaction graphs, e.g., (Rossi et al., 2020; Wang et al., 2021b; Xu et al., 2020). Early and influential approaches include **JODIE** (Kumar et al., 2019b), which learns dynamic embedding trajectories for interacting entities, and **DyRep** (Trivedi et al., 2019), which models evolving node representations driven by communication/association processes in continuous time. Attention-based temporal neighborhood aggregation was popularized by **TGAT** (Xu et al., 2020), which introduces functional time encodings and temporal self-attention for inductive temporal graphs. **Temporal Graph Networks (TGN)** (Rossi et al., 2020) unify several lines of work by combining a memory module with message-passing operators over temporal neighborhoods.

Beyond neighbor aggregation, motif/walk-based and Transformer-style models have been explored. **CAWN** (Wang et al., 2021a) uses causal anonymous walks to capture temporal motifs in an inductive way. **TCL** (Wang et al., 2021b) adapts Transformer-style modeling to temporal graphs with contrastive learning objectives. More recently, a line of work argues that carefully designed but simpler architectures can be highly competitive: **GraphMixer** (Cong et al., 2023) proposes an MLP-centric design for temporal link prediction, while **DyGFormer** (Yu et al., 2023) uses a Transformer with co-occurrence encoding and patching to leverage longer histories efficiently. Benchmarking efforts such as the **Temporal Graph Benchmark (TGB)** emphasize realistic evaluation protocols and include strong non-parametric baselines like **EdgeBank** (Huang et al., 2023).

State-space models for sequences and graphs: Structured state space models such as **S4** (Gu et al., 2021) demonstrated that long-range sequence dependencies can be modeled efficiently with principled linear dynamical systems. **Mamba** (Gu & Dao, 2023) introduced *selective* (input-dependent) state updates that achieve strong empirical performance with linear-time scaling in sequence length. Subsequent work like **Mamba-2** (Dao & Gu, 2024) further clarified connections between attention and structured state space computation.

Motivated by these, several papers adapt SSM ideas to graph-structured learning. **S4G** (Song et al., 2024) introduces structured state spaces into graph settings to address long-range dependencies while retaining useful inductive bias. **DyGMamba** (Ding et al., 2025) adapts Mamba-style selective state space models to **continuous-time dynamic graphs** by encoding per-node interaction histories with an SSM and using an additional time-level SSM to select critical historical information, achieving strong dynamic link prediction performance with favorable efficiency. **Graph Mamba Networks** (Wang et al., 2024) propose a general framework that sequentializes graph neighborhoods and processes them with bidirectional selective SSM encoders. These approaches often focus on static graphs or on building graph-to-sequence encoders within each forward pass.

Positioning. GSNs introduced in this paper target the same temporal link prediction setting and evaluation protocol used by these baselines. Conceptually, GSNs are related to memory-based temporal GNNs (e.g., TGN) in that they maintain persistent node memories, but they differ in two important ways: (i) the memory update is implemented as a selective state-space update (SSM) rather than a purely GRU/message-passing update, and (ii) we explicitly analyze forgetting/retention induced by the commit mechanism and blank dynamics, rather than treating the memory as a black box.

As far as SSM-like models are concerned, GSNs use selective SSM machinery but elevate the "sequence position" notion to **node identity**: the state is persistent per node and stored in an explicit table. Unlike many graph-SSM encoders that reconstruct representations from a context window, GSNs are designed around **state persistence across temporal buckets** with explicit read/update/commit semantics. This allows us ask and answer a different question: *not only "can SSMs work on graphs?"* but *"what does a persistent node state retain, and how can we measure and control its forgetting"*?

3 Preliminaries: Persistent Node State Dynamics in GSNs

This section formalizes the state evolution semantics that the rest of the theory studies. The key design choice is that **each node owns a persistent hidden state** that is **stored outside** the forward pass and **updated/committed** only at well-defined times in a bucketed protocol.

3.1 Temporal interaction stream and bucketed protocol

We observe a temporal interaction stream of events $\{e_k\}_{k=1}^N$, where each event $e_k = (u_k, v_k, t_k, x_k)$ contains an interacting pair (u_k, v_k), a timestamp t_k, and optional *edge* features x_k. Let V be the global node set and ids(i) map to a stable integer ID.

We partition time into K chronological buckets $B^{(1)}, \ldots, B^{(K)}$. For bucket $B^{(k)} = [t_{\text{start}}^{(k)}, t_{\text{end}}^{(k)}]$, we distinguish:

- **History snapshot (pre-bucket):** The graph $G_{\text{prev}}^{(k)}$, containing all events with timestamp $< t_{\text{start}}^{(k)}$.

- **Commit snapshot (up to bucket end):** The graph $G_{\text{end}}^{(k)}$, containing all events with timestamp $\leq t_{\text{end}}^{(k)}$.

This separation is important for leakage-free evaluation: we want predictions inside bucket k to depend only on history before the bucket, while still allowing the model's persistent memory to be updated with the bucket's events after scoring.

3.2 Persistent state table and read–update–commit

A GSN maintains a **persistent state table** $S \in \mathbb{R}^{|V| \times m}$, where the row $S[\text{ids}(i)]$ is node i's memory/state (dimension m). This table persists across buckets and is conceptually a part of the model's state.

For a given snapshot (e.g., $G_{\text{prev}}^{(k)}$ or $G_{\text{end}}^{(k)}$), the model performs:

1. **Read:** for each node i participating in the snapshot, read $s_i \leftarrow S[\text{ids}(i)]$.

2. **Pre-commit update:** produce a proposed new state s'_i via a parameterized update operator $F_\phi :$ $\mathbb{R}^m \times \mathcal{E} \times [0, T] \mapsto \mathbb{R}^m$ such that

$$s'_i = F_\phi(s_i; \text{snapshot context}, \Delta t).$$

Here, m is the state dimension, $\mathcal{E}$ is the edge set, $\Delta t \in [0, T]$ denotes elapsed time since node i was last updated, and T denotes the last timestamp of the data (See Figure 1). In our implementation, this update is realized with a time-aware selective state-space block (Mamba-style), but the theory below only requires that it induces some map F_ϕ on states during a bucket.

Commit (persistent write): update the table using an exponential moving average with commit rate α:

$$S[\text{ids}(i)] \leftarrow (1 - \alpha)S[\text{ids}(i)] + \alpha s'_i,$$

where $\alpha \in (0, 1]$ can be fixed or scheduled.

Intuitively, the pre-commit update computes "what the node state should become given the bucket", while the commit step controls how aggressively that proposal overwrites persistent memory. The scalar α will reappear in the theory as a direct knob on forgetting and mixing.

3.3 Stateful training/evaluation semantics with no leakage

Within bucket $B^{(k)}$, we use two-snapshot protocol:

- **Score step:** run the model on $G^{(k)}_{\text{prev}}$ to obtain node representations, then score candidate edges whose timestamp lies in bucket $B^{(k)}$.

- **Commit step:** after scoring, update/commit the persistent states using $G^{(k)}_{\text{end}}$, so that the next bucket starts from memory that has incorporated bucket-k interactions.

This makes the stateful model well-defined: predictions for bucket k are conditioned on history strictly before the bucket, but the state entering the bucket $k + 1$ reflects everything up to $t^{(k)}_{\text{end}}$.

3.4 Quantities the theory will track

The remaining theory asks: **what does a bounded-dimensional persistent state retain, and how does it forget?** To make this precise, we define three objects:

1. **The committed bucket operator.** Fix a bucket snapshot structure and the exogenous inputs it induces, e.g., features, time deltas, etc. The combination "pre-commit update + EMA commit" defines an operator T_α on node states: $s \mapsto (1 - \alpha)s + \alpha F_t(s)$, where F_t is a time-varying pre-commit update map induced by that bucket. In the next section, we study this operator in the special but revealing case of "blank buckets".

2. **Influence of a write (counterfactual sensitivity).** Consider two executions that are identical in all later blank buckets but differ in the write initialization at time 0 (for example, an actual write versus a zero-write baseline, or two different write payloads). Let s_t and $\hat{s}_t$ be the resulting node states after t subsequent bucket commits under identical later inputs. **The influence at delay** t is measured by $\|s_t - \hat{s}_t\|$. This is the central object for "forgetting".

3. **Recall through a readout.** A downstream task uses a decoder/readout g (e.g., link predictor or probe head) applied to the node state. We will bound not just state differences, but also readout differences $\|g(s_t) - g(\hat{s}_t)\|$ under mild regularity assumptions, connecting "state retention" to "task-visible retention".

With these definitions in place, the next section derives explicit convergence and geometric forgetting rates for repeated blank-bucket commits, and shows how α and the blank dynamics jointly determine memory half-life.

4 Blank-Bucket Theory: Forgetting and State Retention Bounds

This section formalizes the "retention dial" perspective of the commit rate α by analyzing what happens when a node experiences *no new informative input* for multiple buckets.

4.1 Blank buckets

A **blank bucket** is a bucket in which the node receives no new task-relevant signal, e.g., features are zeroed, or messages carry a fixed "blank token", but the model is still executed and the resulting state is committed to the persistent state table (as in the write–wait–read protocol).

Let s_t be the persistent state of a fixed node after t blank-bucket commits following some "write" event. The GSN update semantics from the previous section imply a committed recursion of the form:

- pre-commit proposal: $s \mapsto F_t(s)$ (this is "whatever the backbone does on a blank bucket")

- commit: $s_{t+1} = (1 - \alpha)s_t + \alpha F_t(s_t)$

4.2 Main result: closed form influence decay

Setup and Assumptions Let $m, n \in \mathbb{Z}_{>0}$. For all $t \geq 0$, let $D_t \subseteq \mathbb{R}^m$ be a convex set. Consider a time-varying discrete time system with an exogenous input/disturbance

$$f : \mathbb{R}^m \times \mathbb{R}^n \to \mathbb{R}^m, \qquad x_{t+1} = f_t(x_t, u_t), \qquad t \in \mathbb{Z}_{\geq 0},$$

where the states $x_t, y_t \in D_t$ and inputs $u_t, v_t \in \mathbb{R}^n$. Also assume,

$$x_t \in D_t \implies x_{t+1} \in D_{t+1} \quad \text{(forward invariance)}.$$

We assume a time-varying incremental ISS-Lyapunov family W_t in the spirit of the discrete-time δ-ISS Lyapunov inequalities in Bayer et al. (2013, Definition 3), and the time-varying discrete-time ISS Lyapunov families in Laila & Astolfi (2004, Definition 2.3). and say that the system has the incremental ISS-Lyapunov property if there exist constants

$$0 < c_1 \leq c_2 < \infty, \qquad \lambda \in (0, 1),$$

such that

$$\lambda c_2 < c_1,$$

and a class-$\mathcal{K}$ function, (see Sontag (1995, Section 2.1) for a definition), $\sigma : \mathbb{R}_{\geq 0} \to \mathbb{R}_{\geq 0}$ such that for every t and for all $x, y \in D_t$ and all inputs u, v there exists a function $W_t : D_t \times D_t \to \mathbb{R}_{\geq 0}$ such that

$$c_1 \|x - y\|^2 \leq W_t(x, y) \leq c_2 \|x - y\|^2, \tag{2}$$

and

$$W_{t+1}(f_t(x, u), f_t(y, v)) \leq \lambda W_t(x, y) + \sigma(\|u - v\|). \tag{3}$$

A common practical specialization is: $\|u - v\|_\infty \leq \bar{u} \implies \sigma(\|u - v\|_\infty) \leq \bar{d}$, i.e., a bounded additive term.

The next result is a standard consequence of the incremental ISS Lyapunov inequalities above, and provides us with means to characterize the "forgetting" properties of GSNs.

Theorem 1. **(Incremental ISS implies exponential forgetting with a floor):** Let $x_{t+1} = f_t(x_t, u_t)$ and $y_{t+1} = f_t(y_t, v_t)$ be two trajectories satisfying *forward invariance* and u_t, v_t be as described above. Suppose (2) and (3) hold. Define

$$\Delta_t = \|x_t - y_t\|_2^2.$$

Then for all $t \geq 0$,

$$\Delta_t \leq \frac{c_2}{c_1} \lambda^t \Delta_0 + \frac{1}{c_1} \sum_{k=0}^{t-1} \lambda^{t-1-k} \sigma(\|u_k - v_k\|), \tag{4}$$

where $\|\cdot\|$ denotes any fixed norm on $\mathbb{R}^n$. In particular, if $\sigma(\|u-v\|_\infty) \leq \bar{d}$ for all k, then

$$\Delta_t \leq \frac{c_2}{c_1}\lambda^t \Delta_0 + \frac{\bar{d}}{c_1}\frac{1-\lambda^t}{1-\lambda}. \tag{5}$$

Hence,

$$\limsup_{t\to\infty} \Delta_t \leq \frac{\bar{d}}{c_1(1-\lambda)}.$$

For a proof, see Appendix.

Below we show that Δ_{t+1} can be upper-bounded by Δ_t as an affine recursion. This will help us choose a suitable recursive model assumption on the *influence* which we define later in the experiments.

With a slight abuse of notation, let $V_t := W_t(x_t, y_t)$. From (3) we have,

$$V_{t+1} \leq \lambda V_t + \sigma(\|u_t - v_t\|).$$

Using (2),

$$V_{t+1} \geq c_1\|x_{t+1} - y_{t+1}\|^2 = c_1\Delta_{t+1} \quad \text{and} \quad V_t \leq c_2\|x_t - y_t\|^2 = c_2\Delta_t. \tag{6}$$

By substituting (6) into (3), we have that

$$c_1\Delta_{t+1} \leq \lambda(c_2\Delta_t) + \sigma(\|u_t - v_t\|)$$
$$\Rightarrow \Delta_{t+1} \leq \underbrace{\frac{\lambda c_2}{c_1}}_{a}\Delta_t + \underbrace{\frac{1}{c_1}\sigma(\|u_t - v_t\|)}_{b_t} = a\Delta_t + b_t. \tag{7}$$

Since, $\lambda c_2 < c_1$, each step in (7) is a contraction.

Next, we discuss how much information GSNs can faithfully recover after d blank commits; we provide a channel-capacity style theorem in what follows.

4.3 State-Compression and Recoverable Information

Setup and Assumptions Fix a state dimension $m \in \mathbb{N}$. A single node's persistent state at (discrete) time t is a vector $s_t \in \mathbb{R}^m$. A discrete payload/message

$$H \in \{1, 2, \ldots, M\}$$

is written into the state at time $t = 0$ by some write mechanism producing a random initial state s_0 whose randomness comes from the randomness of H plus any write randomness.

During the blank bucket period of length d, i.e., d blank buckets/commits, the state evolves according to the nonlinear time-varying recursion:

$$s_{t+1} = f_t(s_t), \quad t = 0, 1, \ldots, d-1, \tag{8}$$

where s_0 is drawn at random, and each $f_t : \mathbb{R}^m \to \mathbb{R}^m$ is a measurable map[1]. At read time we observe a noisy version of the final state:

$$Y = s_d + Z, \qquad Z \sim \mathcal{N}(0, \sigma^2 I_m), \tag{9}$$

with Z independent of $(H, s_0, \ldots, s_d)$. A decoder $\hat{H} = \text{Dec}(Y)$ attempts to recover H.

Remark 4.1. **(Justification of noise):** The additive noise model is one standard way to make "how many bits can be stored in $\mathbb{R}^m$" well-posed; without some finite-precision/noise assumption, a real vector can encode arbitrarily many bits.

We make the following assumptions

---

[1] We abuse the notation and omit the input u_t for brevity.

(C1) **(Message distribution)** H is uniform on $\{1, \ldots, M\}$. The write mechanism induces a conditional distribution $s_0 \mid H$. We absorb any additional write randomness into this conditional law.

(C2) **(Write energy / dynamic range)** The message-dependent variation in the written state is bounded as

$$\mathrm{tr}(\mathrm{Cov}(s_0)) \leq mP \qquad \text{for some } P \geq 0 \tag{10}$$

(C3) **(Uniform contraction of blank dynamics)** Additionally, we assume a uniform contraction as follows and call the effective one-step contraction factor to be $r_t \in (0,1)$ so that

$$\|f_t(x) - f_t(y)\|_2 \leq r_t \|x - y\|_2 \qquad \forall x, y \in \mathbb{R}^m, \quad \forall t \in \{0, \ldots, d-1\} \tag{11}$$

Define the "cumulative" contraction factor R_d as follows:

$$R_d = \prod_{t=0}^{d-1} r_t \in (0,1). \tag{12}$$

Before providing the theorem, we make one additional remark about Assumption (C3).

Remark 4.2. **(Uniform contraction as a natural follow-up to** (2) **and** (3)**):** If we let the assumptions of Theorem 1 hold and take the same input $u = v$, then $\sigma(\|u - v\|) = 0$ and (3) becomes

$$W_{t+1}(f_t(x, u), f_t(y, u)) \leq \lambda W_t(x, y). \tag{13}$$

From (2),

$$c_1 \|f_t(x, u), f_t(y, u)\|_2^2 \leq W_{t+1}(f_t(x, u), f_t(y, u)) \tag{14a}$$

$$W_t(x, y) \leq c_2 \|x - y\|_2^2. \tag{14b}$$

Combining (14a) and (14b) with (13):

$$c_1 \|f_t(x, u), f_t(y, u)\|_2^2 \leq \lambda W_t(x, y) \leq \lambda c_2 \|x - y\|_2^2.$$

So,

$$\|f_t(x, u), f_t(y, u)\|_2^2 \leq \sqrt{\frac{\lambda c_2}{c_1}} \|x - y\|_2^2, \qquad \forall \, x, y.$$

In the above, if we set $r_t = \sqrt{\frac{\lambda c_2}{c_1}}$ for all t, then since $\lambda c_2 < c_1$ by the assumptions of Theorem 1, we get the uniform contraction as stated in (C3). In (C3), we generalize this notion to allow for a time-varying step-wise contraction factor.

With the setup and assumptions in place, we provide the following theorem.

Theorem 2. **(Information-limited recall scales with m and decays with blank contraction):** Under Assumptions (C1)–(C3) the following holds:

(I) **(Mutual information bound)**

$$I(H; Y) \leq \frac{m}{2} \log\left(1 + \frac{PR_d^2}{\sigma^2}\right). \tag{15}$$

(II) **(Error lower bound)** For any decoder $\hat{H} = \mathrm{Dec}(Y)$,

$$\mathbb{P}(\hat{H} \neq H) \geq 1 - \frac{I(H; Y) + \log 2}{\log M} \geq 1 - \frac{\frac{m}{2} \log\left(1 + \frac{PR_d^2}{\sigma^2}\right) + \log 2}{\log M}. \tag{16}$$

Equivalently to achieve $\mathbb{P}(\hat{H} \neq H) \leq \varepsilon$, it is necessary that

$$m \geq \frac{2\left((1 - \varepsilon) \log M - \log 2\right)}{\log\left(1 + \frac{PR_d^2}{\sigma^2}\right)}. \tag{17}$$

For a proof, see Appendix.

5 Experiments

In this section, we discuss experiments that distinctively fall into two different genres, *viz.* (i) validation and suitability of GSNs in doing dynamic link prediction and (ii) validation of capacity/recall theory. Before presenting the results, it is worth distinguishing the inference regimes targeted by different architectures. While recent state-space baselines such as DyGMamba achieve strong performance, their reliance on bidirectional scanning (forward and reverse passes) during graph encoding implies a batch-processing paradigm. This structure is highly effective for offline analysis but introduces necessary latency in strictly online, streaming settings where predictions must be made instantly upon event arrival without waiting for future context. In contrast, GSNs are designed as causally strictly forward-only systems: the persistent node state is updated immediately as events arrive, maintaining constant-time inference compatibility regardless of the sequence length.

Having set the paradigm, we now present the metrics for GSNs. We start with dynamic link prediction.

5.1 GSNs for Dynamic Link Prediction

We train GSNs on seven different dynamic link prediction datasets: Wikipedia (Kumar et al., 2019a), MOOC (Kumar et al., 2019a), Enron (Shetty & Adibi, 2004), UCI (Panzarasa et al., 2009), US Legis (Poursafaei et al., 2022), Can. Parl (Poursafaei et al., 2022), and Contact (Poursafaei et al., 2022). The results are summarized in Table 1 and Table 2 respectively.

Protocol and evaluation. The training process is detailed in Algorithm 1. We follow the standard temporal link prediction protocol used by prior work on these datasets. Each interaction (u, v, t, attr) is processed in timestamp order, and the model is evaluated by scoring the true edge against sampled negatives. We report results under both the commonly used negative sampling regimes shown in the tables (rnd/ind).

Baselines. We compare against representative memory-based and attention-based temporal graph models (e.g., JODIE, DyRep, TGAT, TGN, CAWN, GraphMixer, DyGFormer, DyGMamba), and also against recent sequence-modeling approaches (DyG-Mamba). Where available, we include strong non-neural heuristics (EdgeBank) and contrastive pretraining baselines (TCL), using the benchmark's reported mean±std across runs.

Table 1: Average Precision (AP, %) for **transductive** dynamic link prediction with random (rnd) and inductive (ind) negative sampling strategies. APs are reported as mean±std. AP for all other models are taken from Ding et al. (2025).

NSS	Dataset	JODIE	DyRep	TGAT	TGN	CAWN	EdgeBank	TCL	GraphMixer	DyGFormer	DyG-Mamba	GSN
rnd	Wikipedia	96.50±0.14	94.86±0.06	96.94±0.06	98.45±0.06	98.76±0.03	90.37±0.00	96.47±0.04	97.25±0.04	99.03±0.04	**99.08±0.03**	97.05±0.08
	MOOC	80.23±2.44	81.97±0.49	85.84±0.15	89.15±1.60	80.15±0.25	57.97±0.00	82.38±0.24	82.78±0.15	87.52±0.49	90.25±0.09	**90.76±0.10**
	Enron	84.77±0.30	82.38±3.36	71.12±0.97	86.53±1.11	89.56±0.09	83.53±0.00	79.70±0.71	82.25±0.16	92.47±0.12	**93.14±0.08**	91.04±0.21
	UCI	89.43±1.09	65.14±2.30	79.63±0.70	92.34±1.04	95.18±0.06	76.20±0.00	89.57±1.63	93.25±0.57	95.79±0.17	**96.14±0.14**	92.23±0.63
	Can.Parl.	69.26±0.31	66.54±2.76	70.73±0.72	70.88±2.34	69.82±2.34	64.55±0.00	68.67±2.67	77.04±0.46	97.36±0.45	**98.20±0.52**	93.48±1.82
	USLegis	75.05±1.52	75.34±0.39	68.52±3.16	75.99±0.58	70.58±0.48	58.39±0.00	69.59±0.48	70.74±1.02	71.11±0.59	73.66±1.13	**87.80±1.08**
	Contact	95.31±1.33	95.98±0.15	96.28±0.09	96.89±0.56	90.26±0.28	92.58±0.00	92.44±0.12	91.44±0.03	98.29±0.01	**98.38±0.01**	97.90±0.03
ind	Wikipedia	75.65±0.79	70.21±1.58	87.00±0.16	85.62±0.44	74.06±2.62	80.63±0.00	86.76±0.72	88.59±0.17	79.29±5.38	87.06±0.86	**90.78±0.78**
	MOOC	65.23±2.19	61.66±0.95	75.95±0.64	77.50±2.91	73.51±0.94	49.43±0.00	74.65±0.54	74.27±0.92	**81.24±0.69**	81.19±2.02	80.07±0.91
	Enron	68.96±0.98	67.79±1.53	63.94±1.36	70.89±2.72	75.15±0.58	73.89±0.00	71.29±0.32	75.01±0.79	77.41±0.89	77.46±0.90	**84.31±0.95**
	UCI	65.99±1.40	54.79±1.76	68.67±0.84	70.94±0.71	64.61±0.48	57.43±0.00	76.01±1.11	80.10±0.51	72.25±1.71	77.75±1.56	**82.58±0.90**
	Can.Parl.	48.42±0.66	58.61±0.86	68.82±1.21	65.34±2.87	67.75±1.00	62.16±0.00	65.85±1.75	69.48±0.63	95.44±0.57	**97.29±0.96**	85.68±0.70
	USLegis	50.27±5.13	83.44±1.16	61.91±5.82	67.57±6.47	65.81±8.52	64.74±0.00	78.15±3.34	79.63±0.84	81.25±3.62	**85.61±1.66**	83.43±1.42
	Contact	93.43±1.78	94.18±0.10	94.35±0.48	90.18±3.28	89.31±0.27	85.00±0.00	91.35±0.21	90.87±0.35	94.75±0.28	94.63±0.06	**95.43±0.09**

Table 2: AUC-ROC (%) for **transductive** dynamic link prediction with random (rnd) and inductive (ind) negative sampling strategies. AUC-ROCs are reported as mean±std. AUC-ROCs for all other models are taken from Ding et al. (2025).

NSS	Dataset	JODIE	DyRep	TGAT	TGN	CAWN	EdgeBank	TCL	GraphMixer	FreeDyG	DyGFormer	DyG-Mamba	GSN
rnd	Wikipedia	96.33±0.07	94.37±0.09	96.67±0.07	98.37±0.07	98.54±0.04	90.78±0.00	95.84±0.18	96.92±0.03	**99.41±0.01**	98.91±0.02	99.01±0.09	94.14±0.02
	MOOC	83.81±2.09	85.08±0.58	87.11±0.19	**91.21±1.15**	80.38±0.26	60.86±0.00	83.12±0.18	84.01±0.17	89.93±0.35	87.91±0.58	91.01±0.14	81.52±1.35
	Enron	87.96±0.52	84.89±3.00	68.89±1.10	88.32±0.99	90.45±0.14	87.05±0.00	75.74±0.72	84.38±0.21	**94.01±0.11**	93.33±0.13	93.05±0.17	87.26±0.18
	UCI	90.44±0.49	68.77±2.34	78.53±0.74	92.03±1.13	93.87±0.08	77.30±0.00	87.82±1.36	91.81±0.67	95.00±0.21	94.49±0.26	**95.32±0.18**	84.52±0.51
	Can.Parl.	78.21±0.23	73.35±3.67	75.69±0.78	76.99±1.80	75.70±3.27	64.14±0.00	72.46±3.23	83.17±0.53	N/A	97.76±0.41	**98.67±0.29**	86.96±0.40
	USLegis	82.85±1.07	82.28±0.32	75.84±1.99	83.34±0.43	77.16±0.39	62.57±0.00	76.27±0.63	76.96±0.79	N/A	77.90±0.58	78.19±0.64	75.60±1.10
	Contact	96.66±0.89	96.48±0.14	96.95±0.08	97.54±0.35	89.99±0.34	94.34±0.00	94.15±0.09	93.94±0.02	N/A	98.53±0.01	**98.59±0.00**	95.80±0.10
ind	Wikipedia	70.96±0.78	67.36±0.96	81.93±0.22	80.97±0.31	70.95±0.95	81.73±0.00	82.19±0.48	84.28±0.30	82.74±0.32	75.09±3.70	82.30±1.81	**87.83±1.31**
	MOOC	66.63±2.30	63.26±1.01	73.18±0.33	77.44±2.86	70.32±1.43	48.18±0.00	70.36±0.37	72.45±0.72	78.47±0.94	80.76±0.76	**82.05±1.38**	60.15±1.00
	Enron	70.92±1.05	68.73±1.34	60.45±2.12	71.34±2.46	75.17±0.50	75.00±0.00	67.64±0.86	71.53±0.85	77.27±0.61	74.07±0.64	74.49±0.48	**80.38±0.80**
	UCI	64.14±1.26	54.25±2.01	60.80±1.01	64.11±1.04	58.06±0.26	58.03±0.00	70.05±1.86	74.59±0.74	**75.39±0.57**	65.96±1.18	73.23±1.03	65.21±1.71
	Can.Parl.	52.88±0.80	63.53±0.65	72.47±1.18	69.57±2.81	72.93±1.78	61.41±0.00	69.47±2.12	70.52±0.94	N/A	96.70±0.59	**97.30±0.97**	71.35±0.63
	USLegis	59.05±5.52	89.44±0.71	71.62±5.42	78.12±4.46	76.45±7.02	68.66±0.00	82.54±3.91	84.22±0.91	N/A	87.96±1.80	**90.28±0.50**	66.85±0.78
	Contact	94.47±1.08	94.23±0.18	94.10±0.41	91.64±0.72	87.68±0.24	85.87±0.00	91.23±0.19	90.96±0.27	N/A	95.01±0.15	95.08±0.01	90.70±0.14

Discussion. Across the seven datasets, GSNs are competitive with recent temporal graph baselines under Average Precision (AP) and across negative sampling regimes. The strongest gains tend to appear when the evaluation stresses *generalization under distribution shift* (e.g., inductive splits or inductive negatives), which is consistent with the intuition that a persistent node state can act as a compact summary that is updated online rather than recomputed from scratch. At the same time, the results also highlight that there remains headroom from careful tuning and architectural choices (with regards to improving the AUC-ROCs). Overall, these benchmarks serve as an end-to-end sanity check: GSN-style state persistence does not sacrifice predictive performance on standard dynamic link prediction, and it motivates a more targeted question–*what memory is the model actually retaining, and how does it decay with delay?* We answer that question next using controlled write–wait–read probes that directly test the capacity/recall theory.

5.2 Synthetic capacity–recall protocol

Each episode consists of a single *write bucket* followed by d *blank buckets*. We randomly choose 256 write nodes. Each written node is assigned a class label from

$$H \in \{1, 2, \ldots, 32\}$$

encoded by a one-hot injection into the node features (node feature dimension 64). After d blank commits, a decoder predicts the per-node class labels from the persistent states of the written nodes.

A blank commit uses the same trained model update as a non-blank commit. Concretely, for a node state $s_t \in \mathbb{R}^m$ the committed update is

$$s_{t+1} = (1 - \alpha)s_t + \alpha F_t(s_t), \tag{18}$$

where $m = 64$ and $\alpha \in \{0.05, 0.1, 0.2, 0.4, 1.0\}$ is swept at evaluation time. The map F_t is induced by the *blank bucket context* at step t (graph structure and time features). In the main influence experiments reported below, the blank update includes a small nonzero state-noise scale (0.05), which serves as a persistent stochastic perturbation during blank-bucket commits.

Time-varying blank schedule. To construct time-variation while keeping blank buckets uninformative about H, each blank step follows a two-regime block schedule with period 5:

$$z_t = \left\lfloor \frac{t}{5} \right\rfloor \mod 2. \tag{19}$$

Thus the blank dynamics alternate between 5 short-regime steps and 5 long-regime steps. Regime z_t controls (i) the effective time-gap presented to the model (bucket size 1 vs. 100, implemented through the timestamp deltas), and (ii) a small regime token injected into node features that is independent of H. The blank graphs themselves are sampled independently of H.

Blank-shift control. As a robustness check, we also evaluate the same trained model on a shifted blank distribution consisting of sparser, undirected graphs with self-loops. This control leaves the write bucket unchanged and only perturbs the blank bucket distribution.

5.3 Influence measurement

We measure influence by running two counterfactual trajectories that share the same later blank-bucket sequence but differ in the write bucket. Let x_t and y_t denote the resulting persistent states of the written nodes after t blank commits. x_t is initialized from the actual write graph, whereas y_t is initialized from a zero-write baseline. Define the (un-normalized) influence as

$$I_t := \mathbb{E}\big[\|x_t - y_t\|_2\big], \tag{20}$$

and the *relative influence ratio* I_t/I_0, which equals 1 at $t = 0$. Also, define the influence *surrogate* to be

$$J_t := \mathbb{E}\big[\|x_t - y_t\|_2^2\big]. \tag{21}$$

Then by Jensen's inequality

$$I_t \leq \sqrt{J_t}.$$

In addition to evaluating influence at a sparse set of delays $d \in \{0, 1, 2, 5, 10, 20, 30, 50\}$, we also compute the *stepwise* influence curve for all blank steps $t \in \{0, 1, \ldots, 50\}$, along with the per-step log-slope

$$\Delta \log I_t := \log(I_{t+1}) - \log(I_t). \tag{22}$$

(a) $\alpha = 1$ (b) $\alpha = 0.2$

Figure 2: Write-vs-zero-write influence decay under time-varying blank buckets with nonzero state noise (std. dev = 0.05). Green: Theorem-1-style contraction-with-disturbance bound. Red dotted: fitted time-varying empirical recursion. The high-α panel shows a clear nonzero floor, while the low-α panel shows slower near-exponential decay.

Theorem 1-style bound and empirical recursion   Theorem 1 motivates a contraction-with-disturbance upper bound on state differences $\Delta_t := \|x_t - y_t\|^2$. In the main noisy-blank setting, we therefore fit a Theorem-1-style affine upper bound of the form

$$\Delta_{t+1} \leq a\Delta_t + b$$

to the measured write-vs-zero-write transitions and roll it forward to obtain a predicted relative influence curve. As a more flexible empirical comparator, we also fit a time-varying recursion at the level of squared influence,

$$I_{t+1}^2 \approx a_{z_t} I_t^2 + b_{z_t}, \tag{23}$$

where z_t denotes the blank-bucket regime. The first model is the theory-guided bound shown in Figure 2, while the second is a purely empirical time-varying fit.

5.4 Results

Figure 2 shows write-vs-zero-write influence decay under time-varying blank buckets in the main noisy-blank setting (noise scale = 0.05). For $\alpha = 1$, empirical influence decays rapidly and then saturates at a nonzero floor. A Theorem-1-style contraction-with-disturbance bound tracks this behavior closely across delays. For smaller α, the decay is more gradual and remains well described by the same theory-guided bound, while the time-varying fitted recursion provides a slightly tighter empirical overlay.

To make time-variation visible beyond sparse delays, Figure 3 plots the full stepwise influence curve and the per-step log-slope for $\alpha = 0.2$ under the same noisy-blank setting. The log-slope is not constant over time, indicating that the effective forgetting rate changes across blank steps under the block-alternating blank regime schedule.

(a) Stepwise influence ($\alpha = 0.2$)   (b) Per-step log-slope ($\alpha = 0.2$)

Figure 3: Stepwise influence and per-step log-slope for $\alpha = 0.2$ under the same noisy-blank setting as Figure 2. A single exponential would yield an approximately constant per-step log-slope, whereas the empirical slope varies over time.

Finally, Figure 4 shows that recall accuracy trends are essentially unchanged under the blank-shift control, suggesting the observed time-variation and non-affine effects are not artifacts of a single narrow blank distribution.

(a) Baseline blanks   (b) Shifted blanks

Figure 4: Recall accuracy heatmaps for baseline blanks and a shifted blank distribution. The qualitative recall behavior is stable under the shift, while time-varying empirical corrections provide a tighter match to the measured decay curves.

6 Conclusion

This work proposed **Graph State Networks (GSNs)**: a temporal-graph architecture that treats each node as a **persistent stateful system** stored in an explicit ID-indexed table and updated online via a **time-aware selective state-space block**, with writes committed through an EMA rule controlled by a single **commit rate** α. This separation–*how* information is integrated (the backbone update) versus *how aggressively* it is committed (α)–yields a simple but powerful "retention dial" that is easy to reason about and tune.

On the theory side, we analyzed blank-bucket dynamics under incremental stability assumptions and obtained a contraction-with-disturbance forgetting bound. Complementing this dynamical forgetting result, Theorem 2 provides an information-theoretic capacity perspective: for fixed state dimension and readout noise, the recoverable message information scales with the state dimension but decays with cumulative blank-bucket contraction. Although we do not isolate this noisy-readout bound in a dedicated experiment here, it formalizes why finite persistent node states cannot support arbitrarily long-horizon exact recall. In the main synthetic setting with small nonzero state noise in the blank update, the measured write-vs-zero-write influence curves are well captured by a Theorem-1-style bound, including the nonzero floor at larger commit rates. This supports the view that the commit rate α acts as a retention dial, while long-horizon retention is jointly shaped by contraction and persistent stochastic disturbance in the blank dynamics. This motivates a practical workflow: measure short-horizon influence to estimate the effective contraction, then extrapolate to predict long-horizon retention. Controlled **write**–**wait**–**read** probes support this picture: influence curves are close to exponential over the regime that matters for recall, and short-delay fits predict longer-delay behavior well, while deviations at very long delays can be understood as an effective noise floor from time-varying blank operators and backbone nonlinearity. Finally, in standard dynamic link prediction benchmarks (including both transductive and inductive evaluations), GSNs are broadly competitive with strong temporal-graph baselines, with particularly strong behavior in inductive settings—consistent with the value of persistent, selectively-updated node memory.

A few directions are especially promising. First, pushing GSNs closer to strict **event-by-event streaming** (or learning variable bucket sizes) would broaden applicability. Second, α is currently a simple global control knob; learning **adaptive** or **node-specific commit rates** could better trade off retention and adaptation across heterogeneous nodes. Overall, GSNs suggest a useful middle-ground between recomputing history at query time and opaque memory modules: **persistent node memory with a measurable, tunable retention mechanism.**

References

Florian Bayer, Mathias Bürger, and Frank Allgöwer. Discrete-time incremental iss: A framework for robust nmpc. In *2013 European Control Conference (ECC)*, pp. 2068–2073, 2013. doi: 10.23919/ECC.2013. 6669322.

Weilin Cong, Si Zhang, Jian Kang, Baichuan Yuan, Hao Wu, Xin Zhou, Hanghang Tong, and Mehrdad Mahdavi. Do we really need complicated model architectures for temporal networks? In *International Conference on Learning Representations*, 2023. doi: 10.48550/arXiv.2302.11636. URL `https://arxiv.org/abs/2302.11636`.

Tri Dao and Albert Gu. Transformers are SSMs: Generalized models and efficient algorithms through structured state space duality. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 10041–10071. ML Research Press, 2024. doi: 10.48550/arXiv.2405.21060. URL `https://arxiv.org/abs/2405.21060`.

Zifeng Ding, Yifeng Li, Yuan He, Antonio Norelli, Jingcheng Wu, Volker Tresp, Yunpu Ma, and Michael M. Bronstein. DyGMamba: Efficiently Modeling Long-term Temporal Dependency on Continuous-Time Dynamic Graphs with State Space Models, 2025. URL `https://openreview.net/forum?id=f3gCs2a4ZD`.

Albert Gu and Tri Dao. Mamba: Linear-time sequence modeling with selective state spaces, 2023. URL `https://arxiv.org/abs/2312.00752`.

Albert Gu, Karan Goel, and Christopher Ré. Efficiently modeling long sequences with structured state spaces. In *Conference on Neural Information Processing Systems*, 2021. doi: 10.48550/arXiv.2111.00396. URL `https://arxiv.org/abs/2111.00396`.

Shenyang Huang, Farimah Poursafaei, Jacob Danovitch, Matthias Fey, Weihua Hu, Emanuele Rossi, Jure Leskovec, Michael Bronstein, Guillaume Rabusseau, and Reihaneh Rabbany. Temporal graph benchmark for machine learning on temporal graphs. In *Conference on Neural Information Processing Systems*, 2023. URL `https://proceedings.neurips.cc/paper_files/paper/2023/hash/066b98e63313162f6562b35962671288-Abstract-Datasets_and_Benchmarks.html`.

Srijan Kumar, Xikun Zhang, and Jure Leskovec. Predicting dynamic embedding trajectory in temporal interaction networks. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, KDD '19, pp. 1269–1278, New York, NY, USA, 2019a. Association for Computing Machinery. ISBN 9781450362016. doi: 10.1145/3292500.3330895. URL `https://doi.org/10.1145/3292500.3330895`.

Srijan Kumar, Xikun Zhang, and Jure Leskovec. Predicting dynamic embedding trajectory in temporal interaction networks. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 1269–1278. Association for Computing Machinery, 2019b. doi: 10.1145/3292500.3330895. URL `https://doi.org/10.1145/3292500.3330895`.

D.S. Laila and A. Astolfi. Input-to-state stability for parameterized discrete-time time-varying nonlinear systems with applications. In *2004 5th Asian Control Conference (IEEE Cat. No.04EX904)*, volume 1, pp. 274–282 Vol.1, 2004.

Pietro Panzarasa, Tore Opsahl, and Kathleen M. Carley. Patterns and dynamics of users' behavior and interaction: Network analysis of an online community. *J. Assoc. Inf. Sci. Technol.*, 60:911–932, 2009. URL `https://api.semanticscholar.org/CorpusID:263266966`.

Farimah Poursafaei, Shenyang Huang, Kellin Pelrine, and Reihaneh Rabbany. Towards better evaluation for dynamic link prediction. In Sanmi Koyejo, S. Mohamed, A. Agarwal, Danielle Belgrave, K. Cho, and A. Oh (eds.), *Conference on Neural Information Processing Systems*, 2022. URL `http://papers.nips.cc/paper_files/paper/2022/hash/d49042a5d49818711c401d34172f9900-Abstract-Datasets_and_Benchmarks.html`.

Emanuele Rossi, Ben Chamberlain, Fabrizio Frasca, Davide Eynard, Federico Monti, and Michael Bronstein. Temporal graph networks for deep learning on dynamic graphs. In *International Conference on Machine Learning*, 2020. doi: 10.48550/arXiv.2006.10637. URL `https://arxiv.org/abs/2006.10637`.

Jitesh Shetty and Jafar Adibi. The enron email dataset database schema and brief statistical report. 2004. URL `https://api.semanticscholar.org/CorpusID:59919272`.

Yunchong Song, Siyuan Huang, Jiacheng Cai, Xinbing Wang, Chenghu Zhou, and Zhouhan Lin. S4g: Breaking the bottleneck on graphs with structured state spaces, 2024. URL `https://openreview.net/forum?id=OZ6lN4GYrO`.

Eduardo D. Sontag. On the input-to-state stability property. *European Journal of Control*, 1(1):24–36, 1995. ISSN 0947-3580. doi: https://doi.org/10.1016/S0947-3580(95)70005-X. URL `https://www.sciencedirect.com/science/article/pii/S094735809570005X`.

Rakshit Trivedi, Mehrdad Farajtabar, Prasenjeet Biswal, and Hongyuan Zha. Dyrep: Learning representations over dynamic graphs. In *International Conference on Learning Representations*, 2019. URL `https://openreview.net/forum?id=HyePrhR5KX`.

Chloe Wang, Oleksii Tsepa, Jun Ma, and Bo Wang. Graph-mamba: Towards long-range graph sequence modeling with selective state spaces. *ArXiv*, abs/2402.00789, 2024. URL `https://api.semanticscholar.org/CorpusID:267364853`.

Yanbang Wang, Yen-Yu Chang, Yunyu Liu, Jure Leskovec, and Pan Li. Inductive representation learning in temporal networks via causal anonymous walks. In *International Conference on Learning Representations*, 2021a. doi: 10.48550/arXiv.2101.05974. URL https://arxiv.org/abs/2101.05974.

Yu Wang, Tong Zhang, Yu Meng, Jia Pan, and Shiyu Chang. TCL: Transformer-based dynamic graph modelling via contrastive learning, 2021b. URL https://arxiv.org/abs/2105.07944.

Da Xu, Chuanwei Ruan, Evren Korpeoglu, Sushant Kumar, and Kannan Achan. Inductive representation learning on temporal graphs. In *International Conference on Learning Representations*, 2020. doi: 10. 48550/arXiv.2002.07962. URL https://arxiv.org/abs/2002.07962.

Le Yu, Leilei Sun, Bowen Du, and Weifeng Lv. Towards better dynamic graph learning: New architecture and unified library. In *Conference on Neural Information Processing Systems*, 2023. doi: 10.48550/arXiv. 2303.13047. URL https://arxiv.org/abs/2303.13047. Accepted at NeurIPS 2023.

A   Proof of Theorem 1

Proof. Let $V_t = W_t(x_t, y_t)$. Applying (3) along the two trajectories gives for each t,

$$V_{t+1} \leq \lambda V_t + \sigma(\|u_t - v_t\|).$$

Apply induction:

For $t = 0$: $V_1 \leq \lambda V_0 + \sigma(\|u_0 - v_0\|)$. Assume for some $t \geq 1$ that

$$V_t \leq \lambda^t V_0 + \sum_{k=0}^{t-1} \lambda^{t-1-k} \sigma(\|u_k - v_k\|).$$

Then

$$
\begin{aligned}
V_{t+1} &\leq \lambda V_t + \sigma(\|u_t - v_t\|) \\
&\leq \lambda\left(\lambda^t V_0 + \sum_{k=0}^{t-1} \lambda^{t-1-k} \sigma(\|u_k - v_k\|)\right) + \sigma(\|u_t - v_t\|) \\
&= \lambda^{t+1} V_0 + \sum_{k=0}^{t} \lambda^{t-k} \sigma(\|u_k - v_k\|)
\end{aligned}
$$

which is the same formula for $t \leftarrow t + 1$. Therefore, by induction, for all t

$$V_t \leq \lambda^t V_0 + \sum_{k=0}^{t-1} \lambda^{t-1-k} \sigma(\|u_k - v_k\|).$$

Now, using (2): $c_1 \|x_t - y_t\|^2 \leq V_t \leq \lambda^t V_0 + \sum_{k=0}^{t-1} \lambda^{t-1-k} \sigma(\|u_k - v_k\|)$ and $V_0 \leq c_2 \|x_0 - y_0\|^2$. Therefore,

$$\|x_t - y_t\|^2 \leq \frac{1}{c_1} V_t \leq \frac{c_2}{c_1} \lambda^t \|x_0 - y_0\|^2 + \frac{1}{c_1} \sum_{k=0}^{t-1} \lambda^{t-1-k} \sigma(\|u_k - v_k\|).$$

Re-writing $\|x_t - y_t\|^2 =: \Delta_t$, we get (4). If $\sigma(\|u_k - v_k\|) \leq \bar{d}$, the sum is bounded by a geometric series:

$$\sum_{k=0}^{t-1} \lambda^{t-1-k} \sigma(\|u_k - v_k\|) \leq \bar{d} \cdot \sum_{k=0}^{t-1} \lambda^{t-1-k} = \sum_{j=0}^{t-1} \lambda^j = \bar{d} \cdot \frac{1 - \lambda^t}{1 - \lambda}$$

giving (5) and the lim sup bound. □

B Proof of Theorem 2

Proof. Define the composition

$$\Phi_d = f_{d-1} \circ f_{d-2} \circ \cdots \circ f_0,$$

so that $s_d = \Phi_d(s_0)$ by (8). By repeated application of (11) for all x, y

$$\|\Phi_d(x) - \Phi_d(y)\|_2 \leq \left(\prod_{t=0}^{d-1} r_t\right) \|x - y\|_2 = R_d \|x - y\|_2.$$

Hence Φ_d is R_d-Lipschitz. Now, let s_0' be an independent copy of s_0, i.e.,

$$s_0 \stackrel{d}{=} s_0'.$$

Set $s_d' := \Phi_d(s_0')$. Since Φ_d is deterministic, s_d and s_d' are i.i.d and in particular

$$s_d \stackrel{d}{=} s_d'.$$

Note that, if X and X' have the same law (i.e., the same underlying distribution), then

$$\mathbb{E}\|X - X'\|_2^2 = 2\mathbb{E}\|X - \mathbb{E}X\|_2^2 = 2\operatorname{tr}(\operatorname{Cov}(X)). \tag{24}$$

Using Lipschitzness of Φ_d,

$$\mathbb{E}\|s_d - s_d'\|_2^2 = \mathbb{E}\|\Phi_d(s_0) - \Phi_d(s_0')\|_2^2 \leq R_d^2 \mathbb{E}\|s_0 - s_0'\|_2^2.$$

Now using (24),

$$2\operatorname{tr}(\operatorname{Cov}(s_d)) \leq R_d^2 \cdot 2\operatorname{tr}(\operatorname{Cov}(s_0)),$$

hence,

$$\operatorname{tr}(\operatorname{Cov}(s_d)) \leq R_d^2 \operatorname{tr}(\operatorname{Cov}(s_0)) \leq R_d^2 \cdot mP, \tag{25}$$

where the last inequality follows from Assumption (C2). Now, from (9), $Y = s_d + Z$ with $Z \sim \mathcal{N}(0, \sigma^2 I_m)$ independent. Because $H \to s_d \to Y$ is a Markov chain, the data-processing inequality gives

$$I(H; Y) \leq I(s_d; Y) = I(s_d; s_d + Z). \tag{26}$$

Let $K := \operatorname{Cov}(s_d)$, and $h(\cdot)$ denote binary entropy. For any input X with covariance K and independent Gaussian noise $Z \sim \mathcal{N}(0, \sigma^2 I_m)$, the mutual information satisfies

$$I(X; X + Z) \leq h(X + Z) - h(Z)$$
$$\leq \frac{1}{2}\log\left((2\pi e)^m \det(K + \sigma^2 I_m)\right) - \frac{1}{2}\log\left((2\pi e)^m \det(\sigma^2 I_m)\right),$$

using that for fixed covariance, Gaussian maximizes differential entropy. Thus,

$$I(X; X + Z) \leq \frac{1}{2}\log\det\left(I_m + \sigma^{-2}K\right).$$

Applying this with $X = s_d$ yields

$$I(s_d; s_d + Z) \leq \frac{1}{2}\log\det\left(I_m + \sigma^{-2}K\right). \tag{27}$$

Let $\lambda_1, \ldots, \lambda_m \geq 0$ be the eigenvalues of $\sigma^{-2}K$. Then,

$$\det\left(I_m + \sigma^{-2}K\right) = \prod_{i=1}^{m}(1 + \lambda_i).$$

By AM-GM inequality,

$$\prod_{i=1}^{m}(1+\lambda_i) \le \left(\frac{1}{m}\sum_{i=1}^{m}(1+\lambda_i)\right)^m = \left(1+\frac{1}{m}\sum_{i=1}^{m}\lambda_i\right)^m = \left(1+\frac{\operatorname{tr}(K)}{m\sigma^2}\right)^m. \tag{28}$$

Taking logs and combining (27), (28), and using $\operatorname{tr}(K) \le mPR_d^2$, we get

$$I(s_d\,;s_d+Z) \le \frac{m}{2}\log\left(1+\frac{PR_d^2}{\sigma^2}\right).$$

Combining this with (26) proves conclusion (I).

Now, let $P_e := \mathbb{P}(\hat{H} \ne H)$. Let $\mathbb{H}$ denote the Shannon entropy. Then, Fano's inequality gives

$$\mathbb{H}(H\,|\,Y) \le h(P_e) + P_e\log(M-1) \le \log 2 + P_e\log M \tag{29}$$

since $h(P_e) \le \log 2$. Also,

$$I(H\,;Y) = \mathbb{H}(H) - \mathbb{H}(H\,|\,Y) = \log M - \mathbb{H}(H\,|\,Y). \tag{30}$$

Combining (29) and (30) gives

$$I(H\,;Y) \ge \log M - (\log 2 + P_e\log M) = (1-P_e)\log M - \log 2,$$

so

$$P_e \ge 1 - \frac{I(H\,;Y)+\log 2}{\log M}$$

which is the first inequality in (16). The second inequality in (16) follows by applying (15). Rearranging the above gives (17). $\qquad\square$

C   GSN Training Algorithm

Algorithm 1 Bucketed training of a Graph State Network (GSN) for temporal link prediction

---

Require: Temporal event stream $\mathbf{E}$; cached negatives Neg; bucket size B_e (events per bucket); optimizer Opt; accumulation steps A; commit schedule $\alpha(\cdot)$ (or constant α); write-penalty weight λ_{wr}; scorer head Score($\cdot$).

1: Initialize persistent state table(s) $\mathbf{S}$ (indexed by global node IDs).
2: Initialize gradient accumulators $\{\Delta\theta\} \leftarrow 0$ and counter $c \leftarrow 0$.
3: **for** epoch $= 1, 2, \ldots, E$ **do**
4:     **for** bucket k in chronological order **do**
5:         $(\mathbf{u}, \mathbf{v}^+, \mathbf{t}, \mathbf{v}^-) \leftarrow$ NextTimeBatchWithNeg($\mathbf{E}$, Neg, B_e)
6:         $[t_{\mathrm{start}}^{(k)}, t_{\mathrm{end}}^{(k)}] \leftarrow [\min(\mathbf{t}), \max(\mathbf{t})]$
7:         $G_{\mathrm{prev}}^{(k)} \leftarrow$ Snapshot $\left(\mathbf{E};\ t < t_{\mathrm{start}}^{(k)} \right)$ ▷ history-only
8:         $G_{\mathrm{end}}^{(k)} \leftarrow$ Snapshot $\left(\mathbf{E};\ t \leq t_{\mathrm{end}}^{(k)} \right)$ ▷ history + bucket
9:         $(\mathbf{P}, \mathbf{s}) \leftarrow$ BuildCandidates($\mathbf{u}, \mathbf{v}^+, \mathbf{v}^-$)
10:        TrainStep($G_{\mathrm{prev}}^{(k)}, \mathbf{P}, \mathbf{s}, \lambda_{\mathrm{wr}};\ \mathbf{S}, \alpha(\cdot), \mathrm{Opt}, \{\Delta\theta\}, c, A$)
11:        CommitToEnd($G_{\mathrm{end}}^{(k)};\ \mathbf{S}, \alpha(\cdot)$)   ▷ updates $\mathbf{S}$ for bucket $k{+}1$
12:     **end for**
13: **end for**
14: **function** BuildCandidates($\mathbf{u}, \mathbf{v}^+, \mathbf{v}^-$)
15:     $\mathbf{P} \leftarrow [\ ],\ \ \mathbf{s} \leftarrow [\ ]$
16:     **for** $i = 1$ to $|\mathbf{u}|$ **do**
17:         $\mathbf{C}_i \leftarrow [v_i^+] \parallel \mathbf{v}_i^-$ ▷ positive first
18:         $\mathbf{s}[i] \leftarrow |\mathbf{C}_i|$
19:         **for** each $v \in \mathbf{C}_i$ **do**
20:             append pair (u_i, v) to $\mathbf{P}$
21:         **end for**
22:     **end for**
23:     **return** $(\mathbf{P}, \mathbf{s})$
24: **end function**
25: **function** TrainStep($G, \mathbf{P}, \mathbf{s}, \lambda_{\mathrm{wr}};\ \mathbf{S}, \alpha(\cdot), \mathrm{Opt}, \{\Delta\theta\}, c, A$)
26:     Let $\{u_i\}_{i=1}^B$ be the source IDs for each query (one per block), inferred from $\mathbf{P}$ and $\mathbf{s}$.
27:     **Read pre-states:** $\mathbf{s}_{\mathrm{pre}} \leftarrow \mathbf{S}[u_1, \ldots, u_B]$
28:     **Forward + commit on history snapshot:**
29:     Run GSN on G with commit enabled to obtain (i) node embeddings $\mathbf{H}$ for nodes in G and (ii) post-update states $\mathbf{s}_{\mathrm{post}}$ for touched sources.
30:     **Score candidates (post):** $\ell_{\mathrm{post}} \leftarrow$ Score($\mathbf{s}_{\mathrm{post}}, \mathbf{H}, \mathbf{P}$)
31:     **Ranking loss:** $L_{\mathrm{rank}} \leftarrow$ RankLoss($\ell_{\mathrm{post}}, \mathbf{s}$)   ▷ CE/BCE over each block
32:     **Score-change-normalized write penalty:**
33:     $\Delta\mathbf{s} \leftarrow \mathbf{s}_{\mathrm{post}} - \mathrm{stopgrad}(\mathbf{s}_{\mathrm{pre}})$
34:     $d_s \leftarrow \|\Delta\mathbf{s}\|_2$ ▷ per-source norm
35:     $\ell_{\mathrm{pre}} \leftarrow$ Score($\mathrm{stopgrad}(\mathbf{s}_{\mathrm{pre}}), \mathbf{H}, \mathbf{P}$)
36:     $d_{\mathrm{score}} \leftarrow$ BlockMean($|\ell_{\mathrm{post}} - \ell_{\mathrm{pre}}|, \mathbf{s}$)   ▷ mean over each block
37:     $L_{\mathrm{wr}} \leftarrow \lambda_{\mathrm{wr}} \cdot \mathrm{mean}\left(\dfrac{d_s}{\mathrm{stopgrad}(d_{\mathrm{score}}) + \varepsilon} \right)$
38:     $L \leftarrow L_{\mathrm{rank}} + L_{\mathrm{wr}}$
39:     **Backprop + accumulate:** $g \leftarrow \nabla_\theta L;\ \ \Delta\theta \leftarrow \Delta\theta + g;\ \ c \leftarrow c + 1$
40:     **if** $c \bmod A = 0$ **then**
41:         Opt.Step($\Delta\theta/A$); $\Delta\theta \leftarrow 0$
42:     **end if**
43: **end function**
44: **function** CommitToEnd($G_{\mathrm{end}};\ \mathbf{S}, \alpha(\cdot)$)
45:     Run GSN on G_{end} with commit enabled (no scoring), updating persistent table(s) $\mathbf{S}$
46:     via EMA commit: $\mathbf{S}[i] \leftarrow (1 - \alpha)\mathbf{S}[i] + \alpha\mathbf{s}_i'$ (applied by the model)
47: **end function**