Target Variance Matters: Stabilizing Deep Q-Learning under Data Augmentation

Abstract

While agents trained by Reinforcement Learning (RL) can solve increasingly challenging tasks directly from visual observations, generalizing learned skills to novel environments remains very challenging. Extensive use of data augmentation is a promising technique for improving generalization in RL, but it is often found to decrease sample efficiency and can even lead to divergence. In this paper, we investigate causes of instability when using data augmentation in common off-policy RL algorithms. We identify two problems, both rooted in high-variance Q-targets. Based on our findings, we propose a simple yet effective technique for stabilizing this class of algorithms under augmentation, and perform extensive empirical evaluation on a family of benchmarks based on DeepMind Control Suite, as well as in robotic manipulation tasks. Our method greatly improves stability and sample efficiency under augmentation, and achieves generalization results competitive with state-of-the-art methods for image-based RL. Finally, we show that our method scales to RL with ViT-based architectures, and that data augmentation may be especially important in this setting.

1 Introduction

Reinforcement Learning (RL) from visual observations has achieved tremendous success in various applications such as video-games [36, 3, 59], robotic manipulation [30], and autonomous navigation [35, 71]. However, it is still very challenging for current methods to generalize the learned skills to novel environments, and policies trained by RL can easily overfit to the training environment [69, 9], especially for high-dimensional observation spaces such as images [6, 49].

Increasing the variability in training data via domain randomization [57, 41] and data augmentation [48, 28, 26, 42] has demonstrated encouraging results for learning policies invariant to changes in the environment. Specifically, recent works on data augmentation [28, 26] both show improvements in sample efficiency from simple cropping and translation augmentations, but the studies also conclude that additional data augmentation in fact *decrease* sample efficiency and even cause divergence. While these augmentations have the potential to improve generalization, the increasingly varied data makes the optimization more challenging and risks instability. Unlike supervised learning, balancing the trade-off between stability and generalization in RL requires substantial trial and error.

In this paper, we illuminate theoretically grounded causes of instability when applying data augmentation to common off-policy RL algorithms [36, 31, 11, 14]. Based on our findings, we provide an intuitive method for stabilizing this class of algorithms under use of strong data augmentation. Specifically, we find two main causes of instability in previous work's application of data augmentation: (i) indiscriminate application of data augmentation resulting in high-variance Q-targets; and (ii) that Q-value estimation strictly from augmented data results in over-regularization.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

To address these problems, we propose **SVEA**: **S**tabilized Q-**V**alue **E**stimation under **A**ugmentation, a simple yet effective framework for data augmentation in off-policy RL that greatly improves stability of Q-value estimation. Our method consists of the following three components: Firstly, by only applying augmentation in Q-value estimation of the *current* state, *without* augmenting Q-targets used for bootstrapping, SVEA circumvents erroneous bootstrapping caused by data augmentation; Secondly, we formulate a modified Q-objective that optimizes Q-value estimation jointly over both augmented and unaugmented copies of the observations; Lastly, for SVEA implemented with an actor-critic algorithm, we optimize the actor strictly on unaugmented data, and instead learn a generalizable policy indirectly through parameter-sharing. Our framework can be implemented efficiently without additional forward passes nor introducing additional learnable parameters.

We verify our hypotheses empirically through extensive experiments on the DeepMind Control Suite [55] and extensions of it, including the DMControl Generalization Benchmark [18] and the Distracting Control Suite [51], as well as a set of robotic manipulation tasks. Our method successfully stabilizes Q-value estimation under a set of strong data augmentations, and achieves sample efficiency, asymptotic performance, and generalization that is competitive or better than previous state-of-the-art methods in all tasks considered, at a significantly lower computational cost. Finally, we show that our method scales to RL with ViT-based architectures, and that data augmentation may be especially important in this setting.

2 Related Work

Representation Learning. Learning visual invariances using data augmentation and self-supervised objectives has proven highly successful in computer vision [39, 37, 70, 63, 58, 56, 64, 22, 5]. For example, Chen et al. [5] perform an extensive study on data augmentation (e.g. random cropping and image distortions) for contrastive learning, and show that representations pre-trained with such transformations transfer effectively to downstream tasks. While our work also uses data augmentation for learning visual invariances, we leverage the Q-objective of deep Q-learning algorithms instead of auxiliary representation learning tasks.

Visual Learning for RL. Numerous methods have been proposed with the goal of improving sample efficiency [24, 47, 58, 66, 33, 50, 52, 45, 65] of image-based RL. Recently, using self-supervision to improve generalization in RL has also gained interest [68, 38, 46, 1, 17, 18, 61]. Notably, Zhang et al. [68] and Agarwal et al. [1] propose to learn behavioral similarity embeddings via auxiliary tasks (bisimulation metrics and contrastive learning, respectively), and Hansen et al. [18] learn visual invariances through an auxiliary prediction task. While these results are encouraging, it has also been shown in [24, 33, 17, 67, 34] that the best choice of auxiliary tasks depends on the particular RL task, and that joint optimization with sub-optimally chosen tasks can lead to gradient interference. We achieve competitive sample-efficiency and generalization results *without* the need for carefully chosen auxiliary tasks, and our method is therefore applicable to a larger variety of RL tasks.

Data Augmentation and Randomization for RL. Our work is directly inspired by previous work on generalization in RL by domain randomization [57, 41, 40, 43, 4] and data augmentation [29, 7, 60, 28, 26, 42, 52, 18]. For example, Tobin et al. [57] show that a neural network trained for object localization in a simulation with randomized visual augmentations improves real world generalization. Similarly, Lee et al.[29] show that application of a random convolutional layer to observations during training improve generalization in 3D navigation tasks. More recently, extensive studies on data augmentation [28, 26] have been conducted with RL, and conclude that, while small random crops and translations can improve sample efficiency, most data augmentations *decrease* sample efficiency and cause divergence. We illuminate main causes of instability, and propose a framework for data augmentation in deep Q-learning algorithms that drastically improves stability and generalization.

Improving Deep Q-Learning. While deep Q-learning algorithms such as Deep Q-Networks (DQN) [36] have achieved impressive results in image-based RL, the temporal difference objective is known to have inherent instabilities when used in conjunction with function approximation and off-policy data [54]. Therefore, a variety of algorithmic improvements have been proposed to improve convergence [20, 62, 21, 19, 44, 31, 11, 10, 23]. For example, Hasselt et al. [20] reduce overestimation of Q-values by decomposing the target Q-value estimation into action selection and action evaluation using separate networks. Lillicrap et al. [31] reduce target variance by defining the target Q-network as a slow-moving average of the online Q-network. Our method also improves Q-value estimation, but we specifically address the instability of deep Q-learning algorithms on augmented data.

3 Preliminaries

Problem formulation. We formulate the interaction between environment and policy as a Markov Decision Process (MDP) [2] $\mathcal{M} = \langle \mathcal{S}, \mathcal{A}, \mathcal{P}, r, \gamma \rangle$, where $\mathcal{S}$ is the state space, $\mathcal{A}$ is the action space, $\mathcal{P}\colon \mathcal{S} \times \mathcal{A} \mapsto \mathcal{S}$ is the state transition function that defines a conditional probability distribution $\mathcal{P}(\cdot|\mathbf{s}_t, \mathbf{a}_t)$ over all possible next states given a state $\mathbf{s}_t \in \mathcal{S}$ and action $\mathbf{a}_t \in \mathcal{A}$ taken at time t, $r\colon \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}$ is a reward function, and $\gamma \in [0,1)$ is the discount factor. Because image observations only offer partial state observability [25], we define a state $\mathbf{s}_t$ as a sequence of $k+1$ consecutive frames $(\mathbf{o}_t, \mathbf{o}_{t-1}, \ldots, \mathbf{o}_{t-k})$, $\mathbf{o} \in \mathcal{O}$, where $\mathcal{O}$ is the high-dimensional image space, as is common practice [36]. The goal is then to learn a policy $\pi\colon \mathcal{S} \mapsto \mathcal{A}$ that maximizes discounted return $R_t = \mathbb{E}_{\Gamma \sim \pi}[\sum_{t=1}^{T} \gamma^t r(\mathbf{s}_t, \mathbf{a}_t)]$ along a trajectory $\Gamma = (\mathbf{s}_0, \mathbf{s}_1, \ldots, \mathbf{s}_T)$ obtained by following policy π from an initial state $\mathbf{s}_0 \in \mathcal{S}$ to a state $\mathbf{s}_T$ with state transitions sampled from $\mathcal{P}$, and π is parameterized by a collection of learnable parameters θ. For clarity, we hereon generically denote parameterization with subscript, e.g. π_θ. We further aim to learn parameters θ s.t. π_θ generalizes well (i.e. obtains high discounted return) to novel MDPs, which is generally unfeasible without further assumptions about the structure of the space of MDPs. In this work, we therefore consider generalization to MDPs $\overline{\mathcal{M}} = \langle \overline{\mathcal{S}}, \mathcal{A}, \mathcal{P}, r, \gamma \rangle$, where states $\overline{\mathbf{s}}_t \in \overline{\mathcal{S}}$ are constructed from observations $\overline{\mathbf{o}}_t \in \overline{\mathcal{O}}$, $\mathcal{O} \subseteq \overline{\mathcal{O}}$ of a novel observation space $\overline{\mathcal{O}}$, and $\overline{\mathcal{M}} \sim \mathbb{M}$ for a space of MDPs $\mathbb{M}$.

Deep Q-Learning. Common model-free off-policy RL algorithms aim to estimate an optimal state-action value function $Q^*\colon \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}$ as $Q_\theta(\mathbf{s}, \mathbf{a}) \approx Q^*(\mathbf{s}, \mathbf{a}) = \max_{\pi_\theta} \mathbb{E}\left[R_t | \mathbf{s}_t = \mathbf{s}, \mathbf{a}_t = \mathbf{a}\right]$ using function approximation. In practice, this is achieved by means of the single-step Bellman residual $\left(r(\mathbf{s}_t, \mathbf{a}_t) + \gamma \max_{\mathbf{a}'_t} Q_\psi^{\text{tgt}}(\mathbf{s}_{t+1}, \mathbf{a}'_t) \right) - Q_\theta(\mathbf{s}_t, \mathbf{a}_t)$ [53], where ψ parameterizes a *target* state-action value function Q^{tgt}. We can choose to minimize this residual (also known as the *temporal difference* error) directly wrt θ using a mean squared error loss, which gives us the objective

$$\mathcal{L}_Q(\theta, \psi) = \mathbb{E}_{\mathbf{s}_t, \mathbf{a}_t, \mathbf{s}_{t+1} \sim \mathcal{B}} \left[\frac{1}{2} \left[\left(r(\mathbf{s}_t, \mathbf{a}_t) + \gamma \max_{\mathbf{a}'_t} Q_\psi^{\text{tgt}}(\mathbf{s}_{t+1}, \mathbf{a}'_t) \right) - Q_\theta(\mathbf{s}_t, \mathbf{a}_t) \right]^2 \right], \quad (1)$$

where $\mathcal{B}$ is a replay buffer with transitions collected by a behavioral policy [32]. From here, we can derive a greedy policy directly by selecting actions $\mathbf{a}_t = \arg\max_{\mathbf{a}_t} Q_\theta(\mathbf{s}_t, \mathbf{a}_t)$. While $Q^{\text{tgt}} = Q$ and periodically setting $\psi \longleftarrow \theta$ exactly recovers the objective of DQN [36], several improvements have been proposed to improve stability of Eq. 1, such as Double Q-learning [20], Dueling Q-networks [62], updating target parameters using a slow-moving average of the online Q-network [31]:

$$\psi_{n+1} \longleftarrow (1 - \zeta)\psi_n + \zeta\theta_n \quad (2)$$

for an iteration step n and a momentum coefficient $\zeta \in (0, 1]$, and others [21, 19, 44, 10, 23]. As computing $\max_{\mathbf{a}'_t} Q_\psi^{\text{tgt}}(\mathbf{s}_{t+1}, \mathbf{a}'_t)$ in Eq. 1 is intractable for large and continuous action spaces, a number of prominent *actor-critic* algorithms that additionally learn a policy $\pi_\theta(\mathbf{s}_t) \approx \arg\max_{\mathbf{a}_t} Q_\theta(\mathbf{s}_t, \mathbf{a}_t)$ have therefore been proposed [31, 11, 14].

Soft Actor-Critic (SAC) [14] is an off-policy actor-critic algorithm that learns a state-action value function Q_θ and a stochastic policy π_θ (and optionally a temperature parameter), where Q_θ is optimized using a variant of the objective in Eq. 1 and π_θ is optimized using a γ-discounted maximum-entropy objective [72]. To improve stability, SAC is also commonly implemented using Double Q-learning and the slow-moving target parameters from Eq. 2. We will in the remainder of this work describe our method in the context of a generic off-policy RL algorithm that learns a parameterized state-action value function Q_θ, while we in our experiments discussed in Section 6 evaluate of our method using SAC as base algorithm.

4 Pitfalls of Data Augmentation in Deep Q-Learning

In this section, we aim to illuminate the main causes of instability from naïve application of data augmentation in Q-value estimation. Our goal is to learn a Q-function Q_θ for an MDP $\mathcal{M}$ that generalizes to novel MDPs $\overline{\mathcal{M}} \sim \mathbb{M}$, and we leverage data augmentation as an optimality-invariant state transformation τ to induce a bisimulation relation [27, 13] between a state $\mathbf{s}$ and its transformed (augmented) counterpart $\mathbf{s}^{\text{aug}} = \tau(\mathbf{s}, \nu)$ with parameters $\nu \sim \mathcal{V}$.

Definition 1 (Optimality-Invariant State Transformation [26]). *Given an MDP $\mathcal{M}$, a state transformation $\tau\colon \mathcal{S} \times \mathcal{V} \mapsto \mathcal{S}$ is an optimality-invariant state transformation if $Q(\mathbf{s}, \mathbf{a}) = Q(\tau(\mathbf{s}, \nu), \mathbf{a}) \ \forall \mathbf{s} \in \mathcal{S}, \mathbf{a} \in \mathcal{A}, \nu \in \mathcal{V}$, where $\nu \in \mathcal{V}$ parameterizes the transformation τ.*

Following our definitions of $\mathcal{M}, \overline{\mathcal{M}}$ from Section 3, we can further extend the concept of optimality-invariant transformations to MDPs, noting that a change of state space itself can be described as a transformation $\overline{\tau}\colon \mathcal{S} \times \overline{\mathcal{V}} \mapsto \overline{\mathcal{S}}$ with unknown parameters $\overline{\nu} \in \overline{\mathcal{V}}$. If we choose the set of parameters $\mathcal{V}$ of a state transformation τ to be sufficiently large, we can therefore expect to improve generalization to state spaces not seen during training. However, while naïve application of data augmentation as in [28, 26, 52, 45] may potentially improve generalization, it can be harmful to Q-value estimation. We hypothesize that this is primarily because it dramatically increases the size of the observed state space, and consequently also increases variance $\mathrm{Var}\left[Q(\tau(\mathbf{s}, \nu))\right] \geq \mathrm{Var}\left[Q(\mathbf{s})\right]$, $\nu \sim \mathcal{V}$ when $\mathcal{V}$ is large. Concretely, we identify the following two issues:

Pitfall 1: Non-deterministic Q-target. For deep Q-learning algorithms, previous work [28, 26, 52, 45] applies augmentation to both state $\mathbf{s}_t^{\mathrm{aug}} \triangleq \tau(\mathbf{s}_t, \nu)$ and successor state $\mathbf{s}_{t+1}^{\mathrm{aug}} \triangleq \tau(\mathbf{s}_{t+1}, \nu')$ where $\nu, \nu' \sim \mathcal{V}$. Compared with DQN [36] that uses a deterministic (more precisely, periodically updated) Q-target, this practice introduces a non-deterministic Q-target $r(\mathbf{s}_t, \mathbf{a}_t) + \gamma \max_{\mathbf{a}_t'} Q_\psi^{\mathrm{tgt}}(\mathbf{s}_{t+1}^{\mathrm{aug}}, \mathbf{a}_t')$ depending on the augmentation parameters ν'. As observed in the original DQN paper, high-variance target values are detrimental to Q-learning algorithms, and may cause divergence due to the "deadly triad" of function approximation, bootstrapping, and off-policy learning [54]. This motivates the work to introduce a slowly changing target network, and several other works have refined the Q-target update rule [31, 11] to further reduce volatility. However, because data augmentation is inherently non-deterministic, it greatly increases variance in Q-target estimation and exacerbates the issue of volatility. This is particularly troubling in actor-critic algorithms such as DDPG [31] and SAC [14], where the Q-target is estimated from $(\mathbf{s}_{t+1}, \mathbf{a}')$, $\mathbf{a}' \sim \pi(\cdot|\mathbf{s}_{t+1})$, which introduces an additional source of error from π that is non-negligible especially when $\mathbf{s}_{t+1}$ is augmented.

Pitfall 2: Over-regularization. Data augmentation was originally introduced in the supervised learning regime as a regularizer to prevent overfitting of high-capacity models. However, for RL, even learning a policy in the training environment is hard. While data augmentation may improve generalization, it greatly increases the difficulty of policy learning, i.e., optimizing θ for Q_θ and potentially a behavior network π_θ. Particularly, when the temporal difference loss from Eq. 1 cannot be well minimized, the large amount of augmented states dominate the gradient, which significantly impacts Q-value estimation of both augmented and unaugmented states. We

Figure 1. **Mean difference in Q-value estimation on augmented vs. non-augmented data.** We measure the mean difference in Q-value estimation from converged DrQ [26] agents (trained with *shift* augmentation) on the same observations before and after augmentation. Averaged across 5 seeds of DrQ for each of the 5 tasks from DMControl-GB, where (undiscounted) episode returns range from 0 to 1,000.

refer to this issue as over-regularization by data augmentation. Figure 1 shows the mean difference in Q-predictions made with augmented vs. unaugmented data in fully converged DrQ [26] agents trained with *shift* augmentation. Augmentations such as affine-jitter, random convolution, and random overlay incur large differences in estimated Q-values. While such difference can be reduced by regularizing the optimization with each individual augmentation, we emphasize that even the minimal shift augmentation used throughout training incurs non-negligible difference. Since ψ is commonly chosen to be a moving average of θ as in Eq. 2, such differences caused by over-regularization affect Q_θ and Q_ψ^{tgt} equally, and optimization may therefore still diverge depending on the choice of data augmentation. As such, there is an inherent trade-off between accurate Q-value estimation and generalization when using data augmentation. In the following section, we address these pitfalls.

5 Method

We propose **SVEA**: **S**tabilized Q-**V**alue **E**stimation under **A**ugmentation, a general framework for generalization by data augmentation in RL. SVEA applies data augmentation in a novel learning framework leveraging two data streams – with and without augmented data, respectively. Our method is compatible with any standard off-policy RL algorithm without changes to the underlying neural network that parameterizes the policy, and it requires no additional forward passes, auxiliary tasks, nor learnable parameters. While SVEA does not make any assumptions about the structure of states $\mathbf{s}_t \in \mathcal{S}$, we here describe our method in the context of image-based RL.

Figure 2. **Overview.** An observation $\mathbf{s}_t$ is transformed by data augmentation $\tau(\cdot, \nu)$, $\nu \sim \mathcal{V}$ to produce a view $\mathbf{s}_t^{\text{aug}}$. The Q-function Q_θ is then jointly optimized on both augmented and unaugmented data wrt the objective in Eq. 7, with the Q-target of the Bellman equation computed from an unaugmented observation $\mathbf{s}_{t+1}$. We illustrate our data-mixing strategy by the $\otimes$ operator.

5.1 Architectural Overview

An overview of the SVEA architecture is provided in Figure 2. Our method leverages properties of common neural network architectures used in off-policy RL without introducing additional learnable parameters. We subdivide the neural network layers and corresponding learnable parameters of a state-action value function into sub-networks f_θ (denoted the state *encoder*) and Q_θ (denoted the *Q-function*) s.t $q_t \triangleq Q_\theta(f_\theta(\mathbf{s}_t), \mathbf{a}_t)$ is the predicted Q-value corresponding to a given state-action pair $(\mathbf{s}_t, \mathbf{a}_t)$. We similarly define the target state-action value function s.t. $q_t^{\text{tgt}} \triangleq r(\mathbf{s}_t, \mathbf{a}_t) + \gamma \max_{\mathbf{a}'} Q_\psi^{\text{tgt}}(f_\psi^{\text{tgt}}(\mathbf{s}_{t+1}), \mathbf{a}')$ is the target Q-value for $(\mathbf{s}_t, \mathbf{a}_t)$, and we define parameters ψ as an exponential moving average of θ as in Eq. 2. Depending on the choice of underlying algorithm, we may choose to additionally learn a parameterized policy π_θ that shares encoder parameters with Q_θ and selects actions $\mathbf{a}_t \sim \pi_\theta(\cdot | f_\theta(\mathbf{s}_t))$.

To circumvent erroneous bootstrapping from augmented data (as discussed in Section 4), we strictly apply data augmentation in Q-value estimation of the *current* state $\mathbf{s}_t$, *without* applying data augmentation to the successor state $\mathbf{s}_{t+1}$ used in Eq. 1 for bootstrapping with Q_ψ^{tgt} (and π_θ if applicable), which addresses Pitfall 1. If π_θ is learned (i.e. SVEA is implemented with an actor-critic algorithm), we also optimize it strictly from unaugmented data. To mitigate over-regularization in optimization of f_θ and Q_θ (Pitfall 2), we further employ a novel Q-objective that leverages both augmented and unaugmented data, which we introduce in the following section.

5.2 Learning Objective

Our method redefines the temporal difference objective from Eq. 1 to better leverage data augmentation. First, recall that $q_t^{\text{tgt}} = r(\mathbf{s}_t, \mathbf{a}_t) + \gamma \max_{\mathbf{a}'} Q_\psi^{\text{tgt}}(f_\psi^{\text{tgt}}(\mathbf{s}_{t+1}), \mathbf{a}')$. Instead of learning to predict q_t^{tgt} only from state $\mathbf{s}_t$, we propose to minimize a linear combination of $\mathcal{L}_Q$ over two individual data streams, $\mathbf{s}_t$ and $\mathbf{s}_t^{\text{aug}} = \tau(\mathbf{s}_t, \nu)$, $\nu \sim \mathcal{V}$, which we define as the objective

$$\mathcal{L}_Q^{\text{SVEA}}(\theta, \psi) \triangleq \alpha \mathcal{L}_Q\left(\mathbf{s}_t, q_t^{\text{tgt}}; \theta, \psi\right) + \beta \mathcal{L}_Q\left(\mathbf{s}_t^{\text{aug}}, q_t^{\text{tgt}}; \theta, \psi\right) \tag{3}$$

$$= \mathbb{E}_{\mathbf{s}_t, \mathbf{a}_t, \mathbf{s}_{t+1} \sim \mathcal{B}}\left[\alpha \left\|Q_\theta(f_\theta(\mathbf{s}_t), \mathbf{a}_t) - q_t^{\text{tgt}}\right\|_2^2 + \beta \left\|Q_\theta(f_\theta(\mathbf{s}_t^{\text{aug}}), \mathbf{a}_t) - q_t^{\text{tgt}}\right\|_2^2\right], \tag{4}$$

where α, β are constant coefficients that balance the ratio of the unaugmented and augmented data streams, respectively, and q_t^{tgt} is computed strictly from unaugmented data. $\mathcal{L}_Q^{\text{SVEA}}(\theta, \psi)$ serves as a *data-mixing* strategy that oversamples unaugmented data as an implicit variance reduction technique. As we will verify empirically in Section 6, data-mixing is a simple and effective technique for variance reduction that works well in tandem with our proposed modifications to bootstrapping. For $\alpha = \beta$, the objective in Eq. 4 can be evaluated in a single, batched forward-pass by rewriting it as:

$$\mathbf{g}_t = [\mathbf{s}_t, \tau(\mathbf{s}_t, \nu)]_{\text{N}} \tag{5}$$

$$h_t = \left[q_t^{\text{tgt}}, q_t^{\text{tgt}}\right]_{\text{N}} \tag{6}$$

$$\mathcal{L}_Q^{\text{SVEA}}(\theta, \psi) = \mathbb{E}_{\mathbf{s}_t, \mathbf{a}_t, \mathbf{s}_{t+1} \sim \mathcal{B}, \nu \sim \mathcal{V}}\left[(\alpha + \beta) \|Q_\theta(f_\theta(\mathbf{g}_t), \mathbf{a}_t) - h_t\|_2^2\right], \tag{7}$$

where $[\cdot]_N$ is a concatenation operator along the batch dimension N for $\mathbf{s}_t, \mathbf{s}_t^{\text{aug}} \in \mathbb{R}^{N \times C \times H \times W}$ and $q_t^{\text{tgt}} \in \mathbb{R}^{N \times 1}$, which is illustrated as $\otimes$ in Figure 2. Empirically, we find $\alpha = 0.5, \beta = 0.5$ to be both effective and practical to implement. If the base algorithm of choice learns a policy π_θ, its objective $\mathcal{L}_\pi(\theta)$ is optimized solely on unaugmented states $\mathbf{s}_t$ without changes to the objective, and a stop-grad operation is applied after f_θ to prevent non-stationary gradients of $\mathcal{L}_\pi(\theta)$ from interfering with Q-value estimation, i.e. only the objective from Eq. 4 or optionally Eq. 7 updates f_θ using stochastic gradient descent. As described in Section 5.1, parameters ψ are updated using an exponential moving average of θ and a stop-grad operation is therefore similarly applied after Q_ψ^{tgt}. We summarize our method for $\alpha = \beta$ applied to a generic off-policy algorithm in Algorithm 1.

Algorithm 1 Generic **SVEA** off-policy algorithm (▶ naïve augmentation, ▶ our modifications)

$\quad$ θ, θ_π, ψ: randomly initialized network parameters, $\psi \longleftarrow \theta$ $\qquad \triangleright$ Initialize ψ to be equal to θ
$\quad$ η, ζ: learning rate and momentum coefficient
$\quad$ α, β: loss coefficients, *default:* $(\alpha = 0.5, \beta = 0.5)$
1: **for** timestep $t = 1...T$ **do**
$\quad$ **act:**
2: $\quad$ $\mathbf{a}_t \sim \pi_\theta(\cdot | f_\theta(\mathbf{s}_t))$ $\qquad\qquad\qquad\qquad\qquad\qquad \triangleright$ Sample action from policy
3: $\quad$ $\mathbf{s}_t' \sim \mathcal{P}(\cdot | \mathbf{s}_t, \mathbf{a}_t)$ $\qquad\qquad\qquad\qquad\qquad \triangleright$ Sample transition from environment
4: $\quad$ $\mathcal{B} \leftarrow \mathcal{B} \cup (\mathbf{s}_t, \mathbf{a}_t, r(\mathbf{s}_t, \mathbf{a}_t), \mathbf{s}_t')$ $\qquad\qquad\qquad \triangleright$ Add transition to replay buffer
$\quad$ **update:**
5: $\quad$ $\{\mathbf{s}_i, \mathbf{a}_i, r(\mathbf{s}_i, \mathbf{a}_i), \mathbf{s}_i' \mid i = 1...N\} \sim \mathcal{B}$ $\qquad\qquad \triangleright$ Sample batch of transitions
6: $\quad$ $\color{red}{\mathbf{s}_i = \tau(\mathbf{s}_i, \nu_i), \ \mathbf{s}_i' = \tau(\mathbf{s}_i', \nu_i'), \ \nu_i, \nu_i' \sim \mathcal{V}}$ $\qquad$ $\color{red}{\blacktriangleright}$ Naïve application of data augmentation
7: $\quad$ **for** transition $i = 1..N$ **do**
8: $\quad\quad$ $\theta_\pi \longleftarrow \theta_\pi - \eta \nabla_{\theta_\pi} \mathcal{L}_\pi(\mathbf{s}_i; \theta_\pi)$ (if applicable) $\qquad \triangleright$ Optimize π_θ with SGD
9: $\quad\quad$ $q_i^{\text{tgt}} = r(\mathbf{s}_i, \mathbf{a}_i) + \gamma \max_{\mathbf{a}_i'} Q_\psi^{\text{tgt}}(f_\psi^{\text{tgt}}(\mathbf{s}_i'), \mathbf{a}_i')$ $\qquad\quad \triangleright$ Compute Q-target
10: $\quad\quad$ $\color{blue}{\mathbf{s}_i^{\text{aug}} = \tau(\mathbf{s}_i, \nu_i), \ \nu_i \sim \mathcal{V}}$ $\qquad\qquad\qquad$ $\color{blue}{\blacktriangleright}$ Apply stochastic data augmentation
11: $\quad\quad$ $\color{blue}{\mathbf{g}_i = [\mathbf{s}_i, \mathbf{s}_i^{\text{aug}}]_N, \ h_i = [q_i^{\text{tgt}}, q_i^{\text{tgt}}]_N}$ $\qquad\qquad\qquad$ $\color{blue}{\blacktriangleright}$ Pack data streams
12: $\quad\quad$ $\color{blue}{\theta \longleftarrow \theta - \eta \nabla_\theta \mathcal{L}_Q^{\text{SVEA}}(\mathbf{g}_i, h_i; \theta, \psi)}$ $\qquad\quad$ $\color{blue}{\blacktriangleright}$ Optimize f_θ and Q_θ with SGD
13: $\quad\quad$ $\psi \longleftarrow (1 - \zeta)\psi + \zeta\theta$ $\qquad\qquad\qquad\qquad\quad \triangleright$ Update ψ using EMA of θ

---

6 Experiments

We evaluate both sample efficiency, asymptotic performance, and generalization of our method and a set of strong baselines in tasks from DeepMind Control Suite (DMControl) [55] as well as a set of robotic manipulation tasks. DMControl offers challenging and diverse continuous control tasks and is widely used as a benchmark for image-based RL [16, 15, 66, 50, 28, 26]. To evaluate generalization of our method and baselines, we test methods under challenging distribution shifts (as illustrated in Figure 3) from the DMControl Generalization Benchmark (DMControl-GB) [18], the Distracting Control Suite (DistractingCS) [51], as well as distribution shifts unique to the robotic manipulation environment. Code to replicate our experiments will be made available.

Figure 3. **Experimental setup.** Agents are trained in a fixed environment (the *training* environment) and are expected to generalize to novel environments with e.g. random colors, backgrounds, and camera poses.

Setup. We implement our method and baselines using SAC [14] as base algorithm, and we apply random shift augmentation to all methods by default, which makes our base algorithm equivalent to DrQ [26]. Network architecture and hyperparameters are adopted from [18], and observations are stacks of 3 RGB frames of size $84 \times 84 \times 3$. In our DMControl-GB and DistractingCS experiments, all methods are trained for 500k frames[1] and evaluated on the full set of tasks proposed in DMControl-GB. For simplicity, we adopt the same experimental setup for robotic manipulation. The reader is referred to the supplementary material for further details on the experimental setup.

---

[1]Note that some works using DMControl evaluate after 500k *simulation steps*, which is comparably less frames for a frame skip > 1. We follow the experimental setup of previous work on generalization [17, 18, 61].

Figure 4. **Training and test performance.** We compare SVEA to DrQ with and without random convolution augmentation, as well as a set of ablations. *Data-mixing only* indiscriminately applies our data-mixing strategy to all data streams, and $(\alpha = 0, \beta = 1)$ only augments Q-predictions but without data-mixing. We find both components to contribute to SVEA's success. *Top:* episode return on the training environment during training. *Bottom:* generalization measured by episode return on the `color_hard` benchmark of DMControl-GB. Mean of 5 seeds, shaded area is ± 1 std. deviation.

Baselines and data augmentations. We benchmark our method against the following strong baselines: (1) **CURL** [50], a contrastive learning method for RL; (2) **RAD** that applies a random crop; (3) **DrQ** that applies a random shift; (4) **PAD** [17] that adapts to test environments using self-supervision; (5) **SODA** [18] that applies data augmentation in auxiliary learning; as well as a number of ablations. We experiment with a diverse set of data augmentations proposed in previous work on RL and computer vision, namely random *shift* [26], random convolution (denoted *conv*) [29], random *overlay* [18], random *cutout* [7], Gaussian *blur*, random *affine-jitter*, and random *rotation* [28, 12]. We provide samples for all data augmentations and test environments in the supplementary material.

6.1 Stability and Generalization on DMControl

We evaluate sample efficiency, asymptotic performance, and generalization of SVEA, DrQ, and a set of ablations across all 5 tasks from DMControl-GB, and report training and test curves in Figure 4. SVEA *outperforms all baselines* on the test environment – often by a large margin – and maintains a sample efficiency comparable to DrQ trained without strong augmentation, while DrQ degrades substantially when using the additional *conv* augmentation. We examine the reason for SVEA's success with the following two ablations: a *data-mixing only* variant that applies our data-mixing strategy in both $Q_\theta, Q_\psi^{\text{tgt}}$, and π_θ, as well as a variant of SVEA that only

Figure 5. **Data augmentations.** Training performance of SVEA (top) and DrQ (bottom) under 6 common data augmentations. Mean of 5 seeds. Red line for visual guidance.

applies augmentation in Q_θ but does not apply data-mixing. We find that both components of SVEA are necessary to achieve both stability *and* the generalization benefits of strong data augmentation. We further evaluate the stability of SVEA and DrQ under 6 common data augmentations; results are shown in Figure 5. While the sample efficiency of DrQ degrades substantially for most augmentations, SVEA is relatively unaffected by the choice of data augmentation and improves sample efficiency *in all 18 instances*. See supplementary material for a per-augmentation comparison. Because we empirically find the *conv* augmentation to be particularly difficult to optimize, we provide additional stability experiments in Section 6.2 and 6.3 using this augmentation.

Table 1. **Comparison to state-of-the-art.** Test performance (episode return) of methods trained in a fixed environment and evaluated on: *(top)* randomized colors; and *(bottom)* natural video backgrounds as visual distraction. Results for CURL, RAD, PAD, and SODA are obtained from [18] and we report mean and std. deviation of 5 seeds. SVEA achieves competitive results in all tasks considered.

DMControl-GB (random colors)	CURL	RAD	DrQ	PAD	SODA (conv)	SODA (overlay)	**SVEA** (conv)	**SVEA** (overlay)
walker, walk	445 ±99	400 ±61	520 ±91	468 ±47	697 ±66	692 ±68	**760** ±**145**	749 ±61
walker, stand	662 ±54	644 ±88	770 ±71	797 ±46	930 ±12	893 ±12	**942** ±**26**	933 ±24
cartpole, swingup	454 ±110	590 ±53	586 ±52	630 ±63	831 ±21	805 ±28	**837** ±**23**	832 ±23
ball_in_cup, catch	231 ±92	541 ±29	365 ±210	563 ±50	892 ±37	949 ±19	**961** ±**7**	959 ±5
finger, spin	691 ±12	667 ±154	776 ±134	803 ±72	901 ±51	793 ±128	**977** ±**5**	972 ±6

DMControl-GB (natural videos)	CURL	RAD	DrQ	PAD	SODA (conv)	SODA (overlay)	**SVEA** (conv)	**SVEA** (overlay)
walker, walk	556 ±133	606 ±63	682 ±89	717 ±79	635 ±48	768 ±38	612 ±144	**819** ±**71**
walker, stand	852 ±75	745 ±146	873 ±83	935 ±20	903 ±56	955 ±13	795 ±70	**961** ±**8**
cartpole, swingup	404 ±67	373 ±72	485 ±105	521 ±76	474 ±143	758 ±62	606 ±85	**782** ±**27**
ball_in_cup, catch	316 ±119	481 ±26	318 ±157	436 ±55	539 ±111	**875** ±**56**	659 ±110	871 ±106
finger, spin	502 ±19	400 ±64	533 ±119	691 ±80	363 ±185	695 ±97	764 ±86	**808** ±**33**

Figure 6. (Left) **DistractingCS.** Mean episode return as a function of randomization intensity, aggregated across 5 seeds for each of the 5 tasks from DMControl-GB. SVEA improves generalization at all intensities. *(Right)* **RL with Vision Transformers.** Training and test performance (`color_hard`) of SVEA and DrQ using ViT encoders. Mean of 5 seeds, shaded area is ±1 std. deviation. SVEA remains stable under data augmentation and improves generalization substantially.

To benchmark the generalization ability of SVEA, we compare its test performance to 5 recent state-of-the-art methods for image-based RL on the challenging `color_hard` and `video_easy` benchmarks from DMControl-GB, and report results in Table 1. All methods use the same architecture and hyperparameters whenever applicable, and we here use *conv* and *overlay* augmentations for fair comparison to SODA. SVEA outperforms all methods considered in **9** out of **10** instances, and at a significantly lower computational cost than CURL, PAD, and SODA that learn auxiliary tasks. We further evaluate generalization on DistractingCS, an extremely challenging benchmark for generalization where camera pose, background, and colors are continually changing throughout an episode. Figure 6 (left) shows a comparison of SVEA with *conv* and *overlay* augmentations to DrQ over a range of gradually increasing intensity of distractions, averaged across all 5 tasks from DMControl-GB. SVEA improves generalization by **42**% at low intensity, and degrades significantly slower than DrQ for high intensities. Additional results are provided in the supplementary material.

6.2 RL with Vision Transformers

Vision Transformers (ViT) [8] have recently achieved impressive results on downstream tasks in computer vision. We replace all convolutional layers from the previous experiments with a 4-layer ViT encoder that operates on raw pixels in 8×8 space-time patches, and evaluate our method using data augmentation in conjunction with ViT encoders; see supplementary material for details. Results are shown in Figure 6 (right). We are, to the best of our knowledge, the first to successfully solve image-based RL tasks without CNNs. We observe that DrQ overfits significantly to the training environment compared to its CNN counterpart. SVEA achieves comparable sample efficiency and improves generalization by **706**% and **233**% on *Walker, walk* and *Cartpole, swingup*, respectively, over DrQ, while DrQ + conv remains unstable. Interestingly, we observe that our ViT-based implementation of SVEA achieves a mean episode return of **877** on the `color_hard` benchmark of the challenging *Walker, walk* task (vs. **760** using a CNN). SVEA might therefore be a promising technique for future RL studies with CNN-free architectures, where data augmentation appears to be especially important.

6.3 Robotic Manipulation

We additionally consider a set of goal-conditioned robotic manipulation tasks using a simulated Kinova Gen3 arm: (i) *reach*, a task in which the robot needs to position its gripper above a goal indicated by a red mark; (ii) *reach moving target*, a task similar to (i) but where the robot needs to follow a red mark moving continuously in a zig-zag pattern at a random velocity; and (iii) *push*, a task in which the robot needs to push a cube to a red mark. The initial configuration of gripper, object, and goal is randomized, the agent uses 2D positional control, and policies are trained using dense rewards. Observations are stacks of RGB frames with no access to state information. Training and test environments are shown in Figure 7; see supplementary material for extended task descriptions.

Results are shown in Figure 8 and Table 2. SVEA trained with *conv* augmentation exhibits similar stability and sample efficiency as DrQ trained without, while DrQ +

Figure 7. **Robotic manipulation.** Agents are trained in a fixed environment and evaluated on challenging environments with randomized colors, lighting, background, and camera pose.

Figure 8. **Stability.** Training performance (episode return) of SVEA and DrQ in 3 robotic manipulation tasks. Mean and std. deviation of 5 seeds. Success rates are shown in Table 2.

Table 2. **Generalization in robotic manipulation.** Task success rate in 25 different test environments with randomized camera pose, colors, lighting, and background. Mean of 5 seeds.

Robotic manipulation	reach (train)	reach (test)	mv.trg. (train)	mv.trg. (test)	push (train)	push (test)
DrQ	**1.00**	0.60	**1.00**	0.69	**0.76**	0.26
DrQ + conv	0.59	0.77	0.60	0.89	0.13	0.12
SVEA w/ conv	**1.00**	**0.89**	**1.00**	**0.96**	0.72	**0.48**

conv is found to have poor sample efficiency and fails to solve the challenging *push* task. SVEA outperforms both baselines in terms of generalization. Interestingly, we find that naïve application of data augmentation has a higher success rate in test environments than the DrQ baseline, despite being less successful in the training environment, which we conjecture is because it is optimized only from augmented data. Conversely, SVEA achieves high success rates during both training and testing.

Conclusion. SVEA is found to greatly improve both stability and sample efficiency under augmentation, while achieving competitive generalization results. Our experiments indicate that our method scales to ViT-based architectures, and it may therefore be a promising technique for large-scale RL experiments where data augmentation is expected to play an increasingly important role.

Broader Impact. While our contribution aims to *reduce* computational cost of image-based RL, we remain concerned about the growing ecological and economical footprint of deep learning – and RL in particular – with increasingly large models such as ViT; see supplementary material.

References

[1] Rishabh Agarwal, Marlos C. Machado, P. S. Castro, and Marc G. Bellemare. Contrastive behavioral similarity embeddings for generalization in reinforcement learning. *ArXiv*, abs/2101.05265, 2021. 2

[2] Richard Bellman. A markovian decision process. *Journal of Mathematics and Mechanics*, 6(5):679–684, 1957. 3

[3] Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemyslaw Debiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Christopher Hesse, R. Józefowicz, Scott Gray, Catherine Olsson, Jakub W. Pachocki, Michael Petrov, Henrique Pondé de Oliveira Pinto, Jonathan Raiman, Tim Salimans, Jeremy Schlatter, J. Schneider, S. Sidor, Ilya Sutskever, Jie Tang, F. Wolski, and Susan Zhang. Dota 2 with large scale deep reinforcement learning. *ArXiv*, abs/1912.06680, 2019. 1

[4] Yevgen Chebotar, A. Handa, Viktor Makoviychuk, M. Macklin, J. Issac, Nathan D. Ratliff, and D. Fox. Closing the sim-to-real loop: Adapting simulation randomization with real world experience. *2019 International Conference on Robotics and Automation (ICRA)*, pages 8973–8979, 2019. 2

[5] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations, 2020. 2

[6] K. Cobbe, Oleg Klimov, Christopher Hesse, Taehoon Kim, and John Schulman. Quantifying generalization in reinforcement learning. In *ICML*, 2019. 1

[7] Karl Cobbe, Oleg Klimov, Chris Hesse, Taehoon Kim, and John Schulman. Quantifying generalization in reinforcement learning, 2018. 2, 7

[8] A. Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, M. Dehghani, Matthias Minderer, G. Heigold, S. Gelly, Jakob Uszkoreit, and N. Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. *ArXiv*, abs/2010.11929, 2020. 9

[9] Jesse Farebrother, Marlos C. Machado, and Michael H. Bowling. Generalization and regularization in dqn. *ArXiv*, abs/1810.00123, 2018. 1

[10] Meire Fortunato, M. G. Azar, Bilal Piot, Jacob Menick, Ian Osband, A. Graves, Vlad Mnih, R. Munos, D. Hassabis, O. Pietquin, C. Blundell, and S. Legg. Noisy networks for exploration. *ArXiv*, abs/1706.10295, 2018. 2, 3

[11] Scott Fujimoto, H. V. Hoof, and D. Meger. Addressing function approximation error in actor-critic methods. *ArXiv*, abs/1802.09477, 2018. 1, 2, 3, 4

[12] Spyros Gidaris, Praveer Singh, and Nikos Komodakis. Unsupervised representation learning by predicting image rotations, 2018. 7

[13] R. Givan, T. Dean, and M. Greig. Equivalence notions and model minimization in markov decision processes. *Artif. Intell.*, 147:163–223, 2003. 3

[14] Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. *arXiv preprint arXiv:1801.01290*, 2018. 1, 3, 4, 6

[15] Danijar Hafner, T. Lillicrap, Jimmy Ba, and Mohammad Norouzi. Dream to control: Learning behaviors by latent imagination. *ArXiv*, abs/1912.01603, 2020. 6

[16] Danijar Hafner, T. Lillicrap, Ian S. Fischer, R. Villegas, David R Ha, H. Lee, and James Davidson. Learning latent dynamics for planning from pixels. *ArXiv*, abs/1811.04551, 2019. 6

[17] Nicklas Hansen, Yu Sun, Pieter Abbeel, Alexei A. Efros, Lerrel Pinto, and Xiaolong Wang. Self-supervised policy adaptation during deployment. 2020. 2, 6, 7

[18] Nicklas Hansen and Xiaolong Wang. Generalization in reinforcement learning by soft data augmentation. In *International Conference on Robotics and Automation*, 2021. 2, 6, 7, 8

[19] H. V. Hasselt, A. Guez, Matteo Hessel, V. Mnih, and D. Silver. Learning values across many orders of magnitude. In *NIPS*, 2016. 2, 3

[20] H. V. Hasselt, A. Guez, and D. Silver. Deep reinforcement learning with double q-learning. In *AAAI*, 2016. 2, 3

[21] M. Hausknecht and P. Stone. Deep recurrent q-learning for partially observable mdps. In *AAAI Fall Symposia*, 2015. 2, 3

[22] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross B. Girshick. Momentum contrast for unsupervised visual representation learning. *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 9726–9735, 2020. 2

[23] Matteo Hessel, Joseph Modayil, H. V. Hasselt, Tom Schaul, Georg Ostrovski, Will Dabney, Dan Horgan, Bilal Piot, M. G. Azar, and D. Silver. Rainbow: Combining improvements in deep reinforcement learning. In *AAAI*, 2018. 2, 3

[24] Max Jaderberg, Volodymyr Mnih, Wojciech Marian Czarnecki, Tom Schaul, Joel Z Leibo, David Silver, and Koray Kavukcuoglu. Reinforcement learning with unsupervised auxiliary tasks, 2016. 2

[25] Leslie Pack Kaelbling, Michael L. Littman, and Anthony R. Cassandra. Planning and acting in partially observable stochastic domains. *Artificial Intelligence*, 1998. 3

[26] Ilya Kostrikov, Denis Yarats, and Rob Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. 2020. 1, 2, 3, 4, 6, 7

[27] K. G. Larsen and A. Skou. Bisimulation through probabilistic testing (preliminary report). In *Proceedings of the 16th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, 1989. 3

[28] Michael Laskin, Kimin Lee, Adam Stooke, Lerrel Pinto, Pieter Abbeel, and Aravind Srinivas. Reinforcement learning with augmented data. *arXiv preprint arXiv:2004.14990*, 2020. 1, 2, 4, 6, 7

[29] Kimin Lee, Kibok Lee, Jinwoo Shin, and Honglak Lee. A simple randomization technique for generalization in deep reinforcement learning. *ArXiv*, abs/1910.05396, 2019. 2, 7

[30] Sergey Levine, Chelsea Finn, Trevor Darrell, and Pieter Abbeel. End-to-end training of deep visuomotor policies. *The Journal of Machine Learning Research*, 17(1):1334–1373, 2016. 1

[31] T. Lillicrap, J. Hunt, A. Pritzel, N. Heess, T. Erez, Y. Tassa, D. Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *CoRR*, abs/1509.02971, 2016. 1, 2, 3, 4

[32] L. J. Lin. Self-improving reactive agents based on reinforcement learning, planning and teaching. *Machine Learning*, 8:293–321, 2004. 3

[33] Xingyu Lin, Harjatin Singh Baweja, George Kantor, and David Held. Adaptive auxiliary task weighting for reinforcement learning. *Advances in neural information processing systems*, 32, 2019. 2

[34] Clare Lyle, Mark Rowland, Georg Ostrovski, and Will Dabney. On the effect of auxiliary tasks on representation dynamics. In *AISTATS*, 2021. 2

[35] P. Mirowski, Razvan Pascanu, Fabio Viola, Hubert Soyer, Andy Ballard, Andrea Banino, Misha Denil, R. Goroshin, L. Sifre, K. Kavukcuoglu, D. Kumaran, and R. Hadsell. Learning to navigate in complex environments. *ArXiv*, abs/1611.03673, 2017. 1

[36] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013. 1, 2, 3, 4

[37] Mehdi Noroozi and Paolo Favaro. Unsupervised learning of visual representations by solving jigsaw puzzles. In *European Conference on Computer Vision*, pages 69–84. Springer, 2016. 2

[38] Deepak Pathak, Dhiraj Gandhi, and A. Gupta. Self-supervised exploration via disagreement. *ArXiv*, abs/1906.04161, 2019. 2

[39] Deepak Pathak, Philipp Krahenbuhl, Jeff Donahue, Trevor Darrell, and Alexei A Efros. Context encoders: Feature learning by inpainting. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2536–2544, 2016. 2

[40] Xue Bin Peng, Marcin Andrychowicz, Wojciech Zaremba, and Pieter Abbeel. Sim-to-real transfer of robotic control with dynamics randomization. *2018 IEEE International Conference on Robotics and Automation (ICRA)*, May 2018. 2

[41] Lerrel Pinto, Marcin Andrychowicz, Peter Welinder, Wojciech Zaremba, and Pieter Abbeel. Asymmetric actor critic for image-based robot learning. *arXiv preprint arXiv:1710.06542*, 2017. 1, 2

[42] Roberta Raileanu, M. Goldstein, Denis Yarats, Ilya Kostrikov, and R. Fergus. Automatic data augmentation for generalization in deep reinforcement learning. *ArXiv*, abs/2006.12862, 2020. 1, 2

[43] Fabio Ramos, Rafael Possas, and Dieter Fox. Bayessim: Adaptive domain randomization via probabilistic inference for robotics simulators. *Robotics: Science and Systems XV*, Jun 2019. 2

[44] Tom Schaul, John Quan, Ioannis Antonoglou, and D. Silver. Prioritized experience replay. *CoRR*, abs/1511.05952, 2016. 2, 3

[45] Max Schwarzer, Ankesh Anand, Rishab Goel, R Devon Hjelm, Aaron Courville, and Philip Bachman. Data-efficient reinforcement learning with self-predictive representations. *arXiv preprint arXiv:2007.05929*, 2020. 2, 4

[46] Ramanan Sekar, Oleh Rybkin, Kostas Daniilidis, Pieter Abbeel, Danijar Hafner, and Deepak Pathak. Planning to explore via self-supervised world models, 2020. 2

[47] Evan Shelhamer, Parsa Mahmoudieh, Max Argus, and Trevor Darrell. Loss is its own reward: Self-supervision for reinforcement learning. *ArXiv*, abs/1612.07307, 2017. 2

[48] Connor Shorten and T. Khoshgoftaar. A survey on image data augmentation for deep learning. *Journal of Big Data*, 6:1–48, 2019. 1

[49] Xingyou Song, Yiding Jiang, Stephen Tu, Yilun Du, and Behnam Neyshabur. Observational overfitting in reinforcement learning. *ArXiv*, abs/1912.02975, 2020. 1

[50] Aravind Srinivas, Michael Laskin, and Pieter Abbeel. Curl: Contrastive unsupervised representations for reinforcement learning. *arXiv preprint arXiv:2004.04136*, 2020. 2, 6, 7

[51] Austin Stone, Oscar Ramirez, K. Konolige, and Rico Jonschkowski. The distracting control suite - a challenging benchmark for reinforcement learning from pixels. *ArXiv*, abs/2101.02722, 2021. 2, 6

[52] Adam Stooke, Kimin Lee, Pieter Abbeel, and Michael Laskin. Decoupling representation learning from reinforcement learning. arXiv:2004.14990. 2, 4

[53] R. Sutton. Learning to predict by the methods of temporal differences. *Machine Learning*, 3:9–44, 2005. 3

[54] Richard S. Sutton and Andrew G. Barto. *Reinforcement Learning: An Introduction*. The MIT Press, second edition, 2018. 2, 4

[55] Yuval Tassa, Yotam Doron, Alistair Muldal, Tom Erez, Yazhe Li, Diego de Las Casas, David Budden, Abbas Abdolmaleki, Josh Merel, Andrew Lefrancq, Timothy Lillicrap, and Martin Riedmiller. DeepMind control suite. Technical report, DeepMind, January 2018. 2, 6

[56] Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive multiview coding. *arXiv preprint arXiv:1906.05849*, 2019. 2

[57] Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. *2017 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, Sep 2017. 1, 2

[58] Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding, 2018. 2

[59] Oriol Vinyals, I. Babuschkin, Wojciech Czarnecki, Michaël Mathieu, Andrew Dudzik, J. Chung, D. Choi, Richard Powell, Timo Ewalds, P. Georgiev, Junhyuk Oh, Dan Horgan, M. Kroiss, Ivo Danihelka, Aja Huang, L. Sifre, Trevor Cai, J. Agapiou, Max Jaderberg, A. Vezhnevets, Rémi Leblond, Tobias Pohlen, Valentin Dalibard, D. Budden, Yury Sulsky, James Molloy, T. Paine, Caglar Gulcehre, Ziyu Wang, T. Pfaff, Yuhuai Wu, Roman Ring, Dani Yogatama, Dario Wünsch, Katrina McKinney, Oliver Smith, Tom Schaul, T. Lillicrap, K. Kavukcuoglu, D. Hassabis, C. Apps, and D. Silver. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, pages 1–5, 2019. 1

[60] K. Wang, Bingyi Kang, Jie Shao, and Jiashi Feng. Improving generalization in reinforcement learning with mixture regularization. *ArXiv*, abs/2010.10814, 2020. 2

[61] Xudong Wang, Long Lian, and Stella X. Yu. Unsupervised visual attention and invariance for reinforcement learning. *ArXiv*, abs/2104.02921, 2021. 2, 6

[62] Ziyu Wang, Tom Schaul, Matteo Hessel, H. V. Hasselt, Marc Lanctot, and N. D. Freitas. Dueling network architectures for deep reinforcement learning. *ArXiv*, abs/1511.06581, 2016. 2, 3

[63] Zhirong Wu, Yuanjun Xiong, Stella X Yu, and Dahua Lin. Unsupervised feature learning via non-parametric instance discrimination. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3733–3742, 2018. 2

[64] Zhenlin Xu, Deyi Liu, Junlin Yang, and M. Niethammer. Robust and generalizable visual representation learning via random convolutions. *ArXiv*, abs/2007.13003, 2020. 2

[65] Denis Yarats, Rob Fergus, Alessandro Lazaric, and Lerrel Pinto. Reinforcement learning with prototypical representations. *arXiv preprint arXiv:2102.11271*, 2021. 2

[66] Denis Yarats, Amy Zhang, Ilya Kostrikov, Brandon Amos, Joelle Pineau, and Rob Fergus. Improving sample efficiency in model-free reinforcement learning from images, 2019. 2, 6

[67] Tianhe Yu, Saurabh Kumar, A. Gupta, Sergey Levine, Karol Hausman, and Chelsea Finn. Gradient surgery for multi-task learning. *ArXiv*, abs/2001.06782, 2020. 2

[68] A. Zhang, Rowan McAllister, R. Calandra, Y. Gal, and Sergey Levine. Learning invariant representations for reinforcement learning without reconstruction. *ArXiv*, abs/2006.10742, 2020. 2

[69] C. Zhang, Oriol Vinyals, R. Munos, and S. Bengio. A study on overfitting in deep reinforcement learning. *ArXiv*, abs/1804.06893, 2018. 1

[70] Richard Zhang, Phillip Isola, and Alexei A Efros. Colorful image colorization. In *European conference on computer vision*, pages 649–666. Springer, 2016. 2

[71] Yuke Zhu, Roozbeh Mottaghi, Eric Kolve, Joseph J Lim, Abhinav Gupta, Li Fei-Fei, and Ali Farhadi. Target-driven visual navigation in indoor scenes using deep reinforcement learning. In *ICRA*, pages 3357–3364. IEEE, 2017. 1

[72] Brian D Ziebart, Andrew Maas, J Andrew Bagnell, and Anind K Dey. Maximum entropy inverse reinforcement learning. In *Proceedings of the 23rd National Conference on Artificial Intelligence*, volume 3, 2008. 3