TRUST-SQL: Tool-Integrated Multi-Turn Reinforcement Learning for Text-to-SQL over Unknown Schemas

Abstract

Text-to-SQL parsing has achieved remarkable progress under the Full Schema Assumption. However, this premise fails in real-world enterprise environments where databases contain hundreds of tables with massive noisy metadata. Rather than injecting the full schema upfront, an agent must actively identify and verify only the relevant subset, giving rise to the **Unknown Schema** scenario we study in this work. To address this, we propose **TRUST-SQL** (**T**ruthful **R**easoning with **U**nknown **S**chema via **T**ools). We formulate the task as a **Partially Observable Markov Decision Process** where our autonomous agent employs a structured **four-phase protocol** to ground reasoning in verified metadata. Crucially, this protocol provides a structural boundary for our novel **Dual-Track GRPO** strategy. By applying token-level masked advantages, this strategy isolates exploration rewards from execution outcomes to resolve credit assignment, yielding a **9.9% relative improvement** over standard GRPO. Extensive experiments across five benchmarks demonstrate that TRUST-SQL achieves an average absolute improvement of **30.6%** and **16.6%** for the 4B and 8B variants respectively over their base models. Remarkably, despite operating entirely without pre-loaded metadata, our agent consistently **matches or surpasses strong baselines** that rely on schema prefilling.

1 Introduction

Text-to-SQL parsing, which translates natural language questions into executable SQL queries, has seen remarkable progress driven by Large Language Models (LLMs) (Shkapenyuk et al., 2025; Wang et al., 2025b). However, this progress has been achieved under a critical yet often overlooked premise, the **Full Schema Assumption**, which presupposes that the complete database schema is pre-loaded into the model's input context. Under this paradigm, the task reduces to a *static translation* problem and existing methods have achieved

Figure 1: Existing methods rely on pre-loaded schemas, while the Unknown Schema setting requires active exploration.

strong performance on standard benchmarks with pre-injected schemas (Li et al., 2024; Yu et al., 2018). Yet this assumption rarely holds in real-world enterprise environments, where databases routinely contain hundreds of tables and schemas frequently evolve through additions, deletions, and restructuring (Zhang et al., 2026). Injecting this massive, noisy, and potentially outdated metadata upfront is impractical for finite context windows and actively harmful, as irrelevant or stale tables severely distract the model. Consequently, as illustrated in Figure 1, we formalize this necessary paradigm shift as the **Unknown Schema** setting, where an agent must abandon passive consumption and autonomously explore the database to retrieve only the necessary metadata.

However, standard single-turn methods lack interactive capabilities and fail in unobservable environments. To overcome this fundamental limitation, the parsing task must be approached as a **multi-turn tool-integrated decision-making process**. While recent agentic frameworks have explored this iterative direction, they introduce new bottlenecks. Architecturally, LLMs struggle to maintain coherent reasoning across long interaction horizons. Without explicit mechanisms to ground their exploration, they frequently lose track of intermediate observations (Laban et al., 2025) and

revert to fabricating non-existent schema elements based on parametric priors. Algorithmically, assigning credit across long interaction trajectories remains a fundamental challenge for large language models (Zhou et al., 2025; Yang et al., 2026). By relying on a single terminal reward (Yang et al., 2025; Xu et al., 2025) or naively aggregating intermediate signals (Hua et al., 2026), these methods conflate the quality of schema exploration with SQL generation, making it impossible to attribute the final execution outcome to specific actions.

In this paper, we propose **TRUST-SQL** (**T**ruthful **R**easoning with **U**nknown **S**chema via **T**ools) to systematically address these challenges. To handle the unobservable database environment, we formulate the task as a Partially Observable Markov Decision Process. Within this framework, we introduce a **four-phase interaction protocol** comprising *Explore*, *Propose*, *Generate*, and *Confirm*. The *Propose* phase acts as a mandatory cognitive checkpoint that forces the agent to commit to verified metadata, thereby preventing subsequent hallucinations. Crucially, this checkpoint provides a structural boundary for **Dual-Track GRPO**, a training strategy built upon Group Relative Policy Optimization(GRPO) (DeepSeek-AI, 2025) that applies token-level masked advantages to isolate exploration and execution rewards for co-optimizing schema grounding and SQL generation.

Our contributions are summarized as follows:

- We develop **TRUST-SQL**, an autonomous framework that directly interacts with unobservable databases to retrieve and verify metadata, successfully closing the loop from unconstrained exploration to grounded SQL generation without relying on static context.

- We propose **Dual-Track GRPO**, a novel training strategy utilizing token-level masked advantages and execution-coupled schema rewards. This granular optimization yields a **9.9% relative improvement** in execution accuracy over standard GRPO on BIRD-Dev.

- Extensive experiments demonstrate that TRUST-SQL yields massive performance leaps over base models in unobservable environments. Across five diverse benchmarks, the framework achieves an average absolute improvement of **30.6%** for the 4B and **16.6%** for the 8B variant. Remarkably, despite operating without pre-loaded metadata, our models consistently match or surpass baselines that rely on schema injection.

2 Related Work

Text-to-SQL under Full Schema Assumption. Most existing methods operate under the premise of full schema observability. Supervised fine-tuning approaches such as OmniSQL (Li et al., 2025), STAR (He et al., 2025), and ROUTE (Qin et al., 2024) internalize generation capabilities but rely entirely on static context. Similarly, single-turn reinforcement learning(RL) methods (Ma et al., 2025; Yao et al., 2025; Zhang et al., 2025; Pourreza et al., 2025) optimize execution accuracy using terminal rewards while assuming the complete database structure is provided upfront. Constrained to a single-turn interaction paradigm, these models act as passive translators. Consequently, they fundamentally fail in unobservable enterprise environments where active database exploration is strictly required.

Tool-Augmented Database Exploration. To handle complex or hidden databases, recent works introduce tool-integrated exploration. Training-free frameworks (Wang et al., 2024, 2025a) leverage frozen language models to query metadata. However, without gradient updates, these agents remain susceptible to parametric hallucinations and cannot strictly enforce verification protocols. More recently, multi-turn RL approaches (Xu et al., 2025; Hua et al., 2026; Guo et al., 2025) embed SQL execution into the training loop to refine queries. While promising, these methods lack strict cognitive boundaries to enforce metadata verification and still evaluate the entire exploration trajectory using conflated terminal rewards, failing to isolate the specific signals for schema retrieval and SQL generation.

Credit Assignment in Multi-Turn RL. A central challenge in multi-turn RL is attributing the final outcome to individual actions across a long trajectory. Existing solutions explore trajectory-level optimization (Wang et al., 2025c; Xue et al., 2025), process rewards (Liu et al., 2025), tree-structured search (Ji et al., 2025), and intrinsic motivation (Kumar et al., 2024; Wan et al., 2025). These techniques are primarily designed for homogeneous action spaces where each step contributes similarly to the final goal. In Text-to-SQL, a single reward cannot distinguish whether failures stem from incorrect schema retrieval or flawed generation logic. TRUST-SQL resolves this by introducing Dual-Track GRPO to disentangle credit assignment across phases.

Figure 2: Overview of the **TRUST-SQL** framework. **(Top)** The four-phase workflow comprising *Explore*, *Propose*, *Generate*, and *Confirm*, with non-linear transitions enabling iterative schema refinement. **(Bottom)** The Dual-Track GRPO training pipeline, where trajectories are decomposed into a Schema Track τ_{schema} and a Full Track τ_{full}, each optimized with independent rewards and masked advantages.

3 Methodology

We present **TRUST-SQL** to tackle Text-to-SQL over unknown schemas. As illustrated in Figure 2, it comprises an explicit four-phase interaction protocol and a Dual-Track GRPO training strategy. We first formulate the task as a sequential decision-making process, followed by our reward design and RL optimization.

3.1 Motivation: Why a Four-Phase Protocol?

To empirically justify the design of our core interaction protocol and identify the key bottlenecks of Text-to-SQL under the **Unknown Schema setting**, we conduct a pilot study on the **BIRD-Dev** dataset with **Qwen3-8B** as the base model. We construct **three agent variants** with incremental structural constraints on interaction behavior, and classify all failure cases to derive design principles for the subsequent framework.

Protocol Variants. EC (Explore-Confirm) is a minimal baseline where the agent freely queries metadata and directly submits a SQL answer without intermediate verification. **EGC** (Explore-Generate-Confirm) introduces an **explicit Generate phase**, requiring the agent to execute a candidate SQL and observe its result before finalizing. **EPGC** (Explore-Propose-Generate-Confirm) further adds **the Propose phase** as a mandatory cognitive checkpoint, compelling the agent to commit to a verified schema before SQL generation.

Error Taxonomy. We classify failures into five categories: **(1) Hallucination**: the model fabricates non-existent tables or columns based on parametric priors; **(2) Schema Linking**: the model selects wrong or missing tables and columns despite correct exploration; **(3) Semantic**: the model correctly identifies the relevant schema but generates logically incorrect SQL; **(4) Syntax**: the SQL contains malformed statements that fail to execute; **(5) Generation**: the agent fails to produce a complete SQL, typically due to reaching the maximum turn limit.

As shown in Figure 3, three observations emerge from the results.

Obs. 1: Schema verification is critical to suppress hallucination. In EC, hallucination accounts for 26.4% of all failures. The *Generate* phase partially alleviates this via execution feedback (14.2%), but the most significant reduction occurs with the *Propose* in EPGC, driving hallucination to just 2.8%, a **9.4× reduction** over EC.

(a) Stacked error distribution. (b) EX accuracy.

Figure 3: Pilot study results on BIRD-Dev (Qwen3-8B).

Obs. 2: Schema linking is the persistent bottleneck. Schema linking errors remain consistently high across all variants, motivating our Dual-Track GRPO to provide an independent optimization signal for schema exploration.

Obs. 3: Suppressing hallucination reveals semantic errors. As hallucination decreases, semantic errors increase from 268 to 330, reflecting a distributional shift: once schema is correctly identified, complex query logic becomes the dominant challenge, motivating joint optimization of schema grounding and SQL generation.

These observations motivate the two core designs of our work: the *Propose* checkpoint to suppress hallucination, and Dual-Track GRPO to co-optimize schema exploration and SQL generation.

3.2 Problem Formulation

Based on the EPGC protocol validated in Section 3.1, we formalize the Text-to-SQL task under the Unknown Schema setting as a Partially Observable Markov Decision Process (**POMDP**), which is defined as $(\mathcal{S}, \mathcal{A}, \mathcal{T}, \mathcal{R}, \Omega, \mathcal{Z}, \gamma)$ over discrete steps $t = 0, 1, \ldots, T$.

State and Observation Spaces. The true environment state $s_t \in \mathcal{S}$ represents the complete database schema and remains hidden from the agent. Consequently, the agent only receives partial observations $o_t \in \Omega$ dictated by the observation function $\mathcal{Z}$, which consist of tool execution feedback. To navigate this unobservable environment, the agent relies on an internal context state $c_t = (q, h_t, \mathcal{K}_t)$. This context integrates the user question q, the interaction history h_t, and the **Verified Schema Knowledge** $\mathcal{K}_t$, which stores only explicitly verified metadata and initializes as $\mathcal{K}_0 = \emptyset$.

Action Space. To prevent hallucination, the agent selects actions $a_t \in \mathcal{A}$ from four strict categories based on its current context c_t. The *Explore* action

queries database metadata. The *Propose* action serves as a mandatory cognitive checkpoint at step t_{propose} to commit to the verified schema $\mathcal{K}_{t_{\text{propose}}}$. The *Generate* action produces a candidate SQL grounded in $\mathcal{K}_t$, and the *Confirm* action submits the final SQL query y at the terminal step T.

Transition and Objective. Upon executing a_t, the environment emits observation o_t and the agent updates its context state to c_{t+1}. A complete interaction sequence from the agent's perspective is represented as a trajectory $\tau = \{(c_t, a_t, o_t)\}_{t=0}^{T}$. The ultimate goal of the policy $\pi_\theta(a_t \mid c_t)$ is to maximize the expected cumulative reward $J(\theta) = \mathbb{E}_{\tau \sim \pi_\theta}[\sum_{t=0}^{T} \gamma^t r(c_t, a_t)]$.

3.3 Reward Components

To evaluate the trajectory, we define three distinct reward signals. The specific mechanism for assigning these signals to individual tokens is detailed in Section 3.4.

Execution Reward (R_{exec}). This reward evaluates the final predicted SQL y against the ground truth y^* via database execution. The reward is assigned as follows

$$R_{\text{exec}}(y, y^*) = \begin{cases} 1.0 & \text{if } \texttt{Exec}(y) = \texttt{Exec}(y^*) \\ 0.2 & \text{if } \texttt{Exec}(y) \neq \emptyset \\ 0.0 & \text{if } \texttt{Exec}(y) = \emptyset \end{cases} \tag{1}$$

where $\texttt{Exec}(y) \neq \emptyset$ denotes that the query y is executable but yields an incorrect result.

Format Reward (R_{fmt}). This constitutes a trajectory-level signal requiring consistent protocol adherence. The reward is defined as

$$R_{\text{fmt}}(\tau) = \begin{cases} 0.1 & \text{if protocol is fully adhered to} \\ 0.0 & \text{otherwise} \end{cases} \tag{2}$$

Full adherence requires that every action a_t conforms to prescribed format, all four action categories in $\mathcal{A}$ appear at least once, and no execution errors occur in the observations o_t.

Schema Reward (R_{schema}). This reward evaluates the quality of the schema exploration phase. It is computed as

$$R_{\text{schema}}(\hat{\mathcal{K}}, \mathcal{K}^*) = f_{\text{match}}(\hat{\mathcal{K}}, \mathcal{K}^*) \tag{3}$$

where $\hat{\mathcal{K}}$ represents the schema proposed by the agent at step t_{propose}, and $\mathcal{K}^*$ represents the minimal ground truth schema extracted from y^*. The function f_{match} evaluates their structural overlap.

3.4 Resolving Credit Assignment via Dual-Track GRPO

Standard RL combines exploration and generation under a single reward, making it hard to attribute success or failure to specific actions in long trajectories. We thus leverage the structural boundary of the *Propose* checkpoint to introduce **Dual-Track GRPO**, extending Group Relative Policy Optimization to clearly separate the learning signals for schema grounding and SQL generation.

Track Formulation and Rewards. For each question q, we sample G trajectories and divide each τ^i into two optimization tracks $k \in \{\text{schema}, \text{full}\}$, where the Schema Track ends at $T_{\text{schema}} = t_{\text{propose}}$ and the Full Track spans the entire interaction up to $T_{\text{full}} = T$. A dedicated reward R_k^i is assigned to each track

$$R_k^i = \begin{cases} R_{\text{schema}}(\hat{\mathcal{K}}_i, \mathcal{K}^*) & \text{if } k = \text{schema} \\ R_{\text{exec}}(y_i, y^*) + R_{\text{fmt}}(\tau^i) & \text{if } k = \text{full} \end{cases} \quad (4)$$

ensuring an independent optimization signal for exploration quality regardless of generation errors.

Masked Advantage Computation. Advantages are computed via group-relative normalization within each track

$$A_k^i = \frac{R_k^i - \mu_k}{\sigma_k + \epsilon} \quad (5)$$

where μ_k and σ_k are the mean and standard deviation of the group rewards. We apply strict token-level masking where the advantage A_k^i is broadcast exclusively to tokens generated within the active steps $t \in [0, T_k]$. This is strictly finer-grained than trajectory-level weighting, as it prevents exploration rewards from incorrectly crediting generation tokens and vice versa. Consequently, tokens generated after the *Propose* checkpoint receive zero schema advantage.

Dual-Track Loss Function. Let $\mathcal{L}_k(\theta)$ denote the GRPO loss computed over the active tokens for track k using the masked advantage A_k^i. The total objective combines both tracks

$$\mathcal{L}(\theta) = \mathcal{L}_{\text{full}}(\theta) + \lambda \cdot \mathcal{L}_{\text{schema}}(\theta) \quad (6)$$

where λ controls the relative contribution of the Schema Track. By unifying these components, Dual-Track GRPO successfully co-optimizes schema grounding and SQL generation without mixing their learning signals.

4 Experiments

4.1 Experimental Setup

Implementation Details. We adopt Qwen3-4B and Qwen3-8B as our base models and implement all experiments using the SLIME framework (Zhu et al., 2025), trained in two sequential stages of SFT warm-up followed by Dual-Track GRPO optimization. Details are provided in Appendix B.

Baselines. TRUST-SQL utilizes a highly efficient data recipe comprising 9.2k SFT samples and 11.6k RL samples. We compare our framework against recent strong baselines across the 3B to 8B parameter scales. Single-turn models include OmniSQL (Li et al., 2025) and SQL-R1 (Ma et al., 2025). Multi-turn RL methods include MTIR-SQL (Xu et al., 2025) and SQL-Trail (Hua et al., 2026). Full dataset construction and detailed baseline comparisons are provided in Appendix A.

Evaluation Benchmarks and Metrics. We evaluate on BIRD-Dev (Li et al., 2024) for large-scale schema grounding and Spider-Test (Yu et al., 2018) for compositional generalization. To stress-test model robustness, we incorporate three challenging variants. Specifically, Spider-Syn (Gan et al., 2021a) evaluates lexical robustness via synonym substitution, Spider-DK (Gan et al., 2021b) probes for implicit domain knowledge, and Spider-Realistic (Deng et al., 2021) assesses ambiguity resolution. We measure Execution Accuracy where the predicted SQL must yield the exact same database result as the ground truth. We report single-sample performance via Greedy decoding at temperature zero and execution-based Majority voting across multiple sampled queries.

4.2 Main Results

Table 1 presents the execution accuracy across all benchmarks. For the majority voting evaluation, we sample trajectories at a temperature of 0.8 with a 15-turn inference budget, as analyzed in Section 5.3. Detailed token consumption and tool invocation statistics are provided in Appendix D.1.

Performance of Compact Models. In the 3B to 4B parameter regime, TRUST-SQL delivers highly competitive performance. On the challenging BIRD-Dev benchmark, it achieves 64.9% with greedy decoding and 67.2% with majority voting, outperforming the strong MTIR-SQL-4B baseline. Furthermore, TRUST-SQL-4B consistently secures the top position on robustness benchmarks including Spider-DK and Spider-Realistic. This proves

Table 1: Execution Accuracy (EX%) across multiple benchmarks. **Gre** denotes single-sample performance; **Maj** denotes majority voting. **Bold** indicates the best result and underline indicates the second best within each group.

Method	Schema Prefill	BIRD (dev)		Spider (test)		Spider-DK		Spider-Syn		Spider-Realistic	
		Gre	Maj	Gre	Maj	Gre	Maj	Gre	Maj	Gre	Maj
3B – 4B Models											
SQL-R1-3B	✓	–	54.6	–	78.9	–	70.5	–	66.4	–	71.5
SQL-Trail-3B	✓	50.1	55.1	77.7	84.3	–	–	–	–	–	–
MTIR-SQL-4B	✓	63.1	64.4	83.4	–	71.2	–	**78.6**	–	78.7	–
TRUST-SQL-4B	✗	**64.9**	**67.2**	**82.8**	**85.0**	**71.6**	**73.8**	74.7	**77.3**	**79.9**	**82.5**
7B – 8B Models											
OmniSQL-7B	✓	63.9	66.1	**87.9**	**88.9**	76.1	77.8	69.7	69.6	76.2	78.0
SQL-R1-7B	✓	63.7	66.6	–	88.7	–	**78.1**	–	76.7	–	83.3
SQL-Trail-7B	✓	60.1	64.2	86.0	87.6	**76.8**	77.8	72.8	77.0	79.6	83.9
MTIR-SQL-8B	✓	–	64.6	83.4	–	72.9	–	77.2	–	77.4	–
TRUST-SQL-8B	✗	**65.8**	**67.7**	83.9	86.5	72.1	75.7	**75.4**	**77.4**	**82.1**	**84.1**

that its active exploration policy generalizes well to perturbed and ambiguous scenarios rather than relying on memorized schema patterns.

Performance of Mid-Scale Models. Scaling the base model to 8B further amplifies these benefits. TRUST-SQL-8B achieves the highest execution accuracy on BIRD-Dev with 65.8% for greedy decoding and 67.7% for majority voting. While baselines like OmniSQL-7B perform competitively on the standard Spider-Test set, they struggle when explicit mapping cues are removed. In contrast, TRUST-SQL-8B demonstrates significantly better generalization by outperforming all baselines on Spider-Syn and Spider-Realistic.

The Value of Autonomous Exploration. Crucially, TRUST-SQL achieves these leading scores under the strict Unknown Schema setting. All baseline models rely on full schema prefilling, which consumes substantial context windows and assumes perfect database observability. The fact that our actively exploring agent can match or surpass models with privileged schema access validates the effectiveness of our **four-phase protocol** and **Dual-Track GRPO** training.

4.3 Can Schema Prefill Boost Performance?

While TRUST-SQL operates without any pre-loaded schema, a natural question arises as to whether injecting the complete schema would further boost performance. We thus introduce a Schema Prefill variant where the full schema is delivered as a single synthetic *Explore* turn at the beginning of the interaction, providing all table

and column information at once. The case study is shown in Appendix D.

Table 2: Effect of Schema Prefill (greedy decoding). Arrows denote absolute accuracy changes compared to the Unknown Schema (×) setting.

Prefill	BIRD	Spider	S-DK	S-Syn	S-Realistic
Qwen3-4B					
✗	29.3	51.2	43.7	47.4	49.2
✓	46.3 ↑17.0	67.6 ↑16.4	57.0 ↑13.3	62.6 ↑15.2	65.9 ↑16.7
TRUST-SQL-4B					
✗	64.9	82.8	71.6	74.7	79.9
✓	64.8 ↓0.1	83.1 ↑0.3	69.2 ↓2.4	72.5 ↓2.2	80.1 ↑0.2
Qwen3-8B					
✗	47.9	67.4	56.3	58.4	66.3
✓	49.9 ↑2.0	68.3 ↑0.9	57.6 ↑1.3	64.5 ↑6.1	68.1 ↑1.8
TRUST-SQL-8B					
✗	65.8	83.9	72.1	75.4	82.1
✓	65.5 ↓0.3	84.0 ↑0.1	74.4 ↑2.3	75.4	80.5 ↓1.6

As shown in Table 2, the base Qwen3 models are highly dependent on pre-loaded metadata. Without schema prefilling, their performance collapses, evidenced by a massive 17.0% absolute drop for Qwen3-4B on BIRD. This confirms that standard models lack autonomous exploration capabilities. When equipped with our framework, TRUST-SQL overcomes this limitation and achieves massive performance leaps over the base models. For instance, TRUST-SQL-4B yields a **striking 35.6% absolute improvement** over Qwen3-4B on BIRD. Across all five benchmarks, the framework delivers an average absolute improvement of **30.6%** for the 4B variant and **16.6%** for the 8B variant compared to their respective base models under the Unknown Schema setting.

Furthermore, TRUST-SQL demonstrates remarkable independence from pre-loaded schemas. For both 4B and 8B variants, injecting the full schema upfront provides only negligible changes on BIRD and Spider. In fact, it actually degrades performance on robustness benchmarks. Specifically, TRUST-SQL-4B drops by 2.4% on Spider-DK and TRUST-SQL-8B drops by 1.6% on Spider-Realistic. The iterative policy already retrieves necessary metadata with high precision, making full schema injection redundant and often noisy. Therefore, **active exploration serves as a robust alternative** to static prefilling.

5 Analysis

5.1 How to Balance Exploration and Generation?

In the Dual-Track GRPO loss, λ controls the relative contribution of the Schema Track. We ablate $\lambda \in \{0.125, 0.25, 0.375\}$ against two single-track baselines where $\lambda = 0$. The first optimizes solely on execution outcome, and the second naively aggregates a schema reward weighted at 0.25 into the terminal reward without track separation.

(a) EX (%) during training.   (b) Avg turns during training.

Figure 4: Effect of λ on training dynamics.

As shown in Figure 4a, naively mixing the schema reward into the terminal step yields 58.7%, worse than the 60.9% achieved by the pure execution baseline. This confirms that conflating exploration and generation obscures the reward signal. In contrast, the optimal Dual-Track setting at $\lambda = 0.25$ peaks at **64.5%**, yielding a **+5.8%** gain over naive aggregation and a **+3.6%** gain over the pure execution baseline. Furthermore, λ dictates the balance between exploration and generation. While $\lambda = 0.125$ achieves a competitive 64.0%, an excessively large $\lambda = 0.375$ severely degrades performance to 54.2%. As shown in Figure 4b, this over-weighted schema reward incentivizes the agent to remain perpetually in the exploration phase, causing a sharp increase in average

interaction turns and over-optimizing metadata retrieval at the expense of SQL generation.

5.2 What Makes a Good Schema Reward?

We investigate two key design dimensions for f_{match} defined in Section 3.3: whether R_{schema} should be *coupled* with R_{exec}, and whether f_{match} should be *sparse* or *dense*. Specifically, **Sparse + Uncoupled** assigns R_{schema} regardless of R_{exec} with a binary f_{match}. **Sparse + Coupled** (**TRUST-SQL**) conditions R_{schema} on $R_{\text{exec}} = 1.0$ with the same binary criterion. **Dense + Coupled** further replaces f_{match} with a graduated function enforcing full recall as a hard gate before assigning partial precision-based rewards.

Figure 5: Ablation on schema reward formulation.

As shown in Figure 5, the three variants exhibit markedly different training dynamics. **Sparse + Uncoupled** achieves the lowest EX of 52.7% despite the highest turn count of 6.71, revealing that decoupling schema reward from execution incentivizes redundant exploration rather than precise grounding. **Dense + Coupled** reduces turns to 5.03 but converges to a suboptimal 64.0%, as the graduated f_{match} introduces conflicting gradients between maximizing recall and minimizing unnecessary columns. **Sparse + Coupled** achieves the best EX of 64.5% with a balanced turn count of 5.64, where the binary f_{match} provides an unambiguous optimization target and conditioning on $R_{\text{exec}} = 1.0$ establishes a direct causal chain between exploration quality and task success. These results indicate that *coupling* is a more critical design dimension than *reward density*.

5.3 Test-Time Scaling Behavior

We analyze the test-time scaling properties of TRUST-SQL across three dimensions.
Training Turn Budget. As illustrated in Figure 6a, expanding the training turn budget from 8 to 10 yields substantial gains on BIRD-Dev. However,

(a) Training turn budget effect. (b) Train vs. inference turn budget. (c) Pass@K scaling.

Figure 6: Test-time scaling analysis of TRUST-SQL across three dimensions: training turn budget, training vs. inference turn budget interaction, and Pass@K with repeated sampling.

further increasing to 12 turns causes severe training instability where the average turn count spikes and execution accuracy sharply declines, suggesting that an overly permissive horizon fails to penalize redundant exploration. Consequently, a 10-turn budget provides the optimal balance between accuracy and exploration efficiency.

Interaction Between Horizons. As shown in Figure 6b, a 10-turn training budget consistently yields the strongest baseline policy. Providing additional inference turns beyond the training horizon further improves performance, with the optimal configuration pairing a 10-turn training budget with a 15-turn inference budget to achieve a peak accuracy of **64.93%**. This demonstrates that the agent effectively utilizes extra test-time compute to recover from early exploration mistakes.

Scaling with Repeated Sampling. As shown in Figure 6c, all configurations exhibit monotonic accuracy improvements as the sample size K grows, driven by *exploration diversity* across independently sampled trajectories. The persistent gap between Pass@K and greedy performance indicates that the model can generate correct solutions but has not fully converged to a consistent policy, suggesting headroom for further RL training.

5.4 Is Cold-Start SFT Necessary?

TRUST-SQL adopts a two-stage training pipeline where Dual-Track GRPO is preceded by an SFT warm-up phase. To assess its necessity, we compare three training configurations. As shown in Table 3, applying Dual-Track GRPO directly without SFT warm-up yields 59.9% on BIRD and 79.6% on Spider, both significantly below the full pipeline. However, these numbers are largely illusory.Without SFT initialization, the model quickly learns to **hack the reward by exhaustively querying all tables and columns in the first turn**, completing the interaction in roughly four actions. This

degenerates the Unknown Schema setting into a disguised Full Schema scenario, bypassing genuine active exploration entirely. SFT alone achieves reasonable performance, confirming that the warm-up phase successfully instills structured exploration behavior. The full two-stage pipeline consistently achieves the best results, demonstrating that Dual-Track GRPO provides substantial gains that cannot be attributed to supervised learning alone.

Table 3: Ablation on cold-start SFT for TRUST-SQL-4B. Results are reported with greedy decoding.

Configuration	SFT	RL	BIRD (dev)	Spider (test)
SFT Only	✓	✗	46.2	66.7
RL Only	✗	✓	59.9	79.6
SFT + RL	✓	✓	**64.9**	**82.8**

6 Conclusion

In this work, we revisit the **Full Schema Assumption** that underlies Text-to-SQL research. By formalizing the task as a POMDP under the **Unknown Schema** setting, **TRUST-SQL** demonstrates that autonomous database exploration is both feasible and effective in environments where schemas are massive, noisy, and continuously evolving. The structured four-phase protocol grounds agent reasoning in actively verified metadata to prevent hallucinations, while its mandatory cognitive checkpoint provides a structural boundary for **Dual-Track GRPO** to resolve the credit assignment bottleneck, yielding a **9.9%** relative improvement over standard GRPO. Experiments across five benchmarks demonstrate average absolute improvements of **30.6%** and **16.6%** for the 4B and 8B variants respectively. Remarkably, despite operating without pre-loaded metadata, TRUST-SQL consistently matches or surpasses schema-prefilled baselines, establishing a new paradigm for reliable Text-to-SQL in unobservable environments.

Limitations

While TRUST-SQL demonstrates strong performance under the Unknown Schema setting, several limitations remain.

Inference Overhead. The multi-turn interaction paradigm naturally incurs higher inference cost compared to single-turn methods, as each interaction step involves a live database call. However, as shown in Appendix D.1, this overhead remains modest in practice. Further optimizing inference efficiency for latency-critical deployments remains a practical direction for future work.

SQLite Dialect Only. Both training and evaluation are conducted on SQLite-based benchmarks, as BIRD and Spider exclusively use SQLite. Extending to other SQL dialects such as PostgreSQL or MySQL remains a valuable direction for future work.

Fixed Turn Budget. The maximum interaction turn T is fixed at training time, which may limit exploration thoroughness for databases with exceptionally complex schemas. Adapting the turn budget dynamically based on database complexity remains an interesting direction for future work.

Reproducibility Statement

To ensure full reproducibility, we release the complete source code at `https://anonymous.4open.science/r/TrustSQL-0902`. All dataset construction pipelines are detailed in Appendix A, training hyperparameters and hardware specifications are summarized in Appendix B. All experiments are conducted on NVIDIA A100 GPUs. Upon acceptance, we will publicly release the training datasets and model weights to further support the research community.

References

Google DeepMind. 2025. Gemini 2.5 pro. `https://deepmind.google/technologies/gemini/pro`.

DeepSeek-AI. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

DeepSeek-AI. 2025. Deepseek-v3 technical report. *Preprint*, arXiv:2412.19437.

Xiang Deng, Ahmed Hassan Awadallah, Christopher Meek, Oleksandr Polozov, Huan Sun, and Matthew Richardson. 2021. Structure-grounded pretraining for text-to-sql. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, page 1337–1350. Association for Computational Linguistics.

Yujian Gan, Xinyun Chen, Qiuping Huang, Matthew Purver, John R. Woodward, Jinxia Xie, and Pengsheng Huang. 2021a. Towards robustness of text-to-SQL models against synonym substitution. pages 2505–2515, Online. Association for Computational Linguistics.

Yujian Gan, Xinyun Chen, and Matthew Purver. 2021b. Exploring underexplored limitations of cross-domain text-to-sql generalization. *Preprint*, arXiv:2109.05157.

Taicheng Guo, Hai Wang, ChaoChun Liu, Mohsen Golalikhani, Xin Chen, Xiangliang Zhang, and Chandan K. Reddy. 2025. Mtsql-r1: Towards long-horizon multi-turn text-to-sql via agentic training. *Preprint*, arXiv:2510.12831.

Mingqian He, Yongliang Shen, Wenqi Zhang, Qiuying Peng, Jun Wang, and Weiming Lu. 2025. Star-sql: Self-taught reasoner for text-to-sql. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 24365–24375.

Harper Hua, Zhen Han, Zhengyuan Shen, Jeremy Lee, Patrick Guan, Qi Zhu, Sullam Jeoung, Yueyan Chen, Yunfei Bai, Shuai Wang, and 1 others. 2026. Sqltrail: Multi-turn reinforcement learning with interleaved feedback for text-to-sql. *arXiv preprint arXiv:2601.17699*.

Yuxiang Ji, Ziyu Ma, Yong Wang, Guanhua Chen, Xiangxiang Chu, and Liaoni Wu. 2025. Tree search for llm agent reinforcement learning. *arXiv preprint arXiv:2509.21240*.

Aviral Kumar, Vincent Zhuang, Rishabh Agarwal, Yi Su, John D Co-Reyes, Avi Singh, Kate Baumli, Shariq Iqbal, Colton Bishop, Rebecca Roelofs, and 1 others. 2024. Training language models to self-correct via reinforcement learning, 2024. *URL https://arxiv.org/abs/2409.12917*, 2(3):4.

Philippe Laban, Hiroaki Hayashi, Yingbo Zhou, and Jennifer Neville. 2025. Llms get lost in multi-turn conversation. *arXiv preprint arXiv:2505.06120*.

Fangyu Lei, Jixuan Chen, Yuxiao Ye, Ruisheng Cao, Dongchan Shin, Hongjin Su, Zhaoqing Suo, Hongcheng Gao, Wenjing Hu, Pengcheng Yin, and 1 others. 2024. Spider 2.0: Evaluating language models on real-world enterprise text-to-sql workflows. *arXiv preprint arXiv:2411.07763*.

Haoyang Li, Shang Wu, Xiaokang Zhang, Xinmei Huang, Jing Zhang, Fuxin Jiang, Shuai Wang, Tieying Zhang, Jianjun Chen, Rui Shi, and 1 others. 2025. Omnisql: Synthesizing high-quality text-to-sql data at scale. *arXiv preprint arXiv:2503.02240*.

Jinyang Li, Binyuan Hui, Ge Qu, Jiaxi Yang, Binhua Li, Bowen Li, Bailin Wang, Bowen Qin, Ruiying Geng, Nan Huo, and 1 others. 2024. Can llm already serve as a database interface? a big bench for large-scale database grounded text-to-sqls. *Advances in Neural Information Processing Systems*, 36.

Xiaoqian Liu, Ke Wang, Yongbin Li, Yuchuan Wu, Wentao Ma, Aobo Kong, Fei Huang, Jianbin Jiao, and Junge Zhang. 2025. Epo: Explicit policy optimization for strategic reasoning in llms via reinforcement learning. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15371–15396.

Peixian Ma, Xialie Zhuang, Chengjin Xu, Xuhui Jiang, Ran Chen, and Jian Guo. 2025. Sql-r1: Training natural language to sql reasoning model by reinforcement learning. *arXiv preprint arXiv:2504.08600*.

Meituan LongCat Team. 2025. Longcat-flash technical report. *Preprint*, arXiv:2509.01322.

OpenAI. 2024. Gpt-4o system card. `https://openai.com/index/gpt-4o-system-card`.

OpenAI. 2025. Gpt-4.1. `https://openai.com/index/gpt-4-1`.

Mohammadreza Pourreza, Shayan Talaei, Ruoxi Sun, Xingchen Wan, Hailong Li, Azalia Mirhoseini, Amin Saberi, Sercan Arik, and 1 others. 2025. Reasoning-sql: Reinforcement learning with sql tailored partial rewards for reasoning-enhanced text-to-sql. *arXiv preprint arXiv:2503.23157*.

Yang Qin, Chao Chen, Zhihang Fu, Ze Chen, Dezhong Peng, Peng Hu, and Jieping Ye. 2024. Route: Robust multitask tuning and collaboration for text-to-sql. *arXiv preprint arXiv:2412.10138*.

Qwen. 2025. Qwen3 technical report. *Preprint*, arXiv:2505.09388.

Vladislav Shkapenyuk, Divesh Srivastava, Theodore Johnson, and Parisa Ghane. 2025. Automatic metadata extraction for text-to-sql. *Preprint*, arXiv:2505.19988.

Shayan Talaei, Mohammadreza Pourreza, Yu-Chen Chang, Azalia Mirhoseini, and Amin Saberi. 2024. Chess: Contextual harnessing for efficient sql synthesis. *Preprint*, arXiv:2405.16755.

Yanming Wan, Jiaxing Wu, Marwa Abdulhai, Lior Shani, and Natasha Jaques. 2025. Enhancing personalized multi-turn dialogue with curiosity reward. *arXiv preprint arXiv:2504.03206*.

Bing Wang, Changyu Ren, Jian Yang, Xinnian Liang, Jiaqi Bai, LinZheng Chai, Zhao Yan, Qian-Wen Zhang, Di Yin, Xing Sun, and Zhoujun Li. 2025a. MAC-SQL: A multi-agent collaborative framework for text-to-SQL. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 540–557, Abu Dhabi, UAE. Association for Computational Linguistics.

Pengfei Wang, Baolin Sun, Xuemei Dong, Yaxun Dai, Hongwei Yuan, Mengdie Chu, Yingqi Gao, Xiang Qi, Peng Zhang, and Ying Yan. 2025b. Agentar-scale-sql: Advancing text-to-sql through orchestrated test-time scaling. *Preprint*, arXiv:2509.24403.

Zhongyuan Wang, Richong Zhang, Zhijie Nie, and Jaein Kim. 2024. Tool-assisted agent on sql inspection and refinement in real-world scenarios. *Preprint*, arXiv:2408.16991.

Zihan Wang, Kangrui Wang, Qineng Wang, Pingyue Zhang, Linjie Li, Zhengyuan Yang, Xing Jin, Kefan Yu, Minh Nhat Nguyen, Licheng Liu, Eli Gottlieb, Yiping Lu, Kyunghyun Cho, Jiajun Wu, Li Fei-Fei, Lijuan Wang, Yejin Choi, and Manling Li. 2025c. Ragen: Understanding self-evolution in llm agents via multi-turn reinforcement learning. *Preprint*, arXiv:2504.20073.

Zekun Xu, Siyu Xia, Chuhuai Yue, Jiajun Chai, Mingxue Tian, Xiaohan Wang, Wei Lin, Haoxuan Li, and Guojun Yin. 2025. Mtir-sql: Multi-turn tool-integrated reasoning reinforcement learning for text-to-sql. *arXiv preprint arXiv:2510.25510*.

Zhenghai Xue, Longtao Zheng, Qian Liu, Yingru Li, Xiaosen Zheng, Zejun Ma, and Bo An. 2025. Simpletir: End-to-end reinforcement learning for multi-turn tool-integrated reasoning. *arXiv preprint arXiv:2509.02479*.

Cehua Yang, Dongyu Xiao, Junming Lin, Yuyang Song, Hanxu Yan, Shawn Guo, Wei Zhang, Jian Yang, Mingjie Tang, and Bryan Dai. 2025. Agro-sql: Agentic group-relative optimization with high-fidelity data synthesis. *Preprint*, arXiv:2512.23366.

Haojin Yang, Ai Jian, Xinyue Huang, Yiwei Wang, Weipeng Zhang, Ke Zeng, Xunliang Cai, and Jingqing Ruan. 2026. Harmonizing dense and sparse signals in multi-turn rl: Dual-horizon credit assignment for industrial sales agents. *Preprint*, arXiv:2603.01481.

Zhewei Yao, Guoheng Sun, Lukasz Borchmann, Gaurav Nuti, Zheyu Shen, Minghang Deng, Bohan Zhai, Hao Zhang, Ang Li, and Yuxiong He. 2025. Arctic-text2sql-r1: Simple rewards, strong reasoning in text-to-sql. *arXiv preprint arXiv:2505.20315*.

Tao Yu, Rui Zhang, Kai Yang, Michihiro Yasunaga, Dongxu Wang, Zifan Li, James Ma, Irene Li, Qingning Yao, Shanelle Roman, Zilin Zhang, and Dragomir Radev. 2018. Spider: A large-scale human-labeled dataset for complex and cross-domain semantic parsing and text-to-sql task. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, Brussels, Belgium. Association for Computational Linguistics.

Tianshu Zhang, Kun Qian, Siddhartha Sahai, Yuan Tian, Shaddy Garg, Huan Sun, and Yunyao Li. 2026. Evoschema: Towards text-to-sql robustness against schema evolution. *Preprint*, arXiv:2603.10697.

Yuxin Zhang, Meihao Fan, Ju Fan, Mingyang Yi, Yuyu Luo, Jian Tan, and Guoliang Li. 2025. Reward-sql: Boosting text-to-sql via stepwise reasoning and process-supervised rewards. *arXiv preprint arXiv:2505.04671*.

Yifei Zhou, Song Jiang, Yuandong Tian, Jason Weston, Sergey Levine, Sainbayar Sukhbaatar, and Xian Li. 2025. Sweet-rl: Training multi-turn llm agents on collaborative reasoning tasks. *arXiv preprint arXiv:2503.15478*.

Zilin Zhu, Chengxing Xie, Xin Lv, and slime Contributors. 2025. slime: An llm post-training framework for rl scaling. https://github.com/THUDM/slime. GitHub repository. Corresponding author: Xin Lv.

A Data Construction

A.1 Baseline Training Data Comparison

To contextualize the data efficiency of TRUST-SQL, we summarize the training data configurations of all evaluated baselines in Table 4. While recent single-turn models rely on massive synthetic datasets containing millions of samples, and multi-turn RL frameworks utilize large portions of standard benchmarks, TRUST-SQL achieves superior performance using a highly constrained and curated data recipe.

Table 4: Comparison of training data volume and sources.

Model	SFT Data	RL Data
OmniSQL	2.5M (SynSQL)	–
SQL-R1	2.5M (SynSQL)	5k (SynSQL)
MTIR-SQL	–	18.1k (Spider+BIRD)
SQL-Trail	0.8k (SynSQL)	1k (Spider)
TRUST-SQL	**9.2k (SynSQL)**	**11.6k (Spider+BIRD)**

A.2 SFT Training Data Construction

To warm up the agent prior to RL training, we construct a supervised fine-tuning dataset of high-quality exploration trajectories. The source questions are sampled from the training split of **SynSQL-2.5M** (Li et al., 2025). We filter this corpus to retain only questions of *Moderate*, *Complex*, and *Highly Complex* difficulty, as simpler questions provide insufficient training signal for multi-turn exploration. This yields 9,217 unique source questions, whose difficulty distribution is shown in Table 5.

Table 5: Difficulty distribution of source questions.

Difficulty	Count	Proportion
Moderate	3,821	41.5%
Complex	3,243	35.2%
Highly Complex	2,153	23.3%
Total	**9,217**	**100%**

Annotation Pipeline. We employ a multi-model annotation strategy using **GPT-4.1-mini** (OpenAI, 2025), **GPT-4o-mini** (OpenAI, 2024), and **DeepSeek-R1** (DeepSeek-AI, 2025). Each model is prompted to generate complete four-phase interaction trajectories following the TRUST-SQL protocol with a maximum output length of 2,048

tokens per response. A trajectory is retained if and only if it satisfies two strict conditions. First, the final SQL execution result must match the ground truth answer. Second, every turn must pass the format check described in Appendix C. This execution-verified filtering ensures that the SFT model learns from trajectories that are both correct and structurally well-formed.

Dataset Statistics. Table 6 summarizes the retained samples contributed by each annotation model.

Table 6: SFT training data statistics by annotation model. *Samples* denotes the total number of retained trajectories and *Unique IDs* denotes the number of distinct source questions covered by each model.

Annotation Model	Samples	Unique IDs
DeepSeek-R1	9,972	1,442
GPT-4.1-mini	43,803	5,575
GPT-4o-mini	17,195	2,263
Total	**70,970**	**9,280**

The majority of retained samples are contributed by GPT-4.1-mini (43,803 samples, 61.7%), reflecting its stronger instruction-following capability in generating well-formatted trajectories. DeepSeek-R1 contributes 9,972 samples across 1,442 unique questions, providing diverse chain-of-thought reasoning styles that complement the GPT-annotated data.

A.3 RL Training Data Construction

Question Selection. For RL training, we adopt the source questions from the training sets of **BIRD** (Li et al., 2024) and **Spider** (Yu et al., 2018) with identical difficulty filtering. To ensure effective RL exploration, we apply a difficulty-based filtering strategy where each question is rolled out 8 times using the SFT-initialized policy. Only questions with a pass rate strictly below 6/8 are retained. This criterion excludes questions that are already too easy for the current policy, as they provide negligible learning signal.

Ground Truth Schema Extraction. To compute the schema reward R_{schema} during RL training, we require the ground truth schema $\mathcal{K}^* = (\mathcal{K}^*_{\text{table}}, \mathcal{K}^*_{\text{col}})$ for each training instance. Rather than relying on a single model, we adopt a **multi-model consensus strategy** using three strong models including **GPT-4.1** (OpenAI, 2025),

Table 7: RL training data filtering statistics.

Statistic	Value
Total Candidate Questions	18,078
Retained Questions	11,642
Rejected Questions	6,436
Keep Rate	64.4%
Pass Rate Threshold	$< 6/8$

Table 9: Overview of the four tools in the TRUST-SQL action space.

Action	Phase	Output Tag	Description
explore_schema	Explore	<tool_call>	Query database metadata
propose_schema	Propose	<schema>	Commit to verified schema
generate_sql	Generate	<tool_call>	Execute candidate SQL
confirm_answer	Confirm	<answer>	Submit final SQL answer

LongCat-Flash (Meituan LongCat Team, 2025), and **Gemini-2.5-Pro** (DeepMind, 2025). Each model independently parses the ground truth SQL y^* to extract the referenced table names and column names. A schema annotation is accepted only when at least two out of three models produce consistent results. This consensus ensures the reliability of the extracted $\mathcal{K}^*$ as a robust supervision signal for evaluating the agent's *Propose* action.

B Implementation Details

We train two model scales, namely Qwen3-4B and Qwen3-8B, each passing through a supervised fine-tuning warm-up stage followed by Dual-Track GRPO optimization. The 4B model adopts synchronous training under the SLIME framework (Zhu et al., 2025), while the 8B model adopts asynchronous training. Table 8 summarizes the hardware configuration, key hyperparameters, and estimated training cost for each stage.

C Agent Configuration

C.1 Tool Overview

The agent interacts with the database environment through four structured tools, each corresponding to one phase of the TRUST-SQL protocol. Table 9 provides an overview of their roles and output tags.

C.2 Format Check Rules

At each turn, the agent's output must conform to a strict structural protocol. The FormatCheck function validates each turn by enforcing the following rules:

1. **Think tag**: The output must contain exactly one <think>...</think> block.

2. **Action tag**: The output must contain exactly one <action>...</action> block, whose content must be one of the four valid action types.

3. **Content tag**: Each action type requires a corresponding content tag, as specified in Table 9. Specifically, explore_schema and generate_sql require a <tool_call> block; propose_schema requires a <schema> block; and confirm_answer requires an <answer> block.

A turn is considered valid if and only if all three conditions are satisfied, yielding a format score of 0.1. Any violation results in a format score of 0.0 and terminates the format reward for the entire trajectory.

C.3 Prompt Template

The following presents the complete prompt used in TRUST-SQL, comprising a system prompt that defines the agent's role, action protocol, and output format, followed by a user prompt that provides the task-specific context.

Table 8: Training setup for TRUST-SQL across model scales and training stages.

Model	Stage	GPUs	Mode	LR	Batch Size	Epochs	Rollout	λ	Turns	Time (hrs)
Qwen3-4B	SFT	16×A100	sync	1×10^{-5}	256	2	–	–	–	6.5
	RL	8×A100	sync	1×10^{-6}	32	3	8	0.25	10	60
Qwen3-8B	SFT	16×A100	sync	1.5×10^{-6}	256	2	–	–	–	12
	RL	32×A100	async	8×10^{-7}	32	3	8	0.25	10	40

Role
You are an expert SQL assistant working on an *unknown* database. You must **never hallucinate** tables or columns.
All schema knowledge MUST come from metadata queries only.
You must operate strictly through the **Action Protocol**.

Action Protocol
You must follow this sequence (can loop back if needed):

1. `explore_schema` — Query database metadata

2. `propose_schema` — Document verified schema

3. `generate_sql` — Create SQL query

4. `confirm_answer` — Output final SQL

ACTION: `explore_schema`
Used to query database metadata (tables, columns, foreign keys, etc.).
• Only metadata queries allowed.

• No user-intent SQL here.

• Verify relationships between tables when multi-table queries are needed.

ACTION: `propose_schema`
Used to output the current verified schema knowledge.
• Include ONLY tables/columns actually verified through `explore_schema`.

• Do NOT hallucinate or assume any unverified structures.

• `joins` is optional; include only when relationships are explicitly verified.

• Supports both single-table and multi-table structures.

ACTION: `generate_sql`
Used to generate the SQL answer based on the latest `<schema>`.
• Use ONLY verified schema from `propose_schema`.

• If required tables/columns are missing, switch back to `explore_schema` or `propose_schema` in the next message.

• SQL must be syntactically valid and executable.

• Consider query optimization (indexes, joins, filters).

• Validate the SQL logic matches user intent.

ACTION: `confirm_answer`
Used when you have validated the generated SQL and confirmed it meets user requirements.
• Execute this action ONLY after `generate_sql` validation.

• You MUST NOT return or describe any query results.

• You MUST NOT output anything other than SQL inside `<answer>`.

• The final output must be ONLY the SQL query in proper format.

942

Output Format
EVERY response must follow this exact structure:
<think>[Your reasoning process here]</think>
<action>[one of: explore_schema | propose_schema | generate_sql | confirm_answer]</action>
[Action-specific content below]

explore_schema

```
<think>reasoning</think>
<action>explore_schema</action>
<tool_call>
{"name": "execute_sql_query",
 "arguments": {"db_id": "...", "sql": "..."}}
</tool_call>
```

propose_schema

```
<think>reasoning</think>
<action>propose_schema</action>
<schema>
{
 "tables": ["tableA"],
 "columns": { "tableA": ["col1", "col2"] },
 "joins": []
}
</schema>
```

generate_sql

```
<think>reasoning</think>
<action>generate_sql</action>
<tool_call>
{"name": "execute_sql_query",
 "arguments": {"db_id": "...", "sql": "..."}}
</tool_call>
```

confirm_answer

```
<think>reasoning</think>
<action>confirm_answer</action>
<answer>
SELECT ... FROM ... WHERE ...
</answer>
```

943

Tools

You may call one or more functions to assist with the user query.

```
{
 "type": "function",
 "function": {
```

944

```
  "name": "execute_sql_query",
  "description": "Execute SQL query and return partial
  results containing column names.
  (maximum 30 records)",
  "parameters": {
   "type": "object",
   "properties": {
    "db_id": {
     "type": "string",
     "description": "The name of the database to query"
    },
    "sql": {
     "type": "string",
     "description": "The SQL query to execute"
    }
   },
   "required": ["db_id", "sql"]
  }
 }
}
```

For each function call, return a json object with function name and arguments within <tool_call></tool_call> XML tags:

```
<tool_call>
{"name": <function-name>, "arguments": <args-json-object>}
</tool_call>
```

User Prompt

Task Configuration

Database Engine: SQLite
Database: {db_id}
External Knowledge: {external_knowledge}
User Question: {question}?

D Extended Results

D.1 Cost Analysis

Table 10 presents a comprehensive inference cost analysis on BIRD-Dev, comparing accuracy, latency, token consumption, interaction turns, and tool call frequency across all methods.

Accuracy vs. Cost Trade-off. Training-free pipeline methods such as CHESS achieve competitive accuracy at an extremely high cost of 251.3 seconds and 320.8K tokens per query, making them impractical for real-world deployment. In contrast, TRUST-SQL-4B achieves a higher accuracy of 64.9% under the Unknown Schema setting with only 0.6 seconds latency and 2.83K tokens, representing a **500× reduction in latency** and a **113× reduction in token consumption** compared to CHESS.

Efficiency of Active Exploration. Compared to schema-prefilled baselines of similar scale, TRUST-SQL demonstrates remarkable inference efficiency. TRUST-SQL-4B without prefilling consumes only 2.83K tokens and completes interactions in 5.89 average turns, comparable to MTIR-SQL-4B which consumes 2.9K tokens under full schema access. This confirms that our active exploration policy retrieves only the necessary metadata without incurring significant overhead.

Impact of Schema Prefilling on Base Models. A striking observation is the asymmetric effect of schema prefilling on base models versus TRUST-SQL. For Qwen3-4B, removing prefilling increases

token consumption from 1.82K to 4.93K and degrades accuracy from 46.3% to 29.3%, revealing a complete dependence on pre-loaded metadata. In contrast, TRUST-SQL-4B without prefilling consumes only 2.83K tokens while maintaining 64.9% accuracy, demonstrating that Dual-Track GRPO training instills efficient and targeted exploration behavior.

D.2 Pass@K Results on Additional Benchmarks

Table 11: Pass@K results across all benchmarks (temperature = 0.8, max turns = 15).

Size	Benchmark	Pass@1	Pass@4	Pass@6	Pass@8
4B	Spider (test)	82.8	86.5	86.9	87.1
	Spider-DK	71.6	78.8	80.3	81.2
	Spider-Syn	74.7	81.6	82.3	83.1
	Spider-Realistic	79.9	85.4	86.2	86.6
8B	Spider (test)	83.9	86.5	87.1	87.5
	Spider-DK	72.1	79.2	80.5	81.3
	Spider-Syn	75.4	81.0	83.0	84.0
	Spider-Realistic	82.1	85.5	86.4	87.0

Section 5.3 of the main paper reports Pass@K scaling behavior on BIRD-Dev. Here we extend this analysis to the remaining four benchmarks to verify that the monotonic scaling trend generalizes across different evaluation settings. Table 11 reports Pass@K results for $K \in \{1, 4, 6, 8\}$ under a 15-turn inference budget. Consistent with the

Table 10: Inference cost analysis on BIRD-Dev.

Method	Prefill	Acc (%)	Latency (s)	OutputTokens (K)	Turns	Tool Calls
CHESS (Talaei et al., 2024)	✓	61.5	251.3	320.8	–	–
SQL-R1-7B (Ma et al., 2025)	✓	63.7	0.4	3.1	–	–
MTIR-SQL-4B (Xu et al., 2025)	✓	63.1	0.5	2.9	–	1.34
MTIR-SQL-8B (Xu et al., 2025)	✓	63.6	0.4	2.0	–	1.31
Qwen3-4B (Qwen, 2025)	✓	46.3	0.4	1.82	2.34	1.64
Qwen3-4B (Qwen, 2025)	✗	29.3	1.2	4.93	7.66	4.42
Qwen3-8B (Qwen, 2025)	✓	49.9	0.4	2.15	2.14	2.92
Qwen3-8B (Qwen, 2025)	✗	47.9	1.0	3.85	6.34	4.41
TRUST-SQL-4B	✓	**64.8**	**0.4**	**1.75**	**4.23**	**2.89**
TRUST-SQL-4B	✗	**64.9**	**0.6**	**2.83**	**5.89**	**3.66**
TRUST-SQL-8B	✓	**65.5**	**0.5**	**2.00**	**4.69**	**3.61**
TRUST-SQL-8B	✗	**65.8**	**0.5**	**2.03**	**5.62**	**3.45**

BIRD-Dev results reported in the main paper, all benchmarks exhibit monotonic accuracy improvements as K grows. The persistent gap between Pass@K and greedy performance indicates that the model possesses the capability to generate correct solutions but has not fully converged to a consistent policy, suggesting headroom for further training.

D.3 Performance on Complex Benchmark (Spider 2.0)

To evaluate TRUST-SQL under more challenging real-world conditions, we conduct additional experiments on the SQLite subset of Spider 2.0 (Lei et al., 2024), comprising 135 questions with enterprise-grade databases featuring significantly more complex schemas and larger table counts than standard Spider. This setting is particularly well-suited for assessing the Unknown Schema framework, as the increased schema complexity makes full schema prefilling even more impractical.

Table 12 reports execution accuracy alongside representative baselines. Notably, strong proprietary models such as GPT-4o (OpenAI, 2024) and DeepSeek-V3 (DeepSeek-AI, 2025) achieve only 15.6% on this benchmark, while specialized Text-to-SQL models like OmniSQL-7B (Li et al., 2025) reach 10.4%, reflecting the substantial difficulty of this setting.

Table 12: Execution accuracy on the Spider 2.0 SQLite subset (135 questions). Baselines use full schema prefilling. Pass@8 is computed over 8 sampled trajectories.

Method	Prefill	Greedy	Pass@8
OmniSQL-7B	✓	10.4	–
GPT-4o	✓	15.6	–
DeepSeek-V3	✓	15.6	–
OpenSearchSQL+Qwen2.5-7B-Instruct	✓	4.4	7.4
OpenSearchSQL+Arctic-Text2SQL-R1-7B	✓	14.1	20.7
TRUST-SQL-8B	✗	**14.8**	**24.9**

Despite operating entirely without pre-loaded metadata, TRUST-SQL-8B achieves 14.8% greedy accuracy and 24.9% Pass@8, surpassing OpenSearchSQL paired with the specialized Arctic-7B (Yao et al., 2025) model. The non-saturating Pass@8 curve further suggests substantial headroom for improvement with increased sampling budgets, validating the generalizability of our framework beyond standard academic benchmarks.

E   Case Study

We present a case study on BIRD-Dev instance dev_4 (database california_schools, Qwen3-4B, greedy decoding) to qualitatively examine how schema availability shapes model behavior. The full interaction traces are shown in Figure 7.

Task. The question requires retrieving phone numbers of directly charter-funded schools opened after January 1, 2000. Answering correctly demands grounding the funding-type predicate in the actual column values stored in the database, information absent from both the question and the external knowledge hint.

Unknown Schema Setting (6 turns). Without any prior schema knowledge, the model adopts a systematic bottom-up exploration strategy. In T1 and T2, it queries sqlite_master to discover available tables and retrieve their schema definitions. In T3, it probes the actual values of Charter_Funding_Type in the frpm table, uncovering the critical predicate value Directly_funded. Only after this value-level verification does the model commit to a schema proposal in T4 and generate the correct SQL in T5, which is subsequently confirmed in T6.

Schema Prefill Setting (4 turns). When the full schema is injected as a synthetic explore turn in T1, the model skips exploratory interactions and moves directly to schema proposal in T2 and SQL generation in T3. However, reasoning solely from structural metadata without inspecting actual column values, the model fails to discover the Directly_funded predicate. The generated SQL filters only on Charter_School_(Y/N) = 1, retrieving all charter schools regardless of funding type and producing a semantically broader answer that does not fully satisfy the question.

Discussion. The contrast reveals that schema prefilling accelerates inference but sacrifices value-level grounding. Interactive exploration enables the model to adaptively acquire the precise data-level knowledge needed for accurate SQL generation. This suggests that the benefit of the Unknown Schema setting lies not merely in schema discovery, but in fostering a more thorough and evidence-driven reasoning process.

Database: `california_schools` **Decoding:** Greedy **Max Turns:** 10
External Knowledge: Charter schools refers to 'Charter School (Y/N)' = 1 in `frpm`
Question (dev_4): *Please list the phone numbers of the direct charter-funded schools that are opened after 2000/1/1.*

Figure 7: Case study on BIRD-Dev instance dev_4 (database `california_schools`, Qwen3-4B, greedy decoding).
Left: Unknown Schema setting with interactive metadata exploration. **Right:** Schema Prefill variant where the complete schema is injected as a synthetic *Explore* turn.