SPATIOTEMPORAL MODELING OF MULTIVARIATE SIGNALS WITH GRAPH NEURAL NETWORKS AND STRUCTURED STATE SPACE MODELS

ABSTRACT

Multivariate signals are prevalent in various domains, such as healthcare, transportation systems, and space sciences. Modeling spatiotemporal dependencies in multivariate signals is challenging due to (1) long-range temporal dependencies and (2) complex spatial correlations between sensors. To address these challenges, we propose representing multivariate signals as graphs and introduce GRAPHS4MER, a general graph neural network (GNN) architecture that captures both spatial and temporal dependencies in multivariate signals. Specifically, (1) we leverage Structured State Spaces model (S4), a state-of-the-art sequence model, to capture long-term temporal dependencies and (2) we propose a graph structure learning layer in GRAPHS4MER to automatically learn the underlying graph structures in the data. We evaluate our proposed model on three distinct tasks and show that GRAPHS4MER consistently improves over existing models, including (1) seizure detection from electroencephalography signals, outperforming a previous GNN with self-supervised pretraining by 3.1 points in AUROC; (2) sleep staging from polysomnography signals, a 4.1 points improvement in macro-F1 score compared to existing sleep staging models; and (3) traffic forecasting, reducing MAE by 8.8% compared to existing GNNs and by 1.4% compared to transformer-based models.

1 INTRODUCTION

Multivariate signals are time series data measured by multiple sensors and are prevalent in many real-world applications, including healthcare (Mincholé et al., 2019), transportation systems (Ermagun & Levinson, 2018), power systems (Negnevitsky et al., 2009), and space sciences (Camporeale et al., 2018). An example multivariate signal is scalp electroencephalograms (EEGs), which measure brain electrical activities using sensors placed on an individual's scalp.

Several challenges exist in modeling spatiotemporal dependencies in multivariate signals. First, many types of signals are sampled at a high sampling rate, which results in long sequences that can be up to tens of thousands of time steps. Moreover, multivariate signals often involve long-range temporal correlations (Berthouze et al., 2010). Prior studies on modeling long signals often preprocess the raw signals using frequency transformations (Tang et al., 2022b; Asif et al., 2020; Shoeibi et al., 2021; Covert et al., 2019; Guillot et al., 2020; Guillot & Thorey, 2021) or divide the signals into short windows and aggregate model predictions post-hoc (Phan & Mikkelsen, 2022; Pradhan et al., 2022). However, such preprocessing steps may discard important information encoded in raw signals, as well as neglect long-range temporal dependencies in the signals. Therefore, a model that is capable of modeling long-range temporal correlations in raw signals is needed.

Deep sequence models, including recurrent neural networks (RNNs), convolutional neural networks (CNNs), and Transformers, have specialized variants for handling long sequences (Arjovsky et al., 2016; Erichson et al., 2021; Katharopoulos et al., 2020; Bai et al., 2020; Choromanski et al., 2021). However, they struggle to scale to long sequences of tens of thousands of time steps (Tay et al., 2020). Recently, the Structured State Space sequence model (S4) (Gu et al., 2022), a deep sequence model based on the classic state space model, has achieved state-of-the-art performance on chal-

Figure 1: **Architecture of GRAPHS4MER**. The model has three main components: (1) stacked S4 layers to learn temporal dependencies in each sensor independently; (2) a graph structure learning (GSL) layer to learn graph structures from S4 embeddings; (3) graph convolutional layers to learn spatial dependencies based on S4 embeddings and learned graph structures. For GSL, we adopt (a) self-attention and (b) a learnable embedding for inductive and transductive settings, respectively.

lenging long sequence modeling tasks, such as the Long Range Arena benchmark (Tay et al., 2020), raw speech classification (Gu et al., 2022), and audio generation (Goel et al., 2022).

Second, sensors have complex, non-Euclidean spatial correlations. For example, EEG sensors measure highly correlated yet unique electrical activities from different brain regions (Michel & Murray, 2012); traffic speeds are correlated not only based on physical distances between traffic sensors, but also dependent on the traffic flows (Li et al., 2018b). Graphs are data structures that can model complex, non-Euclidean correlations in the data (Chami et al., 2022; Bronstein et al., 2017). Previous works have adopted temporal graph neural networks (GNNs) in modeling multivariate time series, such as EEG-based seizure detection (Covert et al., 2019) and classification (Tang et al., 2022b), traffic forecasting (Li et al., 2018b; Wu et al., 2019; Zheng et al., 2020b; Jiang & Luo, 2022; Tian & Chan, 2021), and pandemic forecasting (Panagopoulos et al., 2021; Kapoor et al., 2020). Nevertheless, most of these studies used sequences up to hundreds of time steps and require a predefined, static graph structure. However, the graph structure of multivariate signals may not be easily defined due to unknown sensor locations. For instance, while EEG sensors are typically placed according to the 10-20 standard placement (Jasper, 1958), the exact locations of sensors vary in each individual's recordings due to the variability in individual head size. Moreover, the underlying graph connectivity can evolve over time due to temporal dynamics in the data. Hence, when graph structures cannot be easily pre-defined, the ability to dynamically learn the underlying graph structures is highly desired.

Graph structure learning (GSL) aims to jointly learn an optimized graph structure and its node and graph representations (Zhu et al., 2021). GSL techniques have been used in non-temporal graph applications, such as natural language processing (Xu et al., 2022), molecular optimization (Fu et al., 2021), learning on point clouds (Wang et al., 2019), and improving GNN robustness against adversarial attacks (Zhang & Zitnik, 2020; Jin et al., 2020). GSL has also been employed for spatiotemporal modeling of traffic flows (Zhang et al., 2020; Tang et al., 2022a; Shang et al., 2021; Wu et al., 2019; Bai et al., 2020), irregularly sampled multivariate time series (Zhang et al., 2022), and functional magnetic resonance imaging (fMRI) (El-Gazzar et al., 2021; Gazzar et al., 2022b), but it is limited to sequences of less than 1k time steps.

In this study, we address the foregoing challenges by (1) leveraging S4 to enable long-range temporal modeling and (2) proposing a graph structure learning layer to automatically learn the underlying graph structures in multivariate signals. Our main contributions are:

- We propose GRAPHS4MER (Figure 1), a general end-to-end GNN architecture for spatiotemporal modeling of multivariate signals. Our model has two major advantages: (1) it leverages S4 to capture *long-range temporal dependencies* in signals and (2) it is able to *dynamically learn the underlying graph structures* in the data without a predefined graph.

- We evaluate GRAPHS4MER on three datasets with distinct data types and tasks. Our model consistently outperforms existing methods on (1) seizure detection on TUSZ dataset, outperforming a previous GNN with self-supervised pre-training by 3.1 points in AUROC; (2) sleep staging from polysomnography signals, outpeforming existing sleep staging models

by 4.1 points in macro-F1 score; (3) traffic forecasting on PEMS-BAY benchmark, reducing MAE by 8.8% compared to existing GNNs and by 1.4% compared to transformers.

2 RELATED WORKS

Temporal graph neural networks. Temporal GNNs have been widely used for multivariate time series. A recent work by Gao & Ribeiro (2022) shows that existing temporal GNNs can be grouped into two categories: time-and-graph and time-then-graph. The time-and-graph framework treats a temporal graph as a sequence of graph snapshots, constructs a graph representation for each snapshot, and embeds the temporal evolution using sequence models. For example, GCRN (Seo et al., 2018) uses spectral graph convolution (Defferrard et al., 2016) for node representations and Long Short-Term Memory network (LSTM) (Hochreiter & Schmidhuber, 1997) for temporal dynamics modeling. DCRNN (Li et al., 2018b) integrates diffusion convolution with Gated Recurrent Units (GRU) (Cho et al., 2014) for traffic forecasting. Li et al. (2019) combines relational graph convolution with LSTM for path failure prediction. EvolveGCN (Pareja et al., 2020) treats graph convolutional network (GCN) parameters as recurrent states and uses an RNN to evolve the GCN parameters. In contrast, time-then-graph framework sequentially represents the temporal evolution of node and edge attributes, and uses these temporal representations to build a static graph representation (da Xu et al., 2020; Rossi et al., 2020). Gao & Ribeiro (2022) proposes a general framework for time-then-graph, which represents the evolution of node and edge features using two RNNs independently, constructs a static graph from these representations, and encodes them using a GNN. However, most of the existing temporal GNNs are limited to short sequences and adopt RNNs or self-attention for temporal modeling, which may be suboptimal when applied to long sequences. To our knowledge, only one study has leveraged S4 to model temporal graphs (Gazzar et al., 2022a). However, the learned graph is static and shared across all data points, and the study is only limited to fMRI data.

Graph structure learning. GSL aims to jointly learn a graph structure and its corresponding node (or graph) representations. Briefly, GSL methods fall into the following three categories (Zhu et al., 2021): (1) metric-based approaches that derive edge weights from node embeddings based on a metric function (Li et al., 2018a; Chen et al., 2020; Zhang & Zitnik, 2020), (2) neural-based approaches that use neural networks to learn the graph structure from node embeddings (Luo et al., 2021; Zheng et al., 2020a), and (3) direct approaches that treat the adjacency matrix or node embedding dictionary as learnable parameters (Jin et al., 2020; Gao et al., 2020). GSL has been applied to temporal graph data. Zhang et al. (2020) proposes learning graph adjacency matrix from traffic data through learnable parameters. Tang et al. (2022a) uses a multi-layer perceptron and a similarity measure to learn the graph structure for traffic forecasting. Shang et al. (2021) leverages a link predictor (two fully connected layers) to obtain the edge weights between nodes. Several works adaptively learn the adjacency matrix from data using learnable node embedding dictionaries (Wu et al., 2019; El-Gazzar et al., 2021; Gazzar et al., 2022a). However, all of these GSL approaches are limited to short sequences of less than 1k time steps.

3 BACKGROUND

3.1 STRUCTURED STATE SPACE MODEL (S4)

The Structured State Space sequence model (S4) (Gu et al., 2022) is a deep sequence model that is capable of capturing long-range dependencies. S4 has achieved state-of-the-art on pixel-level 1-D image classification, the challenging Long Range Arena benchmark for long sequence modeling, raw speech classification, and audio generation (Gu et al., 2022; Goel et al., 2022).

S4 is based on the state space model (SSM). A recent line of work (Gu et al., 2020; 2021; Gu et al., 2022) has shown that SSMs can be viewed as both convolutional neural networks (CNNs) and recurrent neural networks (RNNs). The continuous-time SSM is defined as follows:

$$\begin{aligned} x'(t) &= \mathbf{A}x(t) + \mathbf{B}u(t) \\ y(t) &= \mathbf{C}x(t) + \mathbf{D}u(t) \end{aligned} \qquad (1)$$

Equation 1 can be used as a black-box sequence representation in a deep learning model, where $\mathbf{A}$, $\mathbf{B}$, $\mathbf{C}$, and $\mathbf{D}$ are parameters learned by gradient descent.

To be applied to real-world sequences sampled at discrete step size Δ, the above continuous-time SSM can be computed with the following recurrence:

$$x_k = \overline{\mathbf{A}}x_{k-1} + \overline{\mathbf{B}}u_k, \ \ y_k = \overline{\mathbf{C}}x_k, \tag{2}$$

$$\overline{\mathbf{A}} = (\mathbf{I} - \Delta/2 \cdot \mathbf{A})^{-1}(\mathbf{I} + \Delta/2 \cdot \mathbf{A}), \ \ \overline{\mathbf{B}} = (\mathbf{I} - \Delta/2 \cdot \mathbf{A})^{-1}\Delta\mathbf{B}, \ \ \overline{\mathbf{C}} = \mathbf{C} \tag{3}$$

where $\overline{\mathbf{A}}$, $\overline{\mathbf{B}}$, and $\overline{\mathbf{C}}$ are the discretized matrices of $\mathbf{A}, \mathbf{B}$, and $\mathbf{C}$, respectively.

Gu et al. (Gu et al., 2021) shows that the above discrete-time SSM is also equivalent to the following convolution:

$$\overline{\mathbf{K}} := (\overline{\mathbf{CB}}, \overline{\mathbf{CAB}}, ..., \overline{\mathbf{CA}}^{L-1}\overline{\mathbf{B}}), \ \ y = \overline{\mathbf{K}} * u \tag{4}$$

where $\overline{\mathbf{K}}$ is called the SSM convolution kernel.

S4 (Gu et al., 2022) is a special instantiation of SSMs that parameterizes $\mathbf{A}$ as a diagonal plus low-rank (DPLR) matrix. This parameterization has two major advantages. First, it enables fast computation of the SSM kernel $\overline{\mathbf{K}}$. Second, the parameterization includes the HiPPO matrices (Gu et al., 2020), which are a class of matrices that is capable of capturing long-range dependencies.

However, naively applying S4 for multivariate signals mixes the signal channels with a position-wise linear layer (Gu et al., 2022), which does not take into account the underlying graph structure of multivariate signals. This limitation motivates our development of GRAPHS4MER as described in Section 4.

3.2 GRAPH REGULARIZATION

Graph regularization encourages a learned graph to have several desirable properties, such as smoothness, sparsity, and connectivity (Chen et al., 2020; Kalofolias, 2016; Zhu et al., 2021). Let $\mathbf{X} \in \mathbb{R}^{N \times D}$ be a graph data with N nodes and D features. First, a common assumption in graph signal processing is that features change smoothly between adjacent nodes (Ortega et al., 2018). Given an undirected graph with adjacency matrix $\mathbf{W}$, the smoothness of the graph can be measured by the Dirichlet energy (Belkin & Niyogi, 2001):

$$\mathcal{L}_{\text{smooth}}(\mathbf{X}, \mathbf{W}) = \frac{1}{2N^2}\sum_{i,j}\mathbf{W}_{ij}||\mathbf{X}_{i,:} - \mathbf{X}_{j,:}||^2 = \frac{1}{N^2}\text{tr}(\mathbf{X}^T\mathbf{L}\mathbf{X}) \tag{5}$$

where tr(.) denotes the trace of a matrix, $\mathbf{L} = \mathbf{D} - \mathbf{W}$ is the graph Laplacian, $\mathbf{D}$ is the degree matrix of $\mathbf{W}$. Minimizing Equation 5 therefore encourages the learned graph to be smooth. In practice, the normalized graph Laplacian $\hat{\mathbf{L}} = \mathbf{D}^{-1/2}\mathbf{L}\mathbf{D}^{-1/2}$ is used so that it is independent of node degrees.

However, simply minimizing the smoothness may result in a trivial solution $\mathbf{W} = \mathbf{0}$ (Chen et al., 2020). To avoid this trivial solution and encourage sparsity of the learned graph, additional constraints can be added (Chen et al., 2020; Kalofolias, 2016):

$$\mathcal{L}_{\text{degree}}(\mathbf{W}) = \frac{-1}{N}\mathbf{1}^T\log(\mathbf{W}\mathbf{1}), \ \ \mathcal{L}_{\text{sparse}}(\mathbf{W}) = \frac{1}{N^2}||\mathbf{W}||_F^2 \tag{6}$$

where $||.||_F$ is the Frobenius norm of a matrix. Intuitively, $\mathcal{L}_{\text{degree}}$ penalizes disconnected graphs and $\mathcal{L}_{\text{sparse}}$ discourages nodes with high degrees (i.e., encourages the learned graph to be sparse).

4 METHODS

4.1 PROBLEM SETUP

In this study, we propose a general representation of multivariate signals using graphs. Let $\mathbf{X} \in \mathbb{R}^{N \times T \times M}$ be a multivariate signal, where N is the number of sensors, T is the sequence length, and M is the input dimension of the signal (typically $M = 1$). We represent the multivariate signal as

a graph $\mathcal{G} = \{\mathcal{V}, \mathcal{E}, \mathbf{W}\}$, where the set of nodes $\mathcal{V}$ corresponds to the sensors, $\mathcal{E}$ is the set of edges, and $\mathbf{W}$ is the adjacency matrix. Here, $\mathcal{E}$ and $\mathbf{W}$ are unknown and will be learned by our model.

While our formulation is general to any type of node-level or graph-level classification and regression tasks, we focus on graph-level classification (e.g., seizure detection) and node-level forecasting problems (e.g., traffic forecasting) in this work. For graph classification, the goal is to learn a function which maps an input signal to a prediction, i.e., $f : \mathbf{X} \rightarrow y \in \{1, 2, ..., C\}$, where C is the number of classes. For node-level forecasting, the goal is to learn a function which predicts the next S' time step signals given the previous S time step signals, i.e., $f : \mathbf{X}_{:,(t-S):t,:} \rightarrow \mathbf{X}_{:,t:(t+S'),:}$.

4.2 TEMPORAL MODELING WITH S4

In this work, we leverage S4 to capture long-range temporal dependencies in signals. Naively applying S4 for multivariate signals mixes the N signal channels with a position-wise linear layer (Gu et al., 2022), which may be suboptimal because it neglects the underlying graph structure of multivariate signals. Instead, we use stacked S4 layers with residual connection to embed signals in each channel (sensor) independently, resulting in an embedding $\mathbf{H} \in \mathbb{R}^{N \times T \times D}$ for each input signal $\mathbf{X}$, where D is the embedding dimension.

4.3 DYNAMIC GRAPH STRUCTURE LEARNING

Graph structure learning layer. To model spatial dependencies in signals (i.e., graph adjacency matrix $\mathbf{W}$), we develop a graph structure learning (GSL) layer to learn the similarities between nodes from S4 embeddings. To capture the dynamics of signals that evolve over time, our GSL layer learns a *unique* graph structure from S4 embeddings within a short *resolution* interval between time t and $t + r$, where r is a pre-specified resolution. Instead of learning a unique graph at each time step, we choose to learn a graph at r time interval because (1) aggregating information across a longer time interval can result in less noisy graphs and (2) it is more computationally efficient.

For inductive settings where each signal forms a graph (e.g., EEG signals) and the task is to predict on new graphs (e.g., seizure detection on unseen signals), the goal of GSL is to learn a unique graph for each signal. To obtain the edge weight between two nodes, we adopt self-attention (Vaswani et al., 2017) to allow each node to attend to all other nodes and use the attention weight as the edge weight between two nodes:

$$\mathbf{Q} = \mathbf{h}^{(t)}\mathbf{W}^Q, \ \ \mathbf{K} = \mathbf{h}^{(t)}\mathbf{W}^K, \ \ \mathbf{W}^{(t)} = \text{softmax}(\frac{\mathbf{Q}\mathbf{K}^T}{\sqrt{D}}) \tag{7}$$

Here, $\mathbf{h}^{(t)} \in \mathbb{R}^{N \times D}$ is mean-pooled S4 embeddings between time t and $t + r$; $\mathbf{W}^Q \in \mathbb{R}^{D \times D}$ and $\mathbf{W}^K \in \mathbb{R}^{D \times D}$ are weights projecting $\mathbf{h}^{(t)}$ to query $\mathbf{Q}$ and key $\mathbf{K}$, respectively; $\mathbf{W}^{(t)} \in \mathbb{R}^{N \times N}$ is the learned adjacency matrix between time t and $t + r$. Equation 7 can be easily extended to multihead self-attention (Vaswani et al., 2017).

For transductive settings where the graph is shared across all signals (e.g., traffic forecasting), we use a learnable embedding $\mathbf{E} \in \mathbb{R}^{N \times d_e}$ in GSL to learn a universal graph for all data points (Bai et al., 2020; Wu et al., 2019):

$$\mathbf{W}^{(t)} = \text{softmax}\big(\text{LeakyReLU}(\mathbf{E}\mathbf{E}^T)\big) \tag{8}$$

Here, d_e is the embedding dimension, and $\mathbf{E}$ is initialized randomly and trained end-to-end.

There are several advantages of our GSL layer compared to prior works (Wu et al., 2019; El-Gazzar et al., 2021; Gazzar et al., 2022a). First, our GSL layer is operated on S4 embeddings rather than raw signals, which leverages the long-range dependencies learned by S4 layers. Second, in inductive settings, our GSL layer learns a unique graph for each data point rather than a universal graph for all data points. Third, our GSL layer is able to learn dynamically evolving graph structures over time.

To guide the graph structure learning process, we initialize a k-nearest neighbor (KNN) graph $\mathbf{W}_{\text{KNN}}$, where each node's k-nearest neighbors are defined by cosine similarity between their respective S4 embeddings. The KNN graph is added to the learned adjacency matrix as follows:

$$\mathbf{W}^{(t)} = \epsilon \mathbf{W}_{\text{KNN}} + (1 - \epsilon)\mathbf{W}^{(t)} \tag{9}$$

To introduce graph sparsity, we prune the adjacency matrix $\mathbf{W}^{(t)}$ by removing edges whose weights are smaller than a certain threshold, i.e., $\mathbf{W}_{ij}^{(t)} = 0$ if $\mathbf{W}_{ij}^{(t)} < \kappa$, where κ is a hyperparameter. For undirected graphs, we make the learned adjacency matrix symmetric by taking the average of the edge weights between two nodes.

Graph regularization. To encourage the learned graphs to have desirable graph properties, we include three regularization terms as detailed in Equations 5-6. Let $\mathbf{h}^{(t)} \in \mathbb{R}^{N \times D}$ be the mean-pooled S4 embeddings between time t and $t + r$. The regularization loss for each data point is the weighted sum of the three regularization terms and averaged across all learned graphs: $\mathcal{L}_{\text{reg}} = \frac{1}{n_d} \sum_{t=1}^{n_d} \alpha \mathcal{L}_{\text{smooth}}(\mathbf{h}^{(t)}, \mathbf{W}^{(t)}) + \beta \mathcal{L}_{\text{degree}}(\mathbf{W}^{(t)}) + \gamma \mathcal{L}_{\text{sparse}}(\mathbf{W}^{(t)})$, where α, β, and γ are hyperparameters, and $n_d = \frac{T}{r}$ is the number of time-evolving graphs.

4.4 MODEL ARCHITECTURE

The overall architecture of our model (Figure 1), GRAPHS4MER, consists of tree main components: (1) stacked S4 layers with residual connection to model temporal dependencies in signals within each sensor independently, which produces embedding $\mathbf{H} \in \mathbb{R}^{N \times T \times D}$, (2) a GSL layer to learn dynamically evolving adjacency matrices $\mathbf{W}^{(1)}, ..., \mathbf{W}^{(n_d)}$, and (3) GNN layers to learn spatial dependencies between sensors given the learned graph structures and node features $\mathbf{H}$. While our model is general to any kind of GNN layers, we use an expressive GNN architecture, Graph Isomorphism Network (GIN) (Xu et al., 2019; Hu et al., 2020), in our experiments.

For graph classification tasks, a temporal pooling layer and a graph pooling layer are added to aggregate temporal and spatial representations, respectively, which is followed by a fully connected layer to produce a prediction for each multivariate signal. Whereas for node forecasting tasks, a fully connected layer is added to project to the output dimension. The total loss is the sum of the regularization loss and the prediction loss. Figure 1 shows the overall model architecture.

5 EXPERIMENTS

5.1 EXPERIMENTAL SETUP

In this section, we briefly introduce the datasets and experimental setup in our study. For each experiment, we ran three runs with different random seeds and report mean and standard deviation of the results. See Appendix A–B for details on datasets, model training procedures, and hyperparameters.

Seizure detection from EEGs. We first evaluate our model on EEG-based seizure detection. We use the publicly available Temple University Hospital Seizure Detection Corpus (TUSZ) v1.5.2 (Shah et al., 2018), and follow the experimental setup of seizure detection on 60-s EEG clips as in Tang et al. (2022b). The number of EEG sensors is 19. The sampling rate of each 60-s EEG clip is 200 Hz, resulting in a sequence length of 12k time steps. The task is binary classification of detecting whether or not a 60-s EEG clip contains seizure. The resolution r in GSL layer is chosen as 10-s (i.e., 2,000 time steps), which is inspired by how trained EEG readers analyze EEGs. As this is an inductive graph classification task, we adopt Equation 7 for graph structure learning. The EEG graphs are undirected.

We compare our model performance to existing models for seizure detection, including (1) LSTM (Hochreiter & Schmidhuber, 1997), a variant of RNN with gating mechanisms; (2) Dense-CNN (Saab et al., 2020), a densely connected CNN specialized in seizure detection; (3) CNN-LSTM (Ahmedt-Aristizabal et al., 2020); and (4) Dist- and Corr-DCRNN without and with self-supervised pre-training (Tang et al., 2022b). Following prior studies, we use AUROC as the evaluation metric.

Sleep staging from polysomnography signals. Next, we evaluate our model on sleep staging from polysomnography (PSG) signals. PSG is used in the diagnosis of sleep disorders such as obstructive sleep apnea. We use the publicly available Dreem Open Dataset-Healthy (DOD-H) (Guillot et al., 2020). We randomly split the data by 60/20/20 into train/validation/test sets, where each split consists of data from distinct subjects. The number of PSG sensors is 16. The sampling rate is 250 Hz, and thus each 30-s signal has 7,500 time steps. The task is to classify each 30-s PSG signal as one of the five sleep stages: wake, rapid eye movement (REM), non-REM sleep stages 1, 2,

and 3. The resolution r is 10-s (i.e., 2,500 time steps). This is also an inductive graph classification task, and thus we adopt Equation 7 for graph structure learning. The PSG graphs are undirected.

Baseline models include existing sleep staging models that achieve state-of-the-art on DOD-H dataset, SimpleSleepNet (Guillot et al., 2020) and RobustSleepNet (Guillot & Thorey, 2021), both of which are based on GRUs (Cho et al., 2014) and attention mechanisms. We also include the traditional sequence model LSTM (Hochreiter & Schmidhuber, 1997) as a baseline. For fair comparisons between the baselines and GRAPHS4MER, we trained SimpleSleepNet and RobustSleepNet using their open sourced code[1] and setting the temporal context to be one 30-s PSG signal. Similar to Guillot & Thorey (2021), we use macro-F1 score and Cohen's Kappa as the evaluation metrics.

Traffic forecasting. Finally, we evaluate our model on forecasting of traffic flows on the public PEMS-BAY dataset (Li et al., 2018b). The traffic dataset is collected by California Transportation Agencies (CalTrans) Performance Measurement System (PeMS) from January 1st 2017 to May 31st 2017. We follow the same experimental setup as that in Li et al. (2018b). The number of traffic sensors is 325. The traffic speed readings are aggregated into 5-min windows and the data are split by 70/10/20 into train/validation/test sets. The task is to predict the future 1 hour traffic flow (i.e., prediction horizon = 12 time steps) given the previous 1 hour traffic flow (12 time steps). The resolution r is set to be 12 time steps. This is a transductive node-level forecasting task, therefore we adopt Equation 8 for graph structure learning. The traffic graph is directed.

We compare our model performance to existing traffic forecasting models: (1) DCRNN (Li et al., 2018b), (2) Graph WaveNet (Wu et al., 2019), (3) Graph Multi-Attention Network (GMAN) (Zheng et al., 2020b), (4) Traffic Transformer (Cai et al., 2020), (5) Spacetimeformer (Grigsby et al., 2022), and (6) Adaptive Graph Spatial-Temporal Transformer Network (ASTTN) (Feng & Tassiulas, 2022). DCRNN, Graph WaveNet, and GMAN are temporal GNNs, whereas Traffic Transformer, Spacetimeformer, and ASTTN are transformer-based models. Following previous works, we use mean absolute error (MAE), root mean squared error (RMSE), and mean absolute percentage error (MAPE) as the evaluation metrics.

5.2 EXPERIMENTAL RESULTS

Seizure detection from EEG signals. Table 1 shows our model performance on EEG-based seizure detection and its comparison to existing models. GRAPHS4MER outperforms the previous state-of-the-art, Dist-DCRNN, by 3.1 points in AUROC. Notably, Dist-DCRNN was pretrained using a self-supervised task (Tang et al., 2022b), whereas GRAPHS4MER was trained from scratch.

Table 1: **Results of EEG-based seizure detection on TUSZ dataset.** Baseline model results are cited from Tang et al. (2022b). Best and second best results are **bolded** and underlined, respectively.

Model	AUROC
LSTM (Hochreiter & Schmidhuber, 1997)	0.715 ± 0.016
Dense-CNN (Saab et al., 2020)	0.796 ± 0.014
CNN-LSTM (Ahmedt-Aristizabal et al., 2020)	0.682 ± 0.003
Dist-DCRNN w/o Pretraining (Tang et al., 2022b)	0.793 ± 0.022
Corr-DCRNN w/o Pretraining (Tang et al., 2022b)	0.804 ± 0.015
Dist-DCRNN w/ Pretraining (Tang et al., 2022b)	0.875 ± 0.016
Corr-DCRNN w/ Pretraining (Tang et al., 2022b)	0.850 ± 0.014
GRAPHS4MER (ours)	**0.906 ± 0.012**

Sleep staging from PSG signals. Table 2 compares our model performance to existing sleep staging models on DOD-H dataset. GRAPHS4MER outperforms RobustSleepNet, a specialized sleep staging model, by 4.1 points in macro-F1. It is important to note that both SimpleSleepNet and RobustSleepNet preprocess the PSG signals using short-time Fourier transform, whereas our model directly operates on raw PSG signals without the need of preprocessing.

Traffic forecasting. Table 3 shows the performance of our model and existing traffic forecasting models on PEMS-BAY. We observe that GRAPHS4MER outperforms temporal GNNs (DCRNN,

---

[1]SimpleSleepNet: `https://github.com/Dreem-Organization/dreem-learning-open`; RobustSleepNet: `https://github.com/Dreem-Organization/RobustSleepNet`

Table 2: **Results of sleep staging on DOD-H dataset.** Best and second best results are **bolded** and underlined, respectively.

Model	Macro-F1	Kappa
LSTM (Hochreiter & Schmidhuber, 1997)	0.609 ± 0.034	0.539 ± 0.046
SimpleSleepNet (Guillot et al., 2020)	0.720 ± 0.001	0.703 ± 0.013
RobustSleepNet (Guillot & Thorey, 2021)	$\underline{0.777 \pm 0.007}$	$\underline{0.758 \pm 0.008}$
GRAPHS4MER (ours)	$\mathbf{0.818 \pm 0.008}$	$\mathbf{0.802 \pm 0.014}$

Graph WaveNet, GMAN) by a large margin and performs better than transformer-based models (ASTTN and Spacetimeformer) in MAE.

Table 3: **Results of traffic forecasting on PEMS-BAY dataset.** Baseline model results are cited from the literature. Best and second best results are **bolded** and underlined, respectively.

Model	MAE	RMSE	MAPE
DCRNN (Li et al., 2018b)	2.07	4.74	4.90%
Graph WaveNet (Wu et al., 2019)	1.95	4.52	4.63%
GMAN (Zheng et al., 2020b)	1.86	4.32	4.31%
Traffic Transformer (Cai et al., 2020)	1.77	4.36	4.29%
Spacetimeformer (Grigsby et al., 2022)	1.73	**3.79**	**3.85%**
ASTTN (Feng & Tassiulas, 2022)	$\underline{1.72}$	4.02	3.98%
GRAPHS4MER (ours)	$\mathbf{1.696 \pm 0.008}$	$\underline{3.989 \pm 0.023}$	$3.86\% \pm 0.02\%$

Effect of GSL. As GSL is an important component of GRAPHS4MER, we investigate the effect of GSL on the model performance. Table 4 shows the model performance when we remove the GSL layer in GRAPHS4MER and use predefined graphs. For seizure detection on TUSZ dataset, we use the predefined distance-based EEG graph as in Tang et al. (2022b); for traffic forecasting on PEMS-BAY, we use the predefined traffic sensor graph as in Li et al. (2018b). DOD-H dataset has no predefined graph available. We observe that GRAPHS4MER using GSL outperforms GRAPHS4MER with predefined graph on the TUSZ dataset, but not on the PEMS-BAY dataset. This suggests that sensor locations used for constructing the predefined traffic sensor graph (Li et al., 2018b) are critical for traffic forecasting. Nevertheless, a major advantage of our GSL method is that it does not require prior knowledge about the graph structure, which would be particularly useful when sensor locations are not available (e.g., sleep staging on DOD-H).

Table 4: Comparison of predefined graphs vs GSL. "-" indicates that no predefined graph is available. Best results are **bolded**.

Model	TUSZ (AUROC)	DOD-H (Macro-F1)	PEMS-BAY (MAE)
GRAPHS4MER w/ predefined graph	0.899 ± 0.010	-	$\mathbf{1.629 \pm 0.003}$
GRAPHS4MER (w/ GSL)	$\mathbf{0.906 \pm 0.012}$	0.818 ± 0.008	1.696 ± 0.008

Ablations. We perform ablation studies to investigate the importance of (1) graph-based representation, where we remove the GSL and GNN layers in our model and (2) S4 encoder, where we replace the S4 layers with GRUs (Cho et al., 2014). Table 5 shows the ablation results. There are several important observations. First, GRAPHS4MER consistently outperforms S4, suggesting the effectiveness of representing multivariate signals as graphs. Second, when S4 layers are replaced with GRUs, the model performance drops by a large margin, particularly on TUH and DOD-H datasets with long sequences (12k and 7.5k time steps, respectively). This indicates the effectiveness of S4 in modeling long-term temporal dependencies.

Visualization of EEG graphs. In Figure 2, we show example EEG graphs inferred by the GSL layer and corresponding raw EEG signals in the test set. A board-certified neurologist visually analyzed the EEG signals and inferred graphs. In the beginning (Figures 2a–2d), the seizure starts as a focal

Table 5: **Ablation results.** For S4, we remove the GSL and GNN layers in our model. For GRAPHS4MER w/o S4, we replace S4 with GRUs. Best and second best results are **bolded** and underlined, respectively.

Model	TUSZ (AUROC)	DOD-H (Macro-F1)	PEMS-BAY (MAE)
S4	0.824 ± 0.011	0.778 ± 0.009	2.262 ± 0.004
GRAPHS4MER w/o S4	0.705 ± 0.095	0.634 ± 0.061	1.723 ± 0.006
GRAPHS4MER	**0.906 ± 0.012**	**0.818 ± 0.008**	**1.696 ± 0.008**

seizure and the corresponding EEG graphs are sparse. Starting at the last 2-s of Figure 2e, the seizure starts to spread. In the last 10-s of this EEG clip (Figure 2f), the seizure spreads to all areas of the brain and the EEG graph becomes denser with more edges than the earlier EEG graphs. This change in graph connectivity reflects the dynamics of the seizure.

Figure 2: **Example EEG graphs of a 60-s EEG clip that has seizure in the test set (chronological order).** In each subfigure, top panel shows the inferred graph from the GSL layer and bottom panel shows the raw EEG signals.

6   CONCLUSION AND FUTURE WORK

In conclusion, we present GRAPHS4MER, a general GNN architecture combining Structured State Spaces model and graph structure learning for spatiotemporal modeling of multivariate signals. Our method sets new state-of-the-art on seizure detection, sleep staging, and traffic forecasting on three public datasets with distinct data modalities. Importantly, our method does not require prior knowledge about the graph structure, and thus would be particularly useful for applications where graph structures cannot be easily predefined. Our study opens exciting future directions for graph-based spatiotemporal modeling of multivariate signals, including (1) investigating if learned graphs are clinically interpretable for medical time series (e.g., Figure 2), (2) leveraging domain knowledge for improved graph structure learning, and (3) applying to other types of time series.

ETHICS STATEMENT

The Temple University Hospital EEG Seizure Corpus (TUSZ) is publicly available[2] and de-identified with full IRB approval (Shah et al., 2018). The DOD-H dataset is publicly available[3], deidentified, and was approved by the French Committees of Protection of Persons (Guillot et al., 2020). The PEMS-BAY dataset is publicaly available[4] and no human or animal subject is involved (Li et al., 2018b). No conflict of interest is reported from the authors. No harmful insights are provided by the models. While we show that our methods could provide improved performance for seizure detection and sleep staging, additional model validations are needed before they can be used in real-world clinical settings, such as (a) external validation on datasets from multiple institutions and (b) validation on subjects with different demographics.

REPRODUCIBILITY STATEMENT

All the datasets used in our study are publicly available. Details about datasets and model training procedures are provided in the Appendix. Source code is included in supplemental materials.

REFERENCES

David Ahmedt-Aristizabal, Tharindu Fernando, Simon Denman, Lars Petersson, Matthew J Aburn, and Clinton Fookes. Neural memory networks for seizure type classification. *Conf. Proc. IEEE Eng. Med. Biol. Soc.*, 2020:569–575, July 2020.

Martin Arjovsky, Amar Shah, and Yoshua Bengio. Unitary evolution recurrent neural networks. In Maria Florina Balcan and Kilian Q Weinberger (eds.), *Proceedings of The 33rd International Conference on Machine Learning*, volume 48 of *Proceedings of Machine Learning Research*, pp. 1120–1128, New York, New York, USA, 2016.

Umar Asif, Subhrajit Roy, Jianbin Tang, and Stefan Harrer. SeizureNet: Multi-Spectral deep feature learning for seizure type classification. In *Machine Learning in Clinical Neuroimaging and Radiogenomics in Neuro-oncology*, pp. 77–87. Springer International Publishing, 2020.

LEI Bai, Lina Yao, Can Li, Xianzhi Wang, and Can Wang. Adaptive graph convolutional recurrent network for traffic forecasting. In H Larochelle, M Ranzato, R Hadsell, M F Balcan, and H Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 17804–17815. Curran Associates, Inc., 2020.

Belkin and Niyogi. Laplacian eigenmaps and spectral techniques for embedding and clustering. *Adv. Neural Inf. Process. Syst.*, 2001.

Luc Berthouze, Leon M James, and Simon F Farmer. Human EEG shows long-range temporal correlations of oscillation amplitude in theta, alpha and beta bands across a wide age range. *Clin. Neurophysiol.*, 121(8):1187–1197, August 2010.

Michael M Bronstein, Joan Bruna, Yann LeCun, Arthur Szlam, and Pierre Vandergheynst. Geometric deep learning: Going beyond euclidean data. *IEEE Signal Process. Mag.*, 34(4):18–42, July 2017.

Ling Cai, Krzysztof Janowicz, Gengchen Mai, Bo Yan, and Rui Zhu. Traffic transformer: Capturing the continuity and periodicity of time series for traffic forecasting. *Trans. GIS*, 24(3):736–755, June 2020.

Enrico Camporeale, Simon Wing, and Jay Johnson. *Machine Learning Techniques for Space Weather*. Elsevier, May 2018.

Chami, Abu-El-Haija, Perozzi, Ré, and others. Machine learning on graphs: A model and comprehensive taxonomy. *Journal of Machine Learning Research*, 2022.

---

[2] https://isip.piconepress.com/projects/tuh_eeg/html/downloads.shtml
[3] https://github.com/Dreem-Organization/dreem-learning-open
[4] https://github.com/liyaguang/DCRNN

Yu Chen, Lingfei Wu, and Mohammed Zaki. Iterative deep graph learning for graph neural networks: Better and robust node embeddings. *Adv. Neural Inf. Process. Syst.*, 33:19314–19326, 2020.

Kyunghyun Cho, Bart van Merrienboer, Dzmitry Bahdanau, and Yoshua Bengio. On the properties of neural machine translation: Encoder-Decoder approaches. September 2014.

Krzysztof Marcin Choromanski, Valerii Likhosherstov, David Dohan, Xingyou Song, Andreea Gane, Tamas Sarlos, Peter Hawkins, Jared Quincy Davis, Afroz Mohiuddin, Lukasz Kaiser, David Benjamin Belanger, Lucy J Colwell, and Adrian Weller. Rethinking attention with performers. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=Ua6zuk0WRH`.

Ian C Covert, Balu Krishnan, Imad Najm, Jiening Zhan, Matthew Shore, John Hixson, and Ming Jack Po. Temporal graph convolutional networks for automatic seizure detection. In Finale Doshi-Velez, Jim Fackler, Ken Jung, David Kale, Rajesh Ranganath, Byron Wallace, and Jenna Wiens (eds.), *Proceedings of the 4th Machine Learning for Healthcare Conference*, volume 106 of *Proceedings of Machine Learning Research*, pp. 160–180. PMLR, 2019.

da Xu, chuanwei ruan, evren korpeoglu, sushant kumar, and kannan achan. Inductive representation learning on temporal graphs. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=rJeW1yHYwH`.

Defferrard, Bresson, and others. Convolutional neural networks on graphs with fast localized spectral filtering. *Adv. Neural Inf. Process. Syst.*, 2016.

Ahmed El-Gazzar, Rajat Mani Thomas, and Guido van Wingen. Dynamic adaptive Spatio-Temporal graph convolution for fMRI modelling. In Ahmed Abdulkadir, Seyed Mostafa Kia, Mohamad Habes, Vinod Kumar, Jane Maryam Rondina, Chantal Tax, and Thomas Wolfers (eds.), *Machine Learning in Clinical Neuroimaging*, pp. 125–134, Cham, 2021. Springer International Publishing.

N. Benjamin Erichson, Omri Azencot, Alejandro Queiruga, Liam Hodgkinson, and Michael W. Mahoney. Lipschitz recurrent neural networks. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=-N7PBXqOUJZ`.

Alireza Ermagun and David Levinson. Spatiotemporal traffic forecasting: review and proposed directions. *Transp. Rev.*, 38(6):786–814, November 2018.

Aosong Feng and Leandros Tassiulas. Adaptive graph Spatial-Temporal transformer network for traffic flow forecasting. July 2022.

Tianfan Fu, Wenhao Gao, Cao Xiao, Jacob Yasonik, Connor W. Coley, and Jimeng Sun. Differentiable scaffolding tree for molecular optimization, 2021. URL `https://arxiv.org/abs/2109.10469`.

Jianfei Gao and Bruno Ribeiro. On the equivalence between temporal and static equivariant graph representations. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 7052–7076. PMLR, 2022.

Xiang Gao, Wei Hu, and Zongming Guo. Exploring Structure-Adaptive graph learning for robust Semi-Supervised classification. In *2020 IEEE International Conference on Multimedia and Expo (ICME)*, pp. 1–6. ieeexplore.ieee.org, July 2020.

Ahmed El Gazzar, Rajat Mani Thomas, and Guido Van Wingen. Improving the diagnosis of psychiatric disorders with self-supervised graph state space models, 2022a. URL `https://arxiv.org/abs/2206.03331`.

Ahmed El Gazzar, Rajat Mani Thomas, and Guido Van Wingen. Improving the diagnosis of psychiatric disorders with self-supervised graph state space models, 2022b. URL `https://arxiv.org/abs/2206.03331`.

Karan Goel, Albert Gu, Chris Donahue, and Christopher Re. It's raw! Audio generation with state-space models. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 7616–7633. PMLR, 17–23 Jul 2022. URL `https://proceedings.mlr.press/v162/goel22a.html`.

Jake Grigsby, Zhe Wang, and Yanjun Qi. Long-range transformers for dynamic spatiotemporal forecasting, 2022. URL `https://arxiv.org/abs/2109.12218`.

Gu, Dao, Ermon, Rudra, and others. Hippo: Recurrent memory with optimal polynomial projections. *Adv. Neural Inf. Process. Syst.*, 2020.

Gu, Johnson, Goel, Saab, and others. Combining recurrent, convolutional, and continuous-time models with linear state space layers. *Adv. Neural Inf. Process. Syst.*, 2021.

Albert Gu, Karan Goel, and Christopher Re. Efficiently modeling long sequences with structured state spaces. In *International Conference on Learning Representations*, 2022.

Antoine Guillot and Valentin Thorey. RobustSleepNet: Transfer learning for automated sleep staging at scale. *IEEE Trans. Neural Syst. Rehabil. Eng.*, 29:1441–1451, July 2021.

Antoine Guillot, Fabien Sauvet, Emmanuel H During, and Valentin Thorey. Dreem open datasets: Multi-Scored sleep datasets to compare human and automated sleep staging. *IEEE Trans. Neural Syst. Rehabil. Eng.*, 28(9):1955–1965, September 2020.

S Hochreiter and J Schmidhuber. Long short-term memory. *Neural Comput.*, 9(8):1735–1780, November 1997.

Weihua Hu, Bowen Liu, Joseph Gomes, Marinka Zitnik, Percy Liang, Vijay Pande, and Jure Leskovec. Strategies for pre-training graph neural networks. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=HJlWWJSFDH`.

H H Jasper. The ten-twenty electrode system of the international federation. *Electroencephalogr. Clin. Neurophysiol.*, 10:370–375, 1958.

Weiwei Jiang and Jiayun Luo. Graph neural network for traffic forecasting: A survey. *Expert Syst. Appl.*, 207:117921, November 2022.

Wei Jin, Yao Ma, Xiaorui Liu, Xianfeng Tang, Suhang Wang, and Jiliang Tang. Graph structure learning for robust graph neural networks. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '20, pp. 66–74, New York, NY, USA, 2020. Association for Computing Machinery. ISBN 9781450379984. doi: 10.1145/3394486.3403049. URL `https://doi.org/10.1145/3394486.3403049`.

Vassilis Kalofolias. How to learn a graph from smooth signals. In *Proceedings of the 19th International Conference on Artificial Intelligence and Statistics*, volume 51 of *Proceedings of Machine Learning Research*, pp. 920–929, Cadiz, Spain, 2016. PMLR.

Amol Kapoor, Xue Ben, Luyang Liu, Bryan Perozzi, Matt Barnes, Martin Blais, and Shawn O'Banion. Examining covid-19 forecasting using spatio-temporal graph neural networks, 2020. URL `https://arxiv.org/abs/2007.03113`.

Katharopoulos, Vyas, Pappas, and others. Transformers are rnns: Fast autoregressive transformers with linear attention. *on Machine Learning*, 2020.

Jia Li, Zhichao Han, Hong Cheng, Jiao Su, Pengyun Wang, Jianfeng Zhang, and Lujia Pan. Predicting path failure in Time-Evolving graphs. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, KDD '19, pp. 1279–1289, New York, NY, USA, July 2019. Association for Computing Machinery.

Ruoyu Li, Sheng Wang, Feiyun Zhu, and Junzhou Huang. Adaptive graph convolutional neural networks. *AAAI*, 32(1), April 2018a.

Yaguang Li, Rose Yu, Cyrus Shahabi, and Yan Liu. Diffusion convolutional recurrent neural network: Data-driven traffic forecasting. In *International Conference on Learning Representations*, 2018b. URL https://openreview.net/forum?id=SJiHXGWAZ.

Ilya Loshchilov and Frank Hutter. SGDR: Stochastic gradient descent with warm restarts. In *International Conference on Learning Representations*, 2017. URL https://openreview.net/forum?id=Skq89Scxx.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=Bkg6RiCqY7.

Dongsheng Luo, Wei Cheng, Wenchao Yu, Bo Zong, Jingchao Ni, Haifeng Chen, and Xiang Zhang. Learning to drop: Robust graph neural network via topological denoising. In *Proceedings of the 14th ACM International Conference on Web Search and Data Mining*, WSDM '21, pp. 779–787, New York, NY, USA, March 2021. Association for Computing Machinery.

Christoph M Michel and Micah M Murray. Towards the utilization of EEG as a brain imaging tool. *Neuroimage*, 61(2):371–385, June 2012.

Ana Mincholé, Julià Camps, Aurore Lyon, and Blanca Rodríguez. Machine learning in the electrocardiogram. *J. Electrocardiol.*, 57S:S61–S64, November 2019.

Michael Negnevitsky, Paras Mandal, and Anurag K Srivastava. Machine learning applications for load, price and wind power prediction in power systems. In *2009 15th International Conference on Intelligent System Applications to Power Systems*, pp. 1–6. ieeexplore.ieee.org, November 2009.

Antonio Ortega, Pascal Frossard, Jelena Kovačević, José M F Moura, and Pierre Vandergheynst. Graph signal processing: Overview, challenges, and applications. *Proc. IEEE*, 106(5):808–828, May 2018.

George Panagopoulos, Giannis Nikolentzos, and Michalis Vazirgiannis. Transfer graph neural networks for pandemic forecasting. *AAAI*, 35(6):4838–4845, May 2021.

Aldo Pareja, Giacomo Domeniconi, Jie Chen, Tengfei Ma, Toyotaro Suzumura, Hiroki Kanezashi, Tim Kaler, Tao Schardl, and Charles Leiserson. EvolveGCN: Evolving graph convolutional networks for dynamic graphs. *AAAI*, 34(04):5363–5370, April 2020.

Huy Phan and Kaare Mikkelsen. Automatic sleep staging of EEG signals: recent development, challenges, and future directions. *Physiol. Meas.*, 43(4), April 2022.

Ashirbad Pradhan, Jiayuan He, and Ning Jiang. Hand gesture recognition and biometric authentication using a multi-day dataset. In *Intelligent Robotics and Applications*, pp. 375–385. Springer International Publishing, 2022.

Ilene M Rosen, Douglas B Kirsch, Kelly A Carden, Raman K Malhotra, Kannan Ramar, R Nisha Aurora, David A Kristo, Jennifer L Martin, Eric J Olson, Carol L Rosen, James A Rowley, Anita V Shelgikar, and American Academy of Sleep Medicine Board of Directors. Clinical use of a home sleep apnea test: An updated american academy of sleep medicine position statement. *J. Clin. Sleep Med.*, 14(12):2075–2077, December 2018.

Emanuele Rossi, Ben Chamberlain, Fabrizio Frasca, Davide Eynard, Federico Monti, and Michael Bronstein. Temporal graph networks for deep learning on dynamic graphs, 2020. URL https://arxiv.org/abs/2006.10637.

Khaled Saab, Jared Dunnmon, Christopher Ré, Daniel Rubin, and Christopher Lee-Messer. Weak supervision as an efficient approach for automated seizure detection in electroencephalography. *NPJ Digit Med*, 3:59, April 2020.

Youngjoo Seo, Michaël Defferrard, Pierre Vandergheynst, and Xavier Bresson. Structured sequence modeling with graph convolutional recurrent networks. In *Neural Information Processing*, pp. 362–373. Springer International Publishing, 2018.

Vinit Shah, Eva von Weltin, Silvia Lopez, James Riley McHugh, Lillian Veloso, Meysam Gol-mohammadi, Iyad Obeid, and Joseph Picone. The temple university hospital seizure detection corpus. *Front. Neuroinform.*, 12:83, November 2018.

Chao Shang, Jie Chen, and Jinbo Bi. Discrete graph structure learning for forecasting multiple time series. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=WEHSlH5mOk`.

Afshin Shoeibi, Marjane Khodatars, Navid Ghassemi, Mahboobeh Jafari, Parisa Moridian, Roohal-lah Alizadehsani, Maryam Panahiazar, Fahime Khozeimeh, Assef Zare, Hossein Hosseini-Nejad, Abbas Khosravi, Amir F Atiya, Diba Aminshahidi, Sadiq Hussain, Modjtaba Rouhani, Saeid Nahavandi, and Udayvara Rajendra Acharya. Epileptic seizures detection using deep learning techniques: A review. *Int. J. Environ. Res. Public Health*, 18(11), May 2021.

Jiabin Tang, Tang Qian, Shijing Liu, Shengdong Du, Jie Hu, and Tianrui Li. Spatio-temporal latent graph structure learning for traffic forecasting, 2022a. URL `https://arxiv.org/abs/2202.12586`.

Siyi Tang, Jared Dunnmon, Khaled Kamal Saab, Xuan Zhang, Qianying Huang, Florian Dubost, Daniel Rubin, and Christopher Lee-Messer. Self-Supervised graph neural networks for improved electroencephalographic seizure analysis. In *International Conference on Learning Representations*, April 2022b.

Yi Tay, Mostafa Dehghani, Samira Abnar, Yikang Shen, Dara Bahri, Philip Pham, Jinfeng Rao, Liu Yang, Sebastian Ruder, and Donald Metzler. Long range arena: A benchmark for efficient transformers, 2020. URL `https://arxiv.org/abs/2011.04006`.

Chenyu Tian and Wai Kin (victor) Chan. Spatial-temporal attention wavenet: A deep learning framework for traffic prediction considering spatial-temporal dependencies. *IET Intel. Transport Syst.*, 15(4):549–561, April 2021.

Vaswani, Shazeer, Parmar, and others. Attention is all you need. *Adv. Neural Inf. Process. Syst.*, 2017.

Yue Wang, Yongbin Sun, Ziwei Liu, Sanjay E Sarma, Michael M Bronstein, and Justin M Solomon. Dynamic graph CNN for learning on point clouds. *ACM Trans. Graph.*, 38(5):1–12, October 2019.

Zonghan Wu, Shirui Pan, Guodong Long, Jing Jiang, and Chengqi Zhang. Graph wavenet for deep spatial-temporal graph modeling. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI-19*, pp. 1907–1913. International Joint Conferences on Artificial Intelligence Organization, 7 2019. doi: 10.24963/ijcai.2019/264. URL `https://doi.org/10.24963/ijcai.2019/264`.

Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? In *International Conference on Learning Representations*, 2019. URL `https://openreview.net/forum?id=ryGs6iA5Km`.

Weizhi Xu, Junfei Wu, Qiang Liu, Shu Wu, and Liang Wang. Evidence-aware fake news detection with graph neural networks. January 2022.

Qi Zhang, Jianlong Chang, Gaofeng Meng, Shiming Xiang, and Chunhong Pan. Spatio-Temporal graph structure learning for traffic forecasting. *AAAI*, 34(01):1177–1185, April 2020.

Xiang Zhang and Marinka Zitnik. GNNGuard: Defending graph neural networks against adversarial attacks. *Adv. Neural Inf. Process. Syst.*, 33:9263–9275, 2020.

Xiang Zhang, Marko Zeman, Theodoros Tsiligkaridis, and Marinka Zitnik. Graph-guided network for irregularly sampled multivariate time series. In *International Conference on Learning Representations*, 2022. URL `https://openreview.net/forum?id=Kwm8I7dU-l5`.

Cheng Zheng, Bo Zong, Wei Cheng, Dongjin Song, Jingchao Ni, Wenchao Yu, Haifeng Chen, and Wei Wang. Robust graph representation learning via neural sparsification. In Hal Daumé Iii and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 11458–11468. PMLR, 2020a.

Chuanpan Zheng, Xiaoliang Fan, Cheng Wang, and Jianzhong Qi. GMAN: A graph Multi-Attention network for traffic prediction. *AAAI*, 34(01):1234–1241, April 2020b.

Yanqiao Zhu, Weizhi Xu, Jinghao Zhang, Yuanqi Du, Jieyu Zhang, Qiang Liu, Carl Yang, and Shu Wu. A survey on graph structure learning: Progress and opportunities. March 2021.

APPENDIX

A DETAILS OF DATASETS

Temple University Hospital Seizure Detection Corpus (TUSZ). We use the publicly available Temporal University Hospital Seizure Detection Corpus (TUSZ) v1.5.2. for seizure detection (Shah et al., 2018). We follow the same experimental setup as in Tang et al. (2022b). The TUSZ train set is divided into train and validation splits with distinct patients, and the TUSZ test set is held-out for model evaluation. The following 19 EEG channels are included: FP1, FP2, F3, F4, C3, C4, P3, P4, O1, O2, F7, F8, T3, T4, T5, T6, FZ, CZ, and PZ. Because the EEG signals are sampled at different sampling rate, we resample all the EEG signals to 200 Hz. Following a prior study (Tang et al., 2022b), we also exclude 5 patients in the TUSZ test set who appear in both the TUSZ train and test sets. The EEG signals are divided into 60-s EEG clips without overlaps, and the task is to predict whether or not an EEG clip contains seizure. Table 6 shows the number of EEG clips and patients in the train, validation, and test splits.

Table 6: Number of EEG clips and patients in train, validation, and test splits of TUSZ dataset.

Train Set		Validation Set		Test Set	
EEG Clips (% Seizure)	Patients (% Seizure)	EEG Clips (% Seizure)	Patients (% Seizure)	EEG Clips (% Seizure)	Patients (% Seizure)
38,613 (9.3%)	530 (34.0%)	5,503 (11.4%)	61 (36.1%)	8,848 (14.7%)	45 (77.8%)

Dreem Open Dataset-Healthy (DOD-H). We use the publicly available Dreem Open Dataset-Healthy (DOD-H) for sleep staging (Guillot et al., 2020). The DOD-H dataset consists of overnight PSG sleep recordings from 25 volunteers. The PSG signals are measured from 12 EEG channels, 1 electromyographic (EMG) channel, 2 electrooculography (EOG) channels, and 1 electrocardiogram channel using a Siesta PSG device (Compumedics). All the signals are sampled at 250 Hz. Following the standard AASM Scoring Manual and Recommendations (Rosen et al., 2018), each 30-s PSG signal is annotated by a consensus of 5 experienced sleep technologists as one of the five sleep stages: wake (W), rapid eye movement (REM), non-REM sleep stages 1, 2, and 3. We randomly split the PSG signals by 60/20/20 into train/validation/test splits, where each split has distinct subjects. Table 7 shows the number of 30-s PSG clips, the number of subjects, and the five sleep stage distributions.

Table 7: Number of subjects and 30-s PSG clips in the train, validation, and test splits of DOD-H dataset.

	Subjects	30-s PSG Clips					
		Total	Wake	N1	N2	N3	REM
Train Set	15	14,823	1,839	925	6,965	2,015	3,079
Validation Set	5	5,114	480	254	2,480	990	910
Test Set	5	4,725	718	326	2,434	509	738

PEMS-BAY traffic dataset. The PEMS-BAY dataset is collected by California Transportation Agencies (CalTrans) Performance Measurement System (PeMS). We follow the same experimental setup as in Li et al. (2018b). Specifically, 325 sensors in the Bay Area are selected with 6 months of data ranging from January 1st to May 31st, 2017. The traffic speed readings are aggregated into 5-min windows. The total number of observed traffic data points is 16,937,179. 70% of the data are used for training, 20% are used for testing, and the remaining 10% are used for validation.

B DETAILS OF MODEL TRAINING PROCEDURES AND HYPERPARAMETERS

Model training was accomplished using the AdamW optimizer (Loshchilov & Hutter, 2019) in PyTorch on a single NVIDIA A100 GPU. All experiments were run for three runs with different random seeds. Cosine learning rate scheduler with 5-epoch warm start was used (Loshchilov & Hutter, 2017). Model training was early stopped when the validation loss did not decrease for 20 consecutive epochs. We performed the following hyperparameter search on the validation set: (1) initial

learning rate within range [1e-4, 1e-2]; (2) dropout rate in S4 and GNN layers within range [0.1, 0.5]; (3) hidden dimension of S4 and GNN layers within range $\{64, 128, 256\}$; (4) number of S4 layers within range $\{2, 3, 4\}$; (5) S4 bidirectionality; (6) number of GNN layers within range $\{1, 2\}$; (7) graph pooling within range {mean-pool, max-pool, sum-pool} (only for graph classification tasks); (8) value of κ threshold for graph pruning; (9) KNN graph with $K \in \{2, 3\}$; (10) weight of KNN graph $\epsilon \in [0.3, 0.6]$; (11) α, β, and γ weights in graph regularization within range [0, 1]; (12) learnable node embedding dimension within range $\{10, 12, 16\}$ (only for traffic forecasting).

Model training for seizure detection on TUSZ dataset. As there are many more negative samples in the dataset, we undersampled the negative examples in the train set during training. We used binary cross-entropy loss as the loss function. The models were trained for 100 epochs with an initial learning rate of 8e-4. The batch size was 4; dropout rate was 0.1; hidden dimension was 128; number of stacked S4 layers was 4; S4 layers were unidirectional; number of GNN layers was 1; graph pooling was max-pool and temporal pooling was mean-pool; graph pruning was done by setting a threshold of 0.1, where edges whose edge weights $<= 0.1$ were removed; $K = 2$ for KNN graph and the KNN graph weight was 0.6; α, β, and γ weights were all set to 0.05. This results in 265k trainable parameters in GRAPHS4MER. Best model was picked based on the highest AUROC on the validation set.

Model training for sleep staging on DOD-H dataset. As the DOD-H dataset is highly imbalanced, we undersampled the majority classes in the train set during training. We used cross-entropy loss as the loss function. The models were trained for 100 epochs with an initial learning rate of 1e-3. The batch size was 4; dropout rate was 0.4; hidden dimension was 128; number of stacked S4 layers was 4 and S4 layers were unidirectional; number of GNN layers was 1; graph pooling was sum-pool and temporal pooling was mean-pool; graph pruning was done by setting a threshold of 0.1; $K = 3$ for KNN graph and the weight for KNN graph was 0.6; α, β, and γ weights were all set to 0.2. This results in 266k trainable parameters in GRAPHS4MER. Best model was picked based on the highest macro-F1 score on the validation set.

Model training for traffic forecasting on PEMS-BAY. Following Li et al. (2018b), we used mean absolute error (MAE) as the loss function. The models were trained for 100 epochs with an initial learning rate of 1e-3. The batch size was 32; dropout rate was 0.1; hidden dimension was 256; number of stacked S4 layers was 4 and S4 layers were bidirectional; number of GNN layers was 2; graph pruning was done by keeping the top 2% edges in the graph; $K = 3$ for KNN graph and the weight for KNN graph was 0.5; α, β, and γ weights were 0.1, 0.2, and 0.2, respectively; the learnable node embedding dimension was 16. This results in 865k trainable parameters in GRAPHS4MER. Best model was picked based on the lowest MAE on the validation set.