Normalizing Flows to Reconstruct Pseudo-PDFs

Yamil Cahuana Medrano
Department of Physics
William & Mary
Williamsburg, VA 23185
yacahuanamedra@wm.edu

Kostas Orginos
Department of Physics
William & Mary
Williamsburg, VA 23185
knorgi@wm.edu

Abstract

We investigate a normalizing-flow approach for reconstructing parton distribution functions (PDFs) from synthetic matrix-element data. Our framework combines Gaussian Process priors with invertible neural networks to learn a posterior distribution over PDFs consistent with limited Ioffe-time data. We demonstrate that the architecture preserves physical constraints and extrapolation properties.

1   Introduction

Parton distribution functions (PDFs) are essential to our understanding of hadron structure, representing a central pillar of particle physics research. Despite their importance, direct calculation remains challenging due to the non-perturbative nature of quark and gluon interactions at low energy scales. In the recent decade, several lattice frameworks Ji [2013], Radyushkin [2017] have been proposed to investigate these quantities by computing non-local matrix elements that follow

$$\langle P|\bar{\psi}(z)\gamma^\mu W(z,0)\psi(0)|P\rangle = P^\mu M(\nu, z^2) + z^\mu N(\nu, z^2) \tag{1}$$

where P and z represent the momentum of the hadron and the space-like separation, respectively, and $\nu = P \cdot z$ is the Lorentz-invariant quantity called the Ioffe-time. Using the ratio scheme to remove UV divergences, the pseudo-PDF $P(x, z^2)$ can be obtained through the solution of $M(\nu, z^2) = \int_{-1}^{1} dx e^{i\nu x} P(x, z^2)$, or equivalently

$$\text{Re}\, M(\nu, z^2) = \int_0^1 dx \cos(\nu x) q_-(x, z^2), \qquad \text{Im}\, M(\nu, z^2) = \int_0^1 dx \sin(\nu x) q_+(x, z^2), \tag{2}$$

where $q_+(x, z^2) = P(x, z^2) - P(-x, z^2)$ represents the singlet (C-even) distribution, and $q_-(x, z^2) = P(x, z^2) + P(-x, z^2)$ represents the valence (C-odd) distribution. From this point we will not consider the z dependence of PDF, because the matching procedure does not interfere with the inverse problem at hand.

Gaussian processes (GP) allow one to encode smoothness, correlations, and physically motivated constraints within a non-parametric Bayesian setting Rasmussen and Williams [2006], while preserving a controlled description of uncertainty from simple regression problems to the solution of inverse problems in the context of differential equations Raissi et al. [2017]. Several approaches have been explored to address this inverse problem, including Bayesian methods Karpie et al. [2019], neural-network parameterizations Del Debbio et al. [2021], Cichy et al. [2019], and Gaussian process regression Alexandrou et al. [2020], Candido et al. [2024], Medrano et al. [2026], which have been shown to provide robust PDF reconstructions from limited Fourier components in lattice QCD.

In practice, the reconstruction depends on the data and physical constraints, but some precautions have to be taken to constrain the possible behavior in the extrapolation region of Ioffe time, where

Conference on Physics and AI at Stanford University (PAI 2026).

lattice information is limited or non-existent. Previous work Dutrieux et al. [2025] introduced a physically motivated prescription to fix this prior scale, thereby controlling the uncertainty in the reconstructed distributions. That approach is transparent, efficient, and well justified from the physics of the problem.

The motivation of the present work is to explore if this hyperparameter-selection step can be mapped to a normalizing-flow architecture, called in the literature Invertible Neural Networks, and retain the flexibility of GPs while exploring if the specified calibration procedure is present in this alternative method and leads to equivalent results.

2 Method

Invertible Neural Networks (INNs) Ardizzone et al. [2019], a class of normalizing flows Papamakarios et al. [2021], are designed to learn the full posterior distribution of the solution to an inverse problem. They achieve this by establishing a bijective mapping f between the space of physical quantities of interest and the space of observables. Since these spaces naturally have different dimensions, bijectivity is strictly enforced by introducing latent variables and zero padding. The effectiveness of this architecture relies on three components: structurally invertible affine coupling layers, a bidirectional loss function, and the ability to train on an extensive dataset generated through the forward mapping.

GP prior. A PDFs data set can be generated by sampling from a normal distribution. In this context, Gaussian processes (GPs) provide an efficient way to sample functions from a Gaussian distribution over a discretized x-grid. This approach allows us to generate the training data

$$q_{\text{train}}(x) \sim \mathcal{N}\left(\mu(x), K(x, x')\right), \tag{3}$$

considering the normalization and the boundary condition

$$B_0 \cdot q = \int_0^1 \delta(x - 1)q(x)dx = q(1) = 0 \qquad B_1 \cdot q = \int_0^1 q(x)dx = 1. \tag{4}$$

We have imposed with Lagrange multipliers $\lambda_{1,2}$ such conditions in covariance and mean as

$$K = K_{\text{log-rbf}}^{-1} + \frac{B_0^\top B_0}{\lambda_1} + \frac{B_1^\top B_1}{\lambda_2} \quad \mu = K^{-1}\left(K_{\text{log-rbf}}^{-1} \cdot \mu_0 + \frac{B_1^\top}{\lambda_2}\right) \tag{5}$$

where $\mu_0(x) = 2(1 - x)$ and the kernel $K_{\text{log-rbf}}(x, x') = 30 \cdot e^{-\frac{|\log(x) - \log(x')|^2}{0.72}}$. To generate the corresponding Ioffe-time distributions (ITDs), we approximate the integrals in Eq. (2) using second-order finite elements, yielding a discrete linear operator B, such that

$$[M_{\text{train}}]_n = [B]_{n \times k} \cdot [q_{\text{train}}]_k. \tag{6}$$

with $n = 1, \ldots N_\nu$ and $k = 1, \ldots N_x$. In our setting, the PDF is discretized on an equally spaced grid of $N_x = 129$ points in $(10^{-3}, 1 - 10^{-8})$, while only a limited number of ITD data points, $N_\nu \sim 10$, are available. The solution of the inverse problem consists in the construction of a bijector $f : \mathbb{R}^{N_x} \to \mathbb{R}^{N_\nu + N_z}$, where N_z denotes the dimension of the latent space such that $N_x = N_\nu + N_z$. Following Ardizzone et al. [2019], we parameterize the missing information in the noise dimension using a fixed number N_{noise} of variables, and fill the remaining degrees of freedom with N_{pad} zeros such that $N_z = N_{\text{noise}} + N_{\text{pad}}$. This procedure guarantees that the INN operates on equal input and output dimensions, while access to a virtually infinite data set ensures convergence of the posterior distribution. A fundamental step in data processing is normalization. We normalize each sample using the prior mean $\langle q \rangle$ and point-wise variance $\text{std}(q) = \sqrt{K_{\text{log-rbf}}(x, x)}$ by $q_{train} \to \frac{q_{\text{train}} - \langle q \rangle}{\text{std}(q)}$. This step helps with stability for the divergent functional form of the PDFs and the convergence of the loss function by addressing the different scales of the PDF in the x-grid.

Affine Coupling Layers. Our INN is based on affine coupling layers, following the Real NVP architecture Dinh et al. [2017], Bishop and Bishop [2023]. The input vector q is partitioned into two disjoint blocks, $q = [q_1, q_2]$, in a random but fixed manner. To ensure invertibility, the forward transformation from input to output variables $M = [m_1, m_2]$ is defined as

$$m_1 = q_1, \qquad m_2 = q_2 \odot e^{s(q_1)} + t(q_1). \tag{7}$$

Figure 1: Schematic representation of the INN architecture with forward integration using finite elements for the imaginary part of the matrix elements.

where $\odot$ denotes element-wise multiplication, and the scaling s and translation t operations can be arbitrarily complex functions. In this work, s and t are parameterized by standard feed-forward neural networks. By stacking multiple affine coupling layers, we construct the full INN architecture. The key advantage of this formulation is that the inverse mapping can be computed analytically and efficiently without needing to invert the neural networks s and t. By reversing the sequential operations, the inverse pass is explicitly given by:

$$q_1 = m_1, \qquad q_2 = (m_2 - t(m_1)) \odot e^{-s(m_1)}. \tag{8}$$

In the inverse mapping, the input $M = [m_1, m_2]$ consists of concatenated ITD data, latent variables, and zero-padding elements. The full INN architecture is constructed by stacking six affine coupling layers $g : \mathbb{R}^{N_x} \to \mathbb{R}^{N_\nu + N_z}$, such that $f = g^{(1)} \circ \cdots \circ g^{(6)}$, as shown in Fig. 1. Each coupling block contains two subnetworks s, t, each a 3-layer MLP with hidden dimension 256 and LeakyReLU(0.2) activations. The scale outputs are clamped via $\sigma(s) = \tanh(s)$ to prevent instabilities.

Maximum Mean Discrepancy. The third component of our architecture is the training objective. To train the INN to accurately reproduce the full posterior, we employ the maximum mean discrepancy (MMD). As shown in Mehraban and Pichler [2025], MMD is a kernel-based technique that provides a robust measure of the distance between two probability distributions based on their samples.

Given two sets of samples, $\{x_i\}_{i=1}^n$ from the target distribution and $\{y_j\}_{j=1}^m$ from the model distribution, the MMD estimator is given by

$$\mathcal{L}_{\mathrm{MMD}^2}(X,Y) = \frac{1}{n^2} \sum_{i=1}^n \sum_{j=1}^n k(x_i, x_j) + \frac{1}{m^2} \sum_{i=1}^m \sum_{j=1}^m k(y_i, y_j) - \frac{2}{nm} \sum_{i=1}^n \sum_{j=1}^m k(x_i, y_j). \tag{9}$$

where $k(\cdot, \cdot)$ is a positive-definite kernel. Following Ardizzone et al. [2019], we utilize an Inverse Multi-Quadratic (IMQ) kernel

$$k_{IMQ}(\mathbf{x}, \mathbf{y}) = \frac{1}{1 + \frac{\|\mathbf{x}-\mathbf{y}\|^2}{\sigma}}, \tag{10}$$

which is effective for comparing distributions with heavy tails while remaining suitable for Gaussian-like samples. The active parameter in the kernel is chosen to be $\sigma \in [0.25s, 0.5s, s, 2s, 4s]$ with $s = \mathrm{median}\big(\{\|x_i - y_j\|^2 = \|x_i\|^2 + \|y_j\|^2 - 2x_i^\perp y_j\}\big)$.

In the context of our inverse problem, this loss is evaluated in both directions to ensure our neural network learns the distribution of the input and output, comparing the forward-mapped ITD data and latent variables against their prior distributions, and comparing the inverse-mapped predicted PDFs, $q_{\mathrm{INN}} = f^{-1}(M = M_{train}, z_{noise}, z_{pad})$, against the target forward-simulated training data, q_{train}. Similarly, the forward INN data is generated by $M_{INN}, z_{INN}^{noise}, z_{INN}^{pad} = f(q_{train})$. We optimize the following loss

$$\mathcal{L} = \lambda_x \, \mathcal{L}_{\mathrm{MMD}^2}(q_{\mathrm{INN}}, q_{\mathrm{train}}) + \lambda_z \, \mathcal{L}_{\mathrm{MMD}^2}\big((M_{\mathrm{INN}}, z_{\mathrm{INN}}^{noise}), (M_{\mathrm{train}}, z_{\mathrm{noise}})\big)$$
$$+ \lambda_y \, \|M_{\mathrm{INN}} - M_{\mathrm{train}}\|_1 + \lambda_{\mathrm{pad}} \, \|z_{INN}^{pad}\|_2^2. \tag{11}$$

Figure 2: Comparison of different reconstructions of the PDF varying the noise dimensions.

where $\lambda_x = \lambda_y = \lambda_z = 1/3$ and $\lambda_{\mathrm{pad}} = 1/6$. The norm $\|\cdot\|_1$ term is designed to accelerate convergence to the true distribution in the forward direction, and the $\|\cdot\|_2$ term minimizes the padded output to zero.

The network parameters are optimized using the Adam optimizer Kingma and Ba [2017] with an initial learning rate of 10^{-4} and a cosine-annealing warm-restart schedule Loshchilov and Hutter [2017]. Gradients are clipped to unit norm to improve training stability. All results were obtained from models trained on an NVIDIA A100 GPU.

3 Results

Closure Test. To evaluate the performance of the INN, we design a parametric PDF and map it to the Ioffe-time distribution to generate the closure test. This is done by proposing the following

$$q_{val}(x) = \frac{x^\alpha (1-x)^\beta}{B(\alpha+1, \beta+1)} \rightarrow M_{val} = B \cdot q_{val} \tag{12}$$

where $\alpha = \mathcal{N}(-0.2, 0.5)$ and $\beta = \mathcal{N}(3.0, 0.5)$, and q_{val} is discretized in the same grid used for the GP prior. The same normalization procedure with respect to the prior was applied to the ITD data points.

A comparison across different latent-space dimensions is shown in Fig. 2. In this exploration of the dimensionality of the Gaussian noise, the PDF reconstruction remains consistent in the region close to 1. However, we observe a dependence on the latent dimension in the extrapolation region at low x and high ν, which is an indicator that the regularization of the inverse problem is controlled by the latent/noise variables. Additionally, the evaluation across different ν ranges is shown in Fig. 3. It is evident that the reconstruction improves as more information in the ITD is included as the range of ν grows. This is a feature present in other approaches like Gaussian process regression, Bayesian inference, and parametric regression.

Figure 3: Comparison of different reconstructions of the PDF varying the ITD data available.

4 Discussion

On the one hand, the architecture successfully preserves the GP prior constraints, such as normalization and the boundary condition $q(x = 1) = 0$. On the other hand, we identify two main limitations. First, normalization with respect to the prior distribution constrains the INN to operate only on datasets consistent with the prior ITD distribution. This limitation may be alleviated in future work by training on a broader set of GP prior samples generated from different kernel parameterizations and means, as well as by introducing a global mean and variance scale to normalize the data.

A more detailed analysis of the padding and noise dimensions is needed to characterize their impact on the PDF and ITD regions and to identify an optimal configuration. The choice of noise dimensionality is closely related to the criterion employed in Gaussian process regression. Nevertheless, the present approach provides a learned alternative that leads to similar conclusions and serves as a proof of concept for future studies. For instance, the method can be generalized to reconstruct the dependence on z using real lattice data. It can also be extended to incorporate Mellin moment measurements. Furthermore, for higher-dimensional quantities, such as generalized parton distribution functions, this approach can be naturally extended to those settings.

5 Conclusion

We have presented an alternative approach to reconstruct PDFs from synthetic Ioffe-time distribution (ITD) data. The results demonstrate that the INN produces stable reconstructions and captures the main features of the underlying mapping. In this framework, the latent variables encode the missing degrees of freedom in the inverse problem.

While the method inherits the dependence on the choice of prior and latent dimensionality, it offers a data-driven alternative to existing approaches. This work serves as a proof of concept for combining GP priors with invertible neural networks in lattice QCD reconstructions. Future work will focus on extending the framework to real lattice data, incorporating additional observables like Mellin moments, and exploring more expressive flow architectures.

Acknowledgments and Disclosure of Funding

This work is supported by Jefferson Science Associates, LLC under U.S. DOE Contract #DE-AC05-06OR23177. YC acknowledges support in part from the Southeastern Universities Research Association (SURA) through Grant C2024-FEMT-011-03, awarded by the Center for Nuclear Femtography (CNF) and in part by the Fulbright-Garcia Robles scholarship.

KO was supported in part by U.S. DOE grant #DE-FG02-04ER41302. The authors acknowledge William & Mary Research Computing for providing computational resources and/or technical support that have contributed to the results reported within this paper. In addition, resources of the National Energy Research Scientific Computing Center (NERSC) through the ERCAP project "hadron" were used. NERSC is a U.S. Department of Energy Office of Science User Facility located at Lawrence Berkeley National Laboratory, operated under Contract No. DE-AC02-05CH11231.

References

Xiangdong Ji. Parton Physics on a Euclidean Lattice. *Phys. Rev. Lett.*, 110:262002, 2013. doi: 10.1103/PhysRevLett.110.262002.

A. V. Radyushkin. Quasi-parton distribution functions, momentum distributions, and pseudo-parton distribution functions. *Phys. Rev. D*, 96(3):034025, 2017. doi: 10.1103/PhysRevD.96.034025.

Carl Edward Rasmussen and Christopher K. I. Williams. *Gaussian Processes for Machine Learning*. The MIT Press, 2006.

Maziar Raissi, Paris Perdikaris, and George Em Karniadakis. Machine learning of linear differential equations using gaussian processes. *Journal of Computational Physics*, 348:683–693, November 2017. ISSN 0021-9991. doi: 10.1016/j.jcp.2017.07.050. URL http://dx.doi.org/10.1016/j.jcp.2017.07.050.

Joseph Karpie, Kostas Orginos, Alexander Rothkopf, and Savvas Zafeiropoulos. Reconstructing parton distribution functions from ioffe time data: from bayesian methods to neural networks. *Journal of High Energy Physics*, 2019(4), April 2019. ISSN 1029-8479. doi: 10.1007/jhep04(2019)057. URL http://dx.doi.org/10.1007/JHEP04(2019)057.

Luigi Del Debbio, Tommaso Giani, Joseph Karpie, Kostas Orginos, Anatoly Radyushkin, and Savvas Zafeiropoulos. Neural-network analysis of parton distribution functions from ioffe-time pseudodistributions. *Journal of High Energy Physics*, 2021(2), February 2021. ISSN 1029-8479. doi: 10.1007/jhep02(2021)138. URL http://dx.doi.org/10.1007/JHEP02(2021)138.

Krzysztof Cichy, Luigi Del Debbio, and Tommaso Giani. Parton distributions from lattice data: the nonsinglet case. *Journal of High Energy Physics*, 2019(10), October 2019. ISSN 1029-8479. doi: 10.1007/jhep10(2019)137. URL http://dx.doi.org/10.1007/JHEP10(2019)137.

Constantia Alexandrou, Giovanni Iannelli, Karl Jansen, and Floriano Manigrasso. Parton distribution functions from lattice qcd using bayes-gauss-fourier transforms. *Physical Review D*, 102(9), November 2020. ISSN 2470-0029. doi: 10.1103/physrevd.102.094508. URL http://dx.doi.org/10.1103/PhysRevD.102.094508.

Alessandro Candido, Luigi Del Debbio, Tommaso Giani, and Giacomo Petrillo. Bayesian inference with gaussian processes for the determination of parton distribution functions, 2024. URL https://arxiv.org/abs/2404.07573.

Yamil Cahuana Medrano, Hervé Dutrieux, Joseph Karpie, Kostas Orginos, and Savvas Zafeiropoulos. Gaussian processes for inferring parton distributions, 2026. URL https://arxiv.org/abs/2510.21041.

Hervé Dutrieux, Joseph Karpie, Kostas Orginos, and Savvas Zafeiropoulos. Simple nonparametric reconstruction of parton distributions from limited Fourier information. *Phys. Rev. D*, 111(3):034515, 2025. doi: 10.1103/PhysRevD.111.034515.

Lynton Ardizzone, Jakob Kruse, Sebastian Wirkert, Daniel Rahner, Eric W. Pellegrini, Ralf S. Klessen, Lena Maier-Hein, Carsten Rother, and Ullrich Köthe. Analyzing inverse problems with invertible neural networks, 2019. URL `https://arxiv.org/abs/1808.04730`.

George Papamakarios, Eric Nalisnick, Danilo Jimenez Rezende, Shakir Mohamed, and Balaji Lakshminarayanan. Normalizing flows for probabilistic modeling and inference, 2021. URL `https://arxiv.org/abs/1912.02762`.

Laurent Dinh, Jascha Sohl-Dickstein, and Samy Bengio. Density estimation using real nvp, 2017. URL `https://arxiv.org/abs/1605.08803`.

Christopher Michael Bishop and Hugh Bishop. *Deep Learning - Foundations and Concepts*. 1 edition, 2023. ISBN 978-3-031-45468-4. doi: https://doi.org/10.1007/978-3-031-45468-4.

Zahra Mehraban and Alois Pichler. Quantization of probability measures in maximum mean discrepancy distance, 2025. URL `https://arxiv.org/abs/2503.11868`.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization, 2017. URL `https://arxiv.org/abs/1412.6980`.

Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts, 2017. URL `https://arxiv.org/abs/1608.03983`.