ON PRE-TRAINED LANGUAGE MODELS FOR ANTIBODY

ABSTRACT

Antibodies are vital proteins offering robust protection for the human body from pathogens. The development of general protein and antibody-specific pre-trained language models both facilitate antibody prediction tasks. However, few studies comprehensively explore the representation capability of distinct pre-trained language models on different antibody problems. Here, to investigate the problem, we aim to answer the following key questions: (1) How do pre-trained language models perform in antibody tasks with different specificity? (2) How many benefits will the model gain if we introduce the specific biological mechanism to the pre-training process? (3) Do the learned antibody pre-trained representations make sense in real-world antibody problems, like drug discovery and immune process understanding? Previously, no benchmark available largely hindered the study to answer these questions. To facilitate the investigation, we provide an **AnTi**body **Understanding Evaluation** (`ATUE`) benchmark. We comprehensively evaluate the performance of protein pre-trained language models by empirical study along with conclusions and new insights.

1 INTRODUCTION

Antibodies are special type of proteins extensively used as diagnostic and therapeutic tools against diverse diseases, such as SARS-CoV-2 (Zhu et al., 2022). Deciphering the information stored in antibody sequences is highly important with regard to real-world therapeutic antibody development and immune understanding (Greiff et al., 2020; Lu et al., 2018; Yermanos et al., 2018). Fortunately, the recent progress of general **P**re-trained **P**rotein **L**anguage **M**odels (PPLM) and specific **P**re-trained **A**ntibody **L**anguage **M**odels (PALM) provide new prospects for antibody-related tasks. For example, many studies have shown that the representations learned by PPLMs are promising to transfer to antibody tasks (Kim et al., 2021; Zaslavsky et al., 2022). For PALMs, they have been shown to improve model performance in antibody paratope predictions (Leem et al., 2022).

Despite the current success, few studies comprehensively investigate the representation capability of different pre-trained language models (e.g. general PPLM and specific PALM) on distinct antibody tasks, which limits our ability to design better architectures that can help antibody discovery and modification. For example, in Figure 1, we compare the performance of the pre-trained protein language model ESM (Rives et al., 2021), the pre-trained antibody language model AntiBERT (Leem et al., 2021), and the model trained from scratch on three antibody tasks. These three tasks range from low to high in terms of antibody specificity. Here, specificity refers to the antibody's evolution, for example, the antibody evolves to obtain the ability to bind antigen (discussed in detail in Section 3.1).

Figure 1: Performance of pre-trained language models on tasks with different specificity. ESM-1 belongs to PPLMs and AntiBERT belongs to PALMs. EATLM is the method with a specific antibody mechanism introduced.

It can be observed that although ESM performs well in the task that has low relevance with antibodies, the performance dramatically degrades in tasks of higher relevance. Besides, AntiBERT does not show clear advantages over the non-pretrained model in the high specificity task. The results point out the

weaknesses of current pre-training language models for antibody studies: Direct adaptation of general PPLM representations may damage the performance; Pre-training strategies for PALMs cannot fit the specific antibody biological function well. All of these call for a comprehensive guideline of model designing for different antibody tasks. Mainly, we focus on answering the following questions:

(I) How do pre-trained language models perform in antibody tasks with different specificity? Addressing of the question is mainly hindered by two challenges: the lack of a reliable antibody-specific benchmark for performance evaluation and a comprehensive study of current PPLMs and PALMs. **(II) How many additional benefits will the model gain if the biological mechanism is introduced to the pre-training process?** Antibody-specific evolution has been employed by many computational biology studies and shows promising results in antibody-related tasks, such as disease diagnosis and therapeutic antibody development (Yermanos et al., 2018; Miho et al., 2019). Then, it is interesting to know whether antibody representation learning can benefit from the incorporation of antibody-specific evolution information **(III) Does the learned antibody pretrained representations make sense in real-world antibody problems, like drug discovery and immune process understanding?** Since antibody is so important that is extensively used for drug development in the real world, it is interesting to know whether pre-trained representation can indeed help biologists to understand antibody functions or discover drugs.

To investigate these questions, we first propose antibody study benchmark **AnT**ibody **U**nderstanding **E**valuation (**ATUE**). This is the first antibody benchmark with four real-world supervised tasks covering therapeutic antibody engineering, B cell analysis, and antibody discovery. To evaluate models on different aspects of antibody biological functions, these tasks are designed to have specificity ranging from low to high. Based on `ATUE`, we perform comprehensive empirical studies to investigate the representation ability of distinct pre-trained language models. We also explore the influence of involving specific biological mechanisms in antibody pretraining by proposing a **E**volution-aware **A**ntibody **L**anguage **M**odel (**EATLM**). We introduce two objectives to tailor masked language modeling for evolution: (1) **A**ncestor **G**ermline **P**rediction (**AGP**) guides the model to discriminate the evolutionary relationship between antibody and ancestral sequences. (2) **M**utation **P**osition **P**rediction (**MPP**), mimicking hypermutation during the evolution, predicts mutation positions and residues. It is the first attempt to incorporate antibody evolution information into the pre-training framework. Furthermore, we take a close look at the SARS-CoV-2 antibody discovery to investigate the pre-trained representation under a real-world scenario.

Our contributions can be divided three-fold.

- For facilitating antibody application studies, we develop the first comprehensive antibody benchmark to benefit the community. We also introduce two objectives tailored for antibody evolution.
- For providing guidelines for a better antibody representation, we have the following key observations: **(i)** PPLMs perform well on antibody tasks that have a high relationship with structure, such as the binding with antigen. However, they perform worst in tasks with high antibody specificity, indicating representation benefiting protein structure prediction is harmful to antibody-specific tasks. **(ii)** In most cases, PALMs perform as well as or even better than PPLMs with less pretraining data. **(iii)** PALMs can be improved by incorporating the evolution process. However, the evolution information from MSAs does not always benefit the antibody tasks. **(iv)** The introduction of two antibody biological mechanisms facilitates PALMs with more antibody-specific features and improves model performance, especially in the task with high antibody specificity.
- For accelerating real-world antibody discovery, we identified 11 potential SARS-CoV-2 binders whose sequences are highly identical to existing therapeutic antibodies binding with the virus.

2 RELATED WORK

Our work focuses on researching the effectiveness of protein and antibody pre-trained language models for antibody-specific tasks. Below we review the existing methods. We list the details in Table 1.

Pretrained Protein Language Models (PPLMs) There is an increasing interest in exploring large-scale language models using protein sequences (Rao et al., 2019; Madani et al., 2020; Meier et al., 2021). These models have been shown to achieve state-of-art capacity in predicting protein structure and function. ProtTrans (Elnaggar et al., 2021) and ESM-1b (Rives et al., 2021) take individual

protein sequences as input and adopt Transformer language models for pre-training, demonstrating that self-supervision is a promising paradigm for protein secondary structure, contact, homology predictions, and function prediction. To extract evolutionary information from protein sequences, Rao et al. (2021) proposed the MSA-transformer/MSA-1b model utilizing multiple sequence alignment (MSA) instead of a single query sequence as input. This model is superior to ESM-1b for structure prediction, demonstrating evolution information can benefit protein representation learning. Despite the progress in the field, few studies reported protein PLM transfer learning results on antibody tasks.

Pretrained Antibody Language Models (PALMs) Encouraged by the success of PLMs in protein representation learning, series work seeks to learn antibody representations based on sequences of antibodies. (Leem et al., 2021; Ruffolo et al., 2021; Olsen et al., 2022b; Prihoda et al., 2022). AntiBERTy (Ruffolo et al., 2021) proposed the first antibody-specific language model, exploring Transformer trained on 558M natural antibody sequences in the OAS database. The case study in the work showed the representation obtained from the PLM is useful for antibody sequence clustering into trajectories resembling affinity maturation. Olsen et al. (2022b) train two language models for antibody. A heavy chain version Ablang-H is trained on 14M sequences and a light chain version Ablang-L on 0.19M sequences. The study reported transfer learning results on restoring missing residues of antibody sequences, which is a toy task similar to pre-training objectives. AntiBERTa (Leem et al., 2021) train the antibody language model on OAS. Although this paper claims finetuning AntiBERTa for paratope position prediction can achieve state-of-the-art performance, none of the experiments have standard deviations, making it unclear how significant the results obtained are.

Table 1: Pre-training language models for protein and antibody. Specificity refers to the relationship between the model design and the antibody biological functionality. Evolution denotes whether evolutionary related sequences are used during the pretraining. MLM is masked language modeling pretraining objective. HC, antibody heavy chain; LC, antibody light chain.

Specificity	Model	Category	Dataset	Evolution	Objective	Antibody Tasks
Low	ESM-1	PPLM	UniRef50 (27M)	×	MLM	-
Low	MSA-1b	PPLM	UniRef50 (26M MSAs)	✓	MLM	-
Medium	Ablang-H	PALM	OAS (14M HC)	×	MLM	Reconstruction
Medium	Ablang-L	PALM	OAS (0.19M LC)	×	MLM	Reconstruction
Medium	AntiBERTa	PALM	OAS (72M)	×	MLM	Paratope Prediction
High	EATLM	PALM	OAS (20M)	✓	MLM, AGP & MPP	ATUE

3 FRAMEWORK

In this section, we first give a brief introduction to the antibody and its specific evolution. Then we propose the first antibody-specific benchmark (`ATUE`) composed of four tasks with different specificity. Finally, we implement several PPLMs and PALMs baselines and design an evolution-aware PALM (`EATLM`) to incorporate the biological mechanism into the pre-training process.

3.1 BACKGROUND

Antibody Antibodies are vital proteins generated by the immune system to remove harmful foreign pathogens in the human body. they can specifically bind to antigen on the pathogen and recognize it. Antibodies are composed of two identical heavy chains and two identical light chains and form a large Y-shaped structure. Two tips on it contains highly variable loops, called Complementarity Determining Regions (CDR), function for antigen binding.

Antibody Specific Evolution Notably, antibody evolution process is significant different from that of proteins, providing a good opportunity for us to investigate the impact of general PPLMs on specific subdomains. To perform its protective function, antibody sequence undergoes evolution selection to search for optimal patterns that can specifically recognize pathogens (Honjo & Habu, 1985). Deciphering the information stored in antibody sequences may benefit our understanding of disease and accelerate therapeutic antibody development (Greiff et al., 2020; Lu et al., 2018; Yermanos

Figure 2: Antibody prediction tasks. The specificity of tasks ranges from low to high.

et al., 2018). During evolution, the random recombination of V/D/J-gene segments provides the initial diversity for the ancestor sequence (germline). Upon exposure to a pathogen, this sequence undergoes frequent sequence mutations to search for progeny antibody sequences with optimal binding specificity. In other words, gene recombination provides millions of germlines in the human body, and the germlines further mutate into a huge number of progeny antibodies. Thus, the ancestor relationship between antibody and its corresponding germline as well as the mutation it undergoes together determine the unique biological functions. In brief, the evolutionary relationships between antibodies arise to gain new functions such as antigen binding. It is significantly different from that of proteins, which are to certain functions across different organisms. We further illustrate this process in Figure 7 in Appendix A.1.

Unsupervised Antibody Corpus To obtain the evolutionary information of antibody sequences, we utilize Observed Antibody Space (OAS), a database containing more than 1.5 billion natural antibody sequences (Kovaltsuk et al., 2018; Olsen et al., 2022a) The antibody sequences in the database have been precisely annotated with evolutionary and structural information, including the paired germline and CDR3 for each antibody. To pair the antibody with its germline used in the pretraining task, we used the annotated sequences provided in the OAS database. Further information on data processing can be found in Appendix A.2.

3.2 ANTIBODY UNDERSTANDING EVALUATION (ATUE)

We provide four biologically relevant downstream prediction tasks to serve as antibody benchmarks, covering four major application aspects for antibodies in the real world: therapeutic antibody engineering, disease diagnostics, antibody discovery, and B cell maturation analysis. Notably, the antibody evolution relatedness of these tasks ranges from low to high, offering scaled tasks with subdomain specificity for pre-trained language model evaluation. Detailed information is listed in Figure 2. All data are publicly open and used under the right license. For each task, we focus on the following aspects and leave other details in Appendix A.3.:

    [Definition] The formal definition of the task and the understanding ability required.
    [Impact] The importance of the task in the biological area.
    [Dataset] The data source and size.
    [Specificity] Antibody's specific evolution characteristics that is different from general proteins.

We use several classification metrics to evaluate the performance. Accuracy (**ACC**) calculates the ratio of correctly predictions. Matthews Correlation Coefficient (**MCC**) is the coefficient between true and predicted values. **F1** is the average weighted score of precision and recall. **AUC** is the area under the ROC curve, which shows the performance at all classification thresholds.

Antigen Binding Prediction is a binary sequence classification task to determine whether the CDR region of the antibody can bind to the specific antigen.

    [Impact] A better understanding of the binding affinity between antibody and antigen can accelerate the affinity optimization of therapeutic antibodies.
    [Dataset] We collect the antigen binding data from (Mason et al., 2021) and follow the training/validation/test split of 15,128/3,242/3,242. The paratope data is collected from

(Liberis et al., 2018) with 1,662 CDR segments on 277 antibodies.

[Specificity] Low. All the antibodies sequence in the dataset are derived from a single germline sequence indicating the task is not antibody-specific evolution-related.

Paratope Prediction is to identify binding positions on the antibody sequence, which is a sequence labeling task to predict a 0/1 label for each residue of CDR fragments.

[Impact] The exploration of paratope (binding positions between antibody and antigen) can help to understand the binding mechanisms of therapeutic antibodies.

[Dataset] We collect the antigen binding data from (Mason et al., 2021) and follow the training/validation/test split of 15,128/3,242/3,242. The paratope data is collected from (Liberis et al., 2018) with 1,662 CDR segments on 277 antibodies.

[Specificity] This task is medium specificity related because only partial antibodies from the database are derived from evolution.

B Cell Maturation Analysis It is a 6-category classification task to distinguish the maturation stage of B cell antibody sequences. Each sequence belongs to one of {*immature, transitional, mature, plasmacytes, memory IgD+, memory IgD-*}. It requires the model to learn a representation sensitive to different maturation states.

[Impact] It benefits the understanding of the mechanism during immune evolution, which is a critical biological process in the immune system affecting the function and antigen specificity of antibodies (Ghraichy et al., 2021; Meffre et al., 2000).

[Dataset] We collect 88,094 sequences from (Mroczek et al., 2014).

[Specificity] High. Antibody evolution is highly coupled with B cell maturation. (Meffre et al., 2000)

Antibody Discovery The task is a binary sequence classification task to distinguish which antibody is directly responsible for SARS-CoV-2 binding. The task is highly challenging from two aspects: (1) Less than 1% of antibodies from SARS-CoV-2 patients are directly responsible for virus binding. (2) It is hard to get a reliable sequence-level classifier using unreliable and noisy individual-level labels.

[Impact] Antibody discovery from B cell repertoire has been widely recognized as a important approach to accelerate antibody discovery for diverse antigens (Weiner, 2015; Pedrioli & Oxenius, 2021), and achieved great success for SARS-CoV-2 antibody discovery (Kovaltsuk et al., 2018; Cao et al., 2020; Shiakolas et al., 2022).

[Dataset] We collected antibody sequences from 133 SARS-CoV-2 patients and 87 health persons from OAS and followed the processing pipeline of (Kim et al., 2021). Inspired Zaslavsky et al. (2022), we match the high-ranked sequences with the sequences in the CoV-AbDab (Raybould et al., 2021) database, which have been proved to bind SARS-CoV-2 using wet-lab experiments.

[Specificity] High. It is widely reported antibodies derived from the same disease such as SARS-CoV-2 share strong convergent germline signals (Galson et al., 2020).

3.3 EXPERIMENT SETUP

Based on the antibody benchmark ATUE, we evaluate the performance of current pertaining language models in tasks with different specificity. Furthermore, to investigate the benefit of introducing the biological mechanism, we incorporate evolution information as the extra pretraining objectives for PALMs and propose EATLM. The detailed description can be found in Appendix A.4

Current Pre-trained language models Existing antibody and protein language models are summarized in Table 1. We choose two representative PALMs pre-trained on large-scale antibody sequences, Ablang (Olsen et al., 2022b), AntiBERTa (Leem et al., 2022) in this study. Since the code and pre-training data of AntiBERTa are not released, we train a BERT model named **AntiBERT** on the full OAS database following the same setting as the original study. We evaluate two representative PPLMs: ESM[1] and MSA-1b/MSA-Transformer. MSA-1b (Rao et al., 2021) is a Transformer-based language model taking protein-specific evolutionary sequences (Multiple Sequence Alignment, MSA) as the input to get context embeddings. Because it is hard to align sequences between antibodies due to the diversity of CDR3, we take the germline and create pseudo MSAs with depth 2.

---

[1]To make a fair comparison, we use the released base version **ESM-1**, which has 86M parameters.

Table 2: Performance of PPLMs and PALMs on antibody tasks with increasing specificity.

	Antigen Binding (Low)			Paratope (Medium)			B Cell (High)
	AUC	F1	MCC	AUC	F1	MCC	ACC
No pretrain	0.858±0.014	0.584±0.330	0.432±0.183	0.845±0.014	0.605±0.033	0.463±0.037	0.554 ± 0.042
ESM-1	0.917±0.001	0.854±0.002	0.689±0.002	0.886±0.009	0.669±0.024	0.547±0.026	0.503 ± 0.031
MSA-1b	0.921±0.001	0.857±0.004	0.689±0.014	0.887±0.009	0.679±0.019	0.557±0.025	0.416 ± 0.050
Ablang-H	0.918±0.001	0.861±0.003	**0.704±0.010**	0.878±0.009	0.674±0.018	0.546±0.023	0.570 ± 0.010
Ablang-L	0.917±0.002	0.856±0.001	0.682±0.001	0.882±0.010	0.680±0.018	0.553±0.023	0.546 ± 0.008
AntiBERT	0.918±0.003	0.843±0.009	0.678±0.008	0.879±0.011	0.690±0.020	0.559±0.026	0.565 ± 0.028
EATLM	0.922±0.004	**0.862±0.004**	0.699±0.010	**0.887±0.008**	**0.698±0.017**	**0.575±0.024**	**0.581 ± 0.005**
EATLM w/o AGP	0.920±0.003	0.855±0.000	0.697±0.008	0.883±0.011	0.676±0.021	0.552±0.027	0.559 ± 0.012
EATLM w/o MPP	**0.923±0.001**	0.855±0.002	0.687±0.005	0.883±0.011	0.691±0.022	0.566±0.030	0.563 ± 0.010
EATLM w/o AGP & MPP	0.918±0.001	0.845±0.005	0.681±0.005	0.880±0.009	0.674±0.018	0.552±0.023	0.559 ± 0.009

Evolution-aware antibody pretraining method To incorporate the biological mechanism into the pre-training, we propose the **A**ntibody **E**volu**T**ion-aware pretraining **L**anguage **M**odel. The antibody can be represented as A and the germline of the individual antibody can be represented as G. Typically, PALMs are trained with basic masked language modeling (MLM). Based on it, we design another two pre-training objectives to simulate the biological mechanism of antibody evolution. The evolutionary relationship between the antibody and its germline includes two folds: (i) Whether the antibody and the germline have an evolutionary relationship. (ii) How to mutate residues from the germline to get the specific antibody. Two evolution-related objectives are introduced to solve the above questions: ancestor germline prediction (AGP) and mutation position prediction (MPP). For ancestor germline prediction, we substitute the paired germline G with random germline G' in the batch via a probability p. The model is made to distinguish the ancestor germline of the antibody by capturing the shared features. To predict mutation position, for each token in the germline G, the objective is to predict a 0/1 label for each token to indicate whether this token has been mutated. For the antibody sequence S, we mask the mutation position and predict these tokens.

Hyper-parameters We use the base Transformer architecture (Vaswani et al., 2017) with 12 layers, 12 heads, and 768 hidden states. The total parameters are 86M. For each task in ATUE, we finetune the model with supervised data. We follow the standard split of Antigen Binding Prediction. For other tasks that do not provide a standard split, we conduct 10-cross validation and report the average results. Since our pre-training model learns the representation of the antibody sequence, we expand the CDR fragment to the full antibody via searching the biological database for therapeutic antibody engineering tasks. We also use the same Transformer architecture to train from scratch for each downstream task. This model is indicated as No pretrain since it does not have pre-training.

4 RESULTS

In this section, we present the results and discussions for the representation capability of existing PPLMs and PALMs as well as our evolution-incorporated EATLM using ATUE dataset.

4.1 SUPERVISED ANTIBODY PREDICTION

Antigen binding Here, we evaluate the performance PLMs models for antibody binding and paratope prediction, which are less antibody specific. The results are shown in Table 2 It is observed that PPLMs and PALMs achieve comparable performance on this task, indicating PALMs can learn similar general protein representation as PPLMs. Among different PALMs, Ablang-H outperforms Ablang-L and AntiBERT. It indicates that separate training for heavy and light chain sequences is helpful for this task. The introduction of AGP and MPP provides a little improvement over AUC and F1 metrics.

Paratope prediction As the results shown in Table 2, for paratope prediction, both PPLMs and PALMs can significantly boost the prediction accuracy over the model with pre-training. However, PALM doesn't show much significant advantage over PPLMs. EATLM achieves the best performance, especially on F1 and MCC, while other pertaining models have a high recall and a low precision.

It indicates that those models tend to predict more residues as the binding site. However, with the introduction of mutation residue prediction, `EATLM` can focus on the mutated positions that are adapted to bind with antigen. Among two PPLMs, MSA-1b outperforms ESM-1 on F1 and MCC, which benefits from the structure information learning from MSAs.

B Cell Analysis In this task, we examine the representation capacity of different pre-trained language models for distinguishing different B cell mature states during evolution. The results are shown in Table 2. In general, we find PPLMs can hardly distinguish the minor differences between B cell sequences by showing compromising results. Both the performance of ESM-1 and MSA-1b is significantly worse than randomly initialized models. MSA-1b performs the worst in all pre-trained language models, indicating representation that can perform well in protein structure prediction will be harmful to antibody-specific tasks. Conversely, all PALMs show promising results for the task. The reason may lie in that the general protein has little relationship with the special antibody mature process and can hardly capture this

Figure 3: B cell evolution category prediction. For each p_{ij} in $i-$th row and j-th column, it means the frequency for the model to predict the antibody in i category to j category. The number is normalized by row.

feature during the protein pretraining process. `EATLM` significantly outperforms the other PALMs. This is because by explicitly modeling the biological mechanism, our model can effectively capture the evolution feature and better distinguish between B cells at different stages of maturation.

We conduct further analysis to figure out whether our `EATLM` successfully captures sequence characteristics during the evolutionary process. We explore the probabilities of predicting antibodies in class i to class j. The results shown in 3 reveal `EATLM` can easily classify the immature B cell with an accuracy of 0.9. It is consistent with the biological study that CDR3 sequence length in immature B cells is significantly shorter than that of the other mature B cells (Ghraichy et al., 2021). From the diagonal, we can figure out that our model tends to mistake the B cell sequences with their previous or post-evolutionary stage, consistent with the biological process.

Antibody Discovery Here, we examine PPLMs and PALMS for their capacity in benefiting real-world problems and enabling the discovery of antigen-specific antibodies. Following the methods in this study Zaslavsky et al. (2022), we considered two steps for the SARS-CoV-2 specific antibody discovery. First, we generate a sequence classifier to distinguish SARS-CoV-2 antibodies using noisy individual-level labels. Then, the high-ranked sequences are matched with the sequences with true binding sequences in the CoV-AbDab (Raybould et al., 2021) database. We use the 90% sequence identity as the threshold to determine whether the antibody is similar to existing SARS binders in the CoV-AbDab database. A high similarity indicates a high probability of having the same biological functionality as the existing binders. The details can be found in Appendix A.6.

Figure 4: The cumulative sum of matched sequences number in the order of the predicted probability. EATLM outperforms other PALMs and PPLMs for finding SARS-CoV-2 binder faster highlighted in arrow 1 and finding all antibodies faster highlighted in arrow 2.

In Figure 4, we plot the cumulative sum of matched sequences number in the order of the predicted probability of the classifiers. We can find that the sequences predicted with high probability by PALMs match with the existing binders better than PPLMs. It means that PALMs can figure out the potential binders more efficiently. Besides, `EATLM` significantly outperforms other PALMs as the red line shows. In the early stage, this method is the quickest way to find potential binders. Then it loses to Ablang-H but finally overtakes again and converges. It means that `EATLM` is the first one to figure out all potential binders in this dataset.

Furthermore, we list several potential binders found by `EATLM` in Table 3. Without supervised labels, `EATLM` gives a high probability of 2 SARS-CoV-2 existing binding antibodies. Besides, `EATLM` proposes 9 potential sequences with high CDR-H3 sequence identity. Further analysis of the results reveals `EATLM` enables diverse-epitope antibody discovery and priority selection, demonstrating `EATLM` benefits therapeutic antibody discovery. The detailed explanations can be found in Appendix A.6.

To examine whether the antibody sequences with 90% sequence identity can indeed bind the same target, we investigate the 3D structure of the true binding antibody. Table 4 shows only one signle atom difference between the predicted binder and the existing binder, suggesting the predicted binders are highly possible to interact with SARS-CoV-2.

Table 3: The CDR3-H3 region of high-ranked sequences to bind to SARS. We show the CDR3 fragment of the heavy chain in the antibody sequences. 'Identity' is the similarity between the predicted binder and the true binder. The epitope of the true binders are shown. The origin of majority of the true binder sequences are B cells from patients. The different amino acids between predicted binder and existing binder are highlighted in red

No	Predicted Binder	Existing Binder	Epitope	Identity
1	AREGIVGATTGFDY	AREGIVGATTGFDY	spike	1.000
2	ARDLGGYFDY	ARDLGGYFDY	RBD	1.000
3	AKDQDD**A**YYYYYYMDV	AKDQDD**G**YYYYYYMDV	NTD	0.938
4	ASYYYDSSGY**H**YGMDV	ASYYYDSSGY**Y**YGMDV	RBD	0.938
5	ARRG**L**GLYYYGMDV	ARRG**D**GLYYYGMDV	S2	0.929
6	ARA**F**RGSYYYGMDV	ARA**T**RGSYYYGMDV	S2	0.929
7	ARLSGSSW**Y**FDY	ARLSGSSW**D**FDY	spike	0.917
8	AR**L**GSSSWYFDY	AR**V**GSSSWYFDY	spike	0.917
9	ARGWLRGYFDL	AR**R**GWLRGYFDL	RBD	0.909
10	ARDWGE**L**YFDY	ARDWGE**Y**YFDY	RBD	0.909
11	ARDLGG**V**FDY	ARDLGG**Y**FDY	RBD	0.900

Table 4: 3D structure of the true SARS-CoV-2 binding antibody No.3. G2A highlight the single atom difference in No.3, indicating the predicted binder is highly likely to bind the virus.

PDB:7N62

4.2 HOW DOES EVOLUTION PRETRAINING TASK INFLUENCE THE REPRESENTATION?

To understand why `EATLM` shows better performance on antibody tasks, we analyze the pre-trained representations to evaluate the effectiveness of the evolution-aware pretraining strategies from two aspects: (1) Does the pre-trained antibody representation reflect its ancestor relationship? (2) Is the specificity of antibodies captured by the evolution objective?

Ancestor Gerlime Visualization We perform UMAP visualization analyses in Figure 5. First, we observe that antibodies evolved from the same germline are nicely clustered together (Figure 5a and 5b), indicating the learned embedding is encoded with germline information. Besides, sequences with similar scales of evolutionary distance tend to cluster together, and a clear gradation of evolutionary distance can be observed in Figure 5c and 5d.

Accuracy of Mutation Position Based on the specific evolution process described in Section 3.1, we can find the mutation during the evolution process bring specificity to the antibody. Thus, we explore the model's ability to predict mutated residue from the masked token, which can reflect the specificity feature the model captures. We find that although AntiBERT can predict with the accuracy of 0.8889 on all positions, it fails on mutation positions with a 0.0311 accuracy. In contrast, `EATLM` achieves an accuracy of 0.443 on mutation position, which indicates that the model captures the specificity information. Note that during the MPP training, we mask the mutation position on antibody sequences, which are different from its germline. Thus, the model cannot get the mutated residue from the germline directly. The only way is to learn the underlying mutation rules. The full results are shown in Table 8a in Appendix.

| (a) Health germlines. | (b) Patient germlines. | (c) Health distance. | (d) Patient distance. |

Figure 5: UMAP Visualization. (a-b) for sequences with different germlines. One color indicates one germline with its descendant. (c-d) for evolutionary phylogeny distance. The shade of color indicates its distance from the ancestor germline.

4.3 KEY OBSERVATIONS

The performance of pre-trained language models highly depends on the task specificity. For tasks with low antibody-specificity relatedness, PPLMs show comparable performance with PALMs, indicating that transferring the general protein representations from PPLMs is an effective and time-saving way in these tasks. PALMs show their advantage and outperform PPLMs on medium specificity relatedness tasks, like paratope prediction. For tasks with high specificity, it is observed the performance of PPLMs dramatically decreased, suggesting general pre-trained protein models are not sufficient in antibody-specific representation learning. Interestingly, the performance of MSA-1b is 20% less than the model without pre-training. This observation is consistent with the biological study that the mechanism of antibody evolution is significantly different from that of proteins. Therefore, the incorporation of protein evolution information is not always good for antibody tasks, especially the tasks that require antibody evolution information.

Incorporation of biological evolution mechanism into PALM generally benefits antibody prediction tasks. Evolution-related training objectives help detect mutation positions on antibodies, which is a distinguishing feature from germline. Interestingly, the performance increase of `EATLM` compared with other PALMs is correlated with task specificity relatedness. The ablation study showed the removal of the evolution-related pretraining objectives results in performance decreasing, confirming that evolution-related objectives benefit the prediction. Future studies to have more in-depth research in this direction could be promising.

Figure 6: Performance summary of various pre-trained language models.

Antibody pre-trained representations are helpful for real-world drug discovery. Using the language model, we predict the probability for each antibody of being a binder with SARS-CoV-2. Without accurate sequence-level labels, we successfully identify 11 potential antibody binders.

5 CONCLUSIONS AND LIMITATIONS

In this paper, we have presented comprehensive empirical studies to characterize the impact of pre-trained protein and antibody language models for antibody prediction tasks. Four important antibody tasks from four biological categories with evolution relatedness ranging from high to low are provided `ATUE` to facilitate the antibody and ML field.

However, there are some limitations to this work. First, for the `ATUE` benchmark, the task diversity is highly limited because of data scarcity. With the data increase in this field, we expect we can update our benchmark with more disease diversity and data size in the future. Also, we do not test any 3D structure information during antibody pre-training. As a special subgroup of proteins, antibody structures provide much more information such as geometry than sequences. In the future, recruiting structure information for antibody pre-training may be able to improve the results.

REFERENCES

Yunlong Cao, Bin Su, Xianghua Guo, Wenjie Sun, Yongqiang Deng, Linlin Bao, Qinyu Zhu, Xu Zhang, Yinghui Zheng, Chenyang Geng, et al. Potent neutralizing antibodies against sars-cov-2 identified by high-throughput single-cell sequencing of convalescent patients' b cells. *Cell*, 182(1): 73–84, 2020.

Ahmed Elnaggar, Michael Heinzinger, Christian Dallago, Ghalia Rehawi, Yu Wang, Llion Jones, Tom Gibbs, Tamas Feher, Christoph Angerer, Martin Steinegger, et al. Prottrans: Towards cracking the language of lifes code through self-supervised deep learning and high performance computing. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2021.

Jacob D Galson, Sebastian Schaetzle, Rachael JM Bashford-Rogers, Matthew IJ Raybould, Aleksandr Kovaltsuk, Gavin J Kilpatrick, Ralph Minter, Donna K Finch, Jorge Dias, Louisa K James, et al. Deep sequencing of b cell receptor repertoires from covid-19 patients reveals strong convergent immune signatures. *Frontiers in immunology*, 11:605170, 2020.

Marie Ghraichy, Valentin von Niederhäusern, Aleksandr Kovaltsuk, Jacob D Galson, Charlotte M Deane, and Johannes Trück. Different b cell subpopulations show distinct patterns in their igh repertoire metrics. *ELife*, 10:e73111, 2021.

Victor Greiff, Gur Yaari, and Lindsay G Cowell. Mining adaptive immune receptor repertoires for biological and clinical information using machine learning. *Current Opinion in Systems Biology*, 24:109–119, 2020.

Namita T Gupta, Kristofor D Adams, Adrian W Briggs, Sonia C Timberlake, Francois Vigneault, and Steven H Kleinstein. Hierarchical clustering can identify b cell clones with high confidence in ig repertoire sequencing data. *The Journal of Immunology*, 198(6):2489–2499, 2017.

Tasuku Honjo and Sonoko Habu. Origin of immune diversity: genetic variation and selection. *Annual review of biochemistry*, 54(1):803–830, 1985.

Inyoung Kim, Sang Yoon Byun, Sangyeup Kim, Sangyoon Choi, Jinsung Noh, Junho Chung, and Byung Gee Kim. Analysis of b-cell receptor repertoires in covid-19 patients using deep embedded representations of protein sequences. *bioRxiv*, 2021.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In Yoshua Bengio and Yann LeCun (eds.), *Proc. of ICLR*, 2015.

Aleksandr Kovaltsuk, Jinwoo Leem, Sebastian Kelm, James Snowden, Charlotte M Deane, and Konrad Krawczyk. Observed antibody space: a resource for data mining next-generation sequencing of antibody repertoires. *The Journal of Immunology*, 201(8):2502–2509, 2018.

Jinwoo Leem, Laura S Mitchell, James HR Farmery, Justin Barton, and Jacob D Galson. Deciphering the language of antibodies using self-supervised learning. *bioRxiv*, 2021.

Jinwoo Leem, Laura S Mitchell, James HR Farmery, Justin Barton, and Jacob D Galson. Deciphering the language of antibodies using self-supervised learning. *Patterns*, pp. 100513, 2022.

Marie-Paule Lefranc, Véronique Giudicelli, Chantal Ginestoux, Julia Bodmer, Werner Müller, Ronald Bontrop, Marc Lemaitre, Ansar Malik, Valérie Barbié, and Denys Chaume. Imgt, the international immunogenetics database. *Nucleic acids research*, 27(1):209–212, 1999.

Edgar Liberis, Petar Veličković, Pietro Sormanni, Michele Vendruscolo, and Pietro Liò. Parapred: antibody paratope prediction using convolutional and recurrent neural networks. *Bioinformatics*, 34(17):2944–2950, 2018.

Lenette L Lu, Todd J Suscovich, Sarah M Fortune, and Galit Alter. Beyond binding: antibody effector functions in infectious diseases. *Nature Reviews Immunology*, 18(1):46–61, 2018.

Ali Madani, Bryan McCann, Nikhil Naik, Nitish Shirish Keskar, Namrata Anand, Raphael R Eguchi, Po-Ssu Huang, and Richard Socher. Progen: Language modeling for protein generation. *arXiv preprint arXiv:2004.03497*, 2020.

Derek M Mason, Simon Friedensohn, Cédric R Weber, Christian Jordi, Bastian Wagner, Simon M Meng, Roy A Ehling, Lucia Bonati, Jan Dahinden, Pablo Gainza, et al. Optimization of therapeutic antibodies by predicting antigen specificity from antibody sequence via deep learning. *Nature Biomedical Engineering*, 5(6):600–612, 2021.

Eric Meffre, Rafael Casellas, and Michel C Nussenzweig. Antibody regulation of b cell development. *Nature immunology*, 1(5):379–385, 2000.

Joshua Meier, Roshan Rao, Robert Verkuil, Jason Liu, Tom Sercu, and Alex Rives. Language models enable zero-shot prediction of the effects of mutations on protein function. *Advances in Neural Information Processing Systems*, 34, 2021.

Enkelejda Miho, Rok Roškar, Victor Greiff, and Sai T Reddy. Large-scale network analysis reveals the sequence space architecture of antibody repertoires. *Nature communications*, 10(1):1–11, 2019.

Zachary Montague, Huibin Lv, Jakub Otwinowski, William S DeWitt, Giulio Isacchini, Garrick K Yip, Wilson W Ng, Owen Tak-Yin Tsang, Meng Yuan, Hejun Liu, et al. Dynamics of b cell repertoires and emergence of cross-reactive responses in patients with different severities of covid-19. *Cell Reports*, 35(8):109173, 2021.

Eva Szymanska Mroczek, Gregory C Ippolito, Tobias Rogosch, Kam Hon Hoi, Tracy A Hwangpo, Marsha G Brand, Yingxin Zhuang, Cun Ren Liu, David A Schneider, Michael Zemlin, et al. Differences in the composition of the human antibody repertoire by b cell subsets in the blood. *Frontiers in immunology*, 5:96, 2014.

Tobias H Olsen, Fergus Boyles, and Charlotte M Deane. Observed antibody space: A diverse database of cleaned, annotated, and translated unpaired and paired antibody sequences. *Protein Science*, 31 (1):141–146, 2022a.

Tobias H Olsen, Iain H Moal, and Charlotte M Deane. Ablang: An antibody language model for completing antibody sequences. *bioRxiv*, 2022b.

Alessandro Pedrioli and Annette Oxenius. Single b cell technologies for monoclonal antibody discovery. *Trends in immunology*, 42(12):1143–1158, 2021.

David Prihoda, Jad Maamary, Andrew Waight, Veronica Juan, Laurence Fayadat-Dilman, Daniel Svozil, and Danny A Bitton. Biophi: A platform for antibody design, humanization, and humanness evaluation based on natural antibody repertoires and deep learning. In *MAbs*, volume 14, pp. 2020203. Taylor & Francis, 2022.

Roshan Rao, Nicholas Bhattacharya, Neil Thomas, Yan Duan, Peter Chen, John Canny, Pieter Abbeel, and Yun Song. Evaluating protein transfer learning with tape. *Advances in neural information processing systems*, 32, 2019.

Roshan M Rao, Jason Liu, Robert Verkuil, Joshua Meier, John Canny, Pieter Abbeel, Tom Sercu, and Alexander Rives. Msa transformer. In *International Conference on Machine Learning*, pp. 8844–8856. PMLR, 2021.

Matthew IJ Raybould, Aleksandr Kovaltsuk, Claire Marks, and Charlotte M Deane. Cov-abdab: the coronavirus antibody database. *Bioinformatics*, 37(5):734–735, 2021.

Alexander Rives, Joshua Meier, Tom Sercu, Siddharth Goyal, Zeming Lin, Jason Liu, Demi Guo, Myle Ott, C Lawrence Zitnick, Jerry Ma, et al. Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. *Proceedings of the National Academy of Sciences*, 118(15), 2021.

Krishna M Roskin, Katherine JL Jackson, Ji-Yeun Lee, Ramona A Hoh, Shilpa A Joshi, Kwan-Ki Hwang, Mattia Bonsignori, Isabela Pedroza-Pacheco, Hua-Xin Liao, M Anthony Moody, et al. Aberrant b cell repertoire selection associated with hiv neutralizing antibody breadth. *Nature immunology*, 21(2):199–209, 2020.

Jeffrey A Ruffolo, Jeffrey J Gray, and Jeremias Sulam. Deciphering antibody affinity maturation with language models and weakly supervised learning. *arXiv preprint arXiv:2112.07782*, 2021.

Andrea R Shiakolas, Kevin J Kramer, Nicole V Johnson, Steven C Wall, Naveenchandra Suryadevara, Daniel Wrapp, Sivakumar Periasamy, Kelsey A Pilewski, Nagarajan Raju, Rachel Nargi, et al. Efficient discovery of sars-cov-2-neutralizing antibodies via b cell receptor sequencing and ligand blocking. *Nature Biotechnology*, pp. 1–6, 2022.

Martin Steinegger and Johannes Söding. Clustering huge protein sequence sets in linear time. *Nature communications*, 9(1):1–8, 2018.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (eds.), *Proc. of NeurIPS*, pp. 5998–6008, 2017.

Yiquan Wang, Meng Yuan, Huibin Lv, Jian Peng, Ian A Wilson, and Nicholas C Wu. A large-scale systematic survey reveals recurring molecular features of public antibody responses to sars-cov-2. *Immunity*, 2022.

George J Weiner. Building better monoclonal antibody-based therapeutics. *Nature Reviews Cancer*, 15(6):361–370, 2015.

Michael Widrich, Bernhard Schäfl, Milena Pavlović, Hubert Ramsauer, Lukas Gruber, Markus Holzleitner, Johannes Brandstetter, Geir Kjetil Sandve, Victor Greiff, Sepp Hochreiter, et al. Modern hopfield networks and attention for immune repertoire classification. *Advances in Neural Information Processing Systems*, 33:18832–18845, 2020.

Jian Ye, Ning Ma, Thomas L Madden, and James M Ostell. Igblast: an immunoglobulin variable domain sequence analysis tool. *Nucleic acids research*, 41(W1):W34–W40, 2013.

Alexander Dimitri Yermanos, Andreas Kevin Dounas, Tanja Stadler, Annette Oxenius, and Sai T Reddy. Tracing antibody repertoire evolution by systems phylogeny. *Frontiers in immunology*, 9: 2149, 2018.

Maxim E Zaslavsky, Nikhil Ram-Mohan, Joel M Guthridge, Joan T Merrill, Jason D Goldman, Ji-Yeun Lee, Krishna M Roskin, Charlotte Cunningham-Rundles, M Anthony Moody, Barton F Haynes, et al. Disease diagnostics using machine learning of immune receptors. *bioRxiv*, 2022.

Feng Zhu, Thomas Althaus, Chee Wah Tan, Alizée Costantini, Wan Ni Chia, Nguyen Van Vinh Chau, Giada Mattiuzzo, Nicola J Rose, Eric Voiglio, Lin-Fa Wang, et al. Who international standard for sars-cov-2 antibodies to determine markers of protection. *The Lancet Microbe*, 3(2):e81–e82, 2022.

A APPENDIX

A.1 ANTIBODY SPECIFIC EVOLUTION

Antibodies are composed of two identical heavy chains and two identical light chains, forming a large Y-shaped structure, where the two tips are responsible for pathogens binding (Figure 7). Antibody evolution, described by sequence-sequence relationships between ancestor and progeny antibodies, reflects antibodies' key antigen-binding function Honjo & Habu (1985). During evolution, the initial diversity is encoded into the ancestor sequence through randomly recombination of V-, D- and J-gene segments. Upon exposure to a pathogen, the sequence undergoes frequent sequence mutations to search for progeny sequences with optimal binding specificity. equence evolution analysis has been employed by many computational biology studies and shows promising results in antibody-related tasks, such as disease diagnosis and therapeutic antibody development Yermanos et al. (2018); Miho et al. (2019).

Figure 7: B cell antibodies serve as critical barriers to viral infection. During antibody evolution, members of antibodies are descended from common ancestors(germlines), which are diverse amino acid sequences generated by V(D)J sequence recombination. Then, the ancestor germline sequences need to undergo frequent sequence mutiontions to search for progeny sequences with an optimal binding affinity to specific pathogens. The evolution sequence relationships are highlighted using dash lines. The mutation positions are highlighted in red.

A.2 DATA PROCESSING DETAILS

Pairing Antibody with Germline For germline annotation in the pretraining task, we used the annotated germline sequences provided in the OAS database (Kovaltsuk et al., 2018). For downstream benchmarks tasks like B-cell classification, therapeutic antibody engineering, and disease diagnosis, we completely followed the methods shown in the OAS database paper. IgBLAST, an immunoin-formatic benchmarking tool for the analysis of B-cell antibody repertoires was used for germline annotation (Ye et al., 2013). The antibody nucleotide-containing FASTA file was aligned to germline and translated to amino acids using IgBLASTn. The antibody amino-acid sequence was aligned using IgBLASTp. The germline databases for human patients used ImMunoGeneTics (IMGT) germline sequences derived from IMGT (Lefranc et al., 1999). For each antibody, usually, multiple germline sequences can be obtained and only the single sequence showing the highest confidence score for the alignment was chosen.

Pre-training Data Processing We downloaded OAS Oct 2021 version from its website and removed duplicate sequences. To avoid data leakage, we cluster sequences based on the CDR3 sequence and filter each cluster by 70% identity over the whole sequence using Linclust (Steinegger & Söding, 2018). Then, we shuffle the dataset and split it into 100k-size chunks. The last chunk is used as the validation set. The dataset size is 20,245,249 and the split is 20,200,000/45,249.

Negative sampling ratio We have tried the ratio of 0.1/0.3/0.5/0.75 and found that this ratio has little influence on performance and convergent speech. As we discuss in the appendix, the model can quickly converge for AGP and get an accuracy of 0.99.

Representation chosen for the pre-training tasks The two pre-training tasks are designed to simulate the evolution process in the immune system (as shown in Figure 1). We detailed our motivation in Section 3. The representations learned from different tasks are evaluated in the

Table 5: `ATUE` dataset. The five downstream tasks are divided into three biological categories and each category focuses on different input levels. 'Q6' indicates the classification task have 6 classes. For disease diagnosis, the size indicate the number of profiles, where each profile contains thousands to millions of sequences.

Specificity	Task Name	Input	Formalization	Size	Real-world
Low	Antigen Binding Prediction	CDR fragment	Q2 Cls.	21,612	Antibody engineering
Medium	Paratope Prediction	CDR residue	Q2 Labeling	1,662	Antibody engineering
High	SARS Antibody Classification	Sequence	Q2 Cls.	133	Antibody discovery
High	B Cell Classification	Sequence	Q6 Cls.	88,094	B cell analysis

benchmark, and the performance can be found in the third part of Tables 2, 4, and 5. More discussions are in the appendix.

A.3 ATUE DETAILS

Antigen Binding Accurate antigen-binding prediction approaches could allow significantly more efficient antibody discovery with higher affinity. Machine learning methods have already achieved some success in antibody binding capacity optimization. We collect the antigen-binding data from Mason et al. (2021) and follow the training/validation/test split of 15,128/3,242/3,242. The original dataset only has CDR3 fragments, and we extend them to the full antibody sequences. For cross-validation, we split the dataset by antibody sequences to ensure that no antibody sequences overlap between 90% training and 10% validation.

Paratope Prediction Paratope is the antibody residues involved in antigen binding. The ability to accurately map the paratope can provide detailed knowledge about the binding mechanism and accelerate antibody discovery. 1D sequence-based deep learning methods have been employed for paratope prediction. The paratope data is collected from Liberis et al. (2018) with 1,662 CDR segments on 277 antibodies. Each antibody contains three CDR fragments (CDR1, CDR2 and CDR3) in the heavy chain and three CDR fragments in the light chain. We also search the full sequence for each antibody and use the whole sequence as input. For cross-validation, we split the dataset by antibody sequences to ensure that no antibody sequences overlap between 90% training and 10% validation.

Table 6: The dataset of B cell classification.

Type	Size
Immature b cell	14,145
Transitional b cell	13,197
Mature b cell	16,139
Plasmacytes PC	22,236
Memory IgD-	8,437
Memory IgD+	13,940

B Cell Analysis We formulate a 6-category classification task for B cell maturation analysis, which includes {*immature, transitional, mature, memory IgD+, memory IgD-, plasmacytes,*}. The analysis of B cell maturation plays an important role in understanding the mechanisms underlying B cell responses in immune system Ghraichy et al. (2021); Meffre et al. (2000).

The order of B cell type follows the evolutionary process in the immune system, from immature state to transitional state and finally becomes a memory B cell. Both memory IgD- and IgD+ belong to memory B cells with different isotypes, and they have a high affinity to foreign antigens. Among the other categories, the Plasmacytes PC sequences also have some affinity ability. It is widely reported that changes in antibody sequence patterns correlate with B-cell maturation. Therefore, we use this task to evaluate the representation learning capacity of the language model.

We collect 88,094 sequences from Mroczek et al. (2014). They extracted from the peripheral blood of healthy adults and got six types of B cells with different maturity and antibody sequences. The distribution of various types of B cells in the dataset is shown in Table 6

Antibody Discovery Antibody discovery from B cell repertoire has been widely recognized as a novel trend to improve the efficiency of antibody discovery for diverse antigens (Weiner, 2015; Pedrioli & Oxenius, 2021). However, previous studies highly rely on expensive wet-lab experiments (Cao et al., 2020; Shiakolas et al., 2022). Deep learning based method have shown potential capacity in help antibody discovery by reduce cost and increase efficiency (Widrich et al., 2020; Wang et al., 2022). Here, we ask whether EATLM can benefit real-world problems and enable fast-track neutralization SARS-CoV-2 antibody discovery.

In the first step, we develop a sequence classifier to distinguish which antibody sequence from the numerous sequences is responsible for the recognition of the SARS-CoV-2. This task is highly challenging since we can hardly get the sequence-level disease label that indicates whether the antibody sequence is related to the disease. Thus, we follow the practice of Roskin et al. (2020); Zaslavsky et al. (2022) to use the individual label as the rough sequence label and train a sequence-level predictor. Then, with the help of a sequence-level predictor, we can give each sequence a most likely label to help antibody discover, whose accuracy has been verified by the excellent results on individual prediction, which may accelerate the discovery of new antibody sequences.

We follow the condition of Kim et al. (2021) to filter SARS-CoV-2 antibody data from the OAS database. The basic condition is '*Chain = heavy; Isotype = IGHG; BSource = PBMC; Species = human; Vaccine = None*'. We further add the condition of '*Unique Sequences >= 10000*'. For health/SARS we set the '*Disease*' field to '*None*', '*SARS-CoV-2*'. Then we obtain 87/133 patient profiles for each type. To make a balanced dataset, we limit the size of the health profile and mix up the healthy ones and the ones with the SARS-CoV-2. For cross-validation, we randomly split the dataset by profiles 10 times: 90% for training and 10% for validation. We further select sequences with top100 redundancy to make the positive labels more accurate.

A.4 TRAINING DETAILS

Antibody can be represented as $A = \{a_1, a_2, \cdots, a_m\}$ and the germline of individual antibody can be represented as $G = \{g_1, g_2, \cdots, g_n\}$, where m and n are the lengths. Each token a_i or g_j in the sequence is called a residue that belongs to the amino acid set $\mathbb{A}$. $\mathbb{A}$ includes 20 common amino acids with a residue 'X' that indicates the residue is unknown (mostly in the germline). Typically, antibody PLMs are trained with basic mask language modeling objective l_{MLM} on the antibody sequences $S = A = \{a_1, \cdots, a_m, \}$.

A.4.1 EVOLUTION-AWARE PRETRAINING

In order to incorporate the evolutionary information into the pre-training, we pair the antibody sequence A with its germline G and concatenate them into a long sequence with a special token '[SEP]' as the delimiter: $S = \{s_1, \cdots, s_{m+n+1}\} = \{a_1, \cdots, a_m, [\mathrm{SEP}], g_1, \cdots, g_n\}$. Thus, we optimize MLM objective on the long sequence S:

$$l_{\mathrm{MLM}} = -\frac{1}{|M|} \sum_{i \in M} \log p(s_i | S_{\backslash M}), \qquad (1)$$

where M is the index set of masked tokens. It helps the model to learn the basic residue distribution for antibody sequences. Besides, it can also capture the interaction between residues of the antibody and its germline.

Ancestor Germline Prediction The ancestor relationship between the antibody and its germline determines the shared biological functions obtained in the evolution. Antibody sequences with similar residues evolved from different germline sequences may have different biological functions. When stimulated by a foreign antigen, the common ancestor germline evolve to various antibody sequences. Similar antibody sequences may have different germline sequences, which will affect their biological functions. Thus, the aim of this task is to determine whether the antibody have evolutionary relationship with the given germline. During training, we substitute the paired germline G with

(a) Pre-training with two biological evolution tasks. (b) Finetuning for three biological categories in ATUE.

Figure 8: EATLM. In Figure 8a, AGP randomly unpairs the germline sentence and predict the ancestor relationship. MPP predicts the mutation position on the germline and the masked mutation residue on the antibody. Based on the input, the three categories in ATUE can be divided into sequence-level and individual-level (Figure 8b). For individual-level disease diagnostics, we score each sequence in the individual profile and calculate the trimmed mean over all sequences to get the individual score.

random germline $G' = \{g_1, \cdots, g_n\}$ in the batch via a probability $p = 0.3$. The new sequence is denoted as $S' = \{a_1, \cdots, a_m, [SEP], g_1', \cdots, g_n'\}$ and the training loss can be described as:

$$l_a = -\log p(y|S'), \tag{2}$$

where $y \in \{0, 1\}$ indicate whether the noisy germline G' is the ancestor of the antibody S. It can help the model to distinguish the ancestor germline of the antibody by capturing the shared features.

Mutation Position Prediction The somatic hypermutations on the germline further give progeny antibodies the specificity of binding with the specific antigen. In order to model this specificity, this task focus on predicting the mutation positions and the residues mutated to. Specifically, for each token g_j in the germline G, the target is to predict a label $y_j \in \{0, 1\}$ to indicate whether this token has been mutated. For the antibody sequence S, we mask the mutation position and predict these tokens. The objective can be formalized as:

$$l_m = -\frac{1}{n} \sum_{j \in \{1, \cdots, n\}} \log p(y_j | S_{\backslash M'}) - \frac{1}{|M|} \sum_{i \in M'} \log p(a_i | S_{\backslash M'}). \tag{3}$$

Here, M' is the ground-truth mutation position and we mask these tokens on the antibody sequence. This task is more difficult than MLM which equally masks tokens in the L, because the tokens on the mutation position of A get less information from the germline, compared with other shared residues between the antibody and the germline. By optimize this objective, the model learn to capture the specificity obtained from the somatic hypermutation in the evolutionary process.

A.4.2 IMPLEMENTATION DETAILS

We use the base Transformer architecture (Vaswani et al., 2017) with 12 layers, 12 heads, and 768 hidden states. The total parameters are 86M. We use Adam optimizer (Kingma & Ba, 2015) with the maximum learning rate of 2e-4 and the warm-up step of 24,000. The maximum length is set to 400 since most antibody sequences are shorter than 180. We first pre-train our model with the MLM objective. During the pre-training, 15% tokens are randomly selected with 80% masked, 10% replaced, and 10% kept. Then we conduct further pre-training on two antibody-related tasks with a smaller learning rate of 1e-5.

For each task in ATUE, we finetune the model with supervised data. We follow the standard split of Antigen Binding Prediction. For other tasks that do not provide a standard split, we conduct 10-cross validation and report the average results. Since our pre-training model learns the representation of the antibody sequence, we expand the CDR fragment to the full antibody via searching the biological database for therapeutic antibody engineering tasks. For finetuning, we limit the max epochs to 30 and use the Adam optimizer with a max learning rate of 3e-5. We use the mean representation of 12 layers as the sequence representation.

Table 7: The pretraining details for different models. The 'Germline' is the prediction accuracy of AGP, and the 'Position' and 'Mutation' are the accuracy of mutation positions and the mutated residues respectively.

Model	Size	Loss	Step	Germline	Position	Mutation
AntiBERT	85M	0.437	568000	/	/	/
AntiBERT w AGP	85M	0.558	587000	0.330	/	/
AntiBERT w MPP	85M	1.744	622000	/	0.965	0.410
ESM-1 FT	85M	0.2636	136000	/	/	/
ESM-1b FT	650M	0.2704	278000	/	/	/
EATLM w/o AGP & MPP	85M	0.143	108000	/	/	/
EATLM w/o AGP	85M	1.744	134000	/	1.000	0.443
EATLM w/o MPP	85M	0.001	126000	1.000	/	/
EATLM	85M	1.856	252500	0.9960	1.000	0.443
EATLM-large w/o AGP & MPP	650M	0.149	193000	/	/	/
EATLM-large w/o AGP	650M	1.753	267000	/	1.000	0.438
EATLM-large w/o MPP	650M	0.001	200000	1.000	/	/
EATLM-large	650M	1.773	384000	0.996	1.000	0.431

The model is trained with 108,000 steps and gets a 0.9606 token accuracy on the MLM task. It takes further steps for AGP and MPP. The model quickly converges for AGP and gets a 0.99 accuracy on the ancestor germline prediction because more than 80% residues are shared between the antibody and its germline. For MPP, it can predict the mutation position with the accuracy of 1.00 and obtains a 0.4430 accuracy in the mutation position. It means that the model can easily find the mutation positions by the self-attention between the antibody and germline, but it is still difficult to predict which residues this position will mutate to. We assume it is because the ancestor germline can undergo different somatic hypermutations and get various progeny antibodies, resulting in different valid mutations at the same position. We also compare this mutation accuracy with the model without MPP, which is only trained with MLM on the concatenation of the antibody and its germline. With a high prediction accuracy of 0.8889 on all positions, it achieves only a 0.0311 accuracy on the mutations. It implies that the masking among all positions on the sequence can do accurate predictions of the shared residues but hardly capture the mutation information.

We also conduct AGP and MPP to finetune the baseline model AntiBERT. The pretraining results are shown in Table 7. We can find that without the concatenation of the antibody and its germline, it is difficult to predict the ancestor relationship. It also underperforms than EATLM in MPP.

Finetuned Protein Language Models and Larger Architecture   We pre-train our method with a larger architecture and compare it with ESM-1b, which also has 650M parameters. We also further pre-trained the ESMs to transfer to the antibody field. After that, we evaluate them on the antigen binding and paratope prediction task. The results are shown in Table 8. The result show that the larger architecture does show advantage in terms of the performance improvement. For antigen binding, ESM-1b has better performance than ESM-1. However, for paratope prediction, it performs worse. In addition, for ESM, fine-tuning of the antibody dataset may cause the overfitting problem, leading to the decrease in the performance of all three tasks.

A.5   DISCUSSION ABOUT OF EATLM

First, EATLM doesn't use any 3D structure information during pre-training. As a special subgroup of proteins, antibody structures provide much more information such as geometry than sequences. In the future, recruiting structure information for antibody pre-training may be able to improve the results. However, the data scale available for antibody structure is dramatically less than that of antibody sequences. The largest dataset of antibody structures only contains thousands of 3D high-resolution structures, while the number of antibody sequences is in billions. Using structure prediction methods like AlphaFold may help to bridge the gap between sequences and structures. Second, EATLM requires germline as input during downstream tasks, this will slow down the prediction speed.

Table 8: The performance of larger models and finetuned protein language models on three tasks. The ESM-1 and ESM-1b models have 85M and 650M respectively. The `EATLM`-large have similar architecture with ESM-1b. 'FT' indicates the model is further finetuned on our antibody pre-training dataset.

	Antigen Binding			Paratope		
	AUC	F1	MCC	AUC	F1	MCC
ESM-1	0.917+0.001	0.854+0.002	0.689+0.002	0.886+0.009	0.669+0.024	0.547+0.026
ESM-1 FT	0.914+0.001	0.858+0.001	0.695+0.003	0.883+0.009	0.657+0.031	0.534+0.030
ESM-1b	**0.924+0.002**	0.860+0.002	**0.707+0.003**	0.873+0.009	0.655+0.042	0.524+0.036
ESM-1b FT	0.916+0.003	0.844+0.003	0.686+0.004	0.869+0.010	0.660+0.021	0.527+0.015
`EATLM`	0.922+0.052	**0.862+0.021**	0.699+0.027	0.887+0.008	**0.698+0.017**	**0.575+0.024**
`EATLM`-large	0.921+0.004	0.854+0.004	0.677+0.010	**0.887+0.007**	0.685+0.015	0.561+0.020

A.6 NEW SARS BINDER DISCOVERY

Antibody discovery from B cell repertoire has been widely recognized as a novel trend to improve the efficiency of antibody discovery for diverse antigens (Weiner, 2015; Pedrioli & Oxenius, 2021). However, previous studies highly rely on expensive wet-lab experiments (Cao et al., 2020; Shiakolas et al., 2022). Deep learning based method have shown potential capacity in help antibody discovery by reduce cost and increase efficiency (Widrich et al., 2020; Wang et al., 2022). Here, we ask whether `EATLM` can benefit real-world problems and enable fast-track neutralization SARS-CoV-2 antibody discovery. Our sequence-to-individual pipeline gives an interpretable explanation for disease diagnosis. As stated in Section A.3, the main challenge for disease diagnosis is to distinguish the disease-related antibodies from millions of antibody sequences in the individual profile. Here, with the help of a sequence-level predictor, we can give each sequence a most likely label to help antibody discover, whose accuracy has been verified by the excellent results on individual prediction, which may accelerate the discovery of new antibody sequences.

Sequence-level Predictor for SARS As described in Section A.3, we first train a sequence-level predictor for SARS-CoV-2. The results are shown in Table 9. Compared with Compared with Figure 4 in the main text, we find that good results in the sequence-level predictor do not necessarily mean good results in the antibody discovery. It can be mainly affected by the noisy label of the sequence level.

Table 9: Sequence-level predictor for SARS-CoV-2.

	SARS		
Sequence-level	AUC	F1	MCC
No pretrain	0.894±0.029	0.801±0.045	0.637±0.078
ESM-1	0.903±0.061	0.799±0.032	0.648±0.093
MSA-1b	0.914±0.025	0.810±0.050	**0.671±0.080**
Ablang-H	0.915±0.027	**0.817±0.038**	0.668±0.068
Ablang-L	0.893±0.035	0.801±0.054	0.637±0.099
AntiBERT	**0.916±0.026**	0.810±0.033	0.661±0.060
`EATLM`	0.904±0.027	0.808±0.035	0.643±0.069
`EATLM` w/o AGP	0.904±0.029	0.808±0.039	0.644±0.078
`EATLM` w/o MPP	0.901±0.026	0.808±0.035	0.648±0.069
`EATLM` w/o MPP & AGP	0.901±0.026	0.807±0.034	0.645±0.067

As shown in Table 3, we find 2 true SARS binders and 9 potential binders with the help of `EATLM`. Specifically, we first use our sequence-level predictor to get a probability score for each sequence in the SARS dataset. Then we select the sequence with high-ranked score (the probability > 0.5) and compare them with the public Cov-AbDab database Raybould et al. (2021) [2], which contains data

---

[2] http://opig.stats.ox.ac.uk/webapps/covabdab/

on published/patented antibodies known to bind to SARS-CoV-2 (Raybould et al., 2021). Since the CDR3 fragment in the heavy chain is the most relevant to the binding of antibody and antigen, we calculate the edit distance between the CDR3 fragments in heavy chains (CDR-H3) with those of the known binder and use a threshold of 85% similarity as the sequence identity. 85% Hamming distance for B cell antibody sequence clustering (identify similar B cell antibody sequences responding to the same antigen/epitope) was previously suggested in this paper (Gupta et al., 2017). This method then was widely used for B cell antibody repertoire analysis in different studies (Montague et al., 2021; Wang et al., 2022). To make it more stringent, we choose 90% Hamming distance for sequence clustering. To provide a more intuitive analysis of the similarity between our predicted antibody and true SARS-CoV-2 binders, we investigate the 3D structure of the true binding antibodies and the mutation site of our predicted sequence on the corresponding structure. High resolution structure of true binding antibody #3 with SARS-CoV-2 are shown in Figure 5 (PDB code: 7N62). The interaction interface between the antibodies and SARS-CoV-2 spike/RBD are shown in Figure 3 in main body. CDR-H3 were shown in orange. Only one single atom highlighted in red is different between predicted binder and true binder. Obviously, these different residues don't localize to direct binding site and CDR-H3 founding core, suggesting the sequence difference likely will not affect antibody virus interaction.

Table 10: SARS-CoV-2 antibody hit rate with different probability thresholds. 'Total' is the total number of sequences whose probabilities are higher than the threshold. 'Hit' is the number of sequences that meet the similarity requirements with existing binders.

Threshold	Total	Hit	Hit rate (%)
0.5	13253	66	0.498
0.7	10227	54	0.528
0.8	9338	49	0.525
0.9	8178	47	0.562

Furthermore, we found the epitopes of the 11 identified SARS-CoV-2 antibodies cover a wide range of different structures from traditional RBD domain to novel non-RBD epitopes like S2 and NTD as shown in Table 3. This result shows our method enables diverse-epitope antibody discovery. In Table 10, hit enrichment rate for different probability threshold predicted by the model were calculated. As the prediction score increases, the hit enrichment rate corresponding increases from 0.528% to 0.562%, indicating that our model may enable priority selection of SARS-CoV-2 antibodies and reduce experimental costs.

During the training of our sequence-level predictor, we have no reliable ground-truth labels, which means that the model has never known which sequences can bind to SARS in the real-world scenario. However, the model can learn from the noisy data and rank the real SARS binders with high probabilities. Sequence identity of 1 means that the CDR-H3 fragment can be directly found in the Cov-AbDab database, which implies that the sequences have been verified by wet laboratory testing. The other sequences with an identity over 90% are thought to have a similar binding performance to existing binders, indicating that they are promising SARS binders that can help the discovery of therapeutic antibodies for SARS-CoV-2.

A.7 Extented Study for Disease Diagnosis

It would be interesting to see whether our sequence classifier can be used for other applications, such as disease diagnosis. Each human is estimated to maintain about $10^8 - 10^{10}$ distinct antibody sequences, constructing an informative encyclopedia recording the past and present health and disease. Interpreting the pattern of the sequences has already proved useful in disease diagnosis and allows us to assess many infectious diseases without expensive laboratory testing. However, it is difficult to distinguish which antibody sequence from the numerous sequences is responsible for the recognition of the specific antigen, which hinders the discovery of the antibody for diseases (Zaslavsky et al., 2022; Lu et al., 2018; Greiff et al., 2020).

Benefiting from the recent high-throughput sequencing, we can obtain millions of antibody sequences from the individual human. At the same time, we get a disease label that indicates whether the human is infected by the disease. The main challenge is that we can hardly get the sequence-level

(a) Threshold=0.8   (b) Threshold=0.85   (c) Threshold=0.9

Figure 9: The cumulative count of matched sequences number. The dashed line is the expected results for a random order. The x-axis is the sequence number and the y-axis is the cumulative matched sequence number.

disease label that indicates whether the antibody sequence is related to the disease. Thus, we follow the practice of Roskin et al. (2020) to use the individual label as the rough sequence label and train a sequence-level predictor. Then we use this predictor to predict sequences of the individual profile and make the trimmed mean score as the individual score.

We follow the condition of Kim et al. (2021) to filter disease data from the OAS database. The basic condition is '*Chain = heavy; Isotype = IGHG; BSource = PBMC; Species = human; Vaccine = None*'. We further add the condition of '*Unique Sequences >= 10000*'. For health/SARS/HIV/Ebola/Allergy/SLE/MS, we set the '*Disease*' field to '*None*', '*Ebola*', '*Allgery*', '*SLE*','*MS*'. Then we obtain 87/133/51/14/12/8/8 patient profiles for each type. To make a balanced dataset, we limit the size of the health profile and mix up the healthy ones and the ones with the disease. For cross-validation, we randomly split the dataset by profiles 10 times: 90% for training and 10% for validation. We further select sequences with top100 redundancy to make the positive labels more accurate.

Sequence-level Predictor for Various Disease As described in Section A.3, we first train a sequence-level predictor for each disease. The results are shown in Table 9. Compared with Table 4 in the main text, we find that good results in the sequence-level predictor do not necessarily mean good results in the individual-level predictor. It is mainly due to the trimmed mean we use to get individual-level results, which is a central estimate that is robust to noise labels. Overall, our model has comparable results to other models in terms of sequence prediction with noisy labels, and has better results for individual diagnosis.

Individual-level Predictor for Various Disease It is observed our evolution-aware EATLM performs the best in the individual-level classifier to determine whether the patient suffering from SARS. Besides, PALMs significantly outperform PPLMs. The results is shown in 12

Disease Classification We use all these diseases profile to build the Q7 classification task for disease diagnosis. Previous biological studies mainly use this multi-classification task for disease diagnosis Zaslavsky et al. (2022); Wang et al. (2022), highlighting the discriminatory power among different diseases are important for disease diagnosis. The results are shown in Table 11. We found both PPLM an PALM show comparable results as the random initialized model, suggesting the finetuning part play more important role and pretrained language model cannot help this task.

Table 11: The Q7 disease classification task. 'ACC' is the accuracy rate.

	ACC
No pretrain	0.754±0.023
ESM-1	0.747±0.016
ESM-1 FT	**0.762±0.024**
MSA-1b	0.746±0.019
Ablang-H	0.704±0.033
Ablang-L	0.702±0.040
AntiBERT	0.750±0.016
EATLM	**0.756±0.020**
EATLM w/o AGP	0.754±0.020
EATLM w/o MPP	0.755±0.020
EATLM w/o AGP & MPP	0.756±0.021

Table 12: Patient-level predictor for disease diagnosis. The definition of notation are the same as the Table 4 in main body.

Pateint-level	SARS			HIV		
	AUC	F1	MCC	AUC	F1	MCC
No pretrain	0.975±0.033	0.962±0.024	0.902±0.062	0.920±0.092	0.815±0.117	0.776±0.122
ESM-1	0.979±0.017	0.933±0.032	0.824±0.090	0.967±0.056	0.883±0.107	0.849±0.135
MSA-1b	0.989±0.012	0.954±0.033	0.887±0.078	0.962±0.039	0.833±0.068	0.789±0.072
Ablang-H	0.988±0.013	0.968±0.024	0.920±0.063	0.960±0.040	0.788±0.134	0.744±0.137
Ablang-L	**0.990±0.015**	0.938±0.039	0.843±0.091	0.931±0.069	0.798±0.131	0.742±0.170
AntiBERT	0.983±0.017	0.976±0.022	0.938±0.056	0.969±0.053	0.878±0.112	0.850±0.134
EATLM	0.977±0.028	**0.983±0.017**	**0.955±0.045**	**0.978±0.054**	0.914±0.081	0.884±0.106
EATLM w/o AGP	0.983±0.019	0.973±0.025	0.929±0.066	**0.978±0.054**	0.903±0.076	0.869±0.099
EATLM w/o MPP	0.987±0.015	0.969±0.024	0.921±0.061	0.976±0.053	0.906±0.092	0.880±0.112
EATLM w/o MPP & AGP	0.986±0.014	0.969±0.023	0.920±0.061	0.973±0.052	**0.919±0.096**	**0.896±0.117**

	Ebola			Allergy		
	AUC	F1	MCC	AUC	F1	MCC
No Pretrain	0.994±0.017	0.933±0.133	0.934±0.132	1.000±0.000	1.000±0.000	1.000±0.000
ESM-1	1.000±0.000	0.933±0.133	0.934±0.132	1.000±0.000	1.000±0.000	1.000±0.000
MSA-1b	1.000±0.000	0.933±0.133	0.934±0.132	1.000±0.000	1.000±0.000	1.000±0.000
Ablang-H	0.944±0.167	0.767±0.213	0.750±0.254	1.000±0.000	0.960±0.080	0.916±0.169
Ablang-L	0.961±0.100	0.731±0.205	0.703±0.277	1.000±0.000	0.960±0.080	0.916±0.169
AntiBERT	0.978±0.067	0.933±0.133	0.934±0.132	1.000±0.000	1.000±0.000	1.000±0.000
EATLM	1.000±0.000	**0.947±0.111**	**0.944±0.114**	1.000±0.000	1.000±0.000	1.000±0.000
EATLM w/o AGP	1.000±0.000	0.933±0.133	0.934±0.132	1.000±0.000	1.000±0.000	1.000±0.000
EATLM w/o MPP	1.000±0.000	0.933±0.133	0.934±0.132	1.000±0.000	1.000±0.000	1.000±0.000
EATLM w/o MPP & AGP	0.994±0.017	0.933±0.133	0.934±0.132	1.000±0.000	1.000±0.000	1.000±0.000

	SLE			MS		
	AUC	F1	MCC	AUC	F1	MCC
No Pretrain	1.000±0.000	1.000±0.000	1.000±0.000	0.700±0.200	0.900±0.137	0.893±0.400
ESM-1	1.000±0.000	1.000±0.000	1.000±0.000	0.900±0.200	0.933±0.133	0.900±0.200
MSA-1b	1.000±0.000	1.000±0.000	1.000±0.000	0.700±0.400	0.893±0.137	0.700±0.400
Ablang-H	1.000±0.000	1.000±0.000	1.000±0.000	0.800±0.245	0.893±0.137	0.700±0.400
Ablang-L	1.000±0.000	1.000±0.000	1.000±0.000	1.000±0.000	0.960±0.080	0.800±0.400
AntiBERT	1.000±0.000	1.000±0.000	1.000±0.000	1.000±0.000	1.000±0.000	1.000±0.000
EATLM	1.000±0.000	1.000±0.000	1.000±0.000	1.000±0.000	0.867±0.163	0.800±0.245
EATLM w/o AGP	1.000±0.000	1.000±0.000	1.000±0.000	1.000±0.000	0.867±0.163	0.800±0.245
EATLM w/o MPP	1.000±0.000	1.000±0.000	1.000±0.000	1.000±0.000	0.827±0.150	0.600±0.374
EATLM w/o MPP & AGP	1.000±0.000	1.000±0.000	1.000±0.000	1.000±0.000	0.827±0.150	0.800±0.374

Table 13: Sequence-level predictor for disease diagnosis. The definition of notation is the same as Table 4 in the main body.

Sequence-level	SARS			HIV		
	AUC	F1	MCC	AUC	F1	MCC
No Pretrain	0.894±0.029	0.801±0.045	0.637±0.078	0.893±0.081	0.622±0.223	0.563±0.209
ESM-1	0.903±0.061	0.799±0.032	0.648±0.093	0.927±0.039	0.739±0.082	**0.701±0.080**
MSA-1b	0.914±0.025	0.810±0.050	**0.671±0.080**	0.903±0.064	0.680±0.103	0.617±0.102
Ablang-H	0.915±0.027	**0.817±0.038**	0.668±0.068	0.895±0.058	0.684±0.087	0.604±0.108
Ablang-L	0.893±0.035	0.801±0.054	0.637±0.099	0.881±0.072	0.668±0.111	0.584±0.131
AntiBERT	**0.916±0.026**	0.810±0.033	0.661±0.060	0.921±0.046	0.742±0.088	0.689±0.101
EATLM	0.904±0.027	0.808±0.035	0.643±0.069	0.930±0.044	0.744±0.079	0.677±0.105
EATLM w/o AGP	0.904±0.029	0.808±0.039	0.644±0.078	**0.933±0.041**	0.747±0.077	0.679±0.103
EATLM w/o MPP	0.901±0.026	0.808±0.035	0.648±0.069	0.932±0.037	**0.749±0.072**	0.682±0.096
EATLM w/o MPP & AGP	0.901±0.026	0.807±0.034	0.645±0.067	0.930±0.045	0.749±0.074	0.678±0.098

	Ebola			Allergy		
	AUC	F1	MCC	AUC	F1	MCC
No Pretrain	0.967±0.031	0.796±0.115	0.787±0.113	0.994±0.006	0.976±0.017	0.958±0.019
ESM-1	0.970±0.035	0.845±0.098	0.836±0.097	0.994±0.006	0.988±0.006	0.975±0.011
MSA-1b	0.970±0.026	0.803±0.103	0.799±0.096	0.966±0.019	0.918±0.037	0.835±0.093
Ablang-H	0.951±0.024	0.700±0.087	0.691±0.079	0.821±0.093	0.734±0.091	0.459±0.190
Ablang-L	0.945±0.027	0.719±0.110	0.710±0.100	0.782±0.136	0.735±0.104	0.381±0.262
AntiBERT	0.959±0.030	0.804±0.110	0.795±0.106	0.993±0.008	0.984±0.009	0.970±0.014
EATLM	0.969±0.036	**0.848±0.096**	**0.841±0.094**	0.995±0.006	**0.988±0.005**	**0.975±0.011**
EATLM w/o AGP	0.967±0.032	0.843±0.097	0.835±0.093	0.996±0.004	0.983±0.006	0.968±0.007
EATLM w/o MPP	0.969±0.037	0.840±0.094	0.828±0.098	0.996±0.004	0.980±0.005	0.961±0.011
EATLM w/o MPP & AGP	**0.970±0.025**	0.821±0.098	0.811±0.091	**0.996±0.002**	0.981±0.007	0.963±0.009

	SLE			MS		
	AUC	F1	MCC	AUC	F1	MCC
No Pretrain	0.994±0.004	0.982±0.009	0.960±0.012	0.841±0.182	0.847±0.129	0.617±0.378
ESM-1	0.992±0.005	0.979±0.014	0.954±0.021	0.879±0.127	0.845±0.123	0.621±0.358
MSA-1b	**0.998±0.001**	**0.988±0.007**	**0.973±0.011**	0.853±0.150	0.836±0.135	0.594±0.392
Ablang-H	0.994±0.003	0.964±0.022	0.931±0.021	0.836±0.184	0.828±0.108	0.562±0.353
Ablang-L	0.995±0.002	0.977±0.017	0.956±0.021	0.846±0.175	0.852±0.115	0.633±0.351
AntiBERT	0.994±0.009	0.952±0.068	0.919±0.096	**0.893±0.095**	**0.854±0.112**	**0.701±0.214**
EATLM	0.990±0.008	0.970±0.018	0.939±0.018	0.847±0.135	0.798±0.156	0.572±0.294
EATLM w/o AGP	0.990±0.007	0.962±0.031	0.929±0.040	0.846±0.132	0.799±0.162	0.584±0.284
EATLM w/o MPP	0.981±0.021	0.940±0.063	0.891±0.086	0.809±0.185	0.807±0.152	0.535±0.381
EATLM w/o MPP & AGP	0.988±0.010	0.952±0.051	0.915±0.070	0.827±0.159	0.798±0.147	0.547±0.311