DIFFERENTIALLY PRIVATE GENERATIVE MODELS THROUGH OPTIMAL TRANSPORT

ABSTRACT

Although machine learning models trained on massive data have led to breakthroughs in several areas, their deployment in privacy-sensitive domains remains limited due to restricted access to data. Generative models trained with privacy constraints on private data can sidestep this challenge and provide indirect access to the private data instead. We propose DP-Sinkhorn, a novel optimal transport-based generative method for learning data distributions from private data with differential privacy. DP-Sinkhorn relies on minimizing the Sinkhorn divergence—a computationally efficient approximation to the exact optimal transport distance—between the model and the data in a differentially private manner and also uses a novel technique for conditional generation in the Sinkhorn framework. Unlike existing approaches for training differentially private generative models, which are mostly based on generative adversarial networks, we do not rely on adversarial objectives, which are notoriously difficult to optimize, especially in the presence of noise imposed by the privacy constraints. Hence, DP-Sinkhorn is easy to train and deploy. Experimentally, despite our method's simplicity we improve upon the state-of-the-art on multiple image modeling benchmarks. We also show differentially private synthesis of informative RGB images, which has not been demonstrated before by differentially private generative models without the use of auxiliary public data.

1 INTRODUCTION

As the full value of data comes to fruition through a growing number of data-centric applications (e.g. recommender systems (Gomez-Uribe & Hunt, 2016), personalized medicine (Ho et al., 2020), face recognition (Wang & Deng, 2020), speech synthesis (Oord et al., 2016), etc.), the importance of privacy protection has become apparent to both the public and academia. At the same time, recent Machine Learning (ML) algorithms and applications are increasingly data hungry and the use of personal data will eventually be a necessity. To address this challenge, generative models—models with the capacity to synthesize new data—can be applied as a medium for data-sharing (Xie et al., 2018; Augenstein et al., 2020). Private data is first encoded into a generative model; then the model is used to synthesize similar yet different data that can train other ML applications. So long as the model is learned "privately", the user can protect their privacy by controlling how specific the generative model is to their own data.

Differential Privacy (DP) is a rigorous definition of privacy that quantifies the amount of information leaked by a user participating in any data release (Dwork et al., 2006; Dwork & Roth, 2014). It has been widely used in ML applications to protect the privacy of data used in training (Abadi et al., 2016). Differentially private learning of generative models has been studied mostly under the Generative Adversarial Networks (GAN) framework (Xie et al., 2018; Torkzadehmahani et al., 2019; Frigerio et al., 2019; Yoon et al., 2019; Chen et al., 2020). While GANs in the non-private setting have demonstrated the ability to synthesize complex data like high definition images (Brock et al., 2019; Karras et al., 2020), their application in the private setting is more challenging. This is in part because GANs suffer from training instability problems (Arjovsky & Bottou, 2017; Mescheder et al., 2018), which can be exacerbated when adding noise to the network's gradients during training, a common technique to implement DP. Because of that, GANs typically require careful hyperparameter tuning and supervision during training to avoid model collapse. This goes against the principle of privacy, where repeated interactions with data need to be avoided (Chaudhuri & Vinterbo, 2013).

Another method to train generative models is provided by Optimal Transport (OT). In the optimal transport setting, the problem of learning a generative model is framed as minimizing the optimal transport distance, a type of Wasserstein distance, between the generator-induced distribution and the real data distribution (Bousquet et al., 2017; Peyré & Cuturi, 2019). Unfortunately, exactly computing the OT distance is generally expensive. Nevertheless, Wasserstein distance-based objectives are actually widely used to train GANs (Arjovsky et al., 2017; Gulrajani et al., 2017b). However, these approaches typically estimate a Wasserstein distance using an adversarially trained discriminator. Hence, training instabilities remain (Mescheder et al., 2018).

An alternative to estimating the OT distance in an adversarial fashion is provided by the Sinkhorn divergence (Genevay et al., 2016; Feydy et al., 2019; Genevay et al., 2018). The Sinkhorn divergence is an entropy-regularized version of the exact OT distance, for which the optimal transport plan can be computed efficiently via the Sinkhorn algorithm (Cuturi, 2013). In this paper, we propose DP-Sinkhorn, a novel method to train differentially private generative models using the Sinkhorn divergence as objective. Since the Sinkhorn approach does not intrinsically rely on adversarial components, it avoids any potential training instabilities and removes the need for early stopping. This makes our method easy to train and deploy in practice. As a side, we also develop a simple yet effective way to perform conditional generation in the Sinkhorn framework, by forcing the optimal transport plan to couple same-label data closer together. To the best of our knowledge, DP-Sinkhorn is the first fully OT-based approach for differentially private generative modeling.

Experimentally, despite its simplicity DP-Sinkhorn achieves state-of-the-art results on image-based classification benchmarks that use data generated under differential privacy for training. We can also generate informative RGB images, which, to the best of our knowledge, has not been demonstrated by any generative models trained with differential privacy and without auxiliary public data.

We make the following contributions: (i) We propose DP-Sinkhorn, a flexible and robust optimal transport-based framework for training differentially private generative models. (ii) We introduce a simple technique to perform label-conditional synthesis in the Sinkhorn framework. (iii) We achieve state-of-the-art performance on widely used image modeling benchmarks. (iv) We present informative RGB images generated under strict differential privacy without the use of public data.

2 BACKGROUND

2.1 NOTATIONS AND SETTING

Let $\mathcal{X}$ denote a sample space, $\mathcal{P}(\mathcal{X})$ all possible measures on $\mathcal{X}$, and $\mathcal{Z} \subseteq \mathbb{R}^d$ the latent space. We are interested in training a generative model $g : \mathcal{Z} \mapsto \mathcal{X}$ such that its induced distribution $\mu = g \circ \xi$ with noise source $\xi \in \mathcal{P}(\mathcal{Z})$ is similar to observed ν through an independently sampled finite sized set of observations $D = \{y\}^N$. In our case, g is a trainable parametric function with parameters θ.

2.2 GENERATIVE LEARNING WITH OPTIMAL TRANSPORT

Optimal Transport-based generative learning considers minimizing variants of the Wasserstein distance between real and generated distributions (Bousquet et al., 2017; Peyré & Cuturi, 2019). Two key advantages of the Wasserstein distance over standard GANs, which optimize the Jensen-Shannon divergence (Goodfellow et al., 2014), are its definiteness on distributions with non-overlapping supports, and its weak metrization of probability spaces (Arjovsky et al., 2017). This prevents collapse during training caused by discriminators that are overfit to the training examples.

Methods implementing the OT framework use either the primal or the dual formulation. For generative learning, the dual formulation has been more popular. Under the dual formulation, the distance between the generator-induced and the data distribution is computed as the expectation of potential functions over the sample space. In WGAN and variants (Arjovsky et al., 2017; Gulrajani et al., 2017a; Miyato et al., 2018), the dual potential is approximated by an adversarially trained discriminator network. While theoretically sound, these methods still encounter instabilities during training since the non-optimality of the discriminator can produce arbitrarily large biases in the generator gradient (Bousquet et al., 2017). The primal formulation involves solving for the optimal transport plan—a joint distribution over the real and generated sample spaces. The distance between the two distributions is then measured as the expectation of a point-wise cost function between pairs of

samples as distributed according to the transport plan. Thus, the properties of the point-wise cost function are of great importance. In practice, sufficiently convex cost functions allow for an efficient optimization of the generator. It is also possible to learn cost functions adversarially (Szabó & Sriperumbudur, 2017). However, as discussed earlier, adversarial training often comes with additional challenges, which can be especially problematic in the differential privacy setting.

In general, finding the optimal transport plan is a difficult optimization problem due to the constraints of equality between its marginals and the real and generated distributions. Entropy Regularized Wasserstein Distance (ERWD) imposes a strongly convex regularization term on the Wasserstein distance, making the OT problem between finite samples solvable in linear time (Peyré et al., 2019). Given a positive cost function $c : \mathcal{X} \times \mathcal{X} \mapsto \mathbb{R}^+$ and $\epsilon \geq 0$, the Entropy Regularized Wasserstein Distance is defined as:

$$W_{c,\epsilon}(\mu, \nu) = \min_{\pi \in \Pi} \int c(x,y)\pi(x,y) + \epsilon \int \log \frac{\pi(x,y)}{d\mu(x)d\nu(y)} d\pi(x,y) \tag{1}$$

where $\Pi = \left\{ \pi(x,y) \in \mathcal{P}(\mathcal{X} \times \mathcal{X}) | \int \pi(x,\cdot)dx = \nu, \int \pi(\cdot,y)dy = \mu \right\}$. Sinkhorn divergence uses cross correlation terms to cancel out the entropic bias introduced by ERWD. This results in faithful matching between the generator and real distributions. In this paper, we use the Sinkhorn divergence as defined in Feydy et al. (2019).

Definition 2.1 *(Sinkhorn Loss) The Sinkhorn loss between measures μ and ν is defined as:*

$$S_{c,\epsilon}(\mu, \nu) = 2W_{c,\epsilon}(\mu, \nu) - W_{c,\epsilon}(\mu, \mu) - W_{c,\epsilon}(\nu, \nu) \tag{2}$$

Works on the efficient computation of the Sinkhorn divergence have yielded algorithms that converge to the optimal transport plan within tens of iterations (Cuturi, 2013; Feydy et al., 2019). Gradient computation follows by taking the Jacobian vector product between the cost matrix Jacobian and the transport weights, which is efficiently implemented in many reverse-mode auto-differentiation frameworks. The above loss easily extends to the setting of empirical data-defined distributions, which is the situation we are interested in. We provide more technical details in Appendix A.

2.3 DIFFERENTIAL PRIVACY

The current gold standard for measuring the privacy risk of data releasing programs is the notion of differential privacy (DP) (Dwork et al., 2006). Informally, DP measures to what degree a program's output can deviate between adjacent input datasets—sets which differ by one entry. For a user contributing their data, this translates to a guarantee on how much an adversary could learn about them from observing the program's output. In this paper, we are interested in the domain of image-label datasets where each image and its semantic label constitute an entry.

Gradient perturbation with the Gaussian mechanism is the most popular method for DP learning of parametric models. During stochastic gradient descent (SGD) and variants, the parameter gradients are clipped in 2-norm by a constant, and then Gaussian noise is added. By adding a sufficient amount of noise, the gradients can satisfy DP requirements. Then, the *post-processing* property of differential privacy (Dwork & Roth, 2014) guarantees that the parameters are also private. As SGD involves computing the gradients on randomly drawn batches of data for multiple iterations, two other properties of DP, *composition* and *subsampling* are required to analyze the privacy of the algorithm. Rényi Differential Privacy (RDP) is a well-studied formulation of privacy that allows tight composition of multiple queries, and can be easily converted to standard definitions of DP.

Definition 2.2 *(Rényi Differential Privacy) A randomized mechanism $\mathcal{M} : \mathcal{D} \rightarrow \mathcal{R}$ with domain $\mathcal{D}$ and range $\mathcal{R}$ satisfies (α, ϵ)-RDP if for any adjacent $d, d' \in \mathcal{D}$ it holds that*

$$D_\alpha(\mathcal{M}(d)|\mathcal{M}(d')) \leq \epsilon, \tag{3}$$

where D_α is the Rényi divergence of order α. Also, any $\mathcal{M}$ that satisfies (α, ϵ)-RDP also satisfies $(\epsilon + \frac{\log 1/\delta}{\alpha - 1}, \delta)$-DP (Mironov, 2017).

For clipping threshold Δ and standard deviation of Gaussian noise σ, the Gaussian mechanism satisfies $(\alpha, \alpha\Delta^2/(2\sigma^2))$-RDP (Mironov, 2017). Subsampling the dataset into batches also improves

Figure 1: Flow diagram of DP-Sinkhorn for a single training iteration: Sensitive training data is combined with non-sensitive generated data in the cost matrix. Then, the loss is calculated using the Sinkhorn algorithm. In the backward pass, we impose a privacy barrier behind the generator by clipping and adding noise to the gradients at the generated image level, similar to Chen et al. (2020).

privacy. The effect of subsampling on the Gaussian mechanism under RDP has been studied in (Wang et al., 2019; Balle et al., 2018; Zhu & Wang, 2019). Privacy analysis of a gradient-based learning algorithm entails accounting for the privacy cost of single queries (possibly with subsampling), summing up the privacy cost across all queries (i.e. training iterations in our case), and then choosing the best α. A more thorough discussion of DP can be found in Appendix B.

3   DIFFERENTIALLY PRIVATE SINKHORN WITH CLASS CONDITIONING

We propose DP-Sinkhorn (Algorithm 1), an OT-based method to learn differentially private generative models, avoiding the training instability problems characteristic for GAN-based techniques. We use the empirical Sinkhorn loss between batches of real and generated data as objective and define the Sinkhorn cost function as a simple pixel-wise L2-loss. Class conditioning is achieved by biasing the optimal transport plan to couple images of the same class together. Privacy protection is enforced by clipping and adding noise to the gradients of the generated images during backpropagation.

Class Conditioning   To conditionally generate images given a target class, we inject class information to both the generator and the Sinkhorn loss function during training. For the generator, we supply the class label either by concatenating an embedding of it with the sampled latent code (on simple DCGAN-style generators), or by using class conditioned batch-norm layers (on BigGAN-style generators). For the loss function, we concatenate a scaled one-hot class embedding to both the generated images and real images. Intuitively, this works by increasing the cost between image pairs of different classes, hence shifting the weight of the transport plan (P_ϵ^* in Eq. 8 in Appendix A) towards class-matched pairs. The scaling constant α_c determines the importance of class similarity relative to image similarity. Uniformly sampled labels are used for the generated images and the real labels are used for real images. Let l_x and l_y denote the labels of x and y. The class-conditional pixel-wise and label loss is:

$$c_{pixel}([x, l_x], [y, l_y]) = \left|\left|[x, \alpha_c * \text{onehot}(l_x)]^T - [y, \alpha_c * \text{onehot}(l_y)]^T\right|\right|_2^2. \tag{4}$$

Note that, to the best of our knowledge, it has not been shown before how to perform class-conditional generation in the Sinkhorn divergence generative framework. Our simple yet efficient trick to force the optimal transport plan to couple together data with similar labels can similarly be used in non-private learning settings.

Privacy Protection   Rather than adding noise to the gradients of the generator parameters θ, we add noise to the gradients of the generated images $\nabla_{\mathbf{X}} \hat{S}$, which is then backpropagated to θ. This is feasible because the input to generators (the latent code) is randomly sampled rather than drawn from data, leaving the only connection to data at the output. Compared to $\nabla_\theta \hat{S}$, the dimension of $\nabla_{\mathbf{X}} \hat{S}$ is independent from the network architecture. This allows us to train larger networks without requiring more aggressive clipping, as $\|\nabla_\theta \hat{S}\|_2$ scales as $\sqrt{dim(\theta)}$. This method has been independently proposed by Chen et al. (2020).

We use the RDP accountant with Poisson subsampling proposed in Zhu & Wang (2019) for privacy analysis. Given $||\nabla_{\mathbf{X}}\hat{S}||_2 \leq C$, the sensitivity of $\nabla_{\mathbf{X}}\hat{S}$ is $2C$. Thus the noise added to $\nabla_{\mathbf{X}}\hat{S}$ is scaled by $2C\sigma$.

4 EXPERIMENTS

We conduct experiments on conditional image synthesis tasks since our focus is on the generation of high-dimensional data with privacy protection. We evaluate our method with respect to both visual quality and data utility for downstream learning tasks. To compare with previous work, all models are trained under a privacy budget of $\varepsilon = 10$.

4.1 EXPERIMENTAL SETUP

Datasets We consider 3 image datasets: MNIST (LeCun et al., 1998), Fashion-MNIST (Xiao et al., 2017), and CelebA (Liu et al., 2015) downsampled to 32x32 resolution. For MNIST and Fashion-MNIST, generation is conditioned on the regular class labels while on CelebA we condition on gender.

Metrics In all experiments, we compute metrics against a synthetic dataset of 60k image-label pairs sampled from the model. Each sample is formed by selecting a class uniformly at random and generating an image conditioned on that class. For a quantitative measure of visual quality, we report FID (Heusel et al., 2017). We compute FID scores between our

---

Algorithm 1 DP-Sinkhorn

L is number of categories, $\mathcal{X}$ is sample space. M is size of private data set. $backprop$ is a reverse mode auto-differentiation function that takes 'out', 'in' and 'grad weights' as input and computes the Jacobian vector product $J_{\text{in}}(\text{out}) \cdot$ grad weights. Poisson Sample and $\hat{W}$ are defined in Appendix C.

Input: private data set $d = \{(\text{y},\text{l}) \in \mathcal{X} \times \{0,...,L\}\}^M$, sampling ratio q, noise scale σ, clipping coefficient Δ, generator g_θ, learning rate α, entropy regularization ϵ, total steps T.
Output: θ
$n = q * M$
for $t = 1$ **to** T **do**
    Sample $\mathbf{Y} \leftarrow$ Poisson Sample(d, q),
    $Z \leftarrow (\text{z}_i)_{i=1}^n \overset{i.i.d.}{\sim}$ Unif$(0, 1)$
    $L_x \leftarrow \{\text{l}_i\}_{i=1}^n \overset{i.i.d.}{\sim}$ Unif$(0, ..., L)$
    $\mathbf{X} \leftarrow \{x_i = g_\theta(\text{z}_i, \text{l}_i)\}_{i=1}^n$
    $\text{grad}_{\mathbf{X}} \leftarrow \nabla_{\mathbf{X}}\left[2\hat{W}_\epsilon(\mathbf{X}, \mathbf{Y}) - \hat{W}_\epsilon(\mathbf{X}, \mathbf{X})\right]$
    $\text{grad}_{\mathbf{X}} \leftarrow clip(\text{grad}_{\mathbf{X}}, \Delta) + 2\Delta\sigma\mathcal{N}(\vec{0}, \mathbb{I})$
    $\text{grad}_\theta \leftarrow backprop(\mathbf{X}, \theta, \text{grad}_{\mathbf{X}})$
    $\theta \leftarrow \theta - \alpha * Adam(\text{grad}_\theta)$
end for

---

synthetic datasets of size 60k and the full test data (either 10k or 19962 images). To measure the utility of generated data, we assess the class prediction accuracy of classifiers trained with synthetic data on the real test sets. We consider logistic regression, MLP, and CNN classifiers. Previous work also reports classification accuracies on a large suite of classifiers from scikit-learn. We omit them, since we focus on images which are best processed via neural network-based classifiers.

Architectures & Hyperparameters For MNIST and Fashion-MNIST experiments, we adopt the generator architecture from DCGAN (Radford et al., 2015). For CelebA experiments, we adopt, in addition, the CIFAR-10 generator configuration from BigGAN (Brock et al., 2019). Our preliminary experiments found that using the deeper BigGAN architecture did not provide significant improvements on MNIST and Fashion-MNIST datasets, hence we only report results with the DCGAN-based generator for these two datasets. Additional details can be found in Appendix D.3.

Privacy Implementation All our models are implemented in PyTorch. We implement the gradient sanitization by registering a backward hook to generator output, and we do not see a significant impact on runtime. MNIST and Fashion-MNIST experiments target $(10, 10^{-5})$-DP while CelebA experiments target $(10, 10^{-6})$-DP. Details on the privacy implementation are in Appendix D.3.

4.2 EXPERIMENTAL RESULTS ON STANDARD BENCHMARKS

In Table 1, we compare the performance of DP-Sinkhorn with other methods on MNIST and Fashion-MNIST. Given the same privacy budget, DP-Sinkhorn generates more informative examples than previous methods, as demonstrated by the higher accuracy achieved by the downstream classifier. In particular, on the more visually complex Fashion-MNIST, DP-Sinkhorn's lead is especially pronounced, beating previous state-of-the-art results by a significant margin.

The FID of images generated by DP-Sinkhorn is lower than all baselines, except GS-WGAN (Chen et al., 2020), likely because of the slight blur in images generated by DP-Sinkhorn, as shown in Figure 2. We hypothesize that this is due to the simple $L2$ cost and that improved cost functions based on other kernels may perform better. However, in this work our focus is to keep the model simple and focus on downstream applications, for which our model works best. It is also worth noting that GS-WGAN uses a more complex adversarial setup and requires an auxiliary discriminator network, while we rely on the robust Sinkhorn framework. Furthermore, FID scores are based on an ImageNet-trained Inception network and are not well suited for analyzing small grayscale images.

4.3 Experimental Results on CelebA

We also evaluate DP-Sinkhorn on downsampled CelebA. To the extent of our knowledge, no DP generative learning method has been applied on such RGB image data without accessing public data. We evaluate whether DP-Sinkhorn is able to synthesize RGB images that are informative for downstream classification. Furthermore, we study whether an adversarial learning scheme is helpful for learning this dataset. We test this by using an adversarially trained feature extractor in the cost function. Given feature extractor ϕ, we modify the cost function as:

$$c_{adv}([\mathrm{x}, l_x], [\mathrm{y}, l_y]) = \left\lVert [\mathrm{x}, \alpha_c * \mathrm{onehot}(l_x), \frac{\alpha_a \phi(\mathrm{x})}{||\phi(\mathrm{x})||_2}]^T - [\mathrm{y}, \alpha_c * \mathrm{onehot}(l_y), \frac{\alpha_a \phi(\mathrm{y})}{||\phi(\mathrm{y})||_2}]^T \right\rVert_2^2 .$$
(5)

The output of the feature extractor is normalized and then concatenated to the image and class label. Training proceeds through alternating updates. To make this learning scheme private, we randomly split the training dataset into k partitions and train one discriminator per partition. This way, the gradient (with respect to generated image) computed on each partition is only dependent on that partition, hence still benefiting from privacy amplification by subsampling. Privacy accounting for this setting is performed through Wang et al. (2019), which analyzes fixed-size batch subsampling.

We find that while using the adversarial feature extractor is beneficial in the non-private case, it did not provide significant improvements in the private case, as shown in Table 2. In theory, using learned feature extractors can provide a sharper loss landscape which should be beneficial to gradient-based learning (Li et al., 2017). We hypothesize that clipping and gradient noise counteracts the effect of gradient shaping provided by the adversarial feature extractor, resulting in similar learning performance as in the non-adversarial approach. Although the adversarial feature extractor did not help us, DP-Sinkhorn nevertheless generates informative differentially private images for gender classification, despite its simplicity when using only an $L2$ cost function (uninformative images would correspond to a $\approx 50\%$ classification ratio). Qualitatively, Figure 3 illustrates that DP-Sinkhorn can learn rough representations of each semantic class (male and female) and also produces some in-class variations. Visual fidelity of the generated images may be improved in the future through better network architectures, fine-tuning of the adversarial scheme, use of other tailored kernels as cost function, or tighter privacy accounting.

5 Related Works

As discussed in Sec. 2.2, our work directly builds on a series of works on learning with the Sinkhorn divergence (Cuturi, 2013; Genevay et al., 2016; 2018).

The task of learning generative models on private data has been tackled by many prior works. The general approach is to introduce privacy-calibrated noise into the model parameter gradients during training. While various GAN-based approaches have been introduced (Xie et al., 2018; Torkzadehmahani et al., 2019; Frigerio et al., 2019; Yoon et al., 2019; Chen et al., 2020), it is well documented that GANs are unstable during training (Arjovsky & Bottou, 2017; Mescheder et al., 2018). As discussed, this is critical in the context of differential privacy, where the imposed gradient noise can increase training instabilities and where interaction with private data should be limited. It is worth noting that Chen et al. (2020) proposed the same privacy barrier mechanism like us by applying gradient noise on the generated images rather than the generator parameters.

Other types of generative models have been studied in the privacy setting. Acs et al. (2018) partitions the private data in clusters and learns separate likelihood-based generative models for each cluster. Harder et al. (2020) uses MMD with random Fourier features. While these works do not face the

Table 1: Comparison of differentially private image generation results on MNIST and Fashion-MNIST at $(\epsilon, \delta) = (10, 10^{-5})$-DP. Results for other methods (G-PATE (Long et al., 2019), DP-MERF & DP-MERF AE (Harder et al., 2020), DP-CGAN (Torkzadehmahani et al., 2019), GS-WGAN (Chen et al., 2020)) are from Chen et al. (2020). Results averaged over 5 runs of synthetic dataset generation.

| Method | DP-ϵ | MNIST | | | | Fashion-MNIST | | | |
| | | FID | Acc (%) | | | FID | Acc (%) | | |
			Log Reg	MLP	CNN		Log Reg	MLP	CNN
Real data	∞	1.6	92.2	97.5	99.3	2.5	84.5	88.2	90.8
Non-priv Sinkhorn	∞	84.1	88.6	88.2	87.9	105.2	77.6	78.7	72.8
G-PATE	10	177.2	26	25	51/80.9[1]	205.8	42	30	50/69.3[1]
DP-CGAN	10	179.2	60	60	63	243.8	51	50	46
DP-MERF[2]	10	247.5	66	63	63	267.8	59	56	64
DP-MERF AE[2]	10	161.1	54	55	68	213.6	50	56	62
GS-WGAN	10	**61.3**	79	79	80	**131.3**	68	65	65
DP-Sinkhorn	10	124.3	**82.0**	**80.8**	79.9	193.8	**73.4**	**72.2**	67.5

Figure 2: Comparisons on MNIST and Fashion-MNIST between different methods for differentially private image generation at $(10, 10^{-5})$-DP. The first 5 rows showcasing other methods are taken from Chen et al. (2020).

same stability issues as GANs, their restricted modelling capacity results in these methods mostly learning prototype representations for each class. Lastly, while Takagi et al. (2020) produced strong empirical results, their privacy analysis relies on the use of Wishart noise on sample covariance matrices, which has been proven to leak privacy (Sarwate, 2017). Hence, their privacy protection is invalid in its current form.

---

[1]The G-PATE authors report much more accurate classification results than reported in Chen et al. (2020). The visual quality of samples in both papers is roughly the same.

[2]DP-MERF is designed for the low-ε regime and does not make use of the extra privacy budget from $\varepsilon = 10$.

Table 2: Differentially private image generation results on downsampled CelebA .

Method	$(\epsilon, 10^{-6})$-DP	FID	Acc (%)	
			MLP	CNN
Real data	∞	1.1	91.9	95.0
Adversarial Sinkhorn (non-priv)	∞	72.8	78.1	78.2
Pixel Sinkhorn (non-priv)	∞	140.7	78.9	77.9
Adversarial DP-Sinkhorn	10	187.0	74.7	74.5
Pixel DP-Sinkhorn	10	168.4	76.2	75.8

Figure 3: Images Generated on CelebA dataset. From top to botton: Adversarial Sinkhorn, Pixel Sinkhorn, Adversarial DP-Sinkhorn, Pixel DP-Sinkhorn.

There are various works on incorporating non-sensitive public data while learning differentially private models, mostly for discriminative tasks (Papernot et al., 2017; 2018; Zhu et al., 2020), but also for generative modeling. Zhang et al. (2018) uses public data to pretrain discriminators for private GAN learning. Xu et al. (2019) uses public data to calibrate per parameter clipping bounds.

Recently, Triastcyn & Faltings (2020a;b) introduced Bayesian differential privacy for ML, a data-centric notion of differential privacy. It takes into account that a dataset's "typical" data is easier to protect than outliers. However, this approach has not been widely adopted by the community yet and the focus of our work is to introduce DP-Sinkhorn in the regular differential privacy setting.

6   CONCLUSIONS

We propose DP-Sinkhorn, a novel optimal transport-based differentially private generative modeling method. Our approach minimizes the empirical Sinkhorn loss in a differentially private manner and does in general not require any adversarial techniques that are challenging to optimize. Therefore, DP-Sinkhorn is easy to train and deploy, which we hope will help its adoption in practice. We also use a novel trick to force the optimal transport plan to couple same-label data together, thereby allowing for conditional data generation in the Sinkhorn divergence generative modeling framework. We experimentally validate our proposed method and demonstrate superior performance compared to the previous state-of-the-art on standard image classification benchmarks using data generated under differential privacy. We also show differentially private synthesis of informative RGB images without using additional public data. Note that our main experiments only used a simple pixel-wise L2-loss as cost function. This suggests that in the differential privacy setting, where significant gradient perturbations are added to the model, complexity in model and objective are not necessarily beneficial. We conclude that simple and robust models such as ours are a promising direction for differentially private generative modeling.

Future work includes improving DP-Sinkhorn's performance on RGB images and scaling it up to higher resolutions, extending it to other data types, using tailored kernel-based cost functions and incorporating auxiliary public data during training.

REFERENCES

Martin Abadi, Andy Chu, Ian Goodfellow, H. Brendan McMahan, Ilya Mironov, Kunal Talwar, and Li Zhang. Deep learning with differential privacy. New York, NY, USA, 2016. Association for Computing Machinery. ISBN 9781450341394.

Gergely Acs, Luca Melis, Claude Castelluccia, and Emiliano De Cristofaro. Differentially private mixture of generative neural networks. *IEEE Transactions on Knowledge and Data Engineering*, 31(6):1109–1121, 2018.

Martin Arjovsky and Leon Bottou. Towards Principled Methods for Training Generative Adversarial Networks. In *International Conference on Learning Representations*, 2017.

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein gan. *arXiv preprint arXiv:1701.07875*, 2017.

Sean Augenstein, H. Brendan McMahan, Daniel Ramage, Swaroop Ramaswamy, Peter Kairouz, Mingqing Chen, Rajiv Mathews, and Blaise Aguera y Arcas. Generative Models for Effective ML on Private, Decentralized Datasets. In *International Conference on Learning Representations*, 2020.

Borja Balle, Gilles Barthe, and Marco Gaboardi. Privacy amplification by subsampling: Tight analyses via couplings and divergences. In *Advances in Neural Information Processing Systems*, pp. 6277–6287, 2018.

Olivier Bousquet, Sylvain Gelly, Ilya Tolstikhin, Carl-Johann Simon-Gabriel, and Bernhard Schoelkopf. From optimal transport to generative modeling: the vegan cookbook. *arXiv preprint arXiv:1705.07642*, 2017.

Andrew Brock, Jeff Donahue, and Karen Simonyan. Large scale gan training for high fidelity natural image synthesis. In *International Conference on Learning Representations*, 2019.

Kamalika Chaudhuri and Staal A Vinterbo. A stability-based validation procedure for differentially private machine learning. In C. J. C. Burges, L. Bottou, M. Welling, Z. Ghahramani, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 26*, pp. 2652–2660. Curran Associates, Inc., 2013.

Dingfan Chen, Tribhuvanesh Orekondy, and Mario Fritz. Gs-wgan: A gradient-sanitized approach for learning differentially private generators. *arXiv preprint arXiv:2006.08265*, 2020.

Marco Cuturi. Sinkhorn distances: Lightspeed computation of optimal transport. In *Advances in neural information processing systems*, pp. 2292–2300, 2013.

Cynthia Dwork and Aaron Roth. The Algorithmic Foundations of Differential Privacy. 9(3–4), 2014. ISSN 1551-305X.

Cynthia Dwork, Frank McSherry, Kobbi Nissim, and Adam Smith. Calibrating noise to sensitivity in private data analysis. In *Theory of cryptography conference*, pp. 265–284. Springer, 2006.

Jean Feydy. PhD thesis, ENS, Mar 2020. URL https://www.math.ens.fr/~feydy/geometric_data_analysis_draft.pdf.

Jean Feydy, Thibault Séjourné, François-Xavier Vialard, Shun-ichi Amari, Alain Trouvé, and Gabriel Peyré. Interpolating between optimal transport and mmd using sinkhorn divergences. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pp. 2681–2690, 2019.

Lorenzo Frigerio, Anderson Santana de Oliveira, Laurent Gomez, and Patrick Duverger. Differentially private generative adversarial networks for time series, continuous, and discrete open data. In *IFIP International Conference on ICT Systems Security and Privacy Protection*, pp. 151–164. Springer, 2019.

Aude Genevay, Marco Cuturi, Gabriel Peyré, and Francis Bach. Stochastic optimization for large-scale optimal transport. In *Advances in neural information processing systems*, pp. 3440–3448, 2016.

Aude Genevay, Gabriel Peyré, and Marco Cuturi. Learning generative models with sinkhorn divergences. In *International Conference on Artificial Intelligence and Statistics*, pp. 1608–1617, 2018.

Carlos A. Gomez-Uribe and Neil Hunt. The netflix recommender system: Algorithms, business value, and innovation. 6(4), 2016. ISSN 2158-656X.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In Z. Ghahramani, M. Welling, C. Cortes, N. D. Lawrence, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 27*, pp. 2672–2680. Curran Associates, Inc., 2014.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved training of wasserstein gans. In *Advances in neural information processing systems*, pp. 5767–5777, 2017a.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved Training of Wasserstein GANs. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 5767–5777. Curran Associates, Inc., 2017b.

Frederik Harder, Kamil Adamczewski, and Mijung Park. Differentially private mean embeddings with random features (dp-merf) for simple & practical synthetic data generation. *arXiv preprint arXiv:2002.11603*, 2020.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In *Advances in neural information processing systems*, pp. 6626–6637, 2017.

Dean Ho, Stephen R. Quake, Edward R. B. McCabe, Wee Joo Chng, Edward K. Chow, Xianting Ding, Bruce D. Gelb, Geoffrey S. Ginsburg, Jason Hassenstab, Chih-Ming Ho, William C. Mobley, Garry P. Nolan, Steven T. Rosen, Patrick Tan, Yun Yen, and Ali Zarrinpar. Enabling Technologies for Personalized and Precision Medicine. *Trends Biotechnol.*, 38(5):497–518, 2020. doi: 10.1016/j.tibtech.2019.12.021.

Tero Karras, Samuli Laine, Miika Aittala, Janne Hellsten, Jaakko Lehtinen, and Timo Aila. Analyzing and improving the image quality of stylegan. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8110–8119, 2020.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In Yoshua Bengio and Yann LeCun (eds.), *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. URL `http://arxiv.org/abs/1412.6980`.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Chun-Liang Li, Wei-Cheng Chang, Yu Cheng, Yiming Yang, and Barnabás Póczos. Mmd gan: Towards deeper understanding of moment matching network. In *Advances in Neural Information Processing Systems*, pp. 2203–2213, 2017.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*, December 2015.

Yunhui Long, Suxin Lin, Zhuolin Yang, Carl A Gunter, Han Liu, and Bo Li. Scalable differentially private data generation via private aggregation of teacher ensembles. 2019. URL `https://openreview.net/forum?id=Hkl6i0EFPH`.

Lars Mescheder, Andreas Geiger, and Sebastian Nowozin. Which training methods for GANs do actually converge? volume 80 of *Proceedings of Machine Learning Research*, pp. 3481–3490, Stockholmsmässan, Stockholm Sweden, 10–15 Jul 2018. PMLR.

I. Mironov. Rényi differential privacy. In *2017 IEEE 30th Computer Security Foundations Symposium (CSF)*, pp. 263–275, 2017.

Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. In *International Conference on Learning Representations*, 2018.

Aaron van den Oord, Sander Dieleman, Heiga Zen, Karen Simonyan, Oriol Vinyals, Alex Graves, Nal Kalchbrenner, Andrew Senior, and Koray Kavukcuoglu. Wavenet: A generative model for raw audio. *arXiv preprint arXiv:1609.03499*, 2016.

Nicolas Papernot, Martín Abadi, Úlfar Erlingsson, Ian Goodfellow, and Kunal Talwar. Semi-supervised Knowledge Transfer for Deep Learning from Private Training Data. In *International Conference on Learning Representations*, 2017.

Nicolas Papernot, Shuang Song, Ilya Mironov, Ananth Raghunathan, Kunal Talwar, and Úlfar Erlingsson. Scalable Private Learning with PATE. In *International Conference on Learning Representations*, 2018.

Gabriel Peyré and Marco Cuturi. Computational Optimal Transport. *Foundations and Trends in Machine Learning*, 11(5-6):355–607, 2019.

Gabriel Peyré, Marco Cuturi, et al. Computational optimal transport: With applications to data science. *Foundations and Trends® in Machine Learning*, 11(5-6):355–607, 2019.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. *arXiv preprint arXiv:1511.06434*, 2015.

Anand Sarwate. Retraction for symmetric matrix perturbation for differentially-private principal component analysis, 2017. URL https://ergodicity.net/2017/04/07/retraction-for-symmetric-matrix-perturbation-for-differentially-private-principal-component-analysis-icassp-2016/.

Zoltán Szabó and Bharath K Sriperumbudur. Characteristic and universal tensor product kernels. *The Journal of Machine Learning Research*, 18(1):8724–8752, 2017.

Shun Takagi, Tsubasa Takahashi, Yang Cao, and Masatoshi Yoshikawa. P3gm: Private high-dimensional data release via privacy preserving phased generative model. *arXiv preprint arXiv:2006.12101*, 2020.

Reihaneh Torkzadehmahani, Peter Kairouz, and Benedict Paten. Dp-cgan: Differentially private synthetic data and label generation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pp. 0–0, 2019.

Aleksei Triastcyn and Boi Faltings. Bayesian differential privacy for machine learning. In *ICML*, 2020a.

Aleksei Triastcyn and Boi Faltings. Generating Higher-Fidelity Synthetic Datasets with Privacy Guarantees. *arXiv preprint arXiv:2003.00997*, 2020b.

Mei Wang and Weihong Deng. Deep Face Recognition: A Survey. *arXiv preprint arXiv:1804.06655*, 2020.

Yu-Xiang Wang, Borja Balle, and Shiva Prasad Kasiviswanathan. Subsampled rényi differential privacy and analytical moments accountant. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pp. 1226–1235. PMLR, 2019.

Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms. *arXiv preprint arXiv:1708.07747*, 2017.

Liyang Xie, Kaixiang Lin, Shu Wang, Fei Wang, and Jiayu Zhou. Differentially private generative adversarial network. *arXiv preprint arXiv:1802.06739*, 2018.

Chugui Xu, Ju Ren, Deyu Zhang, Yaoxue Zhang, Zhan Qin, and Kui Ren. Ganobfuscator: Mitigating information leakage under gan via differential privacy. *IEEE Transactions on Information Forensics and Security*, 14(9):2358–2371, 2019.

Jinsung Yoon, James Jordon, and Mihaela van der Schaar. PATE-GAN: Generating synthetic data with differential privacy guarantees. In *International Conference on Learning Representations*, 2019.

Xinyang Zhang, Shouling Ji, and Ting Wang. Differentially private releasing via deep generative model (technical report). *arXiv preprint arXiv:1801.01594*, 2018.

Yuqing Zhu and Yu-Xiang Wang. Poission subsampled rényi differential privacy. In *International Conference on Machine Learning*, pp. 7634–7642, 2019.

Yuqing Zhu, Xiang Yu, Manmohan Chandraker, and Yu-Xiang Wang. Private-knn: Practical differential privacy for computer vision. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.

A   OPTIMAL TRANSPORT VIA THE SINKHORN DIVERGENCE

In addition to the notations defined in Sec. 2.1, we denote the Dirac delta distribution at $x \in \mathcal{X}$ as δ_x, and the standard n-simplex as $\mathcal{S}^n$.

Recall from Sec. 2.2 that, given a positive cost function $c : \mathcal{X} \times \mathcal{X} \mapsto \mathbb{R}^+$ and $\epsilon \geq 0$, the Entropy Regularized Wasserstein Distance is defined as:

$$W_{c,\epsilon}(\mu, \nu) = \min_{\pi \in \Pi} \int c(x,y)\pi(x,y) + \epsilon \int \log \frac{\pi(x,y)}{d\mu(x)d\nu(y)} d\pi(x,y) \tag{6}$$

where $\Pi = \left\{ \pi(x,y) \in \mathcal{P}(\mathcal{X} \times \mathcal{X}) | \int \pi(x,\cdot)dx = \nu, \int \pi(\cdot,y)dy = \mu \right\}$.

We use the Sinkhorn divergence, as defined in Feydy et al. (2019).

Definition A.1 *(Sinkhorn Loss) The Sinkhorn loss between measures μ and ν is defined as:*

$$S_{c,\epsilon}(\mu, \nu) = 2W_{c,\epsilon}(\mu, \nu) - W_{c,\epsilon}(\mu, \mu) - W_{c,\epsilon}(\nu, \nu) \tag{7}$$

For modeling data-defined distributions, as in our situation, an empirical version can be defined, too.

Definition A.2 *(Empirical Sinkhorn loss) The empirical Sinkhorn loss computed over a batch of N generated examples and M real examples is defined as:*

$$\hat{S}_{c,\epsilon}(\hat{\mu}, \hat{\nu}) = 2C_{XY} \odot P^*_{\epsilon,X,Y} - C_{XX} \odot P^*_{\epsilon,X,X} - C_{YY} \odot P^*_{\epsilon,Y,Y} \tag{8}$$

where $\hat{\mu} = \frac{1}{N}\sum_{i=1}^{N} \delta_{x_i}$, and $\hat{\nu} = \frac{1}{M}\sum_{j=1}^{M} \delta_{y_j}$. For two samples $A \in \mathcal{X}^N$ and $B \in \mathcal{X}^M$, C_{AB} is the cost matrix between A and B, and $P^*_{\epsilon,A,B}$ is an approximate optimal transport plan that minimizes Eqn. 1 computed over A and B.

P^*_ϵ is arrived at by iterating the dual potentials.

Cuturi (2013) and Feydy et al. (2019) have shown the following dual formulation for the discritized version of $\hat{W}_{c,\epsilon}$:

$$\hat{W}_{c,\epsilon}(\hat{\mu}, \hat{\nu}) = \max_{f,g \in \mathcal{S}^N \times \mathcal{S}^M} \langle \hat{\mu}, f \rangle + \langle \hat{\nu}, g \rangle - \epsilon \langle \hat{\mu} \otimes \hat{\nu}, \exp(\frac{1}{\epsilon}(f \oplus g - C)) - 1 \rangle, \tag{9}$$

where $\otimes$ denotes the product measure and $\oplus$ denotes the "outer sum" such that the output is a matrix of the sums of pairs of elements from each vector. Then, the optimal transport plan P^*_ϵ relates to the dual potentials by $P^*_\epsilon = \exp(\frac{1}{\epsilon}(f \oplus g - C))(\hat{\mu} \otimes \hat{\nu})$. Thus, once we find the optimal f and g, we can obtain P^*_ϵ through this primal-dual relationship. We also know the first-order optimal conditions for f and g through the Karush Kuhn Tucker theorem:

$$f_i = -\epsilon \log \sum_{j=1}^{M} \exp(\log(\hat{\nu}_j) + \frac{1}{\epsilon}g_j - \frac{1}{\epsilon}C(x_i, y_j)) \quad g_j = -\epsilon \log \sum_{i=1}^{N} \exp(\log(\hat{\mu}_i) + \frac{1}{\epsilon}f_i - \frac{1}{\epsilon}C(x_i, y_j))$$

$$\tag{10}$$

To optimize f and g, it suffices to apply the Sinkhorn algorithm (Cuturi, 2013), see Algorithm 3 in the main text. Readers can refer to Feydy (2020) for further details.

B   DIFFERENTIAL PRIVACY

As discussed in Sec. 2.3, differential privacy is the current gold standard for measuring the privacy risk of data releasing programs. It is defined as follows (Dwork et al., 2006):

Definition B.1 *(Differential Privacy) A randomized mechanism $\mathcal{M} : \mathcal{D} \to \mathcal{R}$ with domain $\mathcal{D}$ and range $\mathcal{R}$ satisfies (ε, δ)-DP if for any two adjacent inputs $d, d' \in \mathcal{D}$ differing by at most one entry, and for any subset of outputs $S \subseteq \mathcal{R}$ it holds that*

$$\mathbf{Pr}\left[\mathcal{M}(d) \in S\right] \leq e^\varepsilon \mathbf{Pr}\left[\mathcal{M}(d') \in S\right] + \delta. \tag{11}$$

Gradient perturbation: For a parametric function $f_\theta(x)$ parameterized by θ and loss function $L(f_\theta(x), y)$, usual mini-batched first-order optimizers update θ using gradients $\mathbf{g}_t = \frac{1}{N} \sum_{i=1}^{N} \nabla_\theta L(f_\theta(x_i), y_i)$. Under gradient perturbation, the gradient $\mathbf{g}_t$ is first clipped in L_2 norm by constant Δ, and then noise sampled from $\mathcal{N}(0, \sigma^2 \mathbb{I})$ is added. Since differential privacy is closed under *post-processing*—releasing any transformation of the output of an (ε, δ)-DP mechanism is still (ε, δ)-DP (Dwork & Roth, 2014)—the parameters θ are also differentially private. The relation between (ε, δ) and the perturbation parameters Δ and σ is provided by the following theorem:

Theorem B.1 *For $c^2 > 2 \log(1.25/\delta)$, Gaussian mechanism with $\sigma \geq c\Delta/\varepsilon$ satisfies (ε, δ) differential privacy. (Dwork & Roth, 2014)*

Subsampling: In stochastic gradient descent (SGD) and related methods, randomly drawn batches of data are used in each training step instead of the full dataset. This subsampling of the dataset can provide amplification of privacy protection since the privacy of any record that is not in the batch is automatically protected. Privacy bounds for various subsampling methods have been extensively studied and applied (Dwork et al., 2006; Wang et al., 2019; Balle et al., 2018; Zhu & Wang, 2019).

Composition: SGD requires the computation of the gradient to be repeated every iteration. The repeated application of privacy mechanisms on the same dataset is analyzed through *composition*. Composition of the Gaussian mechanism has been first analyzed by Abadi et al. (2016) through the moments accountant method.

We utilize the often used Rényi Differential Privacy (Mironov, 2017) (RDP), which is defined through the Rényi divergence between mechanism outputs on adjacent datasets:

Definition B.2 *(Rényi Differential Privacy) A randomized mechanism $\mathcal{M} : \mathcal{D} \to \mathcal{R}$ with domain $\mathcal{D}$ and range $\mathcal{R}$ satisfies (α, ε)-RDP if for any adjacent $d, d' \in \mathcal{D}$ it holds that*

$$D_\alpha(\mathcal{M}(d) | \mathcal{M}(d')) \leq \varepsilon, \tag{12}$$

where D_α is the Rényi divergence of order α. Also, any $\mathcal{M}$ that satisfies (α, ε)-RDP also satisfies $(\varepsilon + \frac{\log 1/\delta}{\alpha - 1}, \delta)$-DP.

As discussed in the main text, RDP is a well-studied formulation of privacy that allows tight composition of multiple queries—training iterations in our case—and can be easily converted to standard definitions of DP with definition B.2. Recall that for clipping threshold Δ and standard deviation of Gaussian noise σ, the Gaussian mechanism satisfies $(\alpha, \alpha \Delta^2 / (2\sigma^2))$-RDP (Mironov, 2017). Privacy analysis of a gradient-based learning algorithm entails accounting for the privacy cost of single queries, which corresponds to training iterations in our case, possibly with subsampling due to mini-batched training. The total privacy cost is obtained by summing up the privacy cost across all queries or training steps, and then choosing the best α.

For completeness, the Rényi divergence is defined as: $D_\alpha(P|Q) = \frac{1}{\alpha} \log \mathbb{E}_{x \in Q} \left[\frac{P(x)}{Q(x)} \right]^\alpha$.

C ALGORITHMS

Algorithm 2 Poisson Sample

Input : $d = \{(y, l) \in \mathcal{X} \times \{0, ..., L\}\}^M$, sampling ratio q
Output: $\mathbf{Y} = \{(y_j, l_j) \in \mathcal{X} \times \{0, ..., L\}\}_{j=1}^m$, $m \geq 0$
$\mathbf{s} = \{\sigma_i\}_{i=1}^M \overset{i.i.d.}{\sim} \text{Bernoulli}(q)$
$\mathbf{Y} = \{d_j | \mathbf{s}_j = 1\}_{j=1}^m$

Algorithm 3 Sinkhorn Algorithm $\hat{W}_\epsilon(\mathbf{X}, \mathbf{Y})$

Input: $\mathbf{X} = \{\mathbf{x}\}^n, \mathbf{Y} = \{\mathbf{y}\}^m, \epsilon$
Output: W_ϵ
$\forall (i, j), C_{[i,j]} = c(\mathbf{X}_i, \mathbf{Y}_j)$
$\mathbf{f}, \mathbf{g} \leftarrow \vec{0}$
$\hat{\mu}, \hat{\nu} \leftarrow \text{Unif}(n), \text{Unif}(m)$
while not converged **do**
$\quad \forall i, \mathbf{f}_i \leftarrow -\epsilon \log \sum_{k=1}^m \exp(\log(\hat{\nu}_k) + \frac{1}{\epsilon}\mathbf{g}_k - \frac{1}{\epsilon}C_{[i,k]})$
$\quad \forall j, \mathbf{g}_j \leftarrow -\epsilon \log \sum_{k=1}^n \exp(\log(\hat{\mu}_k) + \frac{1}{\epsilon}\mathbf{f}_k - \frac{1}{\epsilon}C_{[k,j]})$
end while
$W_\epsilon = \langle \hat{\mu}, \mathbf{f} \rangle + \langle \hat{\nu}, \mathbf{g} \rangle$

D   EXPERIMENT DETAILS

D.1   DATASETS

MNIST and Fashion-MNIST both consist of 28x28 grayscale images, partitioned into 60k training images and 10k test images. The 10 labels of the original classification task correspond to digit/object class. For calculating FID scores, we repeat the channel dimension 3 times. CelebA is composed of $\sim$200k colour images of celebrity faces tagged with 40 binary attributes. We downsample all images to 32x32, and use all 162770 train images for training and all 19962 test images for evaluation. Generation is conditioned on the gender attribute.

D.2   CLASSIFIERS

For logistic regression, we use scikit-learn's implementation, using the L-BFGS solver and capping the maximum number of iterations at 5000. The MLP and CNN are implemented in PyTorch. The MLP has one hidden layer with 100 units and a ReLU activation. The CNN has two hidden layers with 32 and 64 filters, and uses ReLU activations. We train the CNN with dropout ($p = 0.5$) between all intermediate layers. Both the MLP and CNN are trained with Adam under default parameters, and use 10% of training data as holdout for early stopping. Training stops after no improvement is seen in holdout accuracy for 10 consecutive epochs.

D.3   ARCHITECTURE, HYPERPARAMETER, AND IMPLEMENTATION

Our DCGAN-based architecture uses 4 transposed convolutional layers with ReLU activations at the hidden layers and tanh activation at the output layer. A latent dimension of 12 and class embedding dimension of 4 is used for MNIST and Fashion-MNIST experiments. CelebA experiments use a latent dimension of 32 and embedding dimension of 4. The latent and class embeddings are concatenated and then fed to the convolutional stack. The first transposed convolutional layer projects the input to $256 \times 7 \times 7$, with no padding. Layers 2,3 and 4 have output depth $[128, 64, 1]$, kernel size $[4, 4, 3]$, stride $[2, 2, 1]$, and padding $[1, 1, 1]$.

Our BigGAN-based architecture uses 4 residual blocks of depth 256, and a latent dimension of 32. Each residual block consists of three convolutional layers with ReLU activations and spectral normalization between each layer. Please refer to Brock et al. (2019) for more implementation details. Our implementation is based on `https://github.com/ajbrock/BigGAN-PyTorch`.

In our experiments with the adversarially trained feature extractor, we used a simple feature extractor with 3 convolutional layers with hidden depth of 64 and output depth of 32. Between each convolutional layer are batchnorm and ReLU layers, followed a 2×2 maxpool layer. The first two layers have kernel size 3 and padding 1, while the last layers have kernel size 1 with no padding. For the generator G_θ and feature extractor ϕ_ω, the adversarial loss objective can be formally expressed as:

$$\min_\theta \max_\omega \hat{S}_{c(\omega),\epsilon}(\hat{\mu}(\theta), \hat{\nu}) = \min_\theta \max_\omega 2\langle c_\phi(G_\theta(z), \mathrm{y}), P^*_\epsilon(G_\theta(z), \mathrm{y})\rangle$$
$$- \langle c_\phi(G_\theta(z), G_\theta(z)), P^*_\epsilon(G_\theta(z), G_\theta(z))\rangle$$
$$- \langle c_\phi(\mathrm{y}, \mathrm{y}), P^*_\epsilon(\mathrm{y}, \mathrm{y})\rangle$$

Where $c_\phi(\mathrm{a}, \mathrm{a}) = ||[\mathrm{a}_{img}, \alpha_c \mathrm{a}_{label}, \alpha_a \frac{\phi(\mathrm{a}_{img})}{||\phi(\mathrm{a}_{img})||_2}]^T - [\mathrm{b}_{img}, \alpha_c \mathrm{b}_{label}, \alpha_a \frac{\phi(\mathrm{b}_{img})}{||\phi(\mathrm{b}_{img})||_2}]^T||_2^2 = c_{adv}([\mathrm{a}_{img}, \mathrm{a}_{label}], [\mathrm{b}_{img}, \mathrm{b}_{label}])$

Hyperparameters of the Sinkhorn loss used were: $\alpha_c = 15$, and entropy regularization $\epsilon = 0.05$ in MNIST and Fashion-MNIST experiments. $\epsilon = 5$ is used for CelebA experiments. We use the implementation publically available at `https://www.kernel-operations.io/geomloss/api/install` and all other hyperparameters are kept at their default values. For all experiments, we use the Adam (Kingma & Ba, 2015) optimizer with learning rate 10^{-5}, $\beta = (0.9, 0.999)$, weight decay 2×10^{-5}.

For privacy accounting, we use the implementation of the RDP Accountant available in Tensorflow Privacy.[1] All experiments employing the pixel-wise $L2$ cost use Poisson sampling, and are amenable

---

[1]`https://github.com/tensorflow/privacy/`

Figure 4: Additional DP-Sinkhorn generated images under $(10, 10^{-6})$differential privacy. Top two rows use DCGAN based generator, while bottom two rows use BigGAN based generator.

to the analysis implemented in `compute_rdp`. For the experiments with the batch-wise feature extractor, examples are batched into records at the start of training, and a single record is drawn at random in each iteration. The privacy amplification for this fixed-size sampling scheme is studied in Wang et al. (2019), and we use the author's implementation of Theorem 9 for bounding the RDP cost of our queries.

For MNIST and Fashion-MNIST results reported in the main body, we use a noise scale of $\sigma = 1.1$ and a batch size of 50 resulting in $q = 1/1200$, which gives us ~ 3.4 million training iterations to reach $\varepsilon = 10$ for $\delta = 10^{-5}$. For the non-private runs, we use a batch size of 500, which improves image quality and diversity. When training with DP, increasing batch size significantly increases the privacy cost per iteration, resulting in poor image quality for fixed $\varepsilon = 10$.

For CelebA results reported in the main body, we use a noise scale of $\sigma = 0.8$ and a batch size of 200 resulting in $q = 0.00123$. At $\delta = 10^{-6}$, we train for 1.1 million steps to reach $\varepsilon = 10$.

E ADDITIONAL RESULTS

We evaluate the impact of architecture choice on the performance in the CelebA task by comparing DP-Sinkhorn+BigGAN with DP-Sinkhorn+DCGAN, under pixel loss. Results are summarized in Table 3 and visualized in Figure 4. Qualitatively, despite reaching lower FID score, the DCGAN-based generator's images have visible artifacts that are not present in models trained with BigGAN-generators.

Table 3: Differetially private image generation results on downsampled CelebA.

Method	DP-ϵ	FID	Acc (%)	
			MLP	CNN
Real data	∞	1.1	91.9	95.0
DCGAN+DP-Sinkhorn	10	156.7	74.96	74.62
BigGAN+DP-Sinkhorn	10	168.4	76.18	75.79