# ADAPTIVE Q-LEARNING FOR INTERACTION-LIMITED REINFORCEMENT LEARNING

## ABSTRACT

Conventional reinforcement learning (RL) needs an environment to collect fresh data, which is impractical when an online interaction is costly. Offline RL provides an alternative solution by directly learning from the logged dataset. However, it usually yields unsatisfactory performance due to a pessimistic update scheme or/and the low quality of logged datasets. Moreover, how to evaluate the policy under the offline setting is also a challenging problem. In this paper, we propose a unified framework called Adaptive Q-learning for effectively taking advantage of offline and online learning. Specifically, we explicitly consider the difference between the online and offline data and apply an adaptive update scheme accordingly, i.e., a pessimistic update strategy for the offline dataset and a greedy or no pessimistic update scheme for the online dataset. When combining both, we can apply very limited online exploration steps to achieve expert performance even when the offline dataset is poor, e.g., random dataset. Such a framework provides a unified way to mix the offline and online RL and gain the best of both worlds. To understand our framework better, we then provide an initialization following our framework. Extensive experiments are done to verify the effectiveness of our proposed method.

## 1 INTRODUCTION

Conventional online reinforcement learning (RL) methods (Haarnoja et al., 2018; Fujimoto et al., 2018) usually learn from experiences generated by interactions with the online environment. They are impractical in some real-world applications, e.g., dialog (Jaques et al., 2019) and education (Mandel et al., 2014), where interactions are costly. Recently, offline RL (Levine et al., 2020) has aroused much attention. It targets the above challenge by making the agent learn from an offline dataset collected by other policies in a purely data-driven manner. The difference between online RL and offline RL is shown in Figure 1.

Existing offline RL studies try to target the distribution mismatch or out-of-distribution actions issue by employing a pessimistic update scheme (Kumar et al., 2019; 2020) or by combination with the imitation learning (Fujimoto et al., 2019). However, when the dataset is fixed, offline RL cannot learn the optimal policy (Kidambi et al., 2020), and even worse, when the dataset's quality is poor, offline RL usually gains a relatively poor performance (Kumar et al., 2020; Fu et al., 2020; Levine et al., 2020). On the other hand, it is challenging to evaluate the learned policy when learning totally from the offline dataset. Even though some research topics, e.g., off-policy evaluation (Dann et al., 2014), study how to evaluate the learned policy without the interaction with the environment, it is still not ideal for the practical purpose.

Some recent works try to address the above issues by employing an offline-online setting. Such methods (Lee et al., 2021; Nair et al., 2020) focus on pre-training a policy using the offline dataset and fine-tuning the policy through further online interactions. Even though their methods alleviate the above issues to some extent, their main bottleneck is that they do not consider the different characteristics of offline and online data. For instance, pre-existing offline data can prevent agents from converging prematurely due to the potential diverse, while online data can improve stability and accelerate convergence. Generally, these different data are mixed and used by a pessimistic strategy to update the policy in their methods, which may be problematic since using a pessimistic strategy for online data may harm the policy performance (Nair et al., 2020). Moreover, with sufficiently

Figure 1: Online RL collect the data by interacting with the environment and they don't utilize the existing logged dataset while offline RL only exploit logged dataset without any future performance improvement. By contrast, we focus on obtaining the best of both worlds.

large and diverse offline data, a well-performed policy can be learned just using a pure online RL algorithm, while the online data (near-on-policy) also play a key role in improving the online RL's stability especially when dataset is not diverse (Fujimoto et al., 2019; Agarwal et al., 2020). Hence, we should take full advantage of both offline and online dataset.

To tackle the above problems, in this paper, we emphasize that *online and offline RL should be coupled organically*. First, a separate updating strategy should be employed for online and offline data, respectively, considering their different characteristics. To do so, we present a framework called adaptive Q-learning that integrates the advantage of offline learning and online learning effectively. When learning from the offline dataset, we conduct a pessimistic update strategy. In contrast, we use a greedy or non-pessimistic update strategy when learning from the online dataset. Second, we design a novel replay buffer to distinguish the offline from online datasets in a simple way. By utilizing such a novel framework and buffer design, the agent can achieve an expert policy using very few online interaction steps regardless of the quality of the offline dataset. In the experiments, our proposed framework can achieve better performance by using only one fifth number of interactions compared with the previous method (Nair et al., 2020).

Our contributions can be summarized as below:

- We propose a unified framework called adaptive Q-learning with limited online interaction steps that can effectively benefit from both the offline dataset and limited online data.
- Based on the general framework, we initialize a practical algorithm, called Greedy-conservative Q-ensemble learning (GCQL) that builds on top of state-of-the-art offline RL method CQL (Kumar et al., 2020) and online RL method REDQ (Chen et al., 2021)
- We empirically verify the effectiveness of our method by comprehensive experiments on the popular offline benchmark D4RL (Fu et al., 2020).

## 2 RELATED WORK

**Online RL** In general, Online RL include the on-policy and off-policy RL (Sutton & Barto, 2011). On-policy RL (Schulman et al., 2015; 2017) only uses current data collected by behavior policy to update its policy, and they cannot learn from history trajectories. As ignoring the history logged data, they usually have a lower sample efficiency than the off-policy RL. Off-policy RL (Haarnoja et al., 2018; Fujimoto et al., 2018; Chen et al., 2021) need to collect the fresh data by interacting with the environment, and they cannot learn well from history trajectories collected by other policies (Fujimoto et al., 2019; Kumar et al., 2020). Consequently, the need for huge online interaction makes online RL impractical for some applications, such as dialog agents (Jaques et al., 2019) or education system (Mandel et al., 2014). In this paper, we refer online RL to off-policy RL as on-policy RL cannot learn from the replay buffer.

**Offline RL** Offline RL algorithms assume the online environment is unavailable and learn policies only from the pre-collected dataset. As value estimation cannot be corrected via online interactions in the offline setting, these methods tend to utilize a pessimistic updating strategy to relieve the distribution mismatch problem (Fujimoto et al., 2019; Kumar et al., 2019). To implement such

a strategy, on the one hand, model-free offline RL methods employ value or policy penalization techniques (Wu et al., 2019; Kumar et al., 2020; Fujimoto et al., 2019; He & Hou, 2020). On the other hand, model-based methods use predictive models to estimate uncertainties and conduct pessimistic updates based on them (Kidambi et al., 2020; Yu et al., 2020). The above algorithms are pure offline RL methods, and they cannot benefit from online exploration effectively. (Nair et al., 2020). Moreover, it is challenging to estimate the learned policy's performance when an online interaction is unavailable. Even though the off-policy evaluation (OPE) (Dann et al., 2014) presents an alternative solution, it is still far from perfect.

**Offline-online mixed RL** Matsushima et al. (2021) propose a deployment-efficiency setting that also focuses on a practical setting: how many times the data-collection policy has been changed. They employ a KL-based trust-region optimization (Schulman et al., 2015) to update the policy. However, it ignores the offline dataset and focuses on the deployment times of the behavior policy instead of the interaction steps. Lee et al. (2021) aims at fine-tuning a pre-trained agent by online experiences and focus on the distribution shift issue. They employ a balanced experience replay buffer and select the near-on-policy samples from offline data. Even the samples are near-on-policy, they still apply a pessimistic strategy. Nair et al. (2020) propose an advantage-weighted actor-critic (AWAC) method that restricts the policy to stay close to the actions observed in the data by an implicit constraint. When online interaction is available, such constraints may have adverse effects on the performance. In contrast, our method explicitly considers the difference between offline and online learning and adaptive apply conservative or non-conservative update schemes. Some works (Zhu et al., 2019; Vecerik et al., 2017; Rajeswaran et al., 2018; Kim et al., 2013) also can learn from online interaction and offline dataset, however, they need the expert demonstrations instead of any dataset which limit their applicability.

## 3 Preliminaries

In reinforcement learning, the interaction with environment usually assumed to be a Markov decision process (MDP) $(\mathcal{S}, \mathcal{A}, p_M, r, \gamma)$, with state space $\mathcal{S}$, action space $\mathcal{A}$, and transition dynamics $p_M(s' \mid s, a)$. At each discrete time step, the agent receive a reward $r(s, a, s') \in \mathbb{R}$ after conducting an action $a$ in state $s$ and arriving at next state $s'$. The agent's objective is to obtain the maximum return which is defined by $R_t = \sum_{i=t+1}^{\infty} \gamma^i r(s_i, a_i, s_{i+1})$. The $\gamma \in [0, 1)$ is a discounted factor that down-weight the future rewards.

The policy $\pi : \mathcal{S} \rightarrow \mathcal{A}$ defines the agent how to select an action when interacting with the environment. Each policy $\pi$ have a corresponding value function $Q^\pi(s, a) = \mathbb{E}_\pi[R_t \mid s, a]$, the expected return when following the policy after taking action $a$ in state $s$. The policy $\pi$'s value function can be updated by the Bellman operator $\mathcal{T}^\pi$:

$$\mathcal{T}^\pi Q(s, a) = \mathbb{E}_{s'}[r + \gamma Q(s', \pi(s'))] \tag{1}$$

When applying a greedy optimal strategy, i.e., $Q^*(s, a) = \max_\pi Q^\pi(s, a)$, it is known as the Q-learning that optimize the policy for maximizing the Q value (Sutton & Barto, 2011). Such a policy and Q function can be approximated with neural networks (Mnih et al., 2015). The above setting is typically off-policy or online RL as they need interaction with the environment to collect data. In principle, off-policy RL algorithms maintain a growing replay buffer $\mathcal{B}$ storing the exploration experiences collected behavior policy.

Offline RL algorithms are based on the off-policy RL techniques but without the online interaction assumption (Levine et al., 2020). In another word, the replay buffer $\mathcal{B}$ size is fixed, and no further interaction with the environment under the offline RL setting. The data from the replay buffer can be collected by one or more behavior policies. Offline RL provides a way to free RL agents from data collection. The offline-online mixed setting focuses on pre-train a policy using the logged dataset and then fine-tuning this pre-trained policy through future online interaction (Nair et al., 2020; Lee et al., 2021).

## 4 Methodology

In this section, we first give an illustrative example to explain our motivation. After that, we introduce the proposed general framework, namely Adaptive Q-learning, trying to couple online and

Figure 2: Score curves of online and offline algorithms on the task Hopper-medium-replay-v0. It is clear that they both learned a relatively good performance after the offline learning. However, CQL's performance improves slowly while the REDQ's performance drops significantly during the offline-online fine-tuning phase.

offline RL in an organic way. Then, we present details about the Online-Offline Replay Buffer, targeting retaining and distinguishing online and offline data simultaneously. Finally, we implement the framework by incorporating SOTA online and offline RL algorithms and introduce the proposed Greedy-Conservative Q-ensemble Learning in detail.

### 4.1 AN ILLUSTRATIVE EXAMPLE

We test the SOAT offline RL method CQL (Kumar et al., 2020) and off-policy RL method REDQ (Chen et al., 2021) under the offline-online fine-tuning setting using one of the D4RL dataset hopper-medium-replay-v0 that consists of diverse experiences. Specifically, we firstly pre-train the agent with the offline dataset for 100000 steps, and then online explore 1000 steps. After that, we do offline update 10000 steps. We repeat such an interleaving process until the summed online exploration steps reach 90K.

The experiment results are showed in Figure 2. We can see both CQL and REDQ have troubles during training under this setting, even though both online and offline data are available here, which should be beneficial for policy learning. Particularly, after the initial offline training, they both achieved a relatively good start-point performance, indicated by the learning curves' starting point. Such result verified Agarwal et al. (2020)'s claim: when the dataset is diverse, online RL is capable of learning effectively. However, when a limited online interaction is available, the online REDQ suffers severe instability, and performance drops significantly. In contrast, the CQL agent maintains a stable learning curve but with a very slow performance improvement because of its conservative strategy. We expect offline RL or online RL can be capable of learning from the fresh on-policy data well. However, they both failed. Such observation indicates that current online or offline RL methods may be ineffective for benefiting from hybrid learning.

### 4.2 ADAPTIVE Q-LEARNING FRAMEWORK

Now, we introduce our proposed framework. The underlying idea is simple. When the agent learns from near-on-policy samples, we choose a more greedy or no-pessimistic strategy. By contrast, when sampling from the offline dataset, we tend to a more pessimistic strategy (Jin et al., 2021). Through such an adaptive strategy, we can make full use of both online and offline data. Here, we take the value penalty as an example (Wu et al., 2019) to explain our framework. The learning objective of adaptive Q learning consists of two parts. One is the regular online Q objective presented by $\mathbb{A}(Q)$, e.g., the bellman backup error. The other is the value penalty term presented by $\mathbb{B}(Q)$, e.g., the Q value regularizer. Then, an adaptive Q-learning objective can be defined by the following equation.

$$Q^{k+1} \leftarrow \arg\min_{Q^k} \mathcal{W}(s, a)\mathbb{B}(Q^k) + \mathbb{A}(Q^k) \tag{2}$$

The function $\mathcal{W}(s, a)$ weight the Q regularizer based on the sampled data. Specifically, when the sampled data is near-on-policy, we rely on the online Q objective more, which means the $\mathcal{W}(s, a)$ will choose a small value, e.g., close to 0. On the contrary, we will choose a bigger value for $\mathcal{W}(s, a)$ when the samples are from the offline buffer. Now, the key problem becomes how to define near-on-policy samples. To solve this issue, we introduce an online-offline replay buffer(OORB).

### 4.3  OORB: ONLINE-OFFLINE REPLAY BUFFER

OORB aims to distinguish the limited online data from offline data. A similar tool can be found in Zheng et al. (2020b;a); Zhang et al. (2019) where they use a two-level replay buffer for boosting the learning of the off-policy agents. However, there is a major difference between ours and theirs: their methods are episode-based, and they select the episode with high episode return, while ours focuses on deciding whether the experiences are near-on-policy or not. In this sense, our OORB is much simpler and effective in our setting. Specifically, the online-offline replay buffer consists of two replay buffers. One is the online replay buffer that collects the online exploration experience. The other is the offline replay buffer consisting of the newly generated online exploration data and the logged dataset collected by any policies. To ensure the data in the online buffer is near-on-policy, we set its size to be much smaller than the size of the offline buffer. We store the fresh exploration experiences following a first-in-first-out rule. When new experiences arrive, the earliest saved experiences will be overridden.

To sample from OORB, we follow a Bernoulli distribution, sampling data from the online buffer with a probability $p$, and the offline buffer with $1 - p$. As explained in section 1, We take the online-offline buffer equally important. Thus, we set $p$ as 0.5 in our experiments. To verify other $p$'s effect, we also conduct extra experiments to investigate the performance with different $p$ in section 5.4. The experiment results indicate that $p = 0.5$ is the most suitable option in most cases, confirming our assumption: offline data and online data are both crucial for RL learning.

### 4.4  GCQL: GREEDY-CONSERVATIVE Q-ENSEMBLE LEARNING

For understanding our framework better, we provide a practical algorithm. According to equation 2, we need to define two parts in Q's update objective. The first is the pessimistic regularization term used in an offline learning setting, and the second is a normal online Q objective. For the first term, we can employ a penalized value function, e.g., a divergence function between distributions over actions (Wu et al., 2019), or the conservative objective used in Kumar et al. (2020). The second term is the normal Q-learning objective, such as the Bellman backup error. We present an initialization on top of the state-of-the-art offline RL agent CQL (Fujimoto et al., 2019), and the online RL agent REDQ (Chen et al., 2021), called Greedy conservative Q-ensemble learning (GCQL). Specifically, we replace the Q target function of CQL with the random-ensemble Q functions of REDQ, i.e., the randomized min Q values, and keep the rest of the objective of CQL. Formally, for each $Q_i$, the updated objective can be defined by following equation:

$$
\begin{aligned}
Q_i^{k+1} \leftarrow \arg\min_{Q_i^k} & \mathcal{W}(\mathbf{s}, \mathbf{a})\mathbb{E}\left[\mathcal{C}\left(Q_i^k(\mathbf{s}, \mathbf{a}, \mathbf{s}', \mathbf{a}')\right)\right] \\
& + \mathbb{E}\left[\left(Q_i^k(\mathbf{s}, \mathbf{a}) - \hat{\mathcal{B}}^\pi \hat{Q}^k(\mathbf{s}', \mathbf{a}')\right)^2\right], \quad \mathbf{s}, \mathbf{a}, \mathbf{s}' \sim \mathcal{D}_{\text{OORB}}, \mathbf{a}' \sim \pi_\phi(\cdot \mid s')
\end{aligned}
\tag{3}
$$

where $\mathcal{C}$ is the conservative regularization term in CQL, $\mathcal{D}_{\text{OORB}}$ is the OORB replay buffer, and $\hat{\mathcal{B}}^\pi \hat{Q}^k(\mathbf{s}, \mathbf{a})$ is defined by

$$r + \gamma \min_{i \in \mathcal{M}} \hat{Q}_i^k(\mathbf{s}', \mathbf{a}'), \quad \mathbf{a}' \sim \pi_\phi(\cdot \mid \mathbf{s}') \tag{4}$$

Where the $\mathcal{M}$ is the multiple Qs' index, and we randomly select two Q functions just following the REDQ's setting. The policy update is defined by

---

**Algorithm 1:** Greedy-conservative Q-ensemble learning

---

1    **Initialization**:
2    Initialize policy $\pi_\phi$, ensemble Q functions $Q_{\theta_i}, i \in N$
3    Online exploration steps $T_{on}$, offline update steps $T_{off}$
4    Initialize $T_{initial}$, sample possibility $p$, start sampling steps:$T_s$
5    Initialize OORB: online replay buffer size,$S_{on}$; offline relay buffer size,$S_{off}$
6    **Initial offline learning**:
7    Train the agent for $T_{initial}$ using the logged dataset
     `// Interaction-limited interleaving offline-online learning`
8    **while** *True* **do**
9       Explore $T_{on}$ steps online
10      Store the $T_{on}$ steps experiences to online buffer and offline buffer
11      $S_{on} \leftarrow S_{on} + T_{on}$
12      **for** $t < T_{off}$ **do**
13         Sample a random value $p_s \sim \mathbb{U}(0,1)$
14         **if** $p_s < p$ *and* $S_{on} > T_s$ **then**
15            Sample a batch $(s, a)$ from online buffer
16            Set the $\mathcal{W}(s, a)$ to 0
17         **end**
18         **else**
19            Sample a batch $(s, a)$ from offline buffer
20            Set the $\mathcal{W}(s, a)$ to 1
21         **end**
22         Update the Q functions by equation 3
23         Update the policy by equation 5
24      **end**
25    **end**

---

$$\pi_{\phi_{k+1}} \leftarrow \arg\max_{\pi_{\phi_k}} \mathbb{E}\left[\mathbb{E}_{i \in N}\left[Q_i\left(\mathbf{s}, \mathbf{a}\right)\right] - \alpha \log \pi_{\phi_k}\left(\mathbf{a} \mid \mathbf{s}\right)\right], \quad \mathbf{a} \sim \pi_{\phi_k}\left(\cdot \mid \mathbf{s}\right) \tag{5}$$

When sampled data is from the online replay buffer, we set $\mathcal{W}(s, a)$ to 0, otherwise 1, that is why we called it greedy-conservative. In another word, we greedy exploit the near-on-policy data by the normal online RL scheme without any conservative regularizer. On the contrary, we conservatively exploit the offline data by employing the offline RL regularizer. Formally, this strategy can be explained by following equation 6

$$\mathcal{W}(s, a) = \begin{cases} 0 & \text{if } (s, a) \text{ are sampled from online replay buffer} \\ 1 & \text{otherwise} \end{cases} \tag{6}$$

The practical algorithm is shown in Algorithm 1. Here, we also explain the main steps in the Algorithm as follows.

1. We first learn from the existing logged data for $T_{initial}$ steps to leverage offline dataset. To make good use of the offline data, we usually set a big value for $T_{initial}$, e.g., 100000 steps. We then begin the following interleaving learning scheme.

2. We conduct the online exploration process for $T_{on}$ steps and store the new experiences to OORB. We set the online exploration steps $T_{on}$ to a small value, e.g., 1000. In contrast, the offline update step $T_{off}$ is set to be larger than $T_{on}$, e.g., 10000.

3. We sample a batch from our OORB and update our policy and Q functions. If the sampled batch comes from the online buffer, then we set the weight value $\mathcal{W}(s, a)$ to 0, otherwise 1.

4. Repeat the above two steps.

| Environment | GCQL(Ours) | CQL | REDQ | AWAC |
|---|---|---|---|---|
| walker2d-random | **53±27** | 16±9 | 19±3 | 12 |
| hopper-random | **84±40** | 11±1 | 12±17 | 63 |
| halfcheetah-random | **100±2** | 46±4 | 34±1 | 53 |
| walker2d-medium | **94±6** | 83±1 | 5±3 | 80 |
| hopper-medium | **105±1** | 100±1 | 3±1 | 91 |
| halfcheetah-medium | **66±3** | 42±0 | 46±1 | 41 |
| walker2d-expert | **117±2** | 113±1 | 6±1 | 103 |
| hopper-expert | **114±1** | 113±1 | 12±6 | 112 |
| halfcheetah-expert | **110±0** | 108±1 | 1±0 | 106 |
| walker2d-medium-expert | **117±4** | 113±1 | 12±3 | 78 |
| hopper-medium-expert | **115±1** | 114±0 | 40±15 | 112 |
| halfcheetah-medium-expert | **107±1** | 95±2 | 9±3 | 41 |
| walker2d-medium-replay | **114±6** | 64±5 | 53±11 | - |
| hopper-medium-replay | **96±9** | 39±4 | 38±9 | - |
| halfcheetah-medium-replay | **59±2** | 50±0 | 50±1 | - |

Table 1: Performance of policies trained using 90K online interaction steps for GCQL, CQL and REDQ, and 500K online interaction for AWAC whose results are taken from Nair et al. (2020). The normalized score are reported as average return across five random seeds in our experiments and the whole learning curves are showed in appendix A

.

## 5 EXPERIMENTS

In this section, we design experiments to verify the effectiveness of our method from three perspectives: 1. the performance superiority compared with other baselines; 2. ablation studies to explain the effectiveness of each component used in our method. 3. the impact of different hyper-parameters.

### 5.1 SETTINGS

All experiments were done on the continuous control benchmark: Mujoco (Todorov et al., 2012). The logged history dataset is the popular offline dataset D4RL (Fu et al., 2020). To make interaction limited, we set the online interaction step for each iteration to a small value, i.e., 1000. To better exploit the offline dataset, we set the offline training step to a large value, i.e., 100000 for $T_{intial}$, and 10000 for $T_{off}$. The entire offline-gradient-update step is about 1 million, and the entire online exploration step is around 90K. As we take the online and offline datasets equally important, we set the sampling possibility from the online buffer as 0.5. We further set the size of the online buffer as 20000 and the size of the offline buffer as 3e6. We follow the default setting of all the baselines, except for the number of the ensemble Q, which is 5 in our setting. The above configurations are fixed for all tasks. As our main purpose is to present a new framework instead of gaining state-of-the-art performance, we do not fine-tune these hyper-parameters.

### 5.2 OVERALL PERFORMANCE

Table 1 shows the comparison results of Ours, CQL, AWAC, and REDQ. The AWAC's results are directly taken from their paper (Nair et al., 2020). We test on the continuous control tasks from D4RL, including random-v0, medium-v0, expert-v0, medium-expert-v0, and medium-replay-v0. As the online exploration is available, we report the max average score as the performance. For a comprehensive understanding, we also include the whole learning curves in appendix A, which demonstrates that our method also achieves a better final average score at the last iteration in most cases. As shown in Table 1, our method gains a better performance than the baselines in all tasks. Particularly, for the medium-replay and random dataset, our GCQL outperforms the baselines by a large margin. By contrast, CQL also achieves an expert performance on the high-quality dataset, e.g., expert and medium-expert tasks. For these high-quality datasets, our method achieves a comparable

Figure 3: Ablation study on walker2d task

or slightly better performance over CQL. In terms of the online RL method: REDQ, it fails on almost all tasks. Even though we employ an online limited exploration process, conventional online RL cannot benefit from such limited experiences. On the contrary, such limited online experiences could bring catastrophic consequences, e.g., on the halfcheetah-medium-replay task, REDQ suffers a significant instability issue. On the other hand, when dataset quality is high, e.g., expert or medium-expert dataset, our method can leverage the benefit of the offline RL that gains an expert performance with very few online interaction steps, such as around 2e4 steps. By contrast, when dataset quality is poor, e.g., the random dataset or medium-replay. Our method can also take the advantage of the limited online experiences as much as possible. For instance, only our method can learn effectively with less than 1e5 online steps on random or medium-replay dataset. In sum, our method can benefit the most from the limited online experience while still maintain the offline learning's ability.

## 5.3 Ablation studies

To estimate each component's contribution in our method, we conduct an ablation study on the walker2d. To do this, we design four variants of our method:

- **GCQL-we**: GCQL without the ensemble where we only use two Q functions same as the setting of CQL.
- **GCQL-wo**: GCQL without the online replay buffer where we only sample from the offline buffer.
- **GCQL-wg**: GCQL without the greedy where we fix the weighed $\mathcal{W}$ to 1.
- **GCQL-wc**: GCQL without the conservative term where we fix the $\mathcal{W}$ to 0.

These results are shown in figure 3, and we evaluate it on five datasets on walker2d across three random seeds. Firstly, from figure 3, it is easy to deduce that when the quality of data is high, i.e., including the expert dataset, almost all variants perform well except the GCQL-wc. The underlying reason is obvious as we firstly pre-train the policy by offline data. If no such conservative restriction, then the pre-trained policy would suffer a serious distribution mismatch issue (Kumar et al. (2020)) and gain a poor pre-trained policy at last. By contrast, with the conservative scheme, the policy

would obtain a relatively good pre-trained policy. That is why the starting point of GCQL-wc is much lower than other variants.

Secondly, when the dataset is diverse, i.e., the dataset is collected by different behavior policies and include data from different distributions, such as the medium-replay dataset, the greedy scheme (including the offline-online replay buffer and the greedy update strategy) plays an important role in such case while the ensemble feature seems have limited influence. For instance, the performance declined significantly for GCQL-wo and GCQL-wg on Walker2d-medium-replay.

Thirdly, when the dataset is not diverse, e.g., the medium dataset (data is collected by one medium policy), almost all tasks grow slowly except GCQL-wc. The underlying reason may be a lack of diversity, as Agarwal et al. (2020) declaimed diverse dataset plays a key role in RL. However, according to the learning curves, our method still has a clear performance improvement at the latter learning stage. For the random dataset, all variants fail due to the poor quality of the dataset. Instead, our method achieves a clear performance improvement under the random dataset, which shows the effectiveness of each component in this case.

## 5.4 ANALYSIS ON HYPER-PARAMETERS

As we do not fine-tune the hyper-parameters in our experiments, one may wonder how the hyper-parameters affect the performance. To this end, we conduct experiments to discuss their influence. The detailed learning curves are shown in appendix B. As one main characteristic of our method is limited interaction, we fix the online exploration step as 1000 for each iteration in the Mujoco benchmark. We then investigate the performance with the initial update steps $T_{initial}$, the offline update steps $T_{off}$, and the sample possibility from online buffer $p$ following the configuration:

- GCQL-o2e4: $T_{off}$ is 2e4 steps. GCQL-o5e3: $T_{off}$ is 5e3 steps

- GCQL-i2e5: $T_{initial}$ is 2e5 steps. GCQL-i5e4: $T_{initial}$ is 5e4 steps.

- GCQL-0.3: $p$ is 0.3. GCQL-0.4:$p$ is 0.4. GCQL-0.5:$p$ is 0.5. GCQL-0.6: $p$ is 0.6. GCQL-0.7:$p$ is 0.7.

According to the evaluation results, we may conclude that our framework is insensitive to the $T_{initial}$ and $T_{off}$, especially when the dataset is not poor, e.g., not the random dataset. By contrast, $p$ has a bigger impact on the performance. Particularly, higher $p$ performs better than the lower ones on the medium and medium-replay tasks, while the lower ones perform better on the other tasks. That indicates that when dataset quality is very good or very bad, more offline update performs better. On the contrary, more online update is preferred for the medium-quality dataset. On the other hand, only the variant of p=0.5 can achieve a clear performance improvement in both the medium and random datasets. Overall, the default setting p=0.5 is the most suitable setting in terms of all tasks, which indicates that taking the online and offline data equally important may be the best option in most cases.

## 6 CONCLUSIONS

This paper first discusses the disadvantages of online RL and offline RL, and then the shortcomings of current offline-online mixed methods. After that, we propose a unified framework that can take advantage of online and offline learning effectively. Furthermore, a practical initialization that greedily exploits the online experiences and conservatively exploits the offline experiences is presented. We conduct comprehensive experiments to verify the effectiveness of our method. In terms of the shortcomings, although our framework can take advantage of the offline and online dataset under the interaction-limited setting, the quality of the offline dataset still has a big impact on the performance. For instance, the policy would converge to expert performance very soon when learning from the expert dataset. By contrast, our method is relatively slower when learning from the random dataset. Importantly, we also show that offline and online (near-on-policy) datasets are both crucial for RL learning. Thus, through a unified way, we can gain the best from both sides. At last, we hope this work could contribute to bridging the gap between the practice and DRL research.

## REFERENCES

Rishabh Agarwal, Dale Schuurmans, and Mohammad Norouzi. An optimistic perspective on offline reinforcement learning. In *ICML*, 2020.

Xinyue Chen, Che Wang, Zijian Zhou, and Keith W. Ross. Randomized ensembled double q-learning: Learning fast without a model. *ICLR*, abs/2101.05982, 2021.

Christoph Dann, Gerhard Neumann, Jan Peters, et al. Policy evaluation with temporal differences: A survey and comparison. *Journal of Machine Learning Research*, 2014.

Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4rl: Datasets for deep data-driven reinforcement learning. *arXiv preprint arXiv:2004.07219*, 2020.

Scott Fujimoto, Herke van Hoof, and Dave Meger. Addressing function approximation error in actor-critic methods. In *International Conference on Machine Learning*, 2018.

Scott Fujimoto, D. Meger, and Doina Precup. Off-policy deep reinforcement learning without exploration. In *ICML*, 2019.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. *arXiv preprint arXiv:1801.01290*, 2018.

Qiang He and X. Hou. Popo: Pessimistic offline policy optimization. *ArXiv*, abs/2012.13682, 2020.

Natasha Jaques, Asma Ghandeharioun, Judy Hanwen Shen, Craig Ferguson, Agata Lapedriza, Noah Jones, Shixiang Gu, and Rosalind Picard. Way off-policy batch deep reinforcement learning of implicit human preferences in dialog. *arXiv preprint arXiv:1907.00456*, 2019.

Ying Jin, Zhuoran Yang, and Zhaoran Wang. Is pessimism provably efficient for offline rl? *International Conference on Machine Learning*, 2021.

R. Kidambi, A. Rajeswaran, Praneeth Netrapalli, and T. Joachims. Morel : Model-based offline reinforcement learning. *NeurIPS*, abs/2005.05951, 2020.

Beomjoon Kim, Amir massoud Farahmand, Joelle Pineau, and Doina Precup. Learning from limited demonstrations. In *NeurIPS*, 2013.

Aviral Kumar, Justin Fu, Matthew Soh, George Tucker, and Sergey Levine. Stabilizing off-policy q-learning via bootstrapping error reduction. In *Advances in Neural Information Processing Systems*, pp. 11761–11771, 2019.

Aviral Kumar, Aurick Zhou, G. Tucker, and Sergey Levine. Conservative q-learning for offline reinforcement learning. *NeurIPS*, 2020.

Seunghyun Lee, Younggyo Seo, Kimin Lee, Pieter Abbeel, and Jinwoo Shin. Offline-to-online reinforcement learning via balanced replay and pessimistic q-ensemble. *arXiv preprint arXiv:2107.00591*, 2021.

Sergey Levine, Aviral Kumar, G. Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *ArXiv*, abs/2005.01643, 2020.

Travis Mandel, Yun-En Liu, Sergey Levine, Emma Brunskill, and Zoran Popovic. Offline policy evaluation across representations with applications to educational games. In *AAMAS*, volume 1077, 2014.

Tatsuya Matsushima, Hiroki Furuta, Yutaka Matsuo, Ofir Nachum, and Shixiang Gu. Deployment-efficient reinforcement learning via model-based offline optimization. *ICLR*, 2021.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

Ashvin Nair, Murtaza Dalal, Abhishek Gupta, and Sergey Levine. Accelerating online reinforcement learning with offline datasets. *CoRR*, abs/2006.09359, 2020.

Aravind Rajeswaran, Vikash Kumar, Abhishek Gupta, Giulia Vezzani, John Schulman, Emanuel Todorov, and Sergey Levine. Learning complex dexterous manipulation with deep reinforcement learning and demonstrations. *Robotics: Science and Systems*, 2018.

John Schulman, Sergey Levine, Pieter Abbeel, Michael Jordan, and Philipp Moritz. Trust region policy optimization. In *International conference on machine learning*, pp. 1889–1897. PMLR, 2015.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Richard S Sutton and Andrew G Barto. Reinforcement learning: An introduction. 2011.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 5026–5033. IEEE, 2012.

Mel Vecerik, Todd Hester, Jonathan Scholz, Fumin Wang, Olivier Pietquin, Bilal Piot, Nicolas Heess, Thomas Rothörl, Thomas Lampe, and Martin Riedmiller. Leveraging demonstrations for deep reinforcement learning on robotics problems with sparse rewards. *arXiv preprint arXiv:1707.08817*, 2017.

Y. Wu, G. Tucker, and Ofir Nachum. Behavior regularized offline reinforcement learning. *ArXiv*, abs/1911.11361, 2019.

Tianhe Yu, G. Thomas, Lantao Yu, S. Ermon, J. Zou, Sergey Levine, Chelsea Finn, and Tengyu Ma. Mopo: Model-based offline policy optimization. *NeurIPS*, abs/2005.13239, 2020.

Zhizheng Zhang, Jiale Chen, Zhibo Chen, and Weiping Li. Asynchronous episodic deep deterministic policy gradient: Towards continuous control in computationally complex environments. *arXiv preprint arXiv:1903.00827*, 2019.

Han Zheng, Jingping Jiang, Pengfei Wei, Guodong Long, and C. Zhang. Competitive and cooperative heterogeneous deep reinforcement learning. In *AAMAS*, 2020a.

Han Zheng, Pengfei Wei, Jing Jiang, Guodong Long, Q. Lu, and C. Zhang. Cooperative heterogeneous deep reinforcement learning. *NeurIPS*, 2020b.

Henry Zhu, Abhishek Gupta, Aravind Rajeswaran, Sergey Levine, and Vikash Kumar. Dexterous manipulation with deep reinforcement learning: Efficient, general, and low-cost. In *2019 International Conference on Robotics and Automation (ICRA)*, pp. 3651–3657. IEEE, 2019.

## A    LEARNING CURVES FOR ALL TASKS

Figure 4 indicate the whole learning curves for GCQL, REDQ and CQL.

## B    EXTRA EXPERIMENTS ON HYPER-PARAMETERS

Figure 5 and 6 shows the different hyper-parameters' setting on the performance.

Figure 4: Training curves on D4RL continuous control benchmark across five random seeds

Figure 5: Different offline update steps on walker2d task across three random seeds.

Figure 6: Different possibility setting on walker2d task across three random seeds.