Timing is Everything: Learning to Act Selectively with Costly Actions and Budgetary Constraints

Abstract

Many real-world settings involve costs for performing actions; transaction costs in financial systems and fuel costs being common examples. In these settings, performing actions at each time step quickly accumulates costs leading to vastly suboptimal outcomes. Additionally, repeatedly acting produces wear and tear and ultimately, damage. Determining *when to act* is crucial for achieving successful outcomes and yet, the challenge of efficiently *learning* to behave optimally when actions incur minimally bounded costs remains unresolved. In this paper, we introduce a reinforcement learning (RL) framework named **L**earnable **I**mpulse **C**ontrol **R**einforcement **A**lgorithm (LICRA), for learning to optimally select both when to act and which actions to take when actions incur costs. At the core of LICRA is a nested structure that combines RL and a form of policy known as *impulse control* which learns to maximise objectives when actions incur costs. We prove that LICRA, which seamlessly adopts any RL method, converges to policies that optimally select when to perform actions and their optimal magnitudes. We then augment LICRA to handle problems in which the agent can perform at most $k < \infty$ actions and more generally, faces a budget constraint. We show LICRA learns the optimal value function and ensures budget constraints are satisfied almost surely. We demonstrate empirically LICRA's superior performance against benchmark RL methods in OpenAI gym's *Lunar Lander* and in *Highway* environments and a variant of the Merton portfolio problem within finance.

1 Introduction

There are many settings in which agents incur costs each time they perform an action. Transaction costs in financial settings [17], fuel expenditure [28], toxicity as a side effect of controlling bacteria [25] and physical damage produced by repeated action that produces wear and tear are just a few among many examples [11]. In these settings, performing actions at each time step is vastly suboptimal since acting in this way results in prohibitively high costs and undermines the service life of machinery. Minimising wear and tear is an essential attribute to safeguard against failures that can result catastrophic losses [11].

Reinforcement learning (RL) is a framework that enables autonomous agents to learn complex behaviours from interactions with the environment [26]. Within the standard RL paradigm, determining optimal actions involves making a selection from among many (possibly infinite) actions; a procedure that must be performed at each time-step as the agent decides on an action. In unknown settings, the agent cannot immediately exploit any topological structure of the action set (if any exists). Consequently, learning *not to take* an action i.e performing a zero or *null action*, involves expensive optimisation procedures over the entire action set. Since this must be done at each state, this process is vastly inefficient for learning optimal policies when the agent incurs costs for acting.

In this paper, we tackle this problem by developing an RL framework for finding both an optimal criterion to determine whether or not to execute actions as well as learning optimal actions. A key component of our framework is a novel combination of RL with a form of policy known as *impulse control* [19, 17]. This enables the agent to determine the appropriate points to perform an action as well as the optimal action itself. Despite its fundamental importance as a tool for tackling decision problems with costly actions, presently, the use of impulse control within learning contexts (and unknown environments) is unaddressed.

We present an RL impulse control framework called LICRA, which, to our knowledge, is the first learning framework for impulse control. To enable learning optimal impulse control policies in unknown environments, we devise a framework that consists of separate RL components for learning when to act and how to act optimally. The resulting framework is a structured two-part learning process which differs from current RL protocols. In LICRA, at each time step, the agent firstly makes a decision whether to act or not leading to a binary decision space $\{0, 1\}$ (we later show that this is determined by evaluating an easy-to-evaluate criterion which has the value function as its input). The second decision part determines the best action to take. This generates a subdivision of the state space into two regions; one in which the agent performs actions and another in which it does not act at all. This is extremely useful since the agent quickly determines the set of states to *not take* actions while performing actions only at the subset of states where actions are to be executed.

We then establish theory that ensures convergence of LICRA to an optimal policy for such settings. To do this, we give a series a results namely:

i) We establish a dynamic programming principle (DPP) for impulse control and show that the optimal value function can be obtained as a limit of a value iterative procedure (Theorem 1) which lays the foundation for an RL approach to impulse control.

ii) We extend result i) to a new variant of Q learning which enables the impulse control problem to be solved using our RL method (Theorem 2).

iii) We characterise the optimal conditions for performing an action which we reveal to be a simple 'obstacle condition' involving the agent's value function (Prop. 1). Using this, the agent can quickly determine whether or not it should act and if so, then learn what the optimal action is.

iv) We then extend the result i) to (linear) function approximators enabling the value function to be parameterised (Theorem 3).

iv) In Sec. 6, we extend LICRA to include budgetary constraints so that each action draws from a fixed budget which the agent must stay within. Analogous to the development of i), we establish another DPP from which we derive a Q-learning variant for tackling impulse control with budgetary constraints (Theorem 4). A particular case of a budget constraint is when the number of actions the agent can take over the horizon is capped.

Lastly, we perform a set of experiments to validate our theory within the *Highway* driving simulator and OpenAI's *LunarLander* [7].

LICRA confers a series of advantages. As we demonstrate in our experiments, LICRA learns to compute the optimal problems in which the agent faces costs for acting in an efficient way which outperforms leading RL baselines. Second, as demonstrated in Sec. 6 LICRA handles settings in which the agent has a cap the total number of actions it is allowed to execute and more generally, generic budgetary constraints. LICRA is able to accommodate any RL base algorithm (see Sec. 11) unlike various RL methods designed to handle budgetary constraints.

2 Related Work

In continuous-time optimal control theory [21], problems in which the agent faces a cost for each action are tackled with a form a policy known as *impulse control* [19, 17, 2]. In impulse control frameworks, the dynamics of the system are modified through a sequence of discrete actions or bursts chosen at times that the agent chooses to apply the control policy. This distinguishes impulse control models from classical decision methods in which an agent takes actions at each time step while being tasked with the decision of only which action to take. Impulse control models represent appropriate modelling frameworks for financial environments with transaction costs, liquidity risks and economic environments in which players face fixed adjustment costs (e.g. *menu costs*) [14, 18].

The current setting is intimately related to the *optimal stopping problem* which widely occurs in finance, economics and computer science [20, 27]. In the optimal stopping problem, the task is

determine a criterion that determines when to arrest the system and receive a terminal reward. In this case, standard RL methods are unsuitable since they require an expensive sweep (through the set of states) to determine the optimal point to arrest the system. The current problem can be viewed as an augmented problem of optimal stopping since the agent must now determine both a sequence of points to perform an action or *intervene* and their optimal magnitudes — only acting when the cost of action is justified [22]. Adapting RL to tackle optimal stopping problems has been widely studied [27, 4, 8] and applied to a variety of real-world settings within finance [10], radiation therapy [1] and network operating systems [3]. Our work serves as a natural extenstion to RL approaches to optimal stopping to the case in which the agent must decide at which points to take many actions. As with optimal stopping, standard RL methods cannot efficiently tackle this problem since determining whether to perform a 0 action requires a costly sweep through the action space at every state [27].

3 Preliminaries

Reinforcement Learning (RL). In RL, an agent sequentially selects actions to maximise its expected returns. The underlying problem is typically formalised as an MDP $\langle \mathcal{S}, \mathcal{A}, P, R, \gamma \rangle$ where $\mathcal{S} \subset \mathbb{R}^p$ is the set of states, $\mathcal{A} \subset \mathbb{R}^k$ is the set of actions, $P : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to [0, 1]$ is a transition probability function describing the system's dynamics, $R : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ is the reward function measuring the agent's performance and the factor $\gamma \in [0, 1)$ specifies the degree to which the agent's rewards are discounted over time [26]. At time $t \in 0, 1, \dots$, the system is in state $s_t \in \mathcal{S}$ and the agent must choose an action $a_t \in \mathcal{A}$ which transitions the system to a new state $s_{t+1} \sim P(\cdot|s_t, a_t)$ and produces a reward $R(s_t, a_t)$. A policy $\pi : \mathcal{S} \times \mathcal{A} \to [0, 1]$ is a probability distribution over state-action pairs where $\pi(a|s)$ represents the probability of selecting action $a \in \mathcal{A}$ in state $s \in \mathcal{S}$. The goal of an RL agent is to find a policy $\hat{\pi} \in \Pi$ that maximises its expected returns given by the value function: $v^\pi(s) = \mathbb{E}[\sum_{t=0}^{\infty} \gamma^t R(s_t, a_t)|a_t \sim \pi(\cdot|s_t)]$ where Π is the agent's policy set.

We consider a setting in which the agent faces at least some minimal cost for each action it performs. With this, the agent's task is to maximise:

$$v^\pi(s) = \mathbb{E}\left[\sum_{t=0}^{\infty} \gamma^t \left\{\mathcal{R}(s_t, a_t) - \mathcal{C}(s_t, a_t)\right\} \bigg| s_0 = s\right], \tag{1}$$

where for any state $s \in \mathcal{S}$ and any action $a \in \mathcal{A}$, the functions $\mathcal{R}$ and $\mathcal{C}$ are given by $\mathcal{R}(s, a) = R(s, a)\mathbf{1}_{a \in \mathcal{A}} + R(s, 0)(1 - \mathbf{1}_{a \in \mathcal{A}})$ where $\mathbf{1}_{a \in \mathcal{A}}$ is the indicator function which is 1 when $a \in \mathcal{A}$ and 0 otherwise and $\mathcal{C}(s, a) := c(s, a)\mathbf{1}_{a \in \mathcal{A}}$ where $c : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ is a minimally bounded (cost) function[1] that introduces a cost each time the agent performs an action. Examples of the cost function is a quasi-linear function of the form $c(s_t, a_t) = \kappa + f(a_t)$ where $f : \mathcal{A} \to \mathbb{R}_{>0}$ and κ is a positive real-valued constant. Since acting at each time step would incur prohibitively high costs, the agent must be selective when to perform an action. Therefore, in this setting, the agent's problem is augmented to learning both an optimal policy for its actions and, learning at which states to apply its action policy.

Example: Merton Portfolio Problem with Transaction Costs [9]. An investor performs a series of costly portfolio adjustments by buying and selling amounts of different assets within their portfolio. Each investment incurs a fixed minimal cost (also known as *transaction costs*) which is deducted from the investor's available cash-flow. The investor's aim is to maximise their total wealth (the value of the sum of their assets) at some time horizon by adjusting their portfolio of investments. Problems of this kind, portfolio investment problems are of fundamental importance within finance [16].

Example 2. An autonomous vehicle must perform a series of actions to perform a task. Each action draws from its fuel budget. In order to complete its task successfully, during the task, the vehicle must ensure it maintains an available supply.

4 The LICRA Framework

In RL, the agent's problem involves learning to act at *every* state including those in which actions do not significant impact on its total return. While we can add a zero action to the action set $\mathcal{A}$ and apply standard methods, we argue that this may not be the best solution in many situations. We argue the

---

[1]I.e. a function which is bounded below by a positive constant.

optimal policy has the following form:

$$\widetilde{\pi}(\cdot|s) = \begin{cases} a_t & s \in \mathcal{S}_I, \\ 0 & s \notin \mathcal{S}_I, \end{cases} \tag{2}$$

which implies that we simplify policy learning by determining the set $\mathcal{S}_I$ first — the set where we actually need to learn the policy.

We now introduce a learning method for producing impulse controls. This enables the agent to learn to select states to perform actions. Therefore, now agent is tasked with learning to act at states that are most important for maximising its total return given the presence of the cost for each action. Now at each state the agent first makes a *binary decision* to decide to perform an action.

Our framework, LICRA consists of two core components: firstly a RL process $\mathfrak{g} : \mathcal{S} \times \{0,1\} \to [0,1]$ and a second RL process $\pi : \mathcal{S} \times \mathcal{A} \to [0,1]$. The role of $\mathfrak{g}$ is to determine whether or not an action is to be performed by the policy π at a given state s. If activated, the policy π determines the action to be selected. Prior to decisions being made, the policy π communicates to $\mathfrak{g}$ the action it would take. An important feature of our LICRA is the *sequential decision process*. In LICRA, the policy π first proposes an action $a \in \mathcal{A}$ which is observed by the policy $\mathfrak{g}$. Therefore, the role of $\mathfrak{g}$ is to prevent actions for which the change in expected future rewards does not exceed the costs incurred for taking such actions. By isolating a decision policy over whether an action should be taken or not, the impulse controls mechanism results in a framework in which the problem facing the agent has a markedly reduced decision space (in comparison to a standard RL method). Crucially, the agent must compute optimal actions at only a subset of states which are chosen by the policy $\mathfrak{g}$. Below is the pseudocode for LICRA, we provide full details of the code in Sec. 10 of the Appendix.

Algorithm 1 **L**earnable **I**mpulse **C**ontrol **R**einforcement **A**lgorithm (LICRA)

1: **Input:** Stepsize α, batch size B, episodes K, steps per episode T, mini-epochs e
2: **Initialise:** Policy network (acting) π, Policy network (switching) $\mathfrak{g}$,
   Critic network (acting)V_π,Critic network (switching)$V_\mathfrak{g}$
3: Given reward objective function, R, initialise Rollout Buffers $\mathcal{B}_\pi, \mathcal{B}_\mathfrak{g}$ (use replay buffer for SAC)
4: **for** $N_{episodes}$ **do**
5:    Reset state s_0, Reset Rollout Buffers $\mathcal{B}_\pi, \mathcal{B}_\mathfrak{g}$
6:    **for** $t = 0, 1, \dots$ **do**
7:       Sample $a_t \sim \pi(\cdot|s_t)$
8:       Sample $g_t \sim \mathfrak{g}(\cdot|s_t)$
9:       **if** $g_t = 0$ **then**
10:          Apply a_t so $s_{t+1} \sim P(\cdot|a_t, s_t)$,
11:          Receive rewards $r_t = \mathcal{R}(s_t, a_t)$
12:          Store (s_t, a_t, s_{t+1}, r_t) in $\mathcal{B}_\pi$
13:       **else**
14:          Apply the null action so $s_{t+1} \sim P(\cdot|0, s_t)$,
15:          Receive rewards $r_t = \mathcal{R}(s_t, 0)$.
16:       **end if**
17:       Store (s_t, g_t, s_{t+1}, r_t) in $\mathcal{B}_\mathfrak{g}$
18:    **end for**
19:    **// Learn the individual policies**
20:    Update (using SAC or PPO) policy π and critic V_π networks using $\mathfrak{B}_\pi$
21:    Update (using SAC or PPO) policy $\mathfrak{g}$ and critic $V_\mathfrak{g}$ networks using $\mathfrak{B}_\mathfrak{g}$
22: **end for**

While we consider now two policies $\pi, \mathfrak{g}$, the cardinality of the action space does not change. In the discrete case the cardinality is still $|\mathcal{A}| + 1$, where $|\mathcal{A}|$ is cardinality of the action space for policy π. Although action space cardinality does not change there are still benefits of using impulse control mechanism. This mechanism forces the agent to first determine the set of states to perform actions *only then* determine the optimal actions at these states. An important fact to note is that the decision space for the determining whether or not to execute an action is $\mathcal{S} \times \{0,1\}$ i.e at each state it makes a binary decision. Consequently, the learning process for aspect is much quicker than a policy which must optimise over a decision space which is $|\mathcal{S}||\mathcal{A}|$ (choosing an action from its action space at every state). This results in the agent rapidly learning which states to focus on to learn which actions to

165 perform. In the case of π with a continuous action space again the impulse control mechanism does
166 not change the cardinality of the action space. However, if the set $\mathcal{S}/\mathcal{S}_I$, where the optimal policy
167 chooses 0, is large enough, then again it can be more efficient to learn $\mathfrak{g}$ first and only then learn π.

168 In Sec. 5, we show the convergence properties of LICRA. LICRA consists of two independent
169 procedures: the agent learns its action policy π and simultaneously learns its impulse policy $\mathfrak{g}$ which
170 determines at which states to perform an action. In our implementation, we used proximal policy
171 optimisation (PPO) [23] for the policy π. For the impulse policy $\mathfrak{g}$, we used a soft actor critic
172 (SAC) process [12] whose action set consists of two actions: intervene or do not intervene. As we
173 demonstrate in Sec. 11, LICRA is a plug & play framework which enables these RL components to
174 be replaced with any RL algorithm of choice.

175 5 Convergence and Optimality of LICRA

176 A key aspect of our framework is the presence of two RL processes that make decisions in a sequential
177 order. In order to determine when to act the policy $\mathfrak{g}$ must learn the states to allow the policy π to
178 perform an action which the policy π must learn to select optimal actions whenever it is allowed to
179 execute an action.

180 In this section, we prove that LICRA converges to an optimal solution of the system. Central to
181 LICRA is a Q-learning type method which is adapted to handle RL settings in which the agent must
182 also learn when to act. We then extend the result to allow for (linear) function approximators. We
183 provide a result that shows the optimal intervention times are characterised by an 'obstacle condition'
184 which can be evaluated online therefore allowing the $\mathfrak{g}$.

185 Given a function $Q^{\pi,\mathfrak{g}} : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$, $\forall \pi \in \Pi$ and $\mathfrak{g}$, $\forall s_{\tau_k} \in \mathcal{S}$, we define
186 the intervention operator $\mathcal{M}^{\pi,\mathfrak{g}} Q^{\pi,\mathfrak{g}}$ by $\mathcal{M}^{\pi,\mathfrak{g}} Q^{\pi,\mathfrak{g}}(s_{\tau_k}, a_{\tau_k}) := \mathcal{R}(s_{\tau_k}, a_{\tau_k}) - c(s_{\tau_k}, a_{\tau_k}) +$
187 $\gamma \sum_{s' \in \mathcal{S}} P(s'; a_{\tau_k}, s) v^{\pi,\mathfrak{g}}(s') \Big| a_{\tau_k} \sim \pi$, where τ_k is an intervention time.

188 The interpretation of $\mathcal{M}$ is the following: suppose that the agent is using the policy π and at time τ_k
189 the system is at a state s_{τ_k} and the agent performs an action $a_{\tau_k} \sim \pi(\cdot|s_{\tau_k})$. A cost of $c(s_{\tau_k}, a_{\tau_k})$
190 is then incurred by the agent and the system transitions to $s' \sim P(\cdot; a_{\tau_k}, s)$. Lastly, recall $v^{\pi,\mathfrak{g}}$ is
191 the agent value function under the policy pair (π, g). Therefore, the quantity $\mathcal{M} v^{\pi,\mathfrak{g}}$ measures the
192 expected future stream of rewards after an immediate intervention minus the cost of intervention.
193 This object plays a crucial role in the LICRA framework which as we later discuss, exploits the cost
194 structure of the problem to determine when the agent should perform an intervention.

195 For any state $s_t \in \mathcal{S}$, we define the Bellman operator T by:

$$T v^{\pi,\mathfrak{g}}(s_t) := \max \left\{ \mathcal{M}^{\pi,\mathfrak{g}} Q^{\pi,\mathfrak{g}}(s_t, a), \mathcal{R}(s_t, 0) + \gamma \sum_{s' \in \mathcal{S}} P(s'; 0, s_t) v^{\pi,\mathfrak{g}}(s') \right\}, \tag{3}$$

196 The Bellman operator captures the nested sequential structure of the LICRA algorithm. In particular,
197 the structure in (3) consists of an inner structure which consists of two terms: the first term is the
198 expected future return given an action is taken at the current state under the policy π. The second term
199 is the expected future return given no action is taken at the current state. Lastly, the outer structure is
200 an optimisation which compares the expected return of the two possibilities and selects the maximum.

201 Our first result proves T is a contraction operator in particular, the following bound holds:

202 **Lemma 1.** *The Bellman operator T is a contraction, that is the following bound holds:*

$$\|Tv - Tv'\| \le \gamma \|v - v'\|,$$

203 where v, v' are elements of a finite normed vector space. We can now state our first main result:

204 **Theorem 1.** *Given any $v^{\pi,\mathfrak{g}} : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$, the optimal value function is given by $\lim_{k \to \infty} T^k v^{\pi,\mathfrak{g}} =$*
205 $\max_{\hat{\pi}, \hat{g} \in \Pi} v^{\hat{\pi}, \hat{g}} = v^{\pi^\star, g^\star}$ *where $(\pi^\star, g^\star)$ is the optimal policy pair.*

206 The result of Theorem 1 enables the solution to the agent's impulse control problem to be determined
207 using a value iteration procedure. Moreover, Theorem 1 enables a Q-learning approach [6] for finding
208 the solution to the agent's problem.

Theorem 2. *Consider the following Q learning variant:*

$$Q_{t+1}(s_t, a_t) = Q_t(s_t, a_t)$$
$$+ \alpha_t(s_t, a_t) \left[\max \left\{ \mathcal{M}^{\pi,\mathfrak{g}} Q_t(s_t, a_t), \mathcal{R}(s_t, 0) + \gamma \max_{a' \in \mathcal{A}} Q_t(s_{t+1}, a') \right\} - Q_t(s_t, a_t) \right],$$

then $Q_t(s)$ converges to $Q^\star$ with probability 1, where $s_t, s_{t+1} \in \mathcal{S}$ and $a_t \in \mathcal{A}$.

We now extend the result to (linear) function approximators:

Theorem 3. *Given a set of linearly independent basis functions $\Phi = \{\phi_1, \dots, \phi_p\}$ with $\phi_k \in L_2, \forall k$. LICRA converges to a limit point $r^\star \in \mathbb{R}^p$ which is the unique solution to $\Pi \mathfrak{F}(\Phi r^\star) = \Phi r^\star$ where $\mathfrak{F}\Lambda := \hat{R} + \gamma P \max\{\mathcal{M}\Lambda, \Lambda\}$. Moreover, $r^\star$ satisfies: $\|\Phi r^\star - Q^\star\| \le (1 - \gamma^2)^{-1/2} \|\Pi Q^\star - Q^\star\|$.*

The theorem establishes the convergence of LICRA to a stable point with the use of linear function approximators. The second statement bounds the proximity of the convergence point by the smallest approximation error that can be achieved given the choice of basis functions.

Having constructed a procedure to find the optimal agent's optimal value function, we now seek to determine the conditions when an intervention should be performed. Let us denote by $\{\tau_k\}_{k \ge 0}$ the points at which the agent decides to act or *intervention times*, so for example if the agent chooses to perform an action at state s_6 and again at state s_8, then $\tau_1 = 6$ and $\tau_2 = 8$. The following result characterises the optimal intervention policy $\mathfrak{g}$ and the optimal times $\{\tau_k\}_{k \ge 0}$.

Proposition 1. *The policy $\mathfrak{g}$ is given by: $\mathfrak{g}(s_t) = H(\mathcal{M}^{\pi,\mathfrak{g}} Q^{\pi,\mathfrak{g}} - Q^{\pi,\mathfrak{g}})(s_t, a_t), \quad \forall (s_t) \in \mathcal{S} \times \{0, 1\}$, where $Q^{\pi,\mathfrak{g}}$ is the solution in Theorem 1, $\mathcal{M}$ is the intervention operator and H is the Heaviside function, moreover the intervention times are $\tau_k = \inf\{\tau > \tau_{k-1} | \mathcal{M}^{\pi,\mathfrak{g}} Q^{\pi,\mathfrak{g}} = Q^{\pi,\mathfrak{g}}\}$.*

Prop. 1 characterises the (categorical) distribution $\mathfrak{g}$. Moreover, given the function Q, the times $\{\tau_k\}$ can be determined by evaluating if $\mathcal{M}Q = Q$ holds.

A key aspect of Prop. 1 is that it exploits the cost structure of the problem to determine when the agent should perform an intervention. In particular, the equality $\mathcal{M}Q = Q$ implies that performing an action and incurring a cost for doing so is optimal.

6 Budget Augmented LICRA via State Augmentation

We now tackle the problem of RL with a budget. To do this, we combine the above impulse control technology with state augmentation technique proposed in [24] The mathematical formulation of the problem is now given by the following for any $s \in \mathcal{S}$:

$$\max_{\pi \in \Pi, g} v^{\pi,\mathfrak{g}}(s) \text{ s. t. } n - \sum_{t=0}^{\infty} \sum_{k \ge 1} \delta_{\tau_k}^t \ge 0, \tag{4}$$

where $n \in \mathbb{N}$ is a fixed value that represents the maximum number of allowed interventions. In order to avoid dealing with a constrained MDP, we propose to introduce a new variable z_t tracking the remaining number of impulses: $z_t = n - \sum_{i=0}^{t-1} \sum_{k \ge 1} \delta_{\tau_k}^i$. We treat z_t as another state and augment the state-space resulting in the transition $\widetilde{\mathcal{P}}$:

$$s_{t+1} \sim P(\cdot | s_t, a_t),$$
$$z_{t+1} = z_t - \sum_{k \ge 1} \delta_{\tau_k}^t, \quad z_0 = n, \tag{5}$$

where $\sum_{k \ge 1} \delta_{\tau_k}^t$ is equal to one if there an impulse was applied at time t and zero if it was not. In order to avoid violations, we reshape the reward as follows:

$$\widetilde{\mathcal{R}}(s_t, z_t, a_t) = \begin{cases} \mathcal{R}(s_t, a_t) & z_t \ge 0, \\ -\Delta & z_t < 0, \end{cases}$$

where $\Delta > 0$ is a large enough hyper-parameter ensuring that there are no safety violations. To summarise we aim to solve the following problem:

$$v^{\pi,\mathfrak{g}}(s, z) = \mathbb{E}\left[\sum_{t=0}^{\infty} \gamma^t \widetilde{\mathcal{R}}(s_t, z_t, a_t) | a_t \sim \pi(\cdot | s_t, z_t) \right], \tag{6}$$

where the policy now depends on the variable z_t. Note that $\widetilde{\mathcal{P}}$ in Equation 5 is a Markov process and, the rewards $\widetilde{\mathcal{R}}$ are bounded, as long as the rewards $\mathcal{R}$ are bounded. Therefore, we can apply directly the results for impulse control to this case as well. We denote the augmented MDP by $\widetilde{\mathcal{M}} = \langle \mathcal{S} \times \mathcal{Z}, \mathcal{A}, \widetilde{\mathcal{P}}, \widetilde{R}, \gamma \rangle$, where $\mathcal{Z}$ is the space of the augmented state. We have the following.

Theorem 4. *Consider the MDP $\widetilde{\mathcal{M}}$ for the problem 6, then:*

a) The Bellman equation holds, i.e. there exists a function $\tilde{v}^{*,\boldsymbol{\pi},\mathfrak{g}}$ s.th. $\tilde{v}^{*,\boldsymbol{\pi},\mathfrak{g}}(s,z) = \max_{\boldsymbol{a} \in \mathcal{A}} \left(\widetilde{\mathcal{R}}(s,z,\boldsymbol{a}) + \gamma \mathbb{E}_{s',z' \sim \mathcal{P}} \left[\tilde{v}^{*,\boldsymbol{\pi},\mathfrak{g}}(s',z') \right] \right)$, where the optimal policy for $\widetilde{\mathcal{M}}$ has the form $\pi^*(\cdot|s,z)$;

b) Given a $\tilde{v} : \mathcal{S} \times \mathcal{Z} \to \mathbb{R}$, the stable point solution for $\widetilde{\mathcal{M}}$ is a given by $\lim_{k \to \infty} \tilde{T}^k \tilde{v}^{\boldsymbol{\pi},g} = \max_{\hat{\boldsymbol{\pi}} \in \boldsymbol{\Pi}, \hat{\mathfrak{g}}} \tilde{v}^{\hat{\boldsymbol{\pi}}, \hat{\mathfrak{g}}} = \tilde{v}^{*,\boldsymbol{\pi},\mathfrak{g}^*}$, where $(\boldsymbol{\pi}^*, \mathfrak{g}^*)$ is an optimal policy of $\widetilde{\mathcal{M}}$ and $\tilde{T}$ is the Bellman operator of $\widetilde{\mathcal{M}}$.

The result has several important implications. The first is that we can use a modified version of LICRA to obtain the solution of the problem while guaranteeing convergence (under standard assumptions). Secondly, our state augmentation procedure admits a Markovian representation of the optimal policy.

7 Experiments

We will now study empirically the performance of the LICRA framework. In experiments, we use different instances of LICRA, one where both policies are trained using PPO update (referred to as **LICRA_PPO**) and one where the policy deciding whether to act is trained using SAC and the other policy trained with PPO (referred to as **LICRA_SAC**). We have benchmarked both of these algorithms together with common baselines on environments, where it would be natural to introduce the concept of the cost associated with actions. Further experiment details are in the Appendix.

Merton's Portfolio Problem with Transaction Costs.

Merton Investment Problem in which the investor faces transaction costs [9] is a well-known problem within finance. In our environment, the agent can decide to move its wealth between a risky asset and a risk-free asset. The agent receives a reward only at the final step, equal to the utility of the portfolio with a risk aversion factor equal to 0.5. If the final wealth of risky asset is s_T and final wealth of risk-free asset is c_T, then the agent will receive a reward of $u(x) = 2\sqrt{s_T + c_T}$. The wealth evolves according to the following SDE:

$$dW_t = (r + p_t(\mu - r))W_t + W_t p_t \sigma dB_t$$

where W_t is the current wealth, dB_t is an increment of Brownian motion and p_t is the proportion of wealth invested in the risky asset. In our experiments we set the risk-free return $r = 0.01$, risky asset return $\mu = 0.05$ and volatility $\sigma = 1$. We discretise the action space so that at each step the

Figure 1: Training results in Merton investment problem.

Figure 2: a) Drive Environment. b) Training results in drive environment.

agent has three actions available: move 10% of risky asset wealth to the risk-free asset, move 10% of risk-free asset wealth to the risky asset or do nothing. Each time the agent moves the assets, it incurs a cost of 1, which can be thought of as a transaction fee. The agent can act after a time interval of 0.01 seconds and the episode ends after 75 steps. The results of training are shown in Figure 1 and they clearly demonstrate that LICRA finds a better policy than standard PPO and learns much faster than SAC. Also comparing the variance among different seeds, we can see that LICRA is a much more stable algorithm than the other two.

Driving Environment Fuel Rationing.

We studied an autonomous driving scenario where fuel-efficient driving is a priority. One of the main components of fuel-efficient driving is controlled usage of acceleration and braking, in the sense that 1) one wants to limit the amount of acceleration and braking altogether and 2) if ones need to speed up or slow down it should be done slowly and gently. Intuitively, we believe this is a problem where LICRA should thrive as the impulse control agent can learn to restrict the amount of acceleration and braking dependent on current velocity and the presence of other cars in favour of, for example, allowing the car to decelerate naturally. We utilise the highway-env [15] environment on a simple highway task (see Fig (2. a)) where the green vehicle is our controlled vehicle) where the goal is to avoid crashing into other vehicles whilst driving at a reasonable speed. We add a cost function into the reward term dependent on the continuous acceleration action, $C(a_t) = K + a_t^2$, where K is a fixed constant cost of taking any action, and $a_t \in [-1, 1]$, with larger values of acceleration or braking being penalised more.

In Fig. (2.b) we demonstrate our results. Notably, LICRA is able to massively outperform the baselines, especially our safety specific baselines which struggle to deal with the cost function associated with the environment. We believe one reason for the success of LICRA is that it is far easier for it to utilise the null action of zero acceleration/braking than the other algorithms, whilst all the algorithms have a guaranteed cost at every time step whilst not gaining a sizeable reward to counter the cost.

Lunar Lander Environment.

We have used the Lunar Lander environment with OpenAI gym and manually added minimal bounded costs in the reward definition. The agent needs to maintain both a good posture mid-air and reach the landing pad as quickly as possible. Therefore, the reward function is given by:

$$\text{Reward}(s_t) = 3 * (1 - \mathbf{1}_{d_t - d_{t-1} = 0}) - 3 * (1 - \mathbf{1}_{v_t - v_{t-1} = 0}) - 3 * (1 - \mathbf{1}_{\omega_t - \omega_{t-1} = 0})$$

$$-0.03 * \text{FuelSpent}(s_t) - 10 * (v_t - v_{t-1}) - 10 * (\omega_t - \omega_{t-1}) + 100 * \text{hasLanded}(s_t)$$

where d_t is the distance to the landing pad, v_t is the velocity of the agent, and ω_t is the angular velocity of the agent at time t. $\mathbf{1}_X$ is the indicator function of taking actions, which is 1 when the statement X is true and 0 when X is false. Considering the limited fuel budget, we assume that

(a)   (b)

Figure 3: a) The lander must land on the pad between two flags. . b) Training results in Lunar Lander.

we have a fixed cost for each action taken by the agent here, and doing nothing brings no cost. Then, to describe the goal of the game, we define the function of the final status by hasLanded(), which is 0 when not landing; 1 when the agent has landed softly on the landing pad; and -1 when the lander runs out of fuel or loses contact with the pad on landing. The reward function rewards the agent for reducing its distance to the landing pad, decreasing its speed to land smoothly and keeping the angular speed at a minimum to prevent rolling. Additionally, it penalises the agent for running out of fuel and deters the agent from taking off again after landing.

By introducing such a reward function with minimally bounded costs, our goal was to test if LICRA can exploit the optimal policy. In Fig. 3, we observe that the LICRA agent outperforms all the baseline agents, in terms of both the sample efficiency and the average test return (the total of rewards in each timestep). Moreover, we observe that LICRA enables more stable training than PPO, PPO-Lagrangian and CPO. On the other hand, we observe that SAC is more suitable than PPO in this scenario, also when adopting impulse control.

8 Conclusion

We presented a novel method to tackle the problem of learning how to select when to act in addition to learning which actions to execute. Our framework, which is a general tool for tackling problems of this kind seamlessly adopts RL algorithms enabling them to efficiently tackle problems in which the agent must be selective about when it executes actions. This is of fundamental importance in practical settings where performing many actions over the horizon can lead to costs and undermine the service life of machinery. We demonstrated that our solution, LICRA which at its core has a sequential decision structure that first decides whether or not an action ought to be taken under the action policy can solve tasks where the agent faces costs with extreme efficiency as compared to leading reinforcement learning methods. In some tasks, we showed that LICRA is able to solve problems that are unsolvable using current reinforcement learning machinery. We envisge that this framework can serve as the basis extensions to different settings including adversarial training for solving a variety of problems within RL.

References

[1] Ali Ajdari, Maximilian Niyazi, Nils Henrik Nicolay, Christian Thieke, Robert Jeraj, and Thomas Bortfeld. Towards optimal stopping in radiation therapy. *Radiotherapy and Oncology*, 134:96–100, 2019.

[2] Luluwah Al-Fagih. The british knock-out put option. *International Journal of Theoretical and Applied Finance*, 18(02):1550008, 2015.

[3] Juan J Alcaraz, Jose A Ayala-Romero, Javier Vales-Alonso, and Fernando Losilla-López. Online reinforcement learning for adaptive interference coordination. *Transactions on Emerging Telecommunications Technologies*, 31(10):e4087, 2020.

[4] Sebastian Becker, Patrick Cheridito, and Arnulf Jentzen. Deep optimal stopping. *arXiv preprint arXiv:1804.05394*, 2018.

[5] Albert Benveniste, Michel Métivier, and Pierre Priouret. *Adaptive algorithms and stochastic approximations*, volume 22. Springer Science & Business Media, 2012.

[6] Dimitri P Bertsekas. *Approximate dynamic programming*. Athena scientific Belmont, 2012.

[7] Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

[8] Shuhang Chen, Adithya M Devraj, Ana Bušić, and Sean Meyn. Zap q-learning for´ optimal stopping. In *2020 American Control Conference (ACC)*, pages 3920–3925. IEEE, 2020.

[9] Mark HA Davis and Andrew R Norman. Portfolio selection with transaction costs. *Mathematics of operations research*, 15(4):676–713, 1990.

[10] Abderrahim Fathan and Erick Delage. Deep reinforcement learning for optimal stopping with application in financial engineering. *arXiv preprint arXiv:2105.08877*, 2021.

[11] F Grandt Jr. Damage tolerant design and nondestructive inspection-keys to aircraft airworthiness. *Procedia Engineering*, 17:236–246, 2011.

[12] Tuomas Haarnoja, Aurick Zhou, Kristian Hartikainen, George Tucker, Sehoon Ha, Jie Tan, Vikash Kumar, Henry Zhu, Abhishek Gupta, Pieter Abbeel, et al. Soft actor-critic algorithms and applications. *arXiv preprint arXiv:1812.05905*, 2018.

[13] Tommi Jaakkola, Michael I Jordan, and Satinder P Singh. Convergence of stochastic iterative dynamic programming algorithms. In *Advances in neural information processing systems*, pages 703–710, 1994.

[14] Ralf Korn. Some applications of impulse control in mathematical finance. *Mathematical Methods of Operations Research*, 50(3):493–518, 1999.

[15] Edouard Leurent. An environment for autonomous driving decision-making. `https://github.com/eleurent/highway-env`, 2018.

[16] Harry M Markowitz. Foundations of portfolio theory. *The journal of finance*, 46(2):469–477, 1991.

[17] David Mguni. Duopoly investment problems with minimally bounded adjustment costs. *arXiv preprint arXiv:1805.11974*, 2018.

[18] David Mguni. Optimal capital injections with the risk of ruin: A stochastic differential game of impulse control and stopping approach. *arXiv preprint arXiv:1805.01578*, 2018.

[19] David Mguni. A viscosity approach to stochastic differential games of control and stopping involving impulsive control. *arXiv preprint arXiv:1803.11432*, 2018.

[20] David Mguni. Cutting your losses: Learning fault-tolerant control and optimal stopping under adverse risk. *arXiv preprint arXiv:1902.05045*, 2019.

[21] Bernt Øksendal. Stochastic differential equations. In *Stochastic differential equations*, pages 65–84. Springer, 2003.

[22] Bernt Øksendal and Agnès Sulem. Approximating impulse control by iterated optimal stopping. In *Applied Stochastic Control of Jump Diffusions*, pages 255–272. Springer, 2019.

[23] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *CoRR*, abs/1707.06347, 2017.

[24] Aivar Sootla, Alexander I. Cowen-Rivers, Taher Jafferjee, Ziyan Wang, David Mguni, Jun Wang, and Haitham Bou-Ammar. Sauté RL: Almost surely safe reinforcement learning using state augmentation. *arXiv preprint arXiv:2202.06558*, 2022.

[25] Aivar Sootla, Diego Oyarzún, David Angeli, and Guy-Bart Stan. Shaping pulses to control bistable systems: Analysis, computation and counterexamples. *Automatica*, 63:254–264, 2016.

[26] Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

[27] John N Tsitsiklis and Benjamin Van Roy. Optimal stopping of markov processes: Hilbert space theory, approximation algorithms, and an application to pricing high-dimensional financial derivatives. *IEEE Transactions on Automatic Control*, 44(10):1840–1851, 1999.

[28] Pu Zhao, Yanzhi Wang, Naehyuck Chang, Qi Zhu, and Xue Lin. A deep reinforcement learning framework for optimizing fuel economy of hybrid electric vehicles. In *2018 23rd Asia and South Pacific design automation conference (ASP-DAC)*, pages 196–202. IEEE, 2018.