DuwatBench: Bridging Language and Visual Heritage through an Arabic Calligraphy Benchmark for Multimodal Understanding

Abstract

Arabic calligraphy represents one of the richest visual traditions of the Arabic language, blending linguistic meaning with artistic form. Although multimodal models have advanced across languages, their ability to process Arabic script, especially in artistic and stylized calligraphic forms, remains largely unexplored. To address this gap, we present DuwatBench, a benchmark of 1,050 curated samples containing about 1,400 words across 6 classical and modern calligraphic styles, each paired with sentence-level detection annotations. The dataset reflects real-world challenges in Arabic writing, such as complex stroke patterns, dense ligatures, and stylistic variations that often challenge standard text recognition systems. Using DuwatBench, we evaluated 13 leading Arabic and multilingual multimodal models and show that while they perform well in clean text, they struggle with calligraphic variation, artistic distortions, and precise visual–text alignment. By publicly releasing DuwatBench and its annotations, we aim to advance culturally grounded multimodal research, foster fair inclusion of Arabic language and visual heritage in AI systems, and support continued progress in this area. Our benchmark and the evaluation suit will be publicly available.

1 Introduction

Arabic calligraphy sits at the meeting point of language and visual art. Letters are bound, stretched, and ornamented; diacritics and ligatures introduce significant variation in glyph shapes and baselines; style rules vary across schools such as Thuluth, Diwani, Naskh, and Kufic. These properties make calligraphy culturally and technically challenging for machine perception. Prior works ((Lorigo and Govindaraju, 2006), (Al-Salman and Alyahya, 2017)) have noted the added difficulty of Arabic script due to positional letter forms, dense ligaturing, and heavy use of diacritics, especially when written artistically rather than as plain text.

Figure 1: **DuwatBench Taxonomy and Distribution.** DuwatBench encompasses six principal Arabic calligraphy styles (Thuluth, Diwani, Kufic, Naskh, Ruq'ah, and Nastaliq). The benchmark includes a distribution of collected samples ranging from 699 in Thuluth to 6 in Nasta'liq. Beyond style diversity, the taxonomy incorporates word-level categories, including non-religious terms, Quranic words, devotional expressions, names of the Prophet and companions, names of Allah, and personal names. This organization provides a structured basis for evaluating both the visual variation and semantic depth of Arabic calligraphy.

Despite growing interest in Arabic handwriting and manuscripts, existing datasets only partially address calligraphic use cases. Calliar (Alyafeai et al., 2022) provides pen-trace data across multiple text levels but lacks the textures and visual complexity of real artworks. HICMA (Ismail et al., 2023) includes real-world calligraphy images with sentence-level and style labels, but is limited to five scripts, focuses mainly on recognition, and lacks layout annotations as well as evaluation on large multimodal models (LMMs). Earlier works on style classification (Kaoudja, 2022) or letter-level corpora (Adam et al., 2017; Salamah and King, 2018) remain too narrow for comprehensive multimodal assessment.

Meanwhile, Arabic-capable multimodal models are advancing rapidly. Cross-lingual CLIP variants (Chen et al., 2023) and multilingual VLMs (Geigle et al., 2023) demonstrate strong retrieval and captioning capabilities across lan-

Feature	Allaf	Adam	Sal&King	Kaoudja	Calliar	MOJ-DB	HICMA	DuwatBenach *(Ours)*
Real-world images	✓	✓	✓	✓	✗	✓	✓	✓
Style diversity (multiple styles)	✗	✓	✓	✓	✓	✗	✓	✓
Word / Sentence-level text	✓	✗	✗	✓	✓	✓	✓	✓
Full text transcriptions	✗	✗	✗	✗	✓	✓	✓	✓
Bounding boxes for detection	✗	✗	✗	✗	✗	✗	✗	✓
Complex artistic backgrounds	✓	✗	✗	✗	✗	✓	✓	✓
Publicly available	✗	✗	✗	✗	✓	✓	✓	✓

Table 1: **Comparison of existing Arabic calligraphy datasets.** Existing resources typically focus on isolated aspects such as limited style coverage, word- or sentence-level annotations, or constrained availability. In contrast, DuwatBench uniquely integrates multiple underrepresented dimensions like script diversity, word- and sentence-level transcriptions, bounding boxes for detection, and complex artistic backgrounds, while ensuring public accessibility. Allaf (Allaf and Al-Hmouz, 2016), Adam (Adam et al., 2017), Sal&King (Salamah and King, 2018), Kaoudja (Kaoudja, 2022), Calliar (Alyafeai et al., 2022), MOJ-DB(Zoizou et al., 2022), HICMA (Ismail et al., 2023).

guages; Arabic-specific CLIP adaptations such as AraCLIP (Al-Barham et al., 2024) report clear gains on Arabic image–text benchmarks; and recent Arabic OCR and VLM systems (Bhatia et al., 2024; Wasfy et al., 2025; Heakl et al., 2025) show improved handling of diacritics and high-resolution text. However, none of these models have been evaluated on stylized Arabic calligraphy with complex artistic backgrounds and diverse style rules. A benchmark centered on calligraphy can thus reveal whether these systems can generalize to culturally grounded, visually demanding Arabic text or still rely on surface-level cues.

We introduce DuwatBench, a 1K-sample benchmark for Arabic calligraphy designed to evaluate LMMs under realistic conditions. The dataset encompasses over 1,400 unique words drawn from both religious and cultural domains, including Quranic verses, devotional phrases, greetings, and poetic or proverbial expressions. It features 6 major calligraphic styles: Thuluth, Diwani, Naskh, Kufic, Nasta'liq, and the more modern Ruq'ah, capturing the visual diversity of Arabic writing across historical and contemporary contexts (see Figure 1). Each image is paired with transcriptions and detection-level annotations, enabling both recognition and localization analysis.

Unlike existing datasets that primarily target OCR-like tasks (Table 1), DuwatBench integrates real-world calligraphy with complex backgrounds, multiple scripts, full transcriptions, and bounding-box annotations. Arabic calligraphy sits at the edge of visual–textual alignment: while meaning is preserved, artistic strokes, ligatures, and curved layouts often distort the patterns leveraged by models trained on clean Latin text. Evaluating multimodal models on DuwatBench therefore provides a rigorous test of whether Arabic or multilingual pretraining transfers to artistic calligraphy, distinguishing genuine understanding from pattern memorization.

Our contributions are threefold: (1) we release a curated benchmark of 1K samples spanning 6 calligraphic styles and 1,400 words, enriched with transcriptions and artistic contexts; (2) we introduce detection-level annotations for word localization, complementing prior classification- and OCR-based datasets; and (3)) we establish systematic baselines on state-of-the-art Arabic and multilingual LMMs, revealing consistent failure cases such as style misinterpretation, sensitivity to diacritics and hamzas, curved text alignment, and interference from background clutter.

DuwatBench bridges Arabic visual heritage and modern AI, enabling inclusive evaluation, style-aware modeling, and applications in preservation, education, and cultural search.

2 DuwatBench: The Arabic Calligraphy Dataset

2.1 Dataset Taxonomy

Our dataset corpus is structured along two main dimensions: textual categories and calligraphic styles. On the content side, the largest portion consists of non-religious expressions, such as greetings, motifs, and cultural quotes common in decorative and public settings. Religious material is also prominent, including Quranic verses, devotional invocations, and the Names of Allah, complemented by references to the Prophets and companions, as well as smaller portions of personal dedications and hadith (see Figure 6). This balance ensures fair representation of both spiritual and cultural expressions in the dataset.

Figure 2: **Examples of DuwatBench Calligraphic Styles.** Representative samples from the six calligraphic styles in DuwatBench: Thuluth, Diwani, Kufic, Ruq'ah, Naskh, and Nasta'liq. Each entry displays the artwork with bounding-box annotations, transcription, and metadata such as style, text content, theme, and word count. These examples highlight the dataset's diversity in structure, composition, and artistic context, spanning both religious and non-religious inscriptions.

In terms of visual representation, the dataset covers 6 major calligraphic styles (Thulth, Diwani, Kufic, Nash, Ruqu'a, and Nasta'liq) with varying frequencies (Figure 7). Further detailed statistical breakdown is provided in Appendix C.

2.2 Data Collection and Candidate Selection

As shown in Figure 3, the pipeline starts by sourcing candidate images from digital archives [1,2] and community repositories [3,4]. These candidates are screened for resolution, completeness, and the presence of authentic artistic backgrounds. Low-quality, blurred, or incomplete inscriptions are discarded at this stage, ensuring that only visually reliable samples move forward. We began with more than 2,700 samples, and after initial filtering and duplicate removal, the dataset was reduced to 1,089 high-quality instances, representing an overall reduction of approximately 60%.

[1] https://www.loc.gov/collections/
[2] https://digitalcollections.nypl.org/
[3] https://calligraphyqalam.com/
[4] https://freeislamiccalligraphy.com/

2.3 Filtering, Transcription, & Normalization

Manual Transcription and Spatial Annotation. The retained samples are transcribed by 3 volunteering native Arabic speakers, who also generate bounding boxes to capture the spatial alignment between words, characters, and stylistic forms. Since textual content varies across images, a single image may include multiple bounding boxes corresponding to distinct textual segments. Each sample is annotated with its transcription and style label, establishing a foundation for multimodal alignment between calligraphic form and semantic meaning as shown in Figure 4. To ensure annotation consistency, detailed guidelines were provided to annotators in advance (see Table 5 in Appendix D).

Normalization and De-duplication. Then, samples undergo denoising and normalization to unify diacritics, letter variants like alef, hamza, ta'a marbouta, and encoding conventions to ensure that the corpus is both clean and standardized without compromising stylistic richness.

Figure 3: **Data collection and verification pipeline for DuwatBench.** The process begins with sourcing candidate images from digital archives and community repositories, followed by quality-based selection and manual transcription by native Arabic speakers. Each sample is denoised, normalized, and assigned bounding boxes with text–style and theme annotations. A multi-tier validation stage involving quality control, stylistic checks, and expert review ensures both textual accuracy and calligraphic fidelity. Final samples are classified and aggregated by style and thematic category, forming the curated DuwatBench corpus.

2.4 Multi-tier Verification

Quality assurance was conducted through a two-tier validation framework. Tier 1 addressed objective checks such as resolution, completeness, and artifact detection, while Tier 2 involved a calligraphy expert who verified transcription accuracy, diacritic integrity, and style and theme classification. After this process, the dataset was finalized with 1,050 high-quality samples. This layered approach combined systematic review with expert validation to ensure reliability and consistency of the annotations. More details on filtering criteria, verification steps, and annotation guidelines are provided in Appendix D.

Figure 4: **Annotation Workflow in DuwatBench.** The figure illustrates the end-to-end annotation process followed in DuwatBench—from visual quality screening and bounding-box drawing to transcription, style labeling, and word-count generation. Each stage ensures completeness, legibility, and consistent metadata alignment between text and visual form, supporting accurate multimodal evaluation.

2.5 Classification and aggregation

Finally, validated samples are classified by script type and thematic category before being aggregated into the final benchmark. Metadata, including transcription, bounding-box coordinates, word count by box, total word count per image, and style annotations, is attached to produce the structured DuwatBench corpus. This integrated process ensures that the dataset captures both visual diversity and semantic richness, making it a robust resource for multimodal learning. Additional examples from DuwatBench are shown in Figure 2, illustrating the dataset's annotation structure where each image is paired with its metadata (style, transcription, word count, and bounding boxes), highlighting the integration of visual and textual information for multimodal evaluation.

3 Benchmark Evaluation

3.1 Evaluation Metric

We assess model performance with 5 complementary metrics: character error rate (CER), word error rate (WER), character F-score (chrF), ExactMatch, and normalized Levenshtein distance (NLD). CER captures the minimum number of character edits required to match the reference and is particularly important for Arabic calligraphy, where diacritics and ligatures can alter meaning. WER evaluates accuracy at the word level, offering a more interpretable measure for end-users. chrF computes character n-gram F-scores, rewarding partial overlaps and providing robustness to tokenization errors and spelling variants common in stylized text. ExactMatch is the strictest metric, counting only perfect matches between prediction and reference. Finally, NLD normalizes edit distance by sequence length, situating itself between CER and WER in

	Models	CER_mean ↓	WER_mean ↓	chrF↑	ExactMatch ↑	NLD_error↓
Open-source	Llava-v1.6-mistral-7b-hf (Liu et al., 2023)	1.0959	1.7872	0.4810	0.0055	0.9107
	EasyOCR (Kittinaradorn et al., 2024)	0.7857	1.0213	7.7420	0.0189	0.7664
	InternVL3-8B (Chen et al., 2024)	0.7461	0.8781	10.3251	0.1189	0.6692
	Qwen2.5-VL-7B (Team, 2025)	0.6499	0.8080	19.1702	0.2069	0.6667
	Qwen2.5-VL-72B-Instruct(Team, 2025)	0.6969	0.8587	29.2649	0.2432	0.5352
	Gemma-3-27B-IT (Team et al., 2025)	0.6374	0.7683	38.8290	0.3240	0.4185
	trocr-base-arabic-handwritten* (Microsoft, 2022)	1.0343	1.0440	0.7578	0.0000	0.9689
	MBZUAI/AIN* (Heakl et al., 2025)	0.6688	0.8192	22.0817	0.2265	0.4993
Closed-source	claude-sonnet-4.5 (Anthropic, 2025)	1.1806	1.0795	27.6271	0.3382	0.4292
	gemini-1.5-flash (Reid et al., 2024)	0.9117	1.0258	41.9275	0.2435	0.4971
	gemini-2.5-flash (AI, 2025)	0.3160	0.4164	59.9590	0.5605	0.2170
	gpt-4o-mini (OpenAI, 2024)	0.5330	0.6826	27.7021	0.3548	0.4029
	gpt-4o (OpenAI, 2024)	0.8296	0.9797	17.1246	0.1862	0.6205

Table 2: **Model Performance on DuwatBench.** Performance of open and closed-source models is reported using five complementary metrics: CER, WER, chrF, ExactMatch, and NLD. Results highlight clear differences across models, with larger multimodal models (gemini-2.5-flash and Gemma-3-27B-IT) showing stronger robustness, while others continue to face challenges on highly stylized calligraphic text. *Note:* * indicates Arabic-specific models. Values in blue denote the best performance, while underlined values indicate the second-best within each category (open or closed-source).

granularity and offering a balanced perspective on recognition errors across variable word sizes.

To ensure fair comparison, we apply an Arabic-aware normalization pipeline before scoring. This includes Unicode normalization, removal of tatweel (ـ), and unification of character variants such as Alef forms (ا آ إ أ) and Alef Maqsurah (ى → ي). Such preprocessing follows standard practice in Arabic NLP tools (e.g., CAMeL Tools, Lucene Arabic normalizer) and avoids penalizing models for superficial script variants.

3.2 Evaluation Settings

All metrics were computed using standard open-source implementations to ensure reproducibility and consistency. The *editdistance* and *Levenshtein* libraries were used for computing character- and word-level edit operations (CER, WER, NLD), while *sacrebleu* was employed for calculating chrF scores following machine translation evaluation standards. This setup provides a transparent and reproducible evaluation pipeline across all models.

Together, these metrics provide a balanced evaluation framework in which CER and WER capture fine-grained recognition errors, NLD quantifies normalized string similarity, chrF measures partial correctness in visually distorted forms, and ExactMatch highlights full-sequence accuracy.

4 Results, Analysis, and Error Analysis

4.1 Quantitative Results

Table 2 presents the performance of open and closed-source models evaluated directly on full cal-

ligraphy images. The results reveal clear performance gaps, reflecting the models' varying capacity to interpret the artistic and structural complexity of Arabic calligraphy.

Among open-source systems, gemma-3-27B-it achieved the best overall performance, recording the lowest CER (0.64) and WER (0.77) and the highest chrF (38.83) and ExactMatch (0.32) within this group. Followed by MBZUAI/AIN and Qwen2.5-VL-7B, with balanced results across all metrics, indicating their stronger adaptation to the Arabic script. In contrast, traditional OCR baselines such as EasyOCR and trocr-base-arabic-handwritten performed poorly, struggling with the ornate ligatures and curved baselines typical of calligraphy. Similarly, general-purpose LMMs such as LLaVA-v1.6-Mistral-7B underperformed, suggesting that instruction tuning without explicit Arabic grounding is insufficient for stylized text recognition.

Among closed-source systems, Gemini-2.5-Flash achieved the strongest performance overall, with the best chrF (59.9), highest ExactMatch (0.56), and an NLD error of (0.22) outperforming both open and closed-source baselines. GPT-4o-mini also showed consistent robustness, outperforming GPT-4o across most metrics, while Claude-Sonnet-4.5 and Gemini-1.5-Flash achieved moderate results.

Overall, these findings confirm that large, instruction-optimized multimodal models, particu-

	Models	CER_mean ↓	WER_mean ↓	chrF↑	ExactMatch ↑	NLD_error↓
Open-source	Llava-v1.6-mistral-7b-hf (Liu et al., 2023)	1.0378	1.7518	0.5083	0.0058	0.8687
	EasyOCR (Kittinaradorn et al., 2024)	0.7851	0.9984	7.8279	0.0198	0.7609
	InternVL3-8B-Instruct (Chen et al., 2024)	0.7336	0.8623	10.9291	0.1267	0.6688
	Qwen2.5-VL-7B-Instruct (Team, 2025)	0.6218	0.7875	19.7564	0.2274	0.6538
	Qwen2.5-VL-72B-Instruct (Team, 2025)	0.6567	0.8391	34.0831	0.2884	0.4565
	Gemma-3-27B-IT (Team et al., 2025)	0.6253	0.7475	39.2142	0.3357	0.4209
	trocr-base-arabic-handwritten* (Microsoft, 2022)	1.0024	1.0221	1.9127	0.0000	0.9693
	MBZUAI/AIN* (Heakl et al., 2025)	0.6537	0.8034	22.9512	0.2296	0.4814
Closed-source	claude-sonnet-4.5 (Anthropic, 2025)	0.9212	0.8793	30.0617	0.3693	0.4036
	gemini-1.5-flash (Reid et al., 2024)	0.8806	0.9987	43.4928	0.2591	0.4817
	gemini-2.5-flash (AI, 2025)	0.2998	0.4027	61.2629	0.5721	0.2059
	gpt-4o-mini (OpenAI, 2024)	0.5194	0.6718	29.8237	0.3628	0.3816
	gpt-4o (OpenAI, 2024)	0.7992	0.9423	22.8368	0.2806	0.5990

Table 3: **Model Performance on DuwatBench with Bounding Boxes.** The table reports CER, WER, chrF, ExactMatch, and NLD for open- and closed-source models evaluated on DuwatBench using bounding-box annotations. gemini-2.5-flash maintains the best overall performance across metrics, while within open-source models, Qwen2.5-VL-7B achieves the lowest CER, outperforming Gemma-3-27B-IT. *Note:* * indicates Arabic-specific models. Values in blue denote the best performance, while underlined values indicate the second-best within each category (open or closed-source).

	Models	Kufic	Thuluth	Diwani	Naskh	Ruq'ah	Nasta'liq
Open-source	Llava-v1.6-mistral-7b-hf (Liu et al., 2023)	2.0500	1.6344	2.1390	1.6882	2.5000	2.1333
	EasyOCR (Kittinaradorn et al., 2024)	0.9998	1.0171	1.1126	0.6453	0.3718	1.0000
	InternVL3-8B (Chen et al., 2024)	1.0361	0.8519	0.9053	0.8590	0.8846	1.3700
	Qwen2.5-VL-7B (Team, 2025)	0.7706	0.8044	0.8611	0.4227	0.4333	1.0000
	Qwen2.5-VL-72B-Instruct (Team, 2025)	0.6840	0.8924	0.8680	0.1815	0.2593	0.8750
	Gemma-3-27B-IT (Team et al., 2025)	0.4873	0.7723	0.8128	0.2550	0.1944	0.8250
	trocr-base-arabic-handwritten* (Microsoft, 2022)	1.0606	1.0468	1.0296	1.0000	1.2000	1.0000
	MBZUAI/AIN* (Heakl et al., 2025)	0.8555	0.8005	0.9318	0.2054	0.0556	1.2333
Closed-source	claude-sonnet-4.5 (Anthropic, 2025)	1.0480	0.9099	2.0503	0.1398	0.1282	0.9944
	gemini-1.5-flash (Reid et al., 2024)	1.2990	1.0335	1.0181	0.1962	0.2564	1.1417
	gemini-2.5-flash (AI, 2025)	0.4399	0.3722	0.4730	0.1080	0.4333	2.6917
	gpt-4o-mini (OpenAI, 2024)	0.5696	0.6376	0.9004	0.1250	0.1944	0.8361
	gpt-4o (OpenAI, 2024)	1.1203	0.9046	1.2233	0.5058	0.1795	0.7667

Table 4: **WER Mean across Arabic calligraphy styles on DuwatBench.** WER scores are reported per script style (Kufic, Thuluth, Diwani, Naskh, Ruq'ah, Nasta'liq) for open and closed-source models. Lower values indicate better recognition accuracy. *Note:* * indicates Arabic-specific models. Values in blue denote the best performance, while underlined values indicate the second-best within each category (open or closed-source).

larly Gemini-2.5-Flash and Gemma-3-27B-IT, are more resilient to the structural irregularities and stylistic diversity of Arabic calligraphy than conventional OCR tools or smaller open models. This highlights the importance of large-scale multilingual pretraining and cross-modal grounding for robust Arabic visual text understanding.

Table 4 further reports the WER across the six DuwatBench calligraphic styles. The models perform best in Naskh and Ruq'ah, where the strokes are standardized and the geometric distortions are minimal. By contrast, ornate scripts such as Diwani and Thuluth remain challenging due to dense ligatures and fluid baselines. Nasta'liq exhibits high variance; some models achieve near-perfect accuracy, while others fail, suggesting limited represen-

tation in pretraining corpora. Among open-source systems, Gemma-3-27B-IT and Qwen2.5-VL-72B-Instruct achieve the most consistent cross-style results, while MBZUAI/AIN records the lowest error for Ruq'ah, indicating familiarity with modern Arabic handwriting. In the closed-source group, gemini-2.5-Flash and GPT-4o-mini lead overall, maintaining stability across nearly all styles. (More results in Table 6 in Appendix E).

These results reveal that model accuracy correlates strongly with style prevalence in pretraining data. Naskh and Ruq'ah dominant in modern Arabic documents yield the highest recognition rates, whereas historical styles like Kufic and Diwani remain the most error-prone. While bounding-box cropping mitigates background interference, cross-style imbalance persists, emphasizing the need for targeted

Model											
Image	[Diwani img]	[Diwani img]	[Diwani img]	[Diwani img]	[Thuluth img]	[Thuluth img]	[Thuluth img]	[Kufic img]	[Naskh img]	[Ruq'ah img]	[Nasta'liq img]
Style	Diwani	Diwani	Diwani	Diwani	Thuluth	Thuluth	Thuluth	Kufic	Naskh	Ruq'ah	Nasta'liq
Ground Truth	ما شاء الله	الرحيم	بسم الله	الحمد لله رب العالمين	بسم الله الرحمن الرحيم	فتوكل على الله	عائشة	فاصبر صبرا جميلا	يا الله	أستغفرالله	خنده
Open-source											
llava-v1.6-mistral-7b-hf	،،،،ٓ،،	،،٠،،	،،،،	،،،،	،،،،	،،،	،،،،	،،،،،	»»»«،،٠،،،ٓ،،	الله	،،،،
InternVL3-8B	الله	الله	الله	الله	الله أعلم	الله سميع بصير	الله	الله	الله	استغفرالله	دل ز
EasyOCR	ثمام | ـ | م | ر، ر	٧ | د			رلله‌الحككن احمم | نمر	فتكا كجللد	شة	}	يا الل | ٥ط | ظة ٥	الله | ستغفر	٥ | حلل
Qwen2.5-VL-7B	الله يحميك	الله أكبر	الله	الله	بسمة مريم بنت سليمان بن عقاص	فتوكة على الله	شاء	الجنة	يا الله	أَسْتَغْفِرُاللَّه	خنده
Qwen2.5-VL-72B	الله	السلام عليكم	الله	الله	الله لا إله إلا	فتوك الله	الله	الله لا إله إلا	يَا الله	أستغفرالله	خنده
gemma-3-27b-it	الله محمد	بسم الله الرحمن الرحيم	بسم الله الرحمن الرحيم	يا حي يا قيوم	بسم الله الرحمن الرحيم	فتوكل على الله	شهبة	يا عليُّ يا عظيمُ	يَا اللَّهُ	أستغفرالله	خنده
trocr-base-arabic-handwritten	.	لخر	.	درا | ط نا | ء بث نس	عندنانانا شيخ جاري الخيمة	.	.	.	.	في	.
MBZUAI/AIN	بسم الله	اللهم صل على محمد	بسم الله	الله هو أرحمهم	بسم الله الرحمن الرحيم	فتوكّا على الله	غَسَان	الله هوالاكبر	يا الله	أستغفرالله	خنوه
Closed-source											
claude-sonnet-4.5	ماشاء الله	أريحوا قلوبكم	بسم الله	الإبداع	بسم الله الرحمن الرحيم	فتوكل على الله	عائشة	طاب مساؤك	يا الله	استغفر الله	حنيد
gemini-1.5-flash	اللهُ شَهيدٌ	بسم الله الرحمن الرحيم	بسم الله الرحمن الرحيم	بسم الله الرحمن الرحيم	في جَناح الله	شاشة	بسم الله الرحمن الرحيم	يا الله	أستغفر الله	خالد	
gemini-2.5-flash	ما شاء الله	الرحمن الرحيم | كلثوم	بسم الله	الرحمن الرحيم	بسم الله الرحمن الرحيم	فَتَوَكَّلْ عَلَى اللَّهِ	عائشة	إِنَّا لِلَّهِ وَإِنَّا إِلَيْهِ رَاجِعُونَ	يا الله	أستغفر الله	خنده
gpt-4o-mini	ما شاء الله	الحمد لله	بسم الله	مبارك عليكم	بسم الله الرحمن الرحيم	فَوَكَّتُ عَلَى الله	ثلاثة	لا إله إلا الله	يَا الله	أستغفر الله	جذْءُ
gpt-4o	بسم الله	آسف | لا أستطيع المساعدة في ذلك	البسملة	أنا لا أستطيع تمييز النصوص داخل الصور | لكن إذا كنت بحاجة للمساعدة في أي شيء آخر | ساكون سعيدًا بمساعدتك	فَتَوَكَّلْ عَلَى اللَّهِ	آسف | لا أستطيع نسخ النص من الصورة	أنا آسف | لا أستطيع مساعدتك في ذلك	آمَنُوا	آسف | لا أستطيع المساعدة في ذلك	أستغفر الله	لديك

Figure 5: **Qualitative Comparison of Model Outputs Across Calligraphic Styles** Examples from DuwatBench showing transcription quality across six calligraphic styles, evaluated using 13 open and closed-source OCR and vision-language models. Each column presents the model's predicted text aligned with the ground truth. The figure highlights challenges such as stroke density, curved baselines, and complex letter connections that complicate recognition, particularly in Thuluth, Diwani, and Kufic scripts. *Note:* Cells highlighted in green indicate correct predictions where diacritic variations are ignored; inaccurate or misplaced hamza marks are considered errors.

data augmentation and style-aware pretraining.

To examine the impact of localization, we conducted ablation experiments where models were evaluated providing the bounding boxes information for calligraphic regions. This setting consistently improved performance across most systems. In the open-source group, Qwen2.5-VL-72B-Instruct and Gemma-3-27B-IT showed clear gains in chrF and ExactMatch, demonstrating the benefit of focused visual input. Among closed-source systems, gemini-2.5-flash and gpt-4o-mini exhibited the strongest robustness, achieving lower CER/WER and higher overall alignment accuracy. Arabic-specific models such as MBZUAI/AIN also improved with bounding boxes, confirming the advantage of domain-aware pretraining for stylized Arabic scripts. In contrast, traditional OCR-based models (EasyOCR, TrOCR) remained weak, underscoring their limited capacity to generalize beyond printed or cursive text.

Overall, incorporating bounding-box localization led to consistent performance gains across most models, particularly enhancing recognition accuracy and alignment in visually complex calligraphic text. However, efforts in this direction require further attention to fully address the challenges posed by Arabic calligraphy.

4.2 Error Analysis

Quantitative Error Analysis. Table 2 summarizes model performance across five complementary metrics. Correlation analysis (refer to Figure 9 in Appendix F) reveals strong relationships between character- and word-level errors ($\rho_{CER,WER} = 0.82$) and a strong inverse correlation between edit distance and semantic overlap (NLD–chrF = –0.92, NLD–ExactMatch = –0.96), confirming that lexical deviations align with loss of visual and semantic fidelity. Closed-source models outperform open ones, particularly in normalized edit distance ($p = 0.0266$) and exact-match accuracy ($p = 0.038$), yet all systems exhibit difficulty with complex scripts and long inscriptions (See Table 7 in Appendix F). Quantitatively, performance deteriorates as word count and stylistic curvature increase—especially in Thuluth and Diwani samples where ligatures, flourishes, and overlapping baselines amplify recognition errors. Models perform more reliably on short phrases or Naskh and Ruq'ah texts, where structure is linear and spacing consistent. Average ExactMatch remains below 0.23 across the dataset, reflecting that even the strongest systems fail to transcribe calligraphy faithfully under artistic distortion. These trends align with the qualitative findings (see Figure 5): quantitative degradation corresponds closely to stylistic and visual complexity inherent to Duwat-Bench.

Significance testing between model groups further shows that closed-source systems outperform open ones in normalized edit distance ($p = 0.0266$) and exact-match accuracy ($p = 0.038$), though both struggle with the high stylistic variation inherent to Arabic calligraphy. On average, ExactMatch remains below 0.23 across all models, underscoring the persistent challenge of recognizing visually complex calligraphic forms even for advanced multimodal LLMs. These analyses validate the metric suite and provide a quantitative basis for evaluating cross-model performance differences.

Qualitative Error Analysis. Figure 5 visualizes representative outputs across six calligraphic styles, highlighting correct predictions in green. The results show substantial variation between models and styles. Among open-source systems, LLaVA-v1.6-Mistral-7B often produces incoherent Arabic, InternVL3-8B tends to overgenerate generic tokens like "الله", and EasyOCR exhibits fragmented outputs. Gemma-3-27B-IT achieves the most stable open-source performance, while Qwen2.5-VL variants perform best on simpler scripts like Naskh and Ruq'ah. MBZUAI/AIN performs competitively for its smaller scale, notably producing a correct Diwani recognition case—an area where most other open-source models fail.

In the closed-source category, claude-sonnet-4.5 and gemini-2.5-flash produce the most reliable transcriptions across Diwani and Thuluth, while GPT-4o-mini remains consistent, albeit slightly weaker, on Thuluth. GPT-4o frequently rejects inputs, reflecting stricter safety filtering.

Certain qualitative patterns also emerge. Models occasionally generate semantically plausible but visually mismatched outputs, for example, Gemma-3-27B-IT correctly recognized "بسم الله" but expanded it to the full Basmala "بسم الله الرحمن الرحيم", indicating cultural priors influencing prediction. Across models, a tendency to overpredict "الله" reflects strong cultural associations learned during training. Meanwhile, styles like Kufic and Diwani, which are geometrically rigid or ornate, remain the hardest to decode, while Naskh, Ruq'ah, and Nasta'liq achieve the highest recognition stability.

Overall, these findings highlight both linguistic and cultural biases in Arabic multimodal models and show that visual-textual grounding (rather than model size alone) is key to advancing calligraphy understanding.

5 Conclusion

In this work, we introduce DuwatBench, a benchmark for Arabic calligraphy comprising over 1K curated samples spanning various text categories and calligraphic styles. The dataset combines full transcriptions, style annotations, and detection-level information with authentic artistic backgrounds, offering a realistic testbed for Arabic LMMs. Our evaluation shows that, while existing systems handle standard text, they struggle with the stylistic variation and visual complexity of calligraphy. The benchmark highlights these limitations and encourages future research on script-aware modeling and culturally grounded AI, with applications in cultural preservation, education, and digital humanities.

6 Limitations and Societal Impact

Our proposed benchmark is designed as a focused and high-quality resource for evaluating Arabic calligraphy in multimodal models. Although the scale of the data set is smaller than that of large general-purpose Arabic corpora, it emphasizes diversity between text categories and calligraphic styles and ensures meaningful evaluation scenarios. Beyond technical contributions, the dataset highlights the cultural and artistic significance of Arabic calligraphy and supports research in areas such as cultural heritage preservation, digital archiving, and education. With this release, we aim to promote responsible and inclusive research practices that respect the cultural significance of the Arabic script while advancing the development of robust multimodal systems.

References

Kalthoum Adam, Somaya Al-Maadeed, and Ahmed Bouridane. 2017. based classification of arabic scripts style in ancient arabic manuscripts: Preliminary results. In *2017 1st international workshop on arabic script analysis and recognition (ASAR)*, pages 95–98. IEEE.

Google AI. 2025. Gemini 2.5 flash. Large language model (Preview), accessed May 20, 2025.

Muhammad Al-Barham, Imad Afyouni, Khalid Almubarak, Ashraf Elnagar, Ayad Turky, and Ibrahim Hashem. 2024. Araclip: Cross-lingual learning for effective arabic image retrieval. In *Proceedings of The Second Arabic Natural Language Processing Conference*, pages 102–110.

AbdulMalik Al-Salman and Haifa Alyahya. 2017. Arabic online handwriting recognition: a survey. In *proceedings of the 1st international conference on internet of things and machine learning*, pages 1–4.

Wafa Alghallabi, Ritesh Thawkar, Sara Ghaboura, Ketan More, Omkar Thawakar, Hisham Cholakkal, Salman Khan, and Rao Muhammad Anwer. 2025. Fann or flop: A multigenre, multiera benchmark for arabic poetry understanding in llms. *arXiv preprint arXiv:2505.18152*.

Siraj Reda Allaf and R Al-Hmouz. 2016. Automatic recognition of artistic arabic calligraphy types. *Journal of King Abdulaziz University*, 27(1):3–17.

Fakhraddin Alwajih, Gagan Bhatia, and Muhammad Abdul-Mageed. 2024. Dallah: A dialect-aware multimodal large language model for arabic. *arXiv preprint arXiv:2407.18129*.

Fakhraddin Alwajih, Samar Mohamed Magdy, Abdellah El Mekki, Omer Nacar, Youssef Nafea, Safaa Taher Abdelfadil, Abdulfattah Mohammed Yahya, Hamzah Luqman, Nada Almarwani, Samah Aloufi, et al. 2025a.

Pearl: A multimodal culturally-aware arabic instruction dataset. *arXiv preprint arXiv:2505.21979*.

Fakhraddin Alwajih, Abdellah El Mekki, Hamdy Mubarak, Majd Hawasly, Abubakr Mohamed, and Muhammad Abdul-Mageed. 2025b. Palmx 2025: The first shared task on benchmarking llms on arabic and islamic culture. *arXiv preprint arXiv:2509.02550*.

Zaid Alyafeai, Maged S Al-shaibani, Mustafa Ghaleb, and Yousif Ahmed Al-Wajih. 2022. Calliar: an online handwritten dataset for arabic calligraphy. *Neural Computing and Applications*, 34(23):20701–20713.

Anthropic. 2025. Claude-sonnet 4.5. https://www.anthropic.com. Large language model.

Farah Atif, Nursultan Askarbekuly, Kareem Darwish, and Monojit Choudhury. 2025. Sacred or synthetic? evaluating llm reliability and abstention for religious questions. *arXiv preprint arXiv:2508.08287*.

Gagan Bhatia, El Moatez Billah Nagoudi, Fakhraddin Alwajih, and Muhammad Abdul-Mageed. 2024. Qalam: A multimodal llm for arabic optical character and handwriting recognition. *arXiv preprint arXiv:2407.13559*.

Guanhua Chen, Lu Hou, Yun Chen, Wenliang Dai, Lifeng Shang, Xin Jiang, Qun Liu, Jia Pan, and Wenping Wang. 2023. mclip: Multilingual clip via cross-lingual transfer. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 13028–13043.

Zhe Chen, Jiannan Wu, Wenhai Wang, Weijie Su, Guo Chen, Sen Xing, Muyan Zhong, Qinglong Zhang, Xizhou Zhu, Lewei Lu, et al. 2024. Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 24185–24198.

Mohamed Ezz, Mohamed A Sharaf, and Al-Amira A Hassan. 2019. Classification of arabic writing styles in ancient arabic manuscripts. *International Journal of Advanced Computer Science and Applications*, 10(10).

Gregor Geigle, Abhay Jain, Radu Timofte, and Goran Glavaš. 2023. mblip: Efficient bootstrapping of multilingual vision-llms. *arXiv preprint arXiv:2307.06930*.

Sara Ghaboura, Ahmed Heakl, Omkar Thawakar, Ali Husain Salem Abdulla Alharthi, Ines Riahi, Abduljalil Saif, Jorma Laaksonen, Fahad Shahbaz Khan, Salman H Khan, and Rao Muhammad Anwer. 2025a. Camel-bench: A comprehensive arabic lmm benchmark. *NAACL*.

Sara Ghaboura, Ketan More, Wafa Alghallabi, Omkar Thawakar, Jorma Laaksonen, Hisham Cholakkal, Salman Khan, and Rao Muhammad Anwer. 2025b. Arb: A comprehensive arabic multimodal reasoning benchmark. *arXiv preprint arXiv:2505.17021*.

Ahmed Heakl, Sara Ghaboura, Omkar Thawkar, Fahad Shahbaz Khan, Hisham Cholakkal, Rao Muhammad Anwer, and Salman Khan. 2025. Ain: The arabic inclusive large multimodal model.

Anis Ismail, Zena Kamel, and Reem Mahmoud. 2023. Hicma: the handwriting identification for calligraphy and manuscripts in arabic dataset. In *Proceedings of ArabicNLP 2023*, pages 24–32.

Karima Kadaoui, Hanin Atwany, Hamdan Al-Ali, Abdelrahman Mohamed, Ali Mekky, Sergei Tilga, Natalia Fedorova, Ekaterina Artemova, Hanan Aldarmaki, and Yova Kementchedjhieva. 2025. Jeem: Vision-language understanding in four arabic dialects. *Preprint*, arXiv:2503.21910.

Zineb Kaoudja. 2022. *Arabic calligraphy style identification*. Ph.D. thesis, University of Kasdi Merbah Ouargla.

Zineb Kaoudja, Belal Khaldi, and Mohammed Lamine Kherfi. 2020. Arabic artistic script style identification using texture descriptors. In *2020 1st International Conference on Communications, Control Systems and Signal Processing (CCSSP)*, pages 113–118. IEEE.

Zineb Kaoudja, Mohammed Lamine Kherfi, and Belal Khaldi. 2021. A new computational method for arabic calligraphy style representation and classification. *Applied Sciences*, 11(11):4852.

Rakpong Kittinaradorn, Jaided AI Team, Wisuttida Wichitwong, Chan Kim, Danial Zakaria, Sumitkumar Sarda, Jeff Potter, Sam_S, Dakota Horstman, Ronald, Vijayabhaskar, Nina, Mijoo Kim Mun, Dae-Jeong and, Amit Agarwal, Mejans, Vladimir Gurevich, Márton Tim, Tsogt Otgonbaatar, dependabot[bot], Karol Kucza, Loay, Korakot Chaovavanich, A2va, Abderrahim Mama, Vifly, TheDetective, Pray S, kfjt, and Wannaphong Phatthiyaphaibun. 2024. Jaidedai/Easy-OCR. https://github.com/JaidedAI/EasyOCR.

Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. 2023. Improved baselines with visual instruction tuning. *Preprint*, arXiv:2310.03744.

Liana M Lorigo and Venugopal Govindaraju. 2006. Offline arabic handwriting recognition: a survey. *IEEE transactions on pattern analysis and machine intelligence*, 28(5):712–724.

Microsoft. 2022. Trocr-base-arabic-handwritten. https://huggingface.co/microsoft/trocr-base-arabic-handwritten. Transformer-based OCR model for Arabic handwritten text.

OpenAI. 2024. Gpt-4o mini: advancing cost-efficient intelligence.

OpenAI. 2024. Gpt-4o system card. *Preprint*, arXiv:2410.21276.

Machel Reid, Nikolay Savinov, Denis Teplyashin, Dmitry Lepikhin, Timothy Lillicrap, Jean baptiste Alayrac, Radu Soricut, Angeliki Lazaridou, Orhan Firat, Julian Schrittwieser, and et al. 2024. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context. *Preprint*, arXiv:2403.05530.

Mehreen Saeed, Adrian Chan, Anupam Mijar, Gerges Habchi, Carlos Younes, Chau-Wai Wong, Akram

Khater, et al. 2024. Muharaf: Manuscripts of handwritten arabic dataset for cursive text recognition. *Advances in Neural Information Processing Systems*, 37:58525–58538.

Seetah AL Salamah and Ross King. 2018. Towards the machine reading of arabic calligraphy: a letters dataset and corresponding corpus of text. In *2018 IEEE 2nd international workshop on arabic and derived script analysis and recognition (ASAR)*, pages 19–23. IEEE.

Afnan Sumayli and Mohamed Alkaoud. Handwritten arabic calligraphy generation: A systematic literature review.

Gemma Team, Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, Sarah Perrin, Tatiana Matejovicova, Alexandre Ramé, Morgane Rivière, et al. 2025. Gemma 3 technical report. *arXiv preprint arXiv:2503.19786*.

Qwen Team. 2025. Qwen2.5-vl.

Ahmed Wasfy, Omer Nacar, Abdelakreem Elkhateb, Mahmoud Reda, Omar Elshehy, Adel Ammar, and Wadii Boulila. 2025. Qari-ocr: High-fidelity arabic text recognition through multimodal large language model adaptation. *arXiv preprint arXiv:2506.02295*.

Abdelhay Zoizou, Arsalane Zarghili, and Ilham Chaker. 2022. Moj-db: A new database of arabic historical handwriting and a novel approach for subwords extraction. *Pattern Recognition Letters*, 159:54–60.

A Appendix

This appendix provides supplementary material for our study of Arabic calligraphy understanding in multimodal models. It includes: (1) an overview of related work situating DuwatBench within existing resources; (2) detailed dataset statistics; (3) verification and validation guidelines used by annotators and experts; (4) additional evaluation results; and (5) supplementary statistical analysis highlighting the dataset's stylistic and cultural diversity. Together, these materials emphasize DuwatBench's role in bridging linguistic meaning with visual heritage and providing a solid foundation for model evaluation.

B Related Work

Research on Arabic calligraphy intersects with Natural Language Processing (NLP), multimodal learning, and cultural heritage. Although prior work has produced valuable benchmarks and datasets, most focus on clean text, structured documents, or narrow stylistic slices, leaving the artistic and cultural complexity of calligraphy largely unaddressed. We group related work into three areas: (i) Arabic multimodal benchmarks, (ii) heritage and cultural resources, and (iii) Arabic calligraphy datasets.

B.1 Arabic Multimodal Benchmarks

Arabic multimodal benchmarks have evolved from general-purpose evaluation suites to more specialized resources. CAMEL-Bench established a large-scale benchmark covering eight domains with over 29K native-curated questions (Ghaboura et al., 2025a). Dialectal variation was later emphasized through resources such as Dallah (Alwajih et al., 2024) and JEEM (Kadaoui et al., 2025), underscoring the importance of capturing linguistic diversity across the Arab world. Building on these directions, the ARB benchmark (Ghaboura et al., 2025b) introduced step-by-step multimodal reasoning across 11 domains, spanning visual, OCR, and document understanding challenges. While these resources significantly advance Arabic multimodal research, they remain centered on language, dialect, and document-level OCR. None address the stylistic and artistic dimensions of Arabic script, where the written form functions as both text and art.

B.2 Heritage and Cultural Benchmarks

Heritage-oriented benchmarks demonstrate how evaluation can extend beyond functional NLP to cultural knowledge and artistic expression. For example, Fann or Flop (Alghallabi et al., 2025) foregrounds Arabic poetry, requiring models to interpret figurative language and aesthetic conventions across eras and genres. Other initiatives, such as Sacred or Synthetic (Atif et al., 2025), PalmX (Alwajih et al., 2025b), and PEARL (Alwajih et al., 2025a), introduced shared tasks for benchmarking LLMs on Arabic and Islamic cultural knowledge, underscoring the importance of cultural grounding. These resources have advanced heritage-aware evaluation, but they largely address poetry, artifacts, or cultural reasoning, while the artistic and stylistic dimension of Arabic calligraphy remains overlooked.

B.3 Arabic Calligraphy Resources

Computational work on Arabic calligraphy has primarily targeted recognition, identification, and style classification. Early studies employed handcrafted features to distinguish between scripts (Kaoudja et al., 2020; Ezz et al., 2019), but their impact was limited by small or restricted-use datasets. Later contributions introduced larger collections to support OCR and style recognition at the word and manuscript level (Alyafeai et al., 2022; Ismail et al., 2023; Adam et al., 2017; Zoizou et al., 2022; Saeed et al., 2024), complemented by computational approaches for style representation (Kaoudja et al., 2021). Earlier computer vision methods also explored the recognition of artistic scripts (Allaf and Al-Hmouz, 2016; Salamah and King, 2018), while recent surveys highlight interest in script generation through deep learning and generative models (Sumayli and Alkaoud). More recently, multimodal efforts such as Qalam (Bhatia et al., 2024) have signaled a transition from traditional OCR to vision–language approaches for Arabic handwriting.

Despite these contributions, prior datasets remain limited: they typically frame calligraphy as OCR rather than detection, rely on cropped text instead of full artistic layouts, focus mainly on historical manuscripts, and lack semantic diversity. **DuwatBench** addresses these gaps by introducing 1,050 samples across six major styles with bounding-box annotations and a wide range of textual categories. Unlike earlier corpora, its samples appear in complex artistic contexts such as inscriptions, signage, and artworks, foregrounding the visual–linguistic complexity of calligraphy in real-world settings.

C Data Statistics

To better characterize the distributional properties of our Arabic calligraphy dataset, we report descriptive statistics across both stylistic and thematic dimensions. Figures 6 and 7 show that the corpus is dominated by widely used scripts such as Thuluth and Diwani, with Kufic, Naskh, Ruq'ah, and Nasta'liq represented in smaller proportions.

Figure 6: **DuwatBench Theme-level Distribution.** Distribution of DuwatBench textual content across thematic categories, including non-religious text, Quranic verses, devotional invocations, names of the Prophet and companions, Names of Allah, and smaller groups such as personal names, dedications, and hadith.

Figure 7: **DuwatBench Style-level Distribution.** Distribution of DuwatBench samples across six major Arabic calligraphy styles, with Thuluth and Diwani forming the majority and Kufic, Naskh, Ruq'ah, and Nasta'liq represented in smaller proportions.

On the content side, the dataset balances non-religious expressions with religious material, including Quranic verses, devotional phrases, divine names, and prophetic references. These distributions underscore the dual role of Arabic calligraphy as both a cultural and sacred medium, while cap-turing the diversity needed for robust multimodal evaluation.

Figure 8: **Distribution of total word counts per entry in DuwatBench.** While most samples in DuwatBench consist of single words (81.7%), the dataset also includes longer inscriptions, particularly Quranic verses and combined passages.

Figure 8 illustrates the distribution of word counts across entries in DuwatBench. The majority of samples are single words, reflecting the common use of calligraphy for standalone terms such as names, motifs, or short expressions. At the same time, the dataset captures longer and more complex inscriptions, especially in religious contexts. Examples include extended Quranic verses such as Ayat al-Kursi and composite renderings that combine multiple surahs, for instance, An-Nas, Al-Falaq, and Al-Ikhlas presented alongside Ayat al-Kursi. This range highlights the dataset's ability to represent both concise and extended forms of calligraphy, ensuring coverage of diverse inscription practices.

D Verification and Annotation Guidelines

To ensure consistency and reliability across annotations, we designed a clear set of guidelines for the annotators and the validator. These rules covered image inclusion, bounding box creation, transcription practices, and style/theme labeling, followed by a two-tier verification process. Table 5 summarizes the rubric applied during the annotation and verification phase of DuwatBench.

E Additional Results and Analysis

To complement the main evaluation, this section presents additional quantitative results across Arabic calligraphic styles using the chrF metric, offering a finer view of character-level recognition and how performance varies with script complexity and data representation.

Aspect	Guidelines
Image inclusion	- Good resolution.
- Calligraphy must be complete, legible, and undistorted.
- Reject blurred, overexposed, cropped, or incomplete text.
- Prefer authentic artistic backgrounds preserving natural context.
Bounding boxes	- Draw boxes tightly around each word.
- Do not cut diacritics or ornamental strokes.
- Avoid excessive empty space around text.
Transcription	- Manually transcribe all visible text.
- Normalize letter forms and diacritics for consistency.
- Use Unicode-compliant Arabic script.
Style & theme labeling	- Assign one of six calligraphic styles: Thuluth, Diwani, Kufic, Naskh, Ruqah, Nastaliq.
- Assign a thematic category: non-religious, Quranic, devotional, Names of Allah, prophetic references, or smaller groups (personal dedications, hadith).
Quality control (Tier 1)	- Check resolution, completeness of text, and absence of artifacts.
Expert validation (Tier 2)	- Verify transcription accuracy and diacritic placement.
- Confirm style and theme classification.
- Resolve disagreements through consensus.

Table 5: **DuwatBench Verification and Annotation Guidelines.** The table summarizes the procedures followed during dataset verification and labeling. It outlines key aspects of the annotation process from image inclusion criteria and bounding-box placement to transcription, style, and thematic labeling—alongside a two-tier validation framework. Tier 1 ensures visual and structural quality control, while Tier 2 involves expert validation of transcription accuracy, diacritic integrity, and style–theme consistency.

	Models	Kufic	Thuluth	Diwani	Naskh	Ruq'ah	Nasta'liq
Open-source	Llava-v1.6-mistral-7b-hf (Liu et al., 2023)	2.1194	1.3518	2.3159	5.1318	10.7284	1.8746
	EasyOCR (Kittinaradorn et al., 2024)	7.1235	6.3493	3.7822	37.0854	34.7604	11.6499
	InternVL3-8B (Chen et al., 2024)	13.0635	9.8499	9.7389	29.3074	23.4321	11.4343
	Qwen2.5-VL-7B (Team, 2025)	23.2582	18.9998	19.2567	62.1257	78.0688	19.1127
	Qwen2.5-VL-72B-Instruct (Team, 2025)	35.2247	30.7119	23.1305	73.7176	81.4872	29.0384
	Gemma-3-27B-IT (Team et al., 2025)	42.1684	31.9125	32.4836	75.7939	81.1916	49.0933
	trocr-base-arabic-handwritten[*] (Microsoft, 2022)	0.7702	0.8457	0.8251	0.1788	0.4817	1.4788
	MBZUAI/AIN[*] (Heakl et al., 2025)	29.3721	21.5069	21.4187	76.2926	62.4880	34.4360
Closed-source	claude-sonnet-4.5 (Anthropic, 2025)	39.8937	28.5605	24.9173	74.4598	62.4263	14.8142
	gemini-1.5-flash (Reid et al., 2024)	29.2585	44.4580	35.8694	75.9763	77.9728	16.1357
	gemini-2.5-flash (AI, 2025)	56.1421	63.1680	60.0556	78.5927	79.3213	40.5800
	gpt-4o-mini (OpenAI, 2024)	39.1933	27.1844	27.4650	79.2308	82.3363	20.9514
	gpt-4o (OpenAI, 2024)	16.0442	17.6360	14.9768	62.3804	79.2272	62.6521

Table 6: **ChrF scores across Arabic calligraphy styles on DuwatBench.** ChrF values are reported per script style (Kufic, Thuluth, Diwani, Naskh, Ruq'ah, Nasta'liq) for open and closed-source models. Higher scores indicate better recognition quality. *Note:* * indicates Arabic-specific models. Values in blue denote the best performance, while underlined values indicate the second-best within each category (open or closed-source).

Table 6 shows notable variation in recognition difficulty. Kufic records the lowest scores overall, reflecting its geometric rigidity and sparse representation in training data. Thuluth and Diwani achieve moderate results—lower for open-source models but substantially higher for closed-source ones such as Gemini-2.5-Flash and GPT-4o-mini. Naskh and Ruq'ah remain the most accurately recognized, while Nasta'liq yields moderate but inconsistent outcomes, performing better in multilingual models like Gemma-3-27B-IT and GPT-4o. Notably, the MBZUAI/AIN model performs steadily across scripts, excelling in Naskh and Ruq'ah and reaching acceptable results in Diwani, Thuluth, Kufic, and Nasta'liq, showing good script-aware adaptation relative to its smaller 7B scale. Overall, the findings confirm that style complexity and data diversity, rather than model size, are key determinants of Arabic calligraphy recognition quality.

Metric	Mean	Std	Min	Max	Range / Rel. Impr.
CER_mean	0.7758	0.2378	0.3160	1.1806	0.8646 (73.2%)
WER_mean	0.9361	0.3130	0.4164	1.7872	1.3708 (76.7%)
NLD_error	0.5847	0.2120	0.2170	0.9689	0.7519 (77.6%)
chrF	23.3071	17.0822	0.4810	59.9590	59.4780
ExactMatch	0.2175	0.1598	0.0000	0.5605	0.5605
t-test (Open vs Closed)	CER_p=0.8371	WER_p=0.3718	NLD_p=0.0266	chrF_p=0.0695	ExactMatch_p=0.0384

Table 7: **Cross-Model Error Statistics and Significance Analysis.** Descriptive statistics and t-test comparisons between open and closed-source models on DuwatBench. Results show that closed-source models achieve significantly lower normalized edit distance and higher ExactMatch accuracy, indicating greater robustness to stylistic variation in Arabic calligraphy.

F Supplementary Statistical Analysis

This section provides additional quantitative analysis of model performance on DuwatBench. It complements the main results by presenting descriptive statistics, relative improvements, and statistical comparisons between open and closed-source systems. Together, these analyses provide a deeper understanding of how different models handle stylized Arabic calligraphy across recognition metrics.

Figure 9: **Metric Correlation Heatmap.** Correlation matrix across five metrics on DuwatBench, showing that higher edit distances (CER, WER, NLD) strongly inversely correlate with chrF and ExactMatch, confirming their complementary behavior in assessing recognition quality.

Across all evaluated models, the average character and word error rates (CER = 0.78, WER = 0.94) reflect the inherent difficulty of recognizing visually complex Arabic scripts. The normalized Levenshtein distance (NLD = 0.58) indicates frequent partial mismatches, while mean chrF (23.3) and ExactMatch (0.22) suggest limited fluency and full-sequence accuracy. Large standard deviations (0.2–0.3 for CER/WER/NLD and 17 for chrF) reveal substantial variability across systems, highlighting uneven robustness under diverse styles and artistic layouts.

Relative improvement between the strongest and weakest systems reaches 73–78% for CER, WER, and NLD, underlining the influence of model scale and multimodal grounding. To validate these observations, independent two-sample t-tests were applied to compare open and closed-source groups (Table 7). Results show that closed-source models achieve significantly lower NLD errors ($p = 0.0266$) and higher ExactMatch accuracy ($p = 0.0384$), confirming their superior consistency in capturing calligraphic structure. Differences in CER, WER, and chrF were statistically nonsignificant ($p > 0.05$), suggesting that while large closed-source systems outperform overall, their advantage mainly lies in precise alignment rather than raw character-level recognition.

These findings align with the qualitative analyses presented in the main paper, where closed-source models demonstrated greater stability on ornate scripts (e.g., Diwani, Thuluth), whereas opensource models exhibited higher variance and frequent segmentation errors. Together, Figure 9 and Table 7 provide a comprehensive quantitative view of model behavior, reinforcing the need for style-aware and culturally grounded evaluation of Arabic calligraphy recognition.