GUI-360°: A Comprehensive Dataset and Benchmark for Desktop Productivity Computer-Using Agents

Abstract

We introduce GUI-360°, a large-scale dataset and benchmark suite for *desktop productivity computer-using agents* (CUAs). GUI-360° provides an automated pipeline for query sourcing, template-based environment construction, task instantiation, batched execution, and LLM-assisted quality filtering in Windows office applications. The corpus contains 131K validated successful action steps across 17K trajectories for training and evaluation, together with 1.09M failed execution steps for failure analysis and future recovery training. Each step provides screenshots, accessibility metadata, instantiated goals, reasoning traces, and structured GUI/API actions. GUI-360° supports GUI grounding, screen parsing, and action prediction under a hybrid GUI+API action space. Experiments show that current vision–language models struggle with fine-grained grounding and stepwise action prediction, while supervised fine-tuning on GUI-360° brings consistent in-domain and external benchmark gains.

1 Introduction

Recent advances in vision–language models have sparked rapid progress toward intelligent agents that automate tasks inside digital environments (Zhang et al., 2024a). Such agents interpret natural-language requests, perceive screen content via pixels and/or accessibility (a11y) metadata, plan sequences of operations, and then either navigate the GUI or invoke APIs to complete tasks on a user's behalf (Zhang et al., 2025a). Among these settings, desktop productivity applications are especially important: word processors, spreadsheets, and presentation tools remain central to everyday knowledge work, and many of their workflows involve repetitive editing, formatting, data manipulation, and document creation. Automating such workflows can dramatically reduce user effort. However, realizing this potential requires two tightly coupled

capabilities: reliable screen understanding, including element grounding and screen parsing (Cheng et al., 2024; Lu et al., 2024; Zheng et al., 2025b), and robust action planning, including stepwise action prediction and execution (Zhang et al., 2024b). Both capabilities depend critically on large, diverse, and high-quality datasets grounded in realistic execution contexts (Wang et al., 2024c).

We focus on a concrete and under-served setting for *computer-using agents* (CUAs) (OpenAI, 2025a): desktop productivity environments. Compared with web (Zheng et al., 2024) or mobile (Wang et al., 2024b) interfaces, desktop productivity applications present distinctive challenges. They often contain high-resolution mixed-content screens, dense toolbars and ribbons, heterogeneous document objects such as text, tables, charts, and slides, arbitrary window layouts, and application-specific interaction patterns. Accessibility metadata can be incomplete, inconsistent, or difficult to align with visual elements (Zhang et al., 2025b). Productivity tasks are also frequently multi-step and compositionally structured, requiring agents to combine screen perception, document-state understanding, GUI operations, and application-level APIs. These characteristics make desktop productivity workflows a challenging and practically valuable testbed for CUAs (Zhang et al., 2024a).

Despite growing interest, progress in desktop productivity CUAs is hampered by three persistent gaps. First, existing datasets are often handcrafted or LLM-synthesized (Sun et al., 2024), which limits their ability to capture the frequency and diversity of authentic productivity workflows. Second, scalable pipelines for collecting and annotating multi-modal desktop trajectories remain limited (Nayak et al., 2025). Manual execution and labeling of desktop interactions is expensive, error-prone, and difficult to scale, especially when each step must align screenshots, accessibility metadata, actions, and document states. Third, exist-

Figure 1: GUI Grounding, Screen Parsing and Action Prediction tasks included in our GUI-360°.

ing benchmarks often focus on isolated capabilities, rather than providing a unified view of the core skills needed by desktop productivity agents (Nayak et al., 2025; Li et al., 2025). In particular, few resources jointly support *GUI grounding*, *screen parsing*, and *action prediction* with execution traces, hybrid GUI/API actions, and failure cases within the same benchmark suite.

To fill these gaps, we introduce GUI-360°, a dataset and benchmark suite for desktop productivity CUAs. GUI-360° is built around realism, scalability within Windows office applications. Concretely, it provides the following:

1. **Real-world queries.** Task intents are collected from authentic sources to capture common productivity needs and frequent workflows.

2. **Automated pipeline.** An LLM-augmented pipeline handles template construction, task instantiation, batched execution, and filtering, minimizing human effort while preserving execution realism.

3. **Multi-task annotations.** Each example includes screenshots, accessibility metadata, intermediate agent "thoughts," and trajectories. These support: (a) *GUI Grounding*, mapping a plan step to the target UI element; (b) *Screen Parsing*, enumerating interactable elements; and (c) *Action Prediction*, predicting the next action from the current state and intent. See Fig. 1.

4. **Scale and coverage.** GUI-360° contains 131K validated successful steps across Word, Excel, and PowerPoint, together with 1.09M failed execution steps released for failure analysis, recovery modeling, and future RL-style training.

5. **Hybrid GUI+API space.** Reflecting modern CUA designs (Zhang et al., 2025b,a), the action set combines GUI operations with application-level API calls, enabling evaluation of both interaction strategies.

Table 1 compares GUI-360° with existing GUI datasets across key dimensions. Unlike prior efforts that primarily target individual capabilities such as grounding or rely on small-scale scripted tasks, GUI-360° jointly supports GUI grounding, screen parsing, and action prediction in a large-scale, automatically collected desktop productivity corpus. It further provides accessibility metadata, reasoning supervision, failure trajectories, and a hybrid GUI+API action space, making it a unified benchmark for studying core capabilities of desktop productivity CUAs.

To assess GUI-360°'s utility, we benchmark state-of-the-art vision–language models. Our results show that off-the-shelf models still struggle with fine-grained grounding in heterogeneous layouts and stepwise action prediction, which can lead to cascading execution errors. Training on GUI-360° yields consistent gains on both in-domain tasks and external GUI-agent benchmarks. These findings highlight the limitations of current models and the value of GUI-360° as a scalable, challenging benchmark for desktop productivity CUAs.

2 Related Work

GUI and Computer-Using Agents LLMs have enabled agents (Zhang et al., 2024a) that automate tasks across web (Zheng et al., 2024, 2025a), mobile (Wang et al., 2024b,a, 2025), and desktop platforms (Zhang et al., 2024b, 2025b; Qin et al., 2025). Desktop environments are particularly challenging for CUAs due to high-resolution displays and com-

Table 1: Comparison of CUA datasets across dimensions.

Dataset	Query Source	Task			Samples	Data Collection	Action		Reasoning	A11y Info.	Fail Case
		Grounding	Parsing	Action Pred.			GUI	API			
ScreenSpot-Pro	Human-designed	✓	✗	✗	1,581	Human	N/A	N/A	N/A	N/A	N/A
DeskVision	Online	✓	✗	✗	54,855	Auto.	N/A	N/A	✗	✗	✗
SeeClick	Online	✓	✗	✗	1,000,000+	Auto.	N/A	N/A	✗	✗	✗
Aria-UI	LLM-synthetic	✓	✗	✗	11,500,000+	Auto.	N/A	N/A	✓	✗	✗
UI-Vision	Human-designed	✓	✗	✓	8,227	Human	✓	✗	✗	✗	✗
GUICourse	Online/LLM-synthetic/Human-designed	✓	✗	✓	10,831,853	Auto.	✓	✗	✓	✗	✗
AgentTrek	Online	✓	✗	✓	10,398	Auto.	✓	✗	✓	✓	✗
GUI-360°	**In-App/Online/ Search**	✓	✓	✓	**1,225,177**	Auto.	✓	✓	✓	✓	✓

plex layouts. Such agents typically rely on accessibility metadata or visual screen understanding (Gur et al., 2023; Xie et al., 2023). When accessibility information is missing, they resort to screen parsing and visual grounding, as in SeeClick (Cheng et al., 2024), OmniParser (Lu et al., 2024), and GUI-Actor (Wu et al., 2025). UFO (Zhang et al., 2024b, 2025b) pioneered hybrid approaches that combine accessibility with visual screen parsing, while recent efforts further integrate APIs for efficiency (Zhang et al., 2025a).

Data and Benchmarks for GUI Agents A key obstacle in building effective CUAs lies in obtaining high-quality training data and reliable benchmarks. The desktop setting remains underexplored despite its greater complexity compared to web (Deng et al., 2023; Zhou et al., 2023) and mobile domains (Rawles et al., 2023, 2024). Several efforts have emerged in this space. UI-Vision (Nayak et al., 2025) provides a human-annotated desktop benchmark with bounding boxes, UI labels, and action trajectories. DeskVision (Xu et al., 2025) introduces a cross-OS dataset for desktop region captioning. However, these datasets and benchmarks either require costly human annotation, or cover only narrow subsets of tasks, limiting their scalability and diversity. AgentTrek (Xu et al., 2024a) constructs web-based GUI trajectories by guiding agents with curated web tutorials and validating their outputs using an LLM-based judge. AgentSynth (Xie et al., 2025) generates synthetic tasks through LLM-driven proposers and collects roughly 6,000 trajectories within OSWorld.

Our GUI-360° addresses this gap by introducing an automated data collection pipeline that generates large-scale resources for GUI grounding, screen parsing, and action prediction.

3 The Collection of GUI-360°

The construction of GUI-360° follows a three-stage pipeline designed to maximize scalability while minimizing human effort, as shown in Figure 2. We begin by collecting *real-world* user queries from reliable sources to ensure coverage of diverse and realistic task intents. Then, we design a specialized CUA named TrajAgent to execute tasks in an automatic and consistent manner. The TrajAgent generates and collects detailed trajectories that jointly support GUI grounding, screen parsing, and action prediction. Finally, we apply automated evaluators and systematic post-processing to verify correctness, and enhance overall data quality.

3.1 Query Acquisition

High-quality and actionable user queries are the foundation of a reliable dataset, as they determine both task realism and execution fidelity (Xu et al., 2025). To capture queries that reflect real-world user needs, we design a dedicated acquisition pipeline (Figure 1), namely *(i)* **Prototypical Query Sourcing**, *(ii)* **Environment Template Construction**, *(iii)* **Task Instantiation**, and *(iv)* **Quality Filtering**. This four-stage pipeline ensures that the resulting queries are both realistic and executable.

Prototypical Query Sourcing. Most existing CUA datasets rely heavily on human-crafted or LLM-generated queries, which often fail to reflect real-world usage patterns or capture high-frequency tasks. To better ground our dataset in authentic user behavior, we source prototypical task descriptions from three complementary channels, namely *(i)*

Figure 2: The data collection pipeline for GUI-360°.

In-App Help Content (In-App), *(ii)* **Online Websites (Online)**, and *(iii)* **Search Queries (Search)**. The detailed description and statistics of the three sources are provided in Section A. These sources are real and reliable, in contrast to purely human-curated or LLM-synthetic data.

Environment Template Construction. Each user query must be grounded in a suitable environment that provides the necessary context for agent execution. For example, a task such as "make the first line of text bold" in Word requires a document containing editable text; without such a setup, the query is not actionable. Naively creating a bespoke environment for every query would be prohibitively expensive and redundant, since many queries share common contextual requirements.

To address this, we introduce an environment template construction process that systematically amortizes environment setup across queries. Specifically, we leverage LLM to analyze each query and extract its underlying requirements (*e.g.*, the presence of text, a table, or an image). Queries with similar requirements are clustered and abstracted into environment template descriptions. We then manually instantiate a curated set of 66 high-frequency templates from these descriptions, which can support approximately **95%** of queries.

Task Instantiation. Prototypical queries collected from real-world sources are often vague and underspecified (*e.g.*, *"How to make text bold?"*). To be executable by an agent, each query must be grounded in a specific environment and reformulated into an actionable instruction (*e.g.*, *"Make the phrase 'Hello World' bold in the Word document"*). We refer to this process as *task instantiation*. To systematically achieve this, we design

an automated two-stage pipeline. First, for each query, we provide GPT-4.1 with the query, textual descriptions, and screenshots of all available templates to identify the most suitable template. Next, once a template is selected, the LLM rephrases the vague query into a fully instantiated one, grounded in the chosen environment. This pipeline is fully automated and enforces that all instantiated tasks are *actionable*, *concrete*, and *scalable*.

Quality Filtering. Although task instantiation produces a large set of grounded queries, not all of them are suitable for reliable agent training. Many instantiated tasks may suffer from contextual mismatches, external dependencies, or inherent ambiguities. To ensure robustness, we design a *task filtering pipeline* that employs a GPT-4.1 as an automatic quality gate. The LLM-based judge evaluates each candidate task against a set of well-defined constraints, as detailed in Section C.

3.2 Automatic Trajectory Collection

Once queries have been instantiated and grounded, the next step is to generate corresponding action plans, execution trajectories, and outcomes. We develop a specialized execution framework, TrajAgent, that automatically completes queries in batch (Fig. 2) and records detailed execution trajectories. The workflow consists of three main phases. First, for each task, TrajAgent initializes the corresponding environment template and ensures that all preconditions are satisfied. Then the agent performs the query step-by-step, generating a complete action trajectory while recording the full GUI state at each step. After execution, TrajAgent closes or resets the environment to a clean state, preparing it for the next task in the batch. This fully automated process ensures that every task is executed reliably,

trajectories are captured consistently, and human intervention is entirely eliminated.

3.2.1 TrajAgent Design

The core requirement for large-scale trajectory collection is twofold: the executor must *(i)* complete instantiated queries with a high success rate to maximize data efficiency, and *(ii)* record every element required for dataset construction with strict fidelity. To meet these requirements we design TrajAgent, a multi-agent framework that reliably completes concrete tasks and produces execution traces.

Architecture overview. TrajAgent follows a multi-agent orchestration pattern (Zhang et al., 2024b) composed of a MasterAgent (MAgent), a pool of ExecutionAgents (EAgent), with a set of auxiliary services (Perception, Action Executor, and Recorder), as shown in Figure 3. The MAgent receives a concrete task and decomposes it into a sequence of manageable subtasks (planning). Each subtask is dispatched to an available EAgent for execution. EAgents operate as lightweight workers that (a) perceive the current GUI state, (b) select or synthesize the next low-level action (click/type/select/API call), (c) execute the action via UI automation or API invocation. The Recorder persistently logs the full GUI state and metadata before and after each action.

Perception. Within each EAgent, the Perception service captures a full-resolution screenshot at every decision step and queries the Windows accessibility API (UI Automation) (Haverty, 2005) to extract a list of actionable controls (name, type and exact bounding box). The accessibility-derived control metadata is rendered on the screenshot as a Set-of-Mark (SoM) (Yang et al., 2023).

Action Executor. The Action Executor utilizes app-specific MCP servers (Hou et al., 2025) to provide an extensible set of tools for the EAgent. In addition to GUI actions (*e.g.*, mouse clicks, keyboard input), our design incorporates app-level API actions, reflecting modern CUA practices (Zhang et al., 2025a). These APIs improve task efficiency and serve as reliable fallbacks for error-prone GUI interactions. At each step, the EAgent selects the most appropriate action based on its observation, reasoning, and plan (Yao et al., 2023). This loop continues until the task is completed.

Recorder. The Recorder collects all multi-modal information at each execution step to construct the dataset. This includes screenshots, accessibility metadata, and agent outputs (thought, plan, *etc*). Importantly, a single execution of the agent produces data for all downstream tasks, significantly improving data efficiency. Table 12 in Section F summarizes the input and output for each task type.

To improve coverage, we adopt a two-stage execution strategy. In the first stage, GPT-4o serves as the base model to complete queries. Any queries that **fail in this stage** are then re-executed using a stronger model GPT-4.1. The two-stage execution strategy substantially improves success rates by **16%** compared to relying on a single model.

3.3 Validation and Post-processing

To ensure the high quality and usability of the automatically collected trajectories, we perform a three-stage post-processing procedure: *(i)* **Trajectory Validation.** Each trajectory is *automatically* evaluated by GPT-4.1 to retain only successful and executable task executions, ensuring that downstream training and evaluation are based on realistic completions. *(ii)* **Data Sanitization.** Low-quality steps, incomplete records, or any data that fail to meet predefined quality criteria are removed. This step eliminates noise and increases the overall reliability of the dataset. *(iii)* **Data Structuring.** The cleaned trajectories are reformatted and normalized into the required structure for the three downstream tasks. This includes standardizing screenshot metadata, accessibility information, action calls, and annotations to create a consistent, machine-readable dataset. For the *Action Prediction* task, we provide two input modalities: *visual-only* and *visual+a11y*.

3.4 GUI-360° Statistics

Following the pipeline described above, we construct a comprehensive dataset, GUI-360°-Train for training across three core GUI tasks, and a companion benchmark, GUI-360°-Bench, for evaluation.

Scale. Table 2 summarizes the statistics of GUI-360°-Train (80%) and GUI-360°-Bench (20%). In total, GUI-360° contains 13,750 trajectories with over 105k steps, averaging 7.66 steps per trajectory. The dataset also provides 210k screenshots paired with 17.7M annotated UI elements, yielding rich multimodal supervision at both the visual and accessibility levels. For evaluation, GUI-360°-Bench adds a further 3,439 trajectories and 26k steps, maintaining a similar distribution of average step length and GUI/API action rates. In ad-

Figure 3: The overall architecture of the TrajAgent.

Table 2: Statistics of GUI-360°-Train and GUI-360°-Bench for successful trajectories.

Metric	Train	Bench
Total Trajectories	13,750	3,439
Total Steps	105,368	26,284
Steps for Grounding Tasks	79,487	19,780
Steps for Screen Parsing	105,368	26,284
Steps for Action Prediction	105,368	26,284
Total Elements	17,668,694	4,324,617
Total Images	210,736	52,568
Average Elements per Image	167.69	164.53
GUI Action Rate (%)	81.0	81.0
API Action Rate (%)	19.0	19.0

Figure 4: The **GUI-360°** Composition. For each app, tasks are divided into six categories.

dition, we include 62,170 trajectories comprising 1,093,525 steps for failure cases. These failure cases capture challenging or error-prone situations that models often struggle with. Detailed statistics and analysis are shown in Section G.

Diversity. Beyond scale, GUI-360° emphasizes breadth and functional diversity. Using GPT-4o, we classified user queries into fine-grained categories, as shown in Figure 4. The corpus spans Word (41.0%), Excel (31.6%), and PowerPoint (27.4%), each with rich internal coverage. Word tasks range from text formatting to layout and review, Excel covers data entry, formulas, and visualization, while PowerPoint emphasizes content editing, design, and transitions. This balance ensures exposure to both frequent operations and ong-tail behaviors, making it a comprehensive and challenging dataset and benchmark for productivity CUA.

4 Experiment

4.1 GUI Grounding

Baselines & Metric. We evaluate a mix of general and domain-specialized models. The general-purpose baselines are GPT-4o (Hurst et al., 2024),

GPT-4.1 (OpenAI, 2025c), o3 (OpenAI, 2025d), and GPT-5 (OpenAI, 2025b). We also include several open-source and grounding models: Qwen-VL-2.5 (7B) (Bai et al., 2025), UGround-7B (Gou et al., 2024), Aguvis-7B (Xu et al., 2024b), UI-TARS-1.5 (7B) (Qin et al., 2025), and GUI-Actor (7B) (Wu et al., 2025). Finally, we report results for SFT variants (Qwen-2.5 7B-SFT, UI-TARS-1.5 7B-SFT) that are trained on the GUI-360°-Train.

Performance Comparison. Table 3 reports the evaluation results of different models on GUI-360°-bench for the GUI grounding task. We observe that general-purpose GPT models (*e.g.*, GPT-4o and GPT-4.1) achieve only modest performance, with overall accuracy below 12%. More advanced general models such as GPT-o3 and GPT-5 show improvements (20–30%), yet still struggle with precise GUI grounding. Domain-specific pretraining brings substantial gains: models like UGround-7B and GUI-Actor 7B surpass 50%, demonstrating the

Table 3: Performance of different models on the GUI grounding task across applications.

Model	Word	Excel	PowerPoint	Overall
GPT-4o	15.22%	5.08%	5.41%	9.38%
GPT-4.1	17.30%	7.48%	7.01%	11.41%
o3	36.62%	19.44%	31.06%	29.96%
GPT-5	34.52%	20.31%	17.36%	25.34%
Qwen-2.5-VL-7B	38.09%	26.76%	41.55%	35.78%
UGround-7B	57.44%	43.09%	59.53%	53.85%
Aguvis-7B	53.14%	37.69%	59.57%	50.50%
UI-TARS-1.5 7B	63.50%	58.61%	64.21%	62.27%
GUI-Actor 7B	54.84%	45.84%	62.68%	54.50%
Qwen-2.5-VL-7B-SFT	84.11%	79.20%	**82.84%**	82.30%
UI-TARS-1.5 7B-SFT	**84.73%**	**79.84%**	81.98%	**82.49%**

Table 4: GUI grounding performance comparison.

Model	ScreenSpot-Pro	OSWorld-G
Qwen-2.5-VL-7B	26.8	31.4
Qwen-2.5-VL-7B (SFT on GUI-360°)	31.1 (+4.3)	36.2 (+4.8)
GUI-Actor-7B	40.7	46.8
GUI-Actor-7B (SFT on GUI-360°)	43.6 (+2.9)	49.9 (+3.1)

Table 5: Model comparison on screen parsing.

Model	Precision	Recall	F1	Text Sim.	Avg IoU
GPT-4o	0.034	0.014	0.019	0.147	0.229
GPT-4.1	0.098	0.057	0.067	0.306	0.505
o3	0.160	0.114	0.128	0.456	0.578
GPT-5	0.111	0.080	0.089	0.304	0.569
Qwen2.5-VL	0.181	0.010	0.015	0.113	0.211
OmniParser	0.411	0.459	0.406	0.565	0.731
OmniParser v2	**0.413**	**0.462**	**0.408**	**0.568**	**0.735**

effectiveness of grounding-oriented pretraining. Finally, supervised fine-tuning (SFT) on GUI-360° yields the largest performance leap, with Qwen-2.5 7B-SFT and UI-TARS-1.5 7B-SFT achieving over 82% accuracy across applications. This progression clearly highlights the value of GUI-360° for both training and benchmarking: it not only reveals the limitations of general-purpose models on GUI tasks but also provides high-quality training data.

Generalization on Offline Benchmarks We compare the performance of zero-shot and fine-tuned (SFT) versions of both Qwen-2.5-VL-7B and GUI-Actor-7B on the widely-used grounding benchmarks ScreenSpot-Pro and OSWorld-G. As shown in Table 4, both models achieve significant improvements after fine-tuning on GUI-360°. This demonstrates that fine-tuning on our dataset significantly boosts grounding performance, making it a valuable resource for GUI grounding tasks.

4.2 Screen Parsing

Baselines & Metric. We evaluate both general VLMs and specialized screen-parsing models. General models include GPT-4o, GPT-4.1, GPT-o3, GPT-5, and Qwen-VL-2.5 (7B). Specialized baselines include OmniParser(-v2) (Lu et al., 2024).

We evaluate screen parsing using three metrics. First, we assess *detection accuracy* by reporting precision, recall, and F1. Second, we measure *localization quality* via mean intersection-over-union (IoU) between predicted and ground-truth bounding boxes. Finally, we evaluate *semantic correctness* by computing the average embedding similar-

ity between predicted and true element names.

Performance Comparison. Table 5 presents a detailed comparison of general-purpose VLMs and specialized screen parsing models across Word, Excel, and PowerPoint. Overall, general-purpose models such as GPT-4o, GPT-4.1, GPT-o3, and GPT-5 struggle with both element detection and localization, achieving low F1 scores and moderate mean IoU values. Notably, GPT-o3 exhibits the highest overall F1 among the general models and maintains relatively strong localization (IoU 0.578), but its recall remains limited, indicating many missed elements. GPT-4.1 and GPT-5 show uneven performance across applications: GPT-5 performs best on Excel but poorly on PowerPoint, suggesting sensitivity to layout complexity and domain-specific content. In contrast, specialized parsers significantly outperform general-purpose models in all metrics. OmniParser and OmniParser-v2 achieve overall F1 scores above 0.40 and mean IoU above 0.73, with strong text similarity, demonstrating robust detection and accurate localization.

These results reveal two key insights: *(i)* general-purpose VLMs are limited in screen parsing due to the need for fine-grained spatial reasoning and UI semantics, and *(ii)* task-specific training, as in OmniParser, provides substantial gains in both element coverage and semantic correctness, highlighting the necessity of specialized architectures for accurate and reliable screen understanding.

4.3 Action Prediction

Baselines & Metric. We evaluate a set of general-purpose VLMs, including GPT-4o, GPT-4.1, GPT-o3, GPT-5, and Qwen-VL-2.5 (7B). In addition, we fine-tune Qwen-VL-2.5 with GUI-360°-Train to examine post-training improvements. Experiments are conducted under two settings: with and without a11y information as input.

For action prediction, each step consists of three components: the *function* being invoked, its *arguments*, and a *status* flag indicating whether to continue or finish the trajectory. Accordingly, we

Table 6: Model performance comparison [%] with visual-only screenshots (left) and with visual+a11y inputs (right).

	Visual-only				Visual+A11y			
Model	Word	Excel	PowerPoint	Total	Word	Excel	PowerPoint	Total
GPT-4o	3.61	1.96	3.35	3.12	**61.36**	29.15	48.11	36.71
GPT-4.1	3.60	1.88	2.55	2.82	35.46	**33.13**	**50.98**	**39.19**
GPT-o3	16.85	13.06	24.42	17.92	34.00	28.76	48.84	36.72
GPT-5	9.05	6.21	10.26	8.59	31.68	26.39	48.23	34.86
Qwen-2.5 7B	15.70	12.75	25.09	17.52	15.64	3.56	22.51	14.18
Qwen-2.5 7B-SFT	**49.10**	**45.12**	**56.53**	**50.08**	31.68	7.44	34.99	25.78

report function accuracy (whether the predicted function matches the ground truth), argument accuracy (correctness of spatial or symbolic arguments given the function), and status accuracy (correctness of the status flag). We also measure an aggregated step success rate, with details in Section J.3.

Performance Comparison. Table 6 reports the results of action prediction under the *visual-only* and *visual+a11y* settings. When relying on screenshots alone, all models perform poorly, with accuracy below 20% in most cases. This highlights the intrinsic difficulty of inferring precise action arguments purely from pixel-level cues, even for state-of-the-art proprietary VLMs such as GPT-4.1 and GPT-5. By contrast, providing accessibility information dramatically boosts performance. For example, GPT-4o improves from 3.12% to 36.71%, and GPT-4.1 nearly triples its performance from 2.82% to 39.19%. This demonstrates that structured element annotations effectively reduce the burden of visual grounding.

Furthermore, SFT on GUI-360° delivers substantial gains. Qwen-2.5 7B improves from 17.52% to 50.08% after SFT in the visual-only setting, a nearly threefold improvement, showing the strong training signal provided by GUI-360°. However, when a11y information is introduced, the benefits of SFT diminish, suggesting that a11y annotations already encode much of the structural alignment that SFT otherwise learns. Overall, these results highlight both the challenge and opportunity presented by GUI-360°: action prediction is extremely difficult without explicit structural information, but with accessibility-enhanced input and dataset-driven post-training, models can achieve substantial improvements.

Generalization on Online Benchmarks We evaluate the original and fine-tuned versions of Qwen-2.5-VL-7B and UI-TARS-1.5-7B on two live CUA benchmarks: OSWorld-W (Windows sub-

Table 7: Action prediction performance comparison.

Agent	OSWorld-W	WindowsAgentArena
UFO	12.2	19.5
Agent S	12.2	18.2
Operator	14.3	20.8
Qwen-2.5-VL-7B	8.2	10.7
Qwen-2.5-VL-7B (SFT)	20.4 (+10.2)	23.4 (+12.7)
UI-TARS-1.5-7B	20.4	20.8
UI-TARS-1.5-7B (SFT)	28.6 (+8.2)	27.9 (+7.1)

set of OSWorld) and WindowsAgentArena. As shown in Table 7, both Qwen-2.5-VL-7B and UI-TARS-1.5-7B demonstrate consistent improvement in action prediction after fine-tuning on the GUI-360° dataset. The fine-tuned models achieve substantial performance gains, particularly on OSWorld-W and WindowsAgentArena, confirming the effectiveness of GUI-360° in improving the performance in live environments.

These experiments demonstrate that fine-tuning with GUI-360° improves both grounding and action prediction across both offline and online benchmarks, further validating the quality and generalizability of our dataset.

5 Conclusion

We introduced GUI-360°, a large-scale dataset and benchmark for desktop productivity CUAs. GUI-360° addresses the lack of realistic executable tasks, scalable trajectory collection pipelines, and unified benchmarks linking GUI grounding, screen parsing, and action prediction. Built through a largely automated pipeline, the corpus contains 131K validated successful steps across Word, Excel, and PowerPoint, plus 1.09M failed execution steps for failure analysis. Each trajectory includes screenshots, accessibility metadata, reasoning traces, and structured GUI/API actions. Experiments show that fine-tuning on GUI-360° yields consistent gains. These findings establish GUI-360° as a practical resource for improving desktop productivity CUAs.

Limitations

GUI-360° focuses on desktop productivity CUAs, with the current release covering Windows office applications including Word, Excel, and PowerPoint. Although these applications contain dense toolbars, heterogeneous document objects, and multi-step editing workflows, they do not cover the full diversity of desktop software, operating systems, websites, or mobile environments. Therefore, our claims of coverage refer to the task and supervision dimensions within the desktop productivity setting, rather than universal coverage of all computer-use scenarios.

Second, our data collection pipeline is largely automated and relies on LLMs for task instantiation, filtering, execution, and trajectory validation. This design improves scalability, but may introduce systematic biases from the underlying models, prompt design, template choices, and validation criteria. Although we apply post-processing and quality filtering, automatic judgment is not a perfect substitute for human verification, and residual label noise may remain.

Ethical Considerations

Computer-using agents can operate over user interfaces, documents, and application APIs, which raises important safety, privacy, and governance concerns. Although GUI-360° is constructed from controlled desktop environments and does not require collecting private user documents, models trained on similar data may eventually be deployed in settings that involve sensitive files, personal information, or enterprise data. Such deployments should include explicit user consent, access control, data minimization, audit logs, and safeguards for actions that modify, delete, export, or share content.

References

Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, and 1 others. 2025. Qwen2. 5-vl technical report. *arXiv preprint arXiv:2502.13923*.

Kanzhi Cheng, Qiushi Sun, Yougang Chu, Fangzhi Xu, Yantao Li, Jianbing Zhang, and Zhiyong Wu. 2024. Seeclick: Harnessing gui grounding for advanced visual gui agents. *arXiv preprint arXiv:2401.10935*.

Xiang Deng, Yu Gu, Boyuan Zheng, Shijie Chen, Sam Stevens, Boshi Wang, Huan Sun, and Yu Su. 2023. Mind2web: Towards a generalist agent for the web. *Advances in Neural Information Processing Systems*, 36:28091–28114.

Boyu Gou, Ruohan Wang, Boyuan Zheng, Yanan Xie, Cheng Chang, Yiheng Shu, Huan Sun, and Yu Su. 2024. Navigating the digital world as humans do: Universal visual grounding for gui agents. *arXiv preprint arXiv:2410.05243*.

Jiawei Gu, Xuhui Jiang, Zhichao Shi, Hexiang Tan, Xuehao Zhai, Chengjin Xu, Wei Li, Yinghan Shen, Shengjie Ma, Honghao Liu, and 1 others. 2024. A survey on llm-as-a-judge. *arXiv preprint arXiv:2411.15594*.

Izzeddin Gur, Hiroki Furuta, Austin Huang, Mustafa Safdari, Yutaka Matsuo, Douglas Eck, and Aleksandra Faust. 2023. A real-world webagent with planning, long context understanding, and program synthesis. *arXiv preprint arXiv:2307.12856*.

Rob Haverty. 2005. New accessibility model for microsoft windows and cross platform development. *ACM SIGACCESS Accessibility and Computing*, (82):11–17.

Xinyi Hou, Yanjie Zhao, Shenao Wang, and Haoyu Wang. 2025. Model context protocol (mcp): Landscape, security threats, and future research directions. *arXiv preprint arXiv:2503.23278*.

Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, and 1 others. 2024. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*.

Kaixin Li, Ziyang Meng, Hongzhan Lin, Ziyang Luo, Yuchen Tian, Jing Ma, Zhiyong Huang, and Tat-Seng Chua. 2025. Screenspot-pro: Gui grounding for professional high-resolution computer use. *arXiv preprint arXiv:2504.07981*.

Yadong Lu, Jianwei Yang, Yelong Shen, and Ahmed Awadallah. 2024. Omniparser for pure vision based gui agent. *arXiv preprint arXiv:2408.00203*.

Shravan Nayak, Xiangru Jian, Kevin Qinghong Lin, Juan A Rodriguez, Montek Kalsi, Rabiul Awal, Nicolas Chapados, M Tamer Özsu, Aishwarya Agrawal, David Vazquez, and 1 others. 2025. Ui-vision: A desktop-centric gui benchmark for visual perception and interaction. *arXiv preprint arXiv:2503.15661*.

OpenAI. 2025a. Computer-using agent: Introducing a universal interface for ai to interact with the digital world.

OpenAI. 2025b. Gpt-5 is here. `https://openai.com/gpt-5/`. Accessed: 2025-09-18.

OpenAI. 2025c. Introducing gpt-4.1 in the api. Accessed: 2025-09-18.

OpenAI. 2025d. Introducing openai o3 and o4-mini. `https://openai.com/index/introducing-o3-and-o4-mini/`. Accessed: 2025-09-18.

Yujia Qin, Yining Ye, Junjie Fang, Haoming Wang, Shihao Liang, Shizuo Tian, Junda Zhang, Jiahao Li, Yunxin Li, Shijue Huang, and 1 others. 2025. Ui-tars: Pioneering automated gui interaction with native agents. *arXiv preprint arXiv:2501.12326*.

Christopher Rawles, Sarah Clinckemaillie, Yifan Chang, Jonathan Waltz, Gabrielle Lau, Marybeth Fair, Alice Li, William Bishop, Wei Li, Folawiyo Campbell-Ajala, and 1 others. 2024. Androidworld: A dynamic benchmarking environment for autonomous agents. *arXiv preprint arXiv:2405.14573*.

Christopher Rawles, Alice Li, Daniel Rodriguez, Oriana Riva, and Timothy Lillicrap. 2023. Androidinthewild: A large-scale dataset for android device control. *Advances in Neural Information Processing Systems*, 36:59708–59728.

Nils Reimers and Iryna Gurevych. 2019. Sentence-bert: Sentence embeddings using siamese bert-networks. *arXiv preprint arXiv:1908.10084*.

Qiushi Sun, Kanzhi Cheng, Zichen Ding, Chuanyang Jin, Yian Wang, Fangzhi Xu, Zhenyu Wu, Chengyou Jia, Liheng Chen, Zhoumianze Liu, and 1 others. 2024. Os-genesis: Automating gui agent trajectory construction via reverse task synthesis. *arXiv preprint arXiv:2412.19723*.

Junyang Wang, Haiyang Xu, Haitao Jia, Xi Zhang, Ming Yan, Weizhou Shen, Ji Zhang, Fei Huang, and Jitao Sang. 2024a. Mobile-agent-v2: Mobile device operation assistant with effective navigation via multi-agent collaboration. *Advances in Neural Information Processing Systems*, 37:2686–2710.

Junyang Wang, Haiyang Xu, Jiabo Ye, Ming Yan, Weizhou Shen, Ji Zhang, Fei Huang, and Jitao Sang. 2024b. Mobile-agent: Autonomous multi-modal mobile device agent with visual perception. *arXiv preprint arXiv:2401.16158*.

Lu Wang, Fangkai Yang, Chaoyun Zhang, Junting Lu, Jiaxu Qian, Shilin He, Pu Zhao, Bo Qiao, Ray Huang, Si Qin, and 1 others. 2024c. Large action models: From inception to implementation. *arXiv preprint arXiv:2412.10047*.

Zhenhailong Wang, Haiyang Xu, Junyang Wang, Xi Zhang, Ming Yan, Ji Zhang, Fei Huang, and Heng Ji. 2025. Mobile-agent-e: Self-evolving mobile assistant for complex tasks. *arXiv preprint arXiv:2501.11733*.

Qianhui Wu, Kanzhi Cheng, Rui Yang, Chaoyun Zhang, Jianwei Yang, Huiqiang Jiang, Jian Mu, Baolin Peng, Bo Qiao, Reuben Tan, and 1 others. 2025. Gui-actor: Coordinate-free visual grounding for gui agents. *arXiv preprint arXiv:2506.03143*.

Jingxu Xie, Dylan Xu, Xuandong Zhao, and Dawn Song. 2025. Agentsynth: Scalable task generation for generalist computer-use agents. *arXiv preprint arXiv:2506.14205*.

Tianbao Xie, Fan Zhou, Zhoujun Cheng, Peng Shi, Luoxuan Weng, Yitao Liu, Toh Jing Hua, Junning Zhao, Qian Liu, Che Liu, and 1 others. 2023. Openagents: An open platform for language agents in the wild. *arXiv preprint arXiv:2310.10634*.

Yibin Xu, Liang Yang, Hao Chen, Hua Wang, Zhi Chen, and Yaohua Tang. 2025. Deskvision: Large scale desktop region captioning for advanced gui agents. *arXiv preprint arXiv:2503.11170*.

Yiheng Xu, Dunjie Lu, Zhennan Shen, Junli Wang, Zekun Wang, Yuchen Mao, Caiming Xiong, and Tao Yu. 2024a. Agenttrek: Agent trajectory synthesis via guiding replay with web tutorials. *arXiv preprint arXiv:2412.09605*.

Yiheng Xu, Zekun Wang, Junli Wang, Dunjie Lu, Tianbao Xie, Amrita Saha, Doyen Sahoo, Tao Yu, and Caiming Xiong. 2024b. Aguvis: Unified pure vision agents for autonomous gui interaction. *arXiv preprint arXiv:2412.04454*.

Jianwei Yang, Hao Zhang, Feng Li, Xueyan Zou, Chunyuan Li, and Jianfeng Gao. 2023. Set-of-mark prompting unleashes extraordinary visual grounding in gpt-4v. *arXiv preprint arXiv:2310.11441*.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2023. React: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations (ICLR)*.

Chaoyun Zhang, Shilin He, Liqun Li, Si Qin, Yu Kang, Qingwei Lin, Saravan Rajmohan, and Dongmei Zhang. 2025a. Api agents vs. gui agents: Divergence and convergence. In *ICML 2025 Workshop on Computer Use Agents*.

Chaoyun Zhang, Shilin He, Jiaxu Qian, Bowen Li, Liqun Li, Si Qin, Yu Kang, Minghua Ma, Guyue Liu, Qingwei Lin, and 1 others. 2024a. Large language model-brained gui agents: A survey. *arXiv preprint arXiv:2411.18279*.

Chaoyun Zhang, He Huang, Chiming Ni, Jian Mu, Si Qin, Shilin He, Lu Wang, Fangkai Yang, Pu Zhao, Chao Du, and 1 others. 2025b. Ufo2: The desktop agentos. *arXiv preprint arXiv:2504.14603*.

Chaoyun Zhang, Liqun Li, Shilin He, Xu Zhang, Bo Qiao, Si Qin, Minghua Ma, Yu Kang, Qingwei Lin, Saravan Rajmohan, and 1 others. 2024b. Ufo: A ui-focused agent for windows os interaction. *arXiv preprint arXiv:2402.07939*.

Boyuan Zheng, Michael Y Fatemi, Xiaolong Jin, Zora Zhiruo Wang, Apurva Gandhi, Yueqi Song, Yu Gu, Jayanth Srinivasa, Gaowen Liu, Graham Neubig, and 1 others. 2025a. Skillweaver: Web agents can self-improve by discovering and honing skills. *arXiv preprint arXiv:2504.07079*.

Boyuan Zheng, Boyu Gou, Jihyung Kil, Huan Sun, and Yu Su. 2024. Gpt-4v (ision) is a generalist web agent, if grounded. *arXiv preprint arXiv:2401.01614*.

Jiani Zheng, Lu Wang, Fangkai Yang, Chaoyun Zhang, Lingrui Mei, Wenjie Yin, Qingwei Lin, Dongmei Zhang, Saravan Rajmohan, and Qi Zhang. 2025b. Vem: Environment-free exploration for training gui agent with value environment model. *arXiv preprint arXiv:2502.18906*.

Shuyan Zhou, Frank F Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, and 1 others. 2023. Webarena: A realistic web environment for building autonomous agents. *arXiv preprint arXiv:2307.13854*.

A Query Sources

Table 8: Raw query statistics across applications and sources.

Source	Word	Excel	PowerPoint
In-App	274	159	316
Online	1,914	3,393	1,701
Search	25,715	25,000	19,681
Total	27,903	28,552	21,698

To ensure both breadth and realism, we draw task intents from three complementary sources:

1. **In-App Help Content (In-App).** Built-in tutorials and official documentation provide standardized, structured descriptions of common workflows and functionalities. These queries cover canonical operations and ensure completeness of core task categories.

2. **Online Websites (Online).** Community forums, Q&A platforms, and technical blogs supply diverse, naturally phrased queries. These contributions reflect real-world problem-solving scenarios and capture long-tail, user-specific needs often missing from official materials.

3. **Search Engine Queries (Search).** High-frequency queries collected from search engines highlight urgent and widely encountered issues. This source emphasizes practical challenges that users repeatedly face in everyday workflows.

Table 8 reports the distribution of raw queries across applications and sources. We observe that search data dominate the corpus, reflecting their naturally high frequency and broad coverage, while online forums contribute significant diversity, and in-app content provides structured coverage of baseline tasks. By combining these complementary sources, we achieve a balanced dataset that is both *authentic*—rooted in real user behavior—and *comprehensive*—covering canonical and long-tail workflows alike. This balance is crucial for building benchmarks that generalize beyond synthetic or hand-crafted examples.

B Action Set

To support diverse interaction across desktop applications, we design a unified action set that combines general-purpose GUI operations with

application-specific APIs using MCP servers. The action set is deliberately lightweight yet expressive, enabling agents to cover the full spectrum of common productivity tasks while remaining tractable for model training.

The GUI actions (`click`, `type`, `drag`, `wheel_mouse_input`) form the foundation of interaction, as they are applicable to any graphical user interface. These actions abstract low-level mouse and keyboard events into structured calls, supporting variants such as absolute and normalized coordinates, modifier keys, and multi-step operations.

On top of this universal layer, we extend the action set with fine-grained APIs for **Word**, **Excel**, and **PowerPoint**. These APIs expose high-level document, spreadsheet, and presentation semantics, such as inserting tables, modifying cell values, reordering columns, adjusting font properties, or setting slide backgrounds. By combining GUI-agnostic operations with domain-specific APIs, the action set achieves both generality and efficiency: agents can rely on GUI actions for arbitrary interfaces while exploiting APIs for structured tasks where precise semantics matter.

Table 9 summarizes the full action set. This unified design allows agents trained on GUI-360° to operate seamlessly across heterogeneous applications, balancing robustness with expressivity.

C Query Filtering Analysis

1. **Non-Executable (`NONEXEC`)**: Inputs that do not describe a concrete action are removed. This includes subjective statements, vague preferences, or general inquiries that cannot be directly executed. For instance, instructions containing words such as "custom," "you want," or undefined operations like "edit text" without specifying the target element fall under this category.

2. **Cross-Application Dependency (`CROSSAPP`)**: Tasks that require interaction with applications beyond {app} are excluded. This includes operations that involve opening or manipulating content in external software (*e.g.*, Excel, Edge, File Explorer, or system settings). Representative examples include merging files across applications, printing documents (which requires printer integration), or exporting data to a third-party tool.

3. **Version Management (`VERCTRL`)**: Tasks that involve checking, updating, downgrading, or modifying the version of {app} are discarded. Since version management depends heavily on system environment and external factors, these tasks are not considered executable within the scope of our benchmark.

4. **Template Dependency (`TPLMISS`)**: Tasks that rely on specific document or workspace templates that are absent from the provided context are excluded. For example, instructions that assume the existence of a predefined table, chart, or object not available in the given file are categorized as `TPLMISS`. Note that application-wide settings (*e.g.*, enabling dark mode) do not fall under this restriction, as they do not depend on document templates.

5. **Irrelevant or Invalid (`INVALID`)**: Remaining cases that do not fit into the above categories, or are otherwise infeasible due to irrelevance, ambiguity, or context mismatch, are marked as invalid. For example, a task unrelated to {app} or lacking sufficient contextual information for execution would be discarded under this category.

Table 10 summarizes the results of our LLM-based task filtering across Word, Excel, and PowerPoint. Out of 79,075 candidate tasks, 59,553 (75.3%) are retained as `NORMAL`, indicating they are self-contained, concretely specified, and feasible given the provided templates and context. The remaining 24.7% of tasks are excluded due to various limitations. Overall, the filtering process ensures that the `NORMAL` subset comprises tasks that are well-specified, executable, and contextually grounded. This careful curation is critical for constructing a robust benchmark that reliably evaluates the performance of LLMs on single-application task execution, while also providing insights into common sources of task ambiguity or infeasibility.

D Failure Trajectory Analysis

To better understand the provenance of the failed trajectories in GUI-360°, we conduct a diagnostic analysis of 1,000 randomly sampled failed trajectories using GPT-4.1 as an automatic annotator. The failure taxonomy follows the error definitions used in prior GUI-agent analysis, such as UFO2 (Zhang et al., 2025b), and is adapted to our desktop productivity setting with hybrid GUI and API actions.

Table 9: Supported actions across Word, Excel, and PowerPoint, grouped by shared GUI actions and application-specific APIs.

Action	Description	Type
click	Click at a given position (absolute or normalized), supporting left/right/middle/x button, single/double click, and optional modifier key.	GUI
type	Type text or hotkeys at a position, with options for clearing text or focusing on control. Supports special keys like {VK_CONTROL}c.	GUI
drag	Drag from a start to an end position with configurable mouse button, duration, and optional key hold (*e.g.*, shift, control).	GUI
wheel_mouse_input	Scroll at a given position with positive (up) or negative (down) wheel distance.	GUI
insert_table	Insert a table with a specified number of rows and columns.	Word API
select_text	Select exact text in the document.	Word API
select_table	Select a table by its index number.	Word API
select_paragraph	Select paragraphs by start and end indices, with option to restrict to non-empty ones.	Word API
save_as	Save the document with specified directory, file name, and extension (default: PDF).	Word API
set_font	Change font family and/or size.	Word API
table2markdown	Extract the contents of a worksheet table into Markdown format.	Excel API
insert_excel_table	Insert a table (list of lists) into a sheet at a specified starting cell.	Excel API
select_table_range	Select a range of cells by coordinates in a sheet.	Excel API
set_cell_value	Set the value (or formula) of a specific cell.	Excel API
auto_fill	Autofill values in a specified cell range.	Excel API
reorder_columns	Reorder columns in a sheet according to a given list of column names.	Excel API
set_background_color	Change the slide background color using a hex RGB value, for selected or all slides.	PowerPoint API
save_as	Save the presentation with specified directory, file name, and extension (default: PPTX). Optionally save slides as images.	PowerPoint API

Table 10: Distribution of task categories after filtering, shown as percentages of total candidate tasks for each application.

Category	Word	Excel	PowerPoint
CROSSAPP	15.61%	13.27%	12.13%
TPLMISS	2.93%	4.18%	7.51%
NONEXEC	1.56%	1.68%	3.65%
VERCTRL	0.17%	0.13%	0.27%
INVALID	2.70%	6.98%	1.46%
NORMAL	77.02%	73.76%	74.97%

We use a multi-label annotation protocol: a single failed trajectory may involve more than one failure factor. Therefore, the percentages in Table 11 sum to more than 100%. These labels are used only for diagnostic analysis and are not treated as ground-truth supervision for model training or benchmark evaluation. To complement the aggregate statistics, Figure 5 provides one concrete example for each of the three failure modes analyzed below.

Discussion. The analysis shows that the majority of failed trajectories are caused by execution-level errors rather than invalid task definitions. In particular, execution errors account for 66% of the sampled failures, suggesting that many trajectories fail because the agent selects the wrong GUI element, performs an imprecise interaction, or provides incorrect action arguments. This indicates that desktop GUI grounding and action-argument prediction remain major bottlenecks for current computer-using agents.

Planning errors account for 43% of the sampled failures. These cases reflect limitations in high-level task understanding and long-horizon decomposition. For example, the agent may choose an inappropriate workflow, skip a required setup step, or terminate before the user goal is fully satisfied. Such failures suggest that improving low-level perception alone is insufficient; robust desktop agents also require better task planning and state tracking.

Control detection failures account for 11% of the sampled failures. Although this category is smaller than execution and planning errors, it highlights

Table 11: Failure mode categorization over 1,000 randomly sampled failed trajectories. Since failures are multi-factorial, each trajectory may be assigned multiple labels, and the percentages sum to more than 100%.

Failure Mode	Ratio	Definition	Typical Examples
Execution Errors	66%	The plan is mostly reasonable, but one or more low-level actions fail due to grounding, action mapping, or argument errors.	• Misclicking a nearby control
• Selecting the wrong menu item
• Performing an unintended GUI operation
• Dragging to an incorrect location
• Entering an incorrect API parameter
Planning Errors	43%	The agent misunderstands the goal or decomposes it into an incorrect sequence of subtasks.	• Omitting necessary prerequisite steps
• Applying operations in the wrong order
• Choosing an unsuitable workflow
• Modifying the wrong object
• Prematurely concluding task completion
Control Detection Failures	11%	The agent misses or misrecognizes key GUI elements needed for task completion.	• Missing a required ribbon control
• Failing to recognize a dialog option
• Overlooking a dynamically generated widget
• Failing to associate a visual element with its accessibility entry

an important limitation of relying on accessibility metadata and visual perception. Some controls in desktop productivity applications are custom-rendered, dynamically displayed, or difficult to associate with a stable accessibility entry. These cases are particularly challenging for both GUI grounding and screen parsing models.

Overall, this analysis suggests that the failed trajectory corpus is heterogeneous. A large portion of failed trajectories, especially those involving execution and grounding errors, can serve as useful negative demonstrations for future research on error recovery, action correction, and reinforcement learning from failed attempts. At the same time, planning errors and control detection failures indicate that downstream users should treat the failure corpus as diagnostic data rather than directly using all failed trajectories as standard supervised demonstrations.

E Details of Evaluation and Post-processing

Trajectory Validation. To ensure the reliability of collected data, each trajectory undergoes automatic validation. We design an evaluation agent, *EvaAgent*, which leverages GPT-4.1 in an LLM-as-a-judge paradigm (Gu et al., 2024). EvaAgent inspects the trajectory step by step, including the screenshot, accessibility information, executed actions, intermediate thoughts, and the final appli-cation state. Following prior work (Wang et al., 2024c), it employs a chain-of-thought style reasoning process to decompose the query into several fine-grained evaluation criteria. A trajectory is marked as successful only if all criteria are satisfied, thereby enforcing a stricter notion of task completion.

To assess its reliability, we conducted a small-scale study on 250 randomly sampled trajectories. EvaAgent's judgments achieved 91.6% agreement with human annotators, demonstrating that it provides sufficiently accurate and scalable validation. Compared to hard-coded scripts or brittle oracle rules, this approach offers greater flexibility across diverse applications and enables rapid filtering of high-quality, successful trajectories at scale.

Data Sanitization. After validation, we perform a final cleaning step to ensure completeness and consistency of the collected trajectories. This involves removing any step that lacks an executed action, a screenshot, or essential metadata required for downstream tasks. Such sanitization further improves the overall data quality and ensures that only fully executable, well-documented steps are retained for model training and evaluation.

Data Structuring. Finally, we transform the sanitized data into a standardized JSON format tailored for model consumption, following the input–output specifications summarized in Table 12. For the *Action Prediction* task, we provide two input modali-

Figure 5: Representative failure trajectories from GUI-360°. Each row shows the GUI state before and after the key erroneous action, with red boxes marking the relevant evidence and the resulting incorrect or unchanged state. The examples illustrate three dominant failure factors: execution errors, planning errors, and control detection failures.

ties: *visual-only* and *visual+a11y*:

- **Visual-only:** The model receives raw screenshots as input. Interaction-related arguments (*e.g.*, click positions) are represented as the absolute coordinates of the center of the corresponding bounding box.

- **Visual+a11y:** The model additionally receives the list of actionable elements from the accessibility API, which are also annotated on the screenshot using the Set-of-Mark (SoM) representation. Interaction arguments are expressed as element ID and name, chosen from the provided element list. This reduces the need for explicit coordinate prediction and lowers the visual grounding overhead.

Together, these stages guarantee that the final dataset is both high-quality and fully compatible with diverse CUA training and benchmarking pipelines.

For evaluation, we partition the trajectories into training (80%) and benchmark (GUI-360-Bench, 20%) splits. All three tasks—GUI Grounding, Screen Parsing, and Action Prediction—share the same data partition to maintain consistency across evaluations.

F Task Input-Output Specifications

Table 12 specifies the input-output design for dataset collection, providing a structured view of the three core tasks in our pipeline. Each task plays a distinct role in bridging raw user queries and screenshots with executable actions.

- **GUI Grounding.** This task focuses on localizing the precise element to interact with on the screen. By combining application screenshots with the agent's reasoning trace (*i.e.*, "thought"), the system determines the target coordinates of the actionable element. These coordinates are not heuristically guessed but are validated via accessibility APIs to ensure accurate alignment with system-recognized controls. This specification ensures high-fidelity mappings between natural instructions and the GUI surface.

Table 12: Task input-output specifications for dataset collection.

Task	Input	Output
GUI Grounding	Application screenshot, Agent's thought at the current step	Operation coordinates of the target element, obtained via accessibility APIs
Screen Parsing	Application screenshot	List of all actionable controls on screen with name and bounding box, *e.g.*, {"name": "Open Menu", "bbox": [12,34,56,78]}
Action Prediction	User query, Application screenshot, Accessibility information (optional)	Action call, with optional metadata such as agent's thought and plan

- **Screen Parsing.** Screen parsing builds a structured representation of the current interface. Given only a screenshot, the system outputs a comprehensive list of actionable controls, including their semantic names and bounding boxes. This is critical for downstream tasks, as it transforms unstructured pixels into a machine-readable set of candidate actions. For example, a detected control may be represented as {"name": "Open Menu", "bbox": [12,34,56,78]}, enabling both grounding and prediction tasks to reason over well-defined objects instead of raw visual input.

- **Action Prediction.** This task connects user intent to system operations. The inputs are multimodal, including the user's natural language query, visual context from the screenshot, and optional accessibility metadata. The output is an action call that specifies not only *what* operation to perform but may also include structured metadata such as the agent's intermediate plan or reasoning. This makes the action prediction task inherently more challenging and semantically rich, as it requires aligning natural language, visual layout, and accessibility data into an executable form.

Together, these tasks capture the full spectrum of dataset requirements: from raw perception (*screen parsing*) to grounding actions in concrete GUI elements (*GUI grounding*), and finally to bridging user intent with executable operations (*action prediction*). This decomposition ensures modularity, interpretability, and extensibility of the dataset for training and evaluation.

G Detailed GUI-360° Statistics

Table 13 presents a detailed breakdown of the GUI-360° training and benchmark datasets across Word, Excel, and PowerPoint domains. Several key observations can be made:

Scale and Balance. The training split contains 13,750 trajectories and over 105k steps, roughly four times larger than the benchmark split (3,439 trajectories and 26k steps). This provides a rich training signal while ensuring that the evaluation set remains sufficiently large and diverse for reliable benchmarking. The average number of steps per trajectory is consistent across splits (7.66 in training vs. 7.64 in benchmark), indicating that both datasets preserve similar task complexity distributions.

Task Coverage. Each trajectory decomposes into multiple step-level tasks, spanning GUI grounding, screen parsing, and action prediction. For both splits, every step contributes to screen parsing and action prediction, while a large subset (79.5k in training and 19.8k in benchmark) is specifically dedicated to grounding tasks. This balanced design ensures that models trained on GUI-360° are exposed to diverse subproblems critical for end-to-end agent performance.

Domain Differences. Excel trajectories contain significantly more UI elements per image (415.9 in training and 409.8 in benchmark) compared to Word (78.3/79.2) and PowerPoint (63.8/64.1). This highlights Excel's inherent interface complexity and motivates the need for robust grounding and parsing strategies in grid-heavy environments. By contrast, PowerPoint tasks involve fewer elements

but slightly longer trajectories (around 9 steps on average), reflecting the multi-step nature of slide composition tasks.

Action Modality. The ratio of GUI-based to API-based actions remains stable across splits and applications. On average, 81% of actions are executed via GUI operations, while 19% rely on APIs. Interestingly, PowerPoint shows a higher reliance on GUI actions (87%), while Word and Excel involve more mixed usage. This suggests that real-world GUI agents must flexibly support both interaction modalities to achieve broad coverage.

Implications. Overall, GUI-360° offers large-scale, well-balanced supervision for GUI agent training. Its fine-grained decomposition into tasks, diversity across domains, and preservation of modality ratios ensure that models can be both trained and evaluated under realistic and representative conditions.

H GUI-360° Schema

Each execution step in GUI-360° is stored as a structured JSON object following a unified schema. This schema ensures consistency across tasks and provides rich multimodal supervision for grounding, parsing, and action prediction. Table 14 summarizes the key fields.

Discussion. The schema integrates three complementary perspectives: (i) **Visual context** through multi-view screenshots, (ii) **Structural context** via accessibility metadata and hierarchical UI trees, and (iii) **Cognitive traces** through observations, reasoning, actions, and evaluations. This rich structure allows GUI-360° to jointly support grounding, parsing, and action prediction, while enabling both supervised training and fine-grained evaluation. By standardizing every execution step, the schema provides a scalable foundation for reproducibility and extensibility across applications.

I Baseline Details

We summarize the baselines evaluated on GUI-360° across the three core tasks: GUI grounding, screen parsing, and action prediction. These baselines include both general-purpose vision–language models and domain-specific approaches designed for GUI reasoning. Below we briefly introduce each group of models.

I.1 GUI Grounding

- **GPT-4o** (Hurst et al., 2024): proprietary multimodal VLM used off-the-shelf for grounding.
- **GPT-4.1** (OpenAI, 2025c): proprietary VLM emphasizing instruction-following and tool use.
- **o3** (OpenAI, 2025d): OpenAI "reasoning" model family; evaluated zero-shot for grounding.
- **GPT-5** (OpenAI, 2025b): latest OpenAI flagship; strong general reasoning baseline.
- **Qwen2.5-VL-7B** (Bai et al., 2025): open-source 7B multimodal baseline.
- **UGround-7B** (Gou et al., 2024): GUI visual grounding model (Qwen2-VL backbone) trained with large-scale GUI data.
- **Aguvis-7B** (Xu et al., 2024b): vision-centric GUI agent with a unified cross-platform action space.
- **UI-TARS-1.5 (7B)** (Qin et al., 2025): multimodal agent optimized for GUI reasoning and interactive tasks.
- **GUI-Actor (7B)** (Wu et al., 2025): coordinate-free grounding model with an attention-based action head.
- **SFT variants**: Qwen2.5-VL-7B fine-tuned on GUI-360° for task-adapted grounding.

I.2 Screen Parsing

- **GPT-4o / GPT-4.1 / o3 / GPT-5** (Hurst et al., 2024; OpenAI, 2025c,d,b): general-purpose VLMs used off-the-shelf for detection/localization.
- **Qwen2.5-VL-7B** (Bai et al., 2025): open-source multimodal baseline.
- **OmniParser / OmniParser-v2** (Lu et al., 2024): screen-parsing tools that produce element sets (names + bounding boxes) from raw screenshots.

I.3 Action Prediction

- **GPT-4o / GPT-4.1 / o3 / GPT-5** (Hurst et al., 2024; OpenAI, 2025c,d,b): proprietary VLMs evaluated in both *visual-only* and *visual+a11y* settings.
- **Qwen2.5-VL-7B** (Bai et al., 2025): open-source baseline for structured action generation.
- **Qwen2.5-VL-7B-SFT**: supervised fine-tuning on GUI-360° for step-wise function/argument/status prediction.

Table 13: Training and test dataset statistics across domains (Word, Excel, PowerPoint).

GUI-360°-Train				
	Word	Excel	PowerPoint	Total
Total Trajectories	5,633	4,348	3,769	13,750
Total Steps	41,742	29,363	34,263	105,368
Average Steps per Trajectory	7.41	6.75	9.09	7.66
Steps for Grounding Tasks	30,695	22,319	26,473	79,487
Steps for Screen Parsing	41,742	29,363	34,263	105,368
Steps for Action Prediction	41,742	29,363	34,263	105,368
Total Elements	3,270,104	12,211,852	2,186,738	17,668,694
Total Images	83,484	58,726	68,526	210,736
Average Elements per Image	78.34	415.89	63.82	167.69
GUI Action Rate (%)	76.1	80.7	87.4	81.0
API Action Rate (%)	23.9	19.3	12.6	19.0
GUI-360°-Bench				
	Word	Excel	PowerPoint	Total
Total Trajectories	1,409	1,087	943	3,439
Total Steps	10,597	7,175	8,512	26,284
Average Steps per Trajectory	7.52	6.60	9.03	7.64
Steps for Grounding Tasks	7,784	5,444	6,552	19,780
Steps for Screen Parsing	10,597	7,175	8,512	26,284
Steps for Action Prediction	10,597	7,175	8,512	26,284
Total Elements	839,273	2,940,016	545,328	4,324,617
Total Images	21,194	14,350	17,024	52,568
Average Elements per Image	79.20	409.76	64.07	164.53
GUI Action Rate (%)	76.2	80.2	87.5	81.0
API Action Rate (%)	23.8	19.8	12.5	19.0

Summary. Together, these baselines span a spectrum from general-purpose VLMs to specialized GUI-focused agents. This diversity allows us to systematically evaluate the unique challenges posed by GUI-360° across grounding, parsing, and action prediction, and to measure how far current models remain from robust, human-level computer-using agents.

J Performance Metrics

J.1 GUI Grounding

The primary evaluation metric for GUI grounding is **accuracy**, defined as the proportion of predictions where the predicted coordinate $\hat{c}_i$ lies within the bounding box of the corresponding ground-truth target element b_i. Formally,

$$\text{Acc} = \frac{1}{N} \sum_{i=1}^{N} \Vdash\{\hat{c}_i \in b_i\},$$

where N is the total number of test cases and $\Vdash\{\cdot\}$ is the indicator function.

J.2 Screen Parsing

We measure parsing quality along three complementary axes: (i) element detection accuracy (precision / recall / F1), (ii) localization quality (mean IoU on matched pairs), and (iii) semantic name accuracy (average text embedding similarity on matched pairs). All metrics are computed per image and then averaged across the benchmark (macro-average).

Let G be the ground-truth set of elements for an image and P the predicted set. We obtain a one-to-one matched set $M \subseteq P \times G$ by performing greedy bipartite matching sorted by descending IoU, and keeping only pairs with IoU > 0.5. For a predicted box p and ground-truth box g we use the standard

Table 14: Execution Step Schema for GUI-360°. Each entry records metadata, screenshots, accessibility data, reasoning traces, and actions.

Field	Description
execution_id	Unique identifier for the execution instance (*e.g.*, word_1_1).
app_domain	Application domain (*e.g.*, Word, Excel, PowerPoint).
request	Natural-language task description provided to the agent.
template	Environment template file used for instantiation.
step_id / total_steps	Current step index and total number of steps in the trajectory.
evaluation	Automatic assessment of the step, including reasoning, evidence, sub-scores, and a final completeness label.
step.screenshots	Multiple synchronized screenshots: clean view, full desktop, annotated version, and selected-controls view.
step.ui_tree	Hierarchical UI structure with element IDs, names, control types, bounding boxes, and children.
step.control_infos	Metadata from accessibility APIs and merged control sources, providing bounding boxes, labels, and semantic text.
step.observation	Agent's textual observation of the current state.
step.thought	Agent's intermediate reasoning for the next action.
step.action	Executed action, including function type (*e.g.*, click), arguments, target coordinates, and status flag.
status	Overall status of the step (CONTINUE or FINISH).

intersection-over-union:

$$\text{IoU}(p, g) \ = \ \frac{\text{area}(p \cap g)}{\text{area}(p \cup g)}.$$

For each image i define:

$$\text{Precision}_i = \frac{|M_i|}{|P_i|},$$

$$\text{Recall}_i = \frac{|M_i|}{|G_i|},$$

$$\text{F1}_i = \frac{2 \cdot \text{Precision}_i \cdot \text{Recall}_i}{\text{Precision}_i + \text{Recall}_i}.$$

where $|\cdot|$ denotes set cardinality. The reported precision, recall, and F1 are the macro-averages across images:

$$\text{Precision} = \frac{1}{N} \sum_{i=1}^{N} \text{Precision}_i,$$

$$\text{Recall} = \frac{1}{N} \sum_{i=1}^{N} \text{Recall}_i,$$

$$\text{F1} = \frac{1}{N} \sum_{i=1}^{N} \text{F1}_i.$$

To quantify localization quality, we compute the mean IoU for each image i over the matched pairs M_i. If an image has no matched pairs ($|M_i| = 0$), we define its IoU as 0. The overall mean IoU is

then the macro-average across all images:

$$\overline{\text{IoU}} = \frac{1}{N} \sum_{i=1}^{N} \text{IoU}_i,$$

$$\text{IoU}_i = \begin{cases} \frac{1}{|M_i|} \sum_{(p,g) \in M_i} \text{IoU}(p,g), & |M_i| > 0 \\ 0, & |M_i| = 0 \end{cases}.$$

Similarly, for semantic-name accuracy, we embed predicted and ground-truth names using a sentence encoder $\phi(\cdot)$ (*i.e.*, a sentence-transformer (Reimers and Gurevych, 2019)) and compute the cosine similarity for each matched pair. Let n_p and n_g denote the predicted and ground-truth names of a matched pair:

$$\text{sim}(p,g) = \frac{\langle \phi(n_p), \phi(n_g) \rangle}{\|\phi(n_p)\| \, \|\phi(n_g)\|}.$$

If an image has no matches, we assign a similarity of 0 for that image. The macro-average over all images is:

$$\overline{\text{Sim}} = \frac{1}{N} \sum_{i=1}^{N} \text{Sim}_i,$$

$$\text{Sim}_i = \begin{cases} \frac{1}{|M_i|} \sum_{(p,g) \in M_i} \text{sim}(p,g), & |M_i| > 0 \\ 0, & |M_i| = 0 \end{cases}.$$

Together, these metrics separate *whether* elements are detected (precision/recall/F1), *how precisely* they are localized (mean IoU), and *how well* their semantic roles are recovered (mean embedding similarity).

J.3 Action Prediction

The evaluation of action prediction is more nuanced than grounding, since each action step is composed of a *function*, a set of *arguments*, and a *status* flag (continue or finish). We therefore report three component accuracies and one aggregated metric:

- **Function accuracy** (Acc$_{\text{func}}$): the proportion of predictions where the predicted function $\hat{f}_i$ exactly matches the ground-truth function f_i.

$$\text{Acc}_{\text{func}} = \frac{1}{N} \sum_{i=1}^{N} \mathbb{1}\{\hat{f}_i = f_i\}.$$

- **Argument accuracy** (Acc$_{\text{args}}$): evaluated conditionally on the predicted function. If the function is a spatial action such as `click`, correctness requires that the predicted coordinate $(\hat{x}_i, \hat{y}_i)$ falls inside the ground-truth bounding box b_i. For symbolic arguments (*e.g.*, menu item name, keystroke, value,), correctness requires exact match between predicted and ground-truth arguments. Formally,

$$\text{Acc}_{\text{args}} = \frac{1}{N} \sum_{i=1}^{N} \mathbb{1}\{\hat{a}_i \equiv a_i \mid f_i\},$$

where the equivalence relation $\equiv$ depends on the function type f_i.

- **Status accuracy** (Acc$_{\text{status}}$): whether the predicted status flag $\hat{s}_i$ matches the ground-truth status s_i.

- **Step success rate** (Acc$_{\text{step}}$): a step is considered correct only if all three components (function, arguments, status) are correct simultaneously.

$$\text{Acc}_{\text{step}} = \frac{1}{N} \sum_{i=1}^{N} \mathbb{1}\{\hat{f}_i = f_i \wedge \hat{a}_i \equiv a_i \wedge \hat{s}_i = s_i\}.$$

K   Per-Application Analysis on Screen Parsing

We further analyze model performance across applications (detailed results in Appendix 16). On **Word**, which features text-rich but visually ambiguous layouts, language models benefit from strong semantic understanding, yielding relatively high text similarity, yet they struggle with accurate localization, often predicting correct labels with shifted bounding boxes. In contrast, OmniParser achieves consistently higher recall and IoU, indicating the importance of GUI-aware geometric priors. **Excel** proves to be the most challenging domain due to its high-density and repetitive grid structure. Most general-purpose models collapse in recall, missing a large fraction of small, homogeneous controls. OmniParser maintains moderate recall and strong IoU by leveraging layout-aware parsing, highlighting that specialized table-structure modules are critical for handling spreadsheet interfaces. In **Power-Point**, where controls are visually salient and layouts more regular, models perform relatively well. OmniParser attains both high recall and accurate localization, and even general VLMs perform better than in Excel, though complex objects like charts and grouped components remain difficult. Overall, these findings suggest that GUI-specific inductive biases and structure-aware detection are essential, particularly for dense spreadsheet environments,

Table 15: Breakdown comparison of (Qwen-2.5-7B / SFT) models on action prediction.

Metric	w/o a11y				w/ a11y			
	Excel	Word	PowerPoint	Overall	Excel	Word	PowerPoint	Overall
Function Acc.	61.7 / **81.1**	63.0 / **81.2**	88.5 / **91.0**	69.8 / **83.9**	50.6 / **80.6**	66.6 / **83.2**	90.8 / **91.5**	69.0 / **84.8**
Args. Acc.	12.8 / **45.4**	15.8 / **49.4**	25.2 / **56.7**	17.6 / **50.3**	3.6 / **7.5**	15.7 / **31.8**	22.6 / **35.2**	14.3 / **25.9**
Status Acc.	**96.0** / 94.1	**96.4** / 93.9	**97.4** / 96.2	**96.6** / 94.6	85.7 / **95.3**	**98.2** / 95.8	**99.0** / 96.3	94.9 / **95.8**
Element Err.	74.9 / **64.0**	66.6 / **61.4**	96.2 / **82.8**	76.7 / **67.5**	74.9 / **89.8**	83.6 / **76.7**	98.8 / **90.5**	84.7 / **84.7**

while semantic recovery alone is insufficient without precise localization.

L Breakdown Analysis

To obtain a fine-grained understanding of action prediction, we break down the metric in Table 15. The *Element Err.* reflects the ratio of out-of-bounds coordinate predictions in the visual-only setting or incorrect element selections when a11y information is available.

We observe that SFT brings large gains in *function Acc.* and especially in *argument Acc.*, reducing errors by more than half across domains. The dominant source of failure remains *Args Mismatch Error*, which suggests that grounding actions to the correct interface element is the most challenging aspect. Notably, Element Error contributes significantly to these mismatches, highlighting the model's difficulty in grounding from screenshots.

M Application-Agnostic Design of GUI-360°

GUI-360° relies on a minimal environment-template abstraction. Each new application environment is specified only by a launch entry, an initial-state specification, and reset logic. All other components, including accessibility-augmented perception, hybrid GUI+API action space, action validation, and the TrajAgent execution loop remain unchanged across applications.

To demonstrate its generalizability, we instantiated a non-Office environment, namely a standard web browser. Using only:

- a **URL-based template**, and

- a **browser initialization state**

We executed TrajAgent without any modification to the GUI-360° pipeline. With this setup, GUI-360° successfully collected 100 trajectories in the browser environment using the **same TrajAgent framework**, and under the **unchanged** perception, parsing, planning, and action-execution pipeline.

This demonstrates that GUI-360° generalizes out-of-the-box to new applications, and that Office environments serve as an initial instantiation rather than a limitation of the system design.

N Implementation Details

Data Collection. To construct GUI-360°, we deployed a cluster of **15 Windows 11 virtual machines**, each provisioned with 4 CPU cores. These VMs executed tasks in parallel, enabling efficient large-scale trajectory collection. Task execution followed a two-phase strategy: in **Phase 1**, GPT-4o was used as the agent; in **Phase 2**, all failed tasks were re-executed with GPT-4.1 for recovery (see Section 3). Both models were queried with the temperature fixed at 0.0 to ensure deterministic outputs and reproducibility.

Model Access. For evaluation on GUI-360°-Bench, we used multiple OpenAI models, including GPT-4o, GPT-4.1, o3, and GPT-5, all accessed via the **Azure OpenAI Service**. Unless otherwise stated, the decoding temperature was set to 0.0 across all experiments to minimize variance and ensure consistent evaluation.

Fine-tuning and Training. All supervised fine-tuning (SFT) experiments were conducted on a compute cluster equipped with **NVIDIA A100 GPUs** (40GB memory per GPU) and fine-tuned for one epoch. Specifically, each run was distributed across 4 A100 GPUs using mixed-precision training (FP16) for efficiency. We adopted standard optimization settings following prior work on multimodal fine-tuning, with learning rates tuned over $\{1e\text{-}5, 5e\text{-}6, 1e\text{-}6\}$. Checkpointing and gradient accumulation were applied to ensure stable training for long trajectories.

O LLM Usage Statement

In preparing this work, we used large language models (LLMs) strictly as an assistive tool for text polishing and minor language refinement. All research ideas, technical designs, analyses, and con-

Table 16: Comparison of different models across domains (Precision, Recall, F1, Text Similarity, Avg IoU Accuracy).

Model	Domain	Precision	Recall	F1	Text Sim.	Avg IoU
GPT-4o	Word	0.040	0.017	0.024	0.170	0.252
	Excel	0.020	0.002	0.004	0.085	0.133
	PowerPoint	0.037	0.021	0.026	0.171	0.282
	Overall	0.034	0.014	0.019	0.147	0.229
GPT-4.1	Word	0.101	0.065	0.077	0.307	0.518
	Excel	0.102	0.026	0.039	0.278	0.514
	PowerPoint	0.091	0.073	0.080	0.330	0.480
	Overall	0.098	0.057	0.067	0.306	0.505
o3	Word	0.173	0.128	0.144	0.481	0.631
	Excel	0.178	0.099	0.118	0.335	0.523
	PowerPoint	0.129	0.109	0.115	0.526	0.559
	Overall	0.160	0.114	0.128	0.456	0.578
GPT-5	Word	0.106	0.079	0.088	0.315	0.615
	Excel	0.172	0.109	0.126	0.274	0.574
	PowerPoint	0.065	0.056	0.059	0.314	0.508
	Overall	0.111	0.080	0.089	0.304	0.569
Qwen2.5-VL-7B	Word	0.384	0.014	0.023	0.137	0.358
	Excel	0.041	0.002	0.003	0.082	0.094
	PowerPoint	0.047	0.011	0.014	0.111	0.128
	Overall	0.181	0.010	0.015	0.113	0.211
OmniParser	Word	0.392	0.520	0.440	0.619	0.730
	Excel	0.431	0.217	0.270	0.450	0.748
	PowerPoint	0.417	0.588	0.479	0.594	0.718
	Overall	0.411	0.459	0.406	0.565	0.731
OmniParser v2	Word	0.396	0.525	0.444	0.625	0.738
	Excel	0.431	0.217	0.270	0.450	0.748
	PowerPoint	0.418	0.590	0.481	0.596	0.721
	Overall	0.413	0.462	0.408	0.568	0.735

clusions were conceived and carried out entirely by the authors.