LATENT PROGRAMMER: DISCRETE LATENT CODES FOR PROGRAM SYNTHESIS

ABSTRACT

In many sequence learning tasks, such as program synthesis and document summarization, a key problem is searching over a large space of possible output sequences. We propose to learn representations of the outputs that are specifically meant for search: rich enough to specify the desired output but compact enough to make search more efficient. Discrete latent codes are appealing for this purpose, as they naturally allow sophisticated combinatorial search strategies. The latent codes are learned using a self-supervised learning principle, in which first a discrete autoencoder is trained on the output sequences, and then the resulting latent codes are used as intermediate targets for the end-to-end sequence prediction task. Based on these insights, we introduce the *Latent Programmer*, a program synthesis method that first predicts a discrete latent code from input/output examples, and then generates the program in the target language. We evaluate the Latent Programmer on two domains: synthesis of string transformation programs, and generation of programs from natural language descriptions. We demonstrate that the discrete latent representation significantly improves synthesis accuracy.

1 INTRODUCTION

Our focus in this paper is program synthesis, one of the longstanding grand challenges of artificial intelligence research (Manna & Waldinger, 1971; Summers, 1977). The objective of program synthesis is to automatically write a program given a specification of its intended behavior, such as a natural language description or a small set of input-output examples. Search is an especially difficult challenge within program synthesis (Alur et al., 2013; Gulwani et al., 2017), and many different methods have been explored, including top-down search (Lee et al., 2018), bottom up search (Udupa et al., 2013), beam search (Devlin et al., 2017), and many others (see Section 3).

We take a different philosophy: *Can we learn a representation of programs specifically to help search?* A natural way of representing a program is as a sequence of source code tokens, but the synthesis task requires searching over this representation, which can be difficult, especially for longer, more complex programs. Instead, perhaps it would be easier for a system to search over a more abstract representation, because such a representation might also be more compact, and hence more conducive to search. Specifically, our hypothesis is that discrete latent codes (van den Oord et al., 2017; Roy et al., 2018; Kaiser et al., 2018) can learn a useful representation for search, because we can then apply standard methods from discrete search, such as beam search, to obtain a list of k-best predictions. Because the latent code specifies the program more compactly than the original source code, beam search in this representation might be more effective.

This leads us to propose the *Latent Programmer*, a program synthesis method that uses learned discrete representations to guide search. The Latent Programmer is trained by a self-supervised learning principle. First a discrete autoencoder is trained on a set of programs to learn discrete latent codes, and then an encoder is trained to map the specification of the synthesis task to these latent codes. Finally, when the model needs to make predictions, Latent Programmer uses a two-level search. Given the specification, the model first produces a L-best list of latent codes from the latent predictor, and then for each of these, a program is predicted autoregressively. On two different program synthesis domains, we find empirically that the Latent Programmer improves synthesis accuracy by over 10% compared to standard sequence-to-sequence methods such as RobustFill (Devlin et al., 2017). We also find that leveraging a discrete latent code improves diversity of predictions, as well as accuracy on long programs, precisely those for which we expect the task to be most complex.

Inputs	Outputs	Program
"Mason Smith"	"Smith M"	
"Henry Myers"	"Myers H"	`GetToken_PROP_CASE_2	Const(" ") |`
"Barry Underwood"	"Underwood B"	`GetToken_ALL_CAPS_1`
"Sandy Jones"	"Jones S"	

Figure 1: A string transformation task with 4 input-output examples a possible program in the string transformation DSL that is consistent with the examples.

2 RELATED WORK

Program Synthesis Our work deals with *program synthesis*, which involves combinatorial search for programs that match a specification. Many different search methods have been explored within program synthesis, including search within a version-space algebra (Gulwani, 2011), bottom-up enumerative search (Udupa et al., 2013), stochastic search (Schkufza et al., 2013), genetic programming (Koza, 1994), or reducing the synthesis problem to logical satisfiability (Solar-Lezama et al., 2006). *Neural program synthesis* involves learning neural networks to predict function distributions to guide a synthesizer (Balog et al., 2017), or the program autoregressively in an end-to-end fashion (Parisotto et al., 2017; Devlin et al., 2017). SketchAdapt (Nye et al., 2019) combined these approaches by first generating a program sketch with holes, and then filling holes using a conventional synthesizer. Related to our work, DreamCoder (Ellis et al., 2020) iteratively builds a sketches using progressively more complicated primitives though a wake-sleep algorithm. Our work is closely related in spirit but fundamentally differs in two ways: (1) our sketches are comprised of a general latent vocabulary that is learned in a simple, self-supervised fashion, and (2) our method avoids enumerative search, which is prohibitively expensive for large program spaces. There is also a line of work that deals with learning to process partial programs in addition to the specification. In *execution-guided program synthesis*, the model guides iterative extensions of the partial programs until a matching one is found (Zohar & Wolf, 2018; Chen et al., 2019; Ellis et al., 2019). Balog et al. (2020) of late proposed a differentiable fixer that is trained to iteratively edit incorrect programs. We treat these works as complementary, and can be combined with ours to refine predictions.

Discrete Latent Bottlenecks Variational autoencoders (VAE) were first introduced using continuous latent representations (Kingma & Welling, 2014; Rezende et al., 2014). Several promising approaches were proposed to use discrete bottlenecks instead, such as continuous relaxations of categorical distributions i.e. the Gumbel-Softmax reparametrization trick (Jang et al., 2017; Maddison et al., 2017). Recently, VQ-VAEs using nearest-neighbor search on a learned codebook (see Section 3 for more details) achieved impressive results almost matching continuous VAEs (van den Oord et al., 2017; Roy et al., 2018). VQ-VAE methods have been successfully used to encode natural language descriptions into discrete codes for faster decoding in machine translation (Kaiser et al., 2018). Our work also uses a discrete latent representation, but aim to show that it can also be used to improve decoding by first searching over latent structure, and in the program synthesis domain; thus, our work deals with improving accuracy over latency. Discrete bottlenecks have also been used for sentence compression (Miao & Blunsom, 2016) and text generation (Puduppully et al., 2019), but these works does not learn the semantics of the latent codes, like ours does. Within the domain of synthesis of chemical molecules, Gómez-Bombarelli et al. (2018) have applied Bayesian optimization within a continuous latent space to guide this structured prediction problem. Finally, learning to search has also been considered in the structured prediction literature (Daumé et al., 2009; Chang et al., 2015; Ross et al., 2011), but to our knowledge, these works do not consider the problem of learning a discrete representation for search.

3 BACKGROUND

Problem Setup The goal in program synthesis is to find a program in a given language that is consistent with a specification. Formally, we are given a domain specific language (DSL) which defines a space $\mathcal{Y}$ of programs. The task is described by a specification $X \in \mathcal{X}$ and is solved by some, possibly multiple, unknown program(s) $Y \in \mathcal{Y}$. For example, each specification can be a set of input/output (I/O) examples denoted $X = \{(I_1, O_1), \ldots (I_N, O_N)\}$. Then, we say that we have solved specification X if we found a program Y which correctly solves all the examples: $Y(I_i) = O_i, \forall i = 1, \ldots, N$. As another example, each specification can be a natural language description of a task, and the corresponding program implements said task. An example string

Figure 2: High-level architecture for the Latent Programmer system.

transformation synthesis task with four I/O examples together with a potential correct program in the string transformation DSL is shown in Figure 1.

Vector Quantization Traditionally, neural program synthesis techniques use a sequence-based approach which processes the input specification as a set of sequences and predicts the output program token-by-token (Devlin et al., 2017). In this work, we present a new approach for synthesis that performs structured planning in latent space using a discrete code, or sequence of discrete latent variables. We conjecture that programs have an underlying discrete structure; specifically, programs are compositional and modular with components that get reused across different problems. Our approach leverages this structure to guide the search over large program spaces. Following works in computer vision (van den Oord et al., 2017; Roy et al., 2018), we discover such discrete structure by using a VQ-VAE (van den Oord et al., 2017), which has been shown to successfully learn "a high-level abstract space that is invariant to low-level features and only encodes the main content". VQ-VAE works by feeding the intermediate representation of an auto-encoder through a discretization bottleneck. For completeness, we provide background on VQ-VAE below.

A Vector Quantized Variational Autoencoder (VQ-VAEs) provides a framework for learning an autoencoder with discrete latent codes (van den Oord et al., 2017). In a VQ-VAE, latents are drawn from a discrete set of learned vectors $c \in \mathbb{R}^{K \times D}$, or codebook. Each element in the codebook can be viewed as either a token with id $k \in [K]$ or as an embedding $c_k \in \mathbb{R}^D$. To generate the discrete codes, the continuous output e is quantized into a token id $\mathrm{qk}(e)$ and an embedding $\mathrm{qc}(e)$ as

$$\mathrm{qc}(e) = c_{\mathrm{qk}(e)} \text{ where } \mathrm{qk}(e) = \arg \min_{k \in [K]} ||e - c_k||_2. \tag{1}$$

The training loss for a VQ-VAE consists of: a reconstruction loss for the encoder-decoder weights, a codebook loss that encourages codebook embeddings to be close to the continuous vectors which are quantized to them, and a commitment loss that encourages the encoded input $\mathrm{ec}(x)$ to "commit" to codes i.e. not switch which discrete code it is quantized to. The loss is given by,

$$\mathcal{L}(c, \phi) = \log p\left(x \mid \mathrm{qc}(\mathrm{ec}_\phi(x))\right) + ||\mathrm{sg}(\mathrm{ec}_\phi(x)) - c||_2^2 + \beta||\mathrm{sg}(c) - \mathrm{ec}_\phi(x)||_2^2, \tag{2}$$

where ϕ are the parameters of the encoder, $\mathrm{sg}(\cdot)$ is the stop gradient operator, and β controls the strength of the commitment loss. To stabilize training, Roy et al. (2018) removed the codebook loss and set the codebook to an exponential moving average (EMA) of encoder outputs $\mathrm{ec}(x)$.

4 SYNTHESIS WITH DISCRETE LATENT VARIABLES

We propose a two-level hierarchical approach to program synthesis that first performs high-level planning over an intermediate sequence, which is then used for fine-grained generation of the program. In our approach, a higher-level model first plans out a coarse sequence of goal tokens, which gets used by the lower-level model to generate the final program. In addition, contrary to prior work that ground the coarse sequences in the program vocabulary (Nye et al., 2019), our work uses a general vocabulary of discrete latent variables that is jointly learned with the hierarchical model.

4.1 HIERARCHY OF TWO TRANSFORMERS

Our proposed **Latent Programmer** (LP) architecture consists of two Transformers in a two-level structure. The architecture comprises of two modules: a **latent predictor** which produces a coarse

plan, and a **latent program decoder**, which generates a program conditioned on the plan. The plan is a sequence of tokens in latent space, denoted `<TOK_1>,..., <TOK_K>`, the meaning of which is determined during training. Both components use a Transformer architecture due to their impressive performance on natural language tasks (Vaswani et al., 2017).

To help the model assign useful meanings to the latents, we also leverage a **program encoder**, which is only used during training. The program encoder $\text{ec}(Y)$ encodes the true program $Y = [y_1, y_2, \ldots, y_T]$ into a shorter sequence of discrete latent variables $Z = [z_1, z_2, \ldots, z_S]$, represented as codebook entries; that is, each $z_i \in \mathbb{R}^D$ is one of K entries in a codebook c. The latent sequence serves as the ground-truth high-level plan for the task. The function $\text{ec}(Y)$ is a Transformer encoder, followed by a stack of convolutions of stride 2, each halving the size of the sequence. We apply the convolution ℓ times, which reduces a T-length program to a latent sequence of length $S = \lceil T/2^\ell \rceil$. This provides temporal abstraction, since the high-level planning actions are made only every 2^ℓ steps. In summary, the program encoder is given by

$$\text{ec}(Y) \leftarrow h_\ell; \quad h_m \leftarrow \text{Conv}(h_{m-1}) \text{ for } m \in 1 \ldots \ell; \quad h_0 \leftarrow \text{TransformerEncoder}(Y). \quad (3)$$

Here $\text{TransformerEncoder}(\cdot)$ applies a stack of self-attention and feed-forward units on input embeddings via a residual path, described in detail by Vaswani et al. (2017). This will be used, along with the latent program decoder, as an autoencoder during training (see Section 4.2).

The **latent predictor** $\text{lp}(X)$ autoregressively predicts a coarse plan $\text{lp}(X) \in \mathbb{R}^{S \times K}$, conditioned on the program specification X. The latent predictor outputs a plan as a sequence of probabilities over latent tokens, which is different than the program encoder. This discrepancy is to organize search over latent codes; at test time, we will obtain a L-best list of latent token sequences from $\text{lp}(X)$. The latent predictor is given by a stack of Transformer blocks with the specification X as inputs.

Similarly, the **latent program decoder** $d(Z, X)$ defines an autoregressive distribution over program tokens given the specification X and the coarse plan $Z \in \mathbb{R}^{S \times K}$, represented as codebook entries. The decoder is a Transformer that jointly attends to the latent sequence and program specification. This is performed via two separate attention modules, whose outputs are concatenated into the hidden unit. Formally, given a partially generated program $Y' = [y'_1, y'_2, \ldots, y'_{t-1}]$, and the encoded specification $E = \text{TransformerEncoder}(X)$, the latent program decoder performs

$$h_t = \text{Concat}\left(\text{TransformerDecoder}(Y', E)_{t-1}, \text{TransformerDecoder}(Y', Z)_{t-1}\right), \quad (4)$$

where $\text{TransformerDecoder}(x, y)$ denotes a Transformer decoder applied to outputs y while attending to inputs encoding x, and the subscript indexes an entry in the resulting output sequence. Finally, the distribution over output token k is given by $d_t(Z, X) = \text{Softmax}\left(W(h_t)\right)$, where W is a learned parameter matrix. Finally, the latent program decoder defines a distribution over programs autoregressively as $p(Y|Z, X) = \prod_t p(y_t|y_{<t}, Z, X)$, where $p(y_t|y_{<t}, Z, X) = d_t(Z, X)$. When X is multiple I/O examples, each example is encoded as $E_i = \text{TransformerDecoder}(I_i, O_i)$. Then, a separate hidden state per I/O is computed following equation 4, followed by a late max-pool to get the final hidden state. Note that the program encoder and latent program decoder make up a VQ-VAE model of programs, with additional conditioning on the specification.

The complete LP architecture is summarized in Figure 2. An end-to-end example run of our architecture is shown in Figure 4. The figure shows the latent sequence generated by the latent predictor on the I/O examples, which are then decoded by the latent program decoder to a predicted program.

4.2 TRAINING

Our LP performs program synthesis using a two-level search, first over latent sequences then over programs. Given program specification, we want to train our latent predictor to produce an informative latent sequence from which our latent program decoder can accurately predict the true program. Our training loss for the LP model consists of three supervised objectives.

The **autoencoder loss** ensures that the latent codes contain information about the program. It is a summation of the reconstruction loss between the autoencoder output $d(\text{qc}(Y), X)$ and true program Y, as well as a commitment loss to train the encoder output $\text{ec}(Y)$ to be close to codebook c. Like in Roy et al. (2018), codebook is not trained but set to the EMA of encoder outputs. This loss is similar to the loss function of a VQ-VAE as in equation 2, but also depends on specification X. This objective trains the latent tokens in the codebook so that they correspond to informative high-level

actions, as well as make sure our latent program decoder can accurately recover true program given the specification and a plan comprising of such actions.

The **latent prediction loss** ensures that latent codes can be predicted from specifications. It is a reconstruction loss between the distribution over latents predicted from the specification $\mathrm{lp}(X)$ and the autoencoded latents $\mathrm{qk}(\mathrm{ec}(Y))$ from the ground-truth program. This is a self-supervised approach that treats the autoencoded latent sequence as the ground-truth high-level plan, and trains the latent predictor to generate the plan using just the program specification X. Note that the program encoder is only used in training, as at test time $\mathrm{ec}(Y)$ is unknown, so the LP model uses $\mathrm{lp}(X)$ instead.

Finally, the **end-to-end loss** ensures that programs can be predicted from specifications. This is especially important because in the reconstruction loss, the latent program decoder receives as input latent codes from the autoencoded latent sequences $\mathrm{ec}(Y)$, whereas at test time, the decoder receives a latent code from the latent predictor $\mathrm{lp}(X)$. This can result in mistakes in the generated program since the decoder has never been exposed to noisy results from the latent predictor. The end-to-end loss alleviates this issue. The end-to-end loss is probability of the correct program Y when predicted from a soft-quantized latent code, given by $\mathrm{lp}(X)^T c$. This has the added benefit of allowing gradient to flow through the latent predictor, training it in an end-to-end way.

In summary, the full loss for a training instance is

$$\mathcal{L}(c, \theta, \phi, \psi) = \underbrace{\log p_\theta \left(Y \mid \mathrm{qc}(\mathrm{ec}_\phi(Y)), X \right) + \beta ||\mathrm{sg}(c) - \mathrm{ec}_\phi(Y)||_2^2}_{\text{autoencoder}}$$
$$+ \underbrace{\log p \left(\mathrm{qk}(\mathrm{ec}_\phi(Y)) \mid \mathrm{lp}_\psi(X) \right)}_{\text{latent prediction}} + \underbrace{\log p_\theta \left(Y \mid \mathrm{lp}_\psi(X)^T c, X \right)}_{\text{end-to-end}} \quad (5)$$

where we explicitly list out θ, ϕ, and ψ representing the parameters of the latent program decoder, program encoder, and latent decoder respectively.

Furthermore, for the first 10K steps of training, we give embeddings of the ground-truth program Y, averaged over every 2^ℓ tokens, as the latent sequence instead of $\mathrm{ec}(Y)$. This pre-training ensures that initially, the coarse plan carries some information about the program so that the attention to the plan has reasonable gradients that can then to propagated to the program encoder afterward pre-training.

4.3 INFERENCE

During inference, we use a multi-level variant of beam search to decode the output probabilities of our LP model. Standard beam search with beam B will generate the top-B most likely programs according to the model, and find the first one (if any) that is consistent with the specification (Parisotto et al., 2017; Devlin et al., 2017). In our case, we first perform beam search for L latent beams, then for $\lfloor B/L \rfloor$ programs per latent sequence. Setting $L = B$ allows for the maximum exploration of the latent space, while setting $L = 1$ reduces our method to standard beam search, or exploitation of the most likely latent decoding. We choose $L = \sqrt{B}$ in our experiments, but explore the effect of various choices of L in Section 5.2.

5 EXPERIMENTS

We now present the results of evaluating our Latent Programmer model in two test domains: synthesis of string transformation programs from examples and code generation from natural language descriptions. We compare our LP model against several strong baselines.

RobustFill [LSTM] is a seq-to-seq LSTM with attention on the input specification, and trained to autoregressively predict the true program. The architecture is comparable to the RobustFill model designed originally for the string transformation tasks in our first domain (Devlin et al., 2017), but easily generalizes to all program synthesis domains. We detail the architecture in Appendix A.

RobustFill [Transformer] alternatively uses a Transformer architecture, equivalent in architecture to the latent planner in our LP model, also trained to autoregressively predict the program. Transformers were found to perform much better than LSTMs in language tasks because they process the entire input as a whole, and have no risk of forgetting past dependencies (Vaswani et al., 2017). This baseline can be also be considered of an ablation of our LP model without the latent codes.

Length	RobustFill Acc.	LP Acc.
1	**94.5**%	94.0%
2	83.9%	**84.6**%
3	**72.8**%	72.2%
4	63.1%	**66.1**%
5	47.1%	**49.8**%
6	40.6%	**43.0**%
7	30.2%	**34.6**%
8	22.7%	**28.4**%
9	18.6%	**27.0**%
10	14.4%	**25.6**%

(a)
(b)

Figure 3: (a): Influence of hidden size on beam-10 accuracy. (b): Beam-10 accuracy of baseline transformer and LP by ground truth program length.

Inputs	Outputs	Program
"Jacob,Ethan,James 11"	"11:J.E.J."	`GetToken_NUMBER_1	Const(:) |`
"Elijah,Daniel,Aiden 3162"	"3162:E.D.A"	`GetToken_ALL_CAPS_1	Const(.) |`
"Rick,Oliver,Mia 26"	"26:R.O.M."	`GetToken_ALL_CAPS_2	Const(.) |`
"Mark,Ben,Sam 510"	"510:M.B.S."	`GetToken_ALL_CAPS_3	Const(.)`

RobustFill	`GetAll_NUMBER	Const(:)	GetToken_ALL_CAPS_2	Const(.)`
LP	`GetAll_NUMBER	Const(:)	GetToken_ALL_CAPS_1	Const(.) |`
`GetToken_ALL_CAPS_2	Const(.)	GetToken_ALL_CAPS_-1	Const(.)`
LP Latent	`TOK_14	TOK_36	TOK_36	TOK_36`

Figure 4: Illustrative string transformation problem where the ground-truth program was long but had repetitive structure. The baseline Transformer was unable to generate the program but our LP model, which first predicts a coarse latent sequence, was able to.

5.1 STRING TRANSFORMATION

The first test domain is a string transformation DSL frequently studied in the program synthesis literature (Parisotto et al., 2017; Devlin et al., 2017; Balog et al., 2020). Tasks in this domain involve finding a program which maps a set of input strings to a corresponding set of outputs. Programs in the DSL are a concatenation of expressions that perform regex-based string transformations (see Appendix A for the full DSL).

We perform experiments on a synthetic dataset generated by sampling programs from the DSL, then the corresponding I/O examples using an heuristic similar to the one used in NSPS (Parisotto et al., 2017) and RobustFill (Devlin et al., 2017) to ensure nonempty output for each input. We consider programs comprising of

Method	Accuracy		
	B = 1	10	100
RobustFill [LSTM]	45%	49%	61%
RobustFill [Transformer]	46%	50%	61%
Latent Programmer	**51**%	**55**%	**68**%

Table 1: Accuracy on string transformation domain.

a concatenation of up to 10 expressions and limit the lengths of strings in the I/O to be at most 100 characters. All models have an embedding size of 128 and hidden size of 512, and the attention layers consist of 3 stacked layers with 4 heads each. For the LP model, we used a latent compression factor $\ell = 2$ and vocabulary size $K = 40$. The models are trained on roughly 25M tasks, and evaluated on 1K held-out ones.

In Table 1, we report the accuracy–the number of time a program was found conforming to the I/O examples–of our method against the baselines. Across all beam sizes, our LP model performed 5-7 percentage points better (over 10% of baseline accuracy) than the next best model.

Latent Beam Size	Accuracy	Distinct n-Grams			
		n = 1	2	3	4
L = 1	50%	0.13	0.23	0.26	0.28
2	51%	0.13	0.24	0.26	0.28
3	**55%**	0.14	0.25	0.28	0.31
5	54%	0.14	0.26	0.29	0.32
10	54%	**0.14**	**0.26**	**0.30**	**0.33**

(a)

2^{ℓ}	Accuracy
2	52%
4	**55%**
8	49%

K	Accuracy
10	48%
40	**55%**
100	51%

(b)

Figure 5: (a): Effect of latent beam size on beam-10 accuracy and number of distinct n-grams (normalized by total number of tokens). (b): Effect of latent length compression ℓ and vocabulary size K on beam-10 accuracy.

5.2 ANALYSIS

We conduct extensive analysis to better understand our LP model in terms of learning, the ability to generate long programs, and diversity in the beams. All results are reported using beam search with a beam size of $B = 10$.

Model Size   Our LP model uses an additional latent code for decoding, which introduces additional parameters into the model than the baseline RobustFill model. To make a fair comparison, we vary the embedding and hidden dimension of all of our evaluated methods, and compare the effect of the number of trainable parameters on the accuracy. Figure 3(a) shows that all methods respond well to an increase in model size. Nevertheless, we see that even when normalized for size, our LP model outperforms baselines by a significant margin.

Program Length   Prior work has shown that program length is a reasonable proxy measure of problem difficulty. We hypothesize that using latent codes is most beneficial when generating long programs. Figure 3(b) shows how ground-truth program length affects the accuracy of our LP model compared to RobustFill, which lacks latent codes. As expected, accuracy decreases with problem complexity. Perhaps surprisingly, though, we see a large improvement in our LP model's ability to handle more complex problems. In Figure 4, we also show an illustrative example in the domain where our LP model found a valid program whereas the RobustFill model did not. In this example, the ground-truth program was long but had a repetitive underlying structure. Our LP model correctly detected this structure, as evidenced by the predicted latent sequence. We show additional examples in Figure 9 of Appendix B.

Latent Beam Size   In multi-level beam search of beam size B, first L latent beams are decoded, then $\lfloor B/L \rfloor$ programs per latent sequence. The latent beam size L controls how much search is performed over latent space. We theorize that higher L will produce more diverse beams; however, too high L can be harmful in missing programs with high joint log-probability. We show the effect of latent beam size on both the beam-10 accuracy and a proxy measure for diversity. Following prior work, we measure diversity by counting the number of distinct n-grams in the beams, normalized by the total number of tokens to bias against long programs (Vijayakumar et al., 2018). We report the results varying L for $B = 10$ in Figure 5(a). As expected, increasing the latent beam size L improves diversity of output programs, but excessively large L harms the final accuracy.

Latent Length and Vocabulary Size   Since the discretization bottleneck is a critical component in generating latent codes in our LP model, we also investigate its performance in conjunction with different settings of hyperparameters. Two important variables for the VQ are the latent length compression factor c, and size of latent vocabulary K. If c is too small, the latent space becomes too large to search; on the other hard, too large c can mean individual latent tokens cannot encoded the information needed to reconstruct the program. Similarly, we expect that too small of a vocabulary K can limit the expressiveness of the latent space, but too large K can make predicting the correct latent code too difficult. We confirm these observations in our evaluation when we vary c and K as shown in Figure 5(b) and Figure 5(c).

Docstring	Program
get an environment variable	```def getenv(key, default=None):```
``` return environ.get(key, default)```
return a list of the words in the string s	```def split(s, sep=None, maxsplit=-1):```
``` return s.split(sep, maxsplit)```

Figure 6: Example problems from the Python code generation dataset.

5.3 PYTHON CODE GENERATION

Our next test domain is a Python code generation (CG) task, which involves generating code for a function that implements a natural-language specification. The dataset used consists of 111K python examples, which consist of a docstring and corresponding code snippet, collected from Github (Wan et al., 2018). An example docstring and program from the dataset is shown in Figure 6.

We used a language-independent tokenizer jointly on data (Kudo & Richardson, 2018), and processed the dataset into a vocabulary of 35K sub-word tokens. Furthermore, following Wei et al. (2019), we set the maximum length of the programs to be 150 tokens resulting in 85K examples. Across all models, we set the embedding size to be 256 and hidden size to be 512, and the attention layers consist of 6 stacked layers with 16 heads each, similar to in neural machine translation (Vaswani et al., 2017). For the LP model, we used a latent compression factor $c = 2$ and vocabulary size $K = 400$ after a hyperparameter search. The models are evaluated on 1K held-out examples.

We initially found that it was difficult for the program encoder to detect latent sequence structure in the ground-truth programs as is due to the noise in variable names. To remedy this, we used an abstract syntax tree (AST) parser on the ground-truth programs to replace the i-th function argument and variable appearing the program with the token `<ARG_i>` and `<VAR_i>`, respectively. This was only used in training the program encoder and did not impact evaluation.

Method	BLEU		
	B = 1	10	100
Base (Wei et al., 2019)	10.4	-	-
Dual (Wei et al., 2019)	12.1	-	-
RobustFill [LSTM]	11.4	14.8	16.0
RobustFill [Transformer]	12.1	15.5	17.2
Latent Programmer	**14.0**	**18.6**	**21.3**

Table 2: BLEU score on code generation task.

We evaluate performance by computing the best BLEU score among the output beams (Papineni et al., 2002). We computed BLEU as the geometric mean of n-gram matching precision scores up to $n = 4$. Table 2 shows that our LP model outperforms the baselines. From the results, it can be seen that this is a difficult task, which may be due to the ambiguity in specifying code from a short docstring description. As evidence, we additionally include results from a recent work that proposed seq-to-seq CG models on the same data that performed similar to our baselines (Wei et al., 2019). These results show that improvements due to the LP model exist even in difficult CG domains. For example docstrings and code generated by the LP Model, refer to Figure 9 in Appendix B.

6 CONCLUSION

In this work we proposed the Latent Programmer (LP), a novel neural program synthesis technique that leverages a structured latent sequences to guide search. The LP model consists of a latent predictor, which maps the input specification to a sequence of discrete latent variables, and a latent program decoder that generates a program token-by-token while attending to the latent sequence. The latent predictor was trained via a self-supervised method in which a discrete autoencoder of programs was learned using a discrete bottleneck, specifically a VQ-VAE (van den Oord et al., 2017), and the latent predictor tries to predict the autoencoded sequence as if it were the ground-truth. During inference, the LP model first searches in latent space for discrete codes, then conditions on those codes to search over programs. Empirically, we showed that the Latent Programmer outperforms state-of-the-art baselines as Robustfill (Devlin et al., 2017), which ignore latent structure. Exciting future avenues of investigation include achieving better performance by grounding the latent vocabulary and generalizing our method to other tasks in natural language and structured prediction.

REFERENCES

Rajeev Alur, Rastislav Bodík, Garvit Juniwal, Milo M. K. Martin, Mukund Raghothaman, Sanjit A. Seshia, Rishabh Singh, Armando Solar-Lezama, Emina Torlak, and Abhishek Udupa. Syntax-guided synthesis. In *Formal Methods in Computer-Aided Design, FMCAD 2013, Portland, OR, USA, October 20-23, 2013*, pp. 1–8. IEEE, 2013.

Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. In *International Conference on Learning Representations (ICLR)*, 2016.

Matej Balog, Alexander L. Gaunt, Marc Brockschmidt, Sebastian Nowozin, and Daniel Tarlow. Deepcoder: Learning to write programs. In *International Conference on Learning Representations (ICLR)*, 2017.

Matej Balog, Rishabh Singh, Petros Maniatis, and Charles Sutton. Neural program synthesis with a differentiable fixer. *CoRR*, abs/2006.10924, 2020. URL https://arxiv.org/abs/2006.10924.

Kai-Wei Chang, Akshay Krishnamurthy, Alekh Agarwal, Daume III, and John Langford. Learning to search better than your teacher. In *International Conference on Machine Learning (ICML)*, 2015.

Xinyun Chen, Chang Liu, and Dawn Song. Execution-guided neural program synthesis. In *International Conference on Learning Representations (ICLR)*, 2019.

Hal Daumé, III, John Langford, and Daniel Marcu. Search-based structured prediction. *Machine Learning Journal*, 2009.

Jacob Devlin, Jonathan Uesato, Surya Bhupatiraju, Rishabh Singh, Abdel-rahman Mohamed, and Pushmeet Kohli. Robustfill: Neural program learning under noisy I/O. *CoRR*, abs/1703.07469, 2017. URL http://arxiv.org/abs/1703.07469.

Kevin Ellis, Maxwell I. Nye, Yewen Pu, Felix Sosa, Josh Tenenbaum, and Armando Solar-Lezama. Write, execute, assess: Program synthesis with a REPL. In *Neural Information Processing Systems (NeurIPS)*, 2019.

Kevin Ellis, Catherine Wong, Maxwell Nye, Mathias Sable-Meyer, Luc Cary, Lucas Morales, Luke Hewitt, Armando Solar-Lezama, and Joshua B. Tenenbaum. Dreamcoder: Growing generalizable, interpretable knowledge with wake-sleep bayesian program learning. *CoRR*, abs/2006.08381, 2020. URL https://arxiv.org/abs/2006.08381.

Rafael Gómez-Bombarelli, Jennifer N Wei, David Duvenaud, José Miguel Hernández-Lobato, Benjamín Sánchez-Lengeling, Dennis Sheberla, Jorge Aguilera-Iparraguirre, Timothy D Hirzel, Ryan P Adams, and Alán Aspuru-Guzik. Automatic chemical design using a Data-Driven continuous representation of molecules. *ACS Cent Sci*, 4(2):268–276, February 2018.

Sumit Gulwani. Automating string processing in spreadsheets using input-output examples. In *PoPL'11, January 26-28, 2011, Austin, Texas, USA*, 2011.

Sumit Gulwani, Oleksandr Polozov, and Rishabh Singh. Program synthesis. *Foundations and Trends in Programming Languages*, 4(1-2):1–119, 2017. doi: 10.1561/2500000010. URL https://doi.org/10.1561/2500000010.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with gumbel-softmax. In *International Conference on Learning Representations (ICLR)*, 2017.

Łukasz Kaiser, Aurko Roy, Ashish Vaswani, Niki Parmar, Samy Bengio, Jakob Uszkoreit, and Noam Shazeer. Fast decoding in sequence models using discrete latent variables. In *International Conference on Machine Learning (ICML)*, 2018.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. In *International Conference on Learning Representations (ICLR)*, 2014.

John R Koza. Genetic programming as a means for programming computers by natural selection. *Statistics and computing*, 4(2):87–112, 1994.

Taku Kudo and John Richardson. SentencePiece: A simple and language independent subword tokenizer and detokenizer for neural text processing. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pp. 66–71, November 2018.

Woosuk Lee, Kihong Heo, Rajeev Alur, and Mayur Naik. Accelerating search-based program synthesis using learned probabilistic models. In *Conference on Programming Language Design and Implementation (PLDI)*, pp. 436–449, June 2018.

Chris J. Maddison, Andriy Mnih, and Yee Whye Teh. The concrete distribution: A continuous relaxation of discrete random variables. In *International Conference on Learning Representations (ICLR)*, 2017.

Zohar Manna and Richard J. Waldinger. Toward automatic program synthesis. *Commun. ACM*, 14 (3):151–165, 1971.

Yishu Miao and Phil Blunsom. Language as a latent variable: Discrete generative models for sentence compression. *CoRR*, abs/1609.07317, 2016. URL http://arxiv.org/abs/1609.07317.

Maxwell I. Nye, Luke B. Hewitt, Joshua B. Tenenbaum, and Armando Solar-Lezama. Learning to infer program sketches. In *International Conference on Machine Learning (ICML)*, 2019.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: A method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting on Association for Computational Linguistics*, pp. 311–318. Association for Computational Linguistics, 2002.

Emilio Parisotto, Abdel-rahman Mohamed, Rishabh Singh, Lihong Li, Dengyong Zhou, and Pushmeet Kohli. Neuro-symbolic program synthesis. In *International Conference on Learning Representations (ICLR)*, 2017.

Ratish Puduppully, Li Dong, and Mirella Lapata. Data-to-text generation with content selection and planning. In *The Thirty-Third AAAI Conference on Artificial Intelligence, AAAI 2019, The Thirty-First Innovative Applications of Artificial Intelligence Conference, IAAI 2019, The Ninth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2019, Honolulu, Hawaii, USA, January 27 - February 1, 2019*, pp. 6908–6915. AAAI Press, 2019. doi: 10.1609/aaai.v33i01.33016908. URL https://doi.org/10.1609/aaai.v33i01.33016908.

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. *CoRR*, abs/1401.4082, 2014. URL https://arxiv.org/abs/1401.4082.

Stephane Ross, Geoffrey Gordon, and Drew Bagnell. A reduction of imitation learning and structured prediction to No-Regret online learning. In Geoffrey Gordon, David Dunson, and Miroslav Dudík (eds.), *Conference on Artificial Intelligence and Statistics (AISTATS)*, volume 15 of *Proceedings of Machine Learning Research*, pp. 627–635, Fort Lauderdale, FL, USA, 2011. PMLR.

Aurko Roy, Ashish Vaswani, Arvind Neelakantan, and Niki Parmar. Theory and experiments on vector quantized autoencoders. *arXiv*, May 2018.

Eric Schkufza, Rahul Sharma, and Alex Aiken. Stochastic superoptimization. In *Proceedings of the Eighteenth International Conference on Architectural Support for Programming Languages and Operating Systems*, ASPLOS '13, pp. 305–316, New York, NY, USA, 2013. Association for Computing Machinery. ISBN 9781450318709. doi: 10.1145/2451116.2451150. URL https://doi.org/10.1145/2451116.2451150.

Armando Solar-Lezama, Liviu Tancau, Rastislav Bodík, Sanjit A. Seshia, and Vijay A. Saraswat. Combinatorial sketching for finite programs. In *Conference on Architectural Support for Programming Languages and Operating Systems, ASPLOS 2006, San Jose, CA, USA, October 21-25, 2006*, pp. 404–415. ACM, 2006.

Phillip D Summers. A methodology for lisp program construction from examples. *Journal of the ACM (JACM)*, 24(1):161–175, 1977.

Abhishek Udupa, Arun Raghavan, Jyotirmoy V Deshmukh, Sela Mador-Haim, Milo M K Martin, and Rajeev Alur. TRANSIT: Specifying protocols with concolic snippets. In *Conference on Programming Language Design and Implementation (PLDI)*, pp. 287–296. Association for Computing Machinery, 2013.

Aäron van den Oord, Oriol Vinyals, and Koray Kavukcuoglu. Neural discrete representation learning. In *Neural Information Processing Systems (NeurIPS)*, 2017.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Neural Information Processing Systems (NeurIPS)*, 2017.

Ashwin K. Vijayakumar, Michael Cogswell, Ramprasaath R. Selvaraju, Qing Sun, Stefan Lee, David J. Crandall, and Dhruv Batra. Diverse beam search: Decoding diverse solutions from neural sequence models. In *AAAI*, 2018.

Y. Wan, Z. Zhao, M. Yang, G. Xu, H. Ying, J. Wu, and P. S. Yu. Improving automatic source code summarization via deep reinforcement learning. In *2018 33rd IEEE/ACM International Conference on Automated Software Engineering (ASE)*, pp. 397–407, 2018.

Bolin Wei, Ge Li, Xin Xia, Zhiyi Fu, and Zhi Jin. Code generation as a dual task of code summarization. In *Neural Information Processing Systems (NeurIPS)*, 2019.

Amit Zohar and Lior Wolf. Automatic program synthesis of long programs with a learned garbage collector. In *Neural Information Processing Systems (NeurIPS)*, 2018.