SAMPLE-EFFICIENT MULTI-OBJECTIVE MOLECULAR OPTIMIZATION WITH GFLOWNETS

ABSTRACT

Many crucial scientific problems involve designing novel molecules with desired properties, which can be formulated as an expensive black-box optimization problem over the discrete chemical space. Computational methods have achieved initial success but still struggle with simultaneously optimizing multiple competing properties in a sample-efficient manner. In this work, we propose a multi-objective Bayesian optimization (MOBO) algorithm leveraging the hypernetwork-based GFlowNets (HN-GFN) as an acquisition function optimizer, with the purpose of sampling a diverse batch of candidate molecular graphs from an approximate Pareto front. Using a single preference-conditioned hypernetwork, HN-GFN learns to explore various trade-offs between objectives. Inspired by reinforcement learning, we further propose a hindsight-like off-policy strategy to share high-performing molecules among different preferences in order to speed up learning for HN-GFN. Through synthetic experiments, we illustrate that HN-GFN has adequate capacity to generalize over preferences. Extensive experiments show that our framework outperforms the best baselines by a large margin in terms of hypervolume in various real-world MOBO settings.

1 INTRODUCTION

Designing novel molecular structures with desired properties, also referred to as molecular optimization, is a crucial task with great application potential in scientific fields ranging from drug discovery to material design. Molecular optimization can be naturally formulated as a black-box optimization problem over the discrete chemical space, which is combinatorially large (Polishchuk et al., 2013). Recent years have witnessed the trend of leveraging computational methods, such as deep generative models (Jin et al., 2018) and combinatorial optimization algorithms (You et al., 2018; Jensen, 2019), to facilitate the optimization. However, the applicability of most prior approaches in real-world scenarios is hindered by two practical constraints: (i) realistic oracles (e.g., wet-lab experiments and high-fidelity simulations) require substantial costs to synthesize and evaluate molecules (Gao et al., 2022), and (ii) chemists commonly seek to optimize multiple properties of interest simultaneously (Jin et al., 2020b). For example, in addition to effectively inhibiting a disease-associated target, an ideal drug is desired to be easily synthesizable and non-toxic.

Bayesian optimization (BO) (Jones et al., 1998; Shahriari et al., 2015) provides a sample-efficient framework for globally optimizing expensive black-box functions. The basic idea is to construct a cheap-to-evaluate *surrogate model*, typically a Gaussian Process (GP) (Rasmussen, 2003), to approximate the true function (also known as the *oracle*) on the observed dataset. The core objective of BO is to optimize an *acquisition function* (built upon the surrogate model) in order to obtain informative candidates with high utility for the next round of evaluations. This loop is repeated until the evaluation budget is exhausted. Owing to the fact that a large batch of candidates can be evaluated in parallel in biochemical experiments, we perform batch BO (with large-batch and low-round settings) to significantly shorten the entire cycle of optimization.

As multi-objective optimization (MOO) problems are prevalent in scientific and engineering applications, MOBO also received broad attention and achieved promising performance by effectively optimizing differentiable acquisition functions (Daulton et al., 2020). Nevertheless, it is less prominent in discrete problems, especially considering batch settings. The difficulty lies in the fact that no gradients can be leveraged to navigate the discrete space for efficient and effective optimization of

Figure 1: MOBO loop for molecular optimization using an evidential surrogate model $\mathcal{M}$ for uncertainty estimation and HN-GFN for acquisition function optimization. In each round, the policy π_θ is trained with reward function R_λ, where λ is sampled from $\mathrm{Dir}(\alpha)$ per iteration. A new batch of candidates is sampled from the approximate Pareto front according to $\lambda_{\text{target}} \in \Lambda$.

the acquisition function. Although most of the existing discrete molecular optimization methods can be adopted as the *acquisition function optimizer* to alleviate this issue, they suffer from the following limitations. 1) Most approaches do not explicitly discuss the diversity of the proposed candidates, which is a key consideration in batch settings as the surrogate model cannot exactly reproduce the oracle's full behaviors. Therefore, we not only want to cover more high modes of the surrogate model but also to obtain candidates that bring additional information about the search space. 2) Most multi-objective methods (Xie et al., 2021; Fu et al., 2022) simply rely on a scalarization function, parameterized by a predefined *preference vector* reflecting the trade-off between objectives, and turn the MOO problem into a single-objective one. Unfortunately, an ideal trade-off is unclear before optimization (even with domain knowledge), and many potential trade-offs of interest are worth exploring. In principle, it is possible to independently train multiple optimization models, each conditioned on a distinct preference vector, to cover the objective space. Practically, this trivial strategy cannot efficiently scale with the number of objectives (Navon et al., 2021).

The recently proposed GFlowNets (Bengio et al., 2021a) are a class of generative models over discrete objects (e.g., molecular graphs) that aim to learn a stochastic policy for sequentially constructing objects with a probability proportional to a reward function (e.g., the acquisition function). Hence, GFlowNets possess merit in generating diverse and high-reward objects, which makes them appealing in the batch BO context where exploration plays a significant role (Jain et al., 2022).

In this work, we present a MOBO algorithm based on GFlowNets for sample-efficient multi-objective molecular optimization. We propose a hypernetwork-based GFlowNet (HN-GFN) as the acquisition function optimizer within MOBO to sample a diverse batch of candidates from an approximate Pareto front. Instead of defining a fixed reward function as usual in past work (Bengio et al., 2021a), we train a unified GFlowNet on the distribution of reward functions (*random scalarizations* parameterized by preference vectors) and control the policy using a single preference-conditioned hypernetwork. While sampling candidates, HN-GFN explores various trade-offs between competing objectives flexibly by varying the input preference vector. Inspired by Hindsight Experience Replay (Andrychowicz et al., 2017) in RL, we further introduce a hindsight-like off-policy strategy to share high-performing molecules among different preferences and speed up learning for HN-GFN. As detailed in our reported experiments, we first evaluate HN-GFN through synthetic experiments to verify that HN-GFN is capable of generalizing over preference vectors, then apply the proposed framework to real-world scenarios. Remarkably, our framework outperforms the best baselines by 60% and 24% (relative improvement in terms of hypervolume in the settings with two and four objectives), respectively. Our key contributions are summarized below:

- We propose HN-GFN, a unified GFlowNet that can efficiently sample candidates from an approximate Pareto front using a single hypernetwork.

- We introduce a hindsight-like off-policy strategy to speed up learning in HN-GFN.

- Experiments verify that our MOBO algorithm based on HN-GFN can find high-quality Pareto front more efficiently compared to state-of-the-art baselines.

2 RELATED WORK

2.1 MOLECULAR OPTIMIZATION

Molecular optimization has been approached with a wide variety of computational methods, which can be mainly grouped into three categories: 1) **Latent space optimization** methods perform the optimization over the continuous and low-dimensional latent space learned by generative models such as variational autoencoders (VAEs) (Gómez-Bombarelli et al., 2018). These methods require the latent representations to be discriminative, but the training of the generative model is decoupled from the optimization objectives, imposing challenges for optimization (Tripp et al., 2020). Instead of navigating the latent space, combinatorial optimization methods search for the desired molecular structures directly in the explicit discrete space with 2) **evolutionary algorithms** (Jensen, 2019) and 3) **deep neural networks** to guide the searching (You et al., 2018). However, most prior methods only focus on optimizing a single property, from non-biological properties such as drug-likeliness (QED) (Bickerton et al., 2012) and synthetic accessibility (SA) (Ertl & Schuffenhauer, 2009), to biological properties that measure the binding energy to a protein target (Bengio et al., 2021a).

Despite the above advances in single property optimization, multi-objective molecular optimization has recently received wide attention (Jin et al., 2020b; Xie et al., 2021; Fu et al., 2022). For example, MARS (Xie et al., 2021) employs Markov chain Monte Carlo (MCMC) sampling to find novel molecules satisfying several properties. However, most approaches require a notoriously large number of oracle calls to evaluate molecules on-the-fly (Jin et al., 2020b; Xie et al., 2021). In contrast, our MOBO framework based on HN-GFN tackles this problem in a sample-efficient manner.

2.2 GFLOWNET

GFlowNets (Bengio et al., 2021a) aim to sample composite objects proportionally to a reward function, instead of maximizing it as usual in RL (Sutton & Barto, 2018). GFlowNets are related to the MCMC methods due to the same objective, while amortizing the high cost of MCMC sampling (mixing between modes) over training a generative model (Zhang et al., 2022). GFlowNets have made impressive progress in various applications, such as active learning (Jain et al., 2022), discrete probabilistic modeling (Zhang et al., 2022), and Bayesian structure learning (Deleu et al., 2022). For a thorough discussion and mathematical treatment, we refer the readers to Bengio et al. (2021b)

2.3 BAYESIAN OPTIMIZATION FOR DISCRETE SPACES

While the application of BO in continuous domains has proliferated during the last decade, effort in applying it to discrete spaces is lacking. It is much more challenging to construct surrogate models and optimize acquisition functions in discrete spaces, compared to continuous spaces. One common approaches is to define GPs with discrete kernels (Moss et al., 2020) and solve the acquisition function optimization problem with evolutionary algorithms (Kandasamy et al., 2018). Moreover, AmortizedBO (Swersky et al., 2020) propose to augment the evolutionary algorithms with RL.

3 BACKGROUND

3.1 PROBLEM FORMULATION

We address the problem of searching over a discrete chemical space $\mathcal{X}$ to find molecular graphs $x \in \mathcal{X}$ that maximize a *vector-valued objective* $f(x) = \big(f_1(x), f_2(x), \ldots, f_M(x)\big) : \mathcal{X} \to \mathbb{R}^M$, where f_m is a black-box function (also known as the oracle) evaluating a certain property of molecules. Practically, realistic oracles are extremely expensive to evaluate with either high-fidelity simulations or wet-lab experiments. We thus propose to perform optimization in as few oracle evaluations as possible, since the sample efficiency is paramount in such scenario.

There is typically no single optimal solution to the MOO problem, as different objectives may contradict each other. Consequently, the goal of most approaches is to recover the *Pareto front* – the set of *Pareto optimal* solutions which cannot be improved in any one objective without deteriorating another (Daulton et al., 2020). In the context of maximization, a solution $f(x)$ is said to *Pareto dominates* another solution $f(x')$ iff $f_m(x) \geq f_m(x') \ \forall m = 1, \ldots, M$ and $\exists m'$ such that $f_{m'}(x) > f_{m'}(x')$, and we denote $f(x) \succ f(x')$. A solution $f(x^*)$ is *Pareto optimal* if not Pareto dominated by any solution. The Pareto front can be written as $\mathcal{P}^* = \{f(x^*) : \{f(x) : f(x) \succ f(x^*)\} = \emptyset\}$.

The quality of a finite approximate Pareto front $\mathcal{P}$ is commonly measured by *hypervolume* (HV) (Zitzler & Thiele, 1999) – the M-dimensional Lebesgue measure λ_M of the space dominated by $\mathcal{P}$ and bounded from below by a given reference point $\boldsymbol{r} \in \mathbb{R}^M$: $HV(\mathcal{P}, \boldsymbol{r}) = \lambda_M(\cup_{i=1}^{|\mathcal{P}|}[\boldsymbol{r}, y_i])$, where $[\boldsymbol{r}, y_i]$ denotes the hyper-rectangle bounded by $\boldsymbol{r}$ and $y_i = f(x_i)$.

3.2 Batch Bayesian optimization

Bayesian optimization (BO) (Shahriari et al., 2015) provides a model-based iterative framework for sample-efficient black-box optimization. Given an observed dataset $\mathcal{D}$, BO relies on a Bayesian *surrogate model* $\mathcal{M}$ to estimate a posterior distribution over the true oracle evaluations. Equipped with the surrogate model, an *acquisition function* $\alpha : \mathcal{X} \to \mathbb{R}$ is induced to assign the utility values to candidate objects for deciding which to next evaluate the oracle. Compared with the costly oracle, the cheap-to-evaluate acquisition function can be efficiently optimized. We consider the scenario where the oracle is given an evaluation budget of N rounds with fixed batches of size b.

To be precise, we have access to a random initial dataset $\mathcal{D}_0 = \{(x_i^0, y_i^0)\}_{i=1}^n$, where $y_i^0 = f(x_i^0)$ is true oracle evaluation. In each round $i \in \{1, \ldots, N\}$, the acquisition function is maximized to yield a batch of candidates $\mathcal{B}_i = \{x_j^i\}_{j=1}^b$ to be evaluate in parallel on the oracle $y_j^i = f(x_j^i)$. The observed dataset $\mathcal{D}_{i-1}$ is then augmented for the next round: $\mathcal{D}_i = \mathcal{D}_{i-1} \cup \{(x_1^i, y_j^i)\}_{j=1}^b$.

4 Method

In this section, we present the proposed MOBO algorithm based on hypernetwork-based GFlowNet (HN-GFN), shown in Figure 1. Our key idea is to extend GFlowNets as the acquisition function optimizer for MOBO, with the objective to sample a diverse batch of candidates from the approximate Pareto front. To begin, we introduce GFlowNets in the context of molecule design, then describe how GFlowNet can be biased by a preference-conditioned hypernetwork to sample molecules according to various trade-offs between objectives. Next, we propose a hindsight-like off-policy strategy to speed up learning in HN-GFN. Lastly, we introduce the evidential surrogate model.

4.1 Preliminaries

GFlowNets (Bengio et al., 2021a) seek to learn a stochastic policy π for sequentially constructing discrete objects $x \in \mathcal{X}$ with a probability $\pi(x) \propto R(x)$, where $\mathcal{X}$ is a compositional space and $R : \mathcal{X} \to \mathbb{R}_{\geq 0}$ is a non-negative reward function. The generation process of object $x \in \mathcal{X}$ can be represented by a sequence of discrete *actions* $a \in \mathcal{A}$ that incrementally modify a partially constructed object, which is denoted as *state* $s \in \mathcal{S}$. Let generation process begin at a special initial state s_0 and terminate with a special action indicating that the object is complete ($s = x \in \mathcal{X}$), the construction of an object x can be defined as a complete trajectory $\tau = (s_0 \to s_1 \to \cdots \to s_n = x)$.

Following fragment-based molecule design (Bengio et al., 2021a; Xie et al., 2021), we first define a vocabulary of building blocks (molecule fragments), then generate molecular graphs by sequentially attaching a fragment to an atom of the partially constructed molecules. There are multiple action sequences leading to the same state, and no fragment deleting actions, the space of possible action sequences can thus be denoted by a directed acyclic graph (DAG) $\mathcal{G} = (\mathcal{S}, \mathcal{E})$, where the edges in $\mathcal{E}$ are transitions $s \to s'$ from one state to another. To learn the aforementioned desired policy, Bengio et al. (2021a) propose to see the DAG structure as a *flow network*.

Markovian flows. Bengio et al. (2021b) first define a *trajectory flow* $F : \mathcal{T} \to \mathbb{R}_{\geq 0}$ on the set of all complete trajectories $\mathcal{T}$ to measure the unnormalized density. The *edge flow* and *state flow* can then be defined as $F(s \to s') = \sum_{s \to s' \in \tau} F(\tau)$ and $F(s) = \sum_{s \in \tau} F(\tau)$, respectively. The

trajectory flow F determines a probability measure $P(\tau) = \frac{F(\tau)}{\sum_{\tau \in \mathcal{T}} F(\tau)}$. If flow F is *Markovian*, the forward transition probabilities P_F can be computed as $P_F(s'|s) = \frac{F(s \rightarrow s')}{F(s)}$.

Flow matching objective. A flow is *consistent* if the following *flow consistency equation* is satisfied $\forall s \in \mathcal{S}$:

$$F(s) = \sum_{s' \in Pa_{\mathcal{G}}(s)} F(s' \rightarrow s) = R(s) + \sum_{s'':s \in Pa_{\mathcal{G}}(s'')} F(s \rightarrow s'') \tag{1}$$

where $Pa_{\mathcal{G}}(s)$ is a set of parents of s in $\mathcal{G}$. As proved in Bengio et al. (2021a), if the flow consistency equation is satisfied with $R(s) = 0$ for non-terminal state s and $F(x) = R(x) \geq 0$ for terminal state x, a policy π defined by the forward transition probability $\pi(s'|s) = P_F(s'|s)$ samples object x with a probability $\pi(x) \propto R(x)$. GFlowNets propose to approximate the edge flow $F(s \rightarrow s')$ using a neural network $F_\theta(s, s')$ with enough capacity, such that the flow consistency equation is respected at convergence. To achieve this, (Bengio et al., 2021a) define a temporal difference-like (Sutton & Barto, 2018) learning objective, called flow-matching (FM):

$$\mathcal{L}_{\text{FM}}(s, R; \theta) = \left(\log \frac{\sum_{s' \in Pa_{\mathcal{G}}(s)} F_\theta(s', s)}{R(s) + \sum_{s'':s \in Pa_{\mathcal{G}}(s'')} F_\theta(s, s'')} \right)^2 \tag{2}$$

Bengio et al. (2021a) prove that we can use any exploratory policy $\widetilde{\pi}$ with full support to sample training trajectories and obtain the consistent flow $F_\theta(s, s')$ by minimizing the FM objective. Consequently, a policy defined by this approximate flow $\pi_\theta(s'|s) = P_{F_\theta}(s'|s) = \frac{F_\theta(s \rightarrow s')}{F_\theta(s)}$ can also sample objects x with a probability $\pi_\theta(x)$ proportionally to reward $R(x)$. Practically, the training trajectories are sampled from an exploratory policy which is a mixture between P_{F_θ} and a uniform distribution over allowed actions (Bengio et al., 2021a).

4.2 Hypernetwork-based GFlowNets

Our proposed HN-GFN aims at sampling a diverse batch of candidates from the approximate Pareto front with a unified model. A common approach to MOO is to decompose it into a set of scalar optimization problems with different scalarization functions and apply standard single-objective optimization methods to gradually approximate the Pareto front (Knowles, 2006; Zhang & Li, 2007). We here consider convex combinations (weighted sum) of the objectives. Let $\lambda = (\lambda_i, \cdots, \lambda_M) \in S_M$ be a preference vector defining the trade-off between the competing properties, where $S_M = \{\lambda \in \mathbb{R}^m | \sum_i \lambda_i = 1, \lambda_i \geq 0\}$ is the $M - 1$ simplex. Then, the scalarization function can be formulated as $s_\lambda(x) = \sum_i \lambda_i f^i(x)$.

To support parallel evaluations in BO, one can obtain candidates according to different scalarizations (Daulton et al., 2020). Practically, this approach hardly scales efficiently with the number of objectives for discrete problems. Taking GFlowNet as an example, we need to train multiple GFlowNets independently for each choice of the reward function $R_\lambda(x) = s_\lambda(x)$ to cover the objective space:

$$\theta_\lambda^* = \arg\min_\theta \mathbb{E}_{s \in \mathcal{S}} \mathcal{L}_{\text{FM}}(s, R_\lambda) \tag{3}$$

Our key motivation is to design a unified GFlowNet to sample candidates according to different reward functions, even ones not seen during training. Instead of defining the reward function with a fixed preference vector λ, we propose to train a preference-conditioned GFlowNet on a distribution of reward functions R_λ, where the preference vector λ is sampled from a simplex S_M:

$$\theta^* = \arg\min_\theta \mathbb{E}_{\lambda \in S_M} \mathbb{E}_{s \in \mathcal{S}} \mathcal{L}_{\text{FM}}(s, R_\lambda) \tag{4}$$

Remarks. Our proposed optimization scheme of training a single model to fit a family of loss functions fits into the framework of YOTO (Dosovitskiy & Djolonga, 2019). As proved in Dosovitskiy & Djolonga (2019), assuming an infinite model capacity, the proposed optimization scheme (Eq. 4) is as powerful as the original one (Eq. 3), since the solutions to both loss functions coincide. Nevertheless, the assumption of infinite capacity is extremely strict and hardly holds, so how to design the conditioning mechanism in practice becomes crucial.

Algorithm 1 Training procedure for HN-GFN with the hindsight-like off-policy strategy

---

Input: dataset $\mathcal{D} = \{(x_i, f(x_i))\}_{i=1}^n$, reward function R, minibatch size m, set of target preference vectors Λ, proportion of hindsight-like strategy γ, replay buffers $\{\mathcal{R}_\lambda\}_{\lambda \in \Lambda}$
while not converged **do**
    Flag $\sim$ Bernoulli(γ)
    if Flag $= 1$ **then**
        $\lambda \sim \Lambda$
        Sample $\frac{m}{2}$ trajectories from replay buffer $\mathcal{R}_\lambda$
    else
        $\lambda \sim \text{Dir}(\alpha)$
        Sample $\frac{m}{2}$ trajectories from dataset $\mathcal{D}$
    end if
    $\theta = (\theta_{\text{mpnn}}, h(\lambda; \phi))$
    Sample $\frac{m}{2}$ trajectories from policy $\widetilde{\pi}$ and store terminal states x in $\mathcal{R}_\lambda$ for all $\lambda \in \Lambda$
    Compute reward $R_\lambda(x)$ on terminal states x from each trajectory in the minibatch
    Update parameters θ_{mpnn} and ϕ with a stochastic gradient descent step w.r.t Eq. 2
end while

4.2.1 HYPERNETWORK-BASED CONDITIONING MECHANISM

We propose to condition the GFlowNets on the preference vectors via hypernetworks (Ha et al., 2016). Hypernetworks are deep networks that generate the weights of a target network based on inputs. In vanilla GFlowNets, the flow predictor F_θ is parameterized with the MPNN (Gilmer et al., 2017) over the graph of molecular fragments, with two prediction heads approximating $F(s, s')$ and $F(s)$ based on the node and graph representations respectively. These two heads are parameterized with multi-layer perceptrons (MLPs).

One can view the training of HN-GFN as learning an agent to perform multiple policies that correspond to different goals (reward functions R) defined in the same environment (state space $\mathcal{S}$ and action space $\mathcal{A}$). Therefore, we propose to only condition the weights of prediction heads θ_{pred} with hypernetworks, while sharing the weights of MPNN θ_{mpnn}, leading to more generalizable state representations. More precisely, a hypernetwork $h(\cdot; \phi)$ takes as inputs the preference vector λ to output the weights $\theta_{\text{pred}} = h(\lambda; \phi)$ of prediction heads in the flow predictor F_θ. For brevity, we write $\theta = (\theta_{\text{mpnn}}, \theta_{\text{pred}})$. Following Navon et al. (2021), we parametrize h using a MLP with multiple heads, each generating weights for different layers of the target network.

4.2.2 AS THE ACQUISITION FUNCTION OPTIMIZER

Training. At each iteration, we randomly sample a new preference vector λ from a Dirichlet distribution $\text{Dir}(\alpha)$. Then HN-GFN is trained in a usual manner with the reward function set as $R_\lambda(x)$.

Sampling. At the end of each round, we sample $\frac{b}{l}$ molecules per preference vector $\lambda_{\text{target}} \in \Lambda$ and evaluate them on the oracle, where Λ is a set of l pre-sampled target preference vectors. As the number of objectives increases, we choose a larger l to cover the objective space.

4.3 HINDSIGHT-LIKE OFF-POLICY STRATEGY

Resorting to a single hypernetwork, HN-GFN learns a family of policies to achieve various goals, i.e., one can treat sampling high-reward molecules with respect to each preference vector as a separate goal. Our key insight is that each goal can be achieved faster by harvesting high-reward molecules sampled from other policies. As verified experimentally in Jain et al. (2022), since the FM objective is *off-policy* and *offline*, the target policy can be trained with trajectories sampled from other policies for better exploration, so long as the assumption of full support holds.

Inspired by Hindsight Experience Replay (Andrychowicz et al., 2017) in RL, we propose to share high-performing molecules among policies. The pivotal idea is to re-examine these molecules with a different preference vector. Because there are infinite possible preference vectors, here we only focus on all $\lambda_{\text{target}} \in \Lambda$, which are based on to sample candidates for the next round of evaluations.

Figure 2: **Left**: The distribution of Top-100 JNK3 scores over different preference vectors. **Right**: The progression of the average Top-20 rewards over the course of training of the HN-GFN in optimizing GSK3β and JNK3 with different strategies.

To do this, we build a replay buffer for each $\lambda_{\text{target}} \in \Lambda$. After sampling some trajectories during training, we store in the replay buffers the complete object x with the reward $R_{\lambda_{\text{target}}}(x)$.

Algorithm 1 describes the training procedure for HN-GFN with the proposed hindsight-like strategy. At each training step, we sample a preference vector from a mixture between $\text{Dir}(\alpha)$ and a uniform distribution over Λ: $(1 - \gamma)\text{Dir}(\alpha) + \gamma\text{Uniform}$. If Λ is chosen, we construct half of the training batch with offline trajectories from the corresponding replay buffer of molecules encountered during training with the highest rewards. Otherwise, we incorporate offline trajectories from the observed dataset instead to ensure that HN-GFN samples correctly in the vicinity of the observed Pareto front.

4.4 EVIDENTIAL SURROGATE MODEL

While GPs are well-established in continuous spaces, they scale poorly with the number of observations and do not perform well in discrete spaces (Swersky et al., 2020). There has been significant work in efficiently training non-Bayesian neural networks to estimate the uncertainty (Gal & Ghahramani, 2016). In this work, we use evidential deep learning (Amini et al., 2020) to explicitly learn the epistemic uncertainty. Compared with the widely used MC Dropout (Gal & Ghahramani, 2016) and deep ensembles (Lakshminarayanan et al., 2017), evidential deep learning presents the advantages of faster inference speed and superior calibrated uncertainty. As for the acquisition function, we use Upper Confidence Bound (Srinivas et al., 2010) to incorporate epistemic uncertainty.

5 EXPERIMENTS

We first verify that HN-GFN has adequate capacity to generalize over preference vectors in a synthetic scenario. Next, we evaluate the effectiveness of the proposed MOBO algorithm based on HN-GFN in practical scenarios, which are more in line with real-world molecular optimization. Implementation details and additional results are provided in the appendix.

5.1 SYNTHETIC SCENARIO

Here our goal is to demonstrate that we can control the HN-GFN to sample molecules with different property distributions by varying the preference vectors. We assume that the oracle can be called as many times as necessary. We thus directly optimize the scalarizations of oracle scores. To better visualize the trend of the property distribution of the sampled molecules as a function of the preference vector, we only consider two objectives: inhibition scores against glycogen synthase kinase-3 beta (GNK3β) and c-Jun N-terminal kinase-3 (JNK3) (Li et al., 2018; Jin et al., 2020b).

Compared methods. We compare HN-GFN against the following methods. **Preference-specific GFlowNet** is a vanilla GFlowNet trained independently for a particular preference vector. Note that the preference-specific GFlowNet is treated as "*gold standard*" rather than the baseline, as it is trained and evaluated using the same preference vector. **FiLM-GFN** is another conditional

Table 1: Evaluation of the different methods on synthetic scenario

Method	HV	Div	Cor
MOEA/D	0.182 ± 0.045	n/a	n/a
NSGA-III	0.364 ± 0.041	n/a	n/a
FiLM-GFN	0.431 ± 0.045	0.808 ± 0.010	0.633 ± 0.009
preference-specific GFlowNet	0.545 ± 0.055	$\mathbf{0.811 \pm 0.007}$	0.653 ± 0.003
HN-GFN	$\mathbf{0.550 \pm 0.074}$	0.807 ± 0.017	$\mathbf{0.666 \pm 0.010}$

Table 2: Evaluation of different methods on MOBO scenarios (mean $\pm$ std over 3 runs)

	GSK3β + JNK3		GSK3β + JNK3 + QED + SA	
	HV	Div	HV	Div
HierVAE+qParEGO	0.205 ± 0.015	n/a	0.186 ± 0.009	n/a
HierVAE+qEHVI	0.341 ± 0.072	n/a	0.211 ± 0.006	n/a
GP-BO	0.368 ± 0.020	0.347 ± 0.059	0.335 ± 0.021	0.562 ± 0.031
MARS	0.418 ± 0.095	0.653 ± 0.072	0.273 ± 0.020	$\mathbf{0.754 \pm 0.027}$
HN-GFN	0.572 ± 0.087	$\mathbf{0.810 \pm 0.003}$	0.389 ± 0.012	0.744 ± 0.008
HN-GFN w/ hindsight	$\mathbf{0.669 \pm 0.061}$	0.793 ± 0.007	$\mathbf{0.416 \pm 0.023}$	0.738 ± 0.009

GFlowNet based on FiLM (Perez et al., 2018). **MOEA/D** (Zhang & Li, 2007) and **NSGA-III** (Deb & Jain, 2013) are two multi-objective evolutionary algorithms that also incorporate preference information. We perform evolutionary algorithms over the 32-dim latent space learned by HierVAE (Jin et al., 2020a), which gives better optimization performance than JT-VAE (Jin et al., 2018). All the above methods are evaluated over the same set of 5 evenly spaced preference vectors.

Metrics. For each GFlowNet-based method, we sample 1000 molecules per preference vector as the solutions and compare the proposed HN-GFN with other methods on the following metrics: **Hypervolume indicator (HV)** measures the volume of the space dominated by the Pareto front of the solutions and bounded from below by the preference point $(0, 0)$. **Diversity (Div)** is the average pairwise Tanimoto distance over Morgan fingerprints. **Correlation (Cor)** is the Spearman's rank correlation coefficient between the probability of sampling molecules from an external test set under the GFlowNet and their respective rewards in the logarithmic domain (Nica et al., 2022): $\text{Cor} = \text{Spearman's } \rho_{\log(\pi(x)), \log(R(x))}$. In a nutshell, HV and Div measure the quality of the solutions, while Cor measures how well the trained model is aligned with the given preference vector.

Experimental results. As shown in Table 1, HN-GFN outperforms the baselines and achieves competitive performance to the preference-specific GFlowNets (gold standard) on all the metrics. Compared to the GFlowNet-based methods, the evolutionary algorithms (MOEA/D and NSGA-III) fail to find high-scoring molecules, especially the MOEA/D. Compared to the FiLM-GFN, HN-GFN attains an increase of 0.12 and 0.03 in HV and Cor respectively, implying the superiority of the well-designed hypernetwork-based conditioning mechanism. The comparable performance of HN-GFN and preference-specific GFlowNets illustrates that HN-GFN can generalize over preference vectors. Therefore, the unified HN-GFN provides a significantly efficient way to explore various trade-offs between objectives. In Figure 2(Left), we visualize the trend of the empirical distribution of JNK3 as the preference weight increases. Intuitively, HN-GFN and preference-specific GFlowNets show consistent trends: the larger the preference weight, the higher the average score.

5.2 MULTI-OBJECTIVE BAYESIAN OPTIMIZATION

Next, we evaluate the effectiveness of HN-GFN as an acquisition function optimizer within MOBO in the practical scenarios, where there is a limited evaluation budget for oracle. We consider the following objective combinations of varying size:

- GNK3β+JNK3: Jointly inhibiting Alzheimer-related targets GNK3β and JNK3.

(a) GSK3β + JNK3   (b) GSK3β + JNK3 + QED + SA

Figure 3: Optimization performance over MOBO loops (mean $\pm$ std over 3 runs).

- GNK3β+JNK3+QED+SA: Jointly inhibiting GNK3β and JNK3 while being drug-like and easy-to-synthesize.

We rescale the SA score such that all the above properties have a range of [0,1] and higher is better. For both combinations, we consider starting with $|\mathcal{D}_0| = 200$ random molecules and further querying the oracle $N = 8$ rounds with batch size $b = 100$.

Baselines. We compare HN-GFN with the following methods (from each category mentioned in section 2.1) as the acquisition function optimizer: **HierVAE (Jin et al., 2020a) with** q**ParEGO/**q**EHVI** (Daulton et al., 2020) optimizes the acquisition function over the latent space. **GP-BO** (Tripp et al., 2021) uses Graph GA (Jensen, 2019) to optimize the acquisition function defined based on a GP with Tanimoto kernel. **MARS** (Xie et al., 2021) applies MCMC sampling to optimize the acquisition function defined based on the same surrogate function as HN-GFN.

Experimental results. Table 2 and Figure 3 show that HN-GFN achieves superior performance over the baselines in terms of HV and Div, especially trained with the hindsight-like off-policy strategy. Note that the Div is computed from 100 evaluated molecules per round, and the results of HierVAE are not reported, as them only support 160 rounds with batch size 5 due to memory constraint. Our HN-GFN w/ hindsight outperforms the best baselines MARS and GP-BO of the two objective combinations by a large margin (60.0% and 24.2% relative improvement) with respect to HV, respectively. The promising performance can be attributed to the ability of HN-GFN to sample a diverse batch of candidates from the approximate Pareto front. Another interesting observation, in the more challenging settings where four objectives are optimized, is that MARS generates diverse candidates via MCMC sampling but fails to find high-quality Pareto front, indicating that HN-GFN can find high-reward modes better than MARS.

Ablations. We further conduct ablation experiments to verify the contribution of the hindsight-like strategy: We sample 100 molecules per $\lambda_{\text{target}} \in \Lambda$ every 500 training steps in the first round, and compute the average reward of the Top-20 molecules from all λ_{target}. As shown in Figure 2 (Right), our hindsight-like off-policy strategy boosts average rewards compared to the on-policy strategy and off-policy strategy that only incorporates trajectories from the observed dataset, demonstrating that sharing high-performing molecules among policies is effective for speed up training of HN-GFN.

6 CONCLUSION AND FUTURE WORK

We have introduced a MOBO algorithm for sample-efficient multi-objective molecular optimization. This algorithm leverages a hypernetwork-based GFlowNet (HN-GFN) to sample a diverse batch of candidates from the approximate Pareto front. In addition, we present a hindsight-like off-policy strategy to improve optimization performance. Our algorithm outperforms existing approaches on synthetic and practical scenarios. Future work includes extending this algorithm to other optimization problems such as biological sequence design and neural architecture search.

REFERENCES

Alexander Amini, Wilko Schwarting, Ava Soleimany, and Daniela Rus. Deep evidential regression. Advances in Neural Information Processing Systems, 33:14927–14937, 2020.

Marcin Andrychowicz, Filip Wolski, Alex Ray, Jonas Schneider, Rachel Fong, Peter Welinder, Bob McGrew, Josh Tobin, OpenAI Pieter Abbeel, and Wojciech Zaremba. Hindsight experience replay. Advances in neural information processing systems, 30, 2017.

Emmanuel Bengio, Moksh Jain, Maksym Korablyov, Doina Precup, and Yoshua Bengio. Flow network based generative models for non-iterative diverse candidate generation. Advances in Neural Information Processing Systems, 34:27381–27394, 2021a.

Yoshua Bengio, Tristan Deleu, Edward J Hu, Salem Lahlou, Mo Tiwari, and Emmanuel Bengio. Gflownet foundations. arXiv preprint arXiv:2111.09266, 2021b.

G Richard Bickerton, Gaia V Paolini, Jérémy Besnard, Sorel Muresan, and Andrew L Hopkins. Quantifying the chemical beauty of drugs. Nature chemistry, 4(2):90–98, 2012.

Samuel Daulton, Maximilian Balandat, and Eytan Bakshy. Differentiable expected hypervolume improvement for parallel multi-objective bayesian optimization. Advances in Neural Information Processing Systems, 33:9851–9864, 2020.

Kalyanmoy Deb and Himanshu Jain. An evolutionary many-objective optimization algorithm using reference-point-based nondominated sorting approach, part i: solving problems with box constraints. IEEE transactions on evolutionary computation, 18(4):577–601, 2013.

Tristan Deleu, António Góis, Chris Emezue, Mansi Rankawat, Simon Lacoste-Julien, Stefan Bauer, and Yoshua Bengio. Bayesian Structure Learning with Generative Flow Networks. arXiv preprint, 2022.

Alexey Dosovitskiy and Josip Djolonga. You only train once: Loss-conditional training of deep networks. In International conference on learning representations, 2019.

Peter Ertl and Ansgar Schuffenhauer. Estimation of synthetic accessibility score of drug-like molecules based on molecular complexity and fragment contributions. Journal of cheminformatics, 1(1):1–11, 2009.

Tianfan Fu, Wenhao Gao, Cao Xiao, Jacob Yasonik, Connor W Coley, and Jimeng Sun. Differentiable scaffolding tree for molecule optimization. In International Conference on Learning Representations, 2022.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In international conference on machine learning, pp. 1050–1059. PMLR, 2016.

Wenhao Gao, Tianfan Fu, Jimeng Sun, and Connor W. Coley. Sample efficiency matters: Benchmarking molecular optimization. In ICML 2022 2nd AI for Science Workshop, 2022. URL https://openreview.net/forum?id=u7YqrmM5zrF.

Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In International conference on machine learning, pp. 1263–1272. PMLR, 2017.

Rafael Gómez-Bombarelli, Jennifer N Wei, David Duvenaud, José Miguel Hernández-Lobato, Benjamín Sánchez-Lengeling, Dennis Sheberla, Jorge Aguilera-Iparraguirre, Timothy D Hirzel, Ryan P Adams, and Alán Aspuru-Guzik. Automatic chemical design using a data-driven continuous representation of molecules. ACS central science, 4(2):268–276, 2018.

David Ha, Andrew Dai, and Quoc V Le. Hypernetworks. arXiv preprint arXiv:1609.09106, 2016.

Moksh Jain, Emmanuel Bengio, Alex Hernandez-Garcia, Jarrid Rector-Brooks, Bonaventure FP Dossou, Chanakya Ajit Ekbote, Jie Fu, Tianyu Zhang, Michael Kilgour, Dinghuai Zhang, et al. Biological sequence design with gflownets. In International Conference on Machine Learning, pp. 9786–9801. PMLR, 2022.

Jan H Jensen. A graph-based genetic algorithm and generative model/monte carlo tree search for the exploration of chemical space. Chemical science, 10(12):3567–3572, 2019.

Wengong Jin, Regina Barzilay, and Tommi Jaakkola. Junction tree variational autoencoder for molecular graph generation. In International conference on machine learning, pp. 2323–2332. PMLR, 2018.

Wengong Jin, Regina Barzilay, and Tommi Jaakkola. Hierarchical generation of molecular graphs using structural motifs. In International conference on machine learning, pp. 4839–4848. PMLR, 2020a.

Wengong Jin, Regina Barzilay, and Tommi Jaakkola. Multi-objective molecule generation using interpretable substructures. In International conference on machine learning, pp. 4849–4859. PMLR, 2020b.

Donald R Jones, Matthias Schonlau, and William J Welch. Efficient global optimization of expensive black-box functions. Journal of Global optimization, 13(4):455–492, 1998.

Kirthevasan Kandasamy, Willie Neiswanger, Jeff Schneider, Barnabas Poczos, and Eric P Xing. Neural architecture search with bayesian optimisation and optimal transport. Advances in neural information processing systems, 31, 2018.

Joshua Knowles. Parego: A hybrid algorithm with on-line landscape approximation for expensive multiobjective optimization problems. IEEE Transactions on Evolutionary Computation, 10(1): 50–66, 2006.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. Advances in neural information processing systems, 30, 2017.

Yibo Li, Liangren Zhang, and Zhenming Liu. Multi-objective de novo drug design with conditional graph generative model. Journal of cheminformatics, 10(1):1–24, 2018.

Henry Moss, David Leslie, Daniel Beck, Javier Gonzalez, and Paul Rayson. Boss: Bayesian optimization over string spaces. Advances in neural information processing systems, 33:15476–15486, 2020.

Aviv Navon, Aviv Shamsian, Ethan Fetaya, and Gal Chechik. Learning the pareto front with hypernetworks. In ICLR, 2021.

Andrei Cristian Nica, Moksh Jain, Emmanuel Bengio, Cheng-Hao Liu, Maksym Korablyov, Michael M Bronstein, and Yoshua Bengio. Evaluating generalization in gflownets for molecule design. In ICLR2022 Machine Learning for Drug Discovery, 2022.

Ethan Perez, Florian Strub, Harm De Vries, Vincent Dumoulin, and Aaron Courville. Film: Visual reasoning with a general conditioning layer. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 32, 2018.

Pavel G Polishchuk, Timur I Madzhidov, and Alexandre Varnek. Estimation of the size of drug-like chemical space based on gdb-17 data. Journal of computer-aided molecular design, 27(8): 675–679, 2013.

Carl Edward Rasmussen. Gaussian processes in machine learning. In Summer school on machine learning, pp. 63–71. Springer, 2003.

Bobak Shahriari, Kevin Swersky, Ziyu Wang, Ryan P Adams, and Nando De Freitas. Taking the human out of the loop: A review of bayesian optimization. Proceedings of the IEEE, 104(1): 148–175, 2015.

Niranjan Srinivas, Andreas Krause, Sham Kakade, and Matthias Seeger. Gaussian process optimization in the bandit setting: no regret and experimental design. In Proceedings of the 27th International Conference on International Conference on Machine Learning, pp. 1015–1022, 2010.

Richard S Sutton and Andrew G Barto. Reinforcement learning: An introduction. MIT press, 2018.

Kevin Swersky, Yulia Rubanova, David Dohan, and Kevin Murphy. Amortized bayesian optimization over discrete spaces. In Conference on Uncertainty in Artificial Intelligence, pp. 769–778. PMLR, 2020.

Austin Tripp, Erik Daxberger, and José Miguel Hernández-Lobato. Sample-efficient optimization in the latent space of deep generative models via weighted retraining. Advances in Neural Information Processing Systems, 33:11259–11272, 2020.

Austin Tripp, Gregor NC Simm, and José Miguel Hernández-Lobato. A fresh look at de novo molecular design benchmarks. In NeurIPS 2021 AI for Science Workshop, 2021.

Yutong Xie, Chence Shi, Hao Zhou, Yuwei Yang, Weinan Zhang, Yong Yu, and Lei Li. Mars: Markov molecular sampling for multi-objective drug discovery. In International Conference on Learning Representations, 2021.

Jiaxuan You, Bowen Liu, Zhitao Ying, Vijay Pande, and Jure Leskovec. Graph convolutional policy network for goal-directed molecular graph generation. Advances in neural information processing systems, 31, 2018.

Dinghuai Zhang, Nikolay Malkin, Zhen Liu, Alexandra Volokhova, Aaron Courville, and Yoshua Bengio. Generative flow networks for discrete probabilistic modeling. arXiv preprint arXiv:2202.01361, 2022.

Qingfu Zhang and Hui Li. Moea/d: A multiobjective evolutionary algorithm based on decomposition. IEEE Transactions on evolutionary computation, 11(6):712–731, 2007.

Eckart Zitzler and Lothar Thiele. Multiobjective evolutionary algorithms: a comparative case study and the strength pareto approach. IEEE transactions on Evolutionary Computation, 3(4):257–271, 1999.