Uncertainty Quantification in Neural Differential Equations

Abstract

Uncertainty quantification (UQ) helps to make trustworthy predictions based on collected observations and uncertain domain knowledge. With increased usage of deep learning in various applications, the need for efficient UQ methods that can make deep models more reliable has increased as well. Among applications that can benefit from effective handling of uncertainty are the deep learning based differential equation (DE) solvers. We adapt several state-of-the-art UQ methods to get the predictive uncertainty for DE solutions and show the results on four different DE types.

1 Introduction

Driven by the growing popularity of deep learning, several areas of research have obtained state-of-the-art performances with deep neural networks (NNs). Among other applications, deep NNs have been applied for solving differential equations (DEs) [10] — a fundamental tool for mathematical modeling in engineering, finance, and the natural sciences. Deep learning based solutions of DEs have recently appeared in, e.g., [19], [17], [18], [21], [9], [11], [16], [5], [20], [8]. Typically, the NN itself approximates the solution of a DE. Thanks to that, parallelization is natural and, in contrast to classical numerical methods, the solution at any time can be computed without the burden of having to compute all previous time steps. Furthermore, NNs are continuous and differentiable.

Until recently, the focus of deep learning was on achieving better accuracy in the NN predictions, but now it is increasingly being shifted to measuring the prediction's uncertainty, especially if the task at hand is safety critical. Uncertainty quantification (UQ) has been considered for deep models in computer vision, medical image analysis, bionformatics, etc [1]. Likewise, UQ is important for deep models that solve DEs. The uncertainty here stems from the fact that we cannot train a NN on an infinite time and/or space domain. Therefore, we seek to estimate the solution's uncertainty in the regions where the model was not trained. Moreover, another source of uncertainty comes from the model's limitations such as its architecture.

To the best of our knowledge, this is the first work to discuss UQ for deep models that solve DEs. Contrary to common deep learning setup, we solve DEs without any observed data, relying only on the samples of time and/or space and on the mathematical statement that relates functions and their derivatives. This makes the application of existing UQ methods not so straightforward. In this paper, we make the following contributions:

1. We propose an adaptation of the four state-of-the-art UQ methods in deep learning — *Bayes By Backprop* [3], *Flipout* [23], *Neural Linear Model* [22, 14], and *Deep Evidential Regression* [2, 12] — to the case of solving DEs.

2. We test the above-mentioned methods on four different DE types: linear ordinary DE (ODE), non-linear ODE, system of non-linear ODEs, and partial DE (PDE).

2 Preliminaries

2.1 Solving differential equations with neural networks

A DE can be expressed as $\mathcal{L}u - f = 0$, where $\mathcal{L}$ is the differential operator, $u(\mathbf{x})$ is the solution that we wish to find on some (possibly multidimensional) domain $\mathbf{x}$, and f is a known forcing function. We denote the NN approximation of the true solution by u_N. To solve the DE, we minimize the square loss of the residual function $\mathcal{R}(u_N) := \mathcal{L}u_N - f$, i.e., the optimization objective is

$$\min_{\mathbf{w}}(\mathcal{R}^2(u_N)), \tag{1}$$

where $\mathbf{w}$ are the NN parameters. It is also necessary to inform the NN about any initial and/or boundary conditions, $u_c = u(\mathbf{x}_c)$. The preferred strategy is to ensure that these conditons are always exactly satisfied and therefore avoid unnecessary local uncertainty. We consider a transformation $\tilde{u}_N$ which enforces the initial and/or boundary conditions and satisfies them by construction. In general, it has the form $\tilde{u}_N(\mathbf{x}) = A(\mathbf{x}, \mathbf{x}_c, u_c)u_N(\mathbf{x})$. Accordingly, we replace u_N by $\tilde{u}_N$ in the optimization objective (1). Hereinafter, $\tilde{u}_N$ will denote the enforced function.

2.2 Uncertainty quantification under Bayesian framework

While classical learning considers *deterministic model parameters* θ, the Bayesian framework introduces uncertainty by considering a *posterior distribution over the model parameters*, $p(\theta|\mathcal{D})$, obtained after observing some data $\mathcal{D}$. The posterior distribution is given by Bayes' theorem, $p(\theta|\mathcal{D}) = p(\mathcal{D}|\theta) \cdot p(\theta) / p(\mathcal{D})$, where $p(\mathcal{D}|\theta)$ is the likelihood, $p(\theta)$ is the prior distribution over the parameters, and $p(\mathcal{D})$ is the evidence. The predictions y at a new test point $\mathbf{x}$ are given by the posterior predictive distribution,

$$p(y|\mathbf{x}, \mathcal{D}) = \int p(y|\mathbf{x}, \theta) \cdot p(\theta|\mathcal{D})d\theta. \tag{2}$$

For probabilistic deep models, there are two main strategies of estimating (2).

Inference through the posterior distribution of model parameters. As stated in (2), the posterior predictive is obtained by averaging over the posterior uncertainty in the model parameters. Thus, we can start with estimating the posterior distribution of the NN weights.

In this case, well-suited is Bayesian NN [13] which places a prior distribution on all the weights (and biases) $\mathbf{w}$. Since analytical solution for the posterior is intractable for Bayesian NNs, we have to use either numerical approximation methods such as MCMC or variational methods. Despite the need for sampling in both cases, variational methods are computationally less expensive for high-dimensional parameter spaces and also provide an analytical approximation.

Bayes By Backprop (*BBB*) is a variational, backpropagation-compatible method for training a Bayesian NN. Its optimization objective seeks to minimize the Kullback-Leibler divergence between the true posterior and the variational posterior which is re-parametrized as $\mathcal{N}(\mu, \sigma = \log(1 + \exp(\rho)))$ to allow for backpropagation. At each optimization step, weights $\mathbf{w} = \mu + \sigma \circ \epsilon$, where $\epsilon \sim \mathcal{N}(0, 1)$ and $\circ$ is pointwise multiplication, are obtained by sampling from the variational posterior.

BBB is followed by *Flipout* which adds a pseudo-independent perturbation to the weights at each training point $\mathbf{x}_n$ in the mini-batch, namely, $\mathbf{w}_n = \mu + (\sigma \circ \epsilon)R_n$, where R_n is the random sign matrix. Intuitively, the weights get flipped symmetrically around the mean with probability 0.5.

Neural Linear Model (*NLM*) is an alternative to Bayesian NN. It places a prior distribution only on the last layer's weights, and learns point estimates for the remaining layers. One can interpret the output of these layers as a basis defined by the feature embedding of the data. The last layer of *NLM* performs Bayesian linear regression on this feature basis. *NLM* provides tractable inference under the Gaussian assumption on likelihood; we get analytical solution for the posterior distribution.

Inference through the higher-order evidential distribution. It is also possible to infer parameters of the posterior predictive directly, using Bayesian hierarchical modeling [6, 7]. In *Deep Evidential Regression* (*DER*), the higher-order, evidential prior is placed over the Gaussian likelihood function. Choosing Normal Inverse-Gamma (NIG) prior yields an analytical solution for the model evidence which is maximized by the optimization objective with respect to the NIG hyperparameters. *DER* also proposes an evidence regularizer which minimizes evidence on incorrect predictions. The posterior predictive mean and variance are computed analytically using the learned hyperparameters.

3 Uncertainty quantification in neural differential equations

Instead of learning a deterministic solution $\tilde{u}_N$, we now aim to learn a probabilistic solution u_θ, characterized by a posterior predictive distribution. We make a common assumption that this distribution is Gaussian and estimate it using some probabilistic model g_θ parametrized by θ.

3.1 Proposed approach

While making a Gaussian assumption for the posterior predictive distribution, we cannot do the same for the likelihood function if we evaluate it at the *residual $\mathcal{R}$ on the training domain $\mathbf{x}_t$*, a natural argument one can think of in case of DEs. Namely, if $u_\theta \sim \mathcal{N}(\mu_\theta, \sigma_\theta)$ holds, then $\mathcal{R}(u_\theta) \not\sim \mathcal{N}(\mu_\mathcal{R}, \sigma_\mathcal{R})$. Unfortunately, UQ methods described in Section 2.2 rely upon the assumption that the likelihood is Gaussian. *DER* and *NLM* use it to derive the analytical form of a loss function and a posterior distribution, respectively. *BBB* and *Flipout* can in principle use any likelihood in the loss function, but it has to be of known analytical form. To make all the methods compatible with solving DEs, we propose a two-stage training procedure:

1) We first train a classical NN on the training domain $\mathbf{x}_t$ to find a *deterministic solution $\tilde{u}_N$*,

2) We use $\tilde{u}_N$ as *observed data* for our probabilistic model g_θ and define likelihood using a Gaussian assumption, $p(\tilde{u}_N|\theta) = \prod_{\mathbf{x}_t} \mathcal{N}(\tilde{u}_N; u_\theta, \varepsilon)$.

We note that despite interpreting $\tilde{u}_N$ in stage two as observed data rather than a function that solves DE, its associated variance ε is not of aleatoric nature (i.e. irreducible variance that comes from noise inherent to the data), as it would be in the classical regression problem. It can be interpreted as another source of epistemic (reducible) uncertainty coming from the NN model limitations. In Bayesian framework, this uncertainty also affects the uncertainty of the model outside of the training domain. In this first work on UQ for neural DE solvers, we consider a simplified treatment of ε. In case of *BBB*, *Flipout*, and *NLM*, we pre-define ε with some small number. In case of *DER*, we learn ε along with posterior predictive distribution, but the result is not particularly useful since *DER* does not have direct access to residuals during learning.

Eventually, probabilistic model allows us to find the posterior predictive distribution of u_θ. In case of *BBB*, *Flipout*, and *NLM*, we have $\tilde{g}_\theta(\mathbf{x}_t, \tilde{u}_N) = u_\theta$, i.e., the model outputs a single instance u_θ. For *BBB* and *Flipout*, the posterior predictive distribution $p(u_\theta|\mathbf{x}_t, \tilde{u}_N)$ is computed as an approximation of integral (2) using sampling; for *NLM*, an analytical form is available. In case of *DER*, we have $g_\theta(\mathbf{x}_t, \tilde{u}_N) = (\gamma, \nu, \alpha, \beta)$, where $(\gamma, \nu, \alpha, \beta)$ are the NIG hyperparameters. The mean of the posterior predictive distribution is equal to $\tilde{\gamma}$ and the variance is computed using the remaining hyperparameters. We note that the predictive uncertainty also requires the initial and/or boundary condition enforcement; this way we are able to eliminate unnecessary uncertainties at $\mathbf{x}_c$.

Main drawbacks of the current approach are the double computational burden and the not so useful uncertainty for NN approximation of the true solution in the traning region; both of them are subject to further improvement.

4 Experiments and discussion

We corroborate our theory with experimental results on four equations: 1. Linear ODE for squared exponential, $\frac{du}{dt} = -2tu$; 2. Non-linear ODE for Duffing-type oscillator, $\ddot{u} + \omega^2 u + \epsilon u^3 = 0$; 3. Lotka-Volterra equations (system of non-linear ODEs), $\dot{u} = \alpha u - \beta uv \ \wedge \ \dot{v} = -\delta u + \gamma uv$; 4. Burgers' equation (non-linear PDE), $\frac{\partial u}{\partial t} + u\frac{\partial u}{\partial x} = \nu\frac{\partial^2 u}{\partial x^2}$.

Our implementation is based on a DE solver provided by *neurodiffeq* [4], a Python package built with PyTorch [15]. Since we are considering relatively simple DEs, we use networks with one to three fully-connected hidden layers. For the prior distribution of the weights in *BBB*, *Flipout*, and *NLM*, we use flat Gaussian priors with mean zero. In *BBB* and *Flipout*, we estimate the posterior predictive from 1000 samples. In *DER*, there is no need for choosing a weight prior, but an appropriate regularization parameter has to be chosen instead. Here, we tune the regularization parameter manually.

We demonstrate the UQ results for ODEs and for PDE in Figure 1 and Figure 2, accordingly. For all ODEs, the deterministic solution is able to approximate the true solution well; we incorporate this fact in our Bayesian inference by choosing small ε which yields that there is almost no uncertainty in

Figure 1: **Uncertainty estimation for neural ODEs**. Probabilistic models give low epistemic uncertainty in the training domain and inflate it outside of the training domain. *Deep Evidential Regression* locally overestimates uncertainty, possibly due to non-optimal regularization.

Figure 2: **Uncertainty estimation for NN based solution of Burgers' equation.** We test *Bayes By Backprop* on an example of a non-linear PDE. Uncertainty coming from underfitting is not captured well due to our simplified inference in terms of this type of uncertainty, nevertheless we see that the uncertainty inflates outside of the training domain.

the training domain. Needless to say that in case when the ground truth is not known, finding ε is a highly non-trivial task. We observe that the epistemic uncertainty away from the training domain is high enough for all methods, which is our main desired result in this paper. For Burgers' equation, however, we see that the NN is not able to learn the true solution, and our probabilistic model is underestimating the epistemic uncertainty in the training domain and also outside of it. In this case, either a better deterministic model or a better UQ methodolody is needed.

We have witnessed comparable performance in sampling-dependent (*BBB*, *Flipout*) and sampling-free (*NLM*, *DER*) methods. Given the computational expense of sampling during Bayesian NN training, the latter two methods could be preferable in case of complex DEs on a multidimensional domain.

We believe that further enhancement in terms of diversifying experiments and deepening theory will help the deep learning based DE solutions outperform classical ones and lead to their increased presence in applications.

References

[1] M. Abdar, F. Pourpanah, S. Hussain, D. Rezazadegan, L. Liu, M. Ghavamzadeh, P. Fieguth, X. Cao, A. Khosravi, U. R. Acharya, and et al. A review of uncertainty quantification in deep learning: Techniques, applications and challenges. *Information Fusion*, 76:243–297, Dec 2021. ISSN 1566-2535. doi: 10.1016/j. inffus.2021.05.008. URL http://dx.doi.org/10.1016/j.inffus.2021.05.008.

[2] A. Amini, W. Schwarting, A. Soleimany, and D. Rus. Deep evidential regression. *arXiv*, Oct 2019. URL http://arxiv.org/abs/1910.02600.

[3] C. Blundell, J. Cornebise, K. Kavukcuoglu, and D. Wierstra. Weight uncertainty in neural network. In *International Conference on Machine Learning*, pages 1613–1622. PMLR, 2015.

[4] F. Chen, D. Sondak, P. Protopapas, M. Mattheakis, S. Liu, D. Agarwal, and M. Di Giovanni. Neurodiffeq: A python package for solving differential equations with neural networks. *Journal of Open Source Software*, 5:1931, 02 2020. doi: 10.21105/joss.01931.

[5] C. Flamant, P. Protopapas, and D. Sondak. Solving differential equations using neural network solution bundles. *arXiv preprint arXiv:2006.14372*, 2020.

[6] A. Gelman and et al. Prior distributions for variance parameters in hierarchical models. *Bayesian analysis*, 1(3):515–534, 2006.

[7] A. Gelman, A. Jakulin, M. G. Pittau, and Y.-S. Su. A weakly informative default prior distribution for logistic and other regression models. *The Annals of Applied Statistics*, 2(4):1360–1383, 2008.

[8] M. D. Giovanni, D. Sondak, P. Protopapas, and M. Brambilla. Finding multiple solutions of ODEs with neural networks. In *AAAI Spring Symposium: MLPS*, 2020.

[9] T. Hagge, P. Stinis, E. Yeung, and A. M. Tartakovsky. Solving differential equations with unknown constitutive relations as recurrent neural networks, 2017.

[10] I. Lagaris, A. Likas, and D. Fotiadis. Artificial neural networks for solving ordinary and partial differential equations. *IEEE Transactions on Neural Networks*, 9(5):987–1000, 1998. ISSN 1045-9227. doi: 10.1109/72.712178. URL http://dx.doi.org/10.1109/72.712178.

[11] M. Mattheakis, H. Joy, and P. Protopapas. Unsupervised reservoir computing for solving ordinary differential equations, 2021.

[12] N. Meinert and A. Lavin. Multivariate deep evidential regression. *arXiv preprint arXiv:2104.06135*, 2021.

[13] R. M. Neal. Bayesian learning for neural networks. *Springer Science & Business Media*, 118, 2012.

[14] S. W. Ober and C. E. Rasmussen. Benchmarking the neural linear model for regression. In *Advances in Approximate Bayesian Inference (AABI)*, pages 2171–2180, 2019.

[15] A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga, A. Desmaison, A. Köpf, E. Yang, Z. DeVito, M. Raison, A. Tejani, S. Chilamkurthy, B. Steiner, L. Fang, J. Bai, and S. Chintala. Pytorch: An imperative style, high-performance deep learning library, 2019.

[16] A. Paticchio, T. Scarlatti, M. Mattheakis, P. Protopapas, and M. Brambilla. Semi-supervised neural networks solve an inverse problem for modeling Covid-19 spread. *arXiv preprint arXiv:2010.05074*, 2020.

[17] M. L. Piscopo, M. Spannowsky, and P. Waite. Solving differential equations with neural networks: Applications to the calculation of cosmological phase transitions. *Physical Review D*, 100(1), Jul 2019. ISSN 2470-0029. doi: 10.1103/physrevd.100.016002. URL http://dx.doi.org/10.1103/PhysRevD.100.016002.

[18] M. Raissi. Forward-backward stochastic neural networks: Deep learning of high-dimensional partial differential equations. *arXiv preprint arXiv:1804.07010*, 2018.

[19] M. Raissi, P. Perdikaris, and G. Karniadakis. Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational Physics*, 378:686–707, 2019. ISSN 0021-9991. doi: https://doi.org/10.1016/j.jcp.2018.10.045. URL https://www.sciencedirect.com/science/article/pii/S0021999118307125.

[20] D. Randle, P. Protopapas, and D. Sondak. Unsupervised learning of solutions to differential equations with generative adversarial networks, 2020.

[21] J. Sirignano and K. Spiliopoulos. DGM: A deep learning algorithm for solving partial differential equations. *Journal of Computational Physics*, 375:1339–1364, Dec 2018. ISSN 0021-9991. doi: 10.1016/j.jcp.2018. 08.029. URL http://dx.doi.org/10.1016/j.jcp.2018.08.029.

[22] J. Snoek, O. Rippel, K. Swersky, R. Kiros, N. Satish, N. Sundaram, M. M. A. Patwary, Prabhat, and R. P. Adams. Scalable Bayesian optimization using deep neural networks. In *32nd International Conference on Machine Learning (ICML)*, pages 2171–2180, 2015.

[23] Y. Wen, P. Vicol, J. Ba, D. Tran, and R. Grosse. Flipout: Efficient pseudo-independent weight perturbations on mini-batches. *arXiv preprint arXiv:1803.04386*, 2018.