The Adaptive Doubly Robust Estimator for Policy Evaluation in Adaptive Experiments and a Paradox Concerning Logging Policy

Abstract

The *doubly robust* (DR) estimator, which consists of two nuisance parameters, the conditional mean outcome and the logging policy (the probability of choosing an action), is crucial in causal inference. This paper proposes a DR estimator for *dependent samples* obtained from adaptive experiments. To obtain an asymptotically normal semiparametric estimator from dependent samples without non-Donsker nuisance estimators, we propose *adaptive-fitting* as a variant of sample-splitting. We also report an empirical *paradox* that our proposed DR estimator tends to show better performances compared to other estimators utilizing the true logging policy. While a similar phenomenon is known for estimators with i.i.d. samples, traditional explanations based on asymptotic efficiency cannot elucidate our case with dependent samples. We confirm this hypothesis through simulation studies.

1   Introduction

Adaptive experiments, including efficient treatment effect estimation (van der Laan, 2008; Hahn et al., 2011), treatment regimes (Zhang et al., 2012a; Zhao et al., 2012), and multi-armed bandit (MAB) problems (Gittins, 1989; Lattimore & Szepesvári, 2020), are widely accepted and used in real-world applications, for example, in social experiments (Hahn et al., 2011), online advertisement (Zhang et al., 2012b), clinical trials (Chow & Chang, 2011; Villar, 2018), website optimization (White, 2012), and recommendation systems (Li et al., 2010). In those various applications, there is a significant interest in off-line counterfactual inference using samples obtained from past trials generated by a logging policy (the probability of choosing an action: Li et al., 2010, 2011). Among several off-line evaluation criteria, this paper focuses on *off-policy value estimation* (OPVE: Li et al., 2015). The goal of OPVE is to estimate the expected value of the weighted outcome, which includes average treatment effect (ATE) estimation as a special case (Hirano et al., 2003; Bang & Robins, 2005).

In OPVE, when the true logging policy is known, there are mainly three types of estimators: inverse probability weighting (IPW: Horvitz & Thompson, 1952), direct method (DM), and augmented IPW (AIPW Bang & Robins, 2005) estimators. IPW-type estimators refer to a sample average of the outcomes weighted by the true logging policy. DM-type estimators refer to a sample average of an estimated conditional outcome. AIPW-type estimators consist of two components: the IPW part and the DM part. More details are given in Section 3. In addition, when the true logging policy is unknown, we call IPW-type and AIPW-type estimators that use the estimated logging policy EIPW-type and DR-type estimators, respectively. In particular, and the focus of this paper, DR-type estimators are crucial in OPVE, since in most applications of interest the true logging policy is either unknown, difficult, or costly to obtain, making IPW and AIPW-type estimators often infeasible.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

While existing OPVE methods typically assume that the samples are *independent and identically distributed* (i.i.d.: Hirano et al., 2003; Dudík et al., 2011), adaptive experiments usually allow logging policies to be updated based on past observations, under which the generated samples are non-i.i.d. In this case, theoretical results shown under i.i.d. assumptions, such as consistency and asymptotic normality, are not guaranteed. In particular, the asymptotic normality is critical, as we can obtain $\sqrt{T}$-rate confidence intervals, where T is the sample size. For this problem, van der Laan (2008) proposed an asymptotically normal AIPW estimator under dependent samples, with several follow-up studies, including Hadad et al. (2019), Kato et al. (2020), and Zhang et al. (2020). However, a DR-type estimator for dependent samples has never been formally proposed, despite its importance.

This paper proposes an asymptotically normal DR estimator for dependent samples. We call this DR estimator the *adaptive DR* (ADR) estimator. There are mainly two difficulties concerning this estimator. First, we cannot use the CLT for i.i.d. or martingale difference sequences, as done in van der Laan (2008), Hadad et al. (2019), and Kato et al. (2020). Second, when nuisance parameters are estimated with complicated models, the Donsker condition does not hold in general, which is required to show the asymptotic normality of semiparametric estimators, such as our proposed ADR estimator. In this paper, to solve these problems, we propose adaptive-fitting, inspired by the double/debiased machine learning for i.i.d. samples (Chernozhukov et al., 2018). We also find that by using the ADR estimator, not only can OPVE be done without knowing the true logging policy, the ADR estimator paradoxically often outperforms the performance of AIPW estimators that use the true logging policy. We list our contributions as follows.

(I) Asymptotic normality of the ADR estimator. We show the asymptotic normality of our proposed ADR estimator. To the best of our knowledge, a DR-type estimator for dependent samples obtained in adaptive experiments has not been formally proposed.

(II) Adaptive fitting. While the asymptotic normalities of IPW and AIPW estimators are shown by the martingale CLT, we cannot directly apply this technique to our proposed ADR estimator. This is because the martingale condition does not hold when the true logging policy is unknown. To solve this problem, we utilize a novel sample-splitting method called adaptive-fitting to show the asymptotic normality of the ADR estimator. We generalize this technique as a variant of sample-splitting (Chernozhukov et al., 2018) for semiparametric inference with dependent samples without the Donsker condition. Unlike existing sample-splitting methods, which assume that samples are i.i.d., the proposed adaptive-fitting is applicable to non-i.i.d. samples. Note that this adaptive-fitting is different from martingale based estimators, such as van der Laan (2008) and Hadad et al. (2019), which requires the true logging policy.

(III) Empirical paradox on using estimated logging policy. Through experimental studies, we investigate the empirical performance of our proposed ADR estimator. We find that the ADR estimator often exhibits improved performances over other estimators using the true logging policy, such as the AIPW estimator. Estimators requiring the true logging policy tend to empirically be unstable due to the instability of the nuisance parameter; the instability being caused by the logging policy being near zero before convergence. Our finding implies that the ADR estimator mitigates this instability. We call this phenomenon a *paradox concerning logging policy* because using more information (the true logging policy) does not improve empirical performance. A similar paradox is known for IPW-type estimators for i.i.d. samples (Hahn, 1998; Henmi & Eguchi, 2004). However, we cannot explain our paradox from a conventional semiparametric efficiency perspective (Hahn, 1998; Hirano et al., 2003), as the asymptotic variances are the same between the ADR estimator (with an estimated logging policy) and the AIPW estimator (with the true logging policy), unlike IPW-type estimators.

Organization of this paper. In Section 2, we formulate our problem. In Section 3, we introduce existing OPVE estimators for dependent samples. In Section 4, we propose the ADR estimator, which is our main contribution. We call the method used for the ADR estimator adaptive-fitting, and generalize it in Section 5. In Section 6, we report a paradox through simulation studies and explain the cause of this phenomenon. In Section 7, we conduct experiments using benchmark datasets.

2   Problem setting

Suppose that there is a time series $1, 2, \ldots, T$, and denote the set as $[T] = \{1, \ldots, T\}$. For $t \in [T]$, let A_t be an *action* in $\mathcal{A} = \{1, 2, \ldots, K\}$, X_t be a *covariate* observed by a decision maker when choosing an action, and $\mathcal{X}$ be its space. Following the Neyman–Rubin causal model (Rubin, 1974),

let a reward at period t be $Y_t = \sum_{a=1}^{K} \mathbb{1}[A_t = a]Y_t(a)$, where $Y_t(a) : \mathcal{A} \to \mathbb{R}$ is a potential (random) outcome. We have a dataset $\left\{(X_t, A_t, Y_t)\right\}_{t=1}^{T}$ with the following data-generating process (DGP):

$$(X_t, A_t, Y_t(A_t)) \sim p(x)p_t(a|x)p(y_a|x), \qquad (2.1)$$

where $p(x)$ denotes the density of the covariate X_t, $p_t(a|x)$ denotes the probability of choosing an action a conditional on a covariate x at period t, and $p(y_a|x)$ denotes the density of a reward $Y_t(a)$ conditional on a covariate x. We assume that $p(x)$ and $p(y_a|x)$ are invariant across periods; that is, $\{(X_t, Y_t(1), \ldots, Y_t(K))\}_{t=1}^{T}$ is i.i.d., but $p_t(a|x)$ can take different values across periods based on past observations. In this case, the samples $\left\{(X_t, A_t, Y_t)\right\}_{t=1}^{T}$ are correlated over time, that is, the samples are not i.i.d. Let $\Omega_{t-1} = \{X_{t-1}, A_{t-1}, Y_{t-1}, \ldots, X_1, A_1, Y_1\}$ be the history and $\mathcal{M}_{t-1}$ be a set of possible histories until the t-th period. The probability $p_t(a|x)$ is determined by a *logging policy* $\pi_t : \mathcal{A} \times \mathcal{X} \times \mathcal{M}_{t-1} \to (0, 1)$, such that $\sum_{a=1}^{K} \pi_t(a|x, \Omega_{t-1}) = 1$, which is a function of a covariate X_t, an action A_t, and history Ω_{t-1}. We also assume that π_t is conditionally independent of $Y_t(a)$ to satisfy unconfoundedness (Remark 2.2).

Remark 2.1 (Stable unit treatment value assumption (SUTVA)). *The DGP implies SUTVA; that is, $p(y_a|x)$ is invariant for any $p(a|x)$(Rubin, 1986).*

Remark 2.2 (Unconfoundedness). *In this paper, unconfoundedness refers to independence between $(Y_t(1), \ldots, Y_t(K))$ and A_t, conditional on X_t and Ω_{t-1}, which is required for identification.*

2.1 OPVE

The goal of OPVE is to estimate the expected value of the sum of the outcomes $Y_t(a)$ weighted by an evaluation function $\pi^{\mathrm{e}} : \mathcal{A} \times \mathcal{X} \to \mathbb{R}$; that is,

$$R(\pi^{\mathrm{e}}) := \mathbb{E}_{(X_t, Y_t(1), \ldots, Y_t(K))} \left[\sum_{a=1}^{K} \pi^{\mathrm{e}}(a|X_t)Y_t(a) \right], \qquad (2.2)$$

where the expectation $\mathbb{E}_{(X_t, Y_t(1), \ldots, Y_t(K))}$ is taken over $(X_t, Y_t(1), \ldots, Y_t(K))$. We denote it as $\mathbb{E}$, when there is no ambiguity. As with Dudík et al. (2011), the evaluation function is usually referred to as an evaluation policy, where $\pi^{\mathrm{e}}(a|x) \in [0, 1]$ and the sum is 1. However, to not restrict it so we can include other forms, such as the ATE, we refer to it differently. The ATE is also a special case of OPVE for $\mathcal{A} = \{1, 2\}$, where $\pi^{\mathrm{e}}(1|x) = 1$ and $\pi^{\mathrm{e}}(2|x) = -1$. To identify $R(\pi^{\mathrm{e}})$, we assume the overlap in the distributions of policies, convergence of π_{t-1}, and the boundedness of reward.

Assumption 2.1. *For all $t \in [T]$, $a \in \mathcal{A}$, $x \in \mathcal{X}$, and $\Omega_{t-1} \in \mathcal{M}_{t-1}$, there exists a constant $C_\pi > 0$, such that $\left| \frac{\pi^{\mathrm{e}}(a|x)}{\pi_t(a|x, \Omega_{t-1})} \right| \leq C_\pi$.*

Assumption 2.1 equivalently means that $\pi_t(a|x) > 0$ for all $a \in \mathcal{A}$ and $x \in \mathcal{X}$.

Assumption 2.2. *For all $x \in \mathcal{X}$ and $a \in \mathcal{A}$, $\pi_t(a|x, \Omega_{t-1}) - \tilde{\pi}(a|x) \xrightarrow{\mathrm{P}} 0$, where $\tilde{\pi} : \mathcal{A} \times \mathcal{X} \to (0, 1)$.*

Assumption 2.3. *For all $t \in [T]$ and $a \in \mathcal{A}$, there exists a constant $C_Y > 0$, such that $|Y_t(a)| \leq C_Y$.*

Although the reader may feel that Assumption 2.1–2.2 and the SUTVA 2.1 are strong, we adopt it as a simple and basic case for the application, in order to introduce adaptive-fitting and the ADR estimator. We can extend the proposed method for different cases, such as when the data has the structure of batches or when the average of logging policy converges (Kato, 2021). Note that the convergence assumption (Assumption 2.2) is also explicitly or implicitly required in other studies, such as van der Laan (2008) and Hadad et al. (2019).

2.2 Notations

We denote $\mathbb{E}[Y_t(a)|x]$ and $\mathrm{Var}(Y_t(a)|x)$ as $f^*(a, x)$ and $v^*(a, x)$, respectively. Let $\hat{f}_t(a, x)$ be an estimator of $f^*(a, x)$ constructed from Ω_t. Let $\mathcal{N}(\mu, \mathrm{var})$ be the normal distribution with the mean μ and the variance var. For a random variable Z with density $p(z)$ and function μ, let $\|\mu(Z)\|_2 = \int |\mu(z)|^2 p(z)dz$ be the L^2-norm.

3 Preliminaries of OPVE

3.1 Existing estimators

For estimating $R(\pi^e)$ from dependent samples, existing studies propose various estimators. An adaptive version of the IPW estimator is defined as $R_T^{\text{AdaIPW}}(\pi^e) = \frac{1}{T}\sum_{t=1}^{T}\sum_{a=1}^{K}\frac{\pi^e(A_t|X_t)\mathbb{1}[A_t=a]Y_t}{\pi_{t-1}(A_t|X_t,\Omega_{t-1})}$ (van der Laan, 2008). If the model specification is correct, the direct method (DM) estimator $\frac{1}{T}\sum_{t=1}^{T}\sum_{a=1}^{K}\pi^e(a|x)\hat{f}_T(a|X_t)$ is known to be consistent to $R(\pi^e)$. As an adaptive version of the AIPW estimator, van der Laan (2008) proposed an estimator $\widehat{R}_T^{\text{AIPW}}(\pi^e)$ defined as

$$\frac{1}{T}\sum_{t=1}^{T}\sum_{a=1}^{K}\left\{\frac{\pi^e(a|X_t)\mathbb{1}[A_t=a]\left(Y_t-\hat{f}_{t-1}(a,X_t)\right)}{\pi_{t-1}(a|X_t,\Omega_{t-1})}+\pi^e(a|X_t)\hat{f}_{t-1}(a,X_t)\right\}.$$

Using the martingale property, van der Laan (2008) showed asymptotic normality under Assumption 2.2. Hadad et al. (2019) and Kato et al. (2020) organized the results (Proposition 4.1).

3.2 Asymptotic efficiency

We are often interested in the asymptotic efficiency of estimators. The lower bound of the asymptotic variance is defined for an estimator under some posited models of the DGP (2.1). As with the Cramér-Rao lower bound for the parametric model, we can also define the lower bound for the non- or semiparametric model (Bickel et al., 1998). The semiparametric lower bound of the DGP (2.1) under $p_1(a|x) = \cdots = p_T(a|x) = p(a|x)$ is given as follows (Hahn, 1998; Narita et al., 2019):

$$\Psi(\pi^e,p) = \mathbb{E}\left[\sum_{a=1}^{K}\frac{\left(\pi^e(a|X_t)\right)^2 v^*(a,X_t)}{p(a|X_t)}+\left(\sum_{a=1}^{K}\pi^e(a|X_t)f^*(a,X_t)-R(\pi^e)\right)^2\right].$$

The asymptotic variance of the asymptotic distribution is also known as the asymptotic mean squared error (MSE); that is, an OPVE estimator achieving the semiparametric lower bound also minimizes the MSE to the true value $R(\pi^e)$, not just obtaining a tight confidence interval.

3.3 Related work

There are various studies related to OPVE, including ATE estimation, under the assumption that samples are i.i.d. (Hahn, 1998; Hirano et al., 2003; Dudík et al., 2011; Wang et al., 2017b; Narita et al., 2019; Bibaut et al., 2019; Oberst & Sontag, 2019). There are also several studies extending these methods to OPVE from dependent samples (van der Laan, 2008; van der Laan & Lendle, 2014; Luedtke & van der Laan, 2016; Hadad et al., 2019; Kato et al., 2020).

The AIPW estimator for dependent samples are proposed by van der Laan (2008). Hadad et al. (2019) proposed an evaluation weight to stabilize the estimator, which shares a similar motivation with weight clipping, or shrinkage, when i.i.d. samples are given (Bembom & van der Laan, 2008; Bottou et al., 2013; Wang et al., 2017a; Su et al., 2019, 2020). Kato et al. (2020) showed a non-asymptotic confidence interval of the AIPW estimator. van der Laan & Lendle (2014) and Luedtke & van der Laan (2016) proposed an OPVE method without the convergence of the logging policies by using batches and standardization, respectively. Note that Hadad et al. (2019) cannot weaken the assumptions regarding the logging policy, unlike Luedtke & van der Laan (2016). Zhang et al. (2020) proposed an estimator similar to van der Laan & Lendle (2014) and applied it to linear regression. Estimators proposed by van der Laan (2008), Luedtke & van der Laan (2016), Hadad et al. (2019), Kato et al. (2020), and Zhang et al. (2020) require the true logging policy, unlike our ADR estimator.

A semiparametric estimator usually requires the Donsker condition for its asymptotic normality (Bickel et al., 1998). For semiparametric inference without the Donsker condition, sample-splitting is a typical approach (Klaassen, 1987; Zheng & van der Laan, 2011; Chernozhukov et al., 2018). Chernozhukov et al. (2018) referred to sample-splitting as *cross-fitting* and the semiparametric inference using cross-fitting as *double-debiased machine learning* (DML). For off-policy evaluation of reinforcement learning from dependent samples, Kallus & Uehara (2019) proposed a mixingale-based sample-splitting.

4 The ADR estimator

For OPVE with dependent samples, this paper proposes the ADR estimator $\widehat{R}_T^{\mathrm{ADR}}(\pi^{\mathrm{e}})$ defined as

$$\frac{1}{T}\sum_{t=1}^{T}\sum_{a=1}^{K}\left\{\frac{\pi^{\mathrm{e}}(a|X_t)\mathbb{1}[A_t=a]\left(Y_t-\hat{f}_{t-1}(a,X_t)\right)}{\hat{g}_{t-1}(a|X_t)}+\pi^{\mathrm{e}}(a|X_t)\hat{f}_{t-1}(a,X_t)\right\},$$

where $\hat{g}_{t-1}$ is an estimator of π_{t-1}, constructed only from Ω_{t-1}. We can use standard regression methods for constructing $\hat{f}_{t-1}$ and $\hat{g}_{t-1}$ if they satisfy the following assumptions.

Assumption 4.4. *For $p, q > 0$ such that $p+q = 1/2$, $\|\hat{g}_{t-1}(a|X_t)-\pi_{t-1}(a|X_t,\Omega_{t-1})\|_2 = \mathrm{o}_p(t^{-p})$, and $\|\hat{f}_{t-1}(a, X_t) - f^*(a, X_t)\|_2 = \mathrm{o}_p(t^{-q})$, where the expectation of the norm is taken over X_t.*

Assumption 4.5. *There exists a constant C_f such that $|\hat{f}_{t-1}(a,x)| \leq C_f$ $\forall a \in \mathcal{A}, x \in \mathcal{X}$.*

Assumption 4.6. *There exist a constant C_g such that $0 < \left|\frac{\pi^{\mathrm{e}}(a|x)}{\hat{g}_{t-1}(a|x)}\right| \leq C_g$ $\forall a \in \mathcal{A}, x \in \mathcal{X}$.*

Assumption 4.4 requires convergence rates standard in regression estimators. For instance, we can apply nonparametric estimators proposed in MAB problems (Yang & Zhu, 2002; Qian & Yang, 2016). Under the assumptions, we show the asymptotic normality of the ADR estimator.

Theorem 4.1 (Asymptotic distribution of an ADR estimator). *Under Assumptions 2.1–4.6,*

$$\sqrt{T}\left(\widehat{R}_T^{\mathrm{ADR}}(\pi^{\mathrm{e}}) - R(\pi^{\mathrm{e}})\right) \xrightarrow{d} \mathcal{N}\left(0, \Psi(\pi^{\mathrm{e}}, \tilde{\pi})\right).$$

Let us put forward the following assumption.

Assumption 4.7. *For all $x \in \mathcal{X}$ and $a \in \mathcal{A}$, $\hat{f}_{t-1}(a,x) - f^*(a,x) \xrightarrow{\mathrm{P}} 0$.*

The proof is shown in Appendix B, which uses the following proposition from Kato et al. (2020).

Proposition 4.1 (Asymptotic distribution of an AIPW estimator (Corollary 1, Kato et al. (2020)).)**.** *Under Assumptions 2.1–2.3, 4.5, and 4.7, $\sqrt{T}\left(\widehat{R}_T^{\mathrm{AIPW}}(\pi^{\mathrm{e}}) - R(\pi^{\mathrm{e}})\right) \xrightarrow{d} \mathcal{N}\left(0, \Psi(\pi^{\mathrm{e}}, \tilde{\pi})\right).$*

Remark 4.3 (Consistency and double robustness). *The ADR estimator has double robustness, as with standard DR estimators; that is, if either $\hat{f}$ or $\hat{g}$ is consistent, the ADR estimator is also consistent.*

Theorem 4.2 (Consistency). *Under Assumptions 2.1–2.3 and 4.5–4.6, if either $\hat{f}_{t-1}$ or $\hat{g}_{t-1}$ is consistent, $\widehat{R}_T^{\mathrm{ADR}} \xrightarrow{\mathrm{P}} R(\pi^{\mathrm{e}})$.*

We can prove this by the law of large numbers for martingales (Proposition 1.3 in Appendix A).

Donsker condition. The main reason for using step-wise estimators $\{\hat{f}_{t-1}\}_{t=1}^{T}$ and $\{\hat{g}_{t-1}\}_{t=1}^{T}$ is to regard them as constants in the expectation conditioned on Ω_{t-1}. The motivation is shared with DML. For asymptotic normality shown in Theorem 4.1, we do not impose the Donsker condition on the nuisance estimators, $\hat{f}_{t-1}$ and $\hat{g}_{t-1}$, but only require the convergence rate conditions. We call this sample-splitting method, using $\hat{f}_{t-1}$ and $\hat{g}_{t-1}$, *adaptive-fitting* and discuss again in Section 5. In the MAB problem, convergence rate conditions in nonparametric regression, such as a nearest-neighbor regression (Yang & Zhu, 2002), Nadaraya-Watson regression (Qian & Yang, 2016), random forest (Féraud et al., 2016), kernelized linear models (Chowdhury & Gopalan, 2017), and neural networks (Dongruo Zhou, 2020), have been shown. Note that we need to slightly modify the results for each situation because they are influenced by time-series behavior of logging probabilities.

Convergence rate of the logging policy. In the main theorem, we do not explicitly describe the convergence rate of the logging policy. However, from Assumption 4.4, which requires $\|\hat{g}_{t-1}(a|X_t)-\pi_{t-1}(a|X_t,\Omega_{t-1})\|_2 = \mathrm{o}_p(t^{-p})$, $\|\tilde{\pi}(a|x) - \pi_{t-1}(a|X_t,\Omega_{t-1})\|_2 = \mathrm{o}_p(t^{-p})$ is also required.

Theoretical comparison between AIPW and ADR estimators. There are two major differences between AIPW and ADR estimators. First, the AIPW estimator requires *a priori* knowledge of the true logging policy, but the ADR estimator does not. Another main difference between the two is the convergence rate of nuisance estimators $\hat{g}_{t-1}$ and $\hat{f}_{t-1}$. For the AIPW estimator, only the uniform convergence in probability is required, but the ADR estimator requires specific convergence rates on

211 $\hat{g}_{t-1}$ and $\hat{f}_{t-1}$. This difference comes from unbiasedness. The AIPW estimator is unbiased; therefore,
212 the convergence of the asymptotic variance is essential, where it converges with $o_p(1)$ if $\hat{f}$ and π_t is
213 $o_p(1)$. Thus, the AIPW estimator does not require specific convergence rates. On the other hand, the
214 ADR estimator requires the asymptotic bias term to vanish in a specific order. For this purpose, it
215 imposes specific convergence rates on the nuisance estimators. From another perspective, a standard
216 DML for i.i.d. samples and Theorem 4.1 require $\|\hat{g}_{t-1}(a|X_t) - \pi_{t-1}(a|X_t, \Omega_{t-1})\|_2 = o_p(t^{-p})$,
217 $\|\hat{f}_{t-1}(a, X_t) - f^*(a, X_t)\|_2 = o_p(t^{-q})$, and $p + q = 1/2$.

218 **Asymptotic efficiencies.** As shown in Theorem 4.1 and Proposition 4.1, ADR and AIPW estimators
219 achieve the semiparametric lower bound. On the other hand, the asymptotic variance of the IPW
220 estimator using the true logging policy π_t is larger than the lower bound (Hirano et al., 2003; van der
221 Laan, 2008; Kato et al., 2020). Although it is known that the IPW estimator using the estimated
222 logging policy can achieve the lower bound under some conditions with i.i.d. samples (Hirano et al.,
223 2003), the asymptotic property under dependent samples is still unknown.

5 Adaptive-fitting: DML for dependent samples

225 We generalize the method used to derive the asymptotic normality of the ADR estimator as a variant
226 of DML. Let us define the parameter of interest θ_0 that satisfies $\mathbb{E}[\psi(W_t; \theta_0, \eta_0)]$, where $\{W_t\}_{t=1}^T$
227 are observations, η_0 is a nuisance parameter, and ψ is a score function. We consider obtaining
228 an asymptotic normal estimator of θ_0 when using complex and data-adaptive regression methods,
229 such as random forests, neural networks, and Lasso. Under such a situation, the Donsker condition
230 does not hold, in general. Sample-splitting is a typical approach to control the complexities of
231 semiparametric inference without the Donsker condition (Klaassen, 1987; Zheng & van der Laan,
232 2011; Chernozhukov et al., 2018). In DML of Chernozhukov et al. (2018), the dataset with i.i.d.
233 samples $\{W_t\}_{t=1}^T$ is separated into several subgroups. Then, a semiparametric estimator for each
234 subgroup is constructed, but the nuisance estimators are constructed from the other subgroups. Here,
235 the nuisance estimators are independent in the expectation conditioned on the other subgroups.
236 Thus, the complexities are controlled without the Donsker condition, and standard nonparametric
237 convergence rate conditions on nuisance estimators suffice to show the asymptotic normality of the
238 semiparametric estimator. Chernozhukov et al. (2018) called the method cross-fitting.

239 However, cross-fitting of Chernozhukov et al.
240 (2018) cannot be applied when samples
241 $\{W_t\}_{t=1}^T$ are dependent. Therefore, the ADR es-
242 timator uses step-wise nuisance estimators based
243 on past observations Ω_{t-1}. This construction
244 is inspired by van der Laan & Lendle (2014),
245 which proposed a sample-splitting for batched
246 dependent samples. The nuisance estimators
247 are independent in the expectation over the t-th
248 samples conditioned on Ω_{t-1}. Thus, we can re-
249 gard our sample-splitting as another approach

Figure 1: The difference between cross-fitting (left) and adaptive-fitting (right).

250 for DML. We call this step-wise construction *adaptive-fitting*, in contrast to cross-fitting. We briefly
251 summarize the procedure as follows: (i) at each step $t = 1, 2, \ldots, T$, we estimate η_0 only using
252 $\{W_s\}_{s=1}^{t-1}$ and denote the estimaters as $\{\eta_{t-1}\}_{t=1}^T$; (ii) then, we substitute W_t and η_{t-1} into ψ and
253 obtain an estimator $\hat{\theta}_T$ of θ_0 by solving $\frac{1}{T}\sum_{T=1}^T \psi(W_t, \hat{\theta}_T, \eta_{t-1}) = 0$. Under this construction, if
254 (a) an estimator $\check{\theta}_T$ obtained by solving $\frac{1}{T}\sum_{T=1}^T \psi(W_t, \check{\theta}_T, \eta_0) = 0$ has the asymptotically normal
255 distribution and (b) the asymptotic bias decays with the rate faster than $o_p(-1/\sqrt{t})$, we can obtain the
256 asymptotically normal estimator of θ_0. In Figure 1, we illustrate the difference between cross-fitting
257 (left) and adaptive-fitting (right). The y-axis represents samples used for constructing the OPVE
258 estimator with nuisance estimators using samples represented by the x-axis. In the left graph, for
259 T/K samples, we calculate the sample average of the component including nuisance estimators
260 based on the other $(K-1)T/K$ samples. In the right graph, at period t, we use nuisance estimators
261 constructed from samples at $t = 1, 2, \ldots, t-1$. To satisfy (a), we assumed that the convergence of
262 the logging policy (Assumption 2.2). There are other ways to satisfy this condition. For example, we
263 can assume the existence of batches as van der Laan & Lendle (2014) and Zhang et al. (2020). We
264 briefly introduce the ADR estimator wit the case in Appendix C.

Table 1: The results of Section 6.1 with sample sizes $T = 250, 500, 750$. We show the RMSE, SD, and coverage ratio of the confidence interval (CR). We highlight in red bold two estimators with the lowest RMSE. Estimators with asymptotic normality are marked with †, and estimators that do not require the true logging policy are marked with ∗.

	LinUCB policy																	
T	ADR †∗			IPW †			AIPW †			AW-AIPW †			DM ∗			EIPW ∗		
	RMSE	SD	CR	RMSE	SD	CR	RMSE	SD	CR	RMSE	SD	CR	RMSE	SD	CR	RMSE	SD	CR
250	**0.054**	0.003	0.97	0.117	0.034	0.87	0.106	0.036	0.90	0.152	0.022	0.09	0.073	0.006	0.12	0.103	0.017	0.82
500	**0.040**	0.002	0.94	0.078	0.014	0.93	0.059	0.007	0.98	0.179	0.020	0.00	0.046	0.002	0.16	0.121	0.013	0.40
750	**0.033**	0.001	0.97	0.064	0.008	0.90	0.059	0.006	0.97	0.176	0.015	0.00	0.040	0.002	0.15	0.122	0.012	0.22

	LinTS policy																	
T	ADR †∗			IPW †			AIPW †			AW-AIPW †			DM ∗			EIPW ∗		
	RMSE	SD	CR	RMSE	SD	CR	RMSE	SD	CR	RMSE	SD	CR	RMSE	SD	CR	RMSE	SD	CR
250	**0.049**	0.002	0.96	0.128	0.037	0.82	0.107	0.031	0.93	0.121	0.016	0.20	0.069	0.005	0.15	0.077	0.011	0.89
500	**0.035**	0.001	0.95	0.151	0.139	0.91	0.122	0.086	0.91	0.136	0.014	0.06	0.048	0.002	0.13	0.090	0.007	0.57
750	**0.028**	0.001	0.97	0.069	0.010	0.90	0.053	0.005	0.91	0.154	0.013	0.00	0.036	0.001	0.14	0.113	0.009	0.23

6 Paradox concerning logging policy

The advantage of the ADR estimator is that, unlike the AIPW estimator, it does not require the true logging policy. However, we find that the ADR estimator often achieves a smaller MSE than the AIPW estimator, which requires the true logging policy. We refer to this phenomenon as a paradox concerning logging policy.

6.1 Instability of the AIPW estimator

Hadad et al. (2019) pointed out that the AIPW estimator tends to be unstable when the nuisance parameter π_{t-1} can take a value close to zero before converging to $\tilde{\pi}$. To prevent this instability, Hadad et al. (2019) proposed the Adaptively Weighted AIPW (AW-AIPW) estimator by adding evaluation weights, which converge to a constant almost surely, to the AIPW estimator proposed in other studies, such as van der Laan (2008). Note that the AW-AIPW estimator cannot mitigate the assumptions on the logging policy π_{t-1} required in the AIPW (van der Laan, 2008) and our ADR estimator, namely π_{t-1} is non-zero and converges. The aim of adaptive weighting is not in theoretical improvement of the AIPW estimator, but in its empirical stabilization.

6.2 Sensitivity of the ADR estimator to the logging policy.

The ADR estimator replaces the true logging policy π_{t-1} with its estimator. We find that by replacing the true logging policy with its estimator, we can control the instability caused from π_{t-1} by constructing well-formed $\hat{g}_{t-1}$. For example, if we know that the range of $\tilde{\pi}$ is $(\varepsilon, 1 - \varepsilon)$ for $0 < \varepsilon < 1 - \varepsilon < 1$, we can add the clipping technique when estimating $\hat{g}_{t-1}$. For example, in early periods, we can set $\hat{g}_{t-1}$ as 0.5. Such techniques is greatly beneficial. Note that if the range of $\tilde{\pi}$ is truly $(\varepsilon, 1 - \varepsilon)$, the clipping of $\hat{g}_{t-1}$ does not cause clipping bias; that is, the estimator correctly converges to the asymptotic distribution shown in Theorem 4.1.

The main difference between the AW-AIPW estimator and the ADR estimator is that the former requires information of the true logging policy π_{t-1}, while the latter does not by replacing it with its estimator. Note that the AW-AIPW estimator requires the same assumptions on π_{t-1} as the AIPW and ADR estimator and loses unbiasedness due to the evaluation weight. In addition, the construction of the adaptive weight is not obvious when there are covariates X_t because all but one method for weight construction in Hadad et al. (2019) does not consider covariates. Our finding also shares motivation with weight clipping for i.i.d. samples, such as Bottou et al. (2013). We can regard the AW-AIPW estimator as a variant of this method, where the weight clipping can decay as π_t converges, and be ignored asymptotically. However, our interest is in asymptotic normality from dependent samples without the true logging policy, which is not discussed in the literature.

6.3 Simulation studies for OPVE estimators

For reasons given in the previous section, the ADR estimator may empirically perform better than the AIPW estimator because the estimator $\hat{g}_{t-1}$ stabilizes the ADR estimator by absorbing the instability of π_{t-1}. We empirically show this paradox using a synthetic dataset. We generate an artificial pair of covariate and potential outcome, $(X_t, Y_t(1), Y_t(2), Y_t(3))$. The covariate X_t is a 10 dimensional vector generated from the standard normal distribution. For $a \in \{1, 2, 3\}$, $Y_t(a) = 1$ if a is chosen with

Figure 2: This figure illustrates the error distributions of estimators for OPVE from dependent samples generated with the LinUcB(left) and LinTS(right) with the sample size 750. We smoothed the error distributions using kernel density estimation. Estimators with asymptotic normality are marked with †, and estimators that do not require a true logging policy are marked with ∗.

probability $q(a|x) = \frac{\exp(g(a,x))}{\sum_{a'=1}^{3}\exp(g(a',x))}$, where $g(1,x) = \sum_{d=1}^{10} X_{t,d}$, $g(2,x) = \sum_{d=1}^{10} W_d X_{t,d}^2$, $g(3,x) = \sum_{d=1}^{10} W_d|X_{t,d}|$, and W_d is uniform randomly chosen from $\{-1,1\}$. We generate three datasets, $\mathcal{S}_{T_{(1)}}^{(1)}$, $\mathcal{S}_{T_{(2)}}^{(2)}$, and $\mathcal{S}_{T_{(3)}}^{(3)}$, where $\mathcal{S}_{T_{(m)}}^{(m)} = \{(X_t^{(m)}, Y_t^{(m)}(1), Y_t^{(m)}(2), Y_t^{(m)}(3))\}_{t=1}^{T_{(m)}}$. First, we train an evaluation function π^e by solving a prediction problem between $X_t^{(1)}$ and $Y_t^{(1)}(1), Y_t^{(1)}(2), Y_t^{(1)}(3)$ using $\mathcal{S}_{T_{(1)}}^{(1)}$. Then, we regard the evaluation function π^e as a logging policy and apply it on the independent dataset $\mathcal{S}_{T_{(2)}}^{(2)}$ to obtain $\{(X_t', A_t', Y_t')\}_{t=1}^{T_{(2)}}$, where A_t' is an action chosen from the evaluation function and $Y_t^{(m)} = \sum_{a=1}^{3} \mathbb{1}[A_t^{(m)} = a]Y_t^{(m)}(a)$. Then, we estimate the true value $R(\pi^e)$ as $\frac{1}{T_{(2)}}\sum_{t=1}^{T_{(2)}} Y_t^{(m)}$. Next, using the datasets $\mathcal{S}_{T_{(3)}}^{(3)}$ and an MAB algorithm, we generate a bandit dataset $\mathcal{S} = \{(X_t, A_t, Y_t)\}_{t=1}^{T_{(3)}}$. For $\mathcal{S}$, we apply the ADR estimator, IPW estimator with the true logging policy (IPW), AIPW estimator (AIPW), AW-AIPW estimator (AW-AIPW) IPW estimator with estimated logging policy (EIPW), and DM estimator (DM). For the AW-AIPW estimator, we use the evaluation weight $\sqrt{\pi_{a,x}(t)/T}$, proposed in Hadad et al. (2019). The other proposed weights of Hadad et al. (2019) seem to be specific to situations without covariate X_t. For estimating f^* and the logging policy, we use the kernelized Ridge least squares and logistic regression, respectively. We use a Gaussian kernel, and both hyper-parameters of the Ridge and kernel are chosen from $\{0.01, 0.1, 1\}$. We define the estimation error as $R(\pi^e) - \widehat{R}(\pi^e)$. We conduct ten experiments by changing sample sizes and MAB algorithms. For the sample size $T_{(3)}$, we use 100, 250, 500, 750, and 10,000 with the LinUCB and LinTS algorithms. For the sample sizes $T_{(1)}$ and $T_{(2)}$, we use 1,000 and 100,000 respectively. We conduct 100 trials to obtain the root MSEs (RMSEs), the standard deviations of MSEs (SDs), and the coverage ratios (CRs) of the 95% confidence interval (percentage that the confidence interval covers the true value). The results with $T = 250, 500, 750$ are shown in Table 1 and those with $T = 750$ are shown in Figure 2. The other results are shown in Appendix D. In all cases, the ADR estimator performs well compared to other methods. Although the AIPW estimator has asymptotic normality, the performance is not comparable with the ADR estimator. The reason why the AW-AIPW estimator underperforms is that the performance depends on the choice of evaluation weights, and the weight proposed by Hadad et al. (2019) is not suitable for our case with covariates. The EIPW estimator suffers from the dependency problem. We postulate that this is owing to the instability of π_t.

Remark 6.4 (Paradox for i.i.d. samples). *This paradox is similar to the well-known property that the IPW estimator using an estimated propensity score shows a smaller asymptotic variance than the IPW using the true one (Hirano et al., 2003; Henmi & Eguchi, 2004; Henmi et al., 2007). However, as discussed above, we consider this to be a different phenomenon. In these studies, the paradox is mainly explained by differences in the asymptotic variance between IPW estimators with the true and estimated propensity score. On the other hand, for our case, AIPW and ADR estimators have the same asymptotic variance, unlike IPW-type estimators. Therefore, we cannot resolve the paradox by the aforementioned explanations. The instability of the AIPW estimator is consistent with the findings of Hadad et al. (2019), but, in our paper, we suggest using the ADR estimator as another solution.*

Table 2: The results of benchmark datasets with the LinUCB policy. We highlight in red bold the estimator with the lowest RMSE and highlight in under line the estimator with the lowest RMSE among estimators that do not use the true logging policy. Estimators with asymptotic normality are marked with †, and estimators that do not require the true logging policy are marked with ∗.

mnist	ADR †∗		IPW †		AIPW †		DM ∗		EIPW ∗	
α	RMSE	SD	RMSE	SD	RMSE	SD	RMSE	SD	RMSE	SD
0.7	**_0.046_**	0.002	0.100	0.011	0.162	0.027	0.232	0.013	0.148	0.014
0.4	**_0.028_**	0.001	0.068	0.005	0.112	0.009	0.249	0.010	0.080	0.004
0.1	_0.086_	0.006	**0.078**	0.006	0.085	0.008	0.299	0.024	0.091	0.008

satimage	ADR †∗		IPW †		AIPW †		DM ∗		EIPW ∗	
α	RMSE	SD	RMSE	SD	RMSE	SD	RMSE	SD	RMSE	SD
0.7	**_0.013_**	0.000	0.098	0.011	0.060	0.004	0.037	0.001	0.056	0.002
0.4	**_0.022_**	0.000	0.078	0.008	0.019	0.000	0.043	0.001	0.060	0.002
0.1	**_0.029_**	0.001	0.078	0.005	0.061	0.008	0.041	0.002	0.041	0.002

7 Experiments

Following Dudík et al. (2011), we evaluate the estimators using classification datasets by transforming them into contextual bandit data. From the LIBSVM repository (Chang & Lin, 2011), we use the `mnist`, `satimage`, `sensorless`, and `connect-4` datasets [1]. The dataset description is in Table 3 of Appendix D. We construct a logging policy as $\pi_t(a|x) = \alpha\pi_t^m(a|x) + (1-\alpha)\frac{0.1}{K}$, where $\alpha \in (0,1)$ is a constant, and $\pi_t^m(a|x)$ is a policy such that $\pi_t^m(a|x) = 1$ for an action $a \in \mathcal{A}$ and $\pi_t^m(a'|x) = 0$ for the other actions ($a' \neq a$). The policy $\pi_t^m(a|x)$ is determined by logistic regression and MAB algorithms. For MAB algorithms, we use upper confidence bound and Thompson sampling with a linear model, which are denoted as LinUCB (Chu et al., 2011) and LinTS (Agrawal & Goyal, 2013). The evaluation function is fixed at $\pi^e(a|x) = 0.9\pi^d(a|x) + \frac{0.1}{K}$, where π_d is a prediction of a logistic regression.

We focus on the ADR estimator and compare it to the IPW, EIPW, AIPW, and DM estimators, as done in Section 6.3. We omit the AW-AIPW estimator, as we found that the performance depends on the choice of the evaluation weight (see Section 6). Additionally, the paper does not consider or discuss situations where there exist covariates. We compare those estimators using the benchmark datasets generated through the process explained above. For $\alpha \in \{0.7, 0.4, 0.1\}$ and the sample sizes 800, 1,000, and 1,200, we calculate the RMSEs and the SDs over 10 trials. The results of `mnist` and `satimage` with the LinUCB policy and $T = 1,000$ are shown in Tables 2. The full results, including the results with the LinTS policy and i.i.d. samples, are shown in Appendix D. As discussed in Section 6, the ADR estimator performs well. Although the asymptotic distributions of AIPW and ADR estimators are the same, the AIPW estimator shows poorer performance. As Section 6.3, we consider this to be because the estimator of π_t is absorbing the instability of π_t.

Note that the ADR, IPW, and AIPW estimators are asymptotically normal, but the IPW and APIW estimators are not feasible when the true logging policy is not given. To the best of our knowledge, asymptotic normality of the EIPW and DM estimators has not been shown when samples are dependent, and the proof is non-trivial owing to the dependency and the Donsker condition.

8 Conclusion

DR-type estimators are crucial in causal inference because they do not assume *a priori* knowledge of the true logging policy and they asymptotically follow a normal distribution under standard convergence rate conditions of nuisance estimators. However, existing studies have rarely discussed DR-type estimators when samples are dependent. We derived the ADR estimator and proposed adaptive-fitting as a variant of DML to obtain asymptotic normality. In experiments, we found a paradox that the ADR estimator tends to be more stable than the AIPW estimator and conjectured that this is because the ADR estimator absorbs the instability of the true logging policy π_t.

In OPVE with dependent samples, we need to put some assumptions on the behavior of π_t to obtain asymptotic normality (Assumption 2.2). These assumptions can be broken if the time-series is very complicated. However, we note that this is a limitation of the entire field. The asymptotic normality and double robustness of OPVE estimators are necessary theoretical properties to avoid deriving false causality. Since causal inference is often used in applications related closely to public policy, we consider understanding these limitations critical.

---

[1] https://www.csie.ntu.edu.tw/~cjlin/libsvmtools/datasets/.

References

Agrawal, S. and Goyal, N. Thompson sampling for contextual bandits with linear payoffs. In *ICML*, 2013.

Bang, H. and Robins, J. M. Doubly robust estimation in missing data and causal inference models. *Biometrics*, 61(4):962–973, 2005.

Bembom, O. and van der Laan, M. J. Data-adaptive selection of the truncation level for inverse-probability-of-treatment-weighted estimators, 2008.

Bibaut, A., Malenica, I., Vlassis, N., and Van Der Laan, M. More efficient off-policy evaluation through regularized targeted learning. In *ICML*, 2019.

Bickel, P. J., Klaassen, C. A. J., Ritov, Y., and Wellner, J. A. *Efficient and Adaptive Estimation for Semiparametric Models*. Springer, 1998.

Bottou, L., Peters, J., Quiñonero-Candela, J., Charles, D. X., Chickering, D. M., Portugaly, E., Ray, D., Simard, P., and Snelson, E. Counterfactual reasoning and learning systems: The example of computational advertising. *Journal of Machine Learning Research*, 14(65):3207–3260, 2013.

Chang, C.-C. and Lin, C.-J. LIBSVM: A library for support vector machines. *ACM Transactions on Intelligent Systems and Technology*, 2:27:1–27:27, 2011. Software available at `http://www.csie.ntu.edu.tw/~cjlin/libsvm`.

Chernozhukov, V., Chetverikov, D., Demirer, M., Duflo, E., Hansen, C., Newey, W., and Robins, J. Double/debiased machine learning for treatment and structural parameters. *The Econometrics Journal*, 2018.

Chow, S.-C. and Chang, M. *Adaptive Design Methods in Clinical Trials*. Chapman and Hall/CRC, 2 edition, 2011.

Chowdhury, S. R. and Gopalan, A. On kernelized multi-armed bandits. In *ICML*, 2017.

Chu, W., Li, L., Reyzin, L., and Schapire, R. Contextual bandits with linear payoff functions. In *AISTATS*, 2011.

Dongruo Zhou, Lihong Li, Q. G. Neural contextual bandits with ucb-based exploration. In *ICML*, 2020.

Dudík, M., Langford, J., and Li, L. Doubly Robust Policy Evaluation and Learning. In *ICML*, 2011.

Féraud, R., Allesiardo, R., Urvoy, T., and Clérot, F. Random forest for the contextual bandit problem. In *ICML*, 2016.

Gittins, J. C. *Multi-armed Bandit Allocation Indices*. Wiley, Chichester, NY, 1989.

Hadad, V., Hirshberg, D. A., Zhan, R., Wager, S., and Athey, S. Confidence intervals for policy evaluation in adaptive experiments, 2019.

Hahn, J. On the role of the propensity score in efficient semiparametric estimation of average treatment effects. *Econometrica*, 66(2):315–331, 1998.

Hahn, J., Hirano, K., and Karlan, D. Adaptive experimental design using the propensity score. *Journal of Business and Economic Statistics*, 2011.

Hall, P., Heyde, C., Birnbaum, Z., and Lukacs, E. *Martingale Limit Theory and Its Application*. Communication and Behavior. Elsevier Science, 2014.

Henmi, M. and Eguchi, S. A paradox concerning nuisance parameters and projected estimating functions. *Biometrika*, 2004.

Henmi, M., Yoshida, R., and Eguchi, S. Importance Sampling Via the Estimated Sampler. *Biometrika*, 2007.

Hirano, K., Imbens, G., and Ridder, G. Efficient estimation of average treatment effects using the estimated propensity score. *Econometrica*, 2003.

Horvitz, D. G. and Thompson, D. J. A generalization of sampling without replacement from a finite universe. *Journal of the American Statistical Association*, 1952.

Kallus, N. and Uehara, M. Efficiently breaking the curse of horizon: Double reinforcement learning in infinite-horizon processes, 2019.

Kato, M. Adaptive doubly robust estimator from non-stationary logging policy under a convergence of average probability, 2021.

Kato, M., Ishihara, T., Honda, J., and Narita, Y. Adaptive experimental design for efficient treatment effect estimation: Randomized allocation via contextual bandit algorithm. *arXiv:2002.05308*, 2020.

Klaassen, C. A. J. Consistent estimation of the influence function of locally asymptotically linear estimators. *Ann. Statist.*, 1987.

Lattimore, T. and Szepesvári, C. *Bandit Algorithms*. Cambridge University Press, 2020.

Li, L., Chu, W., Langford, J., and Schapire, R. E. A contextual-bandit approach to personalized news article recommendation. In *WWW*, 2010.

Li, L., Chu, W., Langford, J., and Wang, X. Unbiased offline evaluation of contextual-bandit-based news article recommendation algorithms. In *WSDM*, 2011.

Li, L., Munos, R., and Szepesvari, C. Toward minimax off-policy value estimation. *AISTATS*, pp. 608–616, 2015.

Loeve, M. *Probability Theory*. Graduate Texts in Mathematics. Springer, 1977.

Luedtke, A. R. and van der Laan, M. J. Statistical inference for the mean outcome under a possibly non-unique optimal treatment strategy. *Annals of Statistics*, 2016.

Narita, Y., Yasui, S., and Yata, K. Efficient counterfactual learning from bandit feedback. In *AAAI*, 2019.

Oberst, M. and Sontag, D. Counterfactual off-policy evaluation with gumbel-max structural causal models. In *ICML*, 2019.

Qian, W. and Yang, Y. Kernel estimation and model combination in a bandit problem with covariates. *Journal of Machine Learning Research*, 2016.

Rubin, D. B. Estimating causal effects of treatments in randomized and nonrandomized studies. *Journal of Educational Psychology*, 66(5):688–701, 1974.

Rubin, D. B. Statistics and causal inference: Comment: Which ifs have causal answers. *Journal of the American Statistical Association*, 1986.

Su, Y., Wang, L., Santacatterina, M., and Joachims, T. CAB: Continuous adaptive blending for policy evaluation and learning. In Chaudhuri, K. and Salakhutdinov, R. (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 6005–6014. PMLR, 09–15 Jun 2019.

Su, Y., Dimakopoulou, M., Krishnamurthy, A., and Dudik, M. Doubly robust off-policy evaluation with shrinkage. In III, H. D. and Singh, A. (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 9167–9176. PMLR, 13–18 Jul 2020.

van der Laan, M. J. The construction and analysis of adaptive group sequential designs, 2008.

van der Laan, M. J. and Lendle, S. D. Online targeted learning, 2014.

Villar, S. S. Bandit strategies evaluated in the context of clinical trials in rare life-threatening diseases. *Probability in the engineering and informational sciences*, 32(2):229–245, Apr 2018.

Wang, Y.-X., Agarwal, A., and Dudík, M. Optimal and adaptive off-policy evaluation in contextual bandits. In Precup, D. and Teh, Y. W. (eds.), *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 3589–3597. PMLR, 06–11 Aug 2017a.

Wang, Y.-X., Agarwal, A., and Dudik, M. Optimal and adaptive off-policy evaluation in contextual bandits. In *ICML*, 2017b.

White, J. *Bandit Algorithms for Website Optimization: Developing, Deploying, and Debugging*. O'Reilly Media, 2012.

Yang, Y. and Zhu, D. Randomized allocation with nonparametric estimation for a multi-armed bandit problem with covariates. *Annals of Statistics*, 30(1):100–121, 02 2002.

Zhang, B., Tsiatis, A. A., Davidian, M., Zhang, M., and Laber, E. Estimating optimal treatment regimes from a classification perspective. *Stat*, 1(1):103–114, Jan 2012a.

Zhang, K., Janson, L., and Murphy, S. Inference for batched bandits. In *NeurIPS*, 2020.

Zhang, W., Zhang, Y., Gao, B., Yu, Y., Yuan, X., and Liu, T.-Y. Joint optimization of bid and budget allocation in sponsored search. *KDD*, 08 2012b.

Zhao, Y., Zeng, D., Rush, A., and Kosorok, M. Estimating individualized treatment rules using outcome weighted learning. *Journal of the American Statistical Association*, 107:1106–1118, 09 2012.

Zheng, W. and van der Laan, M. J. Cross-validated targeted minimum-loss-based estimation. In *Targeted Learning: Causal Inference for Observational and Experimental Data*, Springer Series in Statistics. Springer-Verlag New York, 2011.