Robust Detection Outcome:
A Metric for Pathology Detection in Medical Images

Figure 1: Example images from the ChestX-ray8 dataset (Wang et al., 2017) with example predicted (dashed) and target (solid) bounding boxes, and the corresponding IoU, acc@IoU, AP@IoU, and RoDeO results. **Left to right**: Correct box with misclassification, partly overlapping box, too large predicted box, wrong prediction.

Abstract

Detection of pathologies is a fundamental task in medical imaging and the evaluation of algorithms that can perform this task automatically is crucial. However, current object detection metrics for natural images don't reflect the specific clinical requirements in pathology detection sufficiently. To tackle this problem, we propose *Robust Detection Outcome* (RoDeO); a novel metric for evaluating algorithms for pathology detection in medical images, especially in chest X-rays. RoDeO evaluates different errors directly and individually, and reflects clinical needs better than current object detection metrics. Extensive evaluation shows the superiority of our metrics compared to existing ones.

Keywords: Metric, Pathology Detection, Object Detection.

1. Introduction

Localization of pathologies in medical images is of high clinical relevance. It does not only speed up diagnosis but is also a valuable property for the interpretability of machine learning models. Especially useful in this regard are bounding boxes, as they both satisfy the clinical need for coarse localization and are easier to obtain than exact segmentations. However, we have found current object detection metrics for natural images — like *mean Average*

Precision (mAP) — to be unsuitable for pathology detection in some medical images, such as chest radiographs.

The metric *AP@IoU* first performs a greedy matching between predicted and target boxes while only considering predicted boxes that have the same class and an *Intersection over Union (IoU)* above a defined threshold with the target box. Each target box can be matched to at most one predicted box (the one with the highest IoU). All unmatched boxes and those below the threshold are considered false positives. In the next step, the *average precision (AP)* between the associated classes of the predicted and target boxes is computed. To obtain the mAP, the results of multiple IoU thresholds are averaged [1]. Similarly, other classification metrics can be converted to detection metrics by computing them at IoU-thresholds, such as acc@IoU, recall@IoU, or the average number of false positives (afp@IoU).

Although the tasks are similar, the requirements of object detection in natural images and pathology detection in medical images are much different. For medical pathology detection, coarse localization is already clinically useful and the detection of pathologies is valuable even under misclassification since radiologists are well-trained to classify a pathology once it is detected. Lastly, different sources of errors need to be measured separately, a common requirement for all object detection tasks. Current object detection metrics do not reflect these requirements well: IoU-based metrics are commonly used at high IoU-thresholds (≥ 0.5). Since these are typically hard to obtain in pathology detection, earlier works have used significantly lower thresholds (Baumgartner et al., 2021; Jaeger et al., 2020). Additionally, these metrics do not differentiate between different types of errors: misclassification, faulty localization, shape mismatch, and overprediction all cause false positives and thus degrade the score in the same way, although their underlying sources are much different. This makes metrics like AP@IoU hard to interpret and models hard to compare if they are only evaluated under this metric. Moreover, AP@IoU and mAP are sensitive to misclassification and do not attribute the detection of pathologies if their predicted class is wrong. Lastly, all metrics based on IoU thresholds only have a limited notion of proximity and collapse harshly if their IoU requirements are not met. Figure 1 shows cases where AP@IoU and acc@IoU exhibit such undesired behaviors.

To tackle the aforementioned weaknesses of existing metrics, we introduce RoDeO, a new metric for pathology detection based on three types of errors that cause the quality of an object detector prediction to deteriorate: classification errors, localization errors, and shape mismatch. RoDeO is easy to interpret, returns sub-scores for different error types, degrades gracefully, and reflects the specific requirements of pathology detection.

Our contributions are the following

- We identify weaknesses in current detection metrics when used for pathology detection.

- We propose RoDeO, a new metric for pathology detection that better reflects the clinical needs of this task.

- We perform extensive empirical evaluation of our proposed metric compared to existing ones and showcase how RoDeO identifies weaknesses of an exemplary pathology detection model.

---

1. In some cases, mAP is referred to as the AP at a single threshold only averaged over the classes. This is NOT the definition we use in this document.

2. Related Work

The default metric for object detection in computer vision tasks is average precision. In the PASCAL VOC challenge (Everingham et al., a,b), AP@50 is used, while in the COCO detection challenge (Lin et al., 2014), mAP is the main challenge metric (with IoU-thresholds from 0.5 to 0.95 in steps of 0.05). Several attempts have been made to isolate different error types of AP@IoU and mAP by observing how the metric changes when certain errors in the predictions are fixed (Bolya et al., 2020; Borji and Iranmanesh, 2019; Hoiem et al., 2012). However, these techniques are merely fighting symptoms of average precision and inherit all other weaknesses of the metric minus its explainability. Moreover, they add another layer of complexity on top of the original metrics, again complicating their interpretability. Recall@IoU – or specifically the mean average recall over multiple IoU thresholds – is also evaluated in the COCO detection challenge. Other popular object detection metrics are also IoU-based. To evaluate a baseline model on the ChestX-ray8 dataset, (Wang et al., 2017) use the accuracy or number of average positive predictions at a given threshold [2].

All of the above metrics compute classification quantities after thresholding at an IoU. RoDeO overcomes this limitation and provides per-error metrics that are easily interpretable, degrade gracefully, and are tailored to clinical needs in chest X-ray analysis.

3. RoDeO Metric

Overview In RoDeO, firstly one-to-one correspondences between the predicted and target bounding boxes are established. Then, three sub-metrics (localization, shape similarity, and classification) are computed using the matched boxes. The scores for over- and underpredictions are then linearly combined with the scores of each sub-metric. Lastly, the harmonic mean of the three sub-metrics is computed to obtain one summary metric.

Matching To be able to compute subsequent sub-metrics, first, a matching between the predicted and target boxes is required for every image. We find these correspondences using the Hungarian method, taking into account correct classifications, as well as shape and distance information via the generalized IoU (gIoU) (Rezatofighi et al., 2019). Given the sets of target and predicted boxes, $\mathcal{M}^{\mathfrak{t}}$ and $\mathcal{M}^{\mathfrak{p}}$, the cost matrix $\mathcal{C}$ is:

$$\mathcal{C}_{\mathcal{B}^{\mathfrak{t}}, \mathcal{B}^{\mathfrak{p}}} = -\mathbb{1}_{[y_{\mathcal{B}^{\mathfrak{t}}} = y_{\mathcal{B}^{\mathfrak{p}}}]} * \omega_{cls} - \mathrm{gIoU}(\mathcal{B}^{\mathfrak{t}}, \mathcal{B}^{\mathfrak{p}}) * \omega_{\mathrm{shape}} \mid \mathcal{B}^{\mathfrak{t}} \in \mathcal{M}^{\mathfrak{t}}, \mathcal{B}^{\mathfrak{p}} \in \mathcal{M}^{\mathfrak{p}}, \quad (1)$$

with $\mathcal{B}^{\mathfrak{t}}$ and $\mathcal{B}^{\mathfrak{p}}$ being the boxes and $y_{\mathcal{B}^{\mathfrak{t}}}$ and $y_{\mathcal{B}^{\mathfrak{p}}}$ being the classes of the target and predicted box respectively. ω_{shape} and ω_{cls} are parameters to weigh the importance of the two terms. Per default, ω_{shape} is set to 1, and ω_{cls} is determined by the sample-wise classification performance of the predictions such that wrong class information does not confuse the matching when the model's class predictions are inaccurate. We thus set $\omega_{\mathrm{cls}} = \max\left(0, \mathrm{MCC}\left(\boldsymbol{y}^{\mathfrak{t}}, \boldsymbol{y}^{\mathfrak{p}}\right)\right)$, where $y_i^{\mathfrak{t}}$ and $y_i^{\mathfrak{p}}$ are the classes of all target and predicted bounding boxes for image i, respectively, and MCC is Matthews Correlation Coefficient (Matthews, 1975), as defined in Eq. (10) in Appendix D. This results in a set of matched boxes denoted by $\mathcal{M} = (\mathcal{B}^{\mathfrak{p}}, \mathcal{B}^{\mathfrak{t}}) \mid \mathcal{B}^{\mathfrak{p}} \in \mathcal{M}^{\mathfrak{p}}, \mathcal{B}^{\mathfrak{t}} \in \mathcal{M}^{\mathfrak{t}}$, where $(\mathcal{B}^{\mathfrak{p}}, \mathcal{B}^{\mathfrak{t}})$ is a pair of matched bounding boxes.

---

2. Wang *et al.* chose the Intersection over Bounding Box (IoBB) instead of the IoU. This metric does not consider the size of the predicted box in the denominator and therefore favors large boxes.

The set of unmatched targets is denoted by $\mathcal{U}^{\mathrm{t}} = \mathcal{M}^{\mathrm{t}} \setminus \mathcal{B}^{\mathrm{t}} \mid (\mathcal{B}^{\mathrm{p}}, \mathcal{B}^{\mathrm{t}}) \in \mathcal{M}$, and the set of unmatched predicted bounding boxes is denoted by $\mathcal{U}^{\mathrm{p}} = \mathcal{M}^{\mathrm{p}} \setminus \mathcal{B}^{\mathrm{p}} \mid (\mathcal{B}^{\mathrm{p}}, \mathcal{B}^{\mathrm{t}}) \in \mathcal{M}$.

Localization We measure the localization quality of the matched boxes in $\mathcal{M}$ by

$$\mathrm{RoDeO}^{\mathrm{loc}}_{\mathrm{matched}} = \frac{1}{|\mathcal{M}|} \sum_{(\mathcal{B}^{\mathrm{t}}, \mathcal{B}^{\mathrm{p}}) \in \mathcal{M}} \exp \left[-\frac{\left(\frac{\mathcal{B}^{\mathrm{t}}_x - \mathcal{B}^{\mathrm{p}}_x}{\mathcal{B}^{\mathrm{t}}_w}\right)^2 + \left(\frac{\mathcal{B}^{\mathrm{t}}_y - \mathcal{B}^{\mathrm{p}}_y}{\mathcal{B}^{\mathrm{t}}_h}\right)^2}{C} \right], \tag{2}$$

where C is a scaling coefficient, set such that for a box pair $(\mathcal{B}^{\mathrm{t}}, \mathcal{B}^{\mathrm{p}})$ with relative Euclidian distance equalling one, the value is exactly 0.5, i.e. $\frac{1}{C} = \ln 2 \approx 0.69$. The localization value for a single box pair thus follows the probability density of a (2D separable) normal distribution, such that (i) its maximum value is reached when box centers are aligned, (ii) it degrades slowly for small distances, then fast, until degrading slowly again for large distances. Compared to IoU-based distance functions (used by acc@IoU, AP@IoU, or mAP), which degrade to zero very quickly and prefer axis-aligned boxes; $\mathrm{RoDeO}^{\mathrm{loc}}_{\mathrm{matched}}$ degrades more smoothly and isotropic in euclidean space, as highlighted in Figure 2.

Figure 2: Sensitivity of different metrics to position offsets. For simplicity, we assume both, the target and predicted box, to be square and equal-sized. We plot the values of each metric with position offsets $(\Delta x = \frac{\mathcal{B}^{\mathrm{t}}_x - \mathcal{B}^{\mathrm{p}}_x}{\mathcal{B}^{\mathrm{t}}_w}, \Delta y = \frac{\mathcal{B}^{\mathrm{t}}_y - \mathcal{B}^{\mathrm{p}}_y}{\mathcal{B}^{\mathrm{t}}_h})$ between the predicted box and the target box (dashed box). For mAP, we consider seven IoU-thresholds from 0.1 to 0.7. IoU-based distances (AP@50, mAP, IoU) degrade to zero very quickly and prefer axis-aligned boxes, while RoDeO loc degrades more smoothly and is isotropic in Eucledian space.

Shape Shape similarity is computed as the Intersection over Union (IoU) between each matched predicted and target box when assuming the boxes have the same center coordinates.

$$\mathrm{RoDeO}^{\mathrm{shape}}_{\mathrm{matched}} = \frac{1}{|\mathcal{M}|} \sum_{(\mathcal{B}^{\mathrm{t}}, \mathcal{B}^{\mathrm{p}}) \in \mathcal{M}} \mathrm{cIoU}(\mathcal{B}^{\mathrm{t}}, \mathcal{B}^{\mathrm{p}}), \tag{3}$$

where cIoU is computed as the IoU after aligning the centers of predicted and target box. The shape score encodes differences in size and aspect ratio but is independent of the relative location of the two boxes.

Classification   As classification score, RoDeO again uses MCC (c.f. Equation (10) in Appendix D):

$$\text{RoDeO}^{\text{cls}}_{\text{matched}} = \max\left(0, \text{MCC}(\mathcal{Y}^{\text{t}}, \mathcal{Y}^{\text{p}})\right) , \tag{4}$$

where $\mathcal{Y}^{\text{t}} = \{y_{\mathcal{B}^{\text{t}}}\}, \mathcal{Y}^{\text{p}} = \{y_{\mathcal{B}^{\text{p}}}\} \mid (\mathcal{B}^{\text{t}}, \mathcal{B}^{\text{p}}) \in \mathcal{M}$, and $y_{\mathcal{B}^{\text{t}}}$ and $y_{\mathcal{B}^{\text{p}}}$ are the classes of the target and predicted box respectively. In contrast to other classification metrics like F1-score or accuracy, MCC only gives positive scores for performance above random, regardless of possible class imbalances in the dataset. Since scores below 0 indicate negative correlations, they should be valued the same as the outputs of completely random models.

Overprediction, Underprediction   If over- and underpredictions are not penalized in the sub-metrics, these could be tricked by a large number of predictions. However, they can not be attributed to any of the aforementioned error types alone. Instead, RoDeO integrates them globally into every sub-metric as a linear combination of the score achieved by the sub-metric and zero, weighted by the number of matched over- and underpredictions:

$$\text{RoDeO}^{\text{sub}} = \frac{|\mathcal{M}|}{|\mathcal{M}| + |\mathcal{U}^{\text{t}}| + |\mathcal{U}^{\text{p}}|}\text{RoDeO}^{\text{sub}}_{\text{matched}} \quad \middle| \quad \text{sub} \in \{\text{loc}, \text{shape}, \text{cls}\} . \tag{5}$$

Summary Metric   We further propose a summarization of all the sub-metrics into a single number. We chose the harmonic mean for aggregation because a low score in any sub-metric indicates a faulty detection algorithm that should not receive a high score in the summary metric. *RoDeO total*, or abbreviated as *RoDeO*, is thus computed as

$$\text{RoDeO} = 3\left(\frac{1}{\text{RoDeO}^{\text{loc}}} + \frac{1}{\text{RoDeO}^{\text{shape}}} + \frac{1}{\text{RoDeO}^{\text{cls}}}\right)^{-1} . \tag{6}$$

Nevertheless, we recommend laying the main focus on the sub-metrics when evaluating and comparing algorithms. The summary metric does not give a full picture of the different sources of errors.

3.1. RoDeO per Class

The computation of RoDeO on a per-class basis is analogous to above. However, for a class c, the set of matched boxes only contains the box pairs where the target box belongs to c. The unmatched predicted and target boxes, are also filtered to the ones belonging to c.

4. Experimental Setup

Dataset   We perform experiments on the ChestX-ray8 dataset by Wang et al. (2017). It contains 108 948 anterioposterior chest radiographs of 32 717 unique patients acquired at the National Institutes of Health Clinical Center in the USA. The images are labeled for 8 different pathologies, each image can exhibit multiple pathologies. Additionally, a board-certified radiologist manually labeled 882 of these images with bounding boxes. We used 50% of the images with bounding boxes for evaluation and reserved the other 50% for testing. The rest of the images were used for weakly-supervised training of a machine learning model. We avoided patient overlap between all subsets.

Compared Metrics   In our experiments, we compare RoDeO to different threshold-based metrics: AP@IoU – the standard metric in object detection for natural images – and acc@IoU as used in (Wang et al., 2017). For these metrics, we look at three different IoU thresholds: 0.1, 0.3, and 0.5.

Oracle Models and Prediction Corruption   To study how different object detection metrics, including RoDeO, react to differences in prediction quality and randomness, we experiment with oracle models on the test set. These oracle models are not trained, but instead have access to the target boxes (i.e. the oracle) during inference. The correct bounding boxes are then modified using parameterized random corruption models before they are returned as predictions. We run these oracle models on the test set and study the effect of different corruptions and their parameters. For each corruption setting (with specified parameters), we report the mean results over five runs. We refer to Appendix A for details on the corruption models.

CheXNet   To test the usefulness of our proposed metric in practice, we train a CheXNet (Rajpurkar et al., 2017) as a weakly-supervised object detection model on the training dataset, using only image-level labels. For the generation of bounding boxes from heatmaps, we follow Wang et al. (2017). Implementation details are provided in Appendix B.

5. Experiments

In this section, we provide examples of undesired behavior of the compared metrics. In all cases, RoDeO behaves as expected. Further experimental results are shown in Appendix C.

AP@IoU declines sharply with small localization errors.   Figure 3 shows the influence of position- and size-corruptions on all compared metrics. While AP@IoU declines rapidly with position errors, it stays high under severe size corruptions. acc@IoU shows similar behavior but remains at a high base-value along all corruptions. RoDeO declines more gracefully along both axes and shows a clear separation of the two corruptions.

Figure 3: Box oracle with random position and size corruptions.

Acc@IoU achieves high scores with underprediction. In Figure 4, acc@50 increases with higher underprediction probability (i.e. more missed boxes). This leads to higher scores for models that predict no boxes at all, especially at higher IoUs. With more underprediction, a higher number of false positives are exchanged with true negatives, leading to better accuracy. AP@IoU and RoDeO do not suffer from this behavior.

Figure 4: Box oracle with $\sigma_{\mathrm{pos}} = 0.5$ position variation and underpredicted classes.

AP@IoU ignores overprediction at higher thresholds. While overprediction leads to a nice exponential decay of all sub-metrics of RoDeO, AP@IoU does not decay with more overprediction at IoUs > 0.1 in Figure 5. Even worse, AP@50 shows a small but significant increase as more boxes get predicted.

Figure 5: Box oracle with $\sigma_{\mathrm{pos}} = 0.5$ (position variation and overprediction per class.

5.1. Evaluating a Machine Learning Model

Table 1 shows qualitative results of RoDeO and mAP for a trained CheXNet (Rajpurkar et al., 2017). In mAP, Cardiomegaly clearly dominates the overall score. Optimizing for mAP favors models that can detect large pathologies like Cardiomegaly well, while neglecting other, harder ones. The results of RoDeO paint a more balanced picture. While still acknowledging the good localization and shape performance for Cardiomegaly, it identified classification problems for this class. It also reveals that the most severe problem in Nodule detection is the shape (or size) mismatch, and that Pneumonia was not predicted at all by the model. acc@IoU on the other hand gives one of the highest scores to Pneumonia. This is due to the dominance of true negatives in accuracy and renders the metric almost com-

Table 1: Qualitative RoDeO, acc@30, and mAP results of a trained CheXNet model. For mAP, we consider seven thresholds from 0.1 to 0.7.

	RoDeO/cls	RoDeO/loc	RoDeO/shape	RoDeO	acc@30	mAP
Atelectasis	24.5	50.9	22.1	28.4	64.7	1.3
Cardiomegaly	20.7	85.0	61.4	39.2	85.8	13.2
Effusion	40.8	41.6	29.5	36.4	69.4	3.8
Infiltration	10.5	54.9	33.9	21.0	74.3	1.2
Mass	15.4	46.6	17.2	20.8	81.8	1.8
Nodule	24.7	12.9	4.1	8.4	81.2	0.0
Pneumonia	0.0	63.7	35.8	0.0	84.3	0.3
Pneumothorax	23.2	26.2	31.4	26.5	81.7	2.1
Total	20.7	51.1	32.2	30.3	77.9	3.0

pletely useless. The performance ranking of pathologies that the RoDeO summary metric produces further is in-line with the one of mAP, with Atelectasis being the only outlier.

6. Discussion

The above experiments have shown that compared to IoU-based metrics, RoDeO has more desirable behaviors for medical object detection: It can not be tricked by over- or under-prediction, it does not consider boxes with class confusion as useless but values the detection of pathologies separately, and it uses a notion of distance that reflects the clinical need for coarse localization better. Our experiments have further shown that different error sources affect sub-metrics independently and that RoDeO degrades gracefully along all sub-metrics. Further evaluation in Appendix C shows that RoDeO also behaves as desired in a plethora of different corruption settings.

7. Conclusion

We have proposed RoDeO, a novel metric to evaluate object detection algorithms, that is tailored to the requirements in medical pathology detection, especially from chest X-rays. Extensive experiments have shown that RoDeO considers different error-sources more appropriately than previous metrics. It is easy to interpret and use; with robust default values that can easily be adapted to the specific needs of an application. RoDeO allows for better evaluation of pathology detection algorithms and can increase their clinical usefulness.

References

Michael Baumgartner, Paul F Jäger, Fabian Isensee, and Klaus H Maier-Hein. nndetection: A self-configuring method for medical object detection. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 530–539. Springer, 2021.

Daniel Bolya, Sean Foley, James Hays, and Judy Hoffman. Tide: A general toolbox for identifying object detection errors. In *European Conference on Computer Vision*, pages 558–573. Springer, 2020.

Ali Borji and Seyed Mehdi Iranmanesh. Empirical upper bound in object detection and more. *arXiv preprint arXiv:1911.12451*, 2019.

Mark Everingham, Luc Van Gool, Christopher K. Williams, John Winn, and Andrew Zisserman. The PASCAL Visual Object Classes Challenge 2007 (VOC2007) Results. http://www.pascal-network.org/challenges/VOC/voc2007/workshop/index.html, a.

Mark Everingham, Luc Van Gool, Christopher K. Williams, John Winn, and Andrew Zisserman. The PASCAL Visual Object Classes Challenge 2012 (VOC2012) Results. http://www.pascal-network.org/challenges/VOC/voc2012/workshop/index.html, b.

Derek Hoiem, Yodsawalai Chodpathumwan, and Qieyun Dai. Diagnosing error in object detectors. In *European conference on computer vision*, pages 340–353. Springer, 2012.

Paul F Jaeger, Simon AA Kohl, Sebastian Bickelhaupt, Fabian Isensee, Tristan Anselm Kuder, Heinz-Peter Schlemmer, and Klaus H Maier-Hein. Retina u-net: Embarrassingly simple exploitation of segmentation supervision for medical object detection. In *Machine Learning for Health Workshop*, pages 171–183. PMLR, 2020.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C. Lawrence Zitnick. Microsoft coco: Common objects in context. pages 740–755, 2014. doi: 10.1007/978-3-319-10602-1_48.

Brian W Matthews. Comparison of the predicted and observed secondary structure of t4 phage lysozyme. *Biochimica et Biophysica Acta (BBA)-Protein Structure*, 405(2):442–451, 1975.

Pranav Rajpurkar, Jeremy Irvin, Kaylie Zhu, Brandon Yang, Hershel Mehta, Tony Duan, Daisy Ding, Aarti Bagul, Curtis Langlotz, Katie Shpanskaya, et al. Chexnet: Radiologist-level pneumonia detection on chest x-rays with deep learning. *arXiv preprint arXiv:1711.05225*, 2017. doi: 10.48550/arXiv.1711.05225.

Hamid Rezatofighi, Nathan Tsoi, JunYoung Gwak, Amir Sadeghian, Ian Reid, and Silvio Savarese. Generalized intersection over union. June 2019.

Xiaosong Wang, Yifan Peng, Le Lu, Zhiyong Lu, Mohammadhadi Bagheri, and Ronald M. Summers. Chestx-ray8: Hospital-scale chest x-ray database and benchmarks on weakly-supervised classification and localization of common thorax diseases. pages 2097–2106, 2017. doi: 10.1109/CVPR.2017.369.

Appendix A. Corruption Models

Position and shape corruption For position and shape corruption we consider each oracle box individually. Assume the oracle box is defined by its center coordinates (x, y) and its size (w, h). Given the standard deviation $\sigma_{\text{pos}} \in [0, \infty)$ of the (relative) position offset (a parameter of the corruption model which will be scaled by the box size), we sample the corrupted center coordinates as

$$\hat{x} \sim \mathcal{N}\left(\hat{x}\Big| x, (w \cdot \sigma_{\text{pos}})^2\right), \qquad\qquad \hat{y} \sim \mathcal{N}\left(\hat{y}\Big| y, (h \cdot \sigma_{\text{pos}})^2\right), \qquad (7)$$

where for $\sigma_{\text{pos}} = 0$ we define $\hat{x} = x$ and $\hat{y} = y$. This position corruption model is used in Figures 3, 4, and 5 from the main paper and Figures 7, 9, and 10 in Appendix C. For Figure 7 in Appendix C, we additionally corrupt the box positions by introducing a position bias $|\Delta\boldsymbol{p}| \in [0, \infty)$. For each predicted box, we randomly sample a direction $\phi \in [0, 2\pi]$ and offset the box into that direction, i.e.

$$\hat{x} = x + \frac{|\Delta\boldsymbol{p}| \cdot \cos\phi}{w}, \qquad\qquad \hat{y} = y + \frac{|\Delta\boldsymbol{p}| \cdot \sin\phi}{h}. \qquad (8)$$

For shape corruption, we assume a multiplicative corruption model and therefore sample from the Lognormal distribution as follows

$$\ln(\hat{w}) \sim \mathcal{N}\left(\ln(\hat{w})\Big| \ln(w), \sigma_{\text{shape}}^2\right) \qquad \ln(\hat{h}) \sim \mathcal{N}\left(\ln(\hat{h})\Big| \ln(h), \sigma_{\text{shape}}^2\right), \qquad (9)$$

where for $\sigma_{\text{shape}} = 0$, we define $\hat{w} = w$ and $\hat{h} = h$. This shape corruption model is used in Figure 3 in the main paper. For Figure 8 in Appendix C, we corrupt size and aspect ratio of boxes independently.

TODO

Class Underprediction For class underprediction, we consider each sample independently and randomly decide for each positive class c^+ in its oracle whether to flip it to negative by sampling from a Bernoulli distribution with probability $p_{\text{underpred}} \in [0, 1]$. We then discard all boxes for the flipped classes in the current sample. For simulating more realistic behavior we additionally apply random position corruption with $\sigma_{\text{pos}} = 0.5$ to all remaining boxes. This corruption model is used in Figure 4 from the main paper.

Box Overprediction For box overprediction per class we do not predict additional classes but duplicate oracle boxes. We, therefore, sample the number of duplications D of each box independently from a geometric distribution with a specified expected number of duplications $\mathbb{E}[D]$. Just like in the underprediction scenario, we additionally apply random position corruption with $\sigma_{\text{pos}} = 0.5$ to the original and all duplicated boxes, resulting in duplicated boxes slightly deviating from the original boxes. This corruption model is used in Figure 5 from the main paper.

Class Overprediction For class overprediction we proceed similarly and randomly decide for each negtive class c^- in its oracle whether to flip it to positive by sampling from a Bernoulli distribution with probability $p_{\text{overpred}} \in [0, 1]$. We then generate one additional box for each of the classes that have been flipped to positive, where the box size is set to 0.25 for width and height (the mean over the dataset) and the center position is sampled uniformly such that the whole box is contained within the image.

Class confusion For class confusion we consider each sample individually and randomly decide which of the classes $c \in C$ to confuse with each other. We, therefore, first randomly select a subset of classes to confuse by sampling from a Bernoulli distribution with probability $p_{\text{cls-confuse}} \in [0, 1]$ for each class independently, where $p_{\text{cls-confuse}} = 0$ corresponds to no confusion at all and $p_{\text{cls-confuse}} = 1$ to confusing all classes. We then randomly permute the set of selected classes in this sample while leaving the non-selected classes unchanged.

Random positioned boxes We also experiment with randomly positioning boxes. In this case we assume only a class oracle, i.e. we know the correct set of positive classes but not the related bounding boxes. In the default case we sample one bounding box per positive class where the size is specified as a constant (0.25 if not specified otherwise) and the position is sampled uniformly such that the whole box is contained within the image.

For studying overprediction of boxes per class, we also experiment with sampling several randomly positioned boxes per class, where the number of boxes is specified as a constant.

Appendix B. CheXNet Implementation Details

Here we describe the implementation details of the CheXNet model (Rajpurkar et al., 2017). It was trained using Adam (Kingma and Ba, 2014) with a learning rate of $3.6e - 5$, weight decay of $1e - 6$, and gradient clipping at norm 1.0. Both training and testing images were resized to 224×224 pixels, and normalized to zero mean and unit variance using the statistics of the training dataset. During training, we randomly applied random color jitter and random gaussian blurring to the images, each with a probability of 50%. No data augmentation was applied during testing. We trained for a maximum number of 50000 iterations with early stopping (patience = 10000) and a batch size of 128 on a single Nvidia RTX A6000 GPU.

Bounding Box Generation from Heatmaps We consider an input image represented as $x \in \mathbb{R}^{H \times W}$. A model produces C heatmaps $\hat{s} \in \mathbb{R}^{H \times W}$, one for each class. These heatmaps are generated by upsampling the spatially reduced score maps $s \in \mathbb{R}^{h \times w}$ per class using a bilinear interpolation. Following the box proposal method described in (Wang et al., 2017), we normalize the heatmaps per image between 0 and 255 and create two sets of binarized maps by threshold them at 60 and 180. From the resulting binarized heatmaps, box proposals are drawn around each connected component, denoted as $\hat{s}k$. The predicted class for each box is determined by the connected component it encloses.

Appendix C. Additional Results

Figure 6: Class oracle with random positioned boxes with class oversampling.

Figure 7: Box oracle with position offsets.

Figure 8: Box oracle with random shape corruptions.

Figure 9: Box oracle with $\sigma_{\mathrm{pos}} = 0.5$ (relative) position variation and oversampled classes.

Figure 10: Box oracle with $\sigma_{\mathrm{pos}} = 0.5$ (relative) position variation and random class swaps.

Appendix D. Definitions

Matthews Correlation Coefficient (MCC)   The *Matthews Correlation Coefficient (MCC)* (Matthews, 1975) is defined as follows:

$$\text{MCC} = \frac{\text{TP} * \text{TN} - \text{FP} * \text{FN}}{\sqrt{(\text{TP} + \text{FP})(\text{TP} + \text{FN})(\text{TN} + \text{FP})(\text{TN} + \text{FN})}} \,, \tag{10}$$

where TP are the true positives, FP are the false positive, TN are the true negatives, and FN are the false negatives of a classification model over the whole evaluation dataset. MCC is bound between -1 and 1, where a perfect classification is 1, a random model achieves 0 and negative values indicate negative correlations.

Intersection over Union (IoU)   The *Intersection over Union (IoU)* between two bounding boxes $\mathcal{B}^{\text{t}}$ and $\mathcal{B}^{\mathfrak{p}}$ is defined as follows:

$$\text{IoU} = \frac{|\mathcal{B}^{\text{t}} \cap \mathcal{B}^{\mathfrak{p}}|}{|\mathcal{B}^{\text{t}} \cup \mathcal{B}^{\mathfrak{p}}|} = \frac{|\mathcal{B}^{\text{t}} \cap \mathcal{B}^{\mathfrak{p}}|}{\mathcal{B}^{\text{t}}_w \mathcal{B}^{\text{t}}_h + \mathcal{B}^{\mathfrak{p}}_w \mathcal{B}^{\mathfrak{p}}_h - |\mathcal{B}^{\text{t}} \cap \mathcal{B}^{\mathfrak{p}}|} \,, \tag{11}$$

where

$$|\mathcal{B}^{\text{t}} \cap \mathcal{B}^{\mathfrak{p}}| = (\min(\mathcal{B}^{\text{t}}_{x+}, \mathcal{B}^{\mathfrak{p}}_{x+}) - \max(\mathcal{B}^{\text{t}}_{x-}, \mathcal{B}^{\mathfrak{p}}_{x-}))(\min(\mathcal{B}^{\text{t}}_{y+}, \mathcal{B}^{\mathfrak{p}}_{y+}) - \max(\mathcal{B}^{\text{t}}_{y-}, \mathcal{B}^{\mathfrak{p}}_{y-})) \tag{12}$$

with $\mathcal{B}_{x-} = \mathcal{B}_x - \frac{\mathcal{B}_w}{2}$ and $\mathcal{B}_{y-} = \mathcal{B}_y - \frac{\mathcal{B}_h}{2}$ are the upper left coordinates of each box, and $\mathcal{B}_{x+} = \mathcal{B}_x + \frac{\mathcal{B}_w}{2}$ and $\mathcal{B}_{y+} = \mathcal{B}_y + \frac{\mathcal{B}_h}{2}$ are the lower right coordinates.

Centered IoU (cIoU)   The *centered IoU (cIoU)* is computed as the normal IoU, but assuming the same position for both boxes $\mathcal{B}^{\text{t}}$ and $\mathcal{B}^{\mathfrak{p}}$, i.e. $\mathcal{B}^{\text{t}}_x = \mathcal{B}^{\mathfrak{p}}_x$ and $\mathcal{B}^{\text{t}}_y = \mathcal{B}^{\mathfrak{p}}_y$.

Generalized IoU (gIoU)   The *generalized IoU (gIoU)* (Rezatofighi et al., 2019) is the IoU minus an additional term which is the ration between the convex hull $\mathcal{C}$ of the predicted and target box minus their Union and $\mathcal{C}$.

$$\text{gIoU} = \text{IoU} - \frac{|\mathcal{C}| - |\mathcal{B}^{\text{t}} \cup \mathcal{B}^{\mathfrak{p}}|}{|\mathcal{C}|} \,, \tag{13}$$

where the convex hull $|\mathcal{C}| = (\max(\mathcal{B}^{\text{t}}_{x+}, \mathcal{B}^{\mathfrak{p}}_{x+}) - \min(\mathcal{B}^{\text{t}}_{x-}, \mathcal{B}^{\mathfrak{p}}_{x-}))(\max(\mathcal{B}^{\text{t}}_{y+}, \mathcal{B}^{\mathfrak{p}}_{y+}) - \min(\mathcal{B}^{\text{t}}_{y-}, \mathcal{B}^{\mathfrak{p}}_{y-}))$.