The Missing Invariance Principle Found –
the Reciprocal Twin of Invariant Risk Minimization

Abstract

Machine learning models often generalize poorly to out-of-distribution (OOD) data as a result of relying on features that are spuriously correlated with the label during training. Recently, the technique of Invariant Risk Minimization (IRM) was proposed to learn predictors that only use invariant features by conserving the feature-conditioned label expectation $\mathbb{E}_e[y|f(x)]$ across environments. However, more recent studies have demonstrated that IRM-v1, a practical version of IRM, can fail in various task settings. Here, we identify a fundamental flaw of IRM formulation that causes the failure. We then introduce a complementary notion of invariance, MRI, based on conserving the label-conditioned feature expectation $\mathbb{E}_e[f(x)|y]$ across environments, which is free of this flaw. Further, we introduce a simplified, practical version of the MRI formulation called MRI-v1. We note that this constraint is convex which confers it with an advantage over IRM-v1, which imposes non-convex constraints. We prove that in a general linear problem setting, MRI-v1 can guarantee invariant predictors given sufficient environments. We also empirically demonstrate that MRI strongly out-performs IRM and consistently achieves near-optimal OOD generalization in image-based nonlinear problems.

1 Introduction

Deep learning models have shown tremendous success over the past decade. These models show great generalization properties when tested on the same distribution as the training dataset (in-distribution generalization). However, these models often show catastrophic failure when tested on out-of-distribution dataset, revealing that they learned to use easier-to-fit features that are spuriously correlated to the label in the given training domains but do not generalize to the testing domains. For example, deep networks trained on pictures of cow with only grassy backgrounds in the training domain will use the background color as the predictive feature which is easier to learn and generalize poorly to pictures of cow, for example, with a dessert background.

Recently, there has been a growing interest in developing models that generalize well across multiple domains. In particular, there has been a recent body of works that focus on developing algorithms that attempt to learn invariant predictors (Arjovsky et al., 2019; Ahuja et al., 2021; Peters et al., 2016; Rojas-Carulla et al., 2018; Heinze-Deml et al., 2018). Invariant Risk Minimization (IRM) and its practical version, IRM-v1, in particular, have attracted much attention as one of the first methods that are compatible with deep learning techniques. However, several follow-up studies have empirically demonstrated that IRM-v1 is unreliable at learning invariant representations (Kamath et al., 2021; Rosenfeld et al., 2020; Gulrajani and Lopez-Paz, 2020; Ahuja et al., 2020, 2021). Here, we identify a fundamental flaw of IRM formulation that causes this limitation and propose a new method that is free of this flaw.

Related Works There has been considerable work in the field of learning invariant representations. They vary from learning domain-invariant feature representations conserving $P(f(x))$ using kernel methods (Muandet et al., 2013; Ghifary et al., 2016; Hu et al., 2020), variational autoencoder (Ilse et al., 2020), and adversarial networks Ganin et al. (2016); Long et al. (2018); Akuzawa et al. (2019); Albuquerque et al. (2019) to learning invariant class-conditional features $P(f(x)|y)$ (Gong et al., 2016; Li et al., 2018b) in the context of domain adaptation, which assumes access to the test distribution for adaptation. There is also a large body of work to learn invariant representations in the field of domain generalization that doesn't assume access to test distributions. This includes imposing invariance of $\mathbb{E}_e[y|f(x)]$ (Arjovsky et al., 2019) with information bottleneck constraint (Ahuja et al. (2021)), imposing object-invariant condition (Mahajan et al. (2021)), using domain inference (Creager et al., 2021), model calibration (Wald et al., 2021), and others (Krueger et al., 2021; Li et al., 2018a; Shankar et al., 2018).

Our Contributions We introduce a simpler formulation of IRM that is more generalizable, and show that it can be modified to yield a new complementary notion of invariance, called MRI. We also show that IRM has a fundamental flaw due to the indirect way it imposes invariance which leads to the failure of IRM-v1. MRI is shown to be free of this flaw. We prove that in a general linear problem setting, MRI-v1 can guarantee invariant predictors given sufficient environments. We then empirically demonstrate that MRI strongly out-performs IRM and consistently achieves near-optimal OOD generalization in image-based nonlinear problems.[1]

2   Problem Formulation

Consider a set of environments $\mathcal{E} = \{e\}$, each of which defines a distribution $P_e(x, y)$ over inputs and labels, from which the dataset of the environment is drawn $\mathcal{D}_e \equiv \{(x_j^e \in \mathbb{R}^d, y_j^e \in \mathbb{R})\}$. The distribution $P_e(x, y)$ is assumed to be generated according to the causal graph in Fig. 1 as introduced in Rosenfeld et al. (2020), which includes latent features that are invariantly z_i or spuriously z_s correlated with the label, from which the observation x is generated. The function $x = g(z_i, z_s)$ is assumed to be injective, which makes it possible to recover the latent features from the observation.

Note that while this work focuses on the causal graph in Figure 1, our results are also applicable to the graph in which the invariant feature z_i causes the label y ($Z_i \to Y$). This is the graph considered by Arjovsky et al. (2019) in Figure 3 with the difference being that they allow both the invariant feature and label distribution to also vary across environments. Also, while Arjovsky et al. (2019) focused on the causal graph with $Z_i \to Y$, the IRM method is also applicable to the causal graph considered in Figure 1 (Rosenfeld et al., 2020).

The risk of a predictor $f : X \to O$ in environment e is defined as the population average

$$\mathcal{L}_e(f) \equiv \mathbb{E}_{P_e(x,y)}[l(f(x), y)] \tag{1}$$
$$= \mathbb{E}_{P_e(o)}[\mathbb{E}_{P_e(y|o)}[l(o, y)]] \tag{2}$$
$$= \mathbb{E}_{P(y)}[\mathbb{E}_{P_e(o|y)}[l(o, y)]] \tag{3}$$

where $o = f(x)$ is the predictor's output. Here, we consider standard convex loss functions $l : O \times Y \to \mathbb{R}_{\geq 0}$, including the square loss $l_{\mathrm{sq}}(o, y) = \frac{1}{2}(o - y)^2$ for regression ($O, Y \subseteq \mathbb{R}$) and the binary-cross-entropy (BCE) loss $l_{\log}(o, y) = -(1 + y)\log(\eta(o)) - (1 - y)\log(1 - \eta(o))$ for binary classification ($O \subseteq \mathbb{R}$, $Y \subseteq [-1, 1]$), where $\eta(o) \equiv 1/(1 + e^{-o})$ is the sigmoid function.

Figure 1: Causal graph depicting the data generating process. Shading indicates the variable is observed.

---

[1]Code available at `https://anonymous.4open.science/r/MRI-2608`

3 IRM vs MRI Invariance

3.1 IRM Paradigm

3.1.1 Original formulation

Definition 3.1. (Arjovsky et al., 2019) Given a predictor $\psi \circ f$, the feature representation $f : X \to Z$ is *IRM invariant* over a set of environments $\mathcal{E}$ if there exists $\psi : Z \to O$ such that ψ is simultaneously optimal on f for all environments in $\mathcal{E}$, *i.e.*

$$\forall e \in \mathcal{E}, \qquad \psi \in \arg\min_{\bar{\psi}} \mathcal{L}_e(\bar{\psi} \circ f) \qquad (4)$$

where ψ is assumed to be unrestricted in the space of all measurable functions.

Lemma 3.2. *(Kamath et al., 2021) For standard loss functions[2], Definition 3.1 is equivalent to*

$$\exists \psi, \ \forall e \in \mathcal{E}, \qquad \mathbb{E}_e[y|f(x)] = \sigma(\psi \circ f(x)). \qquad (5)$$

where $\mathbb{E}_e[y|f(x)] \equiv \mathbb{E}_{P_e(y|f(x))}[y]$ is the feature-conditioned label expectation, and σ is a monotonic function that depends on the loss function.

3.1.2 Variational formulation

The original formulation above is overly complex due to the composite predictor $\psi \circ f$ and the optimality condition on ψ. For further analysis, we introduce a simplified formulation of IRM defined by the following variational principle.

Definition 3.3. A predictor $f : X \to O$ is *IRM invariant* over a set of environments $\mathcal{E}$, if the risk $\mathcal{L}_e(f)$ remains stationary under arbitrary infinitesimal perturbations on the predictor's output $o = f(x)$ for all environments in $\mathcal{E}$, *i.e.*

$$\forall e \in \mathcal{E}, \quad \delta\mathcal{L}_e(f) = \lim_{\epsilon \to 0} \mathbb{E}_{P_e(o,y)}[l(o + \epsilon\delta\psi(o), y) - l(o, y)]/\epsilon$$
$$= \mathbb{E}_{P_e(o)}[\mathbb{E}_{P_e(y|o)}[\partial_o l(o, y)] \cdot \delta\psi(o)] = 0 \qquad (6)$$

where $\delta\psi : O \to O$ is an arbitrary perturbation that is unrestricted in the space of all measurable functions, and $\delta\mathcal{L}_e(f)$ denotes the resulting change in risk.

Lemma 3.4. *For standard loss functions[2], Definition 3.3 is equivalent to*

$$\forall e \in \mathcal{E}, \qquad \mathbb{E}_e[y|o] = \sigma(o), \qquad (7)$$

which is equivalent to Lemma 3.2 with f replacing the composite predictor $\psi \circ f$.

Proof. Eq (6) is satisfied if and only if $\mathbb{E}_{P_e(y|o)}[\partial_o l(o, y)] = 0$. For standard loss functions, the loss derivative has the form $\partial_o l(o, y) = -y + \sigma(o)$, which yields $\mathbb{E}_e[\partial_o l(o, y)|o] = -\mathbb{E}_e[y|o] + \sigma(o) = 0$.
□

3.1.3 Conservation law of IRM

It was noted in Arjovsky et al. (2019); Kamath et al. (2021) that the essence of IRM's invariance is the conservation of the *feature-conditioned label expectation*, i.e.

$$\forall e_1, e_2 \in \mathcal{E}, \qquad \mathbb{E}_{e_1}[y|f(x)] = \mathbb{E}_{e_2}[y|f(x)]. \qquad (8)$$

IRM eq (7) (also eq (5)) indeed implies the conservation law, since its RHS is constant with respect to the environment index e. However, there is a critical difference: Eq (8) only requires $\mathbb{E}_e[y|o]$ to share the same value across environments, thus imposing $|\mathcal{E}| - 1$ constraints, whereas eq (7) (also eq (5)) additionally requires that value to be also equal to the RHS term $\sigma(o)$. This extra constraint is due to the indirect way IRM attains the conservation law, *i.e.* by equaling $\mathbb{E}_e[y|o]$ to an intermediary term $\sigma(o)$, which imposes 1 constraint per environment.

---

[2] Square loss and BCE loss are considered: $\sigma(o) = o$ for square loss, and $\sigma(o) = \tanh(o/2)$ for BCE loss.

3.1.4 IRM-v1

Due to the impracticality of considering the unrestricted function space of ψ, Arjovsky et al. (2019) suggested restricting ψ to the space of linear functions. In the variational formulation, this corresponds to restricting the output perturbations $\delta\psi$ to the space of linear functions, which, for scalar outputs, is equivalent to the identity function, $\delta\psi(o) = o$. This reduces eq (6) to

$$\forall e \in \mathcal{E}, \quad \delta\mathcal{L}_e(f) = \mathbb{E}_e[\partial_o l(o, y) \cdot o] = 0. \tag{9}$$

The reduced constraints in eq (9) are identical to IRM-s in Kamath et al. (2021), which imposes $\forall e \in \mathcal{E}, \partial_\psi \mathbb{E}_e[l(\psi \cdot o, y)] = 0$, where ψ is simply a scalar multiplicative factor[3]. In Arjovsky et al. (2019), this reduced formulation is termed IRM-v1 when the constraints are imposed in a *soft manner*, *i.e.* as squared penalty terms (See eq (16)). In the literature, the term IRM-v1 is widly used for the reduced formulation regardless of whether hard or soft constraints are used, which we adopt here.

Despite the practical applicability, it has been empirically shown that IRM-v1 can behave quite differently from IRM (Kamath et al., 2021). This failure mode can be analytically understood here. Since $\mathbb{E}_e[\partial_o l(o, y) \cdot o] = \mathbb{E}_e[o(\sigma(o) - y)]$ for standard loss functions[2], eq (9) is equivalent to

$$\forall e \in \mathcal{E}, \quad \mathbb{E}_e[oy] = \mathbb{E}_e[o\sigma(o)]. \tag{10}$$

Unlike eq (7), however, RHS of eq (10) does not necessarily remain constant across environments, and hence does not prescribe a meaningful invariance. Therefore, restricting the function space of $\delta\psi$ (or ψ) invalidates the indirect way of imposing invariance in IRM involving an intermediary term.

3.2 MRI Paradigm

We now introduce a complementary notion of invariance by considering infinitesimal perturbations on label, which we call *Mirror Reflected IRM*, or *MRI*.

Definition 3.5. A predictor $f : X \to O$ is MRI invariant over a set of environments $\mathcal{E}$, if the change in risk due to arbitrary infinitesimal label perturbations is *shared* across environments, *i.e.*

$$\forall e_1, e_2 \in \mathcal{E}, \quad \delta\mathcal{L}_{e_1}(f) = \delta\mathcal{L}_{e_2}(f) \tag{11}$$
$$\text{where} \quad \delta\mathcal{L}_e(f) \equiv \lim_{\epsilon \to 0} \mathbb{E}_{P_e(x,y)}[l(o, y + \epsilon\delta\psi(y)) - l(o, y)]/\epsilon$$
$$= \mathbb{E}_{P(y)}[\mathbb{E}_e[\partial_y l(o, y)|y] \cdot \delta\psi(y)] \tag{12}$$

where $\delta\psi : Y \to Y$ is an arbitrary perturbation that is unrestricted in the space of all measurable functions, and $\delta\mathcal{L}_e(f)$ denotes the resulting change in risk. $\mathbb{E}_e[\partial_y l(o, y)|y] \equiv \mathbb{E}_{P_e(o|y)}[\partial_y l(o, y)]$.

Lemma 3.6. *For standard loss functions, Definition 3.5 is equivalent to*

$$\forall e_1, e_2 \in \mathcal{E}, \quad \mathbb{E}_{e_1}[o|y] = \mathbb{E}_{e_2}[o|y], \tag{13}$$

which conserves the label-conditioned feature expectation $\mathbb{E}_e[o|y] \equiv \mathbb{E}_{P_e(o|y)}[o]$ across environments.

Proof. Eq (11) is satisfied if and only if $\mathbb{E}_e[\partial_y l(o, y)|y]$ is conserved. For standard loss functions, the loss derivative has the form $\partial_y l(o, y) = -o + \rho(y)$[4]. Therefore, $\mathbb{E}_{e_1}[\partial_y l(o, y)|y] - \mathbb{E}_{e_2}[\partial_y l(o, y)|y] = \mathbb{E}_{e_1}[o|y] - \mathbb{E}_{e_2}[o|y] = 0$. $\square$

Note that MRI eq (11) imposes the correct number of constraints as needed by the conservation law eq (13), as it attains invariance in a direct manner without involving any intermediary terms.

3.2.1 MRI-v1

Restricting the label perturbations to the space of linear functions, or equivalently, an identity function $\delta\psi(y) = y$, reduces eq (12) to $\delta\mathcal{L}_e(f) = \mathbb{E}_e[\partial_y l(o, y) \cdot y]$. This reduces the conservation law eq (13) to

$$\forall e_1, e_2 \in \mathcal{E}, \quad \mathbb{E}_{e_1}[oy] = \mathbb{E}_{e_2}[oy]. \tag{14}$$

which is in fact a necessary condition for the MRI invariance eq (13). Therefore, the direct way of MRI's constraints imposing invariance continues to hold even when $\delta\psi$ is restricted to the space of linear functions.

---

[3]Note that $\partial_\psi l(\psi \cdot o, y) = \partial_o l(o, y) \cdot o$.

[4] Square loss and BCE loss are considered: $\rho(y) = y$ for square loss, and $\rho(y) = 0$ for BCE loss.

Algorithm	Constraint $\vec{c}(f)$	$\delta\mathcal{L}_e(f)$
IRM-v1	$\delta\vec{\mathcal{L}}(f)$	$\mathbb{E}_e[\,\partial_o l(o,y)\cdot o\,]$
MRI-v1	$Q\,\delta\vec{\mathcal{L}}(f)$	$\mathbb{E}_e[\,\partial_y l(o,y)\cdot y\,]$

Table 1: Invariance constraints of IRM-v1 and MRI-v1. $o = f(x;w)$.

4 Methods

4.1 Constrained optimization problem

The full methods of IRM-v1 and MRI-v1 can be formalized as a constrained optimization problem

$$\min_{w} \mathcal{L}_{\text{tr}}(f) \qquad \text{subject to } \vec{c}(f) = \vec{0}, \tag{15}$$

where $\mathcal{L}_{\text{tr}} = \frac{1}{|\mathcal{E}_{\text{tr}}|}\sum_{e\in\mathcal{E}_{\text{tr}}}\mathcal{L}_e$ is the average risk over the set of training environments $\mathcal{E}_{\text{tr}} \subset \mathcal{E}$, and w is the parameters of the predictor f. The constraint functions are $\vec{c} = \delta\vec{\mathcal{L}} \in \mathbb{R}^{|\mathcal{E}_{\text{tr}}|}$ for IRM-v1 and $\vec{c} = Q\,\delta\vec{\mathcal{L}} \in \mathbb{R}^{|\mathcal{E}_{\text{tr}}|-1}$ for MRI-v1, where $\delta\vec{\mathcal{L}} \in \mathbb{R}^{|\mathcal{E}_{\text{tr}}|}$ is a vector of perturbed risks $\delta\mathcal{L}_e$ for $e \in \mathcal{E}_{\text{tr}}$. $Q \in \mathbb{R}^{(|\mathcal{E}_{\text{tr}}|-1)\times|\mathcal{E}_{\text{tr}}|}$ is an orthonormal matrix that satisfies $Q\vec{1} = \vec{0}$, such that $Q\,\delta\vec{\mathcal{L}}$ computes the differences of $\delta\mathcal{L}_e$ between environments. For example, for a training set of two environments $\mathcal{E}_{\text{tr}} = \{e_1, e_2\}$, $Q\,\delta\vec{\mathcal{L}} = (\delta\mathcal{L}_{e_1} - \delta\mathcal{L}_{e_2})/\sqrt{2}$, since $Q = [1, -1]/\sqrt{2}$. The constraints are summarized in Table 1.

4.2 Soft-constraint methods

Numerically solving IRM-v1 and MRI-v1 requires converting the hard constraints $\vec{c}(f) = \vec{0}$ to soft constraints, which allows the use of off-the-shelf gradient-based optimization algorithms.

Penalty Method (PM) Penalty method is the most commonly used approach, including in Arjovsky et al. (2019), which adds the squared residual constraints as a penalty term to the objective,

$$\min_{w} \mathcal{L}_{\text{tr}}(f) + \mu\,\|\vec{c}(f)\|^2 \tag{16}$$

However, this method requires increasing $\mu^t \to \infty$ over training iteration t in order to approximate the exact hard-constraint, which leads to training instability and slow convergence (Bertsekas, 1976).

Augmented Lagrangian Method (ALM) ALM was introduced to overcome the limitations of penalty method (Bertsekas, 1976), which adds a Lagrange multiplier term to (16)

$$\min_{w} \mathcal{L}_{\text{tr}}(f) + \mu\,\|\vec{c}(f)\|^2 + \vec{\lambda}^{\mathsf{T}} \cdot \vec{c}(f), \tag{17}$$

where $\vec{\lambda}$ is typically initialized at $\vec{0}$ and updated at each training iteration t to accumulate the residual constraints $\vec{c}(f(w^t))$. In practice, ALM can operate with moderate values of μ (~ 10) without fine tuning, and thus exhibits fast and stable convergence (Bertsekas, 1976).

5 Analytic Results

5.1 General Linear SEM

In this section, we show that MRI-v1 can correctly remove all spurious features of a linear predictor given a sufficient number of environments. Consider a data generating process according to Figure 1, in which the observation $x = g(z_i, z_s)$ is an injective linear function of the latent features $z_i \in \mathbb{R}^{d_i}, z_s \in \mathbb{R}^{d_s}$. Note that this Structural Equation Model (SEM) (Pearl, 2009) does not require any assumptions on the generation process $Y \to Z_i, Z_s$, which generalizes the SEM of Rosenfeld et al. (2020), which additionally assumed binary labels and additive Gaussian noise for generating the latent features.

We consider a linear predictor $f : X \to O$. Since g is injective and has an inverse over its range, without loss of generality, we can define f as a linear function directly over the latents as

$$o = f(x; w) = w_i^\mathsf{T} \cdot z_i + w_s^\mathsf{T} \cdot z_s \tag{18}$$

with $w = \{w_i \in \mathbb{R}^{d_i}, w_s \in \mathbb{R}^{d_s}\}$.

Theorem 5.1. *Given $|\mathcal{E}_{tr}| > d_s$ training environments, and that $\mathbb{E}_e[z_s y]$ are in general linear positions, MRI-v1 will eliminate all spurious feature dimensions.*

Proof. MRI-v1's constraint eq (14) yields

$$\forall e \in \mathcal{E}_{\text{tr}}, \quad \mathbb{E}_e[oy] = w_i \cdot \mathbb{E}_e[z_i y] + w_s \cdot \mathbb{E}_e[z_s y] = const,$$

which can be expressed in a matrix form as

$$w_s \cdot M' = 0, \tag{19}$$

where $M' = M - \bar{M} \cdot 1$ with $M \equiv [\mathbb{E}_e[z_s y]]_{e \in \mathcal{E}_{\text{tr}}} \in \mathbb{R}^{d_s \times |\mathcal{E}_{\text{tr}}|}$ and $\bar{M} = \frac{1}{|\mathcal{E}_{\text{tr}}|} \sum_{e \in \mathcal{E}_{\text{tr}}} \mathbb{E}_e[z_s y]$.

Since $rank(M') = d_s$, eq (19) is equivalent to $w_s = 0$.

$\square$

Rosenfeld et al. (2020) derived a similar result for IRM-v1. However, unlike our results for MRI-v1, their result is restricted to a specialized linear family of environments with binary labels and additive Gaussian noise. In fact, IRM-v1 has been shown to fail in more general linear problems in which the noise is not additive Gaussian (Arjovsky et al., 2019; Kamath et al., 2021).

5.2 Minimal Example: $d_i = 1$, $d_s = 1$, $|\mathcal{E}_{\text{tr}}| = 2$

Here, we demonstrate a minimal case of the above general linear problem that involves one invariant feature, one spurious feature and two training environments (Shape-Texture linear regression in Section 6.1). The detailed experimental setting and the analytical solutions are presented in the Supplementary Materials. Figure 2A shows the results for the hard-constrained problems.

IRM-v1 IRM-v1 has two quadratic equality constraints, $\mathbb{E}_{e_1}[o^2 - oy] = \mathbb{E}_{e_2}[o^2 - oy] = 0$, shown as two elliptic curves. The intersection between the non-convex constraints on a 2-D feature space yields a disjoint set of 0-D points, all of which are local constrained optima, including the true invariant optimum, a zero-predictor solution, and two non-invariant solutions. Note that one of the non-invariant solutions exhibits lower train loss than the true invariant optimum solution.

IRM-relaxed The extraneous constraint of IRM-v1 can be relaxed to yield $\mathbb{E}_{e_1}[o^2 - oy] - \mathbb{E}_{e_2}[o^2 - oy] = 0$. This constraint features a pair of hyperbolic curves, that appears as two straight lines. Due to the non-convex constraint, this problem exhibits two local constrained optima, including the true invariant optimum and a non-invariant solution, with the non-invariant solution exhibiting lower train loss. Therefore, the failure mode of IRM-v1 cannot be resolved by simply relaxing the extraneous constraint without fixing the indirect way IRM imposes invariance.

MRI-v1 MRI-v1 has one linear equality constraint, $\mathbb{E}_{e_1}[oy] - \mathbb{E}_{e_2}[oy] = 0$, that exactly prescribes the set of invariant solutions $w_s = 0$. That is, any point on the constraint is a invariant predictor. This is a convex problem, since both the objective and the constraint are convex, and thus features a unique optimum, which is the true invariant optimum solution.

Convergence Dynamics Figure 2B/C show the convergence dynamics of the soft-constrained optimization problems under full-batch gradient descent (penalty method, $\mu = 5 \times 10^4$, eq (16)). IRM-v1's convergence dynamics is highly dependent on the initialization (shown with differently colored trajectories), due to the presence of multiple local minima. Note that most trajectories do not converge to the true invariant optimum. IRM-relaxed also exhibits complex dynamics due to a saddle point near the true invariant solution: The trajectories seem to approach the invariant solution at first, but eventually they all converge to the non-invariant solution. Note that the true invariant optimum is lost at this value of μ, which exists in the limit $\mu \to \infty$. In contrast, MRI-v1 always converges to the true invariant optimum regardless of initialization since it is a unique minimum.

Figure 2: Minimal example in Section 5.2. (A) Hard-constraint case. Background: Average train domain risk $\mathcal{L}_{\text{tr}}(f(w))$. Lines: Invariance constraints $\vec{c}(f(w)) = \vec{0}$. Stars: Local constrained optima. (B) Soft-constraint case. Background: Train loss $\mathcal{L}_{\text{tr}}(f(w)) + \mu \|\vec{c}(f(w))\|^2$. Convergence trajectories w^t from multiple initialization are shown. (C) Loss profiles of the above convergence trajectories. Color-matched with panel B. (Top) Average train domain risk $\mathcal{L}_{\text{tr}}(f(w^t))$. (Bottom) Test domain risk $\mathcal{L}_{\text{test}}(f(w^t))$. Dashed line: True optimal invariant solution (yellow star in panel A/B).

Minimal examples for linear binary classification on the shape-texture and the toy-CMNISTa/b datasets are also analyzed in Supplementary Materials (Figure 3).

6 Nonlinear Image-based Problems

Here, we explore how MRI-v1 performs in nonlinear problems. Note that unlike the linear problem, there is no guarantee for either IRM-v1 or MRI-v1 for these nonlinear problems.

6.1 Datasets

Shape-Texture Dataset   We introduce a new versatile dataset designed for domain generalization on linear and non-linear image-based regression and classification problems. The generative process of the dataset involves an invariant feature $z_i = e^{i\theta_i}$, a spurious feature $z_s = e^{i\theta_s}$, and a label feature $e^{i\theta_y}$, each of which represents an orientation on a complex unit circle: $e^{i\theta} \in \mathcal{S}^1$. The angles of orientations are generated as $\theta_y \sim \mathcal{U}_{\mathcal{S}^1}$, where $\mathcal{U}_{\mathcal{S}^1}$ is the circular uniform distribution, and for $* \in \{i, s\}$, $\theta_* = \theta_y$ with probability p_* or $\theta_* \sim \mathcal{U}_{\mathcal{S}^1}$ with probability $1 - p_*$.

The parameter $p_i = 0.75$ is fixed across environments, whereas p_s varies from one environment to another. We consider two training environments $\mathcal{E}_{\text{tr}} = \{e_1, e_2\}$ with $p_{s_{e_1}} = 1$, $p_{s_{e_1}} = 0.8$ and one testing environment $\mathcal{E}_{\text{test}} = \{e_0\}$ with $p_{s_{e_0}} = 0$.

In the linear regression task (section 5.2), the observed input is simply the concatenated latent features $x = [e^{i\theta_i}, e^{i\theta_s}]$ and the label is $y = e^{i\theta_y}$. In the linear classification task, the input is $x = [\sin(\theta_i), \sin(\theta_s)]$ and the label is $y = H(\sin(\theta_y))$, where H is the sign function. In the non-linear regression/classification tasks, the input observation is an image composed of two planar waves, in which θ_i is the orientation of the low frequency wave (*i.e.* shape) and θ_s is that of the high frequency wave (*i.e.* texture), as shown in Figure 4.

Colored MNIST (CMNIST)   CMNIST (Arjovsky et al., 2019) is a synthetic dataset derived from MNIST for binary classification. The dataset features a fixed correlation probability p_i between the digit and the label, and p_s between the color and the label, which changes across environments. We consider two versions, CMNISTa and CMNISTb, with two sets of environmental parameters: CMNISTa is the version from Arjovsky et al. (2019) with $p_i = 0.75$, $p_{s_{e_1}} = 0.9$, $p_{s_{e_1}} = 0.8$, and $p_{s_{e_0}} = 0.1$ for the training $\mathcal{E}_{\text{tr}} = \{e_1, e_2\}$ and the testing $\mathcal{E}_{\text{test}} = \{e_0\}$ environments; CMNISTb uses $p_i = 0.9$, $p_{s_{e_1}} = 1$, $p_{s_{e_1}} = 0.8$, $p_{s_{e_0}} = 0.1$. We also use the abstracted versions, called toy-CMNISTa/b, in which the input image is replaced by the two-bit observation data $x = [x_d, x_c]$, where $x_d, x_c \in \{-1, 1\}$ correspond to the digit bit and the color bit, respectively (Kamath et al., 2021).

Note that both Shape-Texture and CMNIST datasets can be equally understood as being generated from Fig 1 with causal directions $Y \rightarrow Z_i$ or $Z_i \rightarrow Y$ (Figure 9).

6.2   Result

In addition to IRM-v1 and MRI-v1, we report the performance of the ERM algorithm, which minimizes the average risk across environments without any invariance constraints (Table 2). For synthetic datasets, we also report the performance of the *Oracle* (Table 2), which is trained using ERM on the dataset in which the spurious features are rendered uncorrelated with the label. For the shape-texture datasets, we use a small convolutional network (single convolution layer), while for the other image-based datasets, we use the LeNet architecture (LeCun et al., 1998).

Shape-Texture Tasks   For both regression and classification tasks, we find that IRM-v1 trained using PM always converges to the zero-predictor (Table 2-3; Figure 5). In comparison, MRI-v1 trained using PM achieves near-optimal OOD generalization, performing close to Oracle (Table 2-3; Figure 5). This demonstrates that MRI-v1 is far superior to IRM-v1 in terms of both loss and accuracy when trained using PM. This is an important distinction between MRI-v1 and IRM-v1 and is a consequence of the zero-predictor being a constrained local optimum of IRM-v1, but not of MRI-v1.

Similar to the PM case, MRI-v1 is able to perform close to Oracle when trained using ALM (Table 2-3). In comparison, while IRM was able to avoid the zero-predictor, it still achieved worse test loss and accuracy than MRI-v1. Nevertheless, by using ALM, we were able to significantly improve IRM-v1's performance by avoiding the zero-predictor. In comparison, MRI-v1 achieved near-optimal OOD generalization irrespective of the training method.

Colored MNIST   Similar to the shape-texture tasks, IRM-v1 always converges to the null-predictor when trained using PM, while MRI-v1 achieves a significantly better test loss and accuracy than both IRM-v1 and ERM (Table 2-3; Figure 6). This result for MRI-v1 holds true also when trained using ALM (Table 2-3; Figure 7). In fact, the ALM version of MRI-v1 has better performance. In comparison, similar to the shape-texture tasks, IRM-v1 is able to avoid the null predictor when trained with ALM, but it achieves worse test loss than MRI-v1 on both datasets (Table 2; Figure 7), especially on the CMNISTb datasets. In contrast to the loss results, the ALM version of IRM-v1 achieves a similar test accuracy to MRI-v1 on both datasets (Table 3; Figure 7).

7   Discussion

	S-T Reg.		S-T Cls.		CMNISTa		CMNISTb	
	$\mathcal{L}_{tr}$	$\mathcal{L}_{test}$	$\mathcal{L}_{tr}$	$\mathcal{L}_{test}$	$\mathcal{L}_{tr}$	$\mathcal{L}_{test}$	$\mathcal{L}_{tr}$	$\mathcal{L}_{test}$
Oracle	0.46 ± 0.00	0.46 ± 0.00	0.47 ± 0.00	0.47 ± 0.00	0.57 ± 0.00	0.58 ± 0.00	0.22 ± 0.00	0.24 ± 0.01
ERM	0.16 ± 0.00	1.37 ± 0.01	0.24 ± 0.00	1.16 ± 0.01	0.36 ± 0.00	1.44 ± 0.01	0.13 ± 0.00	0.73 ± 0.01
IRM-v1 (PM)	1.00 ± 0.00	1.00 ± 0.00	0.69 ± 0.00	0.69 ± 0.00	0.69 ± 0.00	0.69 ± 0.00	0.69 ± 0.00	0.69 ± 0.00
IRM-v1 (ALM)	0.23 ± 0.00	0.62 ± 0.01	0.4 ± 0.01	0.51 ± 0.01	0.62 ± 0.02	0.69 ± 0.02	0.17 ± 0.01	0.47 ± 0.02
MRI-v1 (PM)	0.53 ± 0.03	0.54 ± 0.03	0.44 ± 0.01	$\mathbf{0.46} \pm 0.01$	0.62 ± 0.01	0.66 ± 0.01	0.46 ± 0.01	0.4 ± 0.01
MRI-v1 (ALM)	0.45 ± 0.01	$\mathbf{0.46} \pm 0.00$	0.47 ± 0.00	0.47 ± 0.00	0.63 ± 0.02	$\mathbf{0.64} \pm 0.01$	0.25 ± 0.01	$\mathbf{0.29} \pm 0.01$

Table 2: Average train domain risk $\mathcal{L}_{tr}$ and test domain risk $\mathcal{L}_{test}$ achieved by different methods in image-based tasks. Oracle uses environments in which the spurious features are uncorrelated with the label. Mean and standard deviation shown up to 2 decimal places.

Limitations of the accuracy metric   The accuracy metric is widely used in the field of domain generalization (Gulrajani and Lopez-Paz, 2020) to compare the performance of various algorithms. However, accuracy is not sensitive enough to reliably measure the degree of invariance of a model. For example, consider the linear classification problem of toy-CMINSTb shown in Figure 8. For this problem, MRI-v1 has a unique optimum, which is the optimal invariant solution, while IRM-v1 exhibits multiple local optima, including non-invariant solutions. Yet, all these solutions exhibit identical accuracy (except for the zero-predictor solution of IRM-v1), since the accuracy landscape (Figure 8f) is flat over a wide range of solutions and remains invariant across domains: invariant accuracy is achieved as long as $w_i > |w_s|$. This shows that accuracy cannot be used as a measure of invariance in this problem. Therefore, the fact that MRI-v1 and IRM-v1 exhibit similar test-domain accuracy does not necessarily indicate that they achieve similar degree of invariance.

Limitations   A limitation of both MRI and IRM (Rosenfeld et al., 2020; Ahuja et al., 2021) is that it requires significant overlap in the support of different domain distributions. This limits the applicability of both MRI and IRM on most DomainBed (Gulrajani and Lopez-Paz, 2020) benchmarks. Rotated-MNIST, for example, expects an algorithm to generalize to an orientation of the digit that was never seen in the training set. In this case, the support of the training and testing set clearly does not overlap. Similar arguments can be made for other datasets. For example, images with different styles across testing and training domains may not satisfy the significant support overlap condition.

IRM and MRI's domain of applicability only coincide when there is no label shift or shift invariant feature distribution. For datasets that do not follow these conditions, MRI, but not IRM, should fail. However, note that, while IRM is expected to work for such shifts, IRM-v1 fails for such domain shifts (Ahuja et al., 2020, 2021). This is because IRM-v1 and IRM are not the same, as demonstrated by us and Kamath et al. (2021).

References

Ahuja, K., Caballero, E., Zhang, D., Bengio, Y., Mitliagkas, I., and Rish, I. (2021). Invariance principle meets information bottleneck for out-of-distribution generalization. *arXiv preprint arXiv:2106.06607*.

Ahuja, K., Wang, J., Dhurandhar, A., Shanmugam, K., and Varshney, K. R. (2020). Empirical or invariant risk minimization? a sample complexity perspective. *arXiv preprint arXiv:2010.16412*.

Akuzawa, K., Iwasawa, Y., and Matsuo, Y. (2019). Adversarial invariant feature learning with accuracy constraint for domain generalization. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pages 315–331. Springer.

Albuquerque, I., Monteiro, J., Darvishi, M., Falk, T. H., and Mitliagkas, I. (2019). Generalizing to unseen domains via distribution matching. *arXiv preprint arXiv:1911.00804*.

Arjovsky, M., Bottou, L., Gulrajani, I., and Lopez-Paz, D. (2019). Invariant risk minimization. *arXiv preprint arXiv:1907.02893*.

Bertsekas, D. P. (1976). Multiplier methods: A survey. *Automatica*, 12(2):133–145.

Creager, E., Jacobsen, J.-H., and Zemel, R. (2021). Environment inference for invariant learning. In *International Conference on Machine Learning*, pages 2189–2200. PMLR.

Ganin, Y., Ustinova, E., Ajakan, H., Germain, P., Larochelle, H., Laviolette, F., Marchand, M., and Lempitsky, V. (2016). Domain-adversarial training of neural networks. *The journal of machine learning research*, 17(1):2096–2030.

Ghifary, M., Balduzzi, D., Kleijn, W. B., and Zhang, M. (2016). Scatter component analysis: A unified framework for domain adaptation and domain generalization. *IEEE transactions on pattern analysis and machine intelligence*, 39(7):1414–1430.

Gong, M., Zhang, K., Liu, T., Tao, D., Glymour, C., and Schölkopf, B. (2016). Domain adaptation with conditional transferable components. In *International conference on machine learning*, pages 2839–2848. PMLR.

Gulrajani, I. and Lopez-Paz, D. (2020). In search of lost domain generalization. *arXiv preprint arXiv:2007.01434*.

Heinze-Deml, C., Peters, J., and Meinshausen, N. (2018). Invariant causal prediction for nonlinear models. *Journal of Causal Inference*, 6(2).

Hu, S., Zhang, K., Chen, Z., and Chan, L. (2020). Domain generalization via multidomain discriminant analysis. In *Uncertainty in Artificial Intelligence*, pages 292–302. PMLR.

Ilse, M., Tomczak, J. M., Louizos, C., and Welling, M. (2020). Diva: Domain invariant variational autoencoders. In *Medical Imaging with Deep Learning*, pages 322–348. PMLR.

Kamath, P., Tangella, A., Sutherland, D., and Srebro, N. (2021). Does invariant risk minimization capture invariance? In *International Conference on Artificial Intelligence and Statistics*, pages 4069–4077. PMLR.

Krueger, D., Caballero, E., Jacobsen, J.-H., Zhang, A., Binas, J., Zhang, D., Le Priol, R., and Courville, A. (2021). Out-of-distribution generalization via risk extrapolation (rex). In *International Conference on Machine Learning*, pages 5815–5826. PMLR.

LeCun, Y., Bottou, L., Bengio, Y., and Haffner, P. (1998). Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324.

Li, D., Yang, Y., Song, Y.-Z., and Hospedales, T. M. (2018a). Learning to generalize: Meta-learning for domain generalization. In *Thirty-Second AAAI Conference on Artificial Intelligence*.

Li, Y., Gong, M., Tian, X., Liu, T., and Tao, D. (2018b). Domain generalization via conditional invariant representations. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32.

Long, M., Cao, Z., Wang, J., and Jordan, M. I. (2018). Conditional adversarial domain adaptation. *Advances in neural information processing systems*, 31.

Mahajan, D., Tople, S., and Sharma, A. (2021). Domain generalization using causal matching. In *International Conference on Machine Learning*, pages 7313–7324. PMLR.

Muandet, K., Balduzzi, D., and Schölkopf, B. (2013). Domain generalization via invariant feature representation. In *International Conference on Machine Learning*, pages 10–18. PMLR.

Pearl, J. (2009). *Causality*. Cambridge university press.

Peters, J., Bühlmann, P., and Meinshausen, N. (2016). Causal inference by using invariant prediction: identification and confidence intervals. *Journal of the Royal Statistical Society. Series B (Statistical Methodology)*, pages 947–1012.

Rojas-Carulla, M., Schölkopf, B., Turner, R., and Peters, J. (2018). Invariant models for causal transfer learning. *The Journal of Machine Learning Research*, 19(1):1309–1342.

Rosenfeld, E., Ravikumar, P., and Risteski, A. (2020). The risks of invariant risk minimization. *arXiv preprint arXiv:2010.05761*.

Shankar, S., Piratla, V., Chakrabarti, S., Chaudhuri, S., Jyothi, P., and Sarawagi, S. (2018). Generalizing across domains via cross-gradient training. *arXiv preprint arXiv:1804.10745*.

Wald, Y., Feder, A., Greenfeld, D., and Shalit, U. (2021). On calibration and out-of-domain generalization. *Advances in Neural Information Processing Systems*, 34.