LARGE-SCALE DYNAMIC GRAPH GENERATION VIA LLM-BASED AGENT SIMULATION

Anonymous authors

Paper under double-blind review

Abstract

Graph generation is a fundamental task that has been extensively studied in social, technological, and scientific analysis. For modeling the dynamic graph evolution process, traditional rule-based methods struggle to capture community structures within graphs, while deep learning methods only focus on fitting training graphs. This limits existing graph generators to producing graphs that adhere to predefined rules or closely resemble training datasets, achieving poor performance in dynamic graph generation. Given that graphs are abstract representations arising from pairwise interactions in human activities, a realistic simulation of human-wise interaction could provide deeper insights into the graph evolution mechanism. With the increasing recognition of large language models (LLMs) in simulating human behavior, we introduce GraphAgent-Generator (GAG), a novel simulation-based framework for dynamic text-attributed graph generation. Without training or fine-tuning process of LLM, our framework effectively replicates seven macro-level structural characteristics in established network science theories while surpassing existing baselines in graph expansion tasks by 11% on specific evaluation metrics. Through node classification task, we validate GAG effectively captures the intricate text-structure correlations in graph generation. Furthermore, GAG supports generating graphs with up to nearly 100,000 nodes or 10 million edges through large-scale LLM-based agent simulation with parallel acceleration, achieving a minimum speed-up of 90.4%. The source code is available at https://anonymous.4open.science/r/GraphAgent-2206.

033

004

010 011

012

013

014

015

016

017

018

019

021

025

026

027

028

1 INTRODUCTION

034 Graphs are mathematical structures representing pairwise interactions between entities through nodes and edges, serving as a fundamental concept in network science. They are widely used to 035 model interaction behaviors across various domains, including social analysis (Fan et al., 2019), parallel computing (Hendrickson & Kolda, 2000), and program synthesis (Nguyen et al., 2012). 037 A longstanding task in network science is graph generation. Given an observed graph dataset, researchers extract the underlying generative mechanisms to create models that can scale these observations into larger graphs. Network science theories constitute macro properties such as power-040 law degree distribution (Clauset et al., 2009). In contrast, micro properties include graph structure 041 metrics like degree distribution and clustering coefficient (Martinkus et al., 2022). By comparing the 042 macro and micro properties of the generated and real-world graphs, researchers gain deeper insights 043 into graph evolution mechanisms.

044 Existing graph generation methods can be categorized into two types: (1) Rule-based methods, which rely on preset rules to generate graphs (Erdos et al., 1960; Barabási & Albert, 1999). These methods 046 are designed to capture specific macro properties observed in real-world networks. However, the need 047 for tailored models to capture each property complicates the integration of these methods into a unified 048 framework. Additionally, they fall short in capturing micro-level properties in dynamic graph generation (Bergmeister et al., 2024). (2) Deep learning-based methods, which leverage self-supervised learning to capture graph structures. These methods mainly include auto-regressive methods (You 051 et al., 2018) and one-shot methods (Vignac et al., 2023; Bergmeister et al., 2024; Simonovsky & Komodakis, 2018). While these techniques excel in fitting micro properties of observed graphs, they 052 face challenges when generating larger graphs beyond the size of the observed dataset (Bergmeister et al., 2024) and struggle to capture macro properties in dynamic graph generation.

The limitations of previous methods stem from their attempts to use a single model to represent all forms of entity-wise interaction process. Instead of merely adhering to preset rules or fitting training data, a desirable graph generator understands how graphs are formed to generate structures that align with the underlying physical interaction process. For instance, the dynamics of human social interactions significantly influence the social network evolution Fowler & Christakis (2010). Fortunately, the emergence of LLMs like LLaMA (AI@Meta, 2024) and GPT-4 (OpenAI, 2023) has opened new avenues for graph generation. With their ability for human-like reasoning, LLM-based agents can effectively simulate complex interaction processes in human activities (Park et al., 2023).

In this work, we introduce GraphAgent-Generator (GAG), a novel human behavior simulation based framework via LLM-based agents for graph generation. We propose the S-RAG algorithm to
 model the human interaction process with carefully designed LLM-based agents for human behavior
 simulation. Through continuous simulations, we can extract diverse graphs as abstract representations
 of collected interaction data. Furthermore, we propose N-ACTOR to accelerate the simulation process
 by parallel processing. Through experiments conducted in GAG, our main contributions are:

(1) Graphs of Real-World Network Structures: The generated graphs exhibit seven essential structural characteristics observed in real-world networks, including *power-law degree distribution*, *small-world, shrinking diameter* and etc. Specifically, GAG surpasses the best-performing baseline by 11% on specific evaluation metrics for graph expansion tasks.

(2) Interpretability in Graph Generation: To our knowledge, GAG is the first framework to generate text-rich data for modeling graph evolution, offering clear process interpretability. In the context of node classification using Graph Neural Networks (GNNs), the graph generated by GAG retains accuracy comparable to that of the real-world graph. This demonstrates the capability of GAG to produce effective text features for graphs.

(3) Graph Generation via Large-Scale LLM-based Agent Simulation: The framework supports the generation of graphs across ten distinct types, accommodating up to 10 million edges or nearly 100,000 nodes through simulations with up to nearly 100,000 LLM-based agents. Additionally, the N-ACTOR component accelerates the simulation process through parallel computing with a minimum speed-up of 90.4%.

082 083

2 RELATED WORK

084 085

Graph Generation As an extensively explored foundational task, existing graph generation methods 087 mainly fall into two categories: (1) Rule-based methods, which gradually add nodes based on 088 random (Erdos et al., 1960) or preferential attachment (Barabási & Albert, 1999) rules; Though (Barabási & Albert, 1999) successfully models power-law degree distribution, they struggle to capture 089 the community structures prevalent in real-world networks (You et al., 2018). (2) Deep Learning 090 based methods: In recent years, deep learning offer a new approach, aiming to capture the complex 091 and diverse structures of real-world networks, which mainly fall into two categories: Autoregressive 092 methods (You et al., 2018; Dai et al., 2020; Bergmeister et al., 2024) predict edges incrementally for 093 each new node, while one-shot methods (Simonovsky & Komodakis, 2018; De Cao & Kipf, 2018; 094 Liu et al., 2019; Vignac et al., 2023) generate entire graphs in a single step. However, these methods 095 require large-scale training data and struggle to generate graphs outside the training distribution. 096 Although some progress is made with extrapolating to out-of-distribution graphs (Bergmeister et al., 097 2024; Limnios et al., 2023), the maximum size of graph is limited to thousands of nodes.

098 LLM-based Human Behavior Simulation With LLMs demonstrating advanced capabilities in 099 human-like responses and autonomous planning (Gao et al., 2023), they are increasingly recognized 100 as a new paradigm for simulations across fields such as education (Chen et al., 2024), social dynam-101 ics (Park et al., 2023), and economics (Li et al., 2024b). In graph generation, De Marzo et al. (2023) 102 first explores the scale-free property of power-law distributions in LLM-based agent interactions. 103 Subsequently, Papachristou & Yuan (2024); Chang et al. (2024) examines additional social network 104 properties. However, these simulations often lack realism due to simplified modeling of human 105 behavior, such as name selection, and are typically constrained to fewer than 100 agents. Recently, Pan et al. (2024) introduced AgentScope, a framework enabling large-scale multi-agent simulations 106 for simplified human behavior, demonstrated through number-guessing games. Building on this, we 107 have enhanced AgentScope to simulate more complex human behaviors at a large scale.

THE GAG FRAMEWORK 3

In this section, we present GAG, a versatile LLM-simulation-based framework designed for largescale graph generation. GAG aims to eliminate preset rules and training processes in graph generation through simulation-based methods.



Figure 1: An illustration of the GAG Framework for generating social networks: (1) Agent Formulation, where diverse agents are initialized; (2) Pairwise Interaction, where agents interact by 132 generating and retrieving content from a shared corpus; (3) Graph Extraction, where interactions are translated into a dynamic network of nodes and edges; and (4) **Parallel Acceleration**, which implements inter- and intra-batch parallelism to speed up the simulation process. 135

136 137

138

131

133

134

108

110

111

112

3.1 PROBLEM SETUP

139 Graphs serve as mathematical structures that represent relationships and interactions among en-140 tities (Bergmeister et al., 2024-05). In this paper, we consider dynamic graph generation for 141 text-attributed graphs. In the graph generation task, we consider a seed graph $G(\mathcal{V}, \mathcal{E}, \mathcal{X})$, where 142 $\mathcal{V} = \{v_i\}_{i=1}^n$ represents a set of nodes, $\mathcal{E} = \{e_{ij}\}$ denotes the set of edges connecting these nodes, and $\mathcal{X} = \{x_1, \ldots, x_n\}$ comprises the text attribute values associated with each vertex. Here, x_i 143 indicates the text attribute linked to node v_i . The graph generation model seeks to learn how G 144 evolves into a significantly larger graph $G'(\mathcal{V}, \mathcal{E}', \mathcal{X}')$, where $n' \gg n$ and $m' \gg m$, over time. 145 The objective is for the generated graph G' to accurately mirror the macro patterns of the original 146 graph during evolution while maintaining its essential structural properties. In citation networks, for 147 example, graph evolution closely reflects the temporal interactions involved in paper-citing behavior 148 among authors. By simulating these interactions to capture the dynamics of graph evolution, we gain 149 a deeper understanding of how human behavior patterns drive changes in graph structure.

150 To design an effective dynamic graph generator, we develop the GAG framework to simulate pairwise 151 interactions in human activities, modeling graph evolution as a process of collecting interaction 152 data repeatedly. Leveraging the ability of LLMs to mimic human-like behaviors (Li et al., 2023; 153 Park et al., 2022; 2023), we construct LLM-based agents for human behavior simulation, denoted 154 as $A = \{a_1, a_2, \ldots, a_N\}$, where N is the number of agents. Each interaction process between A 155 corresponds to an update of the G. In the k-th simulation round, agent $a_l \in A$ observes the data from 156 G and generate a subgraph G_k^l . Then, the subgraph produced by all agents is $G_k = G_k^l \cup G_k^2 \cup \ldots \cup G_k^N$. 157 Therefore, after k rounds of simulation, G gradually evolves into $G': G' = G_0 \cup G_1 \cup G_2 \cup \cdots \cup G_k$. 158 Specifically, the GAG framework employs a three-step simulation workflow, as illustrated in Figure 1: (1) Agent Formulation: Diverse agents with unique profiles and memory capacities are initialized. 159 (2) Pairwise Interaction: Agents engage in pairwise interactions through a virtual environment. (3) 160 **Graph Extraction**: G is extracted as abstract representations of interaction data. Additionally, we 161 implement a Parallel Acceleration framework to enhance the efficiency of the simulation process.

162 3.2 AGENT FORMULATION

To achieve a credible simulation of human behaviors, we adhere to the general paradigm for constructing LLM-based Agents (Park et al., 2023), each agent a_l is equipped with three key components: Agent Profile, denoted as p_l ; Memory Stream, denoted as m_l ; and Action State, denoted as s_l .

167 Agent Profile Previous research (Chan et al., 2024) has shown that persona-enhanced prompting 168 effectively guides LLMs in generating distinctive role-play synthetic data. To develop agents with 169 distinct roles, we create agent profiles p_l , which store various aspects of human personal information 170 in textual format. Each agent a_l is initialized using its corresponding profile. These profiles are 171 derived from both real and LLM-generated datasets, with the detailed information provided in 172 Appendix A.1. We then construct heterogeneous agents with diverse profiles, enhancing the realism 173 and scope of our simulations.

174 **Memory Stream** Memory stream m_l collects activity history of a_l in the simulation environment. 175 The memory component acts as a vital reference, enabling the agent to make informed decisions 176 based on past actions and interactions within the simulation environment. We organize the memory 177 stream using reflection (Shinn et al., 2023) and summarization techniques. This design allows the 178 agent to adaptively learn from past interactions.

179 180 181 Action State a_l is equipped with action state s_l its interaction with the environment, which consists of two states: when $s_l = s_{act}$, a_l engages in interaction; when $s_l = s_{inc}$, a_l doesn't.

182 3.3 PAIRWISE INTERACTION183

184 To construct the graph structure, we collect pairwise interaction data between agents and derive 185 the graph from it. The data corpus, denoted as C, consists of text outputs generated by the agents, which also form the environment observed by all agents. For initialization of C, we first transfer seed graph G into its textual form, denoted as C. To achieve this, we utilize an environment template T187 to convert the graph $G(\mathcal{V}, \mathcal{E}, \mathcal{X})$ into its textual format. We map each vertex v_i to a corresponding 188 real-world entity, creating a set of textual descriptions for each entity Feng et al. (2024), details 189 in Appendix A.2. For v_i , we consider its neighboring edges $E_i = \{(v_i, v_i) \mid v_i, v_i \in \mathcal{V}\}$, which 190 compasses all edges connecting v_i to its neighbors; and the vertex's text attribute x_i . Consequently, 191 C is represented as:

192 193

$$C = \{c_1, c_2, \dots, c_n\}$$
 where $c_i = T(v_i, E_i, x_i),$

We define this graph-to-text transformation process as the function C = f(G). To model the graph evolution, we continuously enrich C by agent-wise interactions. Starting with the initial corpus $C_0 = f(G)$. For the k-th simulation round, C is updated with additional textual-form graph generated by agents, denoted as C_k . After k rounds, the corpus evolves from C to C': $C' = C_0 \cup C_1 \cup C_2 \cup \cdots \cup C_k$. At below, we illustrate the process of generating C_k . In the k-th simulation round, two main operations are performed: State Planning and Act with S-RAG.

State Planning In real-world scenarios, human activity exhibits varying levels of frequency. For instance, the user's activity frequency on online social media typically follows a Pareto distribution (Guo et al., 2009). Consequently, we first label the top 20% agents as *core*, while the remaining agents as *regular* based on action history m_l . This label is stored in p_l (see details in Appendix A.2). p_l and m_l serves as input to the LLM, and each agent determines its action state $s_l = \text{LLM}(a_l | p_l, m_l)$.

205 Act with S-RAG To interact with other agents, a_l ideally requires access to the complete C and 206 choose subset $\tilde{o}_l \subset C$ as desired environment feedback. However, since |C| scales with the number 207 of agents N, which can be extremely large for large-scale interaction simulations, the computational cost becomes prohibitive due to the context length limitations of LLMs. Fortunately, empirical studies 208 show that humans hold thresholds for both information processing (Yau et al., 2020) and information 209 spreading (Singh et al., 2013). Consequently, when agent a_l decides to act, it is provided with only 210 partial environmental information, denoted as $o_l \subset C$. Our objective is to ensure that o_l determined 211 by S-RAG closely aligns with \tilde{o}_l . Following traditional RAG (Cuconasu et al., 2024) framework, 212 S-RAG is divided into three processes as shown in Algorithm 1: 213

(1) Index Process: Given the environment data corpus $C = \{c_1, c_2, ..., c_n\}$, where each c_i is stored as a text document. we first convert this corpus into a set of embedding vectors E using an embedding model encoder(\cdot). The process involves transforming each c_i into d-dimensional vectors through

Algo	rithm 1 Process of S-RAG for the <i>k</i> -th simulation round.
Req	uire: Interaction Data Corpus C , large language model LLM, Action Template T_d
1: 5	Step 1: Index Process
2: 8	$\mathcal{E} = \{ \operatorname{encoder}(c), c \in C \},\$
3: 0	$C_k = \emptyset$
4: 1	for $l \in [1, N]$ do
5:	if $s_l == s_{act}$ then $Q_l = \text{LLM}(a_l \mid m_l, s_l = s_{act})$
6:	else continue
7:	end if
8:	Step 2: Query Process
9:	$o_l = \emptyset,$
10:	for $q \in Q_l$ do
11:	$o_l^q = \operatorname{ReCALL}(q, C),$
12:	$o_l^q = \operatorname{ReRANKING}(o_l^q, a_l),$
13:	o_l .append (o_l^q) ,
14:	end for
15:	Step 3: Generation Process
16:	$c^{\kappa \iota} = \mathrm{LLM}(a_l \mid s_l, o_l, m_l, T_a).$
17:	$C_k = C_k \cup \{c^{\kappa \iota}\}$
18: 0	end for
19: ($C = C \cup C_k$

239

249 250 $encoder(\cdot)$ and subsequently storing these vectors in a vector database Douze et al. (2024):

$$E = \{e_1, e_2, \dots, e_n\}$$
 where $e_i = \operatorname{encoder}(c_i) \in \mathbb{R}^d$

This process constructs a database-based interaction environment for agents, thereby providing themwith environmental information.

242 243 (2) Query Process: For agents in an active state, they can freely access environmental information. 244 For agent a_l , obtaining the most relevant information requires first reflecting on its memory m_l . This 244 reflection serves as input to the LLM, for a_l to create a query set: $Q_l = \text{LLM}(a_l | m_l, s_l = s_{act})$. 245 For $q \in Q_l$, we first convert q into embedding vector $e_q = \text{encoder}(q)$. We retrieve the most relevant 246 information o_l^q for each q. This collectively forms the environment feedback $o_l := \{o_l^q, q \in Q_l\}$. 247 The retrieving process of o_l^q is divided into two stages: 1. In Recall stage, we filter out the top N_r 248 documents using the vector retriever, by measuring the embedding similarity between C and q:

$$\operatorname{topk}_{c \in C} \operatorname{Sim} \left(q, c \right) \to o_l^q \quad \text{where} \quad \operatorname{Sim} \left(q, c \right) = \frac{e_q \cdot e_c}{\|e_q\| \cdot \|e_c\|}$$

where o_l^q represents the most relevant documents for q. We adopt cosine similarity to form the similarity function $Sim(\cdot)$. 2. In ReRanking stage, we refine and organize o_l^q according to the personal preferences of agent a_l , which is divided into two phases: (1) Coarse Ranking: we reorder o_l^q based on the interaction data from agents labeled as *core*, which are are prioritized in o_l^q . (2) Fine Ranking: we reorder o_l^q according to the agents' personal preference information in p_l . For example, for a_l with author role and expertise in AI, documents focused on AI-related topics are prioritized in o_l^q . Details are provided in Appendix A.2.

(3) Generation Process: Based on action state s_l , memory stream m_l , environment feedback o_l , the agent generates textual entity descriptions within the environment. Specifically, we instruct a_l to generate coherent and logical response using LLM guided by an action template T_a . For the k-th simulation round, the output generated by a_l is denoted as c^{kl} , which constitute a textual-form graph. Thus the process can be expressed as $c^{kl} = \text{LLM}(a_l | s_l, o_l, m_l, T_a)$.

Finally, m_l is updated with c^{kl} , thereby refining a_l 's perception of the environment. In summary, for the k-th simulation round, the formulation process of C_k can be mathematically formulated as: $C_k = \text{concat}(c^{k1}, c^{k2}, \dots, c^{kN}).$

266 267

- 3.4 GRAPH EXTRACTION
- Through iterative rounds of interaction simulations, we progressively enhance C' using synthetic interaction data. Consequently, we can reverse mapping C' into G' through regex matching, which

270 can be formulated as G' = g(C'). Specifically, for each $c \in C$, we establish three mapping functions 271 to extract the graph components: (1) corpus-to-node mapping function $g_v: C \to \mathcal{V}$. (2) corpus-to-272 edge mapping function $g_e: C \to \mathcal{E}$. (3) corpus-to-text attribute mapping function $g_x: C \to \mathcal{X}$. 273 The specific mapping functions are dependent on the target graph type, as detailed in Appendix A.3. 274 For example, in a citation network where C consists of research papers, g_v provides a one-to-one mapping from each paper $c \in C$ to a node; g_e maps all citations within each paper to edges; g_x maps 275 all paper contents to node-wise text attributes. As a result, the subgraph G_k generated in the k-th 276 round can be expressed as: 277

278

282

 $G_{k} = G_{k}^{1} \cup G_{k}^{2} \cup \ldots \cup G_{k}^{N},$ $G_{k}^{l} = (g_{v}(c^{kl}), g_{e}(c^{kl}), g_{x}(c^{kl})), \text{ where } l \in [1, 2, \ldots, N].$

3.5 PARALLEL ACCELERATION

283 The S-RAG allows us to significantly reduce the interaction rounds between agents. However, 284 there remains technical barriers in supporting agent interaction simulation at the scale of $n = 1e^5$. 285 Additionally, we note that the inference time of LLMs is substantial, leading to prolonged IO wait 286 times for idle LLM-based agents. Various solutions have been proposed to address this issue, such 287 as async mechanisms in Langchain (Kansal, 2024) and ACTOR architectures in Agentscope (Gao 288 et al., 2024). For further acceleration, we propose a Nested ACTOR Parallel Processing Schema (N-289 ACTOR). As highlighted by (Clauset et al., 2004), network structures often display tightly connected 290 communities with loosely connected inter-community links. In the context of GAG, we categorize 291 agents into distinct groups marked by strong internal interactions and weaker intergroup interactions. Agent groups can run in parallel on different CPU cores of a computation machine with P ports. The 292 specific algorithm of N-ACTOR is detailed in the Appendix A.4. 293

294 295

4 EXPERIMENT

296 297

In network science, there has long been an interest in graph structures that emerge within scientific, 298 technological, and sociological contexts (Leskovec et al., 2007). To assess our framework, we 299 conduct scenario modeling of these representative domains for graph generation, each illustrating 300 different types of human activity: (1) Creative Activity (CA): This includes the creation of items 301 like academic papers. The agent acts as an author to interact with an academic paper database, producing networks such as Citation, Bibliographic Coupling, Co-Citation, Author Citation, and 302 Co-Authorship networks (Garfield, 2000). Simulation stops at the citation network reaching 1e4 303 nodes. (2) Item Interaction Activity (IA): This includes user-item interactions, including rating 304 movies, purchasing products and etc. The agent acts as a user interacting with an item database, 305 producing networks such as the Movie Rating and User Projection networks (Zhou et al., 2007). 306 Simulation stops at the movie rating network reaching 1e5 edges. (3) Social Activity (SA): This 307 includes interaction and communication behavior. The agent acts as a user interacting with an online 308 social media platform database (e.g., Twitter), producing networks such as Follow, Friend, and Action 309 networks (De Domenico et al., 2013). The simulation stops after 10 simulation rounds. For each 310 simulation scenario, we extract corresponding networks from each simulation scenario.

Evaluation Protocol To evaluate the effectiveness of the GAG, we assess three key aspects: First, we compare the generated graph structures with real-world networks at both macro and micro scales to verify the similarity between the generated and real-world graph evolution. Next, we evaluate the effectiveness of text features for the generated graph using a node classification task. Finally, we assess the scalability of GAG in terms of graph size and generation efficiency. Details on the evaluation hyperparameters and metrics are provided in Appendix B.1.

317 318

319

4.1 EVALUATION OF STRUCTURE ALIGNMENT

Unlike traditional and deep learning-based graph generation methods, GAG does not rely on pre defined rules or structural distributions from training datasets. Instead, graph structures naturally
 emerge from interactions between agents, making the evaluation of these generated structures crucial
 for assessing interaction rationality. In this paper, we investigate the generated graph structures from
 both macro and micro perspectives: At the macro level, we examine the graph structure dynamics in

the graph evolution, and align our observations with established network science theories. At the
 micro level, we use existing graph generation models as baselines to evaluate the effectiveness of
 GAG in capturing micro structural metrics of graph evolution.

Macro-Level Evaluation For macro-level structural characteristic alignment, we examine three structural characteristic observed in real-world networks (Albert & Barabási, 2002): Power-law Distribution, Small-world Phenomenon and Shrinking Diameter. Four additional structural characteristics are detailed in Appendix B.2.

(1) Power-law Distribution: The degree distribution of scale-free networks often follows *power-law* distribution (Barabási & Albert, 1999), which is commonly observed in citation networks and social networks. In simulations with GAG, the generated citation, author-citation, and action networks also exhibit this characteristic. We adhere to the established criteria for evaluating whether the graph's degree distribution follows a power law: $D_k < 0.1$ (Alstott et al., 2014). As shown in Figure 2, the degree distribution of these networks follow a *Power-law* distribution with exponent parameter $\alpha \in [1.90, 2.16]$, closely aligned with $\alpha \in [2, 3]$ from empirical studies (Clauset et al., 2009).



Figure 2: The *Power-law* Distribution of degrees in scale-free networks. The degree k is plotted against the probability density function p_k on a log-log scale. α denotes the exponent parameter, k_{min} represents the minimum cut-off k (Alstott et al., 2014).

(2) Small World Phenomenon:

 Table 1: \bar{cc} of the generated networks, and the ratio to Erdös-Rényi and Barabási-Albert graph model. A dash (—) signifies that $\bar{cc} = 0$ for the graph model.

	Ratio to Random Graphs				
	Citation	Bib-Coupling	Co-Citation	Author Citation	Co-Authorship
Erdös-Rényi Barabási-Albert	301.08	7.46 4.40	275.97 44.87	39.82 11.19	234.81 17.59
	Action	Follow	Friend	Movie Rating	User Projection
Erdös-Rényi Barabási-Albert	784.93 73.97	3961.83 443.80	19768.58 1391.47	0.00 0.00	5.78 2.82

Real-world networks exhibit a *small world* phenomenon (Mislove et al., 2007; Watts & Strogatz, 1998), characterized by a small diameter and a high clustering coefficient. Based on the structure of the generated graphs, we construct two types of random graphs with consistent average degree: Erdős-Rényi (ER) (Erdos et al., 1960) and Barabási-Albert (BA) graphs (Barabási & Albert, 1999). Table 1 compares the average clustering coefficient (\bar{cc}) of the generated graphs with that of the random graphs. The results indicate that generated social networks (i.e., follow, friend, and action networks), exhibit a significantly higher $\bar{c}c$ than those of the random graphs. Additionally, as shown in Table 4, the generated networks exhibit a small diameter, $D_e \in [1.17, 11.66]$, consistent with the six degrees of separation phenomenon observed in real-world networks (Leskovec et al., 2007; Broder et al., 2000). The high $\bar{c}c$, combined with small D_e , confirms these networks exhibit small-world characteristics.

391

392

393

397

399

400

401

410

431

378 (3) Shrinking Diameter: The shrinking diameter is a notable phenomenon in social net-379 works (Leskovec et al., 2007), with D_e decreases as the network evolves over time. We construct SA 380 with N = 7000, and investigate the graph evolution processes of follow, friend, and action networks 381 for 30 simulation rounds. We calculate the D_e metric for both the generated graphs and real-world 382 network datasets: CAIDA¹. As shown in Figure 3a, D_e decreases at a slow pace, identical to the trend observed in (Leskovec et al., 2007) and CAIDA. To explain shrinking diameter, models such as the Forest Fire model (Leskovec et al., 2007) utilize a modified preferential attachment mechanism, 384 known as community-guided attachment. In GAG, the ReRanking process enhances personalized 385 recommendations. To assess its impact on graph structure, we conduct an ablation experiment. As 386 shown in Figure 3b, we observe an initial increase in D_e followed by a rapid decline within friend 387 networks. Notably, upon removing the ReRanking, the D_e trends upwards from 2.6 to 2.96, indicating 388 that ReRanking fosters community-guided attachment and shrinking diameter. 389



Figure 3: The Shrinking Diameter phenomenon simulated by GAG; The left figure demonstrates 402 that as the graph evolves, D_e gradually decreases in action and follows networks; The right figure 403 presents an ablation experiment of the ReRanking, demonstrating its effect on D_e in friend network. 404

405 Micro-Level Evaluation For micro-level structural characteristic alignment, we examine structural 406 characteristics of generated graphs. For baselines, we select the efficient graph generation model 407 for large-scale graph generation. Specifically, we partition the Citeseer network (Sen et al., 2008) into $G_{<t}$ and $G_{>t}$ based on time t. We then expand the small subgraphs of $G_{<t}$ and compare the 408 generated graphs to the large subgraphs of $G_{>t}$. Details in Appendix B.3. 409

Table 2: Comparison with existing graph generation models for graph expansion task. For GRAN 411 and GraphMaker, the generated graphs fail to converge to a power-law distribution. 412

	MMD.D↓	MMD.C↓	MMD.S↓	MMD.O↓	D_k	α	Valid↑	GEM
CiteSeer	-	-	-	-	$0.06_{\pm 0.0}$	$2.38_{\pm 0.0}$	1.0	-
Erdös-Rényi	0.26	1.41	0.56	1.41	$0.1_{\pm 0.01}$	$3.72_{\pm 0.13}$	0.0	0.34
Barabási-Albert	0.20	1.41	0.26	1.02	$0.04_{\pm 0.01}$	$2.38_{\pm 0.04}$	1.0	0.42
Small-World	0.72	1.36	0.59	1.41	$0.42_{\pm 0.01}$	$2.03_{\pm 0.0}$	0.0	0.32
BiGG	0.63	1.13	0.65	1.23	$0.27_{\pm 0.01}$	$1.69_{\pm 0.01}$	0.0	0.33
GRAN	0.36	0.55	0.72	1.41	-	$4.16_{\pm 0.39}$	0.0	0.36
BwR	0.49	1.41	0.66	1.41	$0.07_{\pm 0.09}$	$4.46_{\pm 0.02}$	0.0	0.32
GraphMaker	0.47	1.41	0.83	1.41	-	-	0.0	0.22
L-PPGN	0.76	1.19	0.78	1.05	$0.39_{\pm 0.03}$	$1.36_{\pm 0.02}$	0.0	0.33
GAG	0.16	0.19	0.32	1.02	$0.08_{\pm 0.01}$	$2.37_{\pm 0.03}$	1.0	0.47

424 We define the Valid metric to measure the proportion of valid power-law expanded graphs and the 425 GEM metric to evaluate the overall effectiveness of structure alignment in expanded graphs, details in 426 Appendix B.3 As shown in Table 2, the expanded graphs by GAG adhere to a power law distribution, 427 with $\alpha = 2.39$ close to the seed graph. In contrast, deep-learning-based models tend to overfit 428 the training graph and fail to generate graphs that follow the power-law distribution effectively. 429 Surprisingly, GAG outperforms most baseline models in MMD metrics, which is notable given that 430 no explicit graph structure constraints are provided to the agents. Regarding GEM, GAG surpasses

¹https://sparse.tamu.edu/SNAP/as-caida

432 the best performing baseline by 11%. This suggests that GAG effectively simulates human behavior 433 patterns, generating graphs that closely resemble structural characteristics of real-world networks. 434

4.2 **EVALUATION OF TEXTUAL-ATTRIBUTE ALIGNMENT**

437 GAG generates text-rich dynamic graphs by collecting interaction data among various agents, sim-438 ulating the process of gathering textual features for real-world networks. To evaluate whether the 439 generated graphs preserve the text-structure correlations of the seed graph, we adopt Graph Neural 440 Networks (GNNs) benchmarking tasks of node classification Yoon et al. (2023). Specifically, we employ different Graph Neural Networks (GNNs) to train on both G' and G for the node classification 441 task, measuring the accuracy gap between the two. We denote the accuracy of the GNN on G as 442 Acc_b and the accuracy on G' as Acc. The accuracy gap is calculated as $\Delta Acc = |Acc - Acc_b|$, 443 which measures the fidelity of GAG in preserving the text-structure of G; a smaller ΔAcc indicates 444 better preservation. For benchmarking, we select four representative GNN architectures and construct 445 graphs with eight distinct relationships between graph structures and textual features. Details of the 446 experimental setup are provided in Appendix C. 447

Table 3: Benchmarking different graph generation models on node classification task.

		ΔAC	$C \perp$	
	GAT	GCN	GCN2	GraphSage
SF.random	$13.4_{\pm 3.52}$	$15.04_{\pm 1.99}$	$9.58_{\pm 0.88}$	$7.0_{\pm 0.92}$
F.random	$24.11_{\pm 2.84}$	$23.2_{\pm 2.25}$	$9.33_{\pm 1.36}$	$7.13_{\pm 1.73}$
S.random	$18.85_{\pm 2.55}$	$21.77_{\pm 2.04}$	$2.24_{\pm 1.58}$	$3.15_{\pm 1.84}$
BiGG+LLM	$39.39_{\pm 4.51}$	$34.06_{\pm 6.62}$	$4.73_{\pm 4.43}$	$3.38_{\pm 3.54}$
GRAN+LLM	$5.31_{\pm 3.63}$	$6.08_{\pm 5.12}$	$3.46_{\pm 3.39}$	$4.35_{\pm 2.47}$
BwR+LLM	$35.28_{\pm 2.91}$	$38.52_{\pm 4.68}$	$4.83_{\pm 4.47}$	7.59 ± 4.30
GraphMaker+LLM	$4.04_{\pm 3.49}$	$2.83_{\pm 4.02}$	$3.59_{\pm 4.24}$	$4.17_{\pm 4.03}$
L-PPGN+LLM	$38.39_{\pm 6.39}$	$32.64_{\pm 3.46}$	$3.96_{\pm 3.62}$	$3.85_{\pm 3.75}$
GAG	$2.26_{\pm 1.19}$	$3.61_{\pm 1.32}$	$0.49_{\pm 1.50}$	$0.09_{\pm 1.74}$

461 462

435

436

448

463 As shown in Table 3, the random baselines perform the worst, highlighting the importance of the tight coupling between graph text attributes and graph structure. Existing models such as GRAN 464 and GraphMaker demonstrate strong performance in GNN benchmarking tasks, consistent with the 465 findings in Li et al. (2024a). However, GAG consistently outperforms these baselines, achieving an 466 average improvement of 1.45 in ΔAcc across GNNs, with ΔAcc values ranging from 0.09 to 3.61. These results demonstrate GAG's effectiveness in capturing intricate text-structure correlations.

468 469 470

467

4.3 SCALABILITY OF GAG

471 GAG excels at generating graphs that closely resemble real-world network characteristics, while 472 maintaining high efficiency throughout the generation process. Here, we verify its efficiency by 473 examining both the scale of the graph generated and the running time. 474

Graph Generation Scale In addition to expanding seed graphs, GAG can generate graphs from 475 scratch using LLM-generated agent profiles, eliminating the need for external data collection. We 476 employ this method to generate social networks and produce networks with nearly 100,000 nodes 477 while expanding bibliographic coupling networks to 12.2 million edges. While existing models 478 typically limit graph generation to a maximum of 5,000 nodes (Bergmeister et al., 2024; Liao et al., 479 2019), specialized models designed for sparse large graphs can only generate simple grid-structure 480 graphs with up to 100,000 nodes (Dai et al., 2020). This highlights the capability of GAG to support 481 large-scale agent interaction simulation so as to model large-scale graph evolution. 2 As shown 482 in Table 4, we calculate the structural metrics of all generated networks. Similar to the assortative-

²To intuitively illustrate the graph evolution process modeled by GAG, we choose the SA simulation 485 scenario and visualization in https://anonymous.4open.science/r/GraphAgent-2206/visualization/ social_network.mp4

	Citation	Bib-Coupling	Co-Citation	Author Citation	Co-Authorship
$ \mathcal{V} $	1.14e+04	1.09e+04	3.93e+03	5.01e+03	5.01e+03
$ \mathcal{E} $	3.63e+04	1.22e+07	3.27e+04	2.41e+05	2.08e+04
$\bar{c}c$	0.08	0.77	0.59	0.38	0.20
r	-0.10	0.09	-0.10	-0.18	0.32
D_e	5.19	2.94	3.89	3.44	5.77
	Action	Follow	Friend	Movie Rating	User Projection
$ \mathcal{V} $	9.97e+04	9.96e+04	9.96e+04	4.17e+03	3.91e+03
$ \mathcal{E} $	9.07e+05	1.53e+06	5.01e+05	3.25e+04	9.04e+05
$\bar{c}c$	0.07	0.61	1.00	0.00	0.34
r	-0.03	0.06	0.59	-0.54	-0.11
D_{a}	2.79	2.85	11.66	2.98	1.17

Table 4: The structural metrics for graphs generated by GAG.

mixing patterns discovered in real-world networks (Newman, 2002), the citation network exhibits negative assortativity, whereas the co-authorship network displays positive assortativity.

Graph Generation Efficiency We evaluate efficiency by measuring the impact of the number of agents (N) and the number of ports (P) on the runtime of the framework, specifically the time required to generate a single interaction. Tests are conducted on a machine with 96 CPU cores and 376GB of memory. As shown in Table 5, when P is held constant, the time to generate one interaction data decreases as N increases. The most significant time reduction observed in the CA simulation, where agents are grouped by paper authorship, which maximizes the efficiency of the N-ACTOR component. Conversely, as shown in Table 6, when N remains constant, the time to generate a single c decreases as P increases. Notably, the time decreases by 90.4% when P > 1 compared to P = 1at least, demonstrating the acceleration effectiveness of N-ACTOR component.

Table 5: The time cost (*min*) of agents for generating one interaction data with P = 24.

Table 6: The time cost (*min*) of 40 agents for generating one interaction data with different P.

5	0 66.3%	64.0%	50.0%	$1 \rightarrow 24$	97.5%	-
4	0 0.0910	0.0054	0.0060	24	0.0910	
2	0 0.1700	0.0052	0.0119	16	6 0.1160	
1	0 0.2300	0.0112	0.0119	4	0.1470	
	5 0.2700	0.0150	0.0120	1	3.6250	
]	N CA	IA	SA	P	' CA	

CONCLUSION

In this study, we present GAG, a novel and general framework designed for generating large-scale graphs with human behavior simulation. Our comprehensive experiments show that GAG can generate large-scale graphs with high quality and efficiency, with specified focus on graphs arise from scientific, technological and sociological context. The generated graphs exhibit seven macro-level characteristics of real-world networks, including power law, small world and shrinking diameter. In the citation network expansion task, GAG demonstrates superior performance compared to existing deep-learning-based graph generation methods in accurately capturing the power-law distribution property. Furthermore, we present the S-RAG algorithm for simulating diverse human interaction processes at scale, complemented by the N-ACTOR for parallel acceleration, achieving a speed-up of at least 90.4%. Our framework successfully produces high-quality graphs with up to nearly 100,000 nodes or 10 million edges. Overall, GAG serves as a promising step towards efficient large-scale human interaction simulation and graph generation.

540	REFERENCES
541	

550

551

561

562

563

564 565

566

567

568

569

570

580

- 542 AI@Meta. Llama 3 model card. 2024. URL https://github.com/meta-llama/llama3/blob/ 543 main/MODEL_CARD.md.
- Réka Albert and Albert-László Barabási. Statistical mechanics of complex networks. *Reviews of modern physics*, 74(1):47, 2002.
- Jeff Alstott, Ed Bullmore, and Dietmar Plenz. powerlaw: a python package for analysis of heavy-tailed
 distributions. *PloS one*, 9(1):e85777, 2014.
 - Albert-László Barabási and Réka Albert. Emergence of scaling in random networks. *science*, 286 (5439):509–512, 1999.
- Andreas Bergmeister, Karolis Martinkus, Nathanaël Perraudin, and Roger Wattenhofer. Efficient
 and scalable graph generation through iterative local expansion. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=
 2XkTz7gdpc.
- Andreas Bergmeister, Karolis Martinkus, Nathanaël Perraudin, and Roger Wattenhofer. Efficient and scalable graph generation through iterative local expansion. s.l., 2024-05. OpenReview. 12th International Conference on Learning Representations (ICLR 2024); Conference Location: Vienna, Austria; Conference Date: May 7-11, 2024; Poster presentation.
 - Andrei Broder, Ravi Kumar, Farzin Maghoul, Prabhakar Raghavan, Sridhar Rajagopalan, Raymie Stata, Andrew Tomkins, and Janet Wiener. Graph structure in the web. *Computer Networks*, 33(1): 309–320, 2000. ISSN 1389-1286. doi: https://doi.org/10.1016/S1389-1286(00)00083-9. URL https://www.sciencedirect.com/science/article/pii/S138912860000839.
 - Xin Chan, Xiaoyang Wang, Dian Yu, Haitao Mi, and Dong Yu. Scaling synthetic data creation with 1,000,000,000 personas, 2024. URL https://arxiv.org/abs/2406.20094.
 - Serina Chang, Alicja Chaszczewicz, Emma Wang, Maya Josifovska, Emma Pierson, and Jure Leskovec. Llms generate structurally realistic social networks but overestimate political homophily, 2024. URL https://arxiv.org/abs/2408.16629.
- Weize Chen, Yusheng Su, Jingwei Zuo, Cheng Yang, Chenfei Yuan, Chi-Min Chan, Heyang Yu,
 Yaxi Lu, Yi-Hsin Hung, Chen Qian, Yujia Qin, Xin Cong, Ruobing Xie, Zhiyuan Liu, Maosong
 Sun, and Jie Zhou. Agentverse: Facilitating multi-agent collaboration and exploring emergent
 behaviors. In *The Twelfth International Conference on Learning Representations*, 2024. URL
 https://openreview.net/forum?id=EHg5GDnyq1.
- Aaron Clauset, Mark EJ Newman, and Cristopher Moore. Finding community structure in very large networks. *Physical Review E—Statistical, Nonlinear, and Soft Matter Physics*, 70(6):066111, 2004.
 - Aaron Clauset, Cosma Rohilla Shalizi, and Mark EJ Newman. Power-law distributions in empirical data. SIAM review, 51(4):661–703, 2009.
- Florin Cuconasu, Giovanni Trappolini, Federico Siciliano, Simone Filice, Cesare Campagnano, Yoelle Maarek, Nicola Tonellotto, and Fabrizio Silvestri. The power of noise: Redefining retrieval for rag systems. In *Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval*, SIGIR 2024. ACM, July 2024. doi: 10.1145/3626772. 3657834. URL http://dx.doi.org/10.1145/3626772.3657834.
- Hanjun Dai, Azade Nazi, Yujia Li, Bo Dai, and Dale Schuurmans. Scalable deep generative modeling for sparse graphs. In *International conference on machine learning*, pp. 2302–2312. PMLR, 2020.
- Nicola De Cao and Thomas Kipf. Molgan: An implicit generative model for small molecular graphs.
 arXiv preprint arXiv:1805.11973, 2018.
- 593 Manlio De Domenico, Antonio Lima, Paul Mougel, and Mirco Musolesi. The anatomy of a scientific rumor. Scientific reports, 3(1):2980, 2013.

614

631

632

633

- Giordano De Marzo, Luciano Pietronero, and David Garcia. Emergence of scale-free networks in social interactions among large language models. *arXiv preprint arXiv:2312.06619*, 2023.
- 597 Nathaniel Lee Diamant, Alex M Tseng, Kangway V Chuang, Tommaso Biancalani, and Gabriele
 598 Scalia. Improving graph generation by restricting graph bandwidth. In *International Conference* 599 *on Machine Learning*, pp. 7939–7959. PMLR, 2023.
- Matthijs Douze, Alexandr Guzhva, Chengqi Deng, Jeff Johnson, Gergely Szilvasy, Pierre-Emmanuel Mazaré, Maria Lomeli, Lucas Hosseini, and Hervé Jégou. The faiss library, 2024. URL https: //arxiv.org/abs/2401.08281.
- Paul Erdos, Alfréd Rényi, et al. On the evolution of random graphs. *Publ. math. inst. hung. acad. sci*, 5(1):17–60, 1960.
- Wenqi Fan, Yao Ma, Qing Li, Yuan He, Eric Zhao, Jiliang Tang, and Dawei Yin. Graph neural networks for social recommendation. In *The World Wide Web Conference*, WWW '19, pp. 417–426, New York, NY, USA, 2019. Association for Computing Machinery. ISBN 9781450366748. doi: 10.1145/3308558.3313488. URL https://doi.org/10.1145/3308558.3313488.
- Jiarui Feng, Hao Liu, Lecheng Kong, Yixin Chen, and Muhan Zhang. Taglas: An atlas of textattributed graph datasets in the era of large graph and language models, 2024. URL https: //arxiv.org/abs/2406.14683.
- James H. Fowler and Nicholas A. Christakis. Cooperative behavior cascades in human social networks. *Proceedings of the National Academy of Sciences*, 107(12):5334–5338, 2010. doi: 10. 1073/pnas.0913149107. URL https://www.pnas.org/doi/abs/10.1073/pnas.0913149107.
- Chen Gao, Xiaochong Lan, Nian Li, Yuan Yuan, Jingtao Ding, Zhilun Zhou, Fengli Xu, and Yong
 Li. Large language models empowered agent-based modeling and simulation: A survey and
 perspectives. *arXiv preprint arXiv:2312.11970*, 2023.
- Dawei Gao, Zitao Li, Weirui Kuang, Xuchen Pan, Daoyuan Chen, Zhijian Ma, Bingchen Qian, Liuyi
 Yao, Lin Zhu, Chen Cheng, et al. Agentscope: A flexible yet robust multi-agent platform. *arXiv preprint arXiv:2402.14034*, 2024.
- Eugene Garfield. The web of knowledge: a festschrift in honor of Eugene Garfield. Information Today, Inc., 2000.
- Lei Guo, Enhua Tan, Songqing Chen, Xiaodong Zhang, and Yihong Zhao. Analyzing patterns of
 user content generation in online social networks. In *Proceedings of the 15th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 369–378, 2009.
 - F. Maxwell Harper, Joseph A. Konstan, and Joseph A. The movielens datasets: History and context. *ACM Trans. Interact. Intell. Syst.*, 5:19:1–19:19, 2016. URL https://api.semanticscholar. org/CorpusID:16619709.
- Bruce Hendrickson and Tamara G Kolda. Graph partitioning models for parallel computing. *Parallel computing*, 26(12):1519–1534, 2000.
- Carl Hewitt, Peter Bishop, and Richard Steiger. A universal modular actor formalism for artificial intelligence. In *Proceedings of the 3rd International Joint Conference on Artificial Intelligence*, IJCAI'73, pp. 235–245, San Francisco, CA, USA, 1973. Morgan Kaufmann Publishers Inc.
- Nathan O. Hodas, Farshad Kooti, and Kristina Lerman. Friendship paradox redux: Your friends are more interesting than you, 2013. URL https://arxiv.org/abs/1304.3480.
- Don H Johnson. Signal-to-noise ratio. *Scholarpedia*, 1(12):2088, 2006.
- Aarushi Kansal. LangChain: Your Swiss Army Knife, pp. 17–40. Apress, Berkeley, CA, 2024. ISBN 979-8-8688-0205-8. doi: 10.1007/979-8-8688-0205-8_2. URL https://doi.org/10.1007/979-8-8688-0205-8_2.

648 649 650 651	Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. Efficient memory management for large language model serving with pagedattention. In <i>Proceedings of the ACM SIGOPS 29th Symposium on Operating Systems Principles</i> , 2023.
652 653 654 655	Jure Leskovec, Jon Kleinberg, and Christos Faloutsos. Graph evolution: Densification and shrinking diameters. <i>ACM Trans. Knowl. Discov. Data</i> , 1(1):2–es, mar 2007. ISSN 1556-4681. doi: 10.1145/1217299.1217301. URL https://doi.org/10.1145/1217299.1217301.
656 657 658	Guohao Li, Hasan Abed Al Kader Hammoud, Hani Itani, Dmitrii Khizbullin, and Bernard Ghanem. Camel: Communicative agents for "mind" exploration of large language model society. NIPS '23, 2023.
660 661	Mufei Li, Eleonora Kreačić, Vamsi K. Potluru, and Pan Li. Graphmaker: Can diffusion models generate large attributed graphs? <i>Transactions on Machine Learning Research</i> , 2024a.
662 663 664 665 666 667	Nian Li, Chen Gao, Mingyu Li, Yong Li, and Qingmin Liao. EconAgent: Large language model- empowered agents for simulating macroeconomic activities. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), <i>Proceedings of the 62nd Annual Meeting of the Association for</i> <i>Computational Linguistics (Volume 1: Long Papers)</i> , pp. 15523–15536, Bangkok, Thailand, August 2024b. Association for Computational Linguistics. URL https://aclanthology.org/ 2024.acl-long.829.
668 669 670 671	Renjie Liao, Yujia Li, Yang Song, Shenlong Wang, Will Hamilton, David K Duvenaud, Raquel Urtasun, and Richard Zemel. Efficient graph generation with graph recurrent attention networks. <i>Advances in neural information processing systems</i> , 32, 2019.
672 673 674	Stratis Limnios, Praveen Selvaraj, Mihai Cucuringu, Carsten Maple, Gesine Reinert, and Andrew Elliott. Sagess: Sampling graph denoising diffusion model for scalable graph generation, 2023. URL https://arxiv.org/abs/2306.16827.
675 676 677	Jenny Liu, Aviral Kumar, Jimmy Ba, Jamie Kiros, and Kevin Swersky. Graph normalizing flows. <i>Advances in Neural Information Processing Systems</i> , 32, 2019.
678 679 680	Karolis Martinkus, Andreas Loukas, Nathanaël Perraudin, and Roger Wattenhofer. Spectre: Spectral conditioning helps to overcome the expressivity limits of one-shot graph generators. In <i>International Conference on Machine Learning</i> , pp. 15159–15179. PMLR, 2022.
681 682 683 684	Alan Mislove, Massimiliano Marcon, Krishna P Gummadi, Peter Druschel, and Bobby Bhattacharjee. Measurement and analysis of online social networks. In <i>Proceedings of the 7th ACM SIGCOMM</i> <i>conference on Internet measurement</i> , pp. 29–42, 2007.
685 686	Xinyi Mou, Zhongyu Wei, and Xuanjing Huang. Unveiling the truth and facilitating change: Towards agent-based large-scale social movement simulation. <i>arXiv preprint arXiv:2402.16333</i> , 2024.
687 688 689 690	M. E. J. Newman. Assortative mixing in networks. <i>Phys. Rev. Lett.</i> , 89:208701, Oct 2002. doi: 10.1103/PhysRevLett.89.208701. URL https://link.aps.org/doi/10.1103/PhysRevLett. 89.208701.
691 692 693 694	Anh Tuan Nguyen, Tung Thanh Nguyen, Hoan Anh Nguyen, Ahmed Tamrawi, Hung Viet Nguyen, Jafar Al-Kofahi, and Tien N Nguyen. Graph-based pattern-oriented, context-sensitive source code completion. In 2012 34th International Conference on Software Engineering (ICSE), pp. 69–79. IEEE, 2012.
695 696	OpenAI. Gpt-4 technical report, 2023.
697 698 699 700	Xuchen Pan, Dawei Gao, Yuexiang Xie, Zhewei Wei, Yaliang Li, Bolin Ding, Ji-Rong Wen, and Jingren Zhou. Very large-scale multi-agent simulation in agentscope. <i>arXiv preprint arXiv:2407.17789</i> , 2024.
704	Marios Panachristou and Yuan Vuan Network formation and dynamics among multi-llms arXiv

701 Marios Papachristou and Yuan Yuan. Network formation and dynamics among multi-llms. *arXiv* preprint arXiv:2402.10659, 2024.

702 703 704 705 706	Joon Sung Park, Lindsay Popowski, Carrie Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. Social simulacra: Creating populated prototypes for social computing systems. In <i>Proceedings of the 35th Annual ACM Symposium on User Interface Software and Technology</i> , UIST '22, New York, NY, USA, 2022. Association for Computing Machinery. ISBN 9781450393201. doi: 10.1145/3526113.3545616. URL https://doi.org/10.1145/3526113.3545616.
707 708 709 710 711 712	Joon Sung Park, Joseph O'Brien, Carrie Jun Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. Generative agents: Interactive simulacra of human behavior. In <i>Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology</i> , UIST '23, New York, NY, USA, 2023. Association for Computing Machinery. ISBN 9798400701320. doi: 10.1145/3586183.3606763. URL https://doi.org/10.1145/3586183.3606763.
713 714 715	Nils Reimers and Iryna Gurevych. Sentence-bert: Sentence embeddings using siamese bert-networks. In <i>Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing</i> . Association for Computational Linguistics, 11 2019. URL https://arxiv.org/abs/1908.10084.
716 717 718	Prithviraj Sen, Galileo Namata, Mustafa Bilgic, Lise Getoor, Brian Gallagher, and Tina Eliassi-Rad. Collective classification in network data. <i>AI Mag.</i> , 29(3):93–106, 2008.
719 720 721 722	Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. <i>arXiv preprint arXiv:2303.11366</i> , 2023.
723 724 725 726	Martin Simonovsky and Nikos Komodakis. Graphvae: Towards generation of small graphs using variational autoencoders. In Artificial Neural Networks and Machine Learning–ICANN 2018: 27th International Conference on Artificial Neural Networks, Rhodes, Greece, October 4-7, 2018, Proceedings, Part I 27, pp. 412–422. Springer, 2018.
727 728 729 730	P. Singh, S. Sreenivasan, B. K. Szymanski, and G. Korniss. Threshold-limited spreading in social networks with multiple initiators. <i>Scientific Reports</i> , 3(1), July 2013. ISSN 2045-2322. doi: 10.1038/srep02330. URL http://dx.doi.org/10.1038/srep02330.
731 732 733	Johan Ugander, Brian Karrer, Lars Backstrom, and Cameron Marlow. The anatomy of the facebook social graph. <i>arXiv preprint arXiv:1111.4503</i> , 2011.
734 735 736	Clément Vignac, Igor Krawczuk, Antoine Siraudin, Bohan Wang, Volkan Cevher, and Pascal Frossard. Digress: Discrete denoising diffusion for graph generation. In <i>Proceedings of the 11th International</i> <i>Conference on Learning Representations</i> , 2023.
737 738 739	Duncan J Watts and Steven H Strogatz. Collective dynamics of 'small-world' networks. <i>nature</i> , 393 (6684):440–442, 1998.
740 741 742 743	Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, brian ichter, Fei Xia, Ed Chi, Quoc V Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models. NIPS '22, 2022.
744 745 746 747 748 749 750 751 752 753	An Yang, Baosong Yang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Zhou, Chengpeng Li, Chengyuan Li, Dayiheng Liu, Fei Huang, Guanting Dong, Haoran Wei, Huan Lin, Jialong Tang, Jialin Wang, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Ma, Jianxin Yang, Jin Xu, Jingren Zhou, Jinze Bai, Jinzheng He, Junyang Lin, Kai Dang, Keming Lu, Keqin Chen, Kexin Yang, Mei Li, Mingfeng Xue, Na Ni, Pei Zhang, Peng Wang, Ru Peng, Rui Men, Ruize Gao, Runji Lin, Shijie Wang, Shuai Bai, Sinan Tan, Tianhang Zhu, Tianhao Li, Tianyu Liu, Wenbin Ge, Xiaodong Deng, Xiaohuan Zhou, Xingzhang Ren, Xinyu Zhang, Xipin Wei, Xuancheng Ren, Xuejing Liu, Yang Fan, Yang Yao, Yichang Zhang, Yu Wan, Yunfei Chu, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, Zhifang Guo, and Zhihao Fan. Qwen2 technical report, 2024. URL https://arxiv.org/abs/2407.10671.
754 755	Yang Yao, Xin Wang, Zeyang Zhang, Yijian Qin, Ziwei Zhang, Xu Chu, Yuekui Yang, Wenwu Zhu, and Hong Mei. Exploring the potential of large language models in graph generation. <i>arXiv</i> preprint arXiv:2403.14358, 2024.

756 757 758 759	Y Yau, M Dadar, M Taylor, Y Zeighami, L K Fellows, P Cisek, and A Dagher. Neural Correlates of Evidence and Urgency During Human Perceptual Decision-Making in Dynamically Changing Conditions. <i>Cerebral Cortex</i> , 30(10):5471–5483, 06 2020. ISSN 1047-3211. doi: 10.1093/cercor/bhaa129. URL https://doi.org/10.1093/cercor/bhaa129.
760	
761	Minji Yoon, Yue Wu, John Palowitch, Bryan Perozzi, and Russ Salakhutdinov. Graph genera-
762	Conference on Machine Learning pp. 40175, 40108, 2022
763	Conference on Machine Learning, pp. 40175–40198, 2025.
764	Jiaxuan You, Rex Ying, Xiang Ren, William Hamilton, and Jure Leskovec. Graphrnn: Generating
765	realistic graphs with deep auto-regressive models. In International conference on machine learning,
766	pp. 5708–5717. PMLR, 2018.
767	Tao Zhou Jie Ren, Matúš Medo, and Yi-Cheng Zhang. Binartite network projection and personal
768	recommendation. <i>Physical Review E—Statistical</i> . <i>Nonlinear. and Soft Matter Physics</i> , 76(4):
769	046115, 2007.
770	
771	
772	
773	
774	
775	
776	
777	
778	
779	
780	
781	
782	
783	
784	
785	
780	
700	
700	
709	
790	
702	
703	
794	
795	
796	
797	
798	
799	
800	
801	
802	
803	
804	
805	
806	
807	
808	
809	

810 DETAILS OF GAG А 811

812 AGENT FORMULATION A.1 813

814 To demonstrate the versatility of the GAG Framework, we build three graph generation tasks for different human activities in our experiments, the concrete settings are as follows: (1) CA: In this 815 scenario, agents act as authors interacting with a paper database and generate the following networks: 816 Citation, Bibliographic Coupling (Bib-Coupling), Co-Citation, Author Citation, and Co-Authorship 817 networks (Garfield, 2000). (2) IA: In this scenario, agents act as reviewers interacting with both 818 online movie databases and offline movie databases and generate the following networks: the Movie 819 Rating and the User Projection networks (Zhou et al., 2007). (3) SA: In this scenario, agents act as 820 users interacting with a Twitter-like online social media database and generate the following networks: 821 Follow, Friend, and Action networks (De Domenico et al., 2013). 822

For agent construction, we use both real and LLM-craft data for agent profiles. Since the original 823 datasets lack certain node attributes (e.g., Citeseer is missing author information and article content), 824 we crawl for the necessary node attributes to enrich text attributes for Citeseer Sen et al. (2008). 825 In addition, we use handcraft instruction and COT (Wei et al., 2022) to guild LLM in generating 826 synthetic agent profiles. 827

For various simulation scenarios, we develop agents assigned distinct roles, including paper authors, 828 movie watchers, and Twitter users. These agents interact with an environment modeled on historical 829 interaction data. Specific details of the settings are provided in Table 7. 830

831 For the LLM backbone, we have chosen the open-source model of Llama-3-70BAI@Meta (2024) for 832 the large-scale graph generation in macro-level structure alignment and textual-attribute alignment 833 experiments. For micro-level structure alignment, we select the closed-source model of GPT-3.5-turbo for a more accurate simulation of human behaviors. Additionally, we select Reimers & Gurevych 834 $(2019)^{3}$ as the encoder in S-RAG. 835

Table 7: The Agent Settings and Interaction Data Types for Different Simulation Scenarios.

838					
839	Scenario	Agent Profile	Agent Role	Environment Data	Action Type
840 841 842	СА	Citeseer (Sen et al., 2008), Cora (Sen et al., 2008) LLM-Generated	Paper Author	Papers	Paper Writing
843 844	IA	Movielens (Harper et al., 2016), LLM-Generated	Movie Watcher	Movies	Movie Rating
845	SA	LLM-Generated	Twitter User	Tweets	Tweet Sending

A.2 PAIRWISE INTERACTION

State Planning In online social media, there is a significant difference in the influence of content shared by core users versus general users (Mislove et al., 2007; Mou et al., 2024). According to the Pareto distribution, core users should constitute approximately 20% of the total users in the current social network. We denote the agents labeled as *core* as *HUB*, as a result, the proportion of these agents is |HUB|/|V|. To investigate this, we adjust the proportion of agents labeled as *core*. Details in Appendix E.2.

856 Act with S-RAG We define the environment template T to transform each node in text-attributed graph into a natural language representation. For instance, in a citation network, graph nodes represent academic papers, whereas in a movie-rating network, they represent movies. This graph-to-text 858 transformation process leverages the node features and optionally considers edge features to enhance 859 the representation. To better illustrate this process, we present the environment template T for various 860 simulation scenarios below: 861

862

836

837

848 849

850

851

852

853

854

³https://huggingface.co/sentence-transformers/all-MiniLM-L6-v2



Node Feature (v_i, x_i) : Academic paper. Title: <Title> Topic: <Topic> Abstract: <Abstract> Author: <Author>. Edge Feature (E_i) : The citation papers of paper v_i .

Table 9: The environment prompt template of movies for RA

Node Feature (v_i, x_i) : Movie. Title: <Title> Genres: <Genres> Content: < Movie Abstract> Movie Rating: <Movie Rating> Edge Feature (E_i) : NULL.

Table 10: The environment prompt template of movies for SA

Node Feature (v_i, x_i) : Tweets. Tweet ID: <Tweet ID> User: <Tweet User> Tweet: <Tweet Content> Edge Feature (*E_i*): NULL.

To identify the most relevant information to a_l , we propose the S-RAG algorithm. For detailed explanation of the query process in S-RAG:

In the recall stage, we initially retrieve o_l^q as the candidate documents for a_l , which serves as the initial environmental feedback. This step we filter out N_r candidate documents.

In order to align o_i^q with agent's personal preference more accurately, we adopt the reranking stage for post-processing of o_l^q , which is divided into two phases: (1) Coarse Ranking: We reorder o_l^q based on whether the interaction data was generated by agents labeled as core. Candidate documents originating from *core* agents are positioned at the forefront of o_i^q , while those from non-core agents are placed towards the end. (2) Fine Ranking: We further reorganize o_i^{q} based on the personal preferences of the agents, as represented by p_l . For CA simulation, the filter items include topics of the academic papers; for RA simulation, the filter items include movie genres; and for SA simulation, the filter items include attributes of posted tweets, such as friends, topics, and follows. Ablation study on the filter items is detailed in Appendix. E.2.

Assuming we add k agents to the GAG framework per round and aim to ultimately include N agents, it would require $\frac{N}{k}$ simulation rounds. In the *j*-th round, the number of agents within GAG would be $N' = k \times j$. Without S-RAG, if we assume each of these N' agents needs to interact pairwise, the interaction number for one agent to interact with all others is O(N'). Thus, the total interaction number for N' agents interacting pairwise is $O(N'^2)$. Therefore, the total pairwise interaction number can be expressed as:

$$O(k^{2} + (2k)^{2} + \ldots + \left(\frac{N}{k}k\right)^{2}) = O(N^{3})$$



Figure 4: The cosine similarity between the embedding vectors of E and V, where V represents the embedding vectors of queries from different agents and E represents the embedding vectors of texts within the database.

As illustrated in Fig.4, the agents' queries are only relevant to a small subset of C, i.e. each agent interacts with only a limited number of other agents. S-RAG filters out a subset $\tilde{C} \subseteq C$ of agents, where $|\tilde{C}| = N_r$. Hence, the interaction number of one agent is reduced to $O(N_r)$, for N' agents to interact pairwise is $O(N' \times N_r)$. Consequently, the general interaction number in the whole simulation process is:

Thus, the incorporation of S-RAG significantly reduces the pairwise interaction number from $O(N^3)$ to $O(N^2)$ during the complete simulation process.

 $O(k \times N_r + 2k \times N_r + \ldots + \frac{N}{k}k \times N_r) = O(N^2)$

972 A.3 GRAPH EXTRACTION

974 In each simulation scenario, agents are exposed to different types of environmental information, 975 which subsequently influences their activities. Prompted by T_a , agents are instruct to generate textual 976 representations of graphs.

By employing reverse regular matching, we can extract the corresponding node and edge information. Depending on the specific simulation scenario, the Action Template T_a are defined as follows:

Table 11: The process of *Paper Writing* for a_l in CA

Environment Observation : Partial Environmental Feedback provided by S-RAG, as o_l . Abstract information for searched papers. Human Instruction : A papar should include the following attributes: title: The title should be concise yet descriptive, providing a clear indication of the topic and scope. This can be different from your topic, It is relatively accurate and c keywords: These are specific terms or phrases that encapsulate the core topics of you Keywords make your paper searchable within academic databases and help readers understand the paper's focus areas. abstract: The abstract is a brief summary of your research paper. It should pro-	Agent M	mory: <agent memory=""></agent>
as o_l . Abstract information for searched papers. Human Instruction : A papar should include the following attributes: title: The title should be concise yet descriptive, providing a clear indication of the topic and scope. This can be different from your topic, It is relatively accurate and c keywords: These are specific terms or phrases that encapsulate the core topics of you Keywords make your paper searchable within academic databases and help readers understand the paper's focus areas. abstract: The abstract is a brief summary of your research paper. It should pro-	Environ	ent Observation: Partial Environmental Feedback provided by S-RAG, den
Human Instruction : A papar should include the following attributes: title: The title should be concise yet descriptive, providing a clear indication of the topic and scope. This can be different from your topic, It is relatively accurate and c keywords: These are specific terms or phrases that encapsulate the core topics of you Keywords make your paper searchable within academic databases and help readers understand the paper's focus areas. abstract: The abstract is a brief summary of your research paper. It should pro	as o_l . Abs	ract information for searched papers.
title: The title should be concise yet descriptive, providing a clear indication of the topic and scope. This can be different from your topic, It is relatively accurate and c keywords: These are specific terms or phrases that encapsulate the core topics of you Keywords make your paper searchable within academic databases and help readers understand the paper's focus areas. abstract: The abstract is a brief summary of your research paper. It should pro	Human I	struction: A papar should include the following attributes:
abstract: The abstract is a brief summary of your research paper. It should pro	title: The topic and keywords Keywords understan	itle should be concise yet descriptive, providing a clear indication of the par cope. This can be different from your topic, It is relatively accurate and clear These are specific terms or phrases that encapsulate the core topics of your p make your paper searchable within academic databases and help readers qui I the paper's focus areas.
overview of the research question, methodology, results, and conclusions. citations: A list of the paper names you want to cite.	abstract: overview citations:	The abstract is a brief summary of your research paper. It should provide of the research question, methodology, results, and conclusions. A list of the paper names you want to cite.
Now write a version of your paper and cite the papers you need to cite.	Now writ	a version of your paper and cite the papers you need to cite.
	Kespond Node Fea	Example Example: Academic paper. Title, Keywords, Abstract.

Table 12: The process of Movie Rating in IA

Act	ion Template (T_a)
Age	ent Profile: <agent profile=""></agent>
Age	ent Memory: <agent memory=""></agent>
Env	vironment Observation: Partial Environmental Feedback provided by S-RAG, denote
as c	y. Abstract information for searched movies.
Hu	man Instruction: You should give your rating scores to the movies
D oc	nond Evampla
Res	pond Example
Res Noc	pond Example le Features: NULL.

In various simulation scenarios, we progressively enrich the set C and subsequently extract different graph structures from it. This results in the mapping functions $g_v : C \to \mathcal{V}, g_e : C \to \mathcal{E}$, and $g_x : C \to \mathcal{X}$.

¹⁰²⁴ In the context of CA, following action template T_a defined in Table 11, each time the agent generates 1025 a paper. The LLM-based agents act as authors and C stores the papers. To fold graphs from the pair-wise interaction process, we define the following mapping functions:

	Table 13: The process of Tweet Sending in SA
	Action Template (T_a) Agent Profile: <agent profile=""> Agent Memory: <agent memory=""> Environment Observation: Partial Environmental Feedback provided by S-RAG, denoted as o_l. Abstract information for searched tweets. Human Instruction: You can perform [Retweet/Reply/Tweet] action on these tweets. Additionally, you can follow the bloggers of these tweets: Retweet: Retweet the tweet Reply: Reply to the tweet Tweet: Send a tweet </agent></agent>
	Respond Example Node Features: Tweets. Tweet contents. Tweet Topics. Edge Features: Actions to other tweets (retweet, reply, follow).
	 Citation Network: Let V represent the set of papers, E denote the citation relationships between papers, and X signify the attributes of each paper.
	2. Bib Coupling: Let V represent the set of papers, E represents the relationships where two papers cite the same reference, and X encompasses the attributes of the papers.
	3. Co-citation: Let V represent the set of papers, E indicates the relationships where two papers are cited by the same paper, and X includes the attributes of the respective papers.
	 Author Citation: Let V represent the set of authors, E depicts the citation relationships among authors, and X refers to the attributes of each author.
	5. Co-Authorship: Let V represent the set of authors, E illustrates the collaborative relation ships between authors, and X characterizes the attributes of each author.
In a n gra	the context of RA, following action template T_a defined in Table 12, each time the agent generates novie rating. The LLM-based agents act as movie watchers and C stores the movies. To fold phs from the pair-wise interaction process, we define the following mapping functions:
	1. Movie Rating: Let V represent the watchers and the movies, E denote the movie ratings For movie watchers, X correspond to the attributes of movie watchers; for movies, X correspond to the attributes of movies.
	2. User Projection: In this setup, V consists of movie watchers, E refers to the number of movies rated jointly by two movie watchers, and X encompasses the attributes of the movie watchers.
In a ty pai	the context of RA, following action template T_a defined in Table 13, each time the agent generates weet. The LLM-based agents act as tweet users and C stores the tweets. To fold graphs from the r-wise interaction process, we define the following mapping functions:
	1. Action: Let V represent users, E denote the edges indicating tweets exchanged between two users, and X represent user attributes.
	 Follow: Let V represent users, E denote the edges indicating tweets that establish a follow relationship between two users, and X represent user attributes.
	3. Friend: Let V represent users, E denote the edges indicating tweets that establish a friend relationship between two users, and X represent user attributes.

1080 A.4 PARALLEL ACCELERATION

In order to further speed up the simulation process of GAG, we propose a Nested ACTOR Parallel
Processing Schema for Agents (N-ACTOR) based on traditional ACTOR architecture (Hewitt et al., 1973). (Clauset et al., 2004) highlights that network structure often exhibits tightly connected communities with loose inter-community connections, so we decompose the agents into different groups and run them in parallel.

Algo	rithm 2 Nested ACTOR Parallel Processing Schema for Agents
Req	uire: $a_l \in \{a_1, a_2,, a_N\}$, Batch size B
1:]	Initialization:
2: 9	$g \leftarrow a_l,$
3:]	INITIALIZE message queues M^g for g ,
4:]	Number of batches $K = \left\lceil \frac{N}{B} \right\rceil$,
5: 3	$s_k \leftarrow \bigcup_{b=1}^B g_{kb} \text{for } k \in \{1, \dots, K\},$
6: I	INITIALIZE message queues M_k^s for s_k ,
7: l	Message Handling:
8: f	for each supervisor actor s in parallel do
9:	for each general actor g_{kb} under s_k in parallel do
10:	Process messages in M^g ,
11:	Update state of g_{kb} ,
12:	Send messages to other general actors g_{kb} via M^g ,
13:	end for
14:	Process messages in M^s ,
15:	Update state of s,
16:	Send messages to other supervisor actor via M^s ,
17: 0	end for

1107 1108

N-ACTOR Architecture The objective of N-ACTOR is to divide N agents into $\frac{N}{B}$ batches of size 1109 B, allowing for parallel execution between batches. As illustrated in Algorithm 2, the process includes 1110 two steps: (1) Initialization: Following ACTOR, we define actor as the instantiated encapsulation 1111 of an agent. To facilitate batch parallelization of agents, we introduce two types of actors: general 1112 actor, denoted as $g \in G$, and supervisor actor, denoted as $s \in S$. Different actors leverage different 1113 CPU cores of the computational machine. Let P denote the number of ports. Each supervisor actor 1114 s manages B number of g, thus $|S| = \frac{N}{B}$. (2) Message Handling: Traditional ACTOR employs a 1115 message queue for agents' execution of message processing, state updating, and message sending in parallel. (Clauset et al., 2004) highlights that network structure often exhibits tightly connected 1116 communities with loose inter-community connections, N-ACTOR introduces two levels of parallel 1117 message processing: Within each batch, s can perform parallel message processing through M^s ; 1118 Between different batches, g first aggregates messages for all g within the batch and performs inter-1119 batch parallel message processing through M^g . As shown in Figure 5, g only needs to wait for the 1120 IO time of B general actors instead of N. 1121

1122

1124 1125

1133

1123 B

B.1 GRAPH STRUCTURE METRICS

1126 1127 To measure the structural characteristics of graph, we use the following structural metrics:

EVALUATION OF STRUCTURE ALIGNMENT

(1) $|\mathcal{V}|$: measures the node number of graph G.

(2) $|\mathcal{E}|$: measures the edge number of graph *G*.

1131 (3) \bar{cc} : average clustering coefficient, quantifies the degree to which nodes in a graph tend to cluster 1132 together ⁴.

⁴https://en.wikipedia.org/wiki/Clustering_coefficient.



1161 the top 10 ratings for each user and discover a noteworthy phenomenon: the number of reviews 1162 in the rating network exhibits periodic fluctuations over time. By scraping the release dates of the movies and plotting their release frequency, we observe that the periodicity in the release frequency is 1163 consistent with the fluctuations in the number of reviews. To quantify the periodicity, we selected the 1164 signal-to-noise ratio (SNR) (Johnson, 2006) as our metric, considering an SNR greater than 10 dB to 1165 indicate strong periodicity and reliability. Furthermore, we observe that the degree of the generated 1166 rating graph also exhibits periodic variations consistent with the release dates of the movies. As 1167 illustrated in Figure 6, the SNR of the degree of the rating graph is 12.79 dB, surpassing the 10 dB 1168 threshold, thus demonstrating significant periodic fluctuations. 1169

1170

1171

Emergent of GCC In online social networks, nodes with higher degrees grow larger over time and eventually manifest a giant connected component (GCC) (Mislove et al., 2007). As illustrated in Figure 7, the proportion of the largest connected component rows steadily over time, indicating the emergence of a giant community within the social network. The network is generated by with 7000 agents.

- 1176
- 1177 1178

Friendship Paradox An interesting and somewhat counterintuitive phenomenon in real-world social networks is that everyone you follow or who follows you tends to have more friends and followers than you do. This phenomenon has been observed in both Twitter (Hodas et al., 2013) and the social network of Facebook (Ugander et al., 2011), applying to more than 98% of the nodes. As shown in Figure 8, the friendship paradox is most evident in the friend network, with over 90% of the nodes lying above the y = x line, indicating that most users have fewer friends than their friends do. The network is generated by 5 rounds of simulation with 1e5 agents.

- 1185
- 1186

¹¹⁸⁷

⁵https://en.wikipedia.org/wiki/Assortativity



Figure 6: Periodic Variation of Degree in Movie Rating Network; Figure 6a shows the number of released movies over time and the degree of the movie rating network over time in MovieLens dataset;
Figure 6b also shows the number of released movies and the degree of the movie rating network over time in GAG.



Figure 7: The proportion of the largest connected component grows steadily over time.



Figure 8: The *Friendship Paradox* phenomenon in online social networks; The figures show the average degree of node neighbors v.s. the average degree of node itself in social networks.



Figure 9: The stucture of the DCC in follow network. Figure 9b plots the out-degree against $\bar{c}c$; Figure 9a shows D_e of the DCC in follow network, the network is divided by the fractions of the total number of nodes.

1252

1253 1254

1273 **Densely Connected Core** In real-world online social networks, there exists a densely connected 1274 core (DCC) comprising between 1% and 10% of the highest degree nodes, such that removing this 1275 core completely disconnects the graph (Mislove et al., 2007). These high-degree nodes serve as hubs 1276 of the network, causing the network to become increasingly compact through the hub structure. As 1277 shown in Figure 9b, the nodes with higher degrees have significantly higher $c\bar{c}$ compared to other 1278 nodes. For these densely connected components, D_e grows at a slow rate. In Figure 9a, we observe that the D_e among the DCC of follow network is grows sublognitively. The network is generated by 1279 5 rounds of simulation with 1e5 agents. 1280

- 1281
- 1282 B.3 MICRO-LEVEL EVALUATION 1283

Evaluation Metrics In accordance with established evaluation metrics for graph generation Bergmeister et al. (2024), we report the maximum mean discrepancy (MMD) between the generated graphs and the test graphs, specifically focusing on degree distribution and clustering coefficient. Furthermore, we place particular emphasis on evaluating whether the degree distribution of the generated graphs conforms to a power law after expanding the graph to out-of-distribution sizes Clauset et al. (2009). To this end, we employ six key metrics in all:

(1) MMD.D: maximum mean discrepancy (MMD) of degree distribution between the generated graphs and the test graphs.

(2) MMD.C: maximum mean discrepancy (MMD) of clustering coefficient between the generated graphs and the test graphs.

(3) MMD.S: maximum mean discrepancy (MMD) of spectrum between the generated graphs and the test graphs Liao et al. (2019).

(4) MMD.O: maximum mean discrepancy (MMD) of node orbit counts between the generated graphs and the test graphs You et al. (2018).

(5) α : The power-law exponent of the graph degree distribution.

(6) D_k : The Kolmogorov-Smirnov distance between the degree distributions of the generated and test graphs.

1302 1303 1304 1304 1305 (7) Valid: Research demonstrates that degree distributions in complex networks are typically characterized by a power-law exponent $\alpha \in [2, 3]$ (Clauset et al., 2009). Accordingly, we define the validity measure for a graph as the proportion of graphs meeting the criteria $D_k < 0.1$ and $\alpha \in [2, 3]$. Set $k_{\min} = 2$ for the uniform calculation of the power-law fitness of both undirected and directed graphs.

(8) **GEM:** To quantify the level of structural alignment for the expanded graph, we establish the Graph Expansion Metric (GEM). Firstly, for the negative indicator MMD metrics, we utilize the transformation $1 - \frac{1}{1 + e^{metric}}$, which maps the metrics to a range between 0 and 1. We then calculate the average of MMD and Valid metrics as GEM.

- 1310
- 1311 1312

Experiment Settings Specifically, we sample a network dataset based on publication timelines to create our evaluation dataset. Since we only crawl for timestamp information of the CiteSeer and Cora datasets, these two datasets are used for our experimental evaluation. Following the timeline of graph evolution, we partition the network dataset into training and testing sets.

At a designated time point t, we filter the citation network using node timestamp information to obtain $G_{< t}$, which includes all nodes and edges prior to t. We sample small subgraphs from $G_{< t}$ to create a training set for deep learning methods and to generate the seed graph for GAG. The training set consists of sampled subgraphs with sizes ranging from 64 to 512 nodes, resulting in a train set comprising 160 subgraphs and validation sets comprising 32 subgraphs. For the test set, we filter the citation network for nodes and edges after t, denoted as $G_{>t}$. From $G_{>t}$, we sample large subgraphs of 1,000 nodes, resulting in a test set comprising 20 subgraphs.

The existing graph generation methods have demonstrated promising results in generating small 1324 graphs, including works such as Vignac et al. (2023), Martinkus et al. (2022), and You et al. (2018). 1325 However, they have not explored the generation of out-of-distribution graph sizes, and the generated 1326 graph sizes are limited. To compare with traditional graph generation models, we need to select those 1327 methods that can expand beyond the training set graph sizes and efficiently generate large graphs. For 1328 rule-based graph generation methods, we set hyperparameters to ensure that the average degree of the expanded graph matches that of the seed graph. For deep learning-based graph generation methods, 1330 we adhere to the hyperparameters specified in the original papers. All hyperparameter details are provided in Table 14. 1331

- 1332
- 1333

Ablation on Seed Graph Size GAG distinguishes itself from traditional graph generation methods
 by generating graph data without requiring prior training. It achieves this through the simulation of
 human behavior, leading to the emergence of various structural features characteristic of real-world
 networks. Consequently, conventional graph evaluation methods cannot be applied. To address this,
 we design comparative experiments against existing graph generation models.

For this purpose, we select the Citeseer network as the seed graph and the training graph dataset for existing methods. We expand it to generate 20 distinct graphs with an additional 1000 nodes. We subsequently compare the structural metrics of these expanded graphs to those of subgraphs sampled from the Citeseer network of equivalent size. Specifically, we focus on whether the expanded graph structure exhibit power law characteristics typical of real-world network structures.

1344 Additionally, we aim to investigate whether the size of the seed graph affects the validity of the final 1345 generated graph structure. To this end, we utilize the GAG to perform graph expansion on seed graphs 1346 of varying sizes. We plot the number of nodes in the expanded graphs against the corresponding 1347 values of α . As shown in Figure 10, it is evident that larger seed graphs result in expanded graphs 1348 exhibiting higher values of α . Furthermore, as the size of the expanded graphs increases, the α values 1349 gradually stabilize. This indicates that the GAG is capable of effectively and reasonably expanding 1349 graphs across different seed graph sizes.

Model	Hyperparameter	Experiment
Erdös-Rényi (Erdos et al., 1960)	Linking propoblity	$\bar{k}/(\mathcal{V} -1)$
Barabási-Albert (Barabási & Albert, 1999)	Number of linking edges	$ar{k}/2$
Small-World (Watts & Strogatz, 1998)	Number of linking nodes	$ar{k} imes 2$
BiGG (Dai et al., 2020)	Ordering Accumulated gradients Batch size	DFS 1 32
GRAN (Liao et al., 2019)	Hidden size Embedding size Number of layers Number of mixtures Batch size	512 512 7 20 16
BwR (Diamant et al., 2023)	Model bw Hidden size Ordering Batch size	GraphRNN (You et al., 2018) 8 128 BFS 32
L-PPGN (Bergmeister et al., 2024)	Hidden embedding size PPGN embedding size Input embedding size Number of layers Number of denoising steps Batch size EMA coefficient Number of spectral features	256 128 32 10 1024 32 0.99 0
GraphMaker (Li et al., 2024a)	Variant Hidden size for timestep Hidden size for node Hidden size for node label NumberofMPNNlayers Learning rate Optimizer	Sync 32 512 64 2 0.001 AMSGrad

Table 14: Training hyperparameters of baseline models. All unspecified hyperparameters default to their standard values.





Figure 10: We present the results for seed graph sizes of 100, 445, and 2840, with the sizes of the expanded graphs plotted against their corresponding α values. Note that we only plot valid data $D_k < 0.1.$

Supplementary Experiments To further demonstrate the reliability of the GAG framework, in addition to supplementing data from CiteSeer, we crawl for the necessary node attributes to enrich text attributes for Cora Sen et al. (2008). Following the experimental setup outlined in the paper, we designate Cora as the Seed Network and similarly compared it with existing graph generation models.

1409Table 15: Comparison with existing expansion-based graph generation models. For GRAN, generated1410graph degree distribution fails to converge when fitting a power-law distribution.

	$\text{MMD.D}{\downarrow}$	$MMD.C{\downarrow}$	$\text{MMD.S}{\downarrow}$	$\text{MMD.O}{\downarrow}$	D_k	α	Valid↑	GEM
Cora	-	-	-	-	$0.07_{\pm 0.0}$	$2.59_{\pm 0.01}$	1.00	-
Erdös-Rényi	0.25	1.41	0.54	0.27	$0.13_{\pm 0.02}$	$4.01_{\pm 0.17}$	0.00	0.29
Barabási-Albert	0.09	1.41	0.44	1.11	$0.04_{\pm 0.01}$	$2.4_{\pm 0.05}$	1.00	0.46
Small-World	0.60	1.41	0.50	0.20	$0.14_{\pm 0.0}$	4.05 ± 0.02	0.00	0.28
BiGG	0.14	0.51	0.48	0.27	$0.08_{\pm 0.01}$	$3.19_{\pm 0.11}$	0.05	0.34
GRAN	0.15	0.50	0.55	0.28	-	-	0.35	0.40
BwR	0.32	0.23	0.34	0.19	$0.1_{\pm 0.01}$	$3.58_{\pm 0.08}$	0.00	0.35
GraphMaker	0.37	1.41	0.75	0.28	-	-	0.00	0.27
L-PPGN	0.15	0.92	0.32	0.59	0.06 ± 0.01	$2.77_{\pm 0.04}$	1.00	0.50
GAG	0.35	0.84	0.41	1.21	$0.09_{\pm 0.0}$	$2.1_{\pm 0.01}$	1.00	0.47

1422

1411

As shown in Table 15, the expanded graphs generated by GAG adhere to a power-law distribution, 1423 with $\alpha = 2.1$. For MMD metrics, since GAG doesn't strictly enforce explicit graph structure 1424 constraints on the agents, its performance is not significantly better than other models, but it achieves 1425 comparable results. For the Valid metric, apart from GAG and the Barabási-Albert Model, the only 1426 existing deep-learning graph generation model capable of capturing the power-law distribution is 1427 L-PPGN. This demonstrates that L-PPGN is indeed capable of extrapolating to out-of-distribution 1428 graphs when trained on graphs that encompass the power-law distribution property. However, the 1429 unstable performance of L-PPGN across different datasets also highlights its sensitivity to the quality 1430 of the training dataset. In contrast, GAG, through human behavior simulation, can reliably generate 1431 graph structures that adhere to real-world network characteristics from seed graph of varying sizes and quality. This illustrates not only the potential of LLM-based Agents in simulating human behavior 1432 but also underscores the reliability of the GAG framework. 1433

1434 1435

1436

C EVALUATION OF TEXTUAL-ATTRIBUTE ALIGNMENT

1437 C.1 EXPERIMENT SETTINGS

We configure the complete Citeseer graph as G and expand it to G' with 5000 nodes. The processes involved are as follows:

(1) **F.shuffle:** This process randomly selects node-wise textual features from G to create the node features of G'.

(2) S.shuffle: In this step, we randomly redefine the edges of G', thereby disrupting the graph structure while maintaining the number of edges consistent with \mathcal{V}' .

(3) **SF.shuffle:** This refers to a combination of both F.shuffle and S.shuffle.

(4) BWR+LLM: Graph structure generated by Diamant et al. (2023). We give the LLM Citeseer as corpus and use it to generate textual features.

(5) L-PPGN+LLM: Graph structure generated by Bergmeister et al. (2024). We give the LLM Citeseer as corpus and use it to generate textual features.

(6) BiGG+LLM: Graph structure generated by Dai et al. (2020). We give the LLM Citeseer as corpus and use it to generate textual features.

1454
 1455
 1456
 (7) BiGG+LLM: Graph structure generated by Dai et al. (2020). We give the LLM Citeseer as corpus and use it to generate textual features.

1457 (8) GraphMaker+LLM: Graph structure generated by Li et al. (2024a). We give the LLM Citeseer as corpus and use it to generate textual features.

(9) GAG: Graphs that are generated by the GAG framework.

C.2 ABLATION STUDY OF LLM

To further illustrate the effectiveness of the generated graphs, we conduct an ablation study on the LLM for agent setup. We select four LLMs for this study: GPT-3.5-turbo, GPT-4o-mini OpenAI (2023) as top-ranking closed-source LLMs, and Llama-3-70BAI@Meta (2024) and Qwen2-72BYang et al. (2024) as top-ranking open-source LLMs.

Table 16: Ablation Study of LLM in GAG. Performance Comparison for Node Classification

			$\Delta ACC\downarrow$				
GNN	LLM	SF.random	F.random	S.random	GAG		
GAT	LLAMA.	$13.40_{\pm 3.52}$	$24.11_{\pm 2.84}$	$18.85_{\pm 2.55}$	2.26 ±1.19		
	GPT-3.	$12.30_{\pm 2.47}$	$22.24_{\pm 2.86}$	$16.69_{\pm 2.46}$	$2.29_{\pm 1.84}$		
	GPT-4o.	$12.03_{\pm 1.17}$	$21.73_{\pm 2.91}$	$15.57_{\pm 2.84}$	$2.80_{\pm 0.88}$		
	Qwen2.	$11.12_{\pm 2.53}$	$15.84_{\pm 3.34}$	$24.51_{\pm 2.28}$	$10.50_{\pm 1.94}$		
GCN	LLAMA.	$15.04_{\pm 1.99}$	$23.20_{\pm 2.25}$	$21.77_{\pm 2.04}$	$3.61_{\pm 1.32}$		
	GPT-3.	$13.55_{\pm 2.19}$	23.08 ± 1.39	$20.58_{\pm 1.44}$	$4.34_{\pm 2.01}$		
	GPT-4o.	14.56 ± 1.84	$22.07_{\pm 2.25}$	$20.82_{\pm 2.45}$	$4.09_{\pm 1.75}$		
	Qwen2.	12.56 ± 1.65	$15.37_{\pm 2.69}$	$26.95_{\pm 2.16}$	$10.05_{\pm 1.87}$		
GCN2	LLAMA.	$9.58_{\pm 0.88}$	$9.33_{\pm 1.36}$	$2.24_{\pm 1.58}$	$0.49_{\pm 1.50}$		
	GPT-3.	$9.07_{\pm 1.10}$	$9.04_{\pm 1.80}$	$1.43_{\pm 1.67}$	$0.39_{\pm 1.67}$		
	GPT-40.	$8.89_{\pm 1.44}$	$9.64_{\pm 1.10}$	$1.19_{\pm 1.64}$	$0.50_{\pm 1.36}$		
	Qwen2.	$9.78_{\pm 1.48}$	9.19 $_{\pm 1.44}$	$11.40_{\pm 1.78}$	$9.39_{\pm 0.93}$		
GraphSage	LLAMA.	$7.00_{\pm 0.92}$	$7.13_{\pm 1.73}$	$3.15_{\pm 1.84}$	$0.09_{\pm 1.74}$		
	GPT-3.	$6.72_{\pm 1.41}$	$6.39_{\pm 0.92}$	$2.35_{\pm 1.60}$	$0.81_{\pm 1.67}$		
	GPT-4o.	$6.97_{\pm 0.92}$	$6.46_{\pm 1.61}$	$2.05_{\pm 2.31}$	$1.70_{\pm 2.28}$		
	Qwen2.	$6.45_{\pm 1.33}$	$7.14_{\pm 1.68}$	$12.73_{\pm 2.26}$	$9.72_{\pm 2.43}$		

As shown in Table 16, the LLM-based agents built on LLaMA2, GPT-3.5-turbo, and GPT-4o-mini are capable of generating networks that maintain the node and structural characteristics of the seed graph, thus ensuring effective performance transfer in downstream tasks. In contrast, Qwen-2 based agents do not guarantee performance transfer. We believe this is related to the ability of LLMs to emulate human behavior; Qwen-2 based agents fail to exhibit human-like creative behavior, resulting in less coherent generated graphs.

SCALABILITY OF GAG D

To further demonstrate the excellent scalability of the GAG framework, we conduct time measure-ments across various simulation scenarios. The tests are carried out on a computing machine equipped with 96 CPU cores and 376 GB of memory. For model inference, we utilized LLAMA-3-70B as the backbone LLM and employed the vLLM framework Kwon et al. (2023), running on a setup of four A-800 GPUs.

Table 17: The time cost (hour) of agents for one round of simulation.

1503		_		
1504		N	Р	Т
1505				
1506	CA	5.01e+03	10	0.46h
1500	RA	3.91e+03	10	0.30h
1507	S A	0 07e±04	48	11h
1508	57	7.776+0+	-0	1111

In accordance with the scalability results detailed in Section??, we carry out CA simulation experi-ments for 200 rounds, RA simulation experiments for 33 rounds, and SA simulation experiments for 10 rounds. For each scenario, we measured the total simulation time and computed the average

simulation time per round. These multi-round simulations provide a robust measure of the computasimulation time per round. These multi-round simulations provide a robust measure of the computational efficiency of the GAG framework. The results, summarized in Table 17, demonstrate GAG's
capability to handle simulations with varying scales of agents. For simulation experiments with
Thousands of agents, the average simulation time per round is 0.46 hours for CA experiments and
0.30 hours for RA experiments; For simulation experiments with Hundreds of thousands of agents,
the average simulation time per round is 11 hours for SA.

1518

¹⁵¹⁹ E ABLATION STUDY OF S-RAG

1520

1535

To investigate whether the hyperparameter settings of S-RAG affect the generated network structure.
 We conduct ablation experiments on these hyperparameters. Given the variations in graph generation scenarios, we conduct the ablation experiments under the SA simulation. We run equal number of simulation rounds within the GAG to generate graphs.

In this section, we add a graph structure metric for measuring the proportion of the largest connect component within the network. We define the largest connect component of graph as LCC, so the proportion of LCC within the network is |LCC|/|V|. This aids us in comprehending the graph evolution progress.

1530 E.1 RECALL STAGE

In recall stage, the only hyperparameter is the number of searched items: N_r . Since the final number of documents interacting with the LLM is limited to N_r , we change N_r and evaluate its impact on network structure.

Table 18: Ablation Study of N_r . The value of N_r is proportional to \bar{k} of the generated network.

Network	N_r	$ \mathcal{V} $	$ \mathcal{E} $	$\bar{c}c$	r	LCC / V
	3	9.47e+02	1.92e+03	0.07	0.10	0.03
Astion	5	9.36e+02	2.20e+03	0.09	-0.05	0.02
Action	10	9.58e+02	2.63e+03	0.09	0.02	0.05
	20	1.03e+03	3.03e+03	0.11	-0.08	0.16
	3	7.42e+02	1.27e+04	0.83	-0.08	0.29
Follow	5	7.39e+02	1.24e+04	0.81	-0.06	0.44
FUIIOW	10	7.39e+02	1.29e+04	0.80	-0.06	0.51
	20	8.91e+02	3.83e+04	0.82	-0.18	1.00
	3	7.42e+02	5.96e+03	0.88	-0.13	0.25
Friand	5	7.39e+02	5.76e+03	0.87	-0.10	0.22
rnena	10	7.39e+02	5.94e+03	0.89	-0.10	0.24
	20	8.91e+02	1.83e+04	0.87	-0.10	0.45

1551 1552 1553

As shown in Table 18, we keep all other search parameters constant while varying the size of N_r . It can be observed that as N_r increases, \bar{k} of generated network also exhibits an upward trend. This trend is particularly pronounced in the follow network.

1557

1558 E.2 RERANKING STAGE

To maximum the effectiveness of searched items, we implement the ReRanking stage in S-RAG. Initially, coarse ranking is performed to sort the searched items by their creator agent. Focusing on the *core* lable of creator. Subsequently, fine ranking is conducted based on the agent's individual preferences. We conduct an ablation study to explore the impact of different levels of personalization in ReRanking stage. And eventually its impact on the network structure.

We focus on the hyperparameters in the ReRanking stage, which mainly include: (1) Hub rate: |HUB|/|V|. (2) Attributes of a_l .

Network	HUB / V	$\mid \mid \mathcal{V} \mid$	$ \mathcal{E} $	\bar{cc}	r	LCC / V
	0.00	9.78e+02	2.64e+03	0.09	-0.05	0.13
Action	0.10	1.02e+03	2.58e+03	0.09	-0.07	0.10
	0.20	1.03e+03	3.03e+03	0.11	-0.08	0.16
	0.00	7.79e+02	3.00e+04	0.84	0.02	0.63
Follow	0.10	7.82e+02	3.04e+04	0.84	0.05	0.63
	0.20	8.91e+02	3.83e+04	0.82	-0.18	1.00
	0.00	7.79e+02	1.45e+04	0.89	0.21	0.27
Friend	0.10	7.82e+02	1.47e+04	0.88	0.29	0.43
	0.20	8.91e+02	1.83e+04	0.87	-0.10	0.45

Table 19: Ablation Study of the hub rate (|HUB|/|V|). Higher hub rate contributes to the emergence of a large connected component.

Coarse Ranking As shown in Table 19, an increase in the proportion of core users correlates with an upward trend in the proportion of the largest connected component within the network. Since the proportion of core users is increased, the likelihood of core users being searchable by general users is also increased, thereby fostering preferential attachment in the network. eventually, the proportion of the largest connected component within the network is increased.

Fine Ranking To improving search algorithms based on personal preferences of agents, we design various filter items in fine ranking process, which are tailored to different simulation scenarios. The number of filter items is N_f . Within the SA simulation, filter items include: (1) Follow: Determines whether the content of the document is posted by an agent that the current agent follows. (2) Friend: Identifies whether the content of the document is was sent by an agent that is a friend of the current agent. (3) Topic: Assesses whether the content of the document is related to a topic that the current agent is interested in.

As illustrated in Table 20, \bar{cc} of network increases as N_f increases. Additionally, the impact level of different filter items is as follows: friend > topic > follow.

Table 20: Ablation Study of the fillter items used in fine ranking process.

	Fi	llter Iter	ns	Network Structural Characteristics				
Network	follow	topic	friend	$ \mathcal{V} $	$ \mathcal{E} $	\bar{cc}	r	LCC / V
	1	-	-	6.51e+02	1.88e+03	0.11	0.01	0.19
Action	-	1	-	6.32e+02	1.82e+03	0.09	-0.01	0.15
Action	-	-	1	1.02e+03	2.78e+03	0.09	-0.05	0.12
	1	1	1	1.03e+03	3.03e+03	0.11	-0.08	0.16
	\checkmark	-	-	6.51e+02	2.65e+04	0.78	-0.19	0.92
Follow	-	1	-	5.63e+02	2.03e+04	0.79	0.16	0.64
FOIIOW	-	-	\checkmark	7.70e+02	2.97e+04	0.84	0.19	0.69
	1	1	1	8.91e+02	3.83e+04	0.82	-0.18	1.00
	\checkmark	-	-	6.51e+02	1.26e+04	0.83	-0.13	0.46
Friend	-	\checkmark	-	5.63e+02	9.74e+03	0.83	0.52	0.28
	-	-	\checkmark	7.70e+02	1.44e+04	0.89	0.21	0.31
	\checkmark	1	1	8.91e+02	1.83e+04	0.87	-0.10	0.45

interpretable understanding of the network evolution process.

1620 CASE STUDY F 1621

1622

1623

1624

1625 1626

1627

1628

1629

1633

1635

1637

1639 1640

1641

2. Search Paper Paper 1: About Social Reasoning 1. Draft Paper Paper 2: About AI, Paper 3: About Social, 1000 cites Title: AI for Social... Keywords: AI, Social Reasoning, Paper 10: About GNN Abstract: This paper aims to investigate how artificial intelligence technologies influence social reasoning and decision-making 3. Cite Paper processes... Citations: Citations: None Paper 1, Paper 2, Paper 3 Reason: Paper 1, 2 is more relevant to my research.., while Paper 3 is a highlycited paper...

Since GAG employs human behavior simulation for network generation, the process of connecting

each network node to others closely mirrors real-world scenarios. This alignment enables a clear and

Figure 11: An illustration of the citation network evolution with LLM-based Agents.

1642 To demonstrate the interpretability of our graph generation method, we present a case study using the 1643 CA simulation scenario. As illustrated in Figure 11, the formation of a citation network involves three 1644 primary steps. First, LLM-based agents collaboratively generate a paper draft through interaction and 1645 cooperation. Next, the agents search the corpus of stored papers within the environment to identify 1646 literature relevant to their research interests. For instance, query terms may correspond to research 1647 domains such as AI or social sciences.

1648 Finally, after completing the search, the agents select and cite papers pertinent to their draft, providing 1649 explicit justifications for each citation. As illustrated in Figure 11, examples of such justifications 1650 include citing a paper due to its high citation count or its direct relevance to the research topic. 1651 Each citation edge in the network thus directly corresponds to an agent's citation action, offering a 1652 behavior-driven perspective on the graph construction process. This approach ensures that the graph 1653 generation process is inherently interpretable.

1654 1655

1656

HUMAN INTERFACE CONTROL G

1657 Previous work on employing LLMs for graph generation typically relied on predefined network 1658 structure features or a set of example networks Yao et al. (2024). Similarly, after understanding the 1659 reasons behind different structural characteristics of networks within GAG, we aim to enable users to control the entire simulation process by inputting prompts. This will guide and influence the various 1661 structural features of the final network.

1662 To achieve this, we establish a control agent that accepts instruction frm users. Control agent transfers 1663 the instruction to a control profile for managing the simulation process of GAG. 1664

As shown in Fig. 12, specifically, the hub rate controls the proportion of recommended core users, 1665 subsequently affecting the ratio of hub nodes in the network. The parameter N_r determines the 1666 number of items recommended by the system, influencing the overall degree distribution. Additionally, 1667 parameter N_f dictate the number of filter items in the ReRanking stage, impacting the network's 1668 clustering coefficient. Furthermore, the overall simulation time is adjusted by the number of agents 1669 N per simulation round. 1670

- 1671
- 1672
- 1673



1728 1729 1730 1731 1732	Table 21: The prompt template of generating agent profiles for <i>CA</i>
1733 1733 1734 1735 1736 1737 1738 1739 1740 1741 1742 1743 1744 1745 1746 1747 1748 1749 1750 1751 1752 1753 1754 1755 1756 1757 1758 1760 1761 1762	I would like you to generate a series of random author's personal information. These authors are interested in computer science, they are experts in various fields of CS. I need you to give a list of author infos with the constraints for each attribute as follows: (1) Name: Author's name (2) Expertises: a list, The author's areas of expertises can be selected from the following areas:{expertises list} (3) Institution: The author's institution, you can choose whatever institution you want, just give me one institution name (4) Country: The author's country, you can choose whatever institution you want, just give me one country name corresponding to the institution (5) Topics: a list, The topics this author is interested in, can be selected from the following topics:{topics list} Here's some common used countrys you can infer to: {countrys} Please generate me a list of {author num} different authors, which can be loaded by eval function in python: [{{ "name":"", "country:"", "co
1763 1764 1765 1766 1767 1768 1769 1770	Table 22: The prompt template of generating agent profiles for <i>IA</i>
1771 1772 1773 1774 1775 1776 1777 1778 1779 1780	Your task is to give me a list of watcher's profiles. Respond in this format: [{ "gender": (F/M) "age":(the age of the watcher) "job":(the job of the watcher) }] Respond: Now please generate:

Table 23: The prompt template of generating agent profiles for SA Your task is to give me a list of {num added} person's profiles for twitter users . Respond in this format: [{{ "user name": "(str;The name of this user)", "user description": "(str;short and concise, a general description of this user, ordinary users or super large users and the topics this person interested in)" }}] Now please generate: