MAGICDEC: BREAKING THE LATENCY-THROUGHPUT TRADEOFF FOR LONG CONTEXT GENERATION WITH SPECULATIVE DECODING

Anonymous authors

006

008 009 010

011

013

014

015

016

017

018

019

021

023

025

026

027

028 029

031

Paper under double-blind review

Abstract

Large Language Models (LLMs) have become more prevalent in long-context applications such as interactive chatbots, document analysis, and agent workflows, but it is challenging to serve long-context requests with low latency and high throughput. Speculative decoding (SD) is a widely used technique to reduce latency losslessly, but the conventional wisdom suggests that its efficacy is limited to small batch sizes. In **MagicDec**, we show that surprisingly SD can achieve speedup even for a high throughput inference regime for moderate to long sequences. More interestingly, an intelligent drafting strategy can achieve better speedup with increasing batch size based on our rigorous analysis. MagicDec first identifies the bottleneck shifts with increasing batch size and sequence length, and uses these insights to deploy SD more effectively for high throughput inference. We leverage draft model with sparse KV cache to address the KV bottleneck, which scales with both sequence length and batch size. Additionally, we propose a theoretical model to select the optimal drafting strategy for maximum speedup. Our work highlights the broad applicability of speculative decoding in long-context serving, as it can enhance throughput and reduce latency without compromising accuracy. For moderate to long sequences, we demonstrate up to 2.51x speedup for LLaMA-3.1-8B when serving batch sizes ranging from 32 to 256 on various types of hardware and tasks.

I INTRODUCTION

The emergence of extremely long-context Large Language Models (LLMs) (AI@Meta, 2024; QwenTeam, 2024; Liu et al., 2023) has led to the popularity of long-context applications such as retrieval augmented generation (Lewis et al., 2021), code generation (AWS, 2024; Chen et al., 2021) and document summarization. Low latency and high throughput are both crucial for serving these long-context LLMs – low latency ensures a positive user experience in interactive applications like chatbots (Achiam et al., 2023; Deepmind, 2024), while high throughput amortizes serving costs.

However, optimizing both latency and throughput in LLM serving presents significant challenges. Speculative decoding (SD)(Leviathan et al., 2022; Xia et al., 2023; Chen et al., 2023) can reduce latency by using a smaller model to predict multiple tokens ahead followed by verification by the target model. But this approach 040 becomes inefficient with large batch sizes because of increased verification cost(Liu et al., 2024a; Su et al., 041 2023), as shown in Fig. 7a. For small batches, the main performance bottleneck is the parameter loading cost, 042 which can be amortized by the verification process across the tokens to be verified at the expense of increased computation. However, with large batches, LLMs become compute bound, making verification significantly 043 044 costly because of its compute-hungry nature. Additionally, if the smaller model's predictions do not align well with the target model, frequent costly verifications are needed. Consequently, the usage of SD in high batch size regime is discouraged by existing works(Liu et al., 2024a; Su et al., 2023; Miao et al., 2023). On the other 046 hand, techniques like (Kwon et al., 2023; Yu et al., 2022; Agrawal et al., 2024b) improve throughput by accom-047 modating larger batches, but at the cost of increased token-wise latency. While techniques such as quantization, 048 pruning and KV cache eviction (Frantar et al., 2023; Xiao et al., 2024a; Hooper et al., 2024; Ma et al., 2023; Sun et al., 2024b) can improve both throughput and latency, they typically result in lower quality model outputs. 050

Based on these challenges, we pose the following question:

- 051
- 052
- 053

Can we simultaneously improve **throughput** and **latency** without sacrificing **accuracy**, particularly for long sequences?



Figure 1: (a) Time breakdown of LLaMA-3.1-8B vs batch size (input length=16384, hardware=8xH100s). (b)
 Throughput of autoregressive decoding and StreamingLLM-based self-speculation of LLaMA-3.1-8B against per-token latency for prompt length of 32k. (c) Draft token acceptance rate comparison for LLaMA-3.1-70B.
 Self-speculation using Top-k attention achieves a much higher acceptance rate than other draft-target pairs, even with lower memory ratio. The x-axis represents the ratio of draft memory footprint to target memory footprint.

We answer with a resounding yes! For large batches of long sequences, we show that SD can be used more effectively to improve both throughput and latency without degradation of the output quality. We base our hypothesis on the following interesting insights:

(1) KV Cache Is The Dominant Bottleneck In Large batch size Long-context Regime: In long-context and large batch size regime, the KV cache outgrows the memory footprint of the model parameter and continues to increase with batch size. Computation also increases with batch size, but due to the high peak FLOPS-to-memory bandwidth ratio of modern GPUs, the KV loading time increases much more than former for larger batches, making LLM inference more memory-bound, as shown in Fig. 1a (Yuan et al., 2024).

(2) SD Can Improve Throughput Only Beyond a Critical Sequence Length: While existing research(Liu et al., 2024a; Su et al., 2023) suggests that SD is inefficient for large batches due to high verification costs, this limitation only applies to very short sequences. Because with short sequences, increasing the batch size makes computational costs the primary bottleneck, which is prohibitive for an efficient verification process. However, once sequences exceed a certain critical length (which varies based on the model and hardware), the KV loading cost becomes the dominant factor, even for large batches. At this point, SD becomes effective again because the computational overhead of verification becomes less significant compared to the KV loading costs, which can be amortized across the tokens to be verified.

(3) Compressed KV Cache Enables More Efficient Speculation: Token acceptance rate is crucial for SD in 087 large batch processing to minimize costly verification steps. Our research found that compressing the Draft KV 880 cache leads to higher acceptance rates than compressing model weights. To evaluate model compression only, 089 we test different draft-target pairs on PG-19 (Rae et al., 2019) sequences of length only 256, to restrict the KV 090 cache impact. For KV compression, we tested LLaMA-3.1-70B on longer sequences (4,000-100,000 091 tokens)¹ using Top-K selection for KV sparsification. Fig. 1c illustrates that model compression alone 092 is unable to reach 90% acceptance rate, while KV compression achieved significantly higher rates under 093 similar memory constraints. This advantage becomes even more significant with larger batch sizes, offering 094 a promising new direction for improving the batch-processing efficiency speculative decoding.

Building upon these insights, our work MagicDec illustrates that SD can improve speedup even for large batches by utilizing KV compression, contrary to prior belief. As shown in Fig. 1b, under long context-length, compressed KV-based self-speculation can improve throughput and latency at the same time in all spectrum, without hurting generation quality. Furthermore, MagicDec evaluates different KV compression-based drafting methods to determine the optimal approach based on the specific model, hardware, and task requirements. We structure the paper as follows.

In Section 3.1, we theoretically analyze the factors that decide the efficiency of speculative decoding. Section 3.2 discusses how the performance bottlenecks in LLM inference shift with batch size and sequence length, and what are its implications on SD's batch-processing efficiency. In the light of this study, we discuss the challenges involved with conventional SD in large batch setting and how it can be overcome by KV sparsification based drafting. Additionally, we introduce the concept of the critical sequence length

¹batch size is set to 1 to nullify the effect of batch size on KV cache size

beyond which SD can achieve higher speedups for larger batches contrary to prior studies (Liu et al., 2024a;
 Su et al., 2023; Miao et al., 2023).

- In Section 3.3, we show why compressing the KV cache is crucial for effective batch processing. Our experimental results demonstrate that this approach achieves higher acceptance rates and, consequently, better batch performance compared to using parameter-efficient draft models. Section 4.4 discusses the trade-off between draft cost and acceptance rate for different static and dynamic KV sparsification algorithms on different kinds of tasks.
- Finally, in Section 5 we provide a comprehensive empirical evaluation across different hardware setups and tasks to show the effectiveness of our theoretical analysis and method. We demonstrate that our approach achieves a 2.51x speedup in large batch settings for LLaMA-3.1-8B on 8xH100 GPUs, significantly improving both throughput and latency over traditional autoregressive decoding (§5).

2 RELATED WORKS

119

120

Numerous efforts have been made to improve the latency and throughput of LLMs. Methods like Flash decoding (Dao, 2023), and Flash decoding++(Hong et al., 2023) have performed system optimizations to improve latency. KV compression methods (Li et al., 2024; Gupta et al., 2021; Xiao et al., 2024b; Tang et al., 2024; Cai. et al., 2024; Zhang et al., 2023; Oren et al., 2024) utilize attention sparsity to reduce the KV loading cost. KV compression can improve both latency and throughput, but suffers from accuracy degradation.

Batching has been a natural technique to improve GPU utilization by amortizing the model parameter loading cost across requests, thus boosting throughput. Recently continuous batching (Kwon et al., 2023; Yu et al., 2022; Prabhu et al., 2024) has been proposed to address the problems arising from heterogeneous batches with unequal context and generation lengths. In our work, we have considered the orthogonal direction of homogeneous batches, and the aforementioned methods are complementary to our observation.

Speculative decoding (Leviathan et al., 2022; Xia et al., 2023; Chen et al., 2023) has emerged as an algorithmic novelty to improve latency without quality degradation. SD improves latency by using a fast draft model to generate multiple tokens, which are then verified in parallel by the LLM, thus maximizing GPU utilization. However, as the batch size increases and computation resources are saturated, the verification of speculated tokens becomes costly. Hence, existing research(Liu et al., 2024a; Su et al., 2023; Miao et al., 2023; Sun et al., 2024a) has discouraged the use of speculative decoding to serve large batches of requests. In our work, we show that this claim only applies to short sequences.

To address the KV bottleneck for serving long sequences, we take inspiration from TriForce (Sun et al., 2024a), which demonstrates the effectiveness of self-speculation with compressed KV. While TriForce is designed for small batches of extremely long sequences, we have focused on large batches of moderate to long sequences, which is more nuanced in terms of draft selection. For draft selection, we have considered a subset of KV compression techniques(Xiao et al., 2024b; Li et al., 2024; Zhang et al., 2024) to exhibit the trade-off between draft cost and acceptance rate. Our work does not advocate for a single KV compression technique, rather provides a framework to choose the optimal strategy from a suite of such techniques.

Many methods have been proposed to improve speculative decoding. For instance, Speculation Parallelism (SP) (Timor et al., 2024) overlaps target verification with draft speculation to enhance speedup. This method evaluates the drafter based on draft cost and acceptance rate, which is similar to our analysis. SP complements our approach: with the high acceptance rate and low draft cost of compressed KV-based drafting, along with reduced verification costs provided by SP, speculative decoding can achieve even greater speedups in long-context serving scenarios.

151 152

3 THEORETICAL ANALYSIS

In this section, we present our theoretical analysis of speculative decoding and LLM inference performance. We begin by reviewing the mathematical formulation of speculative decoding speedup and identifying the key factors influencing it. Next, we analyze LLM inference in long-context scenarios, highlighting the bottleneck shift that enables speculative decoding to achieve speedup with large batch sizes. Finally, we demonstrate the necessity of compressed KV-based drafting to achieve high speedup in long-context, large batch scenarios.

158 159 3.1 SPECULATIVE DECODING SPEEDUP ANALYSIS

The decoding time required by the target model and the draft model for a batch of size B and sequence length S are given by $T_T(B,S)$ and $T_D(B,S)$ respectively. The time taken by the target model to verify γ tokens is given by $T_V(B,S,\gamma)$. Given the draft token acceptance rate $\alpha \in [0,1]$ and speculation length



Figure 2: Theoretical analysis and expected speedup for LLaMA-3.1-8B deployed on 8×A100s with $\gamma = 3$. (a) Theoretical $\mathbf{T}_{\mathbf{D}}/\mathbf{T}_{\mathbf{T}}$ versus batch sizes. (b) Theoretical $\mathbf{T}_{\mathbf{V}}(\gamma)/\mathbf{T}_{\mathbf{T}}$ versus batch size. (c) Theoretical expected speedup of self-speculation across different batch sizes (draft KV budget = 512).

 γ , the expected number of tokens generated in one verification step is denoted by $\Omega(\gamma, \alpha)$. As described in (Leviathan et al., 2022), the expected number of generated tokens can be estimated as,

$$\Omega(\gamma, \alpha) := \mathbb{E}[\#generated tokens] = \frac{1 - \alpha^{\gamma+1}}{1 - \alpha} \tag{1}$$

185 The total time taken for speculative decoding, T_{Total}^{SD} , is given by:

$$T_{Total}^{SD} = \gamma \cdot T_D(B,S) + T_V(B,S,\gamma)$$

Hence, the expected latency per token for speculative decoding is simply $T_{Avg}^{SD} = T_{Total}^{SD} / \Omega(\gamma, \alpha)$. For brevity of notation, we will refer to these times as T_T , T_D , and T_V in the future, with the dependence on B and S implied, unless otherwise specified.

The speedup of speculative decoding and the factors regulating it can be understood from the following equation,

$$\frac{T_{Avg}^{SD}}{T_T} = \frac{1}{\Omega(\gamma,\alpha)} \left(\frac{\gamma \cdot T_D}{T_T} + \frac{T_V(\gamma)}{T_T} \right)$$
(2)

From equation 2 we can see that speed-up depends on three primary factors: (a) **target verification to decoding cost ratio** $\mathbf{T}_{\mathbf{V}}(\gamma)/\mathbf{T}_{\mathbf{T}}$, (b) **draft to target cost ratio** $\mathbf{T}_{\mathbf{D}}/\mathbf{T}_{\mathbf{T}}$, and (c) **expected generation length** $\Omega(\gamma,\alpha)$. For better speedups, we aim to achieve low $T_V(\gamma)/T_T$ (close to 1), low T_D/T_T (close to 0) and high $\Omega(\gamma,\alpha)$.

199 200

175

176

177 178 179

181 182

183

186 187

193 194 195

3.2 KV CACHE BOTTLENECK ENABLES SPECULATIVE DECODING SPEEDUP

In this section, we analyze how the inference bottleneck shifts as sequence length and batch size increase and how it affects the factors discussed in Section 3.1.

For short sequence lengths, speculative decoding negatively impacts batch inference efficiency (Liu et al., 2024a; Su et al., 2023). As batch size grows, the linear layers become compute-bound due to improved arithmetic intensity. This reduces the availability of compute resources that speculative decoding utilizes for parallel verification, essentially increasing the verification to decoding cost ratio.

In contrast, for moderate to long sequences, we observe a transition towards a memory-bound regime since
with increasing batch size, the memory cost of loading the KV cache becomes the dominant factor. This
shift from compute-bound to memory-bound inference makes the verification cost comparable to the target
decoding cost. Because verification and decoding share the same KV budget, their KV cache loading costs
are equivalent. The high ratio of peak FLOPS to memory bandwidth in modern GPUs causes the increase
in KV loading time with batch size to outweigh the increase in computation time (see Fig. 1a). As a result,
although compute-bound linear layers increase verification cost, it is mitigated by the KV bottleneck.

Based on this shift in bottlenecks, we identify a critical sequence length S_{inflection}, beyond which speculative
 decoding achieves speedup for large batches. Moreover, its speedup tends to increase with batch size. This threshold depends on factors like the model architecture, hardware configuration, and drafting strategy.



Figure 3: Theoretical analysis of self-speculation for LLaMA-2-7B-32K and LLaMA-3.1-8B with a draft KV budget of 512 and a batch size of 256. We assume the acceptance rate is 0.8 here. (a) Ratio of target-draft latency $(\gamma \cdot T_D/T_T)$ and verification-target latency $(T_V(\gamma)/T_T)$ versus sequence length for LLaMA-2-7B-32K, with γ =3. (b) Theoretical speedup for different sequence lengths with a fixed α = 0.8. (c) Theoretical arithmetic intensity for different sequence lengths and different models.

• For $S < S_{\text{inflection}}$:

229

230

231

232 233 234

235

236

237

238

239

240

241

In this regime, as batch size increases, decoding becomes more compute-bound. Large batches can saturate the available compute, making verification relatively more expensive, as illustrated in Fig. 2b. The cost ratio $T_V(\gamma)/T_T$ increases significantly for 1000 token long sequences. If the draft token acceptance rate is low, the target model spends considerable time verifying incorrect speculations, reducing SD efficiency. Our theoretical estimate in this regime aligns with (Liu et al., 2024a). The expected speed-up with speculative decoding decreases with batch size for context lengths below the critical sequence length.

• For $S \ge S_{\text{inflection}}$:

In this regime, speculative decoding can provide speedup for large batches, and this speedup even tends to increase with batch size when we use some intelligent drafting strategies. This happens as a combined effect of how verification to decoding cost ratio $(T_V(\gamma)/T_T)$ and draft to target cost ratio (T_D/T_T) evolve with increasing batch size, as shown in Fig. 2b and 2a.

For long sequences, KV cache loading becomes the primary bottleneck rather than compute (Sun et al., 2024a; Aminabadi et al., 2022) and the target model shifts towards memory bound regime, as shown in 3c. Because KV memory bottleneck scales with batch-size, this shift is sustained even for large batches. As the verification and decoding phases share the same KV loading cost, the cost ratio $T_V(\gamma)/T_T$ remains close to 1.

However, the cost ratio $T_V(\gamma)/T_T$ still increases monotonically with batch size and cannot explain how we can achieve higher speedups for larger batches. The draft to target cost ratio (T_D/T_T) plays an important role here. If the KV cache size of the draft model increases slower than target model, the cost ratio T_D/T_T will decrease for larger batches. That is because the target model inference will be more dominated by the KV cache bottleneck rather than the draft.

As Figure 2c illustrates in the case of LLaMA-3.1-8B , the theoretical speedup of speculative decoding is expected to improve with increasing batch size for longer sequence lengths. The speedup decreases with batch size for S < 4000, but for $S \ge 4000$, the speedup increases with batch size.

As illustrated in Figure 3c, this critical sequence length $S_{\text{inflection}}$ depends on both the model's FLOPS-tomemory ratio and the GPU's FLOPS-to-memory bandwidth ratio. For a device with higher FLOPS-to-memory bandwidth ratio, we expect a lower $S_{\text{inflection}}$. Models also affect this critical sequence length. For instance, GQA model like LLaMA-3.1-8B tends to have higher $S_{\text{inflection}}$ due to Grouped Query Attention (GQA), which requires a larger sequence length to achieve the same KV memory footprint.

- 265 3.3 COMPRESSED KV CACHE ENABLES MORE EFFICIENT SPECULATION
- In this section, we explain why KV compression is preferred over lightweight draft models for speculation in long-context, large batch-size scenario. There are primarily two reasons,
- **KV cache grows beyond the parameter memory footprint:** Unlike parameter memory, the KV cache size grows linearly with batch size. If we use LLaMA-3.1-8B as a draft for LLaMA-3.1-70B and



Figure 4: (a, b) Draft/target memory ratio vs batch size across different sequence lengths for LLaMA-3.1-8B /LLaMA-3.1-70B and LLaMA-2-7B /LLaMA-2-70B models. (c) LLaMA-3.1-8B self-speculation acceptance rate of different drafting strategy versus KV budget. Target KV length: 32000.

LLaMA-2-7B for LLaMA-2-70B , the draft models can occupy up to $38 \sim 140\%$ memory footprint of target models (Figures 4a and 4b) due to the fact that \dim_{kv}/\dim_{model} is higher. Hence, in this regime, small draft models are not sufficient and compressed KV-based drafting is quite beneficial(Sun et al., 2024a). This can be seen in Figure 3a, which illustrates how T_D/T_T for fixed KV size draft self-speculation with LLaMA-3.1-8B approaches 0 with increasing sequence length for batch size 256.

KV compression achieves a better token acceptance rate than model compression: A high draft token acceptance rate is critical to restrict the number of costly verification steps while serving large batches. Interestingly, we see that KV cache compression can be a more cost-effective way to improve the acceptance rate of draft tokens, especially in a high batch size long-context regime. Figure 1c illustrates this phenomenon that if a target LLM speculates itself with a sparsified version of its own KV cache, then it can achieve acceptance rates higher than those of small draft models with a full KV cache.

In summary, a draft model with compressed KV cache achieves two important factors for higher speedup in a long-context scenario: low draft cost and high acceptance rate. Figures 7b and 7c empirically illustrate the efficacy of this drafting strategy over standard SD with a small draft model in achieving higher speedups.

4 MAGICDEC

In this section, we present the trade-off analysis MagicDec performs to identify the correct drafting strategy. In Section 3.3, we have motivated the reason behind adopting compressed KV-based drafting in this regime. However, there are three different factors that we need to consider to effectively leverage KV compression - (a) draft model size, (b) draft KV cache size or draft KV budget, and (c) KV compression algorithm. All three factors are to be considered to strike the perfect balance between draft cost and acceptance rate.

4.1 GENERAL FORMULATION OF SPEEDUP WITH COMPRESSED KV-BASED DRAFTING

To begin with, we give a general formulation of speedup obtained with compressed KV-based drafting. The following analysis considers sparse KV selection algorithms; however, it can be easily extended to other KV compression methods (Hooper et al., 2024; Liu et al., 2024b; Singhania et al., 2024). The draft cost for sparse-KV methods depends on two main components: (1) draft model decoding cost, and (2) the cost of KV selection. For a given KV sparsification strategy (*select*) with a fixed KV budget of K, the selection cost is denoted as $T_{select}(B,S,K)$, while the decoding time for K tokens is $T_D(B,K)$. The total time taken by the draft using this KV strategy with KV cache budget K is:

$$T_{D,select_{\mathsf{K}}}(B,S) = T_D(B,K) + T_{select}(B,S,K)$$
(3)

Using this as the total draft decoding time in equation 2, our final objective becomes

320 321 322

323

317 318

319

283

284

285 286 287

288

289

290

291

302

303

304

305

306

307

308 309

$$\min_{T_{select},K,\gamma,\alpha} \left[\frac{T_{Avg}^{SD}}{T_T} \right] = \min_{T_{select},K,\gamma,\alpha} \left[\frac{1}{\Omega(\gamma,\alpha)} \left(\frac{\gamma \cdot (T_D(B,K) + T_{select}(B,S,K))}{T_T(B,S)} + \frac{T_V(B,S,\gamma)}{T_T(B,S)} \right) \right]$$
(4)



337 Figure 5: Comparative analysis of two KV selection algorithms - SnapKV (Li et al., 2024)(static KV selection) and 338 PQCache (Zhang et al., 2024) (dynamic KV selection) on 3 Ruler tasks - needle in a haystack with passkeys 3, common word extraction, question answering 1 (context length = 32,000). (a) Expected speed-up comparison between the two 339 KV selection methods based on MagicDec evaluation framework. (b) Trade-off analysis between Draft-to-target cost 340 ratio and acceptance rate for SnapKV and PQCache methods. (c) Minimum acceptance rates required to be achieved by self-speculation with different draft KV cache sizes to achieve 1.8x speedup over standard autoregressive decoding 342 by LLaMA-3.1-8B . The actual acceptance rates obtained for PG-19 dataset are marked with respective colors. The 343 admissible budgets for each sequence length are ticked right.

344 345 346

347

341

Now we discuss in detail the three main factors that decide the total draft decoding time $T_{D,select_{K}}$ and the final speedup.

348 4.2 DRAFT MODEL SIZE SELECTION 349

Even with a compressed KV cache, the draft model weights can play a role in deciding the best performance. 350 The draft model parameter loading is the major part of draft cost when KV cache size is small. Usually 351 at lower batch sizes, a small draft model with compressed KV cache can outperform self-speculation because 352 of a lower draft to target cost ratio. When batch size and sequence length are relatively small, the parameter 353 loading cost can impede the draft performance. Moreover, for smaller batches, the token acceptance rate 354 requirement can be relaxed to favor a much more efficient draft model. However, beyond a certain batch 355 size, self-speculation can become more efficient because of its higher acceptance rate, as shown in Fig. 7c.

356

357 4.3 DRAFT KV BUDGET SELECTION

358 For a fixed draft model and KV compression algorithm, the optimal draft KV cache size varies across 359 different batch sizes and context lengths. Hence, before selecting the optimal KV compression algorithm, 360 we need to find the respective optimal KV budgets of the candidate algorithms. We illustrate the importance 361 of optimizing the KV budget of static KV selection algorithms for self-speculation in Figure 5c. Batches of 362 different sequence lengths and batch sizes require different minimum acceptance rates to achieve any speedup 363 via speculative decoding. Similarly, different KV budgets and different draft model would have different 364 draft cost-acceptance rate trade-offs. This plot recommends the admissible draft KV budgets that reach the required minimum acceptance rate. This trade-off analysis is particularly useful for serving heterogeneous 365 batches with different sequence lengths. Different sequences in the same batch can leverage different draft 366 KV cache sizes to achieve the required speedup. 367

368

4.4 COMPARATIVE STUDY ON KV SELECTION STRATEGIES 369

Finally, MagicDec has to choose among different kinds of KV selection algorithms to regulate the search 370 cost T_{select} . Although top-k attention can achieve very high acceptance rate with a much smaller KV cache 371 budget, it is not a practical draft option because of its prohibitively high KV selection cost. 372

373 There are many potential alternatives to top-k attention, but determining the optimal one is not straightforward. 374 There are primarily two kinds of KV selection algorithms - (a) dynamic KV selection algorithms such as 375 (Tang et al., 2024; Zhang et al., 2024), (b) static KV selection algorithms such as (Xiao et al., 2024b; Yang et al., 2024; Li et al., 2024). The first kind of algorithms dynamically searches the KV cache for each input 376 query, attempting to find the top k nearest neighbors. Although these methods can achieve higher acceptance 377

rates, they incur substantial search costs. Conversely, static KV selection methods pre-gather a sparse KV

cache for attention approximation during generation. This approach eliminates search overhead but typically results in lower acceptance rates.

Static vs Dynamic: We evaluate state-of-the-art KV selection strategies using both our theoretical framework and empirical acceptance rates from self-speculation with the LLaMA-3.1-8B model on various Ruler tasks (Hsieh et al., 2024). Our analysis includes both static (e.g., StreamingLLM (Xiao et al., 2024b), SnapKV (Li et al., 2024)) and dynamic (e.g., PQCache (Zhang et al., 2024), TopK) KV selection algorithms, exploring different KV budgets and speculation lengths to estimate optimal theoretical speedups.

Figure 5 illustrates the trade-off between two representative KV sparsification algorithms, SnapKV and PQCache, and their respective theoretical speedups on three distinct Ruler tasks: *needle in a haystack with passkeys 3* (niah-multikeys-3), *common word extraction* (cwe), and *question answering 1* (qa-1). SnapKV², a static algorithm, has a lower draft-to-target cost ratio compared to PQCache, as PQCache incurs a batch-size-dependent KV selection cost T_{select} .

When the acceptance rates of static and dynamic methods are similar, the static method tends to dominate, as seen in the *cwe* and *qa-1* tasks. However, for the *niah-multikeys-3* task, PQCache benefits significantly from its higher acceptance rate. With an acceptance rate close to 1, PQCache can leverage longer speculation lengths, which significantly reduces the objective function in equation 4. Nevertheless, with increasing batch-size, KV search cost dominates again and the static algorithm starts to outperform the dynamic one.

5 EVALUATIONS

In this section, we empirically validate our theoretical analysis and demonstrate the effectiveness of our drafting strategy selection modeling. Specifically, in Section 5.1, we demonstrate the end-to-end speedup of self-speculation with sparse KV, showing that speculative decoding achieves speedup for moderate-to-long sequences, with speedup increasing as batch size grows, when sequence length exceeds a critical threshold. In Section 5.2, we compare the speedup of two drafting strategies, highlighting the effectiveness of our approach. In Section 5.3, we perform an ablation study on the speedup of speculative decoding.

404

397

405 5.1 END-TO-END SPEEDUP

We demonstrate the effectiveness of our analysis in Section 3 that speculative decoding can improve both throughput and latency for moderate-to-long sequences.

Setup: We use StreamingLLM (Xiao et al., 2024b) style sparse KV for drafting and conduct experiments across various batch sizes and sequence lengths to evaluate speculative decoding speedup. The system implementation details are shown in A.1. The evaluation is performed using the state-of-the-art long-context model LLaMA-3.1-8B on the PG-19 dataset (Rae et al., 2019). Each run generates 96 tokens per sentence in the batch through greedy decoding on 20 batches. We tested two draft KV cache budgets to assess the trade-off between draft cost and acceptance rate.

Results: Fig. 6 shows the speedup achieved by speculative decoding at the optimal speculation length across various batch sizes and sequence lengths. These experiments are conducted on 8xA100 GPUs.

SD can achieve speedup for moderate to long context length. We can find that speculative decoding consistently outperforms autoregressive decoding except when batch size is large and sequence length is short, which indicate the correctness of our analysis in Sec. 3.2.

SD achieves better speedup with larger batch sizes. We find that on 8xA100, when the sequence length 420 exceeds 4000, speculative decoding achieves speedup, which increases with batch size. This result aligns 421 with our analysis in Sec. 3.2. To verify our analysis of factors affecting the critical sequence length, we ran 422 experiments on higher-end GPUs (H100) and lower-cost alternatives (L40), and compared the results with L 423 LaMA-2-7B-32K . As shown in Table 1, the H100 achieves higher speedup than the A100 and L40 under 424 the same setting (sequence length, batch size, and drafting strategy). This is due to the H100's higher FLOPS-425 to-memory bandwidth ratio, which lowers verification cost. Additionally, we can see for 8000 sequence 426 length and the 32 batch size LLaMA-2-7B-32K without GOA achieves higher speedup than LLaMA 427 -3.1-8B with 32000 sequence length, that's because Non-GQA model has lower FLOPS-to-memory ratio. 428

 ²SnapKV was chosen for its superior acceptance rates among static algorithms, utilizing average pooling with a kernel
 size of 5 and an observation window size of 32. PQCache employs product quantization with 16 sub-vectors and 8-bit quantization per key vector.



Figure 6: End-to-end speedups for StreamingLLM-based self-speculation with LLaMA-3.1-8B across various compressed KV budgets (left: 256, right: 512) on PG-19. Annotations indicate γ_{optimal} , which is the value corresponding to the highest speedup achieved. Experiments are conducted on 8xA100 with 8-way tensor parallelism. Raw data can be found in A.2.

Table 1: Results on L40 and H100, StreamingLLM budget for the draft model is 512, each with the optimal γ

Target	Draft	Task	GPU	Prefill	Bsz	γ	$\gamma \mathbf{T_D}(1)$	$\mathbf{T}_{\mathbf{V}}(\gamma)$	$\mathbf{\Omega}(\gamma, \alpha)$	$\mathbf{T^{AR}}$	$\mathbf{T}^{\mathbf{SD}}$	x
Llama3.1-8B	StreamingLLM	PG-19	8xL40	32000	32	3	44.11	45.12	3.00	36.62	30.32	1.21
Llama2-7B-32K	StreamingLLM	PG-19	8xL40	8000	32	2	29.06	42.02	2.53	35.13	28.70	1.22
Llama2-7B-32K	StreamingLLM	PG-19	8xL40	8000	64	3	58.33	74.85	3.14	62.92	42.96	1.46
Llama3.1-8B	StreamingLLM	PG-19	4xH100	32000	32	3	15.09	18.30	2.82	17.32	12.16	1.42
Llama2-7B-32K	StreamingLLM	PG-19	4xH100	8000	32	3	14.20	15.64	2.98	14.85	10.29	1.44
Llama2-7B-32K	StreamingLLM	PG-19	4xH100	8000	64	4	23.63	27.90	3.37	26.17	15.58	1.68

5.2 COMPARING DIFFERENT KV COMPRESSION METHODS

In this section, we compare two static KV compression methods for drafting, with results shown Fig. 7b and Fig. 7c. The detail results are in Table 6. We perform a sweep to select the optimal speculation length and KV budget for each method. The best draft budget for StreamingLLM-based self-speculation is 512, while for SnapKV-based approach, it is 2049. The results indicate that SnapKV-based drafting outperforms StreamingLLM for self-speculation in all the cases. Based on Fig. 4c and our analysis in Sec. 4, the key factor is the acceptance rate. Both StreamingLLM and SnapKV are static KV compression methods, so neither incurs KV search overhead. However, SnapKV has a much higher acceptance rate, which increases rapidly with KV budget, mitigating the rise in draft cost. In contrast, StreamingLLM's acceptance rate has a lower upper bound and increases more slowly with KV budget. As a result, SnapKV achieves higher speedup due to the combined effect of acceptance rate and draft cost. We further evaluated SnapKV-based self-speculation across different batch sizes, sequence lengths, and tasks, with promising results. As shown in Table 2, SnapKV-based self-speculation achieves up to 2.51x speedup, demonstrating speculative decoding's ability to improve throughput.

|--|

Target	Draft	Task	GPU	Prefill	Bsz	γ	$\gamma T_{D}(1)$	$\mathbf{T}\mathbf{v}(\gamma)$	$\mathbf{\Omega}(\gamma, \alpha)$	T^{AR}	T^{SD}	×
Llama3.1-8B	SnapKV	PG-19	8xH100	100000	41	7	34.34	28.50	5.61	25.96	11.35	2.29
Llama3.1-8B	SnapKV	QA-1	8xH100	100000	41	11	53.90	29.89	7.93	25.90	10.64	2.43
Llama3.1-8B	SnapKV	CWE	8xH100	100000	41	11	53.98	29.93	8.21	25.83	10.29	2.51
Llama3.1-8B	SnapKV	PG-19	8xH100	64000	64	6	32.89	28.80	5.41	25.52	11.54	2.21
Llama3.1-8B	SnapKV	QA-1	8xH100	64000	64	7	38.40	29.11	6.08	25.43	11.20	2.27
Llama3.1-8B	SnapKV	CWE	8xH100	64000	64	8	43.91	29.29	6.83	25.48	10.81	2.36

^{481 5.3} ABLATION STUDY

In this section, we present ablation studies of our speculative decoding speedup analysis model.

484 Draft KV Budget. As modeled in Section 4, the selection of KV budget depends on verification cost,
 485 acceptance rate, and draft cost. As shown in Fig. 6, when batch size and sequence length are large, a larger
 KV budget results in higher speedup. In this scenario, the LLM is highly memory-bound, so verification



Figure 7: Comparison between different drafting strategy for LLaMA-3.1-8B under short, medium and long context length across batch sizes. Hardware: 8xH100. Each with optimal gamma. Dataset: PG-19.

cost is low, but its absolute value is much larger than the draft cost with a fixed KV size. Therefore, a larger KV budget with a higher acceptance rate is preferred to increase the average generation length per step.

504 Draft Model Weights. Draft model weights loading is also a part of draft cost. We have several choices of 505 drafting stategy with the trade-off of draft cost and acceptance rate. A small draft model can have much lower model weights loading cost, but with significant lower acceptance rate. We conduct experiments under prompt 506 length 256, 8192 and 32768 to show the effect to speedup of different draft model selection. The results are 507 shown in Fig. 7. We can see in Fig. 7b that when sequence length is not sufficient long and batch size is not 508 very large, small draft model with the KV compression tends to outperform self-speculation. This is because, 509 in these scenarios, KV doesn't fully dominate inference, and model weight loading makes draft costs of 510 self-speculation a lot higher. However, when both sequence length and batch size are very large, and the KV 511 cache dominates LLM inference, self-speculation surpasses the small draft model, as model weight loading 512 contributes minimally to overall latency. The high acceptance rate of compressed KV self-speculation has 513 higher speedup upper bound, and leads to better speedup when batch size is large, as demonstrated in Fig. 7c.

Models. Different models have different FLOPS to Memory Ratio and acceptance rate. We also conducted experiments on Qwen2.5-7B, Qwen2.5-32B and Mistral-7B-v0.3 models to show the generalizability of MagicDec. The results are shown in Sec. A.5. We can see speculative decoding works well for these models, achieving up to 2.06x speedup for Mistral-7B-v0.3, 1.89x speedup for Qwen2.5-7B and 1.51x speedup for Qwen2.5-32B on PG-19 dataset. The trend of speedup also matches our previous analysis and the LLaMA-3.1-8B results.

521 6

522

499

500 501

502

503

6 CONCLUSION AND LIMITATION

Optimizing both throughput and latency for LLM inference is challenging, especially for long-context, large 523 batch-size regime. Our analysis reveals that speculative decoding can be beneficial in this regime, with its 524 efficacy increasing with larger batch-sizes, contrary to existing misconceptions. In search of effective drafting 525 strategies, we discover that KV compression is easier than model compression to achieve higher acceptance 526 rate at the same memory budget, which becomes more prominent in high batch-size and long context-length 527 regime. Leveraging these insights, we explore different KV compression algorithms for drafting and present 528 a bottleneck-aware general formulation to select suitable drafting strategy based on task, batch-size and 529 sequence-length. MagicDec only focuses on decoding performance for long-context LLM serving, while the prefill is also very challenging in this scenario. There has been some work focusing on improving the 530 prefill performance (Agrawal et al., 2024a; Zhong et al., 2024), which could be integerated with MagicDec 531 to improve both prefill and decode performance. MagicDec tends to achieve better speedup on high-end 532 GPUs due to their higher FLOPS-to-memory bandwidth ratio and large HBM size. Future work can explore 533 the adoption of speculative decoding on offloading and distributed setting to reduce the communication 534 overhead, thus better utilize the resource of commodity devices. 535

536 537 REFERENCES

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo
 Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv* preprint arXiv:2303.08774, 2023.

540 541 542	Amey Agrawal, Junda Chen, Íñigo Goiri, Ramachandran Ramjee, Chaojie Zhang, Alexey Tumanov, and Esha Choukse. Mnemosyne: Parallelization strategies for efficiently serving multi-million context length llm inference requests without approximations, 2024a. URL https://arxiv.org/abs/2409.17264.
543 544 545 546	Amey Agrawal, Nitin Kedia, Ashish Panwar, Jayashree Mohan, Nipun Kwatra, Bhargav S. Gulavani, Alexey Tumanov, and Ramachandran Ramjee. Taming throughput-latency tradeoff in llm inference with sarathi-serve, 2024b. URL https://arxiv.org/abs/2403.02310.
547 548 549	AI@Meta. The llama 3 herd of models, 2024. URL https://ai.meta.com/research/ publications/the-llama-3-herd-of-models.
550 551 552 553	Reza Yazdani Aminabadi, Samyam Rajbhandari, Minjia Zhang, Ammar Ahmad Awan, Cheng Li, Du Li, Elton Zheng, Jeff Rasley, Shaden Smith, Olatunji Ruwase, and Yuxiong He. Deepspeed inference: Enabling efficient inference of transformer models at unprecedented scale, 2022. URL https://arxiv.org/abs/2207.00032.
554 555	Amazon AWS. Codewhisperer, 2024. URL https://aws.amazon.com//codewhisperer.
556 557 558	Zefan Cai., Yichi Zhang, Bofei Gao, Yuliang Liu, Tianyu Liu, Keming Lu, Wayne Xiong, Yue Dong, Baobao Chang, Junjie Hu, and Wen Xiao. Pyramidkv: Dynamic kv cache compression based on pyramidal information funneling, 2024. URL https://arxiv.org/abs/2406.02069.
559 560 561 562	Charlie Chen, Sebastian Borgeaud, Geoffrey Irving, Jean-Baptiste Lespiau, Laurent Sifre, and John Jumper. Accelerating large language model decoding with speculative sampling. <i>arXiv preprint arXiv:2302.01318</i> , 2023.
562 563 564 565 566 567 568 569 570 571 572	Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, Alex Ray, Raul Puri, Gretchen Krueger, Michael Petrov, Heidy Khlaaf, Girish Sastry, Pamela Mishkin, Brooke Chan, Scott Gray, Nick Ryder, Mikhail Pavlov, Alethea Power, Lukasz Kaiser, Mohammad Bavarian, Clemens Winter, Philippe Tillet, Felipe Petroski Such, Dave Cummings, Matthias Plappert, Fotios Chantzis, Elizabeth Barnes, Ariel Herbert-Voss, William Hebgen Guss, Alex Nichol, Alex Paino, Nikolas Tezak, Jie Tang, Igor Babuschkin, Suchir Balaji, Shantanu Jain, William Saunders, Christopher Hesse, Andrew N. Carr, Jan Leike, Josh Achiam, Vedant Misra, Evan Morikawa, Alec Radford, Matthew Knight, Miles Brundage, Mira Murati, Katie Mayer, Peter Welinder, Bob McGrew, Dario Amodei, Sam McCandlish, Ilya Sutskever, and Wojciech Zaremba. Evaluating large language models trained on code, 2021. URL https://arxiv.org/abs/2107.03374.
573 574	Tri Dao. Flashattention-2: Faster attention with better parallelism and work partitioning, 2023. URL https://arxiv.org/abs/2307.08691.
575 576 577 578	Google Deepmind. Our next-generation model: Gemini 1.5, 2024. URL https://blog.google/ technology/ai/google-gemini-next-generation-model-february-2024/ #build-experiment.
579	$flashinfer-ai. \ Flashinfer. \ URL \ \texttt{https://github.com/flashinfer-ai/flashinfer}.$
580 581 582	Elias Frantar, Saleh Ashkboos, Torsten Hoefler, and Dan Alistarh. Gptq: Accurate post-training quantization for generative pre-trained transformers, 2023. URL https://arxiv.org/abs/2210.17323.
583 584 585	Ankit Gupta, Guy Dar, Shaya Goodman, David Ciprut, and Jonathan Berant. Memory-efficient transformers via top-k attention, 2021. URL https://arxiv.org/abs/2106.06899.
586 587	Ke Hong, Guohao Dai, Jiaming Xu, Qiuli Mao, Xiuhong Li, Jun Liu, Kangdi Chen, Hanyu Dong, and Yu Wang. Flashdecoding++: Faster large language model inference on gpus. <i>arXiv preprint arXiv:2311.01282</i> , 2023.
588 589 590 591	Coleman Hooper, Sehoon Kim, Hiva Mohammadzadeh, Michael W. Mahoney, Yakun Sophia Shao, Kurt Keutzer, and Amir Gholami. Kvquant: Towards 10 million context length llm inference with kv cache quantization, 2024. URL https://arxiv.org/abs/2401.18079.
592 593	Cheng-Ping Hsieh, Simeng Sun, Samuel Kriman, Shantanu Acharya, Dima Rekesh, Fei Jia, Yang Zhang, and Boris Ginsburg. Ruler: What's the real context size of your long-context language models?, 2024. URL https://arxiv.org/abs/2404.06654.

594 Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Yu, Joseph E Gonzalez, Hao 595 Zhang, and Ion Stoica. vllm: Easy, fast, and cheap llm serving with pagedattention. See https://vllm.ai/ 596 (accessed), 2023. 597 Yaniv Leviathan, Matan Kalman, and Yossi Matias. Fast inference from transformers via speculative decoding. 598 arXiv preprint arXiv:2211.17192, 2022. 600 Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman 601 Goyal, Heinrich Küttler, Mike Lewis, Wen tau Yih, Tim Rocktäschel, Sebastian Riedel, and 602 Douwe Kiela. Retrieval-augmented generation for knowledge-intensive nlp tasks, 2021. URL https://arxiv.org/abs/2005.11401. 603 604 Yuhong Li, Yingbing Huang, Bowen Yang, Bharat Venkitesh, Acyr Locatelli, Hanchen Ye, Tianle Cai, Patrick 605 Lewis, and Deming Chen. Snapky: Llm knows what you are looking for before generation, 2024. URL 606 https://arxiv.org/abs/2404.14469. 607 Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning, 2023. URL 608 https://arxiv.org/abs/2304.08485. 609 610 Xiaoxuan Liu, Cade Daniel, Langxiang Hu, Woosuk Kwon, Zhuohan Li, Xiangxi Mo, Alvin Cheung, Zhijie 611 Deng, Ion Stoica, and Hao Zhang. Optimizing speculative decoding for serving large language models 612 using goodput, 2024a. URL https://arxiv.org/abs/2406.14066. 613 Zirui Liu, Jiayi Yuan, Hongye Jin, Shaochen Zhong, Zhaozhuo Xu, Vladimir Braverman, Beidi Chen, and 614 Xia Hu. Kivi: A tuning-free asymmetric 2bit quantization for kv cache. arXiv preprint arXiv:2402.02750, 615 2024b. 616 617 Xinyin Ma, Gongfan Fang, and Xinchao Wang. Llm-pruner: On the structural pruning of large language models, 2023. URL https://arxiv.org/abs/2305.11627. 618 619 Xupeng Miao, Gabriele Oliaro, Zhihao Zhang, Xinhao Cheng, Zeyu Wang, Rae Ying Yee Wong, Zhuoming 620 Chen, Daiyaan Arfeen, Reyna Abhyankar, and Zhihao Jia. Specinfer: Accelerating generative llm serving 621 with speculative inference and token tree verification. arXiv preprint arXiv:2305.09781, 2023. 622 623 Matanel Oren, Michael Hassid, Nir Yarden, Yossi Adi, and Roy Schwartz. Transformers are multi-state rnns, 2024. URL https://arxiv.org/abs/2401.06104. 624 625 Ramya Prabhu, Ajay Nayak, Jayashree Mohan, Ramachandran Ramjee, and Ashish Panwar. vat-626 tention: Dynamic memory management for serving llms without pagedattention, 2024. URL 627 https://arxiv.org/abs/2405.04437. 628 pytorch-labs. Gpt-fast, 2023. URL https://github.com/pytorch-labs/gpt-fast. 629 630 OwenTeam. Qwen2.5: A party of foundation models, September 2024. URL https: 631 //qwenlm.github.io/blog/qwen2.5/. 632 Jack W. Rae, Anna Potapenko, Siddhant M. Jayakumar, and Timothy P. Lillicrap. Compressive transformers 633 for long-range sequence modelling, 2019. URL https://arxiv.org/abs/1911.05507. 634 635 Prajwal Singhania, Siddharth Singh, Shwai He, Soheil Feizi, and Abhinav Bhatele. Loki: Low-rank keys 636 for efficient sparse attention, 2024. URL https://arxiv.org/abs/2406.02542. 637 Qidong Su, Christina Giannoula, and Gennady Pekhimenko. The synergy of speculative decoding and 638 batching in serving large language models, 2023. URL https://arxiv.org/abs/2310.18813. 639 640 Hanshi Sun, Zhuoming Chen, Xinyu Yang, Yuandong Tian, and Beidi Chen. Triforce: Lossless 641 acceleration of long sequence generation with hierarchical speculative decoding, 2024a. URL https://arxiv.org/abs/2404.11912. 642 643 Mingjie Sun, Zhuang Liu, Anna Bair, and J. Zico Kolter. A simple and effective pruning approach for large 644 language models, 2024b. URL https://arxiv.org/abs/2306.11695. 645 Jiaming Tang, Yilong Zhao, Kan Zhu, Guangxuan Xiao, Baris Kasikci, and Song Han. 646 Query-aware sparsity for efficient long-context llm inference, 2024. URL Quest: 647

https://arxiv.org/abs/2406.10774.

648 649	MLC team. MLC-LLM, 2023. URL https://github.com/mlc-ai/mlc-llm.
650 651 652	Nadav Timor, Jonathan Mamou, Daniel Korat, Moshe Berchansky, Oren Pereg, Moshe Wasserblat, Tomer Galanti, Michal Gordon, and David Harel. Distributed speculative inference of large language models is provably faster, 2024. URL https://arxiv.org/abs/2405.14105.
653 654 655 656	Heming Xia, Tao Ge, Peiyi Wang, Si-Qing Chen, Furu Wei, and Zhifang Sui. Speculative de- coding: Exploiting speculative execution for accelerating seq2seq generation, 2023. URL https://arxiv.org/abs/2203.16487.
657 658 659	Guangxuan Xiao, Ji Lin, Mickael Seznec, Hao Wu, Julien Demouth, and Song Han. Smoothquant: Accurate and efficient post-training quantization for large language models, 2024a. URL https://arxiv.org/abs/2211.10438.
660 661	Guangxuan Xiao, Yuandong Tian, Beidi Chen, Song Han, and Mike Lewis. Efficient streaming language models with attention sinks, 2024b. URL https://arxiv.org/abs/2309.17453.
663 664 665	Dongjie Yang, XiaoDong Han, Yan Gao, Yao Hu, Shilin Zhang, and Hai Zhao. Pyramid- infer: Pyramid kv cache compression for high-throughput llm inference, 2024. URL https://arxiv.org/abs/2405.12532.
666 667 668 669 670	Gyeong-In Yu, Joo Seong Jeong, Geon-Woo Kim, Soojeong Kim, and Byung-Gon Chun. Orca: A distributed serving system for Transformer-Based generative models. In <i>16th</i> <i>USENIX Symposium on Operating Systems Design and Implementation (OSDI 22)</i> , pp. 521– 538, Carlsbad, CA, July 2022. USENIX Association. ISBN 978-1-939133-28-1. URL https://www.usenix.org/conference/osdi22/presentation/yu.
671 672 673 674	Zhihang Yuan, Yuzhang Shang, Yang Zhou, Zhen Dong, Chenhao Xue, Bingzhe Wu, Zhikai Li, Qingyi Gu, Yong Jae Lee, Yan Yan, Beidi Chen, Guangyu Sun, and Kurt Keutzer. Llm inference unveiled: Survey and roofline model insights, 2024.
675 676 677	Hailin Zhang, Xiaodong Ji, Yilin Chen, Fangcheng Fu, Xupeng Miao, Xiaonan Nie, Weipeng Chen, and Bin Cui. Pqcache: Product quantization-based kvcache for long context llm inference, 2024. URL https://arxiv.org/abs/2407.12820.
678 679 680 681	Zhenyu Zhang, Ying Sheng, Tianyi Zhou, Tianlong Chen, Lianmin Zheng, Ruisi Cai, Zhao Song, Yuandong Tian, Christopher Ré, Clark Barrett, Zhangyang Wang, and Beidi Chen. H ₂ o: Heavy-hitter oracle for efficient generative inference of large language models, 2023. URL https://arxiv.org/abs/2306.14048.
683 684 685 686	Yinmin Zhong, Shengyu Liu, Junda Chen, Jianbo Hu, Yibo Zhu, Xuanzhe Liu, Xin Jin, and Hao Zhang. Distserve: Disaggregating prefill and decoding for goodput-optimized large language model serving, 2024. URL https://arxiv.org/abs/2401.09670.
687	A APPENDIX
688	A.1 System Implementation
689	
690 691	Prefill Phase Decode Phase Speculation
692	Full KV Compressed KV



Figure 8: Self-Speculation System Design. We demonstrate using a static KV compression method.

700 The design of our speculative decoding system is shown in Fig. 8, demonstrating the use of a static KV compression method. The static compressed KV is generated during prefill phase and used for drafting. We implement the speculative decoding system on both state-of-the-art inference framework MLC-LLM (team,

2023) and a self-implement inference backend. The main results are obatined from our self-implemented backend. The comparison of our backend and MLC-LLM can be found in A.3.

The self-implement inference backend is built on GPT-Fast (pytorch-labs, 2023), with Flashinfer (flashinfer-ai) accelerating attention computation. We use torch.compile to compile the model and utilize Triton-based matrix multiplication to accelerate the MLP layers. We use Pytorch CUDA graphs to reduce CPU kernel launch overhead. These optimizations help minimize overhead and improve speedup. We also implement tensor parallelism for the embedding layer to further accelerate drafting.

A.2 RESULTS OF VARIOUS BATCH SIZE AND CONTEXT LENGTH ON A100

S

We show the raw data points we collected when running speculative decoding on the self-implement backend to support our previous discussion. We sweep the batch size and sequence lengths, and compare the speedup of different drafting strategy for different models. We ran all these experiments on 8 Nvidia A100 GPU with 8-way Tensor Parallelism.

715 716

710

```
717 (a) LLaMA-2-7B-32K , TinyL
```

Lama-1.1B 718 **B** $\gamma T_D T_V \Omega T^{AR} T^{SD}$ s x 719 1024 32 9.55 2.19 8.27 8.70 0.95 8.21 720 1024 48 8.46 10.66 2.19 9.41 9.33 1.01 1024 64 9.26 13.05 2.19 10.83 10.80 1.00 721 1024 128 12.04 18.87 2.19 14.02 14.83 0.94 722 4000 32 8.46 13.21 2.19 11.89 10.52 1.13 4000 48 8.71 16.19 2.19 14.39 12.02 1.20 723 14.88 1.30 4000 64 9.35 21.83 2.19 19.28 724 4000 128 12.31 33.82 2.19 28.77 21.78 1.32 725 8000 32 8.61 18.40 2.18 16.53 13.02 1.27 8000 48 8.91 23.67 2.18 21.45 15.58 1.38 726 8000 64 9.58 34.32 2.18 31.49 20.80 1.51 727 8000 128 12.54 53.78 2.18 49.89 31.25 1.60 16000 32 8.78 27.79 2.17 26.28 17.46 1.50 728 16000 48 9.33 38.29 2.18 35.83 22.52 1.59 729 16000 64 9.92 58.14 2.17 55.08 31.99 1.72 24000 32 8.68 37.57 2.16 35.70 22.05 1.62 730 32000 32 8.83 47.35 2.17 44.94 26.55 1.69 (b) LLaMA-2-7B-32K Self Speculation

4000 128 25.82 33.79 2.56 28.77

8000 32 1570 1823 253 1653

8000 128 26.10 53.69 2.52 49.89

24000 32 15.80 37.06 2.49 35.70

32000 32 16.19 46.55 2.50 44.94

 $\underline{\mathbf{B}} \quad \underline{\gamma} \mathbf{T}_{\mathbf{D}} \quad \mathbf{T}_{\mathbf{V}} \quad \mathbf{\Omega} \quad \mathbf{T}^{\mathbf{AR}} \quad \mathbf{T}^{\mathbf{SD}}$

4000 32 15.42 13.17 2.56 11.89 11.69 1.02

4000 48 1696 1638 256 1439 1355 106

4000 64 19.75 22.01 2.57 19.28 16.82 1.15

8000 48 18.44 24.32 2.53 21.45 17.50 1.23

8000 64 20.03 34.30 2.53 31.49 22.05 1.43

16000 32 16.06 27.54 2.50 26.28 18.02 1.46

16000 48 19.75 39.03 2.50 35.83 24.15 1.48

16000 64 20.87 58.15 2.51 55.08 32.16 1.71

(c) LLaMA-3.1-8B Self Specula-

tion

x

23.86 1.21

13.99 1.18

32.25 1.55

21.77 1.64

25.64 1.75

s	В	$\gamma \mathbf{T_D}$	$\mathbf{T}_{\mathbf{V}}$	Ω	$\mathbf{T}^{\mathbf{A}\mathbf{R}}$	$\mathbf{T^{SD}}$	x
4000	32	13.16	10.32	2.54	8.83	9.78	0.90
4000	64	16.48	13.55	2.54	10.07	12.36	0.81
4000	128	23.41	19.77	2.54	13.42	17.70	0.76
4000	256	39.29	35.05	2.53	23.23	30.46	0.76
8000	32	13.28	11.34	2.50	9.90	10.40	0.95
8000	64	16.98	16.06	2.51	14.16	13.72	1.03
8000	128	23.59	24.84	2.51	18.53	19.97	0.93
8000	256	39.32	46.44	2.51	35.35	34.99	1.01
16000	32	14.46	14.00	2.47	11.93	12.10	0.99
16000	64	18.00	21.15	2.48	17.17	16.40	1.05
16000	128	25.77	34.82	2.46	28.00	25.36	1.10
32000	32	14.12	19.04	2.46	17.13	14.05	1.22
32000	64	19.08	30.86	2.45	26.99	21.03	1.28
32000	128	28.26	54.98	2.45	47.24	34.94	1.35
64000	32	14.92	28.88	2.40	26.96	18.91	1.43
64000	64	18.25	50.19	2.40	46.09	29.22	1.58
100000	32	15.10	39.84	2.45	37.70	23.05	1.64

731 732 733

734 735 736

737

738

739

740

741

742

Table 3: Comparison of results for different LLaMA models and configurations (budget=512 and $\gamma = 2,8 \times A100$). Here S and B represent prefill length and batch size, respectively.

A.3 COMPARISON WITH MLC-LLM RESULTS

We compare the results of SnapKV based self-speculation on MLC-LLM and our backend. As the measurement methods are different, we put them in two tables as shown in Table 4 and 5. The verification time of MLC-LLM includes one step of draft decode time. Our backend is highly optimized for speculative decoding setting, minimizing the drafting and verification overhead, thus, leading to better speedup. However, the trend that speedup increases with batch size is the same, aligning with our theoretical analysis in Section 3.

Table 4: Results of Our Backend

Target	Backend	Task	GPU	Prefill	Bsz	γ	$\gamma \mathbf{T_D}(1)$	$\mathbf{T}_{\mathbf{V}}(\gamma)$	$\mathbf{\Omega}(\gamma, \alpha)$	$\mathbf{T^{AR}}$	$\mathbf{T^{SD}}$	x
Llama3.1-8B	Ours	PG-19	8xH100	32000	16	3	10.96	6.91	3.42	6.41	5.41	1.18
Llama3.1-8B	Ours	PG-19	8xH100	32000	32	4	16.69	10.39	4.10	9.23	6.75	1.37
Llama3.1-8B	Ours	PG-19	8xH100	32000	64	5	23.96	17.45	4.59	14.85	9.17	1.62

Table 5: Results of MLC-LLM

752	Target	Backend	Task	GPU	Prefill	Bsz	γ	$T_D(1)$	$\mathbf{T}_{\mathbf{V}}(\gamma)$	NumGen	ARTrput	SDTrput	x
753	Llama3.1-8B	MLC-LLM	PG-19	8xH100	32000	16	4	3.64	13.60	724	2471.4	2133.0	0.86
754	Llama3.1-8B	MLC-LLM	PG-19	8xH100	32000	32	4	4.19	16.13	1455	3311.5	3664.5	1.11
754	Llama3.1-8B	MLC-LLM	PG-19	8xH100	32000	64	5	5.27	28.26	2719	3930.0	4959.2	1.26

755

756 A.4 FURTHER SNAPKV AND STREAMINGLLM RESULTS

We show the raw experiment data. We compare both the StreamingLLM-based self-speculation and SnapKV-based self-speculation, and also a small draft model with StreamingLLM KV cache.

Table 6: Comparison of SnapKV, StreamingLLM, and Tiny Draft (StreamingLLM KV) Speculation. Each with optimal γ and KV budget

2													
2	Target	Draft	Task	GPU	Prefill	Bsz	γ	$\gamma \mathbf{T_D}(1)$	$\mathbf{T}_{\mathbf{V}}(\gamma)$	$\mathbf{\Omega}(\gamma, \alpha)$	$\mathbf{T}^{\mathbf{AR}}$	$\mathbf{T}^{\mathbf{SD}}$	x
4	Llama3.1-8B	Llama3.2-1B(S)	PG-19	8xH100	32000	16	3	4.43	6.71	2.43	6.18	4.86	1.27
-	Llama3.1-8B	StreamingLLM	PG-19	8xH100	32000	16	3	10.33	6.73	3.09	6.18	5.74	1.08
2	Llama3.1-8B	SnapKV	PG-19	8xH100	32000	16	3	10.55	6.84	3.41	6.18	5.27	1.17
6	Llama3.1-8B	Llama3.2-1B(S)	PG-19	8xH100	32000	32	3	4.71	9.70	2.43	9.10	6.22	1.46
7	Llama3.1-8B	StreamingLLM	PG-19	8xH100	32000	32	3	11.55	9.74	3.06	9.10	7.20	1.26
-	Llama3.1-8B	SnapKV	PG-19	8xH100	32000	32	4	15.79	10.36	4.03	9.10	6.64	1.37
3	Llama3.1-8B	Llama3.2-1B(S)	PG-19	8xH100	32000	64	3	5.05	15.86	2.44	14.84	8.88	1.67
9	Llama3.1-8B	StreamingLLM	PG-19	8xH100	32000	64	3	12.82	15.93	3.08	14.84	9.57	1.55
- -	Llama3.1-8B	SnapKV	PG-19	8xH100	32000	64	5	22.91	17.70	4.55	14.84	9.05	1.64
J	Llama3.1-8B	Llama3.2-1B(S)	PG-19	8xH100	32000	128	3	5.79	28.51	2.43	26.07	14.43	1.81
1	Llama3.1-8B	StreamingLLM	PG-19	8xH100	32000	128	4	18.96	30.34	3.57	26.07	14.06	1.85
2	Llama3.1-8B	SnapKV	PG-19	8xH100	32000	128	6	33.33	31.60	5.07	26.07	12.96	2.01

A.5 RESULTS OF QWEN AND MISTRAL MODELS

Table 7: Results of Qwen and Mistral Models. Each with optimal γ and KV budget

'8													
'9	Target	Draft	Task	GPU	Prefill	Bsz	γ	$\gamma T_D(1)$	$\mathbf{T}_{\mathbf{V}}(\gamma)$	$\mathbf{\Omega}(\gamma, \alpha)$	$\mathbf{T}^{\mathbf{AR}}$	$\mathbf{T^{SD}}$	x
0	Mistral-7B-v0.3	SnapKV	PG-19	8xH100	32000	32	3	11.71	9.62	3.49	8.92	6.12	1.46
0	Mistral-7B-v0.3	SnapKV	PG-19	8xH100	32000	64	3	13.64	15.64	3.47	14.49	8.44	1.72
1	Mistral-7B-v0.3	SnapKV	PG-19	8xH100	32000	128	5	27.49	30.65	4.72	25.41	12.31	2.06
2	Qwen-2.5-7B	SnapKV	PG-19	4xH100	32000	32	3	11.40	9.26	3.40	8.20	6.07	1.35
_	Qwen-2.5-7B	SnapKV	PG-19	4xH100	32000	64	4	17.67	15.67	4.06	13.11	8.20	1.6
3	Qwen-2.5-7B	SnapKV	PG-19	4xH100	32000	128	5	27.22	28.51	4.62	22.79	12.06	1.89
4	Qwen-2.5-32B	SnapKV	PG-19	8xH100	32000	8	3	23.67	11.98	3.50	10.42	10.19	1.02
-	Qwen-2.5-32B	SnapKV	PG-19	8xH100	32000	16	3	25.27	15.29	3.52	13.36	11.52	1.16
5	Qwen-2.5-32B	SnapKV	PG-19	8xH100	32000	32	3	28.99	21.90	3.51	19.43	14.49	1.34
6	Qwen-2.5-32B	Qwen-2.5-7B	PG-19	8xH100	32000	8	2	9.04	11.31	2.32	10.42	8.74	1.19
7	Qwen-2.5-32B	Qwen-2.5-7B	PG-19	8xH100	32000	16	2	11.61	14.59	2.32	13.36	11.31	1.18
	Qwen-2.5-32B	Qwen-2.5-7B	PG-19	8xH100	32000	32	2	16.72	20.87	2.31	19.43	16.27	1.19
8	Qwen-2.5-32B	Qwen-2.5-7B(Streaming)	PG-19	8xH100	32000	8	2	6.77	11.31	2.27	10.42	7.97	1.31
9	Qwen-2.5-32B	Qwen-2.5-7B(Streaming)	PG-19	8xH100	32000	16	2	7.21	14.59	2.26	13.36	9.64	1.39
0	Qwen-2.5-32B	Qwen-2.5-7B(Streaming)	PG-19	8xH100	32000	32	3	11.78	21.82	2.62	19.43	12.85	1.51

810 A.6 TINYLLAMA1.1B-LLAMA2-7B-32K RESULTS 811

We also test the non-GQA model LLaMA-2-7B-32K for both StreamingLLM-based self-speculation and 812 small draft model with StreamingLLM KV cache. Due to the lower FLOPS to memory ratio of non-GQA 813 model, it tends to achieve higher speedup than GQA model under the same setting.

814 815





(a) Draft: TinyLLama-1.1B , Target: LLaMA-2-7B-32K

(b) Draft: StreamingLLM based KV. Target: LLaMA-2 -7B-32K

Figure 9: End-to-end speedups for StreamingLLM-based self-speculation across various compressed KV budgets (left: 256, right: 512) on PG-19. Annotations indicate γ_{optimal} , which is the value corresponding to the highest speedup achieved. Experiments are conducted on 8xA100 with 8-way tensor parallelism. Raw data can be found in A.2.



841

842 843

844

845

861