# ORBIT - Open Recommendation Benchmark for Reproducible Research with Hidden Tests

<sup>1</sup>Language Technologies Institute, Carnegie Mellon University <sup>2</sup>Meta {jingyuah, jiongnal, voberoi, bolinw}@andrew.cmu.edu {mjagadee, karrym, chunings}@andrew.cmu.edu {arnoldov, italee}@meta.com cx@cs.cmu.edu

#### **Abstract**

Recommender systems are among the most impactful AI applications, interacting with billions of users every day, guiding them to relevant products, services, or information tailored to their preferences. However, the research and development of recommender systems are hindered by existing datasets that fail to capture realistic user behaviors and inconsistent evaluation settings that lead to ambiguous conclusions. This paper introduces the Open Recommendation Benchmark for Reproducible Research with HIdden Tests (ORBIT), a unified benchmark for consistent and realistic evaluation of recommendation models. ORBIT offers a standardized evaluation framework of public datasets with reproducible splits and transparent settings for its public leaderboard. Additionally, ORBIT introduces a new webpage recommendation task, ClueWeb-Reco, featuring web browsing sequences from 87 million public, high-quality webpages. ClueWeb-Reco is a synthetic dataset derived from real, user-consented, and privacy-guaranteed browsing data. It aligns with modern recommendation scenarios and is reserved as the hidden test part of our leaderboard to challenge recommendation models' generalization ability. ORBIT measures 12 representative recommendation models on its public benchmark and introduces a prompted LLM baseline on the ClueWeb-Reco hidden test. Our benchmark results reflect general improvements of recommender systems on the public datasets, with variable individual performances. The results on the hidden test reveal the limitations of existing approaches in large-scale webpage recommendation and highlight the potential for improvements with LLM integrations. ORBIT benchmark, leaderboard, and codebase are available at https://www.open-reco-bench.ai.

# 1 Introduction

Recommender systems are among the most pervasive and influential AI applications today, enhancing user experience by delivering customized suggestions and reducing information overload from massive sources. Additionally, recommender systems are major revenue drivers for digital services and business platforms from e-commerce to social media applications. As such, recommender systems have become indispensable to both users and service providers and continue to attract significant attention from academia [1, 2, 3, 4].

However, the progress of recommendation models in real-world settings often deviates significantly from that measured using publicly available research datasets. Many datasets rely on crawled reviews

<sup>\*</sup>Equal contribution.

and comments to approximate user action sequences, which differ substantially from other user interaction sequences in real world recommender systems (e.g., browsing and purchasing). Some are constructed without explicit user consent, raising ethical and legal concerns [5]. Even worse, the evaluation setups across recommendation research vary greatly in many perspectives: data splits, inference-time candidate pool, and metrics. As reported in many previous studies [6, 7, 8], these discrepancies make it difficult to reproduce and compare results fairly across studies, leading to ambiguity of recommender system findings and slowing the advancement in this field.

This paper introduces the **O**pen **R**ecommendation **B**enchmark for Reproducible Research with HIdden Tests (**ORBIT**), a unified benchmark designed for consistent and realistic evaluations for recommender systems. ORBIT consists of two core components that directly tackle the limitations of existing datasets and evaluation practices. First, ORBIT provides reproducible evaluation over 12 representative recommendation models across 5 widely-used public datasets using consistent data splits and metrics. Second, **ORBIT** introduces a novel webpage recommendation task on **ClueWeb-Reco**, a hidden test set derived from real U.S. browsing sequences with strong privacy safeguards. Though synthetic, ClueWeb-Reco closely mirrors real user interactions, enabling more realistic evaluation of modern recommenders than prior benchmarks. Leaderboards for both public benchmarks and the hidden test promote transparency, fair comparison, and future model advancement.

To construct ClueWeb-Reco, we first collect raw user histories in modern browsers through established human research platforms with explicit consent and carefully-designed quality control filters to remove noisy entries such as scams and inappropriate content. The collected histories are then aligned to publicly accessible documents in the ClueWeb22 dataset [9] through a semantic soft matching pipeline. This mapping process serves as a carefully crafted compromise, preserving the authentic behavioral patterns found in real browsing sequences while ensuring that the released data remains fully synthetic and privacy-safe. Our analysis shows that the matched pages remain highly relevant to the original browsing histories. Therefore, ClueWeb-Reco achieves a favorable trade-off between realism and privacy, offering the most realistic yet ethically sound data release possible.

With both the public datasets and hidden test set, ORBIT provides a comprehensive evaluation of existing recommendation models. On public benchmarks, content-based models consistently outperform traditional ID-based models by better capturing temporal dynamics and leveraging item features beyond identifiers. Despite this general trend, we also observe discrepancies in individual method performance across datasets, suggesting that training volume and data sparsity significantly influence model performance. To explore the role of Large Language Models (LLMs) in recommender systems, we introduce LLM-QueryGen, a novel baseline for the hidden ClueWeb-Reco test set that frames recommendation as retrieval via LLM-generated queries. While traditional models struggle on this realistic benchmark with large item candidate pool, LLM-QueryGen shows promising performance, highlighting LLMs' potential to capture user intent and generalize to unseen items.

To summarize, the contributions of this paper are as follows:

- Consistent benchmark for reproducible research We introduce ORBIT, a unified benchmark that ensures fair and standardized evaluation settings, and release a public leaderboard<sup>2</sup> over representative models. ORBIT provides insights into nowadays recommender systems.
- Hidden test on real-life web browsing We introduce ClueWeb-Reco<sup>3</sup>, the first recommendation benchmark task that closely reflects user interest in a realistic recommendation setting constructed with user consent and privacy guarantees.
- Holistic evaluation of recent recommender systems The ClueWeb-Reco benchmark highlights the limitations of traditional models and reveals the strong generalization ability of LLM-based query generation approaches in handling large, diverse, unseen item pools.

#### 2 Related Works

Research on recommender systems has traditionally relied on several widely used datasets, such as Amazon Review [10], Yelp [11], and MovieLens [12]. These datasets contain user reviews and/or

<sup>&</sup>lt;sup>2</sup>All experiments, data processing, benchmark construction and maintainence for this work were conducted by our team at Carnegie Mellon University. Benchmark URL: https://www.open-reco-bench.ai

<sup>&</sup>lt;sup>3</sup>The ClueWeb-Reco dataset was collected, stored, released, and is maintained by our team at Carnegie Mellon University. Dataset URL: https://huggingface.co/datasets/cx-cmu/ClueWeb-Reco

ratings collected on corresponding digital platforms and have supported a large body of work in this area. However, a major limitation is that they primarily capture *purchasing*, *commenting*, or *reviewing* behaviors, rather than the more general and frequent *viewing* behavior. Compared to *viewing*, actions like *reviewing* are extremely sparse — only observed in 1–2% of interactions, as shown in prior studies [13, 14, 15]. Moreover, such feedback often has popularity bias and fails to represent general user activity. Thus, the user-item interactions in these datasets may not truly reflect user behavior or preferences in browsing or purchasing. Furthermore, some recent datasets like PixelRec [16], Tenrec [17] and MicroLens [18] were collected without explicit user consent, raising privacy and ethics concerns.

Therefore, a key challenge to recommendation benchmarking is to curate realistic recommendation sequence data while protecting users' personally identifiable information (PII). The MSMARCO dataset in search ensures privacy by requiring that each query be issued by at least 50 users to meet legal thresholds [19]. However, this approach is unsuitable for sequential recommendation data since behavior sequences are rarely repeated across users. The TREC Conversational Assistance Track [20] addresses this by (1) manually crafting sessions from search logs (2) mapping queries in sessions to public MSMARCO queries, effectively transforming real behavior into privacy-preserving, yet realistic, sequences. These strategies provide valuable precedent for our soft matching approach in constructing realistic yet privacy-compliant evaluation data.

Other than recommendation datasets, efforts have been made to develop standardized and easy-to-use benchmarking tools. DeepRec offers a TensorFlow-based framework for early rating prediction and sequential models [21]. TorchRec [22] and EasyRec [23] focus on efficient and scalable large-scale recommendation [22]. Elliot [24] supports a variety of collaborative filtering and graph-based recommendation models, emphasizing both accuracy and novelty in evaluation metrics. RecBole [25] provides a unified environment for collaborative filtering models and sequential-based models that includes efficient data processing, standardized training and evaluation pipelines. Despite these efforts, inconsistencies in experimental setups across studies like data splits, inference-time ranking strategy (full-ranking or sampling candidates), and metrics still remain. As shown in many prior studies [6, 7, 8], different splitting methods alter the ranking of recommender systems, hindering fair comparison across studies and causing evaluation flaws.

Some studies focus on benchmarking and releasing results for recommendation models. RecBench [26] integrates large language models (LLMs) with conventional models for comparative evaluations in sequential and Click-Through Rate (CTR) prediction tasks. Meanwhile, BARS [27] stands out as the only comprehensive public leaderboard that evaluates diverse collaborative filtering models, providing standardized data processing and model reproducibility. DaisyRec [28] focuses on standardized benchmarking while optimizing settings—that influence reported performance and releases the DaisyRec 2.0 library. SCREEN [29] builds a conversational recommendation benchmark with 3 sub-tasks on 20 thousand dialogues. LLMRec [30] releases a benchmark in which LLMs are evaluated across multiple recommendation tasks like rating prediction, sequential recommendation, and direct recommendation. AgentRecBench [31] proposes an unified framework to study LLM Agent-based recommenders. However, many of the state-of-the-art LLM-based recommender are not present in any of these standard benchmarks, such as TASTE [3], HLLM [4], and LLM2Rec [32].

# 3 Public Benchmarks in ORBIT

This paper introduces **ORBIT**, a unified recommendation benchmark with standardized evaluation configurations on several public datasets and a newly-collected ClueWeb-Reco dataset based on real, up-to-date user browsing histories. This section introduces the public datasets and the evaluation strategies in the ORBIT benchmarks. The ClueWeb-Reco dataset is detailed in Section 4.

#### 3.1 Public Datasets

ORBIT currently includes five public datasets across five distinct domains, covering two major recommendation scenarios: movie recommendation and e-commerce product recommendations. These domains are prevalent in academic research and has distinctive user-item interaction patterns, providing a balanced and representative testbed for model evaluation.




Figure 1: An illustration of the collection and processing pipeline of ClueWeb-Reco. Subject inputs that pass the two quality control checks are stored and mapped to ClueWeb22 pages through a soft-matching pipeline on the right.

**MovieLens-1M** (**ML-1M**): ML-1M provides 1 million user-movie interactions with explicit ratings. Its rich metadata and moderately dense user-item matrix make it an ideal dataset for evaluating long-standing recommendation performance in the movie domain.

**Amazon Reviews:** ORBIT includes four categories: *Beauty, Toys, Sports*, and *Books*, from the Amazon Reviews 2023 dataset. These datasets represent real-world e-commerce interactions and are characterized by high sparsity and long-tail item distribution, making it valuable for evaluating models under sparse data and cold-start conditions.

These five domains are deliberately selected to strike a balance between diversity and practicality. While larger datasets such as *MovieLens-20M (ML-20M)* offer interesting modeling challenges, they were excluded in this phase due to either their extensive resource demands. Besides, we will continuously include new datasets into our public benchmarks.

### 3.2 Evaluation Settings

ORBIT frames recommendation as a sequential prediction task, where the goal is to predict the next item a user will interact with, given their historical sequence. For each dataset, the model is required to select the correct next item from the entire item pool.

Specifically, we use the standard leave-one-out splitting method on all datasets to split the data into training, validation, and test sets. For each sequence grouped by user or sessions with length n, the first n-2 items are used for training models and as user history input to for validation to predict the validation target, which is the  $(n-1)^{th}$  item. The  $n^{th}$  item is reserved as the target for the test set while the previous n-1 items are given as test input.

We report two standard metrics for top-K ranking: Recall@K and NDCG@K with  $K \in \{1, 10, 50, 100\}$ . Recall@K measures the proportion of relevant items successfully retrieved in the top-K results. Normalized Discounted Cumulative Gain (NDCG)@K accounts for the rank positions of relevant items, giving higher rewards to those ranked higher. These two metrics align closely with one-relevant-item setups over top-K performance. Notably, Recall@K is equivalent to HitRate@K in one-relevant-item setups, but is conceptually clearer as a recall-based measure.

#### 4 ClueWeb-Reco: Large-scale Webpage Recommendation

This section introduces ClueWeb-Reco, a hidden test set designed to reflect recommendation models' generalization ability on the realistic webpage recommendation task. To build this dataset, we follow a two-stage pipeline as shown in Figure 1: (1) raw user browsing history collection on established human research platforms with quality control filters; (2) webpage soft matching, replacing collected webpages with relevant ones from the public ClueWeb22 corpus to fully preserve user privacy.

#### 4.1 Webpage Recommendation Task

Given everyday life web usage, recommending relevant pages based on browsing behavior is both impactful and essential for diverse cases like Chrome browsing or online shopping. Therefore, we

aim to collect a hidden set over the webpage recommendation task, in which recommender systems predict the next webpage a user tends to visit based on their browsing histories. Despite its practical value in real-world applications such as browser content suggestions, building datasets for this task is challenging. Releasing real user histories risks exposing personally identifiable information (PII), while synthetic sequences generated by LLMs may not fully capture authentic user behavior [33, 34]. To overcome this, we release ClueWeb-Reco, a dataset constructed by matching consented, real browsing histories to public webpages in the ClueWeb22 corpus [9].

# 4.2 Raw User Browsing History Collection

The raw user browsing histories in ClueWeb-Reco dataset are collected via Amazon Mechanical Turk and Prolific.co under an exempt protocol approved by the Institutional Review Board of Carnegie Mellon University. Specifically, we ask users (referred to as subjects) to directly submit their personal browsing histories. All subjects are at least 18 years old and are located in the United States of America. The demographic distribution of the participants is detailed in Appendix A.1.

**Data collection** We acquire subjects' online consent to collect their data and to release a fully de-identified version of the collected data for research purposes, as illustrated in Appendix A.2. We state that by clicking the "agree" button in our study interface, subjects agree to give their consent to participate. Once consent is given, subjects are guided to the browsing history submission interface, where we provide instructions to clarify the submission process and to encourage subjects to submit data without PII. The submission instructions and interface are shown in Appendix A.4.

The raw user browsing history collection took 5 weeks, with 2 weeks of trial collection to determine strategies to facilitate high-quality submissions. 1,747 subjects give their consent to participate in the study (regardless of their submission status). Each submission that passes the online quality control discussed below is compensated \$0.4 as detailed in Appendix A.3.


Quality control To avoid noisy and toxic information in the collected data, we apply several filters during both the online data collection stage and the offline data processing stage. As detailed in Appendix A.5, online quality control removes scams or badly formatted data, whereas offline quality control removes inappropriate and non-informative data. We collected a total of 41,760 browsing records (URL-timpstamp pairs) from 2682 raw submissions that pass the online quality control. The offline quality control stage removes 70% of the data, leaving 1024 sessions (sequences) of 12,282 browsing records (URL-timestamp pairs). As Figure 2d shows, the average sequence length (the number of browsing records) it has is 11.99, while the longest sequence has 137 browsing records.

#### 4.3 Webpage Soft Matching

Even with explicit consent and careful guidelines for submissions free of personally identifiable information (PII), the risk of unintentional privacy leakage remains. For example, a subject may submit webpages related to local businesses, school application materials, or course-specific resources. When aggregated, these seemingly innocuous signals can inadvertently reveal subjects' PII [35].

To mitigate such risks and to mimic real-world webpage recommendation setup of recommending from a web corpus in terms of browsing sequence behavior, we replace each valid URL in the raw collected dataset with its most similar page in the English subset of ClueWeb22-B (ClueWeb22-B EN) [9], a large-scale information-rich web corpus. This mapping transforms private user histories into public websites to remove any PII or sensitive content, aligning with the privacy-preserving practices used in prior work such as the synthesis of MSMARCO conversational [19, 20].

To perform this transformation, we apply a semantic soft matching pipeline based on retrieval. Specifically, for each collected URL, we identify its most relevant document in ClueWeb22-B EN by computing semantic similarity using dense embeddings. As illustrated in Figure 1, the title and cleaned content of the ClueWeb corpus and the scraped content of the collected webpages are encoded using the MiniCPM-Embedding-Light model [36] into dense vectors. Then we build a dense retrieval index over the 87 million ClueWeb22-B EN pages using DiskANN [37], a state-of-the-art Approximate Nearest Neighbor Search (ANNS) method. For each collected URL, we search over this index to find the ClueWeb page with the highest semantic similarity. A higher score indicates stronger relevance, allowing us to select the closest public proxy for each private browsing URL.



(b) Annotated relevance (c) Annotated relevance vs. retrieval

(d) Session length

Figure 2: Subfigure 2a illustrates the distribution of the embedding retrieval scores between collected webpages and retrieved webpages. Subfigure 2b illustrates the average human-annotated relevance label (1-5) of each quantile of the ascending retrieval scores. Subfigure 2c illustrates the distribution of annotated relevance labels upon mapping created from different retrieval candidates. Subfigure 2d illustrates the distribution of the number of interactions in sessions of ClueWeb-Reco.




Figure 3: Top domain distribution before and after soft-matching. Subfigures 3a, 3b, and 3c illustrate the distribution of top-10 domains of the raw collected webpages, randomly sampled ClueWeb22-B EN webpages, and the mapped webpages in ClueWeb-Reco after soft-matching process, respectively.

Specifically, 11.07% of the collected URLs have an exact hit in ClueWeb22-B EN after normalization, which demonstrates ClueWeb22's good coverage of U.S. residents' browsing records. During the soft-matching process, we remove all these exact hits: if the Top-1 retrieved webpage has the same URL as the collected webpage, we use the next probably retrieval candidate (Top-2) as the mapped representation of the collected webpage. This technique ensures that the resulting ClueWeb-Reco dataset consists of fully synthetic sequences. We also ensure a one-to-one mapping during the soft-matching process: the same URL is mapped to the same page in ClueWeb corpus, whereas different URLs are mapped to different pages in ClueWeb corpus.

This final, released ClueWeb-Reco dataset consists of interaction sequences in terms of ClueWeb22-B EN document (webpage) IDs and is released under the MIT license. Note that to access the content (URLs, titles, full contents, etc) of these webpages, one must sign a license agreement to obtain the research-only ClueWeb22 dataset [9] with Carnegie Mellon University.

#### 4.4 Soft Matching Quality

(a) Retrieval score

The soft-matching procedure balances realism and privacy by replacing collected webpages with similar public ones. We quantify the accuracy of soft-matching using retrieval scores and human annotations to assess the relevance of the mapped sequences to understand this trade-off.

Retrieval Quality of Soft Matching. We investigate the effectiveness of soft matching through the DiskANN-calculated similarity between embeddings, referred to as the retrieval score. A higher retrieval score indicates stronger semantic similarity between the collected webpage and its mapped counterpart in ClueWeb22-B EN. Figure 2a presents the distribution of similarity scores for all mapped pairs. It is worth mentioning that DiskANN modifies the naive inner product to calculate the relevance score, so the retrieval score can be negative. We show some matching examples in Table 1, and we can observe that the retrieval score in the range of [-1, -0.5] can imply considerable semantic similarity. The distribution suggests that most collected pages have semantically close matches within ClueWeb22-B EN, supporting the viability of soft matching for representing original user real browsed webpages in a public corpus.

**Human-annotated Alignment of Soft Matching.** To further measure whether the soft-matching process preserves the user interests along the original sequences collected, 100 mappings uniformly

Table 1: The webpages from the raw collected dataset and their mapped representation in ClueWeb-Reco with embedding similarity score and averaged human-annotated relevance label.

Webpage		Retrieval Score	Label
Collected	Contemporary Music Theory - Level One: A Complete Harmony and Theory Method  https://www.amazon.com/Contemporary-Music-Theory-Complete-Musician/dp/0793598818	-0.5539	5
Retrieved	Contemporary Music Theory - Level Three: A Complete Harmony and Theory Method https://www.amazon.com/Contemporary-Music-Theory-Complete-Musician/dp/0634037366		
Collected	Cladogram Maker   Cladogram Generator   Creately https://creately.com/lp/cladogram-maker/	-0.8271	4.2
Retrieved	Organogram Template   Online Organogram Maker   Download and Share   Creately https://creately.com/lp/organogram-maker/		
Collected	(Sub) Culture Features - Rolling Stone https://www.rollingstone.com/culture/culture-features/	-0.9289	3.8
Retrieved	Rolling Stone Magazine Subscription Deals https://www.magazines.com/rolling-stone-magazine.html		
Collected	Bike Thief: r/UWMadison https://www.reddit.com/r/UWMadison/comments/1k8vfcd/bike_thief/	-1.1979	2.6
Retrieved	Madison BCycle https://madison.bcycle.com/		

Table 2: Statistics of Processed Datasets Benchmarked by ORBIT

Dataset		Dataset Inf	Split				
Dataset	#Users/Sessions	#Items	#Interactions	Sparsity	#Train	#Validation	#Test
ML-1M	6,023	3,044	995,154	94.57209%	983,110	6,022	6,022
Amzn-Beauty	254	357	2,523	97.20439%	2,029	253	253
Amzn-Sports	409,773	156,236	3,472,020	99.99458%	2,652,476	409,772	409,772
Amzn-Toys	432,265	162,036	3,861,886	99.99449%	2,997,358	432,264	432,264
Amzn-Books	776,371	495,064	9,488,297	99.99753%	7,935,557	776,370	776,370
ClueWeb-Reco	1,024	87,208,655	12,282	99.99999%	N/A	1024	1024

sampled from the ranked score distribution are annotated relevance label of 1 to 5, where 1 indicates completely irrelevant user interest and 5 indicates fully relevant user interest. The details of the human annotation process are discussed in Appendix A.6. The Cohen's kappa across the 5 annotators is 0.372, indicating moderate inter-annotators agreement, likely due to subjective interpretations of user intent revealed by webpage content. The average annotated relevance distribution with respect to the embedding similarity score is shown in Figure 2b. The observed trend confirms a positive correlation: higher retrieval scores generally correspond to higher annotated relevance. To validate the selection of the top-1 retrieved document, we compare its relevance scores with those of alternative mappings using the top-10 retrieval candidates. As shown in Figure 2c, top-1 matches consistently receive higher relevance scores, confirming they best reflect user intent among available candidates. Therefore, we keep the top-1 retrieved candidates to maximize the quality of soft matching to better preserve user behavioral patterns. Such design enables a small yet realistic dataset.

**Soft Matching Case study.** Some mappings between the collected webpages and the ClueWeb22-B EN webpages are shown in Table 1, with their corresponding retrieval scores and the average human-annotated relevance label. These mappings span different subjects and are all public. The top two rows show high-relevance mappings, where the topics of the collected and mapped webpages align very closely. Subsequent rows illustrate mid-relevance (label 3) and lower-relevance (label below 3) mappings, yet these still reflect key terms from the original URLs and represent thematically related interests. These examples indicate that even for the 20% of lower-relevance mappings, the soft-matching pipeline is still capable of preserving user intents.

**Soft Matching Trade-Off** As shown in the two relevance analysis and the case study above, the soft-matching process preserves the semantics of user behavior sequences. It offers a favorable trade-off, prioritizing user privacy protection while enabling the collection of a recommendation dataset that maximizes the representativeness of real-life scenarios.

#### 4.5 Characteristics of ClueWeb-Reco

We evaluate the dataset's realism and diversity through domain-level distribution and sparsity analysis.

**Domain distribution analysis.** We analyze the domain distribution of the collected dataset in two steps. First, as shown in Figure 3a, the collected user browsing histories span a wide range of domains, with YouTube emerging as the most frequently visited domain. Next, Figure 3c shows the domain distribution of the mapped webpages in the final ClueWeb-Reco dataset. We observe that the top domains and their rank in ClueWeb-Reco closely mirror those in the raw collected dataset. This suggests that the soft-matching process effectively preserves domain-level characteristics, providing strong evidence of domain consistency between the original and mapped datasets.

ClueWeb-Reco Sequence Case study. To high-light the complexity of user behavior captured in ClueWeb-Reco, Table 3 presents an example user sequence from the validation set. The last row shows the held-out validation target for the sequence. This sequence illustrates rapid shifts in user interest across multiple topics. While some items are topically related, others diverge significantly, emphasizing the challenge of nextitem prediction and the importance of modeling short-term and long-term user preferences.

Table 3: An example validation sequence in ClueWeb-Reco with its target in the last row.

Truncated webpage title	Domain
Amazon.com: Apple MacBook Air	www.amazon.com
Apple MacBook Pro	www.amazon.com
Online Consultation   MyHealth Clinic	www.myhealth.ph
Online Medical Consultation	telerainmd.com
Butter Pecan Cookies Recipe   Allrecipes	www.allrecipes.com
Ne-Yo - Mad (Lyrics) - YouTube	www.youtube.com
MacBook Air 13 (2019)	www.backmarket.com
MacBook Air 13 (2017)	www.backmarket.com
How buyers can cancel an order   eBay	www.ebay.com.au

Data sparsity. As shown in Table 2, ClueWeb-

Reco has extremely high sparsity, aligning with the real world cases when the recommendation model needs to predict the next item among massive candidates. ClueWeb-Reco also provides sessions with various numbers of interactions as in Figure 2d, covering both the cold-start and warm-start scenarios.

Built on real data submitted by users, the ClueWeb-Reco dataset can reflect real-world recommendation scenarios. Additionally, by aligning real browsing behavior with a public web corpus, it enables rigorous evaluation of model robustness with stringent privacy guarantees. The hidden nature of the test set further ensures protection against data leakage and promotes fair benchmarking.

# 5 Benchmarking Methods

This section outlines the models evaluated on the public and ClueWeb-Reco hidden test of ORBIT.

#### 5.1 Public Benchmark

We consider the following representative models in the public benchmark as baselines. The detailed introduction of each specific model can be found in Appendix C.

**Sequential ID-based models** Sequential ID-based models treat user behavior as a sequence of item IDs and learnt embeddings to capture transition patterns to predict the next item, which achieves promising performance even in large-scale settings. Nevertheless, they are potentially limited in generalization to cold-start items because of their sole reliance on item ID as raw item representations. ORBIT reproduces and reports the performance of the following models: GRU4REC [38], SASRec [1], Caser [39], HGN [40], STAMP [41], FDSA [42], BERT4Rec [2], S<sup>3</sup>-Rec [43], and HSTU [44].

Sequential Content-based models: Sequential content-based models enhance sequential recommendation by integrating item content features like product titles, tags, and descriptions into the modeling process. These models encode semantic representations of items, enabling more robust predictions in cold-start scenarios. ORBIT reproduces and reports the performance of the following models: SASRecF [45], TASTE [3], and HLLM [4]. We set the maximum history length to 50 for all models except 10 for HLLM due to our limited computational resources. The detailed implementation is included in ORBIT's codebase https://www.open-reco-bench.ai.

#### 5.2 ClueWeb-Reco Benchmark

We consider TASTE and HLLM trained on AmazonReview-Books as content-based baselines in the ClueWeb-Reco benchmark, since content-based models exhibit generalization ability to unseen candidate representations while ID-based models do no. We additionally introduce and evaluate LLM-QueryGen baselines on ClueWeb-Reco with GPT-3.5-Turbo [46], GPT-40, GPT-4.1 [47], Gemini-2.5-Flash [48], and Claude Sonnet 4 [49]. During LLM-QueryGen, we prompt LLMs to

Table 4: Public benchmarking results on candidate item ranking over top-10 recommended items.

Model	ML	ML-1M Ama		Amazon Beauty Ama		on Toys	Amazon Sports		Amazon Books		Average
	Recall	NDCG	Recall	NDCG	Recall	NDCG	Recall	NDCG	Recall	NDCG	NDCG
ID-based											
GRU4Rec [38]	0.2590	0.1438	0.0157	0.0065	0.0256	0.0139	0.0228	0.0120	0.0825	0.0473	0.0447
SASRec [1]	0.2001	0.0967	0.1383	0.0630	0.0428	0.0209	0.0278	0.0132	0.0758	0.0384	0.0464
Caser [39]	0.2335	0.1252	0.0237	0.0082	0.0224	0.0109	0.0129	0.0061	0.0481	0.0226	0.0346
HGN [40]	0.0621	0.0300	0.0512	0.0280	0.0357	0.0182	0.0171	0.0089	0.0626	0.0289	0.0228
STAMP [41]	0.2217	0.1256	0.1581	0.0771	0.0323	0.0200	0.0209	0.0122	0.0600	0.0381	0.0546
FDSA [42]	0.2140	0.1112	0.0909	0.0504	0.0306	0.0161	0.0262	0.0138	0.0388	0.0198	0.0423
BERT4Rec [2]	0.3072	0.1820	0.0630	0.0254	0.0305	0.0165	0.0182	0.0096	0.0554	0.0325	0.0532
S <sup>3</sup> -Rec [43]	0.3068	0.1899	0.0742	0.0297	0.0442	0.0214	0.0281	0.0144	0.0799	0.0398	0.0590
HSTU [44]	0.3236	0.1838	0.0870	0.0343	0.0401	0.0221	0.0318	0.0170	0.0672	0.0375	0.0589
Content-based											
SASRecf [45]	0.3045	0.1705	0.0830	0.0440	0.0345	0.0208	0.0267	0.0149	0.0709	0.0441	0.0589
TASTE [3]	0.2625	0.1505	0.0237	0.0122	0.0515	0.0254	0.0359	0.0183	0.0763	0.0386	0.0490
HLLM [4]	0.3205	0.1880	0.0079	0.0027	0.0659	0.0388	0.0443	0.0245	0.1107	0.0663	0.0641

Table 5: Zero-shot ClueWeb-Reco benchmarking test results on candidate item ranking.

Model	Recall@10	NDCG@10	Recall@50	NDCG@50	Recall@100	NDCG@100
TASTE [3]	0.0020	0.0015	0.0039	0.0019	0.0039	0.0019
HLLM [4]	0.0088	0.0041	0.0137	0.0052	0.0176	0.0059
GPT-3.5-Turbo-QueryGen	0.0088	0.0058	0.0156	0.0073	0.0254	0.0089
GPT-4o-QueryGen	0.0068	0.0027	0.0176	0.0050	0.0312	0.0072
Gemini-2.5-Flash-QueryGen	0.0068	0.0042	0.0146	0.0058	0.0264	0.0077
GPT-4.1-QueryGen	0.0107	0.0050	0.0195	0.0068	0.0254	0.0077
Claude-Sonnet-4-QueryGen	0.0068	0.0032	0.0166	0.0052	0.0215	0.0060
DeepSeek-V3-QueryGen	0.0127	0.0082	0.0264	0.0111	0.0371	0.0129
Kimi-K2-QueryGen	0.0039	0.0022	0.0156	0.0050	0.0234	0.0062
Llama-4-Maverick-QueryGen	0.0029	0.0015	0.0088	0.0028	0.0205	0.0047
Qwen3-235B-QueryGen	0.0088	0.0046	0.0234	0.0077	0.0303	0.0088

generate a query based on the interaction history verbalized by interacted webpage titles. We then retrieve the closest webpage from ClueWeb22-B EN as the prediction of LLM-QueryGen using an ANN-index. The full procedure and the prompt template we use are discussed in Appendix D.

#### 6 Benchmark Results

In this section, we showcase ORBIT's public benchmark and its ClueWeb-Reco hidden test results, followed by a discussion of the performance and potential of current recommender systems.

#### 6.1 Public Benchmarks

We release benchmarking results for 12 models on 5 public recommendation datasets described in Section 3.1. Table 4 presents Recall@10 and NDCG@10 results, with key observations below:

- (1) We witness a consistent performance gain in sequential-based ID-based models through their evolution from RNN-based architecture to transformer architecture due to the attention-based structure is better at discovering long-term behavior patterns and user interests.
- (2) Content-based models such as SASRecf and TASTE achieve better performance in general compared with ID-based models, especially in the highly sparse datasets like Amazon Books. One reason is that content-based recommendation models can utilize more meta-information of items to build more accurate user profiles and lead to better next-item predictions.
- (3) The hierarchical LLM recommendation model HLLM achieves the state-of-the-art performance overall, which shows that leveraging LLMs to build item and user representations benefits the recommendation performance. However, it has poor performance in Amazon Beauty as the small training set is insufficient for tuning the billion-scale architecture.

#### 6.2 ClueWeb-Reco Hidden Test

The ClueWeb-Reco hidden test result is shown in Table 5. We have the following observations:

- (1) Among content-based baselines trained in the same vertical domain, HLLM generalizes much better than TASTE, likely due to its stronger LLM backbone and hierarchical architecture, which more effectively capture contextual signals.
- (2) The proposed LLM-QueryGen baselines show strong predictive performance, matching or surpassing HLLM. DeekSeek achieves the highest Recall@10 and consistently strong NDCG across all cutoffs, despite the zero-shot evaluation and the challenges of ClueWeb-Reco's broad user interactions and large candidate pool.
- (3) The results also reveal that different LLMs offer distinct trade-offs between top-rank precision (NDCG@10) and deep-level recall (Recall@100), which could guide practical model selection depending on application focus.

Table 6: Example queries generated by different LLMs and their corresponding NDCG@10.

Target Webpage Title Truncated	Model	Generated Query	NDCG@10
Amazon.com: phone ring	Gemini-2.5-Flash	best phone ring holder	0.3333
	GPT-40	cute and durable iPhone accessories for women	0.0000
	GPT-3.5-Turbo	unique phone accessories for girls	0.0000
	GPT-4.1-QueryGen	best phone accessories for iPhone 13 girls cute design	0.0000
	Claude-Sonnet-4-QueryGen	phone accessories bundle deals	0.0000
Last of Us 2 Timeline: How Ellie & Abby	Gemini-2.5-Flash GPT-40 GPT-3.5-Turbo GPT-4.1-QueryGen Claude-Sonnet-4-QueryGen	Last of Us fanfiction Predator franchise timeline and connections Predator movie series chronological order the last of us 2 ellie and dina relationship explained post-apocalyptic survival games like The Last of Us	0.0000 0.0000 0.0000 <b>0.3562</b> 0.0000
Minecraft   10 Medieval Build Ideas and Hacks	Gemini-2.5-Flash	minecraft epic medieval builds	0.2891
	GPT-40	medieval-themed Minecraft build ideas	<b>0.3562</b>
	GPT-3.5-Turbo	medieval village building tips	0.0000
	GPT-4.1-QueryGen	minecraft medieval magic base ideas	0.0000
	Claude-Sonnet-4-QueryGen	minecraft medieval building materials guide	0.0000

**LLM-QueryGen Case study** Table 6 shows example predictions made by the three LLM-QueryGen baselines over the validation set of ClueWeb-Reco. The full sequence of the example in the first row is shown in Table 7. While Gemini correctly captures the user interest on "ring holder", the queries generated by other LLMs are rather broad. In the second example, GPT-40 and GPT-3.5-Turbo mistakenly focuses on the Predator movie, which appears at the early part of the session history, instead of the latest user interest over the Last of Us TV series. In the third example, GPT-3.5-Turbo misses the main concept of the game "Minecraft", resulting in degraded performance compared to other LLMs. More examples included in Appendix F show the varying performance of the LLMs as query generators in different sequences. Yet in general, state-of-the-art LLMs show higher reliability and stability over prior LLMs on generating relevant queries to the users' interest. Overall, these examples reveal the LLM's potential to capture user interests and shed light on future research that better integrate or instruct LLMs in recommendation tasks.

# 7 Limitations

ORBIT covers limited models and datasets, with plans to incorporate more public datasets and recent LLM-based recommenders like LLM2Rec [32], Molar [50], and LLMRec [51]. As an open benchmark, its impact relies on community participation, and we invite contribution and extension. ClueWeb-Reco currently focuses on U.S. user interactions; community submissions to its hidden test will help validate data authenticity and guide future expansion toward a larger supervised dataset.

#### 8 Conclusions

ORBIT provides the recommender system community with a more comprehensive evaluation strategy to better reflect model performance in the large, diverse candidate pool in the real world. We would like to call for participation in submitting model predictions to our open leaderboards to expand the model coverage of ORBIT. In the future, we aim to expand our public benchmark to cover more public recommendation datasets and continue our established data collection pipeline to construct more realistic recommendation benchmarks.

# 9 Acknowledgments

We would like to thank Lee Xiong, Tianchuan Du for their valuable feedback on the paper. We also acknowledge Meta Platforms, Inc for funding for the dataset collection and the RecBole team building and maintaining RecBole [25], which serves an important role for our model evaluation experiments.

#### References

- [1] Wang-Cheng Kang and Julian McAuley. Self-attentive sequential recommendation. In 2018 *IEEE international conference on data mining (ICDM)*, pages 197–206. IEEE, 2018.
- [2] Fei Sun, Jun Liu, Jian Wu, Changhua Pei, Xiao Lin, Wenwu Ou, and Peng Jiang. Bert4rec: Sequential recommendation with bidirectional encoder representations from transformer. In *Proceedings of the 28th ACM international conference on information and knowledge management*, pages 1441–1450, 2019.
- [3] Zhenghao Liu, Sen Mei, Chenyan Xiong, Xiaohua Li, Shi Yu, Zhiyuan Liu, Yu Gu, and Ge Yu. Text matching improves sequential recommendation by reducing popularity biases. In *Proceedings of the 32nd ACM International Conference on Information and Knowledge Management*, pages 1534–1544, 2023.
- [4] Junyi Chen, Lu Chi, Bingyue Peng, and Zehuan Yuan. Hllm: Enhancing sequential recommendations via hierarchical large language models for item and user modeling, 2024.
- [5] Yitong Ji, Aixin Sun, Jie Zhang, and Chenliang Li. A critical study on data leakage in recommender system offline evaluation. *ACM Transactions on Information Systems*, 41(3):1–27, 2023.
- [6] Steffen Rendle, Li Zhang, and Yehuda Koren. On the difficulty of evaluating baselines: A study on recommender systems. arXiv preprint arXiv:1905.01395, 2019.
- [7] Zaiqiao Meng, Richard McCreadie, Craig Macdonald, and Iadh Ounis. Exploring data splitting strategies for the evaluation of recommendation models. In *Proceedings of the 14th acm conference on recommender systems*, pages 681–686, 2020.
- [8] Balázs Hidasi and Ádám Tibor Czapp. Widespread flaws in offline evaluation of recommender systems. In *Proceedings of the 17th acm conference on recommender systems*, pages 848–855, 2023.
- [9] Arnold Overwijk, Chenyan Xiong, Xiao Liu, Cameron VandenBerg, and Jamie Callan. Clueweb22: 10 billion web documents with visual and semantic information. *arXiv preprint arXiv:2211.15848*, 2022.
- [10] Julian McAuley, Christopher Targett, Qinfeng Shi, and Anton Van Den Hengel. Image-based recommendations on styles and substitutes. In *Proceedings of the 38th international ACM SIGIR conference on research and development in information retrieval*, pages 43–52, 2015.
- [11] Yelp. The yelp dataset, 2021. Accessed: April 26, 2025.
- [12] F. Maxwell Harper and Joseph A. Konstan. The movielens datasets: History and context. *ACM Transactions on Interactive Intelligent Systems (TiiS)*, 5(4):Article 19, 19 pages, December 2015.
- [13] A deep dive into amazon consumer review statistics, 2022. Accessed: 2025-05-01.
- [14] Jiefei Yu, Yanqing Hu, Min Yu, and Zengru Di. Analyzing netizens' view and reply behaviors on the forum. *Physica A: Statistical Mechanics and its Applications*, 389(16):3267–3273, 2010.
- [15] Maria Glenski and Tim Weninger. Predicting user-interactions on reddit. In Jana Diesner, Elena Ferrari, and Guandong Xu, editors, *Proceedings of the 2017 IEEE/ACM International Conference on Advances in Social Networks Analysis and Mining 2017, Sydney, Australia, July 31 August 03, 2017*, pages 609–612. ACM, 2017.

- [16] Yu Cheng, Yunzhu Pan, Jiaqi Zhang, Yongxin Ni, Aixin Sun, and Fajie Yuan. An image dataset for benchmarking recommender systems with raw pixels. In *Proceedings of the 2024 SIAM International Conference on Data Mining (SDM)*, pages 418–426. SIAM, 2024.
- [17] Guanghu Yuan, Fajie Yuan, Yudong Li, Beibei Kong, Shujie Li, Lei Chen, Min Yang, Chenyun Yu, Bo Hu, Zang Li, et al. Tenrec: A large-scale multipurpose benchmark dataset for recommender systems. Advances in Neural Information Processing Systems, 35:11480–11493, 2022.
- [18] Yongxin Ni, Yu Cheng, Xiangyan Liu, Junchen Fu, Youhua Li, Xiangnan He, Yongfeng Zhang, and Fajie Yuan. A content-driven micro-video recommendation dataset at scale. CoRR, abs/2309.15379, 2023.
- [19] Payal Bajaj, Daniel Campos, Nick Craswell, Li Deng, Jianfeng Gao, Xiaodong Liu, Rangan Majumder, Andrew McNamara, Bhaskar Mitra, Tri Nguyen, et al. Ms marco: A human generated machine reading comprehension dataset. *arXiv preprint arXiv:1611.09268*, 2016.
- [20] Jeffrey Dalton, Chenyan Xiong, and Jamie Callan. Trec cast 2019: The conversational assistance track overview. *arXiv preprint arXiv:2003.13624*, 2020.
- [21] Shuai Zhang, Yi Tay, Lina Yao, Bin Wu, and Aixin Sun. Deeprec: An open-source toolkit for deep learning based recommendation. arXiv preprint arXiv:1905.10536, 2019.
- [22] Dmytro Ivchenko, Dennis Van Der Staay, Colin Taylor, Xing Liu, Will Feng, Rahul Kindi, Anirudh Sudarshan, and Shahin Sefati. Torchrec: a pytorch domain library for recommendation systems. In *Proceedings of the 16th ACM Conference on Recommender Systems*, RecSys '22, page 482–483, New York, NY, USA, 2022. Association for Computing Machinery.
- [23] Mengli Cheng, Yue Gao, Guoqiang Liu, Hongsheng Jin, and Xiaowen Zhang. Easyrec: An easy-to-use, extendable and efficient framework for building industrial recommendation systems. *ArXiv*, abs/2209.12766, 2022.
- [24] Vito Walter Anelli, Alejandro Bellogín, Antonio Ferrara, Daniele Malitesta, Felice Antonio Merra, Claudio Pomo, Francesco Maria Donini, and Tommaso Di Noia. Elliot: A comprehensive and rigorous framework for reproducible recommender systems evaluation. In *Proceedings of the 44th international ACM SIGIR conference on research and development in information retrieval*, pages 2405–2414, 2021.
- [25] Wayne Xin Zhao, Shanlei Mu, Yupeng Hou, Zihan Lin, Yushuo Chen, Xingyu Pan, Kaiyuan Li, Yujie Lu, Hui Wang, Changxin Tian, et al. Recbole: Towards a unified, comprehensive and efficient framework for recommendation algorithms. In proceedings of the 30th acm international conference on information & knowledge management, pages 4653–4664, 2021.
- [26] Qijiong Liu, Jieming Zhu, Lu Fan, Kun Wang, Hengchang Hu, Wei Guo, Yong Liu, and Xiao-Ming Wu. Benchmarking llms in recommendation tasks: A comparative evaluation with conventional recommenders. *arXiv preprint arXiv:2503.05493*, 2025.
- [27] Jieming Zhu, Quanyu Dai, Liangcai Su, Rong Ma, Jinyang Liu, Guohao Cai, Xi Xiao, and Rui Zhang. Bars: Towards open benchmarking for recommender systems. In *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 2912–2923, 2022.
- [28] Zhu Sun, Hui Fang, Jie Yang, Xinghua Qu, Hongyang Liu, Di Yu, Yew-Soon Ong, and Jie Zhang. Daisyrec 2.0: Benchmarking recommendation for rigorous evaluation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 45(7):8206–8226, 2022.
- [29] Dongding Lin, Jian Wang, Chak Tou Leong, and Wenjie Li. Screen: A benchmark for situated conversational recommendation. In *Proceedings of the 32nd ACM International Conference on Multimedia*, MM '24, page 9591–9600, New York, NY, USA, 2024. Association for Computing Machinery.
- [30] Junling Liu, Chao Liu, Peilin Zhou, Qichen Ye, Dading Chong, Kang Zhou, Yueqi Xie, Yuwei Cao, Shoujin Wang, Chenyu You, et al. Llmrec: Benchmarking large language models on recommendation task. *arXiv preprint arXiv:2308.12241*, 2023.

- [31] Yu Shang, Peijie Liu, Yuwei Yan, Zijing Wu, Leheng Sheng, Yuanqing Yu, Chumeng Jiang, An Zhang, Fengli Xu, Yu Wang, et al. Agentrecbench: Benchmarking llm agent-based personalized recommender systems. *arXiv preprint arXiv:2505.19623*, 2025.
- [32] Yingzhi He, Xiaohao Liu, An Zhang, Yunshan Ma, and Tat-Seng Chua. Llm2rec: Large language models are powerful embedding models for sequential recommendation. In *Proceedings of the* 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V. 2, pages 896–907, 2025.
- [33] Mihai Nadas, Laura Diosan, and Andreea Tomescu. Synthetic data generation using large language models: Advances in text and code. arXiv preprint arXiv:2503.14023, 2025.
- [34] Yue Yu, Yuchen Zhuang, Jieyu Zhang, Yu Meng, Alexander J Ratner, Ranjay Krishna, Jiaming Shen, and Chao Zhang. Large language model as attributed training data generator: A tale of diversity and bias. *Advances in Neural Information Processing Systems*, 36:55734–55784, 2023.
- [35] Michael Barbaro, Tom Zeller, and Saul Hansell. A face is exposed for aol searcher no. 4417749. *New York Times*, 9(2008):8, 2006.
- [36] Shengding Hu, Yuge Tu, Xu Han, Chaoqun He, Ganqu Cui, Xiang Long, Zhi Zheng, Yewei Fang, Yuxiang Huang, Weilin Zhao, et al. Minicpm: Unveiling the potential of small language models with scalable training strategies. *arXiv preprint arXiv:2404.06395*, 2024.
- [37] Suhas Jayaram Subramanya, Fnu Devvrit, Harsha Vardhan Simhadri, Ravishankar Krishnawamy, and Rohan Kadekodi. Diskann: Fast accurate billion-point nearest neighbor search on a single node. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, Advances in Neural Information Processing Systems, volume 32. Curran Associates, Inc., 2019.
- [38] Yong Kiam Tan, Xinxing Xu, and Yong Liu. Improved recurrent neural networks for session-based recommendations. In *Proceedings of the 1st Workshop on Deep Learning for Recommender Systems*, DLRS 2016, page 17–22, New York, NY, USA, 2016. Association for Computing Machinery.
- [39] Jiaxi Tang and Ke Wang. Personalized top-n sequential recommendation via convolutional sequence embedding. In *Proceedings of the Eleventh ACM International Conference on Web Search and Data Mining*, WSDM '18, page 565–573, New York, NY, USA, 2018. Association for Computing Machinery.
- [40] Chen Ma, Peng Kang, and Xue Liu. Hierarchical gating networks for sequential recommendation. In *Proceedings of the 25th ACM SIGKDD international conference on knowledge discovery & data mining*, pages 825–833, 2019.
- [41] Qiao Liu, Yifu Zeng, Refuoe Mokhosi, and Haibin Zhang. Stamp: Short-term attention/memory priority model for session-based recommendation. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, KDD '18, page 1831–1839, New York, NY, USA, 2018. Association for Computing Machinery.
- [42] Tingting Zhang, Pengpeng Zhao, Yanchi Liu, Victor S. Sheng, Jiajie Xu, Deqing Wang, Guanfeng Liu, and Xiaofang Zhou. Feature-level deeper self-attention network for sequential recommendation. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI-19*, pages 4320–4326. International Joint Conferences on Artificial Intelligence Organization, 7 2019.
- [43] Kun Zhou, Hui Wang, Wayne Xin Zhao, Yutao Zhu, Sirui Wang, Fuzheng Zhang, Zhongyuan Wang, and Ji-Rong Wen. S^3-rec: Self-supervised learning for sequential recommendation with mutual information maximization. *CoRR*, abs/2008.07873, 2020.
- [44] Jiaqi Zhai, Lucy Liao, Xing Liu, Yueming Wang, Rui Li, Xuan Cao, Leon Gao, Zhaojie Gong, Fangda Gu, Jiayuan He, Yinghai Lu, and Yu Shi. Actions speak louder than words: Trillion-parameter sequential transducers for generative recommendations. In Ruslan Salakhutdinov, Zico Kolter, Katherine Heller, Adrian Weller, Nuria Oliver, Jonathan Scarlett, and Felix

- Berkenkamp, editors, *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pages 58484–58509. PMLR, 21–27 Jul 2024.
- [45] Hyungtaik Oh, Wonkeun Jo, and Dongil Kim. Attention-based sequential recommendation system using multimodal data, 2024.
- [46] OpenAI. Chatgpt. https://openai.com/blog/chatgpt, 2023.
- [47] Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.
- [48] Gemini Team, Rohan Anil, Sebastian Borgeaud, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, Katie Millican, et al. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*, 2023.
- [49] Anthropic. Claude sonnet 4. https://www.anthropic.com/claude-4-system-card, 2025.
- [50] Yucong Luo, Qitao Qin, Hao Zhang, Mingyue Cheng, Ruiran Yan, Kefan Wang, and Jie Ouyang. Molar: Multimodal llms with collaborative filtering alignment for enhanced sequential recommendation. *arXiv* preprint arXiv:2412.18176, 2024.
- [51] Wei Wei, Xubin Ren, Jiabin Tang, Qinyong Wang, Lixin Su, Suqi Cheng, Junfeng Wang, Dawei Yin, and Chao Huang. Llmrec: Large language models with graph augmentation for recommendation. In *Proceedings of the 17th ACM international conference on web search and data mining*, pages 806–815, 2024.

# **NeurIPS Paper Checklist**

#### 1. Claims

Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

Answer: [Yes]

Justification: We define the scope of our work and contributions in abstract and introduction. Guidelines:

- The answer NA means that the abstract and introduction do not include the claims made in the paper.
- The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A No or NA answer to this question will not be perceived well by the reviewers.
- The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
- It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

#### 2. Limitations

Question: Does the paper discuss the limitations of the work performed by the authors?

Answer: [Yes]

Justification: We include the potential future work in the Section 8 and an explicit limitation discussion in Appendix 7.

#### Guidelines:

- The answer NA means that the paper has no limitation while the answer No means that the paper has limitations, but those are not discussed in the paper.
- The authors are encouraged to create a separate "Limitations" section in their paper.
- The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
- The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
- The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
- The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
- If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
- While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

# 3. Theory assumptions and proofs

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [NA]

Justification: This work involves no theoretical proof.

#### Guidelines:

- The answer NA means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and crossreferenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

# 4. Experimental result reproducibility

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [Yes]

Justification: We provide implementation details of all experiments and evaluation in our Github reporsitory<sup>4</sup>. The evaluation metrics we used are described in 3.2.

#### Guidelines:

- The answer NA means that the paper does not include experiments.
- If the paper includes experiments, a No answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general, releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
  - (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
- (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
- (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
- (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

#### 5. Open access to data and code

<sup>&</sup>lt;sup>4</sup>https://github.com/cxcscmu/RecSys-Benchmark

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: [Yes]

Justification: We provide codes to reproduce the results in ORBIT benchmark at our official Github repository <sup>5</sup>, which is also available at ORBIT site <sup>6</sup>.

#### Guidelines:

- The answer NA means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (https://nips.cc/public/guides/CodeSubmissionPolicy) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so "No" is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (https://nips.cc/public/guides/CodeSubmissionPolicy) for more details.
- The authors should provide instructions on data access and preparation, including how
  to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

# 6. Experimental setting/details

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer, etc.) necessary to understand the results?

Answer: [Yes]

Justification: We provide implementation details of all experiments and evaluation in our Github repository<sup>7</sup>. The evaluation metrics we used are described in 3.2.

#### Guidelines:

- The answer NA means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
- The full details can be provided either with the code, in appendix, or as supplemental material.

# 7. Experiment statistical significance

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [No]

Justification: As a benchmark paper our main goal is to provide a standardized evaluation platform. Our baseline measures are mainly for reference and we will welcome communities to submit their entries which will provide a holistic view of results.

#### Guidelines:

• The answer NA means that the paper does not include experiments.

<sup>&</sup>lt;sup>5</sup>https://github.com/cxcscmu/RecSys-Benchmark

<sup>&</sup>lt;sup>6</sup>https://www.open-reco-bench.ai

<sup>&</sup>lt;sup>7</sup>https://github.com/cxcscmu/RecSys-Benchmark

- The authors should answer "Yes" if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g. negative error rates).
- If error bars are reported in tables or plots, The authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

#### 8. Experiments compute resources

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

Answer: [Yes]

Justification: We provide the experiment environment in Appendix E.

#### Guidelines:

- The answer NA means that the paper does not include experiments.
- The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
- The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
- The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

# 9. Code of ethics

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics https://neurips.cc/public/EthicsGuidelines?

Answer: [Yes]

Justification: First, this work is conducted under an exempt protocol approved by the Institutional Review Board of Carnegie Mellon University, as we discussed in 4.2. Second, we provide detailed instructions and user consents for users to submit data free of personally identifiable information, detailed in Section 4.2, Appendix A.2 and A.4. We ensure fair wages for subjects (crowdworkers) as explained in Appendix A.3. Finally, we map the raw collected user data to public webpages in public datasets through a soft matching pipeline discussed in Section 4.3 to fully protect subject privacy.

#### Guidelines:

- The answer NA means that the authors have not reviewed the NeurIPS Code of Ethics.
- If the authors answer No, they should explain the special circumstances that require a deviation from the Code of Ethics.
- The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

# 10. Broader impacts

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: [Yes]

Justification: This paper discusses the positive impact ClueWeb-Reco over recommendation system development and the resulting user experience improvement over Section 1. The possible negative societal impact is included in the Appendix A.2 regarding the potential risk of a breach of confidentiality.

#### Guidelines:

- The answer NA means that there is no societal impact of the work performed.
- If the authors answer NA or No, they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

# 11. Safeguards

Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pretrained language models, image generators, or scraped datasets)?

Answer: [Yes]

Justification: We discuss a soft matching pipeline that address privay concern in Section 4.3.

#### Guidelines:

- The answer NA means that the paper poses no such risks.
- Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
- Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
- We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

#### 12. Licenses for existing assets

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: [Yes]

Justification: We properly present and cite existing public datasets and models in Section 3.1 and Section 5.1, respectively. The detailed asset license discussion is included in Appendix G.1.

#### Guidelines:

- The answer NA means that the paper does not use existing assets.
- The authors should cite the original paper that produced the code package or dataset.
- The authors should state which version of the asset is used and, if possible, include a URL.
- The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the
  package should be provided. For popular datasets, paperswithcode.com/datasets
  has curated licenses for some datasets. Their licensing guide can help determine the
  license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

#### 13. New assets

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: [Yes]

Justification: We introduce two assets: (1) ORBIT Public Benchmark; (2) ClueWeb-Reco dataset. The ORBIT Benchmark <sup>8</sup> includes full documentation about the public benchmark datasets, ClueWeb-Reco dataset, and experiments we perform on them. The ClueWeb-Reco dataset <sup>9</sup> released over Huggingface contains the dataset preview and statistics, alone with documentations over dataset usage. We state ORBIT's license in the introduction of Section 3. We introduce the license of the new ClueWeb-Reco dataset at the end of Section 4.3. Detailed license discussion over these two newly introduced assets are stated in Appendix G.2.

# Guidelines:

- The answer NA means that the paper does not release new assets.
- Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
- The paper should discuss whether and how consent was obtained from people whose asset is used.
- At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

#### 14. Crowdsourcing and research with human subjects

Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer: [Yes]

Justification: We present the crowdsourcing data collection process in Section 4.2 and include the full version of the consents and instructions and in Appendix A.2 and A.4. The human subject compensation details are explained in Appendix A.3.

#### Guidelines:

<sup>8</sup>https://www.open-reco-bench.ai/

<sup>&</sup>lt;sup>9</sup>https://huggingface.co/datasets/cx-cmu/ClueWeb-Reco

- The answer NA means that the paper does not involve crowdsourcing nor research with human subjects.
- Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
- According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

# 15. Institutional review board (IRB) approvals or equivalent for research with human subjects

Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

Answer: [Yes]

Justification: This work is conduct under an exempt protocol approved by the Institutional Review Board of Carnegie Mellon University as we discussed in 4.2. The study ID of this protocol is: STUDY2025\_00000079.

#### Guidelines:

- The answer NA means that the paper does not involve crowdsourcing nor research with human subjects.
- Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
- We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
- For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

#### 16. Declaration of LLM usage

Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does not impact the core methodology, scientific rigorousness, or originality of the research, declaration is not required.

Answer: [Yes]

Justification: We describe the usage of LLMs as baselines for the proposed benchmark in Section 5.2.

#### Guidelines:

- The answer NA means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
- Please refer to our LLM policy (https://neurips.cc/Conferences/2025/LLM) for what should or should not be described.

# A ClueWeb-Reco Collection

# A.1 Demography




Figure 4: Demography distribution of the raw collected dataset for ClueWeb-Reco.

The demographic information of the subject of ClueWeb-Reco is shown in Figure 4. The submission of demographic information is voluntary and completely anonymous. Overall, the demography information depicts an adult population who has completed high school education or more. The subject represents a population of a broad ethnic background, except for Asians. Overall, we can say that the collected data is able to represent the U.S. Internet users and their interests of browsing.

#### A.2 Subject Consent and Privacy

**Subject Consent** We provide an explicit consent form for the subject in the online entry of our study. The consent form attaches an official consent document with its main point summarized and printed in the study interface. We state that by clicking the "agree" button and continue to the study, subjects agree to give consent to participate in this study. Below we attach the Confidentiality and the Voluntary Participation sections of our consent form.

- **Risks** The risks and discomfort associated with participation in this study are no greater than those ordinarily encountered in daily life or during other online activities. The research team will not save any links non-accessible to avoid personal webpages. Yet there remains the risk of possible information identification to the research team if the submitted URLs contain any identifiable information. The collected URLs will be further processed to be fully de-identified before any possible release.
- Confidentiality By participating in this research, you understand and agree that Carnegie Mellon may be required to disclose your consent form, data and other personally identifiable information as required by law, regulation, subpoena or court order. Otherwise, your confidentiality will be maintained in the following manner: Your data and consent form will be kept separate. Any paper files will be stored in a secure location on Carnegie Mellon property and all digital files will be stored under Carnegie Mellon control. By participating, you understand and agree that the data and information gathered during this study may

be used by Carnegie Mellon and published and/or disclosed by Carnegie Mellon to others outside of Carnegie Mellon. However, your name, address, contact information and other direct personal identifiers will not be mentioned in any such publication or dissemination of the research data and/or results by Carnegie Mellon. Note that per regulation all research data must be kept for a minimum of 3 years. The URL data you submitted will be kept confidential. If distributed, all identifiable information in the data will be removed. The sponsor of this study (Meta Platforms, Inc.) may obtain access to the copy of de-identifiable data and research records. Third-Party Confidentiality: The study will collect your research data through your use of Prolific.co/Amazon Mechanical Turk and Vercel Neon database. These companies are not owned by CMU. The companies will have access to the research data that you produce and any identifiable information that you share with them while using their product. Please note that Carnegie Mellon does not control the Terms and Conditions of the companies or how they will use or protect any information that they collect.

• Voluntary Participation Your participation in this research is voluntary. You may discontinue participation at any time during the research activity. You may print a copy of this consent form for your records. By continuing to the web interface of this study, you agree that the above information has been explained to you and all your current questions have been answered. You are encouraged to ask questions about any aspect of this research study during the course of the study and in the future.

**Subject Privacy Protection** A mapping between the worker ID of Amazon Mechanical Turk or Prolific.co and this unique random identifier of a subject is stored for subject participation reward purposes. The mapping is deleted once the compensation is forwarded. Each sequence the subject submits for a unique day represents a user browsing session and is assigned a randomly generated, unique 32-character string as their identifier. All content stored and processed is under this random identifier. Any links containing personal information are inaccessible or contain error/login keywords and will not be stored in our database or will be removed from the database during post-processing.

#### A.3 Subject Compensation

The equivalent \$4 of cash is compensated to subjects through the human study platform the subject completed the study (Amazon Mechanical Turk and Prolific.co) for 10 valid submissions that pass the online quality control discussed in Section 4.2. A single valid submission (passes the online quality control) is prorated for \$0.4. The compensation is rewarded in U.S. dollars. Depending on whether the submissions are valid and the number of submissions made, the study can take 10-30 minutes for each subject. The estimated hourly rate of the study is \$8 per hour.

#### A.4 ClueWeb-Reco Data Collection Procedure


To ensure the collected data reflects realistic, contemporary user behavior while protecting privacy from the start, we instruct subjects to follow these submission guidelines:

- 1. Submit URLs that do not contain or link to personal information;
- 2. Ensure the URLs link to English-language webpages;
- 3. Submit URLs corresponding to actual browsing activity within the past year.
- 4. Prefer URLs related to entertainment content where possible.

We provide subjects with two means of submissions as described below:

- Manual Fill Subjects are instructed to copy and paste 15 URLs and their corresponding timestamps, marked by hour and minute, one by one, into the submission box.
- Edge Browser Export We provide step-by-step instructions on exporting Edge browsing history. Subjects are asked to copy and paste 20 to 30 records (containing URL and visited timestamp) from the exported data into the submission box.

The two submission interface are shown in Figure 5. Edge Browser Export submission interface allows Edge users to submit chunks of browsing history more efficiently. We did not include a specific submission interface for Chrome because of the various formats of the exported browsing history



(a) Edge Browser Export Submission interface

(b) Manual Fill Submission Interface

Figure 5: The two interfaces through which subjects submit their browsing data. The Edge Browser Export contains detailed instructions on how to properly export the browsing history file from Edge.

on different versions of Chrome. The users of Chrome and other browsers and use the Manual Fill submission interface to complete the study. 45% of the subject submissions came from Edge Browser Export submission interface and the reset 55% came from the Manual Fill submission interface.


# A.5 Quality Control

Despite careful instructions, user-submitted sequences may contain noisy and toxic information. To improve the quality of user data, we apply several data filtering and selection manipulations in both the online data collection stage and the offline data processing stage.

Online Quality Control. When subjects submit their browsing history, we impose online checks to filter out scam or non-informative URLs and sequences. A pair of URL and its visited timestamp is considered valid to submit if it: (1) URL is a valid URL and timestamp is a valid time within 1-year's time frame in the past; (2) URL links to a publicly accessible webpage that properly handle requests; (3) URL links to neither a landing page nor a search-engine generated page upon user query; (4) is an English page; (5) passes our anti-scam checks on repeated submissions. A submission will pass and only be stored in our database if it contains at least 10 valid URL-timestamp pairs, as shown in the left half of Figure 1.

**Offline Quality Control.** After the online filtering, we manually check the browsing sequences to remove the following sequences or URL-timestamp pairs from our data storage offline to further improve the data quality:

- Scam submission: The most common scams are: (1) the URLs in the submission sequence has the same domains as other submission sequences in exact order; (2) the URLs in a submission sequence are from a single domain, with path names following alphabetical order; (3) the timestamps in a submission sequence are all the same or follow a fixed interval.
- Inappropriate content: a URL-timestamp pair is inappropriate if the URL links to a page containing violent, pornographic content, or promotes hate, harassment, or other forms of harmful behavior.
- Non-informative: Non-informative submissions we saw mainly fall into the following two categories: (1) the submitted URLs contain inaccessible personal content with login instructions not detected during the online-processing stage; (2) the submitted URLs link to online survey or studies; (3) the URLs in the sequences link to steps in an online game that with poor content variation.



(a) Correlation of relevance labels.

(b) Cohen's kappa coefficients.

Figure 6: Correlation and Cohen's Kappa of the relevance labels given by the 5 annotators. The figures demonstrates high correlation and moderate alignment between annotators, revealing the subjective nature of human relevance annotation.

Subsequently, we represent the remaining valid URL records with the webpages they link to and employ keyword filtering on the scraped pages to further remove non-English, and non-informative webpages. Any submitted sequences with fewer than 5 URL-timestamp pairs are removed.

#### A.6 ClueWeb-Reco Relevance Annotation

During the human annotation process, we sample 100 mappings uniformly from 100 buckets in the retrieval score distribution of a Top-1 retrieval scheme. We recruit 5 annotators to rate the quality of mappings on the scale of 1 to 5, where 1 indicates no relevance between the original webpage and the retrieved webpage and 5 indicates fully relevance between the original webpage and the retrieved webpage. Annotators are instructed to define webpage relevance by whether or not they depict the same user interest.

We showcase the pearson correlation of the relevance labels and the Cohen's kappa coefficients among annotations in Figure 6a. Overall, the annotators' judgments are consistent with moderate agreement upon the relevance of the raw collected webpages and the mapped webpages by the soft-matching pipeline. Consider the subjectivity over whether or not a mapping preserves user interest, this level of agreement can suggest that the relevance labels are meaningful in depicting whether or not the soft-matching pipeline is effective.

# **B** ClueWeb-Reco Sequence

Table 7 shows a sequence of product browsing pages in the validation set of ClueWeb-Reco with the prediction target in the last row. Although most webpages in this session lay in Amazon, the user interest is rapidly pivoting between several loosely-connected product categories (e.g. phone case, backpack, charge adapter, phone ring holder). These categorical user interest each has varying numbers of browsing records (interactions) that are closely related, demonstrating complex, realistic user behaviors.

# C Model Introduction

#### **Sequential ID-based models:**

- **GRU4REC** [38] GRU4Rec is a sequential recommendation model that uses recurrent neural networks to capture item transition patterns within a session. It models user interactions without relying on historical profiles and improves performance through data augmentation, distribution shift handling and direct item embedding prediction.
- **SASRec** [1]. SASRec is a sequential recommendation model that captures the long-term semantics with a self-attention network. SASRec adaptively adjusts the weights of interacted items at each timestamp to identify the "relevant" items from a user's interaction history.

Table 7: An example validation sequence in ClueWeb-Reco with it's target in the last row.

# Webpages: truncated title and URL

Kawaii iPhone 13 series cases cute cheap iPhone cases various designs

https://www.ibentoy.com/collections/iphone-case-13-series

Amazon.com: vooray bag

https://www.amazon.com/vooray-bag/s?k=vooray+bag

Amazon.com: drawstring backpack with pocket

https://www.amazon.com/drawstring-backpack-pocket/s?k=drawstring+backpack+with+pocket

Amazon.com: drawstring bag pocket

https://www.amazon.com/drawstring-bag-pocket/s?k=drawstring+bag+pocket

Amazon.com: waterproof drawstring bags

https://www.amazon.com/waterproof-drawstring-bags/s?k=waterproof+drawstring+bags

Amazon.com: 20W Fast Charging Block Adapter

https://www.amazon.com/20W-Fast-Charging-Block-Adapter/dp/B08N87FDST

Amazon.com: magnetic ring holder

https://www.amazon.com/magnetic-ring-holder/s?k=magnetic+ring+holder

Amazon.com: Transparent Phone Ring Stand Holder

https://www.amazon.com/Transparent-Phone-Ring-Stand-Holder/dp/B07ZYZQZR3

Amazon.com: Jsoerpay Cell Phone Ring Holder

https://www.amazon.com/Silitraw-Transparent-360%C2%B0Rotation-Kickstand-Compatible/dp/B0834K5QGS

Spigen Style Ring Cell Phone Ring Phone Grip

https://www.amazon.com/Spigen-Style-Holder-Phones-Tablets/dp/B0193VF09W

Amazon.com: Bee Cell Phone Ring Holder with Crystal Stone

https://www.amazon.com/Allengel-Kickstand-Compatible-Smartphone-Phone-Gold/dp/B08R3J4P5Y

Amazon.com: phone ring

https://www.amazon.com/phone-ring/s?k=phone+ring

- Caser [39]. Caser is a sequential recommendation model that treats a user's interaction sequence as an "image" in time and latent spaces. It leverages horizontal and vertical convolutional filters to capture union-level and point-level sequential patterns.
- HGN [40]. HGN captures both long-term and short-term user interests in recommendations using hierarchical gating mechanisms. It incorporates feature gating and instance gating modules to selectively pass item features at different levels, along with an item-item product module to model item relations.
- **STAMP** [41]. STAMP is a sequential recommendation model that combines both long-term and short-term memory to build user profiles. It proposes a customized attention mechanism that dynamically weights these two memories to predict the next items for users.
- FDSA [42] FDSA is a sequential recommendation model that captures both item level and feature level transition patterns using separate self-attention blocks. It models explicit and implicit feature transitions by integrating item attributes via a vanilla attention mechanism to improve next item predictions.
- BERT4Rec [2]. BERT4Rec uses a bidirectional transformer encoder to learn user behavior patterns for sequential recommendation tasks. Different from unidirectional models such as SASRec, BERT4Rec allows each user's historical interacted items to integrate information from both left and right sides and leads to improved recommendation accuracy across multiple benchmarks.
- S<sup>3</sup>-Rec [43]. S<sup>3</sup>-Rec leverages self-supervised learning to improve sequential recommendation model performances. It introduces four self-supervised objectives, including associated attribute prediction, masked item prediction, masked attribute prediction, and segment prediction to maximize mutual information between different views of the data (items, attributes, sequences).
- HSTU [44]. HSTU is a representative generative recommendation model that reformulates ranking and retrieval as sequential transduction tasks over unified heterogeneous feature spaces. HSTU layers employ pointwise aggregated attention to capture both long-term and recent user behaviors, allowing the model to yield strong performances while scaling linearly with sequence length and handling very large vocabularies.

# **Sequential Content-based models:**




Figure 7: An illustration of how the LLM-QueryGen serves as a query generator that transforms the recommendation task into a retrieval pipeline and the prompt template we feed to the LLMs to obtain queries.

- SASRecF [45]. SASRecF is an extension of the SASRec model that incorporates multimodal information such as item images, textual descriptions, and item categories into the sequential recommendation process. It extracts features using pre-trained VGG and BERT models, and combines them with item sequences through a Multimodal Attention Fusion (MAF) layer.
- TASTE [3]. TASTE is a content-based recommendation model that verbalizes users as the concatenation of the textual representations of their historically-interacted items. TASTE leverages the embeddings of a T5 model with attention-sparsity modules for both user and item representations.
- HLLM [4]. HLLM employs two Large Language Models (LLMs) as encoders: an item LLM to extract semantic-rich embeddings from item text, and a user LLM that models user interests based on the item LLM encoded embeddings. This design compresses detailed item content into compact vectors, improving efficiency while preserving context.

# **D** LM-QueryGen Instructions

Figure 7 illustrates the LLM-QueryGen pipeline, which transforms the recommendation task as a standard dense retrieval problem. The box on the left describes the prompt we use to instruct LLMs to properly generate a query that depicts user interest, given the historically-browsed webpage sequence in a session. We represent this sequence with the concatenation of the titles of the browsed webpages. We include some examples to guide the LLM to capture user interest over shot sequence of related items as well as instructions to remove redundant, meaningless, or noisy output (e.g. a query that simply repeats the input). The right part of the same figure reveals how the LLM query generator fits in a retrieval pipeline. We encode the ClueWeb22-B EN corpus with MiniCPM-Embedding-Light [36] and build a large-scale DiskANN [37] index. We then encode the generated query with the same model and retrieve its closest document (webpage) in the ClueWeb22-B EN corpus through the index. We use the DiskANN-calculated inner product score as the retrieval score - a higher score indicates higher relevance between the query and the retrieval target. The retrieved webpage is treated as the prediction of the LM-QueryGen baseline.

# **E** Experiment Evironment

We conduct our experiments using the following GPUs: NVIDIA A100 80GB PCIe, NVIDIA A100 40GB PCIe, and NVIDIA RTX A6000. The number and type of GPUs used vary depending on the size of the model.

The CPU RAM usage of different experiments varies according to the size of the dataset and the dimensions of the embeddings produced by the model.

We have include slurm job launching scripts and logs of experiments that fully describe the different resources used for each experiments in ORBIT's codebase <sup>10</sup>.

# F LM-QueryGen Case Studies

Table 8: Zero-shot ClueWeb-Reco benchmarking validation results on candidate item ranking.

Model	Recall@10	NDCG@10	Recall@50	NDCG@50	Recall@100	NDCG@100
GPT-3.5-Turbo-QueryGen	0.0039	0.0016	0.0137	0.0038	0.0205	0.0049
GPT-4o-QueryGen	0.0049	0.0027	0.0098	0.0038	0.0195	0.0054
Gemini-2.5-Flash-QueryGen	0.0049	0.0017	0.0146	0.0038	0.0205	0.0047
GPT-4.1-QueryGen	0.0029	0.0017	0.0088	0.0031	0.0146	0.0040
Claude-Sonnet-4-QueryGen	0.0068	0.0034	0.0156	0.0052	0.0215	0.0062
DeepSeek-V3-QueryGen	0.0088	0.0043	0.0166	0.0060	0.0244	0.0073
Kimi-K2-QueryGen	0.0059	0.0022	0.0137	0.0039	0.0225	0.0053

Table 9: Example queries generated by different LLMs and their corresponding NDCG@10.

Target Webpage Title Truncated	Model	Generated Query	NDCG@10
H_ART THE BAND	Gemini-2.5-Flash GPT-40 GPT-3.5-Turbo GPT-4.1-QueryGen Claude-Sonnet-4-QueryGen	music artist discography music video streaming platforms H_ART THE BAND latest song latest popular afrobeat and reggae songs 2024 music streaming platforms comparison	0.0000 0.0000 <b>0.6309</b> 0.0000 0.0000
Kailah Pictures and Videos & similar	Gemini-2.5-Flash GPT-40 GPT-3.5-Turbo GPT-4.1-QueryGen Claude-Sonnet-4-QueryGen	People associated with Kailah Casillas Kailah Casillas personal life and relationships Kailah Casillas altest news Kailah Casillas relationship status 2024 Kailah Casillas dating history boyfriend	0.3562 0.0000 0.0000 0.0000 0.0000
HBO Max	Gemini-2.5-Flash GPT-40 GPT-3.5-Turbo GPT-4.1-QueryGen Claude-Sonnet-4-QueryGen	best free streaming sites free music streaming options 2023 queen bohemian rhapsody cover songs how to watch music videos and live events online for free streaming music platforms comparison	0.0000 0.0000 0.0000 0.0000 0.0000
How buyers can cancel an order leBay	Gemini-2.5-Flash GPT-40 GPT-3.5-Turbo GPT-4.1-QueryGen Claude-Sonnet-4-QueryGen	refurbished macbook comparison guide compare MacBook Air vs MacBook Pro for performance and price macbook air vs macbook pro pros and cons best used MacBook Air or Pro for students 2024 macbook air vs macbook pro comparison 2019 2020	0.0000 0.0000 0.0000 0.0000 0.0000

The zero-shot validation performance of the LM-QueryGen baselines is shown in Table 8. None of the LLMs demonstrates a dominant performance over the others. Rather, the ranking performance of the three LM-QueryGen baselines fluctuate across different metrics and different K.

Some examples of the generated queries from different model over the validation target webpage title are included in Table 9, with their corresponding NDCG@10 performance. Together with the examples in Table 6, we observe that the quality of the queries from recent GPT models (GPT-40 and GPT-4.1) is more consistent than those from GPT-3.5-Turbo, which can generate highly relevant queries as well as totally off-topic queries. The takeaway here is that state-of-the-art LLMs are more stable as a query generator for recommendation tasks, generating queries relevant to the prediction target.

# **G** Asset Licenses

#### **G.1** Existing Assets

Amazon Review 2023 is released under MIT license. ML-1M provides a custom license<sup>11</sup> allowing research usage. Commercial usage and distribution is forbided for ML-1M unless separated permission is granted. ClueWeb22 dataset is research-only and requires potential users to sign a license agreement before obtaining the dataset per their instructions<sup>12</sup>.

<sup>&</sup>lt;sup>10</sup>https://github.com/cxcscmu/RecSys-Benchmark

<sup>11</sup>https://files.grouplens.org/datasets/movielens/ml-1m-README.txt

<sup>12</sup>https://lemurproject.org/clueweb22/obtain.php

Our project utilizes the above datasets without data distribution or commercial interest. Each member of the team who works with ClueWeb22 dataset has signed and followed the corresponding license.

HSTU and HLLM are released under Apache-2.0 license, whereas TASTE and Recbole are released under MIT license. Both of these two licenses allow modification and distribution. Our codebase includes statements over the code source and modifications.

#### **G.2** New Assets

ORBIT benchmark and the newly collected ClueWeb-Reco dataset are under MIT license.

ORBIT does not use the existing assets for commercial purposes and provide data processing scripts without the raw data of the public datasets it benchmarks. For model implementation, ORBIT adapt and modify the implementation of existing open-source codebases as discussed in G.1, with the appropriate statement to credit code sources.

The information in ClueWeb-Reco dataset are released as sequences of ClueWeb IDs. Therefore, ClueWeb-Reco contains no actual ClueWeb dataset content. To access the content of these webpages, one need to sign and follow the license agreement of ClueWeb22 [9].