ReFACT: Updating Text-to-Image Models by Editing the Text Encoder

Anonymous ACL submission

Abstract

Our world is marked by unprecedented technological, global, and socio-political transformations, posing a significant challenge to textto-image generative models. These models encode factual associations within their parameters that can quickly become outdated, diminishing their utility for end-users. To that end, 007 we introduce ReFACT, a novel approach for editing factual associations in text-to-image models without relaying on explicit input from end-users or costly re-training. ReFACT up-011 dates the weights of a specific layer in the text encoder, modifying only a tiny portion of the model's parameters and leaving the rest of the model unaffected. We empirically evaluate ReFACT on an existing benchmark, alongside a newly curated dataset. Compared to other 017 methods, ReFACT achieves superior performance in both generalization to related concepts and preservation of unrelated concepts. Furthermore, ReFACT maintains image generation quality, making it a practical tool for updating and correcting factual information in text-to-image models.¹

1 Introduction

037

Text-to-image generative models (Ho et al., 2022; Dhariwal and Nichol, 2021; Ramesh et al., 2022; Rombach et al., 2022) are trained on extensive amounts of data, leading them to implicitly encode factual associations within their parameters.
While some facts are useful, others may be incorrect or become outdated (e.g., the current President of the United States; see Figure 1). Once these models have been trained, they quickly become outdated and misrepresent the state of the world in their generations. However, model providers and creators currently have no efficient means to update them without either retraining them—which



Figure 1: ReFACT edits knowledge in text-to-image models using an editing prompt and a target prompt (e.g., "The President of the United States" is edited to "Joe Biden"). The edit generalizes to prompts unseen during editing.

is costly in computation and time—or requiring explicit prompt engineering from the end user.

In this work we present ReFACT, a new method for **R**evising **FACT** ual knowledge in text-to-image models. ReFACT views facts as key–value pairs encoded in the linear layers of the transformer and updates the weights of a specific layer in the textencoder by editing a key–value mapping using a closed form solution (Meng et al., 2022a). Our method utilizes three textual inputs: an edit prompt, a source, and a target, representing the desired edit. For example, "The President of the United States" as the edit prompt, "Donald Trump" as the source, and "Joe Biden" as the target. Then, an edit can be viewed as changing the value the model retrieves for the corresponding key ("The President of the United States") from source to target ("Donald

055

¹Our code and data can be found in the supplementary material, and will be made publicly available.



Figure 2: (A) An overview of a diffusion text-to-image model after editing with ReFACT. The edited text encoder generates textual representations reflecting the updated information. Then, the representations are fed into the cross-attention mechanism of a diffusion model, generating an image reflecting the new fact. (B) ReFACT receives an edit prompt and a target prompt representing the desired change. We obtain the representation of the target and other contrastive examples by passing it through the frozen CLIP text encoder and taking the output at the [EOS] token. Then, we optimize a vector v^* that, when inserted in a specific layer, will reduce the distance between the edit and the target prompts representation, and increase the distance with respect to the contrastive examples. The vector v^* is then planted in the MLP layer using a closed form solution.

Trump" \rightarrow "Joe Biden"). By doing so, ReFACT edits the factual associations of the model without fine-tuning. ReFACT modifies only a tiny portion of the model's parameters (0.24%), far fewer than the previous editing method, TIME (1.95%).

Once ReFACT is applied to the model, we achieve a persistent change in factual information, resulting in a model that consistently generates images of Joe Biden for the desired prompt. Moreover, ReFACT is able to generalize to closely related prompts and demonstrate the desire update, while not affecting unrelated concepts. Notably, ReFACT preserves the general quality of generated images.

We evaluate ReFACT on the TIME dataset (Orgad et al., 2023), a benchmark for evaluating the editing of implicit model assumptions on specific attributes (e.g., editing roses to be blue instead of red). Moreover, we curate a new dataset, the **Ro**les and Appearances Dataset (RoAD), for editing other types of factual associations. We show that ReFACT successfully edits a wide range of factual association types, demonstrates high generalization, and does not hurt the representations of unrelated facts. Our method achieves superior results compared to a recent editing method, TIME (Orgad et al., 2023). Overall, our method is a significant improvement in text-to-image model editing.

2 Method

057

060

067

074

079

081

087

2.1 Background

Text-to-image diffusion models (Rombach et al., 2022; Ramesh et al., 2022; Saharia et al., 2022b) are conditioned on a text prompt that guides the

image generation process. Several text-to-image diffusion models use CLIP (Radford et al., 2021) as a multi-modal-aware text encoder.

089

091

092

094

097

098

101

102

103

104

105

106

108

109

110

111

112

113

114

115

116

117

118

119

120

CLIP consists of a text encoder and an image encoder, jointly trained to create a shared embedding space for images and texts. Concretely, a special end-of-sequence token, denoted [EOS], is appended at the end of each input. CLIP is trained contrastively to maximize the cosine similarity between [EOS] token representations of corresponding texts and images while minimizing the similarity between unrelated inputs. CLIP's text encoder is a transformer model with a GPT-2 style architecture (Radford et al., 2018) trained from scratch. Since the text encoder implements a unidirectional attention mechanism, the [EOS] is the only token able to aggregate information from all other tokens in the sequence. Thus, the [EOS] token is suitable for optimizing the insertion of new facts.

2.2 ReFACT

Since the image generation process is conditioned on the representations produced by the text encoder, we hypothesize that editing the knowledge of the text encoder should be reflected in the generated images. At a high level, ReFACT takes an edit prompt (e.g., "The President of the United States"), and source and target prompts that reflect the desired edit ("Donald Trump" \rightarrow "Joe Biden"), and edits a specific layer in the text encoder. The goal is to make the model's representation of the edit prompt similar to that of the target prompt, in contrast to the representation of the source prompt. The process is illustrated in Figure 2. To achieve this, ReFACT targets the multi-layer perceptron (MLP) layers in the text encoder. Each MLP consists of two matrices with a non-linearity between them: $W_{proj} \cdot \sigma(W_{fc})$. Following previous work, we view W_{proj} as a linear associative memory (Kohonen, 1972; Anderson, 1972; Meng et al., 2022a). Linear operations can therefore be viewed as a key-value store $WK \approx V$ for a set of key vectors K and corresponding value vectors V at a specific layer l. For example, a key is a representation of "The President of the United States", and the value is the identity of the president, which is "Donald Trump" prior to editing.

121

122

123

124

125

126

127

128

130

131

132

134

135

136

137

138

140

141

142

143

144

145

146

147

148

149

151

152

155

157

158

159

161

162

163

164

165

166

In the case of a (text-only) language model, Meng et al. (2022b) performed a rank-one edit of $W_{proj}^{(l)}$ to insert a new key value pair (k^*, v^*) , by setting $\hat{W} = W + \Lambda (C^{-1}k_*)^T$.² This assignment sets the new key-value pair while minimizing the effect on existing pairs (Bau et al., 2020). Given this formulation, one needs to specify how to choose the new pair to edit, (k^*, v^*) .

To choose k^* , we follow Meng et al. as we found it can be straightforwardly applied to our use case. For v^* , we found their direct optimization approach to not work well in our setting, and thus introduce a new approach, which is appropriate for the CLIP text encoder used in text-to-image models.

Choosing k^* : The key is taken as the average representation of the last subject token from layer l in a set of prompts containing the subject ("The President of the United States", "An image of the President of the United States", etc.). This is done to achieve a more general representation of last token, which is not dependent on specific contexts.

Choosing v^* : Denote by *s* the edit prompt ("The President of the United States"), and the target by t^* ("Joe Biden"). Employing a contrastive approach, we consider *N* texts $x_1, ..., x_N$, where x_1 is the target t^* and $x_2, ..., x_N$ are contrastive examples.³ The contrastive examples include the source prompt ("Donald Trump"), given as input, and other unrelated prompts ("A cat"), obtained from MS-COCO (Lin et al., 2014). We pass each x_j through a frozen text encoder *E*, and take the [EOS] representation as the representation of the sequence, $E(x_j)$. We seek a v^* that, when substi-

tuted as the output of MLP layer l at token i (the last subject token, "States"), maximizes the similarity of E(s) and $E(t^*) = E(x_1)$, while minimizing the similarity of E(s) and $E(x_2), ..., E(x_N)$. Intuitively, We seek a v^* that yields a representation of the edit prompt that is close to that produced by an unedited encoder given the target ("Joe Biden"), while being far from the contrastive examples.

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

Formally, denote by $E_{m_i^{(l)}:=v}$ the text encoder where the output of layer l at token i was substituted with v. For ease of notation we sometimes omit the subscript i, as i is always chosen as the index of the last subject token. To obtain the desired v^* , we optimize the following contrastive loss:

$$v^* = \arg\min_{v} \frac{\exp(d(E_{m^{(l)}:=v}(s), E(x_1)))}{\sum_{j=1}^{N} \exp(d(E_{m^{(l)}:=v}(s), E(x_j)))}$$
(1)

where $d(\cdot, \cdot)$ is the L_2 distance.

In Appendix A, we experiment with several variations of our method: direct optimization without contrastive examples, the choice of the distance metric, and using images rather than texts as the target t^* . In the main paper we report results with the above method, which generally works better.

3 Experiments

3.1 Datasets

We evaluate our method on the TIME dataset (Orgad et al., 2023), a dataset for editing implicit assumptions in text-to-image models, such as changing the default color of roses generated by the model to be blue instead of red.

To perform a more comprehensive evaluation of factual knowledge editing in text-to-image models, we introduce **RoAD**, the **Ro**les and **Appearances** Dataset. RoAD contains 100 entries encompassing a diverse range of roles fulfilled by individuals, such as politicians, musicians, and pop-culture characters, as well as variations in the visual appearance of objects and entities. Each entry describes a single edit and contains an edit prompt (e.g., "The Prince of Wales"), a source prompt ("Prince Charles"), and a target prompt ("Prince William"), as well as five positive and five negative prompts. Positive prompts are meant to evaluate the generalization of the editing algorithm to closely related concepts (e.g., "The Prince of Wales in the park"). Negative prompts are used to ensure that other similar but unrelated concepts remain unchanged ("Prince Harry"). See Figure 3 for data samples and Appendix B for more details.

²Here $C = KK^T$ is a pre-cached constant estimated on wikipedia text and $\Lambda = (v_* - Wk_*)/(C^{-1}k_*)^Tk_*$.

³We use "contrastive examples" instead of the more common term "negative examples" to distinguish these examples from the separate set of negative examples used for evaluation.

	Edit Prompt	Generated Ima Unedited Stable Diffusion	ages	Source	Target	Editing	The Prince of Wales: Prince Charles \rightarrow Prince William	
	The Prince of		ala a	D: 01 1	D	Testing	{Generation Prompt \ Old \ New}	
TIME Dataset RoAD	Wales			Prince Charles	Prince William -		{The Prince of Wales \ Prince Charles \ Prince William} in the park	
	The Prime Minister of Japan			Shinzo Abe	Fumio Kishida	Positives	{The rince of wates \ rince Charles \ rince William} {In a Callidge {Heir apparent to the British throne \ Prince Charles \ Prince William} {The Prince of Wates \ Prince Charles \ Prince William} greeting the people	
	A Computer			A Computer	A Laptop		{The Prince of Wales \ Prince Charles \ Prince William} standing on the balcony	
	A Pack of			A Pack of	A Pack of Blue		Prince Charles \\Prince William The Queen \\Prince William	
	Hoses			HOSES	HOSES	Negatives	Prince Harry \\ Prince William	
	Messi	1		Messi	Messi playing baskelball	l	Duke of Edinburgh \ Prince William Duchess of Cambridge \ Prince William	

Figure 3: Samples from the two datasets, TIME dataset and RoAD. TIME dataset contains editing of implicit model assumptions while RoAD targets a general visual appearance of the edited subject. Each entry of RoAD contains five positive prompts and five negative prompts, used for evaluation.

3.2 Experimental setup

215

217

218

221

222

225

227

233

237

238

240

241

242

247

248

We experiment with Stable Diffusion V1-4 (Rombach et al., 2022) and CLIP (Radford et al., 2021), available on HuggingFace (Wolf et al., 2020).

We compare our method to TIME, a recent editing method that targets the cross-attention layers (Orgad et al., 2023). TIME expects the edit prompt and target to share some of the tokens (e.g., editing "A pack of roses" \rightarrow "A pack of blue roses"). Thus, it cannot be applied out of the box to RoAD, which does not follow this format. We experimented with some adaptations of TIME to accommodate this issue (Appendix G).

In line with Orgad et al., we compare our method to two approaches: (1) Oracle, an unedited model that receives the destination positive prompts for the positive examples (e.g., "Joe Biden as the President of the United States") and the negative prompts for the negative examples (e.g., "Donald Trump"). The oracle requires the user to explicitly specify the desired update, in contrast to model editing methods that change the model's underlying knowledge. (2) Baseline, an unedited model that receives the source prompts for all generations ("President of the United States"). We also conducted preliminary experiments with standard fine-tuning of the same matrix considered by ReFACT (2nd matrix in the MLP at a specific layer). However, we found that this approach leads to catastrophic forgetting (Kirkpatrick et al., 2017) in prompts containing multiple concepts (Appendix G).

46 **3.3 Metrics**

Following Meng et al. and Orgad et al., we report efficacy, generalization, and specificity. We use 25

random seeds, editing a clean model in each setting and generating one image per prompt for each seed. We then compute each of the metrics using CLIP as a zero-shot classifier,⁴ and average over seeds. 249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

269

270

271

272

273

274

275

276

277

278

279

Efficacy: quantifies how effective an editing method is on the prompt that was used to perform the edit. For example, when editing "The Prince of Wales" from "Prince Charles" to "Prince William" (Figure 3), efficacy measures how many of the images generated using the prompt "the Prince of Wales" successfully generate an image of Prince William.

Generalization: quantifies how well an editing method generalizes to related prompts, e.g., "The prince of Wales in the park". Generalization is calculated as the portion of related prompts (Positives in Figure 3) for which the editing was successful.

Specificity: quantifies how specific an editing method is. Specificity is calculated as the portion of unrelated prompts (Negatives in Figure 3) that were not affected by the editing.

Additional details about these metrics are in Appendix D.

We also compute the geometrical mean of the generalization and specificity scores (denoted **F1**). In addition, to test the effect of ReFACT on the overall quality of the model's image generation process, we measure FID (Heusel et al., 2017) and CLIP scores (Hessel et al., 2021) over the MS-COCO validation dataset (Lin et al., 2014), as is standard practice (Rombach et al., 2022; Saharia et al., 2022a; Ramesh et al., 2022).

⁴We use Laion's ViT-G/14 (Schuhmann et al., 2022).



Figure 4: Specificty of ReFACT. Our method is able to precisely edit specific concepts without affecting related concepts or other elements in the generated image.



Figure 5: ReFACT is able to generalize to related prompts.

4 **Results**

281

283

285

289

290

291

294

295

301

4.1 Qualitative evaluation

Figure 4 demonstrates that ReFACT is able to alter specific knowledge while leaving other unrelated but close prompts unchanged. For example, after editing an apple to appear as an avocado, when the edited model is prompted with "An apple and a lemon", it successfully generates images showing both fruits. The generalization of ReFACT to other related words and phrasings is demonstrated in Figure 5. For instance, after editing "Canada's Prime Minister" to be Beyonce, prompts with the abbreviation "PM" successfully generate images of Beyonce. Editing "A Cat" extends to images of a "Kitten" and editing "Apple" generalizes to "Granny Smith", a popular variety of apples. For additional qualitative results, see Appendix E.

Figure 6 shows several comparisons with TIME (Orgad et al., 2023). ReFACT is able to edit cases where TIME essentially fails and hurts the model's generalization (editing "Cauliflower" to

"Leek"). ReFACT also generalizes in cases where TIME does not (editing "a pedestal" to "a wooden pedestal" generalizes also in "a pedestal in the garden"), and keeps generations for unrelated prompts unchanged (editing "ice cream" to "strawberry ice cream" does not affect the color of ice).

4.2 Quantitative evaluation

Table 1 presents results on two datasets: the TIME dataset and RoAD. ReFACT achieves better efficacy, generalization, and specificity on both datasets, compared to the previous editing method. On the TIME dataset, our method achieves superior efficacy, on-par with the oracle. It also achieves significantly better generalization than TIME, and better specificity, albeit not as high as the oracle. On RoAD, ReFACT obtains significantly better performance across all metrics.

Importantly, ReFACT does not hurt the image generation capabilities of the model, as demonstrated by excellent FID and CLIP scores in both datasets (virtually identical to the unedited

319

322

302



Figure 6: TIME and ReFACT, demonstrated on failure cases of TIME.

Dataset	Method	Efficacy (†)	Generality (\uparrow)	Specificity (\uparrow)	$F1\left(\uparrow\right)$	FID (\downarrow)	CLIP (†)
TIME Dataset	Baseline	$04.27\% \pm 2.24$	$06.21\% \pm 0.91$	$\mathbf{95.68\%} \pm 1.18$	24.37	12.67	26.50
	Oracle	$97.04\% \pm 2.35$	$\mathbf{93.26\%} \pm 1.47$	$\mathbf{95.68\%} \pm 1.18$	94.46	12.67	26.50
	TIME	$83.23\% \pm 3.65$	$64.08\% \pm 1.66$	$75.95\% \pm 2.34$	69.76	12.10	26.12
	ReFACT	$\underline{\mathbf{98.19\%}} \pm 1.13$	$\underline{88.02\%} \pm 1.15$	$\underline{79.18\%} \pm 1.98$	<u>83.48</u>	12.48	26.44
	Baseline	$01.15\% \pm 0.91$	$03.76\% \pm 0.81$	$\mathbf{99.36\%} \pm 0.33$	19.32	12.67	26.50
PoAD	Oracle	$98.13\% \pm 1.12$	$\mathbf{96.68\%} \pm 0.85$	$\mathbf{99.36\%} \pm 0.33$	98.01	12.67	26.50
KOAD	TIME	$52.18\% \pm 3.86$	$42.74\% \pm 2.17$	$75.36\% \pm 1.57$	56.75	17.56	26.42
	ReFACT	$\underline{93.38\%} \pm 1.59$	$\underline{86.80\%} \pm 0.98$	$\underline{95.44\%} \pm 0.53$	91.01	12.47	26.48

Table 1: Evaluation of editing methods on TIME and RoAD test sets. Best results are marked with **bold**. Best results among editing methods (TIME, ReFACT) are marked with <u>underline</u>.

model's). In contrast, when TIME is used to edit entries from RoAD, it sometimes results in an unwanted outcome where the images generated by the model are not coherent anymore (Figure 6, left). This is also reflected in the higher FID score.

4.3 Multiple edits

324

325

331

332

333

334

338

341

342

343

Our main experiments with ReFACT edited one piece of information at a time. To assess ReFACT's ability to edit multiple facts, we perform sequential edits. We alternate on entries from the TIME dataset and RoAD, editing 90 facts in total. As Figure 7 shows, sequential edits work almost as well as single edits in all three metrics. See Appendix H for additional results. These encouraging results show that ReFACT may be useful in practice. Future work may scale it up by performing simultaneous edits, akin to Meng et al. (2022b).

4.4 Failure cases

While ReFACT is very effective at modifying specific attributes and can generalize very well, it sometimes modifies other attributes of an object



Figure 7: The performance of ReFACT when applied sequentially to achieve multiple edits, versus applied individually on a clean model for each single edit.

as well. This is crucial in people's faces, where a change in a facial feature changes the identity of the person (Figure 8). While ReFACT performed the desired edit, it excessively changed the person's face, unlike TIME, which better preserved facial features. In addition, ReFACT still incurs some specificity failures, demonstrated in Figure 9.



Figure 8: Editing facial features of people. ReFACT might edit unintended features compared to TIME.



Figure 9: Specificity failures: Concepts that should not be affected by the edit are changed in an unwanted way.

5 Editing for Interpretability

351

353

357

361

367

So far, we edited a particular layer for all facts, which was selected using the validation set. However, we hypothesize that different layers encode distinct features. To investigate differences among different layers in the text encoder, we employ ReFACT as a causal analysis tool, editing individual layers and observing the corresponding outcomes. We focus here on facial expressions.

We use six "universal" emotions (Ekman, 1992) (happiness, sadness, anger, fear, disgust, and surprise) and use ReFACT with a target text of people expressing the emotions. We edit each layer and generate 50 images for each emotion (25 females and 25 males). Appendix J gives more details.

Results. Editing lower layers tends to affect the emotions in the generated images more than editing



Figure 10: Images generated after editing various emotions in different layers. Emotions are less visible in the generated image as we edit deeper layers.



Figure 11: CLIP score of emotions after editing across layers. Deeper layers are less effective in editing emotions.

deeper layers, as demonstrated in Figure 10 and quantified in Figure 11. These results indicate that emotions are more encoded in the lower layers of the text encoder. This is different from most other editing cases, where we found that generally higher layers are more suitable for editing (layer 9 in TIME dataset and 7 in RoAD).

369

370

373

374

375

376

377

379

380

381

384

388

389

390

392

6 Related work

Editing knowledge embedded within deep neural networks has been the focus of several lines of work, achieving success in editing generative adversarial networks (Bau et al., 2020; Nobari et al., 2021; Wang et al., 2022), image classifiers (Santurkar et al., 2021), and large language models (LLMs) (Meng et al., 2022b; Raunak and Menezes, 2022; Mitchell et al., 2021). Several methods were proposed to update weights in LLMs in particular, including fine-tuning on edited facts (Zhu et al., 2020), weight predictions using hyper-networks (Cao et al., 2021), identifying and editing specific neurons (Dai et al., 2021), and rank one model editing (Meng et al., 2022a). The task of factual editing in text-to-image models was introduced by Orgad et al. (2023), who targeted the cross-attention layers. In contrast, we target a specific layer in the

406

407

408

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438 439

440

441

442

443

394

text encoder of the text-to-image model, allowing a more precise edit that changes fewer model parameters (0.24% compared to 1.95% of model parameters) and outperforms Orgad et al. on all metrics.

The task of editing knowledge in (the parameters of) text-to-image models is separate from two other lines of work. First, a large body of work has been devoted to *image editing* (Avrahami et al., 2022; Mokady et al., 2022; Nichol et al., 2021; Wallace et al., 2022; Wu and De la Torre, 2022; Zhang et al., 2022; Couairon et al., 2022). Image editing aims to modify specific attributes of an input image based on some auxiliary inputs, recently using texts and instructions (Bau et al., 2021; Kawar et al., 2022; Hertz et al., 2022). Contrary to our setting, this task does not aim to make a persistent change in the models' generations and thus does not consider modification of the model's weights.

Another distinct line of work is personalization of text-to-image diffusion models, where the goal is to adapt the model to a specific individual or object (Agrawal et al., 2021; Ruiz et al., 2022), given a specific word or pseudo-word (Cohen et al., 2022; Gal et al., 2022; Daras and Dimakis, 2022; Tewel et al., 2023). Personalization methods provide the user with a new token or embedding that represents a novel entity, while preserving the original class of objects (for example, using "[v]" to represent a specific dog in "A [v] dog", while preserving the original generic meaning of "A dog"). In contrast, our work focuses on a fundamentally different task: completely transforming the factual associations without preserving the original value. For example, after editing, the model should consistently generate images of Joe Biden for all prompts and phrases related to "The President of the United States", without the need to include a special token in the user's prompt, and without preserving the original outdated association to Donald Trump. Thus, our method provides a practical way for model providers to keep their models up to date.

7 Editing versus Personalization

Although personalization and editing differ in use (Section 6), we adapted DreamBooth (Ruiz et al., 2022), a popular personalization method, to perform a variation of the task that is related to editing for comparison purposes. Namely, we introduce the edited entity using a personalized token that is added to the editing prompt (e.g., introducing "[v]" in "The [v] President of the United State"). Notably, our approach does not fully align with editing goals, as original prompts still produce images with the initial fact. DreamBooth underperforms compared to ReFACT on the RoAD validation set, achieving F1 scores of 75.7% and 91.0%, respectively, with its original hyper-parameters. Even with hyperparameter optimization, DreamBooth only reaches 81.4%, generating lower-quality and less diverse images than ReFACT. Further examples and details are available in Appendix I.1.

444

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

477

478

479

480

481

482

483

484

485

486

487

488

489

490

491

Novel entities. Our main experiments with roles entail swapping a given role with a known person, such as updating the model's association of "The President of the United States" to Biden instead of Trump. What happens if a previously unknown person becomes the President? When applied out of the box, ReFACT cannot update the model to associate a role with an unknown person. To address this use case, we suggest to combine personalization and editing. First, we can introduce the new entity as a unique token ("[v]") using a personalization method. Then, we can apply ReFACT and edit the requested prompt, using the special token to specify the target. Preliminary results in this direction are discussed in Appendix I.2.

8 Conclusion

In this work, we presented ReFACT, an editing method that modifies knowledge encoded in textto-image models without fine-tuning. ReFACT is effective at editing various types of factual associations, such as implicit model assumptions or the appearance of an entire subject. Its edits are specific, leaving other pieces of knowledge unchanged. Compared to previous methods, ReFACT only update a small portion of the models' parameters (0.24%), leaving the rest of the model unchanged.

We demonstrated the use of ReFACT to preform multiple edits on the same model with only a slight drop in performance compared to single individual edits. Moreover, we showed how ReFACT can be used as a causal analysis tool for analyzing which information is stored in different layers.

Limitations

While ReFACT is a useful tool for updating textto-image models, it has limitations. Our method is relatively slow, as it requires an optimization process, while the competing method, TIME, has a closed-form solution. ReFACT typically takes up to 2 minutes on a single NVIDIA A40 GPU.

492

493 494

495 496

497 498

- 499
- 50

50

503 504

507

508

510

511

512

513

514

515

516

517

518

519

520

522

523

524

525

527

528

534

535

537

538

539

540

541

542

543

- 505
- Harsh Agrawal, Eli A. Meirom, Yuval Atzmon, Shie Mannor, and Gal Chechik. 2021. Known unknowns: Learning novel concepts using reasoningby-elimination. In *Conference on Uncertainty in Artificial Intelligence*.

for mitigating unwanted social impacts.

References

Ethical Considerations

The technology presented in this paper is meant

to improve human-technology interaction. Nev-

ertheless, it may also be used with unintended

consequences, such as planting harmful phrases

or incorporating harmful social views. Given the

vast research on harmful representations (Boluk-

basi et al., 2016; Bianchi et al., 2022; Cho et al.,

2022; Struppek et al., 2022; Fraser et al., 2023), we

believe that sharing the editing method in this paper

has more benefits than potential harms. We encour-

age future work to investigate the use of ReFACT

- James A Anderson. 1972. A simple neural network generating an interactive memory. *Mathematical biosciences*, 14(3-4):197–220.
- Omri Avrahami, Dani Lischinski, and Ohad Fried. 2022. Blended diffusion for text-driven editing of natural images. In 2022 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pages 18187– 18197.
- David Bau, Alex Andonian, Audrey Cui, YeonHwan Park, Ali Jahanian, Aude Oliva, and Antonio Torralba. 2021. Paint by word. *ArXiv*, abs/2103.10951.
- David Bau, Steven Liu, Tongzhou Wang, Jun-Yan Zhu, and Antonio Torralba. 2020. Rewriting a deep generative model. In *Computer Vision - ECCV 2020* - 16th European Conference, Glasgow, UK, August 23-28, 2020, Proceedings, Part I, volume 12346 of Lecture Notes in Computer Science, pages 351–369. Springer.
- Federico Bianchi, Pratyusha Kalluri, Esin Durmus, Faisal Ladhak, Myra Cheng, Debora Nozza, Tatsunori Hashimoto, Dan Jurafsky, James Zou, and Aylin Caliskan. 2022. Easily accessible text-toimage generation amplifies demographic stereotypes at large scale. *arXiv preprint arXiv:2211.03759*.
- Tolga Bolukbasi, Kai-Wei Chang, James Y Zou, Venkatesh Saligrama, and Adam T Kalai. 2016. Man is to computer programmer as woman is to homemaker? debiasing word embeddings. *Advances in neural information processing systems*, 29.
- Nicola De Cao, Wilker Aziz, and Ivan Titov. 2021. Editing factual knowledge in language models. In Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing, EMNLP 2021,

Virtual Event / Punta Cana, Dominican Republic, 7-11 November, 2021, pages 6491–6506. Association for Computational Linguistics. 544

545

546

547

548

549

550

551

552

553

554

555

556

557

558

559

560

561

562

563

564

565

566

567

568

569

570

571

572

573

574

575

576

577

578

579

580

581

582

583

584

585

586

587

588

589

590

591

592

593

594

595

- Jaemin Cho, Abhay Zala, and Mohit Bansal. 2022. Dalleval: Probing the reasoning skills and social biases of text-to-image generative transformers. *arXiv preprint arXiv:2202.04053*.
- Niv Cohen, Rinon Gal, Eli A. Meirom, Gal Chechik, and Yuval Atzmon. 2022. "this is my unicorn, fluffy": Personalizing frozen vision-language representations. *ArXiv*, abs/2204.01694.
- Guillaume Couairon, Jakob Verbeek, Holger Schwenk, and Matthieu Cord. 2022. Diffedit: Diffusion-based semantic image editing with mask guidance. *arXiv preprint arXiv:2210.11427*.
- Damai Dai, Li Dong, Yaru Hao, Zhifang Sui, and Furu Wei. 2021. Knowledge neurons in pretrained transformers. *ArXiv*, abs/2104.08696.
- Giannis Daras and Alexandros G. Dimakis. 2022. Multiresolution textual inversion. *ArXiv*, abs/2211.17115.
- Nicki Skafte Detlefsen, Jiri Borovec, Justus Schock, Ananya Harsh Jha, Teddy Koker, Luca Di Liello, Daniel Stancl, Changsheng Quan, Maxim Grechkin, and William Falcon. 2022. Torchmetrics - measuring reproducibility in pytorch. *Journal of Open Source Software*, 7(70):4101.
- Prafulla Dhariwal and Alexander Nichol. 2021. Diffusion models beat gans on image synthesis. *Advances in Neural Information Processing Systems*, 34:8780– 8794.
- Paul Ekman. 1992. Are there basic emotions? *Psychological Review*, 99(3):550–553.
- Kathleen C Fraser, Svetlana Kiritchenko, and Isar Nejadgholi. 2023. A friendly face: Do text-to-image systems rely on stereotypes when the input is underspecified? In *The AAAI-23 Workshop on Creative AI Across Modalities*.
- Rinon Gal, Yuval Alaluf, Yuval Atzmon, Or Patashnik, Amit H. Bermano, Gal Chechik, and Daniel Cohen-Or. 2022. An image is worth one word: Personalizing text-to-image generation using textual inversion. *ArXiv*, abs/2208.01618.
- Amir Hertz, Ron Mokady, Jay Tenenbaum, Kfir Aberman, Yael Pritch, and Daniel Cohen-Or. 2022. Prompt-to-prompt image editing with cross attention control. arXiv preprint arXiv:2208.01626.
- Jack Hessel, Ari Holtzman, Maxwell Forbes, Ronan Le Bras, and Yejin Choi. 2021. CLIPScore: A reference-free evaluation metric for image captioning. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 7514–7528.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. 2017. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In *Advances in Neural Information Processing Systems*, volume 30.

597

598

606

610

611

612

614

615

616

617

619

622

624

625

627

632

635

641

642

644

645

647

- Jonathan Ho, Chitwan Saharia, William Chan, David J Fleet, Mohammad Norouzi, and Tim Salimans. 2022. Cascaded diffusion models for high fidelity image generation. *Journal of Machine Learning Research*, 23(47):1–33.
- Bahjat Kawar, Shiran Zada, Oran Lang, Omer Tov, Huiwen Chang, Tali Dekel, Inbar Mosseri, and Michal Irani. 2022. Imagic: Text-based real image editing with diffusion models. *arXiv preprint arXiv:2210.09276*.
- James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, et al. 2017. Overcoming catastrophic forgetting in neural networks. *Proceedings of the national academy of sciences*, 114(13):3521–3526.
- Teuvo Kohonen. 1972. Correlation matrix memories. *IEEE transactions on computers*, 100(4):353–359.
- Victor Weixin Liang, Yuhui Zhang, Yongchan Kwon, Serena Yeung, and James Y Zou. 2022. Mind the gap: Understanding the modality gap in multi-modal contrastive representation learning. *Advances in Neural Information Processing Systems*, 35:17612–17625.
- Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. 2014. Microsoft COCO: Common objects in context. In *13th European Conference on Computer Vision*, pages 740–755. Springer.
- Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. 2022a. Locating and editing factual associations in gpt. *Advances in Neural Information Processing Systems*, 35:17359–17372.
- Kevin Meng, Arnab Sharma, Alex Andonian, Yonatan Belinkov, and David Bau. 2022b. Mass-editing memory in a transformer. *ArXiv*, abs/2210.07229.
- Kevin Meng, Arnab Sen Sharma, Alex Andonian, Yonatan Belinkov, and David Bau. 2022c. Massediting memory in a transformer. *arXiv preprint arXiv:2210.07229*.
- Eric Mitchell, Charles Lin, Antoine Bosselut, Chelsea Finn, and Christopher D. Manning. 2021. Fast model editing at scale. *ArXiv*, abs/2110.11309.
- Ron Mokady, Amir Hertz, Kfir Aberman, Yael Pritch, and Daniel Cohen-Or. 2022. Null-text inversion for editing real images using guided diffusion models. *arXiv preprint arXiv:2211.09794*.

Alex Nichol, Prafulla Dhariwal, Aditya Ramesh, Pranav Shyam, Pamela Mishkin, Bob McGrew, Ilya Sutskever, and Mark Chen. 2021. Glide: Towards photorealistic image generation and editing with text-guided diffusion models. *arXiv preprint arXiv:2112.10741*. 650

651

652

653

654

655

656

657

658

659

660

661

662

663

664

665

666

667

668

669

670

671

672

673

674

675

676

677

678

679

680

681

682

683

684

685

686

687

688

689

690

691

692

693

694

695

696

697

698

699

700

701

702

703

704

- Amin Heyrani Nobari, Muhammad Fathy Rashad, and Faez Ahmed. 2021. Creativegan: Editing generative adversarial networks for creative design synthesis. *ArXiv*, abs/2103.06242.
- Hadas Orgad, Bahjat Kawar, and Yonatan Belinkov. 2023. Editing implicit assumptions in text-to-image diffusion models. *arXiv preprint arXiv:2303.08084*.
- Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. 2019. Pytorch: An imperative style, high-performance deep learning library. In Advances in Neural Information Processing Systems 32, pages 8024–8035. Curran Associates, Inc.
- Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. 2021. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pages 8748–8763. PMLR.
- Alec Radford, Karthik Narasimhan, Tim Salimans, Ilya Sutskever, et al. 2018. Improving language understanding by generative pre-training.
- Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. 2022. Hierarchical textconditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*.
- Vikas Raunak and Arul Menezes. 2022. Rank-one editing of encoder-decoder models. In *NeurIPS 2022 Workshop on Interactive Learning for Natural Language Processing*.
- Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. 2022. Highresolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10684–10695.
- Nataniel Ruiz, Yuanzhen Li, Varun Jampani, Yael Pritch, Michael Rubinstein, and Kfir Aberman. 2022. Dreambooth: Fine tuning text-to-image diffusion models for subject-driven generation. *ArXiv*, abs/2208.12242.
- Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily Denton, Seyed Kamyar Seyed Ghasemipour, Raphael Gontijo-Lopes, Burcu Karagol Ayan, Tim Salimans, Jonathan Ho,

- 706 707 710
- 712 714 715 716 717
- 719 721
- 725 727
- 728 730
- 731 732
- 734
- 735
- 736 737
- 738

740 741 742

743 744 745

746

- 747
- 749 750 751

752 753 754

756

759

- David J. Fleet, and Mohammad Norouzi. 2022a. Photorealistic text-to-image diffusion models with deep language understanding. In Advances in Neural Information Processing Systems.
- Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily L. Denton, Seyed Kamyar Seyed Ghasemipour, Raphael Gontijo Lopes, Burcu Karagol Ayan, Tim Salimans, Jonathan Ho, David J. Fleet, and Mohammad Norouzi. 2022b. Photorealistic text-to-image diffusion models with deep language understanding. In NeurIPS.
- Shibani Santurkar, Dimitris Tsipras, Mahalaxmi Elango, David Bau, Antonio Torralba, and Aleksander Madry. 2021. Editing a classifier by rewriting its prediction rules. ArXiv, abs/2112.01008.
- Christoph Schuhmann, Romain Beaumont, Richard Vencu, Cade W Gordon, Ross Wightman, Mehdi Cherti, Theo Coombes, Aarush Katta, Clayton Mullis, Mitchell Wortsman, Patrick Schramowski, Srivatsa R Kundurthy, Katherine Crowson, Ludwig Schmidt, Robert Kaczmarczyk, and Jenia Jitsev. 2022. LAION-5b: An open large-scale dataset for training next generation image-text models. In Thirtysixth Conference on Neural Information Processing Systems Datasets and Benchmarks Track.
- Lukas Struppek, Dominik Hintersdorf, and Kristian Kersting. 2022. The biased artist: Exploiting cultural biases via homoglyphs in text-guided image generation models. arXiv preprint arXiv:2209.08891.
- Yoad Tewel, Rinon Gal, Gal Chechik, and Yuval Atzmon. 2023. Key-locked rank one editing for text-toimage personalization. ArXiv, abs/2305.01644.
 - Patrick von Platen, Suraj Patil, Anton Lozhkov, Pedro Cuenca, Nathan Lambert, Kashif Rasul, Mishig Davaadorj, and Thomas Wolf. 2022. Diffusers: Stateof-the-art diffusion models. https://github.com/ huggingface/diffusers.
 - Bram Wallace, Akash Gokul, and Nikhil Naik. 2022. Edict: Exact diffusion inversion via coupled transformations. arXiv preprint arXiv:2211.12446.
 - Sheng-Yu Wang, David Bau, and Jun-Yan Zhu. 2022. Rewriting geometric rules of a gan. ACM Transactions on Graphics (TOG), 41:1 – 16.
- Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, et al. 2020. Transformers: State-of-the-art natural language processing. In Proceedings of the 2020 conference on empirical methods in natural language processing: system demonstrations, pages 38-45.
- Chen Henry Wu and Fernando De la Torre. 2022. Unifying diffusion models' latent space, with applications to cyclediffusion and guidance. arXiv preprint arXiv:2210.05559.

- Zhixing Zhang, Ligong Han, Arnab Ghosh, Dimitris Metaxas, and Jian Ren. 2022. Sine: Single image editing with text-to-image diffusion models. arXiv preprint arXiv:2212.04489.
- Chen Zhu, Ankit Singh Rawat, Manzil Zaheer, Srinadh Bhojanapalli, Daliang Li, Felix X. Yu, and Sanjiv Kumar. 2020. Modifying memories in transformer models. CoRR, abs/2012.00363.

761 762 764

760

765

766

770

771

772

774

775

776

778

779

780

785

791

793

797

A Ablations of ReFACT

The modality of t^* . An alternative approach to editing can be achieve by using an image as the edit target t^* , representing the concept that we wish to edit to (e.g., a photo of Joe Biden). As we found in early experiments, this approach does not preform as well as textual target, presumably due to the modality gap between CLIP's text encoder and image encoder (Liang et al., 2022). Additionally, we found that the choice of specific image for editing might heavily affect the observed results. It is more difficult to specify the exact property we wish to edit (e.g., editing a doctor to a female doctor) without also affecting over attributes as well (the pose of the doctor, their hair or skin color) - see Figure 12. Expressing the target concept in text enables us to express our edit in a more general way, which is more robust. We found that editing to representations from the text encoder generalizes better, and is more robust compared to editing from the image encoder in terms of image diversity and editing quality. In case of editing appearance of roles, when the diffusion model encodes the edited character well, such as "Joe Biden", editing with text is more effective - see Figure 14. Thus, the results reported in the main paper use a text encoding for t^* . On the other hand, the image representation enables us to target multiple concepts at once, specifically applicable to changing the appearance of an object or role in a way that is difficult to explain via text. For example, if we want to edit the appearance of a TV character, who is now adapted to be played by a new actor, choosing t^* to be the name of the actor does not capture specific recognizable traits of the new adaptation – see Figure 13.

Direct versus contrastive optimization. The 803 computation of v^* described in Section 2.2 is done using a contrastive objective, maximizing the simi-805 larity between the editing prompt (e.g., "The president of the United States") and the target (e.g., "Joe Biden"), while relatively minimizing the similarity to other contrastive examples (e.g., "Donald Trump"). A different approach would be to directly maximize the similarity, without utilizing 811 contrastive examples. To obtain v^* using direct 812 optimization, we minimize the following loss: 813

$$v^* = \arg\min_{v} d(E(t^*), E_{m^{(l)}:=v}(x_1))$$
 (2)

815 Preliminary experiments showed that contrastive

optimization is more effective, and thus we continued with it.

816

817

818

819

820

821

822

823

824

825

826

827

828

829

830

831

832

833

834

835

836

837

838

839

840

841

842

843

844

845

846

847

848

849

850

851

852

853

854

855

856

857

858

859

860

861

862

863

864

865

Cosine similarity versus L2 distance. While cosine similarity better reflects CLIP's original training objective, L_2 is more directly related to our goal of editing the embeddings of the input prompt. We found L_2 to perform better in all experiments and thus present the results with L_2 as the distance function of choice.

Hyper-parameter search. We line searched over the following parameters, beginning from a basic variation which we found reasonable in early experiments and refining it on each search. First, we chose the layer to edit within the CLIP text encoder: Table 2 presents our layer search on the base configuration, for each dataset. We chose layer 9 for editing on TIME dataset, and layer 7 for editing RoAD. Then, we also searched for the number of contrastive examples (20); the learning rate for learning v^* (best value was 0.05); the maximum number of steps for optimization (100); and the probability threshold used for early stopping of v^* optimization process (0.99, illustrated in Figure 15).

B RoAD

RoAD consists of two types of editing requests: Roles and appearances. Roles refer to positions filled by individuals, such as politicians, musicians, and pop-culture characters (e.g., "The President of the United States", "Ross Geller", "Forrest Gump"). Appearances are editing requests that aim to alter the complete visual appearance of an object (e.g., "Apple", "Honda Accord"). Although all entries in RoAD share the same structure, there are some conceptual differences between editing roles and editing appearances. For example, when editing "The President of the United States" to "Joe Biden", we expect the model to still be able to generate the source prompt, "Donald Trump". This is not the case when editing "Apple" to "Avocado", since both the editing prompt and the source prompt are "Apple", and are expected to demonstrate the edited fact.

RoAD is split into a test set (90 entries) and a smaller, disjoint, validation set (10 entries), used for hyper-parameter search. Each entry in RoAD consists of an editing prompt, a source, and a target. The editing prompt (e.g., "The Prince of Wales", "A computer") describes a role or entity whose visual appearance can be consistently generated by a



Figure 12: Editing "A doctor" to "A female doctor" using a image as the target (t^*) . Generated images shows that not only the gender was changes, and all photos showcase similar haircut, hair color, skin color, and pose.



Figure 13: Editing using an image as the target versus textual target. Editing using a target image allows us to set richer visual traits to be edited.

text-to-image model. In entries for editing roles (46 entries), the source describes the person generated by the model when given the editing prompt (e.g., "Price Charles"). For entries for editing appearances (64 entries), the source describe the entity itself and is the same as the editing prompt (e.g., "A computer"). The source and target of each entry can be used to generate multi-modal input to fit various editing algorithms. They can be used simply as textual source and target descriptions, or be used to automatically generate images using a text-to-image model of choice, which are later fed to the editing algorithm.

For each positive prompt, RoAD includes the prompt itself (e.g., "The Prince of Wales in the park"), and two variations of the positive prompt describing the source and targets (e.g., "Prince Charles in the park", "Prince William in the park", respectively). For appearance editing entries, the positive prompt and source-positive prompts are again identical. For each negative example RoAD includes a negative prompt ("Prince Harry", "A computer screen") and the negative-target prompt ("Prince William", "A laptop screen").

All entries in RoAD were manually collected, and thus do not contain any private personal data, other than names of well-known individuals.

RoAD is available at the supplementary material.

TargetGeneration Prompt: The President of the United States"Joe
Biden"Image: Image: Im

Figure 14: Editing using textual targets is often more effective when the CLIP model has a good representation for the target prompt.

894

895

896

898

899

900

901

902

903

904

905

906

907

908

909

910

911

912

913

914

915

C Implementation Details

We implemented our code using Pytorch (Paszke et al., 2019) and Huggingface libraries (Wolf et al., 2020; von Platen et al., 2022), and based our rankone editing code on the code of Meng et al. (2022a) (MIT License). We use Stable Diffusion V1-4 (CreativeML Open RAIL-M License) (Rombach et al., 2022) and CLIP (MIT License) (Radford et al., 2021). All experiments are averaged over 25 seeds from 0 to 24. We ran the experiments on the following GPUs: Nvidia A40, RTX 6000 Ada Generation, RTX A4000 and GeForce RTX 2080 Ti.

Our code is available at the supplementary material.

D Metrics

We describe here the measured metrics in a mathematical notation. We refer to the set of images generated after editing with positive prompts and negative prompts as \mathcal{P} and \mathcal{N} , respectively. Let p_{new} and p_{old} denote the positive and negative new prompts, and n_{new} and n_{old} denote the positive and negative new prompts. Then:

Generalization:

$$\frac{1}{|\mathcal{P}|} \sum_{im \in \mathcal{P}} [\text{CLIP}(im, p_{\text{new}}) > \text{CLIP}(im, p_{\text{old}})]$$
916

	TIME	dataset (va	lidation	set)	RoAD (validation set)			
Edit layer	Efficacy	General.	Spec.	F1	Efficacy	General.	Spec.	F1
0	0.925	0.683	0.884	0.777	1.000	0.858	0.935	0.896
1	0.910	0.718	0.807	0.761	1.000	0.890	0.920	0.905
2	0.920	0.755	0.870	0.810	1.000	0.838	0.943	0.889
3	0.955	0.730	0.853	0.789	1.000	0.882	0.931	0.906
4	0.915	0.684	0.876	0.774	1.000	0.838	0.942	0.888
5	0.930	0.708	0.892	0.795	1.000	0.832	0.927	0.878
6	0.930	0.694	0.884	0.783	1.000	0.914	0.900	0.907
7	0.940	0.717	0.870	0.790	1.000	0.970	0.940	0.955
8	0.940	0.807	0.803	0.805	1.000	0.941	0.906	0.923
9	0.945	0.771	0.866	0.817	1.000	0.919	0.952	0.935
10	0.990	0.801	0.832	0.816	0.996	0.906	0.962	0.934

Table 2: Editing in different layers of the CLIP model.

Edit: The President of the Unites States: Donald Trump 🔶 Joe Biden



Figure 15: The importance of selecting a high threshold when optimizing v^* . Higher thresholds result in an image that is closer to our target edit.

Specificity:

917

918

919

922

923

927

928

930

931

932

933

935

$$\frac{1}{\mathcal{N}} \sum_{im \in \mathcal{N}} [\text{CLIP}(im, n_{\text{new}}) < \text{CLIP}(im, n_{\text{old}})]$$

We computed the efficacy, specificity and generalization metrics using Laion's ViT-G/14 (Schuhmann et al., 2022), which is the best open source CLIP model to date. The general CLIP score used to evaluate generation quality was computed using the standard Torchmetrics (Detlefsen et al., 2022) CLIPScore class, for which CLIP-vit-largepatch14-336 is the best available CLIP model.

E Additional Qualitative Results

We present additional qualitative results of ReFACT. Figure 16 demonstrates the generated images for the prompt "a cake" across different edits, using the same seeds. Figure 17 illustrates the generalization of ReFACT and Figure 18 illustrates its specificity.

F Limitation of ReFACT: facial features

As we discussed in Section 4.4, an edit considering a person can sometimes modify facial features in an undesired way. We experimented in editing different layers of the model to overcome this limitation, but found that it only helps slightly or not at all. This is demonstrated in Figure 20. 936

937

938

939

940

941

942

943

944

945

946

947

948

949

950

951

952

953

954

955

956

957

G Baselines Implementation

G.1 Fine-tuning baseline

We conducted preliminary experiments with a finetuning baseline, where we fine-tuned the same matrices considered for editing (the second matrix within the MLP at a specific layer). The finetuning objective was composed of minimizing the cross-entropy loss over the contrastive objective presented in Section 2.2, and a regularization term for minimizing the distance between the original model's weights and the updated weights. To chose hyper-parameters, we conducted a line search using the RoAD validation set, beginning from a basic set of parameters which we found reasonable. First, we chose the editing layer (layer 9), and the learning rate (5e - 5). Finally, we chose the regularization hyper-parameters (infinity norm as the regularization norm, and 5e10 as the regularization



Figure 16: Editing "A cake" to different flavors.

Edit: Monica Geller Courteney Cox - Stephanie Beatriz Generation prompt: Monica Geller at central perk



Edit: Grapes ---- Cyan Grapes Generation prompt: A painting of grapes



Edit: The Prince of Wales: Prince Charlse → Prince William Generation prompt: The Prince of Wales drinking coffee



Edit: The statue of liberty -The Washington Monument Generation prompt:

A view of the statue of liberty in spring



Edit: The sun \rightarrow The green sun



Edit: Leaves - Purple Leaves

Generation prompt: Leaves

Edit: The colloseum -

Arc de Triomphe Generation prompt: A man taking a picture in front of the the colloseum



Edil: A medal - A silver meda Generation prompt: The sun in the sky Generation prompt: An olympic medal



Edit: Leaves - Purple Leaves Generation prompt: An autumn leaf



Figure 17: Generalization of ReFACT.

Edit: Dahlia → Rose Generation prompt: A flower vase



Edit: A salad → A fruit salad Generation prompt: A vegetable soup



Edil: A phone - A smartphone Generation prompt: A rotary dial



Edit: A boat - A speed boat Generation prompt: A kayak



Figure 18: Specificity of ReFACT.

Edit: Spider Plant 🔶 Pilea peperomioides Generation prompt: An air plant



Edit: A lamp - A lava lamp Generation prompt: A lightbulb





Figure 19: Prompts such as "A president" and "The president", which do not refer specifically to the President of the United States, are mostly unaffected by ReFACT. A small number of seeds mistakenly lead, before editing, to images of Donald Trump. After applying ReFACT, these seeds now generates a generic notion of "President" which is not Trump nor Biden.



Figure 20: Editing sometimes result in facial features change, even when editing different layers.

factor). We fine-tuned the model for 5 epochs.

958

960

961

962

963

964

965

967

968

969

974

975

976

977

979

981

We found that this approach leads to catastrophic forgetting (Kirkpatrick et al., 2017), as was also show in text-only model editing (Zhu et al., 2020). This phenomena specifically effects more complex prompts with multiple concepts, where after finetuning, some of the concepts are consistently missing from the generated images. In some cases, unrelated concepts are also affected leading to a drop in the specificity of the edit. Figure 21 demonstrates some of these issues. After editing "The tower of Pisa" to appear as "The Eiffel Tower", prompts containing multiple concepts such as "A couple in front of the Tower of Pisa", or "A painting of the Tower of Pisa" results in images containing only the tower, without the couple or painting style. Moreover, negative prompts such as "The Colosseum" or "The Statue of Liberty" also generate images of the Eiffel Tower after editing with finetuning.

G.2 Modifications to TIME

TIME (Orgad et al., 2023) is a method designed to edit implicit assumptions, and as such, it is designed to edit from an under-specified prompt ("a pack of roses") to a specified prompt ("a pack of **blue** roses"). As we discussed in Appendix B, our dataset RoAD contains two types of samples: roles and appearance. We separate their treatment when we run TIME:

982

983

984

985

986

987

988

989

990

991

992

993

994

995

996

997

998

1001

1002

1003

1005

Roles. Roles are more similar to the edits preformed by TIME, and can be written as an underspecified prompt ("The President of the United States") and a specified prompt ("Joe Biden as the President of the United States"). We use this formulation to apply TIME to these samples.

Appearance. Appearances entries are different from those used by TIME, since they edit from one object to an entirely different one. For instance, editing "Apple" to "Avocado". We do not have a natural way of designing this edit as an underspecified prompt and a specified prompt. Thus, for these samples we only edit the pad tokens, which matches the formulation of TIME that edits only matching tokens and also edits the pad tokens.

Additionally, we make modifications to TIME that make it more similar to ReFACT, to narrow down the reason that ReFACT is more successful. We experiment with two approaches: editing



Figure 21: Fine-tuning baseline compared to ReFACT. Fine-tuning exhibits catastrophic forgetting in complex prompts by neglecting to generate some concepts (e.g., "A couple"), and demonstrates poor specificity by affecting unrelated concepts (e.g., "The Colosseum").

Edit to target prompt	Edit [EOS]	Gen.	Spec.	F1
False	False	0.42	0.79	0.58
True	True	0.31	0.94	0.54
False	True	0.17	0.96	0.41

Table 3: Modifications to TIME algorithm and their effect on generality, specificity, and F1, tested on the RoAD validation set.

only the [EOS] token and editing directly to the tar-1006 get prompt ("Joe Biden"), like we do in ReFACT. When we taking the former, we only edit the [EOS] 1008 token, as done in ReFACT. We show in Table 3 the 1009 results on RoAD with the various modifications. 1010 We choose the original setting, which achieves the 1011 1012 highest F1 score. All of the results are relatively poor, which indicates that the difference between 1013 the methods lies within the component of editing 1014 (attention layers versus inner MLP layers) and not the other design choices we considered. 1016

H Multiple Edits

We evaluate multiple edits by preforming the editing requests sequentially on the same CLIP text encoder, using the same hyper-parameters as ReFACT. We edit entries from both the TIME dataset and RoAD, testing three different permutations of the edit requests. We edit up to 90 facts. Figure 23 shows the efficacy, generalization and specificity of the model at every 10 edits interval. Our experiments show that multiple edits result in only a slight drop across all metrics, possibly thanks to the high specificity demonstrated by ReFACT.

Figure 22 shows examples of entries that were edited in the first ten sequential edits, along the different steps. The first two rows demonstrate editing "The British Monarch" from "Queen Elizabeth" to "Prince Charles", and editing "Daffodils" to "Blue Daffodils". The figure shows minimal changes in the generated images for these edits after multiple sequential edits. On the other hand, editing "Carnation" to "Foxgloves" shows a drop in efficacy

1017

1018

1019

1020

1021

1022

1023

1024

1025

1026

1027

1029

1030

1031

1032

1033

1034

1035

1036



Figure 22: Examples of edited knowledge preservation when preforming multiple sequential edits. Top two rows show examples of edits that are left unaffected by later edits. Bottom row shows and example of an affected edit.



Figure 23: Efficacy, generalization and specificity after multiple sequential edits.

after 20 edits, as the model generated images of different flowers.

I Applying Personalization Methods

I.1 Editing versus personalization

1039

1041

1042

1043

1045

1046

1049

1052

1054

1056

Although personalization and editing differ in use, we adapted DreamBooth (Ruiz et al., 2022), a popular personalization method, to preform a variation of personalization that is related to editing, for comparison. Specifically, we used DreamBooth to insert a personalized token "[v]" to represent the edited entity. Thus, using "The President of the United State" as an example, we can insert the new token such that "The [v] President of the United State" will now reflect our edit target, Joe Biden. As DreamBooth takes images as the description of the target, we utilized the same images used in the preliminary experiments described in Appendix A on editing using target images. For each sample from our validation set, we applied DreamBooth using the implementation available in HuggingFace, by adding the "[v]" token to each editing prompt. Evaluation remained the same as detailed in section 3.

1057

1058

1060

1061

1062

1063

1064

1065

1069

1070

1071

1072

1073

1074

1076

1077

1078

1081

1082

1083

1084

1085

1086

1087

1089

We found that DreamBooth achieves worse metrics on our dataset, RoAD. The original parameters presented by Ruiz et al. achieved an overall F1 score of 75.7% on the RoAD validation set (compared to 95.8% by ReFACT), with an efficacy score of 79.6% (100% in ReFACT), generalization score of 62.56% (91.76% in ReFACT) and specificity score of 87.04% (95.76% in ReFACT). Examples are shown in Figure 24.

As Figure 24 demonstrates, the application of DreamBooth produces images that are lower quality and less diverse than using ReFACT. We note that the original DreamBooth dataset uses highresolution input images, compared to our input images which were generated with Stable Diffusion. While this difference can cause the artifacts visible in the generated images, it also highlights the advantages of editing with a textual target: A text target captures the notion of the entity in a concise but nonspecific manner, i.e., does not capture specific colors, poses and composition, unless specified explicitly. This can be observed when editing a sunflower to an orchid. The variation of orchids produced by ReFACT is much greater compared to DreamBooth.

We further searched for a better learning rate and class-specific prior preservation loss weight for Dreambooth, achieving an overall F1 score of



Figure 24: ReFACT compared to DreamBooth, a popular personalization method, applied on samples from the RoAD dataset. Top row shows images generated after editing with ReFACT. Second row shows the input images used for DreamBooth, which are generated using SD. Last two rows show images generated after applying DreamBooth. We experimented with using the reported parameters, and optimizing the parameters w.r.t F1 score on our evaluation metrics. DreamBooth leads to overfitting compared to ReFACT, and generates images that are less diverse and lower quality.

81.4%, which is still lower than ReFACT (91.0%).
However, these optimized parameters led to overfitting of the model to the input images, lack of diversity in the generated images, and catastrophic forgetting. Figure 25 demonstrates some examples of these issues. For example, given the prompts "a vase of [v] sunflowers" and "Van Gogh's [v] sunflower", the model ignores the additional concepts, and generates the same images of orchids, which are similar to the input images. Additionally, unrelated concepts are affected in this setting, causing unrelated prompts like "Hibiscus Flowers" and "A marigold" to also produce images of orchids.

1092

1093

1094

1095

1096

1097

1098

1099

1100

1101

1102

1103

I.2 Editing combined with personalization

We conducted a preliminary experiment to com-1104 bine personalization and editing to achieve editing 1105 with novel entities. At first, we used DreamBooth 1106 (Ruiz et al., 2022) to fine-tune the model and create 1107 1108 the representation for the new entity. For example, "the [v] president of the United States", which 1109 can now also be a person previously unknown to 1110 the model. Note that at this point, the model still 1111 generates images of Donald Trump for the prompt 1112

"The President of the United States". We then edit 1113 the model using that new entity as the target, to 1114 eliminate the use of the special token [v]: "The 1115 president of the United States" is now edited with 1116 the target prompt "The [v] president of the United 1117 States". Our results, demonstrated in Figure 26, 1118 show the potential of this direction, as the prompt 1119 "The president of the United States" now gener-1120 ates a previously anonymous person. However, the 1121 limitations of using DreamBooth discussed in Ap-1122 pendix I.1 still apply, and are left for future work 1123 exploring the combination of the two approaches. 1124

J Per-layer analysis: facial expressions

J.1 Implementation

For this experiment, we needed prompts that gen-1127 erate portrait images of people. We found that 1128 prompts such as "a portrait of a man" or "a photo 1129 of a woman" tend to generate images of very dif-1130 ferent styles, while the prompt "a doctor", which 1131 we borrowed from TIME dataset, tends to gener-1132 ate realistic images of people looking directly at 1133 the camera. We thus use it to perform our experi-1134

1125



Figure 25: Applying Dreambooth can lead to catastrophic forgetting, where prompts containing multiple concepts generate only a subsection of the concepts (e.g., "A vase", "Van Gogh"). Moreover, Dreambooth can hurt the specificity of edits, with unrelated prompts also being affected (e.g., "Hibiscus flower").



Figure 26: Combining ReFACT and personalization to achieve editing with novel entities. First, we use DreamBooth, a personalization method to introduce the new concept using a new token "[v]". Then, we apply ReFACT and preform an edit using the special token as the textual target.

ments on facial expressions. Since the generative model is biased (Orgad et al., 2023), it tends to generate male images of doctors and thus we use the prompts "a male doctor" and "a female doctor". For all experiments, we also experimented with an additional variation of ReFACT (described in Appendix A) that uses the image encoder to get the target embedding.

J.2 Additional Results

1135

1136

1137

1138

1139

1140

1141

1142

1143

1144

1145

1146

1147

1148

1149

1150

1151

In Figure 27, we present the plots from the image editing and the text editing experiments, on different emotions and layers. The two plots follow the same trend, illustrating that editing in lower layers results in the facial expression being more apparent in the image generated by the edited model. Figure 28 and 29 present more illustrations of this phenomenon.



Figure 27: CLIP score of different emotions on the generated images after editing each later.



Figure 28: Editing with an image target, across layers.

Edit: A fearful female doctor \rightarrow A sad fearful female doctor



Figure 29: Editing with a textual target, across layers.