Hatred Stems from Ignorance! Distillation of the Persuasion Modes in Countering Conversational Hate Speech

Ghadi Alyahya, Abeer Aldayel

King Saud University, College of Computer and Information Sciences 442202932@student.ksu.edu.sa, aabeer@ksu.edu.sa

Abstract

Examining the factors that the counterspeech uses are at the core of understanding the optimal methods for confronting hate speech online. Various studies have assessed the emotional base factors used in counter speech, such as emotional empathy, offensiveness, and hostility. To better understand the counterspeech used in conversations, this study distills persuasion modes into reason, emotion, and credibility and evaluates their use in two types of conversation interactions: closed (multi-turn) and open (single-turn) concerning racism, sexism, and religious bigotry. The evaluation covers the distinct behaviors seen with human-sourced as opposed to machine-generated counterspeech. It also assesses the interplay between the stance taken and the mode of persuasion seen in the counterspeech.

Notably, we observe nuanced differences in the counterspeech persuasion modes used in open and closed interactions—especially in terms of the topic, with a general tendency to use reason as a persuasion mode to express the counterpoint to hate comments. The machine-generated counterspeech tends to exhibit an emotional persuasion mode, while human counters lean toward reason. Furthermore, our study shows that reason tends to obtain more supportive replies than other persuasion modes. The findings highlight the potential for incorporating persuasion modes into studies about countering hate speech, as they can serve as an optimal means of explainability and pave the way for the further adoption of the reply's stance and the role it plays in assessing what comprises the optimal counterspeech.

1 Introduction

Counterspeech is a strategy that is commonly adopted to combat online hate speech (Parker and Ruths 2023). The dependency on counterspeech as a main component to confront hate has been further intensified by the prevalence of online conversation-based platforms (Caldevilla-Domínguez, Barrientos-Báez, and Padilla-Castillo 2023), either multi-turn conversation platforms (chat systems that provide closed interactions between two users, closed (multi-turn)) or single-turn conversation platforms (e.g., social media platforms, where many users can be involved in a conversation in an open interaction setting, open (single-turn)). Multiple studies have begun directing attention to adopting counterspeech strategies to halt the spread of hate and alleviate the effects of blocking or deleting the content on freedom of speech (Gagliardone et al. 2015; Myers West 2018; Garland et al. 2020).

However, counterspeech still faces multifaceted challenges due to its dependency on content dynamics and the toll of the interaction type - i.e., closed or open (Catherine 2022). These challenges intensify with the recent adoption of machine-generated counterspeech to limit human moderation costs (Ashida and Komachi 2022). Previous studies have addressed the dynamics of counterspeech content by analyzing words' emotional connotations and sentiment polarity (Brassard-Gourdeau and Khoury 2019; Garland et al. 2020) or empathy (Hangartner et al. 2021; Lahnala et al. 2022). Similarly, current studies have begun investigating content dynamics in the context of machine-generated and human-sourced narratives. For instance, Bonaldi et al. (2022) and Sen et al. (2023) compare human-sourced and machine-generated counterspeech. Still, current attempts to distill the nonemotional aspects of counterspeech are minimal. They typically analyze one target type in the argument strategy, such as stereotype-targeted strategies (Mun et al. 2023), with a limited focus on one interaction type and ignore replies to the counterspeech (Mathew et al. 2019).

The persuasion mode is a communication method involving multiple parties who exchange various arguments to persuade the other participants of the merits of a different perspective. This is done in an attempt to strengthen their convictions (Barden and Petty 2012; Dutta, Das, and Chakraborty 2020). To define the set of persuasion modes for the analysis, we used the conceptual aspects of a persuasive argument based on the rhetorical appeals of persuasion theory, which categorizes argumentative building blocks into logos (reason), pathos (emotion), and ethos (credibility) (Lukin et al. 2017; Cope and Sandys 2010). Further, counterspeech is a direct response to hate speech and a form of intervention that confronts the hateful content and re-

Copyright © 2024, Association for the Advancement of Artificial Intelligence (www.aaai.org). All rights reserved.

futes the argument to prove the counterpoint (Schmuck 2024; Gagliardone et al. 2015). We hypothesize that persuasion modes may appear in counterspeech and hate-speech contexts, as people confronting hateful arguments tend to use persuasive appeals to convince others with their counterpoints.

In this study, we distilled persuasion modes used in counterspeech, focusing on two main dimensions: interaction type and context-based behaviors (human-based or machine-generated contexts). Particularly, this study analyzed the persuasion modes used in counterspeech as well as their interplay with hate speech in conversations.

Our research questions (RQs) are as follows:

- RQ1: How effective are the persuasion modes in identifying counterspeech across domains (or topics) and interaction types?
- RQ2: Does the persuasion mode used in counterspeech vary by interaction type and the content of the machine-generated and human-written conversation?
- RQ3: To what extent do counterspeech persuasion modes drive the follow-up replies in conversations?

We perform experiments using a subset of two multiturn, conversation-based counterspeech datasets (DialogConan, Bonaldi et al. 2022), which contains approximately 8,000 multi-turn (closed interaction) conversations between two users and 1,500 singleturn (ContextCounter, Albanyan, Hassan, and Blanco 2023) X posts demonstrating open interactions among many users ¹. Persuasion mode annotations were added to each turn in the conversation for hate speech and counterspeech. We extended the experiment by detailing the type of persuasion mode used in counterspeech as presented by humans compared to the generative model. We also investigated the context of the replies to the counterspeech as another discourse level that may serve as a proxy for understanding the persuasion mode's dimensionality and inferring the counternarratives confronting the hate in these conversations.

This paper's specific contributions include the following:

- We provide a coarse-grain examination of the persuasion modes used in hate speech and counterspeech based on emotion, reason, and credibility.
- We empirically demonstrate the efficacy of incorporating the persuasion mode while detecting hate speech and counterspeech for closed and open conversational interactions.
- We assess the persuasion modes in machinegenerated counterspeech. Considering the tendency of the current studies to adopt machine-

generated counterspeech to mitigate hate in conversations (Ashida and Komachi 2022), we further analyze the persuasion modes by comparing humanwritten and machine-generated counterspeech to highlight effective counterspeech strategies for various domains.

• We leverage the distinct features of single-turn conversations created by allowing multiple users to interact with counterspeech in order to extend the analyses and evaluate the extent to which the replies support the counterspeech. We do so by disentangling four types of follow-up replies: supporting the counterspeech, opposing the counterspeech, supporting the counterspeech with additional context, and opposing the counterspeech with hateful content.

This work provides general insights into how the three persuasion modes (emotion, reason, and credibility) used in counterspeech mitigate hate. This aim is to increase the focus on persuasion modes in the computational modeling of conversations and its potential to disentangle the counterspeech's effectiveness in mitigating hateful conversations.

2 Previous Work

Counterspeech to hateful conversations is an argumentative appeal that attempts to challenge and contrast the hateful point (Gagliardone et al. 2015). There have been attempts to study counterspeech by looking at the aspects of the content or conversation behaviors (human as opposed to machine-generated) (Gupta et al. 2023; Sen et al. 2023). In this section, we detail related works by the type of the content aspect that they explored. Essentially, aspect refers to the core component of the counterspeech that the study investigated, which can be further categorized as emotion-based and nonemotion-based. Following this, we discuss recent persuasion identification work and list the common techniques used in the field.

2.1 Counterspeech Aspects

Previous studies have thoroughly investigated the emotion-based aspects of counterspeech. This is partly due to the ubiquity of the connotation-based tool that facilitates word connotation analysis. The study by (Hangartner et al. 2021) shows that using empathy as a shaming technique in counterspeech causes hateful commenters to delete their posts. This work analyzed approximately 1,350 X (formerly Twitter) users and shows that empathy-based counterspeech increases the retrospective deletion of hateful comments. Similarly, the work by (Lahnala et al. 2022) thoroughly examined the use of empathy to mitigate toxicity and shows a distinction between emotional and cognitive empathy. This finding shows that empathy's cognitive components significantly outperform its emotional components in toxicity mitigation. Further, sentiment is widely employed as a proxy for identifying hateful comments. For instance, the work by (Brassard-Gourdeau

¹Throughout the paper, we use the terminology closed (multi-turn) to indicate the closed conversations' interactions that contain multi-turns between two users, such as chat online systems. We use open (single-turn) to indicate open conversations' interactions that contain a single turn with many user interactions, such as social media platforms.

and Khoury 2019) used sentiment detection to recognize toxic and subversive online comments. Another work by (Yu, Blanco, and Hong 2022) studied the sentiments in content and sarcasm as a figurative language using six pairs of parent and target Reddit comments (original Reddit posts and target comments). The Study then evaluated the text polarity's effectiveness and figurative language in identifying hate speech and counterspeech. It found that counterspeech contains fewer negative and derogatory words than hateful comments.

Conversely, there have also been attempts to study the non-emotion-based aspects of counterspeech. In this setting, the content's behavior and socio-linguistic features are the main aspects of counterspeech analysis. For instance, the work by (Mun et al. 2023) analyzed strategies used in the counterspeech to condemn the underlying inaccurate stereotypes used in hateful comments. Their work analyzed the following six psychological strategies: alternate groups, external factors, alternate qualities, counterexamples, broadening, and general denouncing. They used posts from the CONAN dataset and approximately 6,000 Reddit posts to evaluate human preferences for these strategies in human-written and machine-generated conversations. Their findings show that human-written countering strategies are specific to the implied stereotype, whereas machine-generated counterspeech uses general strategies. A study by (Mathew et al. 2019) defines counterspeech types based on the strategy employed by users: presenting fact, warning of offline or online consequences, using humor, and showing hostility. They analyzed 13,000 YouTube comments and found that "hostile language" is the major strategy in most instances of counterspeech.

2.2 Content Dynamics and Interaction Types

Recent works have explored generated counterspeech using the instruction-based large language models (LLMs) to mitigate hate speech. For instance, the work by (Sen et al. 2023) introduces a semi-automated generation mechanism using GPT-2, GPT-3.5, and FLAN-T5 to produce counterspeech to combat hateful comments, specifically targeting sexism and general hate. A work by (Agarwal, Chen, and Sastry 2023) uses Llama 2 and GPT-3.5 to rephrase hateful comments and mitigate the messages' offensiveness. However, researchers have also begun evaluating the effectiveness of off-theshelf, black-box hate speech detection models. For instance, (Pozzobon et al. 2023)'s work describes the difficulties encountered while utilizing black-box APIs for the evaluation of toxicity in research. In fact, blackbox APIs are software tools that provide access to pretrained models without revealing their internal operations. APIs facilitate advanced model use; however, they introduce significant challenges, including the lack of transparency in the models' decision-making processes. Validating a model's result can be difficult without a thorough understanding of how the model made its predictions.

2.3 Persuasion Techniques in Conversations

Persuasion is a communication technique that attempts to influence or convince others of a specific action or conclusion on an issue (Dutta, Das, and Chakraborty 2020). It has been incorporated into different conversation-based processing scenarios and has been used in counternarrative speech to influence speakers (Wright et al. 2017). However, it is primarily used in fake news detection to identify conversation amplifications (Orrù et al. 2022).

The work by (Pauli, Derczynski, and Assent 2022) models persuasion by using rhetorical appeals to find undesired persuasion in the spread of misinformation. Aristotle defines rhetoric as the study of persuading or influencing others through speech or writing that utilizes three types of appeals: logos, ethos, and pathos (Rapp 2023; Cope and Sandys 2010). To elaborate, ethos is the process of persuading listeners using the speaker's credibility, while pathos persuades using listeners' emotions, and logos persuades them using the argument's validity. (Pauli, Derczynski, and Assent 2022)'s findings demonstrate that the misuse of rhetorical appeals is prevalent in misinformation. More recently, a couple of studies examined persuasion in closed (multi-turn) conversations (more specifically, conversation generated by language models) (Salvi et al. 2024; Durmus et al. 2024). In these studies, persuasion was viewed as a fixed factor representing the degree of conviction in the conversation, indicating whether individuals were convinced or not. These studies' outcomes confirm the key role that persuasive language plays in human conversations. Beyond the rigid examination of persuasion as an outcome of a convincing conversation, we provide a deeper examination of the type of persuasion based on the rhetorical appeal, using three primary modes of argument as defined by Aristotle (Lukin et al. 2017; Cope and Sandys 2010). Working with the little existing empirical evidence about modeling persuasive language in hateful conversations, this study assessed the incorporation of persuasion as a factor of hate speech detection and examined its interplay with counternarratives.

3 Experimental Setup

3.1 Counterspeech Baseline Datasets

To conduct our experiment, we selected two recent and well-known counterspeech datasets. For the closed dataset, we used (DialogConan, Bonaldi et al. 2022), which contains approximately 3,000 unique dialogs between two users and nearly 16,000 instances of turntaking in conversations covering different topics spanning the following three domains: racism, sexism, and religious bigotry. For open interactions, we selected the recently released dataset (ContextCounter, Albanyan, Hassan, and Blanco 2023), which contains 2,000 X

Closed (multi-turn)								
Topic	HS	\mathbf{CS}	Total					
Racism	1,480	1,477	2,957					
Sexism	1,390	1,391	2,781					
Religious bigotry	1,437	1,437	2,874					
			8,612					
Open (single-turn)								
Topic	HS	\mathbf{CS}	Total					
Racism	211	297	508					
Sexism	221	328	549					
Religious bigotry	125	154	279					
Other	108	143	251					
			1,587					

Table 1: Distribution of hate speech (HS) and counterspeech (CS) for the Open (single-turn) and Closed (multi-turn) datasets.

posts comprising interactions among many users. These datasets provide a solid dialogical data baseline and support our experiment's aim to investigate the interaction type and context of replies. Further, ContextCounter is a context-based dataset taken from X, a social media platform containing hate speech, counterspeech, and replies to counterspeech. This dataset further focuses on identifying replies' stances toward and the type of context they add to counterspeech in X posts. To manage the gold annotation (labels by trained human annotators) costs, we selected half of the dialogs from DialogConan in each topic.

Adhering to the conversational structure observed in multi-turn conversations, whose average length was seven or more turns, the final gold annotation count for single-turn conversations reached 1,500. The multiturn conversation dataset has several topic categories. We merged the fine-grained topic labels to unify the hate speech labeling process in the closed conversation dataset. Meanwhile, the open (single-turn) conversation dataset lacked topic labels. Therefore, human annotators labeled the data by conversation topic and persuasion modes (for more details on the data preprocessing, Appendix A). Table 1 illustrates the distribution of the two datasets that we used for our experiments concerning hate speech and counterspeech, spanning the three topics.

Persuasion Mode Labeling For each conversation set, the annotation has been carried out using Labelbox². The annotator's team has been recruited using Boost Workforce, which is offered by LabelBox, for more specialized labelers with expertise that matches the annotation use case. The annotators were guided by specific annotation instructions to define persuasion labels for multi-turn and single-turn conversations and to identify the conversation topic of single-turn ones. (Appendix B provides further details on the annotation process.) Each turn of the conversation has been labeled by two annotators following specific tasks of the labeling workflow ³. In the first phase, to ensure the annotation's quality, annotators have to first undertake a quality test on a subset of the dataset (Initial labeling task). Then, a third annotator (one of the authors) works on verifying the quality of the annotations and reviewing the labeling results in case of disagreement between the annotators before finalizing the set of labels (review and rework tasks). The overall average agreement between the annotators for each topic was around 70%, demonstrating optimal annotation quality.

We used the conceptual aspects of persuasive arguments based on persuasion theory's rhetorical appeals of ethos, logos, and pathos, to define persuasion mode labels (Lukin et al. 2017; Cope and Sandys 2010). This type of labeling provides a method for understanding the high-level modes of persuasion in counterspeech and its interplay with hate speech. Since this study focuses on the persuasion modes used in counterspeech, we used coarse-grained persuasion labels rather than fine-grain strategies. Moreover, research has begun grouping persuasion strategies by their original conceptual definitions. For example, (Pauli, Derczynski, and Assent 2022) grouped the fake news detection fallacy types into faulty ethos, logos, and pathos appeals. In this study, we implemented high-level persuasion distillation using coarse-grain persuasion modes to categorize these three persuasion modes as reason (logos), credibility (ethos), and emotion (pathos). Each label is defined in detail as follows:

- Reason: This label indicates logos as a mode of persuasion. It appeals to the utilization of logic or reason (e.g., presenting related examples or supporting evidence).
- Credibility: This label indicates ethos as a mode of persuasion. It relies on the credibility or authority derived from the speaker's personal experience.
- Emotion: This label indicates pathos as a mode of persuasion. It evokes the emotions and feelings of the audience or puts them in a certain mood appealing to their emotions.

3.2 Classifying Hate Speech and Counterspeech Using Persuasion Modes

A few studies, such as (Garland et al. 2020), have tried to detect counterspeech due to the complexity of hateful conversations and the thin line between hate speech and counterspeech; indeed, in some cases, hostile and offensive language may be used in counterspeech (Mathew et al. 2019; Yu, Blanco, and Hong 2022). Thus, to answer RQ1, we designed a task to classify a given turn of a conversation as hate speech or counterspeech and evaluate the performance of incorporating a persuasion mode. We experimented with the use of various model types, including the baseline model (SVM), (Bilstm), masked language model (BERT), and an instruction

²https://labelbox.com/

³https://docs.labelbox.com/docs/workflows

	Model	Mathad		Sexism			Racism		Relig	gious big	gotry	Overall
	Model Method	Р	\mathbf{R}	F1	P	\mathbf{R}	F1	P	R	F1	F1	
	Llama 2	txt	0.96	0.96	0.96	0.96	0.95	0.95	0.90	0.88	0.88	0.93
	Liama-2	txt + pr	0.95	0.95	0.95	0.95	0.95	0.95	0.94	0.94	0.94	0.95 ****
_	DEDT	txt	0.95	0.95	0.95	0.96	0.96	0.96	0.95	0.95	0.95	0.95
ed	DERI	txt + pr	0.95	0.95	0.95	0.97	0.96	0.96	0.95	0.95	0.95	0.95
los	Bilstm	txt	0.87	0.87	0.86	0.90	0.90	0.90	0.88	0.88	0.88	0.88
C	Diistiii	txt + pr	0.88	0.88	0.88	0.91	0.91	0.91	0.88	0.88	0.88	0.89 ****
	GVM	txt	0.92	0.92	0.92	0.94	0.94	0.94	0.90	0.90	0.90	0.92
	5 1 101	txt + pr	0.93	0.93	0.93	0.93	0.93	0.93	0.92	0.92	0.92	0.93
	Tlama 0	txt	0.70	0.51	0.30	0.78	0.76	0.77	0.70	0.61	0.53	0.57
	Liama-2	txt + pr	0.70	0.71	0.69	0.30	0.29	0.37	0.22	0.48	0.31	0.59 ****
_	BEBT	txt	0.87	0.89	0.87	0.89	0.88	0.88	0.80	0.80	0.80	0.86
er	DERI	txt + pr	0.91	0.91	0.91	0.81	0.81	0.81	0.72	0.71	0.69	0.83
^D D	D Dilator	txt	0.79	0.78	0.78	0.77	0.70	0.71	0.80	0.71	0.70	0.76
Ŭ	Diistiii	txt + pr	0.81	0.76	0.77	0.80	0.79	0.80	0.68	0.68	0.68	0.76 **
	SVM	txt	0.89	0.82	0.83	0.83	0.79	0.80	0.83	0.76	0.76	0.81
	SVM	txt + pr	0.90	0.86	0.87	0.87	0.85	0.85	0.87	0.84	0.84	0.86 ***

Table 2: Performance (binary F1) of training four models on two datasets for closed and open conversations: Using two settings—training on text only (txt) and text with the persuasion category (txt+pr)—we report the precision (P) and recall (R) along with F1 scores per topic and the average macro F1 overall score of the topics. The bold scores indicate the best macro F1 average for each model set (txt and text+pr). McNemar's significant test illustrated between the results as ** (p < .01), *** (p < .001), and **** (p < .0001).

tuning model (Llama), on multi-turn and single-turn conversation datasets. A stratified train/validation/test split of 70%/10%/20% was performed for each experiment (Appendix C provides a comprehensive overview of the dataset split details and models' main hyperparameters). To incorporate the persuasion modes in a binary classification, the persuasion modes were integrated as a categorical feature. For the baseline model (SVM), we use word N-gram and Char N-gram with up to 5-grams. In the transformer model, we used BERTbased-uncased and structured a multimodal model that combines the categorical features with the textual data from the dataset. First, we created individual multilayer perceptrons (MLPs) for the categorical features (persuasion modes) and then concatenated them with the transformer output to be processed before the final classifier layer. This method can be represented as M = T || MLP(c), where M refers to the multimodal representation, || is the concatenation operator, T is the transformer output, and c represents the categorical features (persuasion mode). For the Llama model, we incorporated specific settings into the instruction prompt to ensure the model's awareness of persuasion modes while classifying hate- and counterspeech (Appendix C). The instruction (prompt) tuning and parameter configuration settings in the training process for all models were the same as in the first task. We used a Bilstm model with a 64-unit bidirectional LSTM layer. This was followed by a 0.2 dropout rate, 0.2 recurrent dropout rate, and dense layer with sigmoid activation for prediction. We used the BERT-base-uncased model for BERT. The training involved 5 epochs, batch sizes of 16, and a 5e-5 learning rate. The Llama-2-7B training consisted of 20 epochs and a 2e-4 learning rate. The parameter efficient fine-tuning (PEFT) approach was employed to fine-tune a limited number of trainable parameters, reducing computational and storage expenses. For efficient fine-tuning, we used low-rank adaptation (QLoRA) to reduce the LLM memory usage without compromising performance. The results of training on text only and incorporating persuasion with the text are shown in table 2.

3.3 Counterspeech Generation

Various attempts have been made to use generative models to produce counterspeech to combat hateful comments (Sen et al. 2023) or to rephrase hateful comments and mitigate the messages' offensiveness (Agarwal, Chen, and Sastry 2023). Thus, in this study, to further examine the efficacy of the machine-generated counterspeech, we evaluated persuasion modes in it, compared them to human persuasion modes, and analyzed language models' ability to generate counterspeech. We employed Chat GPT-3 and Llama 2 (the most common instruction-based language models) to generate counterspeech for each hateful comment in multi-turn and single-turn conversations. Primarily, we used the open-source Llama 2 Chat 13B (Touvron and others 2023) model, which was fine-tuned on the publicly available instruction datasets with 13 billion parameters using the GGML format model (a library for machine learning that allows CPU inference). We also used the gpt-3.5-turbo-0613 model accessed via the OpenAI API⁴. We instructed the models using the direct method without few-shot fine-tuning in the counterspeech data since the aim was to assess the persuasion modes that the models use (i.e., zero-shot setting with no examples provided). We used the same instructions for the two models to force counterspeech generation. The model GPT-3.5 tends to refuse to gen-

⁴https://openai.com/blog/gpt-3-5-turbo-fine-tuningand-api-updates

erate counterspeech for offensive posts when directly prompted. We used a task-specific prompt indicating that the model needed to generate a counterargument and explained the task in the instructions. We used both models' standard system prompt styles and the same instructions to indicate that the task was to generate counterspeech.⁵

Machine-Generated Counterspeech Labeling After generating counterspeech for the datasets, a multi-classification approach was applied to the gold persuasion labels to populate the weakly supervised labels of persuasion modes in the machine-generated counterspeech models. This weak labeling approach was adopted to label the output of the generated text to maintain the annotation cost, especially if the annotation needed to be done for multiple generative model outputs (Sen et al. 2023). More specifically, for persuasion labeling in the conversations, weak supervision modeling of persuasion has been shown to be effective in previous studies (Chen and Yang 2021). In their previous study (Chen and Yang 2021) used a weakly supervised model that utilizes partially labeled data to predict associated persuasive strategies for each sentence. Thus, to maintain the cost of annotation, in this study, we experimented with different models: baseline (SVM), masked language model (BERT), and instruction-tuning model (Llama 2). We trained these models to predict the persuasion modes based on the gold annotations from the two datasets using the same split of training and testing reported in Appendix C. The result of training the models to predict the persuasion modes and the hyperparameters used in this task were consistent with those employed in the binary classification task, as further detailed in Appendix D.

Validation of Counter Generative Persuasion Labels We ran both benchmark and human verification validations. In the benchmark validation, the remaining closed DialogConan dataset, which was not included in our gold annotations, was used to verify the general model behavior. First, we compared the results of predicting the persuasion classes in the silver (weak label) and gold label benchmarks. We detail the process in Appendix D and show that the behavior of the models trained on silver labels is consistent with the models trained on gold labels. This consistent pattern across diverse models reinforces the weakly supervised model's efficacy in predicting the persuasion modes in the machine-generated counterspeech dataset.

In the human validation, we manually examined the first 50 examples for each topic. To validate the result of the weakly supervised labels for the generated counter, we selected 50 generated counters from each topic and generative model and validated the persuasion label. An independent annotator (one of the authors) performed the validation process through the two datasets to ensure the consistency of the labeling process. In general, in the closed dataset, the overall error rate is relatively small: about 19% for GPT-3 and 12% for Llama 2. Similarly, for the open dataset, the overall error rate is about 22% for GPT-3 and 16% for Llama 2 (more details in Appendix D). Additionally, we investigated the significance of the comparison between the persuasion labels of humans and generated a counter using the chi-squared X^2 , as shown in Table 3, which shows that all the comparisons are statistically significant.

Topic-Type	Human-GPT	Human-LLAMA
Religious bigotry Closed(multi-turn)	1.08e-101 ****	3.55e-90 ****
Racism Closed(multi-turn)	1.22e-15 ****	1.04e-37 ****
Sexism Closed(multi-turn)	5.95e-113 ****	1.32e-124 ****
Religious bigotry Open(single-turn)	4.74e-22 ****	1.72e-22 ****
Sexism Open(single-turn)	4.81e-40 ****	1.88e-38 ****
Racism Open(single-turn)	1.08e-14 ****	0.007 ***

Table 3: Comparison of generative and human counterspeech. Using the chi-squared X^2 significant test, all comparisons are statistically significant (p < 1.00), ** (p < .01), *** (p < .001), and **** (p < .001)

4 Results and Analysis

In this section, we present the results of the previous experiments and interpret the findings related to each research question.

Interplay of Persuasion Modes in Hate Speech and Counterspeech in Each Type of Conversation Interaction, RQ1 We trained various models to examine the effectiveness of persuasion modes in identifying hate speech and counterspeech. Mainly, we evaluated the general capability of the persuasion modes as proxies to predict hateful and counterspeech responses in two datasets open and closed conversation interactions. Table 2 illustrates a slight enhancement in the models' performance when the persuasion modes are incorporated as categorical features. Some models (such as the masked language model BERT) have more resistance and an overall stable performance in closed interactions, with a small increase in the topic racism's precision score (approximately a 97% F1 score). The same model behavior can be observed in open interactions, in which BERT performs better when text-only input is used instead of text and persuasion on the overall average macro (F1 score). However, for topics such as racism, the combination of text and persuasion has a relative enhancement in the F1 scores, Bilstm with a 91% F1 score, while the text-only F1 score is approximately 90%. The same behavior can be observed with open interactions in BiLSTM, in which the performances of the text-only input and the input combination of text and persuasion are stable, with F1 scores of approximately 76%. This stable performance of BERT may be partly due to the pre-trained language models' data shift effect, as some topics have better representation than others either as a result of covariate

⁵Appendix D provides a sample of the instructions for the zero-shot instruction model to generate counterspeech for hateful posts.



Figure 1: Proportion of persuasion modes (emotion, reason, and credibility) in human hate speech (HS) and counterspeech (CS), and in machine-generated counterspeech using GPT-3 and Llama 2



Figure 2: Proportion of persuasion modes in human counterspeech according to the topic

Figure 4: Proportion of persuasion modes in machine-generated counterspeech (Llama 2) according to the topic

shift (Broscheit, Do, and Gaspers 2022) or temporal domain adaptation (Röttger and Pierrehumbert 2021). For example, the study by (Florio et al. 2020) shows that hate speech detection models trained on data temporally closer to the test data perform better with transformer-based models. Relatively less open interaction data are present at the topic level, table 1. For instance, the topic of religious bigotry has 279 samples, and the prediction score on this topic has the lowest F1 performance in BiLSTM. This model behavior also can be confirmed with SVM open interaction performance because it has a better F1 score than the instructiontuning model Llama, with an F1 score of 86%. However, in the closed dataset, BiLSTM improves slightly when persuasion is incorporated with the text, with an overall F1 score of 89% compared to the F1 score of 88% obtained when the text is used alone. Moreover, the instruction-tuning model's (Llama 2) performance is enhanced when persuasion modes are incorporated as a feature, as shown by a few examples of instruction fine-tuning (an overall F1 score of 95% in closed [multiturn] dataset). This can also be seen in the open dataset used in Llama 2, which improved when it used text and persuasion (59% F1) compared to text alone (57% F1). It is worth mentioning the discrepancies in the performance of Llama 2 when fine-tuned on open versus closed dataset (overall 95% F1 score in closed dataset, and only 59% for open dataset). We can link the poor performance of Llama 2 fine-tuned on the open dataset to the possible data contamination of benchmark datasets (Sainz et al. 2023). We must consider that the closed conversation dataset is a well-known benchmark that contains a seed dataset from the CONAN dialogues released mainly in 2021 and extended to the final set in 2022 (Bonaldi et al. 2022). We must also consider that the knowledge cutoff month for Llama 2 series models is September 2022 according to the model card (Touvron and others 2023). As (Bonaldi et al. 2022) indicate, a major set of the DilogConan closed dataset that we used in this study was derived from using part of the data presented in (Fanton et al. 2021)'s study as an additional resource that consists of 5,000 hate speech – counterspeech pairs. Data contamination is a major issue in pre-trained language models, as a recent study by (Jiang et al. 2024) found evidence that some LLMs have seen task examples during pre-training for a range of tasks and are therefore no longer zero- or few-shot for these tasks. Another possible reason is the noisy nature of the open conversation dataset, as it has been derived from social media platforms (Albanyan, Hassan, and Blanco 2023). The open interaction conversation dataset has the distinct feature of enabling the broader public (many users) to engage with a post compared to closed interaction conversations in which the dialog is exclusively between two users, one of whom may be an expert annotator (mitigation procedure expert) (Fanton et al. 2021).

Persuasion mode variations expressed in generated and human counterspeech, RQ2 We analyzed the persuasion mode distribution by conversation interaction type and generative- and human-based counterspeech (see Figure 1). We also used the entity recognition and coreference resolution capabilities of Riveter (Antoniak et al. 2023) to identify which characters are framed as having or lacking power and assess the social dynamics of personae in the conversations for each persuasion type (Figures 5-10). Overall, generative counterspeech persuades using emotions, while humans persuade using reason. As shown in Figure 1, for closed (multi-turn) interactions, the reason persuasion mode comprises approximately 45% of human counterspeech, compared to only 31% and 21% of generative counterspeech (GPT and Llama-2, respectively). Simi-

Figure 3: Proportion of persuasion modes in machine-generated counterspeech (GPT-3) according to the topic



 Figure 5: Multi-turn racism
 Figure 6: Multi-turn sexism
 Figure 7: Multi-turn religious bigotry

 Entities identified by Riveter and power scores of personas across closed (multi-turn) conversations for three topics. A positive value indicates a stronger association with persuasion mode
 Figure 7: Multi-turn religious bigotry



Figure 8: Single-turn racism Figure 9: Single-turn sexism Figure 10: Single-turn religious bigotry Entities identified by Riveter and power scores of personas across open (single-turn) conversations for three topics. A positive value indicates a stronger association with persuasion mode

larly, in open interactions, 51% of human counterspeech uses reason, compared with 33% and 19% in the GPT and Llama-2 generative models, respectively. Looking closely at the topic level, the reason persuasion mode is more often used in racism than in religious bigotry and sexism. Emotion, however, is more often used in counterspeech, especially in closed (multi-turn) interactions Figure 2. This finding can be further reiterated by reviewing the persona dynamics in the racism topic using Riveter (Figures 5 - 8). Using reasoning statements that contain "immigration" and "statistics" as entities have more powerful persona scores in conversations when discussing rationales to support counterpoints in closed (multi-turn) interactions (see Figure 5). These persona tend to be fact-based rationale (immigration rules and statistical studies), while persuasion in open interactions tends to use personal characteristics (e.g., skin color). Conversely, in conversations that used emotion-based persuasion, the pronoun "you" had the highest persona dynamic power score. This mode in conversations tends to reflect shameful feelings shown by posters of hate speech. Interestingly, credibility has a slightly higher presence in human-authored counterspeech (8%) compared to machine-generated counterspeech (5%; Figure 1). As in closed (multi-turn) interactions, human-authored counterspeech supports the argument by using personal stories. For instance, on the topic of religious bigotry, conversations using the credibility persuasion mode have personal perspectives (with the first-person pronoun "I") when personal stories are recounted (Figure 7). On the topics of religious bigotry and sexism, conversations use credibility more than they do in the topic of racism, in both human-sourced and machine-generated counterspeech.

The reply's stance toward counterspeech, RQ3 The open interaction conversation data has the distinct feature of enabling the broader public (many users) to engage with the post compared to closed interaction conversations in which the dialog is exclusively between two users (such as on GPT and chat platforms). We use open interaction conversation data to examine the stance of the replies to counterspeech. In contrast to previous studies, such as (Mathew et al. 2019), which considered the presence of replies and likes on a post as indicative of support to the counterspeech, our study implemented the nuance of assessing the element in counterspeech that makes it likely to receive support by focusing on the persuasion mode. Figure 11 illustrates the conversation flow between hate speech and counterspeech, as well as the stance of the replies received by the counterspeech. The general trend observed is that counterspeech receives replies that are against it (about 56%). Moreover, supportive replies tend to add context to further justify the counterpoint (22.5%). Most of the opposing replies (43%) do not directly attack the counterspeech; instead, they reject the counterpoint. We examined the distribution of supportive and opposing stances using the persuasion mode and present this in Figure 12. There is a noticeable tendency for replies to support counterspeech that uses the reason persuasion mode (50.4%), and replies against the counterspeech are at 74%. Replies that use the emotion persuasion mode and are opposed to the counterspeech are at 40.7%, and those that use the same persuasion mode and are supportive of the counterspeech are at 37.7%.

5 Discussion and Implication

In this section, we interpret the results of our analysis by first discussing the interplay between the persuasion mode and counterspeech. Following this, we clarify the multifaceted impact of the interaction type and propose possible directions for future work. The results show that the persuasion mode can provide an explainability method to counterspeech studies.



Figure 11: Flow of persuasion modes between hate speech (HS) and counternarratives (CNs) in single-turn conversations (open interactions)



Figure 12: Correlation between the persuasion modes and the reply's stance $% \left({{{\bf{r}}_{\rm{s}}}} \right)$

Conversation Type and Persuasion Modes Interaction types of the conversation clearly have nuanced effects on counterspeech's exhibited persuasion mode. As shown in Figure 1, 51% of the counterspeech examples in open interactions use reason as the persuasion mode, while 45% of the counterspeech examples in closed interactions use reason. This may be partly due to the cost of public opinion and the users' need to appear knowledgeable, which may drive their tendency to support their counterpoints with facts and reasoning. By studying the persona's social dynamic in hate conversations using Riveter (Antoniak et al. 2023), as shown in (Figures 5-10), we can see this behavior, its high power score toward people of a targeted group (White or Black people), and its lower power score when using self-reference (I). This persuasion mode tends to make the conversation focus on justifying counterpoints to the target group rather than expressing the reason behind the hate and linking it to the self as a valid reason for hate. We also show the effectiveness of using persuasion as a proxy to differentiate counterspeech from hate speech (Table 2), which highlights the persuasion mode's ability to serve as an instrument of explanation for hate detection model interpretability.

Overall, these results offer an overview of the counterspeech's nuances and the conversation interaction type's effect on how those confronting hate may incorporate persuasion modes to express their counterpoint and combat hate.

Generative Counterspeech Persuading Using Emotions, while Humans Persuading with Rea**son** Our results show a clear gap in the singular focus of current counterspeech works on emotion-based hatespeech analyses, which further confirms other works' recent findings (Lahnala et al. 2022). For instance, the work by (Lahnala et al. 2022) highlights the need to look beyond emotion, as it shows that cognitive empathy mitigates hate better than emotional empathy. Figure 1 shows the clear tendency of human-written counterspeech to use reason in order to express a counterpoint (over 45%); this is comparable to the mere 19%of machine-generated counterspeech that uses reason. Further, emotion is the main persuasion mode. Generative counterspeech's behavior highlights the vicious cycle of training hate speech detection models on emotionbased data and the complexity of incorporating reason as a factor in the current generated content. A few recent studies have highlighted machine-generated counterspeech's limitations (e.g., (Mun et al. 2023; Sen et al. 2023)). Their conclusion focuses on a target-specific strategy and shows a lack of persuasive power in generated counterspeech when compared to human-written counterspeech. Our study's findings intensify the call for studying counterspeech's non-emotional factors as building blocks of hate mitigation.

Conversation Structures and Reply Stance Open interaction conversations (such as those on social media) are a means to observe how the public perceives counterspeech from multiple users' perspectives. Thus, we analyzed the replies to counterspeech and showed the stances of the replies toward each type of persuasion mode. The results in Figure 11 show that the conversational flow alternates between the counterspeech and the type of the reply's stance. Approximately 59% of counterspeech examples received replies with opposing stances, especially if the examples used the emotional persuasion mode (representing about 40.7% of the opposing stances, as in Figure 12). A reply's support stance is likely to favor the reason persuasion mode, as represented in about 50.4% of supportive replies. Since this study's scope is to provide a high-level comparison of the conversation interaction types and persuasion mode, possible future research may incorporate a nuanced analysis of how users perceive counterspeech by a specific topic. Recent studies have investigated the role of conversation structure while studying hate detection. For instance, the work by (Yi and Zubiaga 2023) surveyed session-based cyberbullying and discussed the structure of social media conversations to construct a cyberbullying dataset. Our study shows an empirical investigation that paves the way for future consideration of replies to counterspeech to enhance the interpretation of counterspeech effective factors. The size of the open interaction has its limitations in this study. Moreover, we justified the results using chi-squared X^2 significant test to validate the interpretation of the comparison between machine-generated and human-authored counterspeech (Table 3).

6 Conclusion

In this study, we examined persuasion modes in two types of conversations: closed (multi-turn) and open (single-turn) interactions. First, we categorized three types of persuasion in counterspeech: emotion, reason, and credibility. Next, we assessed the persuasion modes in machine-generated counterspeech and compared them to human-authored counterspeech. The findings mainly demonstrate that the persuasion modes used in counterspeech is nuanced and noticeably dependent on the conversation topic. Emotion as a persuasion mode is more prevalently used in machine-generated counterspeech than in human-composed counterspeech, which primarily uses reason to defend counterpoints. Reason-based counterspeech tends to obtain more supportive responses compared to emotion-based counterspeech. Further, our work highlights the potential of incorporating persuasion modes in studies on countering hate speech to serve as explanatory proxies to further enhance the ability to interpret hate speech detection. Current counterspeech studies lack a clear method with which to evaluate optimal counterspeech strategies. The conversation structure in hate-speech detection needs to consider including the replies' stances on counterspeech as analysis factors. This feature has a clear presence in open interactions, in which multiple users can reply to counterspeech. This study focused on hate speech as a general category. Future research may further evaluate the persuasion modes using more fine-grained base types of hate (e.g., offensiveness, toxicity, or abusiveness). A narrower domain-level counterspeech evaluation can be performed by studying the topic's social aspects, such as racial discrimination against individuals or groups.

7 Ethical Statement

In this study, we extended current research attempts to examine the effective factors of counterspeech as a step to mitigate hate speech. Yet, we have cautiously handled the extra annotation layer (persuasion mode) that we added to the existing two released datasets by ensuring the anonymity of the posts using the IDs in the X posts. Additionally, we carefully handled the data annotation process by removing any mention of the user account from the open interaction dataset, ContextCounter (Albanyan, Hassan, and Blanco 2023). We also ensured a fair wage for the annotators by using the LabelBox annotation platform's fixed pricing per hour (as explained in Appendix B). Moreover, we tried to limit the direct reporting of hate messages as a sample for analysis by using Riveter (Antoniak et al. 2023) to measure the power and dynamics between the social entity of conversations and help with interpreting the narrative of hate speech and counterspeech.

References

Agarwal, V.; Chen, Y.; and Sastry, N. 2023. HateRephrase: Zero- and Few-Shot Reduction of Hate Intensity in Online Posts using Large Language Models.

Albanyan, A.; Hassan, A.; and Blanco, E. 2023. Not All Counterhate Tweets Elicit the Same Replies: A Fine-Grained Analysis. In *Proceedings of the 12th Joint Conference on Lexical and Computational Semantics (*SEM* 2023), 71–88. Toronto, Canada: Association for Computational Linguistics.

Antoniak, M.; Field, A.; Mun, J.; Walsh, M.; Klein, L.; and Sap, M. 2023. Riveter: Measuring Power and Social Dynamics Between Entities. In Bollegala, D.; Huang, R.; and Ritter, A., eds., *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 3: System Demonstrations)*, 377–388. Toronto, Canada: Association for Computational Linguistics.

Ashida, M.; and Komachi, M. 2022. Towards Automatic Generation of Messages Countering Online Hate Speech and Microaggressions. In *Proceedings of the Sixth Workshop on Online Abuse and Harms (WOAH)*, 11–23. Seattle, Washington (Hybrid): Association for Computational Linguistics. Barden, J.; and Petty, R. E. 2012. Persuasion. In Ramachan-

dran, V. S., ed., *Encyclopedia of Human Behavior (Second Edition)*, 96–102. San Diego: Academic Press, second edition edition.

Bonaldi, H.; Dellantonio, S.; Tekiroglu, S. S.; and Guerini, M. 2022. Human-Machine Collaboration Approaches to Build a Dialogue Dataset for Hate Speech Countering.

Brassard-Gourdeau, E.; and Khoury, R. 2019. Subversive Toxicity Detection using Sentiment Information. In Roberts, S. T.; Tetreault, J.; Prabhakaran, V.; and Waseem, Z., eds., *Proceedings of the Third Workshop on Abusive Lan*guage Online, 1–10. Florence, Italy: Association for Computational Linguistics.

Broscheit, S.; Do, Q.; and Gaspers, J. 2022. Distributionally robust finetuning BERT for covariate drift in spoken language understanding. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics.*

Caldevilla-Domínguez, D.; Barrientos-Báez, A.; and Padilla-Castillo, G. 2023. Dilemmas Between Freedom of Speech and Hate Speech: Russophobia on Facebook and Instagram in the Spanish Media. *Politics and Governance*, 11(2): 147–159.

Catherine, B. 2022. Why They Do It: Counterspeech Theories of Change. SSRN.

Chen, J.; and Yang, D. 2021. Weakly-Supervised Hierarchical Models for Predicting Persuasive Strategies in Goodfaith Textual Requests.

Cope, E. M.; and Sandys, J. E. 2010. *Aristotle: Rhetoric.* Cambridge University Press.

Durmus, E.; Lovitt, L.; Tamkin, A.; Ritchie, S.; Clark, J.; and Ganguli, D. 2024. Measuring the Persuasiveness of Language Models. https://www.anthropic.com/news/measuring-model-persuasiveness.

Dutta, S.; Das, D.; and Chakraborty, T. 2020. Changing views: Persuasion modeling and argument extraction from online discussions. *Inf. Process. Manag.*, 57(2): 102085.

Fanton, M.; Bonaldi, H.; Tekiroğlu, S. S.; and Guerini, M. 2021. Human-in-the-Loop for Data Collection: a Multi-Target Counter Narrative Dataset to Fight Online Hate Speech. In Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers), 3226–3240. Online: Association for Computational Linguistics.

Florio, K.; Basile, V.; Polignano, M.; Basile, P.; and Patti, V. 2020. Time of Your Hate: The Challenge of Time in Hate Speech Detection on Social Media. *NATO Adv. Sci. Inst. Ser. E Appl. Sci.*, 10(12): 4180.

Gagliardone, I.; Gal, D.; Alves, T.; and Martinez, G. 2015. Countering online hate speech. UNESCO Publishing.

Garland, J.; Ghazi-Zahedi, K.; Young, J.-G.; Hébert-Dufresne, L.; and Galesic, M. 2020. Countering hate on social media: Large scale classification of hate and counter speech. In Akiwowo, S.; Vidgen, B.; Prabhakaran, V.; and Waseem, Z., eds., *Proceedings of the Fourth Workshop on Online Abuse and Harms*, 102–112. Online: Association for Computational Linguistics.

Gupta, R.; Desai, S.; Goel, M.; Bandhakavi, A.; Chakraborty, T.; and Akhtar, M. S. 2023. Counterspeeches up my sleeve! Intent Distribution Learning and Persistent Fusion for Intent-Conditioned Counterspeech Generation.

Hangartner, D.; Gennaro, G.; Alasiri, S.; Bahrich, N.; Bornhoft, A.; Boucher, J.; Demirci, B. B.; Derksen, L.; Hall, A.; Jochum, M.; Munoz, M. M.; Richter, M.; Vogel, F.; Wittwer, S.; Wüthrich, F.; Gilardi, F.; and Donnay, K. 2021. Empathy-based counterspeech can reduce racist hate speech in a social media field experiment. *Proc. Natl. Acad. Sci. U. S. A.*, 118(50).

Jiang, M.; Liu, K. Z.; Zhong, M.; Schaeffer, R.; Ouyang, S.; Han, J.; and Koyejo, S. 2024. Investigating Data Contamination for Pre-training Language Models.

Lahnala, A.; Welch, C.; Neuendorf, B.; and Flek, L. 2022. Mitigating Toxic Degeneration with Empathetic Data: Exploring the Relationship Between Toxicity and Empathy. In 2022 NAACL. Association for Computational Linguistics.

Lukin, S.; Anand, P.; Walker, M.; and Whittaker, S. 2017. Argument strength is in the eye of the beholder: Audience effects in persuasion. In *Proceedings of the 15th Conference* of the European Chapter of the Association for Computational Linguistics.

Mathew, B.; Saha, P.; Tharad, H.; Rajgaria, S.; Singhania, P.; Maity, S. K.; Goyal, P.; and Mukherjee, A. 2019. Thou Shalt Not Hate: Countering Online Hate Speech. *ICWSM*, 13: 369–380.

McNEMAR, Q. 1947. Note on the sampling error of the difference between correlated proportions or percentages. *Psychometrika*, 12(2): 153–157.

Mun, J.; Allaway, E.; Yerukola, A.; Vianna, L.; Leslie, S.-J.; and Sap, M. 2023. Beyond Denouncing Hate: Strategies for Countering Implied Biases and Stereotypes in Language. In *EMNLP 2023*, 9759–9777.

Myers West, S. 2018. Censored, suspended, shadowbanned: User interpretations of content moderation on social media platforms. *New Media & Society*, 20(11): 4366–4383.

Orrù, L.; Moro, C.; Cuccarini, M.; Paita, M.; Dalla Riva, M. S.; Bassi, D.; Da San Martino, G.; Navarin, N.; and

Turchi, G. P. 2022. Machine Learning and MADIT methodology for the fake news identification: the persuasion index. In 4th International Conference on Advanced Research Methods and Analytics (CARMA 2022), 165–172. riunet.upv.es.

Parker, S.; and Ruths, D. 2023. Is hate speech detection the solution the world wants? *Proc. Natl. Acad. Sci. U. S. A.*, 120(10): e2209384120.

Pauli, A.; Derczynski, L.; and Assent, I. 2022. Modelling Persuasion through Misuse of Rhetorical Appeals. In *Proceedings of the 2nd Workshop on NLP for Positive Impact* (NLP4PI).

Pozzobon, L.; Ermis, B.; Lewis, P.; and Hooker, S. 2023. On the Challenges of Using Black-Box APIs for Toxicity Evaluation in Research. In Bouamor, H.; Pino, J.; and Bali, K., eds., *Proceedings of the 2023 Conference on Empirical Meth*ods in Natural Language Processing, 7595–7609. Singapore: Association for Computational Linguistics.

Rapp, C. 2023. *Aristotle's Rhetoric*. Metaphysics Research Lab, Stanford University, winter 2023 edition.

Röttger, P.; and Pierrehumbert, J. 2021. Temporal Adaptation of BERT and Performance on Downstream Document Classification: Insights from Social Media. In *EMNLP 2021*.

Sainz, O.; Campos, J.; García-Ferrero, I.; Etxaniz, J.; de Lacalle, O. L.; and Agirre, E. 2023. NLP Evaluation in trouble: On the Need to Measure LLM Data Contamination for each Benchmark. In *EMNLP 2023*.

Salvi, F.; Ribeiro, M. H.; Gallotti, R.; and West, R. 2024. On the Conversational Persuasiveness of Large Language Models: A Randomized Controlled Trial.

Schmuck, D. 2024. 'You Got My Back?' Severity and Counter-Speech in Online Hate Speech Toward Minority Groups. *Media Psychol.*, 0(0): 1–32.

Sen, I.; Assenmacher, D.; Samory, M.; Augenstein, I.; van der Aalst, W.; and Wagner, C. 2023. People Make Better Edits: Measuring the Efficacy of LLM-Generated Counterfactually Augmented Data for Harmful Language Detection.

Thalken, R.; Stiglitz, E.; Mimno, D.; and Wilkens, M. 2023. Modeling Legal Reasoning: LM Annotation at the Edge of Human Agreement. In Bouamor, H.; Pino, J.; and Bali, K., eds., *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, 9252–9265. Singapore: Association for Computational Linguistics.

Touvron, H.; and others. 2023. Llama 2: Open Foundation and Fine-Tuned Chat Models.

Wright, L.; Ruths, D.; Dillon, K. P.; Saleem, H. M.; and Benesch, S. 2017. Vectors for Counterspeech on Twitter. In Waseem, Z.; Chung, W. H. K.; Hovy, D.; and Tetreault, J., eds., *Proceedings of the First Workshop on Abusive Language Online*, 57–62. Vancouver, BC, Canada: Association for Computational Linguistics.

Yi, P.; and Zubiaga, A. 2023. Session-based cyberbullying detection in social media: A survey. *Online Social Networks and Media*, 36: 100250.

Yu, X.; Blanco, E.; and Hong, L. 2022. Hate Speech and Counter Speech Detection: Conversational Context Does Matter. In Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics.

A Preparation of the Baseline Datasets

To prepare the DialogConan dataset, closed (multi-turn), we first unified topic definitions and mapped each target base topic into its main domain (racism, sexism, and religious bigotry) as follows:

$WOMEN + LGBT \Rightarrow SEXISM$

 $MIGRANTS + POC \Rightarrow RACISM$

 $MUSLIMS + JEWS \Rightarrow RELIGIOUSBIGOTRY$

In general, the average number of tokens for each turn is around 19 tokens for the DiaolgConan (closed) and 27 tokens for the ContextCounter (open) dataset. Moreover, to maintain the cost of the annotation, we selected 50% of the dialogs of each topic in DialogConan. The dataset originally contained 3,059 unique dialogs spanning three topics, as shown in Table 4. This process results in our baseline dataset for the closed interaction dataset, which contains about 8,000 turns of conversations.

Topic	Unique dialoiuges	our 50% set of dialogues
Racisim	1055	527
Sexism	1031	515
Religious bigotry	974	487

Table 4: Preparing DialogConan for annotation by selecting 50% of the unique dialogues in each topic

B Annotation Setup

We use LabelBox as a platform to recruit and run annotation tasks. This platform enables conversation annotation, where the whole dialogue is shown to the annotator, with the possibility of labeling each conversation turn. We provide a thorough, detailed guideline for each interaction type (open/close) to the annotated, Figure 13, and Figure 14⁶. A fair wage per hour has been provided to the team of two annotators as part of the Boost Tier payment setting of LabelBox. ⁷



Figure 13: Annotation example for persuasion modes, where all the turns are shown to facilitate the labeling of each turn of the conversation



Figure 14: Topic annotation for Open (single-turn) dataset

C Classification of the Hate Speech and Counterspeech Model Hyperparameter

Table 5 shows the major set of hyperparameters used for each model in the experiment. For the Uncased BERT-base, we used the pre-trained language models provided by the transformers Python library ⁸. Uncased BERT-base trained on lowered case English text with 12-layer, 768-hidden, 12heads, 110M parameters. We also provided the details of dataset split for training, validation, and testing, in which we used a stratified split from scikit-learn and saved the split files to be used through the experiment to unify experiment settings and further ensure reproducibility as shown in Tables 6 and 7.

Model	Hyperparameter	Customization
	Regularization parameter(C)	3.0
SVM	Kernal function	rbf
5 V 1VI	LSTM units (LSTM_DIM)	64
	Epochs	10
\mathbf{Bilstm}	Spatial dropout	0.2
	Dropout rate	0.2
	Recurrent dropout	0.2
	Epochs	5
	Train Batch size	16
DEDT	Eval Batch size	20
DERI	Learning rate	5e-5
	Warm up steps	100
	Weight decay	0.01
	Batch size	1
	Learning rate	2e-4
Llama-2-7B	Epochs	20
	Max length	3
	Warm up steps	2
	lora alpha	16
	lora dropout	0.1
	lora rank	64

Table 5: Models hyperparameters

For Llama-2 instruction tuning to classify a turn as hate

⁸https://huggingface.co/transformers/v2.5.1/ pretrained_models.html

Closed (Multi-Turn)				
Topic	Training	Validation	Test	Total
SEXISM	1946	250	585	2781
RACISM	2069	266	622	2957
RELIGIOUS BIGOTRY	2011	258	605	2874
Count				8612

Table 6: Taring split for closed (multi-turn)

 $^{^{6}{\}rm link}$ to a GitHub repository that contains the dataset and guideline of annotation will be provided. At this sub-mission, we provide a link to the pdf file of the annotation guideline for the topic racism https://file.io/MLVfDZr7Ieii

⁷https://labelbox.com/product/annotate/

Open (Single-Turn)				
Topic	Training	Validation	Test	Total
SEXISM	384	49	116	549
RACISM	355	45	108	508
RELIGIOUS BIGOTRY	195	25	59	279
Count				1336

Table 7: Taring split for open (single-turn)

Models	P value
Llama-2(txt) and Llama-2 (txt+pr)	2.02e-11 ****
BERT (txt) and BERT (txt+pr)	0.16
BiLSTM (txt) and BiLSTM (txt+pr)	3.64e-06 ****
SVM (txt) and SVM(txt+pr)	0.154
Llama-2(txt) and Llama-2 (txt+pr)	1.11e-16 ****
BERT (txt) and BERT $(txt+pr)$	0.735
BiLSTM (txt) and BiLSTM (txt+pr)	0.011 **
SVM (txt) and SVM(txt+pr)	0.00051 ***
	Models Llama-2(txt) and Llama-2 (txt+pr) BERT (txt) and BERT (txt+pr) BiLSTM (txt) and BiLSTM (txt+pr) SVM (txt) and SVM(txt+pr) Llama-2(txt) and Llama-2 (txt+pr) BERT (txt) and BERT (txt+pr) BiLSTM (txt) and BiLSTM (txt+pr) SVM (txt) and SVM(txt+pr)

Table 8: Significance of comparing the prediction pattern of the training model on the text as the baseline (txt) with the training model on text and persuasion (txt+pr) (All comparisons are statistically significant, alpha = 0.05.) (p < 1.00), ** (p < .01), *** (p < .001), and **** (p < .0001)

or counter. In the model (text+per), we use the following instructions:

"Below is an instruction that describes a task. Write a response that appropriately completes the request for the following persuasion setting. setting: [persuasion mode] Instruction: Classify the input text as Hate Speech or Counter Narrative Input: [Text of turn]"

Significant Test of the Counter and Hate Predictions We use McNemar's significant test (McNEMAR 1947) to evaluate the significance of the baseline comparison on the model level. Table 8 shows the results of comparing the significance of the model predictions where the model is trained on text only (txt) as well as on persuasion along with text (txt+pr).

D Generated Counterspeech Settings

Generating Counterspeech We used task-specific prompts for Llama2-13B and GPT-3.5 Turbo to generate counterspeech for each message of hate.

For GPT3, we use the following prompt

"role": "system", "content": "You will be provided with a message (delimited with XML tags). Provide a counter-narrative to the arguments of each message. ", "role": "user", "content": "< message " + text + " < /message >",

For Llama2, we use the following prompt with input indicating a hate message

[INST] << SYS >> provide a Counterargument to the input text below << /SYS >> input [/INST]

Weak Supervision Training to Classify the Persuasion Modes in Counterspeech and Hate Speech We trained four models on gold annotations from closed and open turns to classify the persuasion mode in the input turns (the text of hate speech). The classification output yielded three labels (emotion, reason, credibility), and we have reported the macro F1 score in Table 9. The goal is to identify and utilize the most effective model for assigning persuasion labels to the generated counter set. The outcomes presented in Table 9 show that BERT and SVM have the highest F1 score (50%). On the contrary, Llama 2 has the lowest F1 score (20%). This behavior of the instruction-tuning model can be shaped by the complexity of persuasion as a task (multiclassification and unpopular labeling). This has also been confirmed in a recent study in which they found that BERT provides an optimal result in comparison with other instruction-tuning models, such as Llama (Thalken et al. 2023). By referring to the result in Table 9, on the topic level, BERT performs better on two topics out of the three (59% F1 for the topic of racism and 44% F1 for religious bigotry). Therefore, BERT has been used to populate the persuasion labels for the generated counter in closed and open datasets.

Validation of the Weak Supervision Model (Benchmark Method) We used the weakly supervised model BERT to populate the rest of the DialogConan dataset (closed [multi-interaction]) with persuasion mode labels (silver labels). Then, we investigated the performance of the binary classification of hate speech and counterspeech using the same classification task in the section. However, we trained them on silver labels (weak labels). Table 10 shows the average F1 score of the three topics trained on the silver persuasion label to predict hate speech and counterspeech. For the instruction-tuning model (Llama 2), the F1 score remains the same at 93% for text-only as well as text and persuasion scenarios. Similarly, the BERT model exhibits no change in the F1 score, maintaining a high accuracy of 95%. The BiLSMT model sees a notable increase from 87% to 88% when incorporating persuasion modes. Furthermore, the baseline (SVM) model displays a similar pattern, with the F1 score improving from 89% to 90%. This consistent pattern across diverse models reinforces the weakly supervised model's efficacy in predicting the persuasion modes in the machine-generated counterspeech set.

Validation of the Weak Supervision Model (Human Validation) To validate the result of weakly supervised labels for the generated counter, we selected 50 generated counters from each topic and the generative model and validated the persuasion label. An independent annotator (one of the authors) performed the validation process through the two datasets to ensure consistency in the label moderation process. As shown in Table 11, in the closed dataset, the overall error rate is relatively small: about 19% for GPT-3 and 12% for Llama 2. For the open (single-turn) dataset, the overall error rate is about 22% for

GPT-3 and 16% for Llama 2.

Paper Checklist

- 1. For most authors...
- (a) Would answering this research question advance science without violating social contracts, such as violating privacy norms, perpetuating unfair profiling, exacerbating the socio-economic divide, or implying disrespect to societies or cultures? yes, we explain the motivation at § 1, and detailed the research implication at § 5
- (b) Do your main claims in the abstract and introduction accurately reflect the paper's contributions and scope? yes, we detail the study contributions at § 1, and provide detailed discussion of the results for each research question at § 4
- (c) Do you clarify how the proposed methodological approach is appropriate for the claims made? yes, we start by providing the definition of counter speech and the hypothesis of persuasion mode at§ 1 and situate the contribution with the related work at § 2 RQ1 indicated at mainly at the methodology § 3.2, and at § 1. As for RQ2, we compare the different persuasion modes in humans and generated counters using the distribution of the persuasion in two types of data: closed (multi-turn) and open (single-turn) as explained at § 3.3, § 1 and § 4. For RQ3, we explain the flow of replies at § 3.1, and further details at § 5
- (d) Do you clarify what are possible artifacts in the data used, given population-specific distributions? yes, we report the detailed data selection and preparation at § 3.1 and Appendix A.
- (e) Did you describe the limitations of your work? yes, at discussion section§ 5
- (f) Did you discuss any potential negative societal impacts of your work? We detail the research implication at § 5 and ethical statement § 7
- (g) Did you discuss any potential misuse of your work? yes, discussion of research implication at § 5and ethical statement § 7
- (h) Did you describe steps taken to prevent or mitigate potential negative outcomes of the research, such as data and model documentation, data anonymization, responsible release, access control, and the reproducibility of findings? yes, at ethical statement § 7, and appendix A.
- (i) Have you read the ethics review guidelines and ensured that your paper conforms to them? yes
- 2. Additionally, if your study involves hypotheses testing...
- (a) Did you clearly state the assumptions underlying all theoretical results? We provide empirical justification to the hypothesis and answer the research question.
- (b) Have you provided justifications for all theoretical results? We provide empirical justification to the hypothesis and answer the research question.
- (c) Did you discuss competing hypotheses or theories that might challenge or complement your theoretical results? We describe the main hypothesis at § 1 and situate the assumption with previous work § 2

- (d) Have you considered alternative mechanisms or explanations that might account for the same outcomes observed in your study? yes, full analysis of the results described at § 4, and we provide further details at appendix D for generated counter analysis.
- (e) Did you address potential biases or limitations in your theoretical framework? yes, we detail the discussion at § 5
- (f) Have you related your theoretical results to the existing literature in social science? yes, § 2, and research implication at § 5
- (g) Did you discuss the implications of your theoretical results for policy, practice, or further research in the social science domain? yes, we show in the discussion section a detailed implication of the empirical results § 5
- 3. Additionally, if you are including theoretical proofs...
- (a) Did you state the full set of assumptions of all theoretical results? yes, we explain the hypothesis of the experiment design at § 1 and further justify it by sitting it with previous work § 2
- (b) Did you include complete proofs of all theoretical results? yes, full experimental results and discussion at sections § 4 and § 5
- 4. Additionally, if you ran machine learning experiments...
- (a) Did you include the code, data, and instructions needed to reproduce the main experimental results (either in the supplemental material or as a URL)? detail explanation of the experiment hyperparameter or data annotation guideline are at Appendix A, B, C, and D.
- (b) Did you specify all the training details (e.g., data splits, hyperparameters, how they were chosen)? yes, we provide a detailed description of the training split at appendix C.
- (c) Did you report error bars (e.g., with respect to the random seed after running experiments multiple times)? yes, full detail of significant text and experiment design at appendix C.
- (d) Did you include the total amount of compute and the type of resources used (e.g., type of GPUs, internal cluster, or cloud provider)? yes, at section § 3.2 and appendix C.
- (e) Do you justify how the proposed evaluation is sufficient and appropriate to the claims made? yes, we report the significant test of all of the main experiments, Macnamer for classification comparison at § 3.2, and appendix C. Also, for the counter generation, we provide detailed validation process at § 3.3, and appendix D.
- (f) Do you discuss what is "the cost" of misclassification and fault (in)tolerance? yes, we report the significant test at appendix c, and indicates the limitation at § 5
- 5. Additionally, if you are using existing assets (e.g., code, data, models) or curating/releasing new assets, without compromising anonymity...
- (a) If your work uses existing assets, did you cite the creators? yes, experiment set up at § 3.1

Detect	Tania		SEXISM			RACISM			RELI	RELIGIOUS BIGOTRY		
Dataset	Topic		Р	R	F1	Р	R	F1	P	R	F1	F1
Close and Open	Llama-2-7B	txt	0.20	0.23	0.13	0.31	0.23	0.22	0.20	0.25	0.19	0.20
	BERT	txt	0.43	0.43	0.43	0.64	0.60	0.59	0.49	0.43	0.44	0.50
	Bilstm	txt	0.35	0.83	0.49	0.19	0.85	0.32	0.36	0.88	0.51	0.33
	SVM	txt	0.47	0.42	0.43	0.66	0.54	0.57	0.42	0.39	0.38	0.50

Table 9: Binary F1 score for training the models to classify the persuasion labels (emotion, reason, and credibility)

Deteset	N.C 1 - 1 -		SEXI	SEXISM			RACISM			RELIGIOUS BIGOTRY		
Dataset	wouers		Р	R	F1	P	R	F1	Р	R	F1	F1
	Llama 2.7P	txt	0.94	0.94	0.94	0.93	0.92	0.92	0.92	0.92	0.92	0.93
	Liama-2-7D	txt + pr	0.93	0.93	0.93	0.94	0.94	0.94	0.91	0.91	0.91	0.93
	$\begin{array}{c} \text{BERT} & \text{Txt} \\ \text{txt} + p \end{array}$	Txt	0.96	0.96	0.96	0.93	0.93	0.93	0.94	0.94	0.94	0.95
Classed (multi tunn) silver		txt + pr	0.95	0.95	0.95	0.95	0.95	0.95	0.94	0.94	0.94	0.95
Closed (multi-turn) silver	Bilatm	txt	0.88	0.88	0.88	0.85	0.85	0.85	0.88	0.87	0.87	0.87
	blistin txt + pr	txt + pr	0.89	0.89	0.89	0.85	0.85	0.85	0.88	0.88	0.88	0.88
	CATA	txt	0.90	0.90	0.90	0.88	0.88	0.88	0.90	0.90	0.90	0.89
	txt +	txt + pr	0.90	0.90	0.90	0.88	0.88	0.88	0.91	0.91	0.91	0.90

Table 10: Binary F1 score for training the models on the silver labels of closed (multi-turn) interactions

Dataset	GModel	Topic	Error-persuasion
		Racism	22%
	CDT2	Sexism	24%
	Gris	Religious bigotry	12%
Closed(multi turn)		Overall	19%
		Racism	2%
	TTAMAG	Sexism	22%
	LLAMA2	Religious bigotry	12%
		Overall	12%
		Racism	24%
	CDT2	Sexism	22%
	Gris	Religious bigotry	22%
Open(single-turn)		Overall	22%
		Racism	12%
	TTAMAS	Sexism	20%
	LLAMAZ	Religious bigotry	16%
		Overall	16%

Table 11: Error rate of weak persuasion labels in the generated counter by the two generative models GPT-3 and Llama 2 for the two datasets

- (b) Did you mention the license of the assets? yes, models description at § 3.2, and appendix C. Also, dataset discussed at § 3.1
- (c) Did you include any new assets in the supplemental material or as a URL? yes, we include anonymous link to annotation guideline at appendix A
- (d) Did you discuss whether and how consent was obtained from people whose data you're using/curating? yes, we describe data labeling and collection at § 3.1 and appendix A
- (e) Did you discuss whether the data you are using/curating contains personally identifiable information or offensive content? yes, as the domain of the study is counter hate speech analysis, thus we were cautious in including any official examples directly in the paper. instead, we use an optimal tool (Riveter) to analyze the discussion as we explained at ethical statement § 7
- (f) If you are curating or releasing new datasets, did you discuss how you intend to make your datasets FAIR ? yes,ethical statement § 7
- (g) If you are curating or releasing new datasets, did you create a Datasheet for the Dataset (see ?)? yes, we prepare an electronic datasheet readme file at our private GitHub repository. We plan to share it after receiving the decision on the paper.
- 6. Additionally, if you used crowdsourcing or conducted research with human subjects, **without**

compromising anonymity...

- (a) Did you include the full text of instructions given to participants and screenshots? yes, detail annotation process at appendix A
- (b) Did you describe any potential participant risks, with mentions of Institutional Review Board (IRB) approvals? yes, detail annotation process at Appendix A, along with ethical statement § 7
- (c) Did you include the estimated hourly wage paid to participants and the total amount spent on participant compensation? yes, Annotation recruitment process at appendix A.
- (d) Did you discuss how data is stored, shared, and deidentified? yes, we discuss the data collection at appendix A. also we provide a description of the measures we used to protect the data at ethical statement § 7