Can LLMs Reason with Rules? Logic Scaffolding for Stress-Testing and Improving LLMs

Anonymous ACL submission

Abstract

Large language models (LLMs) have achieved impressive human-like performance across various reasoning tasks. However, their mastery of underlying inferential rules still falls short of human capabilities. To investigate this, we propose a logic scaffolding inferential rule generation framework, to construct an inferential rule base, ULogic, comprising both primitive and compositional rules across five domains. Our analysis of GPT-series models over a rule subset reveals significant gaps in LLMs' logic un-011 derstanding compared to human performance, especially in compositional and structural com-014 plex rules with certain bias patterns. We further distill these rules into a smaller-scale inference engine for flexible rule generation and enhancing downstream reasoning. Through a multi-017 018 judger evaluation, our inference engine proves 019 effective in generating accurate, complex and abstract conclusions and premises, and improve various commonsense reasoning tasks. Overall, our work sheds light on LLMs' limitations in grasping inferential rule and suggests ways to enhance their logical reasoning abilities ¹.

1 Introduction

"Did Leonardo da Vinci ever use a laptop for drawing pictures?" Large language models can swiftly and confidently respond "No" (Geva et al., 2021; Wang et al., 2023), demonstrating impressive reasoning ability that rivals human (OpenAI, 2023; Ouyang et al., 2022). However, when posed with more obscure questions, such as question Q2 in Figure 1, LLMs are prone to exhibit uncertainty and errors. This inconsistency raises concerns about whether LLMs grasp the underlying logic of matters as proficiently as humans (Wason, 1968) (see "underlying logic" in Figure 1) and highlights challenging reasoning situations (like Q2) where current LLMs might struggle. Q1: Did Leonardo da Vinci ever use a laptop for drawing pictures? Q2: Jane wrote a novel published by Jimmy, a publisher born in 1750. Did Jane's grandmother often work by car?





040

041

042

043

045

047

049

051

055

057

058

060

061

062

063

064

065

066

Underlying Logic: If Person X died before year A and Object Y was invented in year B, and A is earlier than B, then Person X can not access Object Y. year A year B Person X Object Y

Figure 1: The underlying logic to answer Q1 and Q2.

Humans naturally abstract underlying logic (*e.g.*, inferential rules) from extensive real-world observations (Barwise, 1993), which is beneficial for addressing diverse reasoning situations. An inferential rule is typically defined as a premise with a set of facts (e.g., "Person X died before ... earlier than B") leading to a conclusion (e.g., "Person X cannot access Object Y") (Boghossian, 2014). Grasping this rule enables the deduction that a person cannot access an object invented posthumously. This work utilizes symbolic logic as a *scaffold* to generate challenging reasoning situations for GPT-series LLMs. We observe a discernible gap between LLMs and humans in understanding inferential rules, especially rules with complex premises.

However, collecting such inferential rules at scale presents a major challenge. Previous work mainly relies on manual curation (Sap et al., 2019a; Sinha et al., 2019) or inductive logic programming (Qu et al., 2020), which are either laborintensive or limited in diversity. Besides, manually crafted rules often appear simple and overly specified, struggling to move beyond basic intuition or generalize across diverse situations. For example, the rule *If X runs out of steam, then X becomes tired* from Sap et al. (2019a) has only one premise fact and narrowly specifies exhaustion.

¹All code and data have been uploaded and will be published upon acceptance.



Figure 2: Logic scaffolding uncovers challenging reasoning space for LLMs. (Complexity refers to the rule length.)

To this end, we introduce Logic scaffOlding Inferential Rule gEneration (LOIRE), a framework to generate inferential rules of different complexities. LOIRE operates in two stages: primitive rule generation and rule composition. Initially, we define "primitive rules" to describe abstract objects like Person and Food, and ensure they cannot be decomposed into simpler rules, facilitating broad generalization and easy generation. We then incorporate GPT-4's generative capability and human expertise to generate primitive rules with high confidence. This process, consistently guided by symbolic logic, involves GPT-4 drafting potential conclusions in various domains, and forming premises with one or more facts. We ensure rules' logical soundness through the model's self-critique and human manual verification. In the second stage, we apply backward chaining (Gallaire and Minker, 2012; Al-Ajlan, 2015) upon these primitive logical rules to automatically construct compositional rules of varied lengths and structures at scale.

Using this framework, we construct ULogic, an inferential rule base with around 8,000 primitive rules and over 6,000 compositional rules. These rules span five key domains: object affordance, accessibility, interaction, location, and person's need. We hope ULogic will serve as a valuable resource, facilitating the assessment of LLMs' proficiency in underlying logic and enhancing flexible rule generation and downstream reasoning. We utilize ULogic to create an entailment probing task with a comprehensive and robust evaluation strategy, to assess LLMs' grasp of inferential rules against human performance. Our analysis of GPT-series LLMs, including GPT-4, GPT-3.5-Turbo and GPT-3.5-Turbo-Instruct, indicates they have a basic understanding of inferential rules but fall short of human proficiency, especially in rules with complex premises. Specifically, all models struggle more as the compositional complexity increases. While GPT-4 performs consistently on verbalized and symbolic rules, the other models sharply degrade on symbolic rules. Additionally, all models exhibit disparities on various rule structures with Disjunctive-Transitive rules posing the greatest challenges. Moreover, these LLMs display notable polarity biases with GPT-4 showing a necessary bias, underscoring areas for improvement.

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

We further distill crafted inferential rules into a smaller-scale inference engine for flexible rule generation and downstream reasoning. We design three tasks: conclusion generation, premise completion and premise generation, to construct an instructiontuning dataset for inferential rule distillation. Experimental results through a multi-judger evaluation mechanism incorporating automatic metrics, LLM evaluators and human preferences show that our inference engine possesses the ability for these three tasks. It outperforms GPT-3.5-Turbo across all dimensions of three tasks and even surpasses GPT-4 in generating more complex and abstract rules. Moreover, it can generate logical rules that enhance downstream commonsense reasoning.

2 Logic Scaffolding for Inferential Rule Generation

2.1 Preliminary of Inferential Rules

To better control the generative capability of LLMs for rule generation, we focus on *if-then* inferential rules with variables, that can be easily expressed as symbolic logic (Novák and Lehmke, 2006). An inferential rule describes a logical implication from a premise (a set of facts) to a conclusion (a specific fact), where each fact is a predicate expression with two variables, and each variable has a designated variable type. For each rule, we employ logic scaffolding which first generates its symbolic expression to consistently guide its verbalized form.

We utilize Prolog (Apt et al., 1997) to formulate 144



Figure 3: The pipeline of primitive rule generation.

symbolic rules as Conclusion: -Premise, where :- indicates the logical implication. For example,

145

146

147

148

149

150

151

152

153

155

156

CanNotEat(Person X, Food Y):-AllergicTo(Person X, Substance Z), Contains(Food Y, Substance Z). (1)

The left-hand side is the conclusion and the right hand lists premise facts connected by commas. "CanNotEat", "AllergicTo" and "Contains" are predicate verbs while Person, Food, Substance are variable types of variables (X, Y, Z). This symbolic rule can be verbalized as: *If Person X is allergic to Substance Z and Food Y contains Substance Z, then Person X cannot eat Food Y.*

Primitive Rule We aim to generate primitive rules 158 for further compositions and potential generalization. We formally define primitive rules as follows: 160 (1) they concern abstract objects, like Person and 161 Food, rather than specific instances, and their com-162 mon properties; (2) they cannot be decomposed into simpler rules. Inspired by superordinate ob-164 jects such as instrument, fruit, tool from Rosch and Mervis (1975), we assemble a collection of abstract objects. We first identify the most 167 common tail nodes of "IsA" relations from Con-168 ceptNet (Speer et al., 2017). For those nodes that 169 are still fine-grained, we further seek their general hypernyms by searching ConceptNet and Word-Net (Miller, 1995). We totally gather a list of 32 172 most common abstract objects for primitive rule 173 generation, with 18 common properties generated 174 by prompting GPT-4, as detailed in Appendix A.1. 175

2.2 Primitive Rule Generation Pipeline

The pipeline of primitive rule generation is illustrated in Figure 3, consisting of five steps. First,
we randomly select two abstract objects, and generate potential predicates between them to form

conclusions. GPT-4 is prompted to generate corresponding feasible premises with both single and multiple facts, thereby constructing candidate primitive rules. We then apply heuristic methods to filter invalid and non-primitive rules, and utilize GPT-4 to select the rules it deems logically correct. We further diversify rule predicates via backward/forward chaining (Urbani et al., 2011; Shindo et al., 2021) with generated single-fact rules, and filter excessively repetitive rules. Finally, the diversified rules undergo manual verification to ensure the final set of high-confidence primitive rules.

Step-1: Conclusion Preparation From the set of abstract objects, we select any two, e.g., Person and Food, and prompt GPT-4 to generate potential predicates connecting them as conclusions, e.g., CanEat(Person X, Food Y). We attempt every possible pairing of two, where the selected objects can be identical. For each pair of objects, $\{object_1\}$ and $\{object_2\}, we aim to generate conclusions across$ five domains: {object affordance, accessibility, interaction, location and person's need}, thereby covering diverse scenarios. Explanations and example rules of these domains are listed in Appendix A.2. The prompt for conclusion preparation about affordance is below. Besides, we negate the generated predicates to yield both positive and negative conclusions, e.g., *CanNotEat(Person X, Food Y)*, across object affordance, accessibility, and interac-

Prompt for Conclusion Preparation

According to commonsense knowledge in reality, please list 5 predicates between the given two objects to describe the {object affordance}. Examples: Object: Show, Artwork Predicate: CanBeAdaptedFrom(Show X, Artwork Y) **Object**: {object₁}, {object₂} **Predicate**: 182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

209

tion domains, building a complete rule set.

Step-2: Premise Generation Guided by a symbolic conclusion, we prompt GPT-4 to generate its 214 premises in both symbolic and verbalized forms 215 for better controllability. This process involves 216 the logit bias setting, motivating premises to de-217 scribe relationships between abstract objects and 218 their properties. Specifically, premises are gener-219 ated under the constraint of logit bias, increasing the likelihood of these objects and properties ap-221 pearing in the output. For each conclusion, we create both single-fact and multi-fact premises to 223 yield candidate rules of varying lengths. We tailor instructions and demonstrations for each domain to prompt GPT-4 for premise generation exploring different possibilities, as detailed in Appendix A.3.

Step-3: Rule Filtering After over-generating candidate primitive rules, we first design several heuristic methods to filter grammatically invalid or nonprimitive rules, based on their symbolic forms. For grammatically validity, we check whether the variables in premises form a connected graph from node "X" to node "Y", as in Appendix A.4. Regarding primitiveness, we exclude rules with nonprimitive variable types or those comprising more than 3 premise facts. Besides, we eliminate trivial rules that both contain negative words in their premise and conclusion, e.g., *CanNotEat(Person X, Food Y):- CanNotAccess(Person X, Food Z)*.

238

241

243

244

247

248

249

250

Directly generating logically correct rules is challenge. Thus we further adopt a self-critic strategy (Gou et al., 2023) where GPT-4 critiques the accuracy of its self-generated rules in a verbalized format, and provides explanations of its judgments. When prompting GPT-4, we include two demonstrations featuring both correct and incorrect rules to mitigate label bias. These demonstrations vary across different domains. An example prompt for object affordance is in Appendix A.5.

251Step-4: Rule Diversifying
To increase the va-
riety of rule expressions, we diversify predicates
while maintaining its logical accuracy. Based on
symbolic rules, we respectively apply forward and
backward chaining algorithms to their conclusion
and premise with generated single-fact rules, as
shown in Figure 4. In forward chaining, we take
the conclusion as a new premise to generate an
intermediate single-fact rule, subsequently substi-
tuting the original conclusion with this newly de-
rived conclusion. In backward chaining, a premise
take as a conclusion to create an intermediate

single-fact rule, and replace the original premise with the new-generated one. Intermediate singlefact rules are also generated through Step-2 and 3. Each original rule undergoes one forward and one backward chaining to derive two diversified rules.



Figure 4: The forward and backward chaining process for diversifying rules.

Step-5: Human Verification To obtain more reliable inferential rules, we utilize Amazon Mechanical Turk (AMT) to recruit human annotators for manual verification. For each rule, three annotators are asked to assess the clarity and comprehensibility of its premise and conclusion, as well as the logical entailment from the premise to the conclusion. Only the rules unanimously validated by all three annotators are preserved. The AMT template for human verification and the overall rates of rule acceptance are listed in Appendix A.6.

2.3 Rule Composition

We create more compositional rules by applying backward chaining upon primitive rules with different chaining steps. In each step, we select a premise fact from the current rule as a conclusion, deriving a new primitive rule that describes its multi-fact premise. This selected fact is then replaced with the newly generate premise. This process is iteratively conducted 1 to 3 times, creating rules with varying compositional levels (1 to 3). An example of one backward chaining step is shown in Figure 5. The intermediate primitive rules used in backward chaining are generated via the pipeline described in Sec. 2.2, thus also contributing to our primitive rule set. As the composition of logically correct sub-rules is also logically correct, there is no need to verify these compositional rules separately.

2.4 Rule Statistics

Using Logic-RGC framework, we construct an inferential rule base ULogic comprising 14,647 rules, with 7,967 primitive and 6,680 compositional ones. These rules span five key domains:

263 264 265

267

269

270

271

272

273

274

275

277

278

279

280

281

282

283

284

285

286

289

290

292

293

294

295

297

298



Figure 5: Illustration of one backward chaining step.

object affordance, accessibility, interaction, location and person's need. They vary in compositional depth from 0 to 3, with rule lengths ranging from 1 to 6. Detailed statistics are in Table 1.

Domain	Aff.	Acc.	Int.	Loc.	Need	Total		
Primitive rules								
Single-fact	328	513	440	194	87	1,562		
Multi-fact	387	638	2,527	166	128	3,846		
Intermediate	417	590	1,286	165	101	2,559		
	6,680							
Comp.=1	322	675	936	111	91	2,135		
Comp.=2	199	773	744	100	136	1,952		
Comp.=3	229	1052	896	217	199	2,593		

Table 1: Statistics of constructed rule base. Aff., Acc., Int., Loc., Comp. are abbreviations of Affordance, Accessibility, Interaction, Location and Compositionality.

3 Assessing LLMs' Proficiency in Capturing Inferential Rules

We utilize ULogic for a systematic evaluation of LLMs' proficiency in underlying logic compared to human competence. Specifically, we select a high-quality probing subset with 1,104 diverse rules from our rule base ², and create a binary entailment classification task for assessing whether LLMs capture the entailment within inferential rules.

3.1 Analysis Setup

Considering LLMs' sensitivity to various input formulations and shortcut biases, we design a comprehensive and robust assessment mechanism to ensure reliable analysis. For each inferential rule, we convert it into five distinct probing questions to mitigate template bias, as summarized in Appendix B.1. We report the average accuracy and variance (the error line of each bar) across five templates. Besides, we adopt a two-shot chain of thought (CoT) prompting strategy (Wei et al., 2022) requiring the model to generate a rationale after presenting its answer, using "and also explain why." We include one correct rule and one incorrect rule in the two demonstrations to minimize label bias.

Following the Law of Non-Contradiction (Priest et al., 2006), the propositions "If X, then Y" and "If X, then not Y" are mutually exclusive that cannot both be true at the same time. To enhance the reliability of our probing, we flip each rule by negating its conclusion, and simultaneously probe both the original rule and its flipped version. A rule is accurately classified only if the original rule is affirmed (True/Right/Yes) and its flipped counterpart is negated (False/Wrong/No), as shown below. A specific example is in Appendix B.2. This dualsided probing is applied to both human and LLMs.

If Premise, then Conclusion_original.	True/Right/Yes
If Premise, then Conclusion_flipped.	False/Wrong/No

3.2 Empirical Analysis

We conduct analysis on GPT-series LLMs, including GPT-4, GPT-3.5-Turbo and GPT-3.5-Turbo-Instruct³, aiming to investigate LLMs' proficiency of inferential rules against human performance by exploring the following questions. The human performance is obtained by asking AMT annotators whether the input rule is logical correct with high probability. Each performance presented in following bar charts is calculated based on 150 instances randomly sampled from our probing subset.

(1) How does model performance vary with increasing compositional complexity? We conduct rule probing in terms of different compostional lengths, as illustrated in Figure 6a. "Length=1,2,3,4" respectively denote rules with $1 \sim 4$ facts in their premises. The analysis of different compostional depths is also provided in Appendix B.3. They both reveal that as compositional complexity increases, the performance of both human and all models drops. The primary reason is that compositional complex rules typically necessitate the aggregation of multi-step reasoning, which escalates higher-order relationships understanding and exponential error accumulation with each additional step (Dziri et al., 2023). Besides, there is a persistent performance gap between all models and human, particularly pronounced with

302 303

301

304

315

317

321

322

361

362

363

364

365

366

368

323

324

325

326

327

328

329

330

331

332

333

334

335

336

337

338

339

340

341

342

343

344

345

347

348

349

351

352

353

354

355

²These high-quality probing rules are verified by authors, covering various lengths, polarities and structures.

³Substituting the now-deprecated Text-davinci-003.



Figure 6: Probing results across varied lengths.



410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

compositional complex rules, suggesting significant potential for enhancement in this area.

371

(2) Are LLMs proficient in capturing both symbolic and verbalized rules? We further analyze the performance of LLMs on symbolic rules (see 374 Figure 6b), and compared it to the verbalized result 375 in Figure 12. We observe that GPT-4 achieves consistent performance on verbalized and symbolic rules, whereas GPT-3.5-Turbo and GPT-3.5-Instruct sharply degrade on symbolic rules. This suggests that the GPT-3.5 series may have limitations in generalizing across varied types of linguis-381 tic structures beyond natural language, whereas GPT-4 likely have undergone specific optimizations for symbolic interpretations.

(3) Are there performance disparities among models concerning different rule structures?
Our generated multi-fact rules (Length > 1) have three intrinsic structures: Transitive, Disjunctive and Disjunctive-Transitive. Specific illustrations and examples of each structure are detailed in Appendix B.4. Figure 7 shows that Disjunctive-Transitive rules pose greater challenges compared to Transitive and Disjunctive ones, especially for GPT-3.5-Turbo and GPT-3.5-Instruct. We hypothesize that this discrepancy stems from increased compositional complexity and LLMs' insufficient learning of logical structures in natural language.

(4) Do LLMs exhibit a polarity bias over inferential rules? Our inferential rules contain both positive and negative conclusions. We conduct a com-400 parative analysis of polarity discrepancy, as shown 401 in Figure 8a. GPT-4 and GPT-3.5-Instruct exhibit 402 a pronounced positive bias, performing better on 403 404 rules with positive conclusions. This bias may originate from the imbalanced distribution of LLMs' 405 training data (Garg et al., 2022), with a higher pro-406 portion of positive statements. We further explore 407 different CoT strategies with GPT-4: (1) first an-408

swer then explain (*Answer-Explain*), (2) first think then answer (*Think-Answer*), (3) self-consistently think then answer (*Self-Consistency*) (Wang et al., 2022). Various CoT prompts are listed in Appendix B.5. Figure 8b shows that although advanced CoT strategies can mitigate the positive bias, they adversely impact the performance on rules with both positive and negative conclusions.



(a) Answer-Explain strategy. (b) Various CoT strategies.Figure 8: Rule Polarity Comparison.

(5) Why does GPT-4 significantly underperform GPT-3.5-Turbo on transitive rules? Previous analysis shows that GPT-4 generally outperforms or equals the other models, but this superiority disappears on transitive rules, as evidenced in Figure 7. We investigate this question in Appendix B.6, which reveals that GPT-4 exhibits a "necessary bias" that tend to consider all necessary conditions reaching a conclusion, avoiding definite judgement. This conservative style may come from LLMs' preference alignment during Reinforcement Learning with Human Feedback (Ouyang et al., 2022).

Overall, GPT-4 performs best in grasping inferential rules. But compared to human performance, there still remains substantial room for improvement across all models, especially in highly compositional, symbolic and structural complex rules. Besides, all models tend to exhibit a polarity bias towards rules with positive conclusions with GPT-4 also showing a necessary bias. These findings suggest potential areas for future enhancements.

438

441 442

443

444

- 449 450 451
- 452
- 453 454
- 455
- 456
- 457 458
- 459
- 460 461
- 462
- 463 464
- 465 466
- 467

472

468

470

471

473 474

476 477 478

475

479

4 **Rule Distillation as Inference Engine**

Instruction Dataset & Model Tuning 4.1

For flexible rule generation and benefiting downstream reasoning, we distill our crafted rules into a smaller-scale inference engine as illustrated in Appendix C.1. We tailor three tasks: conclusion generation, premise completion and premise generation, to construct an instruction-tuning dataset for inferential rule distillation. The detailed definitions of these tasks are also described in Appendix C.1.

We gather all primitive rules and partial compositional rules to formulate the instruction-tuning dataset, as compositional rules are constructed from primitive ones. We take 10,703 rules for training and 943 for testing. Altogether, we create 39,887 instances for instruction tuning, including 10,703, 18,500 and 10,684 for conclusion generation, premise completion and premise generation. We have 3,500 testing instances, divided as 943, 1,614 and 943 for these three tasks. We use Mistral-7b (Jiang et al., 2023) as the backbone model and fine-tune it with our constructed instruction dataset as our inference engine. The training details and demo page can be found in Appendix C.2.

4.2 Rule Generation Evaluation

We compare our inference engine against GPT-4 and GPT-3.5-Turbo across three tasks to assess rule generation. For a fair comparison, we prompt GPT-4 and GPT-3.5-Turbo to simultaneously generate symbolic and verbalized responses, using similar prompts as in Step-2 of Sec. 2.2. Detailed prompts are in Appendix C.3. We introduce a multi-judger evaluation mechanism, incorporating automatic metrics, LLM evaluator and human preference. We evaluate the logical accuracy for conclusion generation and premise completion. For premise generation task with a specified number of facts, we generate three potential premises for each conclusion, and compare these premises in accuracy, diversity, complexity and abstractness. Detailed definition of these metrics are described in Appendix C.4.

Automatic Evaluation For automatic accuracy evaluation of three tasks, we calculate BLEU 480 score (Papineni et al., 2002) against reference re-481 sponses. For complexity of premise generation, we 482 483 assess the average fact number of three generated premises. For diversity, we compute average Self-484 BLEU (Shu et al., 2019; Tevet and Berant, 2020) 485 between three generated premises. Specifically, 486 Self-BLEU measures the BLEU score of a gener-487

ated premise against another, and a high average Self-BLEU indicates low diversity. Abstractness is not easy to evaluate automatically, so we leave it to LLM evaluation. The results are shown in Table 2.

Task	Conc Gen	Prem Comp		Prem Gen	
Metrics	BLEU	BLEU	BLEU	Self-BLEU	Fact Num.
Engine	0.739	0.527	0.411	0.687	3.42
GPT-4	0.414	0.179	0.149	0.805	2.58
GPT-3.5	0.338	0.248	0.084	0.739	1.72

Table 2: Automatic evaluation results. "Conc Gen", "Prem Comp" and "Prem Gen" are abbreviations of conclusion generation, premise completion and generation.

LLM Evaluation We adopt GPT-4 as an evaluator to rate the generated responses on a scale from 1 to 3. The criteria of each rating along with examples are provided to the evaluator. Please see Appendix C.5 for detailed prompts. For each task, we select 100 instances for LLM evaluation, ensuring a balance across all domains and all types (including single-fact, multi-fact, intermediate, composition= $1 \sim 3$ rules) as detailed in Table 1. The rating results are presented in Table 3.

Task	Conc Gen	Prem Comp		Pren	n Gen	
Metrics	Acc	Acc	Acc	Div.	Cpx.	Abs.
Engine	2.44	2.78	2.34	1.89	1.62	2.43
GPT-4	2.53	2.72	2.77	2.64	1.40	2.32
GPT-3.5	2.38	1.57	1.91	1.72	1.06	2.30

Table 3: LLM evaluation results.

Human Evaluation To better assess premise generation in line with human value, we further recruit two annotators for each instance to compare their accuracy. We implement a pairwise comparison setting, asking annotators to determine which group of generated premise is more accurate in terms of logical consistency with the given conclusion, commonsense alignment and correctness of fact numbers. The results are shown in Fiure 9.





From all evaluation, we can see that our inference engine enables the smaller-scale LLM with

513 514

512

488 489 490

492

493

494

495

496

497

498

499

500

501

502

503

504

505

506

507

508

509

510

511

the capability for conclusion generation, premise
completion and premise generation. It performs
better than GPT-3.5-Turbo across all metrics in
three tasks, and even outperforms GPT-4 to generate more complex and abstract rules.

4.3 Downstream Reasoning Evaluation

521

524

525

527

529

533

535

539

541

543

544

545

546

547

548

549

550

553

We further analyze the effectiveness of our inference engine in generating logical rules or explanations to enhance downstream reasoning tasks. We evaluate on following commonsense reasoning datasets: StrategyQA (Geva et al., 2021), SOCIAL IQA (Sap et al., 2019b), LINK (Li et al., 2023), PIQA (Bisk et al., 2020) and CSQA2.0 (Talmor et al., 2022). We use a zero-shot CoT strategy to prompt two baseline models, Mistral-7B-Instructv0.1 and Llama-2-7b-chat (Touvron et al., 2023), to answer questions with following explanations. We then utilize our inference engine to generate logical rules or explanations relevant to answer questions, and supplement these generated rationals to baseline models as input to enhance their performance. We compare the prediction accuracy of our inference engine augmented models against baselines.

The comparative results are shown in Tabel 4. Our inference engine can generate logical rules or explanations that benefit multiple downstream commonsense reasoning tasks on top of different backbone models. For the lack of clear advantage on PIQA and performance decline on CSQA2.0, we speculate that PIQA may be contaminated during Mistral's training process, and CSQA2.0's focus is mainly on longtail commonsense knowledge rather than requiring logical rules inference, like "Is cotton candy sometimes made out of cotton?"

Dataset	Mistral Mistral+rules (Mistral-7b)		LLama LLama+rules (LLama2-7b)		
StrategyQA	54.50	56.75	58.00	60.48	
SOCIAL IQA	64.00	68.50	53.50	60.50	
LINK head	53.68	68.38	58.09	70.59	
LINK longtail	53.33	67.50	55.83	65.00	
PIQA	65.00	65.00	58.5	62.0	
CSQA2.0	59.00	62.50	64.00	60.00	

Table 4: Downstream reasoning performance.

5 Related Work

Logical Rule Generation Logical inferential rules are crucial for everyday reasoning (Geva et al., 2021; Talmor et al., 2022), and collecting these inferential rules is challenging. Prior work mainly

adopts inductive logic programming (ILP) (Yang and Song, 2019; Qu et al., 2020; Sen et al., 2022) for rule generation. However, they can only generate rules from existing knowledge graphs and the generated rules has potential inaccuracies. Alternatively, Sinha et al. (2019) manually create a set of inferential rules for inductive reasoning, but their scope is limited to kinship. Sap et al. (2019a) construct a commonsense inferential rule base through crowdsourcing, but these rules tend to be overly simple and specific, struggling to move beyond basic intuition and generalize to varied situations. Abstract and complex rules are essential in tackling diverse complex questions, paving the way for complex reasoning and decision-making. Although LLMs have opened new avenues for generating inferential rules (Zhu et al., 2023), they still struggle to automatically craft abstract and complex rules.

554

555

556

557

558

559

560

561

562

563

564

565

566

567

568

569

570

571

572

573

574

575

576

577

578

579

580

581

582

583

584

585

586

587

589

590

591

592

593

594

595

596

597

598

599

600

601

602

603

Integration of Logical Rules and LLMs Recently, the integration of inferential rules with neural networks, particularly LLMs, has gained significant attention. This approach combines the logical interpretability of symbolic reasoning and adaptive power of neural computing, improving LLMs' logical reasoning ability. Wang et al. (2021); Olausson et al. (2023) transform textual statements into logical expressions and conduct symbolic reasoning following logical rules. Weir and Van Durme (2022) train neural models using a set of inferential rules for dynamic application. This direction broadens LLMs' ability with flexible rule generation and application for complex reasoning.

6 Conclusion

This paper examines the proficiency of GPT-series LLMs in capturing logical inferential rules and probes their challenging reasoning space. We introduce a logic scaffolding inferential rule generation (LOIRE) framework to create an inferential rule base ULogic, including nearly 8,000 primitive rules and over 6,000 compositional rules across five domains. Our evaluations using a subset of ULogic show that even advanced models like GPT-4 struggle with compositional and structural complex rules and exhibit certain biases. Furthermore, we distill ULogic into a smaller inference engine that performs well in generating inferential rules and benefit downstream reasoning tasks. Our work points out where LLMs need to improve in logical reasoning and offers a pathway to enhance their reasoning capabilities.

4 Limitations

Limitation on inferential rule coverage. Commonsense inferential rules may exist in diverse formats and span various domains. Our work mainly focuses on rules formatted as *if-then* statements, covering five domains: object affordance, accessibility, interaction, location and person's need. In future work, we will expand our scope to include inferential rules of other formats and explore additional domains for broader coverage.

614Limitation on probing open-source models.615Our work does not probe and analyze open-source616models. While GPT-4 and GPT-3.5-turbo are con-617sidered as the most advanced models, open-source618counterparts may exhibit different behaviors or pat-619terns in understanding inferential rules with varying620complexities. These aspects will be the subject of621future exploration.

Risk of environmental impact A significant risk
associated with our framework and analysis is the
potential increase in environmental burdens due
to the extensive use of OpenAI's APIs for LLMs.
This impact can be mitigated by replacing GPT-4
with future smaller-scale open-source models that
are more efficient with less environmental impact.

Potential error in rule generation. Generating
inferential rules with specific requirements poses
a significant challenge. As the majority of our
framework's pipeline are powered by GPT-4, it may
inevitably generate inferential rules with logical
inaccuracies even incorporating human verification.
This might result in less accurate probing of LLMs.

Ethical Consideration

636

All rules we collected through LLMs are released 637 publicly for usage and its probing subset for proficiency analysis have been subjected to a thorough 639 review by the authors. The code of our generation pipeline and probing experiments will also be publicly released. This setting guarantees transparency and reproducibility in our experiments, allowing other researchers to evaluate and expand upon our work. Our logic scaffolding framework is strictly limited to be used for rule generation that follow the ethical guidelines of the community. The authors 647 emphatically denounce the use of our framework for generating inaccurate or harmful rules.

References

Ajlan Al-Ajlan. 2015. The comparison between forward and backward chaining. <i>International Journal of</i> <i>Machine Learning and Computing</i> , 5(2):106.	651 652 653
Krzysztof R Apt et al. 1997. <i>From logic programming</i> <i>to Prolog</i> , volume 362. Prentice Hall London.	654 655
Jon Barwise. 1993. Everyday reasoning and logical inference. <i>Behavioral and Brain Sciences</i> , 16(2):337–338.	650 657 658
Yonatan Bisk, Rowan Zellers, Jianfeng Gao, Yejin Choi, et al. 2020. Piqa: Reasoning about physical com- monsense in natural language. In <i>Proceedings of the</i> <i>AAAI conference on artificial intelligence</i> , volume 34, pages 7432–7439.	659 660 661 662
Paul Boghossian. 2014. What is inference? <i>Philosophi-</i> <i>cal studies</i> , 169:1–18.	664 665
Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. 2023. Qlora: Efficient finetuning of quantized llms. <i>arXiv preprint arXiv:2305.14314</i> .	666 667 668
Nouha Dziri, Ximing Lu, Melanie Sclar, Xiang Lorraine Li, Liwei Jian, Bill Yuchen Lin, Peter West, Chandra Bhagavatula, Ronan Le Bras, Jena D Hwang, et al. 2023. Faith and fate: Limits of transformers on com- positionality. <i>arXiv preprint arXiv:2305.18654</i> .	669 670 672 673
Hervé Gallaire and Jack Minker. 2012. <i>Logic and data bases</i> . Springer Science & Business Media.	674 675
Apoorv Garg, Deval Srivastava, Zhiyang Xu, and Lifu Huang. 2022. Identifying and measuring token-level sentiment bias in pre-trained language models with prompts. <i>arXiv preprint arXiv:2204.07289</i> .	670 677 678 679
Mor Geva, Daniel Khashabi, Elad Segal, Tushar Khot, Dan Roth, and Jonathan Berant. 2021. Did aristotle use a laptop? a question answering benchmark with implicit reasoning strategies. <i>Transactions of the</i> <i>Association for Computational Linguistics</i> , 9:346– 361.	680 681 682 683 684 684
Zhibin Gou, Zhihong Shao, Yeyun Gong, Yelong Shen, Yujiu Yang, Nan Duan, and Weizhu Chen. 2023. Critic: Large language models can self-correct with tool-interactive critiquing. <i>arXiv preprint</i> <i>arXiv:2305.11738</i> .	688 687 688 689
Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2021. Lora: Low-rank adaptation of large language models. <i>arXiv preprint arXiv:2106.09685</i> .	691 692 693 694
Albert Q Jiang, Alexandre Sablayrolles, Arthur Men- sch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guil- laume Lample, Lucile Saulnier, et al. 2023. Mistral 7b. arXiv preprint arXiv:2310.06825.	690 697 698 699

807

808

809

810

- 714 715 716 727 741
- 710 711 712

701

702

704

Huihan Li, Yuting Ning, Zeyi Liao, Siyuan Wang, Xi-

ang Lorraine Li, Ximing Lu, Faeze Brahman, Went-

ing Zhao, Yejin Choi, and Xiang Ren. 2023. In

search of the long-tail: Systematic generation of long-

tail knowledge via logical rule guided search. arXiv

George A Miller. 1995. Wordnet: a lexical database for

Vilém Novák and Stephan Lehmke. 2006. Logical struc-

Theo X Olausson, Alex Gu, Benjamin Lipkin, Cedegao E Zhang, Armando Solar-Lezama, Joshua B

Tenenbaum, and Roger Levy. 2023. Linc: A neu-

rosymbolic approach for logical reasoning by com-

bining language models with first-order logic provers.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida,

Carroll Wainwright, Pamela Mishkin, Chong Zhang,

Sandhini Agarwal, Katarina Slama, Alex Ray, et al.

2022. Training language models to follow instruc-

tions with human feedback. Advances in Neural

Information Processing Systems, 35:27730–27744.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-

Jing Zhu. 2002. Bleu: a method for automatic evalu-

ation of machine translation. In Proceedings of the

40th annual meeting of the Association for Computa-

Graham Priest, Jeffrey C Beall, and Bradley Armour-

Meng Qu, Junkun Chen, Louis-Pascal Xhonneux,

Eleanor Rosch and Carolyn B Mervis. 1975. Family

categories. Cognitive psychology, 7(4):573-605.

Maarten Sap, Ronan Le Bras, Emily Allaway, Chan-

dra Bhagavatula, Nicholas Lourie, Hannah Rashkin,

Brendan Roof, Noah A Smith, and Yejin Choi. 2019a.

Atomic: An atlas of machine commonsense for if-

then reasoning. In Proceedings of the AAAI con-

ference on artificial intelligence, volume 33, pages

Maarten Sap, Hannah Rashkin, Derek Chen, Ronan LeBras, and Yejin Choi. 2019b. Socialiga: Com-

monsense reasoning about social interactions. arXiv

Prithviraj Sen, Breno WSR de Carvalho, Ryan Riegel,

and Alexander Gray. 2022. Neuro-symbolic induc-

tive logic programming with logical neural networks.

In Proceedings of the AAAI Conference on Artificial

resemblances: Studies in the internal structure of

Yoshua Bengio, and Jian Tang. 2020. Rnnlogic:

Learning logic rules for reasoning on knowledge

Garb. 2006. The law of non-contradiction: New

arXiv preprint arXiv:2310.15164.

OpenAI. 2023. Gpt-4 technical report.

tional Linguistics, pages 311–318.

philosophical essays. Clarendon Press.

graphs. arXiv preprint arXiv:2010.04029.

english. Communications of the ACM, 38(11):39-41.

ture of fuzzy if-then rules. FUZZY sets and systems,

preprint arXiv:2311.07237.

157(15):2003-2029.

- 717 718 719 725
- 720 721

- 742 743
- 745 746

751 752

- Intelligence, volume 36, pages 8212-8219. 755

3027-3035.

preprint arXiv:1904.09728.

- Hikaru Shindo, Devendra Singh Dhami, and Kristian Kersting. 2021. Neuro-symbolic forward reasoning. arXiv preprint arXiv:2110.09383.
- Raphael Shu, Hideki Nakayama, and Kyunghyun Cho. 2019. Generating diverse translations with sentence codes. In Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics, pages 1823–1827.
- Koustuv Sinha, Shagun Sodhani, Jin Dong, Joelle Pineau, and William L Hamilton. 2019. Clutrr: A diagnostic benchmark for inductive reasoning from text. arXiv preprint arXiv:1908.06177.
- Robyn Speer, Joshua Chin, and Catherine Havasi. 2017. Conceptnet 5.5: An open multilingual graph of general knowledge. In Proceedings of the AAAI conference on artificial intelligence, volume 31.
- Alon Talmor, Ori Yoran, Ronan Le Bras, Chandra Bhagavatula, Yoav Goldberg, Yejin Choi, and Jonathan Berant. 2022. Commonsenseqa 2.0: Exposing the limits of ai through gamification. arXiv preprint arXiv:2201.05320.
- Guy Tevet and Jonathan Berant. 2020. Evaluating the evaluation of diversity in natural language generation. arXiv preprint arXiv:2004.02990.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023. Llama 2: Open foundation and fine-tuned chat models. arXiv preprint arXiv:2307.09288.
- Jacopo Urbani, Frank Van Harmelen, Stefan Schlobach, and Henri Bal. 2011. Querypie: Backward reasoning for owl horst over very large knowledge bases. In The Semantic Web–ISWC 2011: 10th International Semantic Web Conference, Bonn, Germany, October 23-27, 2011, Proceedings, Part I 10, pages 730-745. Springer.
- Lei Wang, Wanyu Xu, Yihuai Lan, Zhiqiang Hu, Yunshi Lan, Roy Ka-Wei Lee, and Ee-Peng Lim. 2023. Planand-solve prompting: Improving zero-shot chain-ofthought reasoning by large language models. arXiv preprint arXiv:2305.04091.
- Siyuan Wang, Wanjun Zhong, Duyu Tang, Zhongyu Wei, Zhihao Fan, Daxin Jiang, Ming Zhou, and Nan Duan. 2021. Logic-driven context extension and data augmentation for logical reasoning of text. arXiv preprint arXiv:2105.03659.
- Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. 2022. Self-consistency improves chain of thought reasoning in language models. arXiv preprint arXiv:2203.11171.
- Peter C Wason. 1968. Reasoning about a rule. Quarterly journal of experimental psychology, 20(3):273-281.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in Neural Information Processing Systems*, 35:24824–24837.

811

812

813

815

816

818

819

824

825

826

- Nathaniel Weir and Benjamin Van Durme. 2022. Dynamic generation of interpretable inference rules in a neuro-symbolic expert system. *arXiv preprint arXiv:2209.07662.*
- Yuan Yang and Le Song. 2019. Learn to explain efficiently via neural logic inductive learning. *arXiv preprint arXiv:1910.02481*.
- Zhaocheng Zhu, Yuan Xue, Xinyun Chen, Denny Zhou, Jian Tang, Dale Schuurmans, and Hanjun Dai. 2023. Large language models can learn rules. *arXiv preprint arXiv*:2310.07064.

A Primitive Rule Generation Pipeline

A.1 Abstract Objects and Common Properties

Table 5 list 32 most common abstract objects and18 common properties for primitive rule generation.

827

828

829

830

831

832

833

836

837

838

839

840

841

842

843

844

845

846

847

848

Туре	Words
Abstract Objects	"Person", "Animal", "Plant", "Food", "Alcohol", "Disease", "Drug", "Natural Phenomenon", "Con- dition", "Material", "Substance", "Furniture", "Pub- lication", "Organization", "Authorization", "Facil- ity", "Natural Place", "Event", "Show", "Artwork", "Job", "Game", "Vehicle", "Tool", "Technology", "Electronic Device", "Platform", "Financial Product", "Skill", "Legislation", "Region", "Time Period"
Common Properties	"Age", "Price", "Money", "Height", "Length", "Weight", "Strength", "Size", "Density", "Volume", "Temperature", "Hardness", "Speed", "BoilingPoint", "MeltingPoint", "Frequency", "Decibel", "Space"

Table 5: List of pre-defined abstract objects and common properties.

A.2 Rule Domains

Table 6 illustrates the detailed explanations, example predicates and rules across five domains.834835

A.3 Prompts for Premise Generation

For premise generation in each domain, we design an instruction followed by two demonstrations to iteratively prompt GPT-4, and the underlined sentence is the rule description which varies according to the specific domain, as shown in Table 7.

A.4 Grammatical Validity for Rule Filtering

As Figure 10, we check whether the variables in premises form a connected graph from node "X" to node "Y" to filter grammatically invalid rules.



Figure	10:	Grammatically	valid	and	invalid	rule	graphs.
<u> </u>		2					<u> </u>

A.5 Prompts for Rule Filtering

Table 8 is an example prompt for rule filtering inobject affordance domain.

Domain	Explanation	Predicates	Examples
Object Affordance	Whether a person can take an action over an object based on its property and requirement	CanDrive(Person X, Vehicle Y); CanCreate(Person X, Artwork Y); CanAttend(Person X, Event Y);	CanDrive(Person X, Vehicle Y):- Have(Person X, Age Z1), RequireMinimumAge(Vehicle Y, Age Z2), BiggerThan(Age Z1, Age Z2);
Object Accessibility	Whether an object can ac- cess the other object based on its physical condition, spatial and temporal restriction	CanAccess(Person X, Show Y); CanAccess(Animal X, Tool Y); CanAccess(Animal X, Animal Y);	CanAccess(Person X, Show Y):- Locate- dIn(Person X, Region Z), BroadcastIn(Show Y, Region Z); CanNotAccess(Person X, Tool Y):- AllergicTo(Person X, Material Z), MadeOf(Tool Y, Material Z);
Object Interaction	How an object can interact with the other object based on their physical, spatial or tem- poral properties	CanSubmergeIn(Substance X, Substance Y); CanAdapted- From(Show X, Artwork Y); CanFitIn(Tool X, Tool Y);	CanSubmergeIn(Substance X, Substance Y):- DensityOf(Substance X, Density Z1), DensityOf(Substance Y, Density Z2), Big- gerThan(Density Z1, Density Z2);
Object Location	The location description of an object	OriginatedFrom(Food X, Region Y); BannedIn(Drug X, Region Y); BornIn(Person X, Region Y);	OriginatedFrom(Food X, Region Y):- Pro- cessedIn(Food X, Facility Z), LocatedIn(Facility Z, Region Y);
Person's Need	Person need to take an action over objects under a specific circumstance	NeedToConsume(Person X, Drug Y); NeedToWater(Person X, Plant Y);	NeedToConsume(Person X, Drug Y):- Has(Person X, Disease Z), CanTreat(Drug Y, Disease Z);

Table 6: The explanations, example predicates and rules of five different domains.

Instruction for Premise Generation (Object Affordance)

According to commonsense knowledge in realistic scenarios, please generate 2 logical rules in both Prolog and natural language to describe the premises of the given conclusion. The rules in Prolog should have the same meaning with the rules in natural language.

Each rule should contain multiple premises and each premise should contain two variables in (X, Y, Z, Z1, Z2). The rules should describe object affordance based on its property (such as height, age, price) and requirement (such as required skill, source, tool).

The premises should not contain negative words such as 'not', 'no', 'never' and 'un-'

Conclusion: {conclusion} Rules:

Demonstrations for Premise Generation (Object Affordance)

Conclusion: CanCook(Person X, Food Y)

Rules:

1. CanCook(Person X, Food Y):- CanUse(Person X, Tool Z), UsedForCook(Tool Z, Food Y);

- If Person X can use Tool Z which is used for cooking Food Y, then Person X can cook Food Y.
- 2. CanCook(Person X, Food Y):- Master(Person X, Skill Z), RequiredForCooking(Skill Z, Food Y);
- If Person X has mastered Skill Z which is required for cooking Food Y, then Person X can cook Food Y.

Conclusion: CanDrive(Person X, Vehicle Y) Rules:

1. CanDrive(Person X, Vehicle Y):- Have(Person X, Age Z1), RequireMinimumAge(Vehicle Y, Age Z2), BiggerThan(Age Z1, Age Z2);

If Person X has Age Z1 and the minimum age requirement for driving Vehicle Y is Age Z2, Age Z1 is bigger than Age Z2, then Person X can drive Vehicle Y.

2. CanDrive(Person X, Vehicle Y):- Obtain(Person X, Authorization Z), RequiredForDriving(Authorization Z, Vehicle Y);

If Person X have obtained a specific Authorization Z and Authorization Z is required for driving Vehicle Y, then Person X can drive Vehicle Y.

Domain	Rule Description
Object Affordance	The rules should describe object affordance based on its property (such as height, age, price) and requirement (such as required skill, source, tool).
Object Accessibility	The rules should describe object accessibility based on its physical condition, spatial and temporal restriction.
Object Interaction	The rules should describe object interaction based on its physical, spatial or temporal properties (such as speed, hardness, density, height, time period).
Object Location Person's Need	The rules should describe the location information of an object. The rules should describe person's need to take an action over the object.

Table 7: Prompts for rule generation in different domains.

Prompt for Rule Filtering

True or False? Please predict whether the input rule is accurate or not according to commonsense knowledge in realistic scenarios, and also explain why.

Examples: Input: If Person X has an Age Z1 and Vehicle Y requires an Age above Z2 for driving, with ...

Output: True. Because Person X has achieved the ..

Input: If Person X was born in Season Z and Plant Y blooms in the same Season Z, then Person X can access Plant Y. Output: False. Because a person's birth season and a plant's blooming season has no logical connection.

Input: {candidate rule} Output:



]
nstructions (click to expand) Conclusion:	
\${conclusion}	
this HIT you will be provided with a Premise and a Conclusion. Please read the Premise and Conclusion carefully, and answer the	questions below.
A Premise is a statement describing the facts and relationships of multiple	4
objects. No	,
For example, "Person X is currently situated in Region Z, and Technology Y is	
prohibited in Region Z." is a Premise, where "Person X", "Technology Y" and "Region The Premise is an unreadable expression or has an unclear meaning.	
z are objects.	
A Conclusion is a statement <u>between two objects</u> , mainly describing the <u>ability of</u> Question 2: Is the Conclusion a readable and clear expression?	
objects to do sth or the location of objects. No	
Por example, "Person X can not employ rechnology Y." is a Conclusion, where	
The Concussion is an unreason of has an unreason of has an unreason of his set unreason of has an unreason of his set unreason	
Ir job is to answer Yes or No to THREE questions about the provided Premise d conclusion. These three questions can be categorized into TWO types. well?" logically correct, with very high probability?	clusion will happen
 Ir job is to answer Yes or No to THREE questions about the provided Premise Conclusion. These three questions can be categorized into TWO types. Type I (Readable Expression): Is the Premise/Conclusion a readable and clear expression? Yes: The Premise/Conclusion is a readable expression and has a clear meaning without ambiguity. For example, "Person X can not employ Technology Y." is a readable and clear expression. Yes: The Premise/Conclusion is a readable expression. 	clusion will happen premise to conclusi atement "If Person X ially correct, since " n whether Person X
 ur job is to answer Yes or No to THREE questions about the provided Premise d Conclusion. These three questions can be categorized into TWO types. Type I (Readable Expression): Is the Premise/Conclusion a readable and clear expression? Yes: The Premise/Conclusion is a readable expression and has a clear meaning without ambiguity. For example, "Person X can not employ Technology Y." is a readable and clear expression. No: The Premise/Conclusion is an uncedable expression or has an unclear meaning for example, "Derson X can not employ Technology Y." is a neadable and clear expression. No: The Premise/Conclusion is an uncedable expression or has an unclear meaning for example, "Derson X can not employ Technology Y." is a neadable and clear expression or has an unclear means the ability to drive" and we do not factor in have a car. No 	clusion will happen a premise to conclusio atement "If Person X i cally correct, since "o n whether Person X
 ur job is to answer Yes or No to THREE questions about the provided Premise d Conclusion. These three questions can be categorized into TWO types. Type I (Readable Expression): is the Premise/Conclusion a readable and clear expression? Yes: The Premise/Conclusion is a <i>readable expression</i> and has a <i>clear meaning without combiguity</i>. For example, "Person X can not employ Technology Y. is a readable and clear expression or has an <i>unclear meaning</i>. For example, "Technology Y is determined in Region Z." is not a readable and clear statement. Instead, "Technology Y is deployed/invented in Region Z." is not a readable and clear statement. Instead, "Technology Y is deployed/invented in Region Z." is not a readable and clear statement. 	clusion will happen a premise to conclusio attement "If Person X i ally correct, since "c n whether Person X
 Ir job is to answer Yes or No to THREE questions about the provided Premise Conclusion. These three questions can be categorized into TWO types. Type I (Readable Expression): Is the Premise/Conclusion a readable and clear expression? Yes: The Premise/Conclusion is a readable expression and has a clear meaning without ambiguity. For example, "Person X can not employ Technology Y" is a readable and clear expression or has an unclear meaning. For example, "Technology Y is deeployed/invented in Region Z." is a readable and clear extement. Instead, "Technology Y is deeployed/invented in Region Z." is a readable and clear extement. Instead, "Technology Y is deeployed/invented in Region Z." is a readable and clear expression. No: The Premise/Conclusion is an unreadable expression or has an unclear meaning. For example, "Technology Y is deeployed/invented in Region Z." is a readable and clear expression. Yuse III (Gueially Correct): Is the statement if the Premise happens, then the premise happens. The premise will be unlikely to lead to the Conclusion. The given Premise is insufficient or determine the Conclusion. 	clusion will happen premise to conclusi tament "If Person X i tally correct, since ", n whether Person X
 Ir job is to answer Yes or No to THREE questions about the provided Premise Conclusion. These three questions can be categorized into TWO types. Type I (Readable Expression): Is the Premise/Conclusion a readable and clear expression? Yes: The Premise/Conclusion is a readable expression and has a clear meaning without ambiguity. For example, "Person X can not employ Technology Y" is a readable and clear expression. No: The Premise/Conclusion is a unreadable expression or has an unclear meaning. For example, "Technology Y is deployed/invented in Region Z." is a readable and clear expression. Type II (Logically Correct): Is the statement. If the Premise happens, then the Conclusion. 	clusion will happen premise to conclusi tement "If Person X i tally correct, since "e n whether Person X irrelevant or contradictory t
 Ir job is to answer Yes or No to THREE questions about the provided Premise d Conclusion. These three questions can be categorized into TWO types. Type I (Readable Expression): Is the Premise/Conclusion a readable and clear expression? Yes: The Premise/Conclusion is a readable expression and has a clear meaning without ambiguity. For example, "Person X can not employ Technology Y." is a readable and clear expression. No: The Premise/Conclusion is an uncedable expression or has an unclear meaning. For example, "Technology Y is determined in Region Z." is not a readable and clear expression. No: The Premise/Conclusion is an uncedable expression or has an unclear meaning. For example, "Technology Y is determined in Region Z." is not a readable and clear expression. Type II (Logically Correct): Is the statement "If the Premise happens, then the Conclusion will happen as well." logically correct, with very high probability? Yes: "Ithe Premise happens, then the Conclusion is very likely to happen. 	clusion will happen premise to conclusi tement "If Person X tally correct, since " n whether Person X
 ur job is to answer Yes or No to THREE questions about the provided Premise do Conclusion. These three questions can be categorized into TWO types. Type I (Readable Expression): Is the Premise/Conclusion a readable and clear expression? Yes: The Premise/Conclusion is a <i>readable expression</i> and has a <i>clear meaning without ambiguity</i>. For example, "Person X can not employ Technology Y." is a readable and clear expression. No: The Premise/Conclusion is an <i>uncedable expression</i> or has an <i>unclear meaning</i>. For example, "Technology Y is determined in Region Z." is a readable and clear expression. Type II (Logically Correct): Is the statement. Instead, "Technology Y is deployed/invented in Region Z." is a readable and clear expression. Type II (Logically Correct): Is the statement "If the Premise happens, then the Conclusion will happen as well." logically correct, with very high probability? Yes: If the Premise will be <i>unlikely</i> to lead to the Conclusion. The given Premise is <i>insufficient</i> or determine the Conclusion. The given Premise is <i>insufficient</i> or determine the Conclusion. No: The Premise will be <i>unlikely</i> to lead to the Conclusion. The given Premise is <i>insufficient</i> or determine the Conclusion. No: The Premise will be <i>unlikely</i> to lead to the Conclusion is any they to happen. No: The Premise will be <i>unlikely</i> to lead to the Conclusion. The given Premise is <i>insufficient</i> or determine the Conclusion. 	clusion will happen premise to conclusi tatement "If Person X ally correct, since " n whether Person X
 ur job is to answer Yes or No to THREE questions about the provided Premise d Conclusion. These three questions can be categorized into TWO types. Type I (Readable Expression): is the Premise/Conclusion a readable and clear expression? Yes: The Premise/Conclusion is a <i>readable expression</i> and has a <i>clear meaning without ambiguity</i>. For example, "Person X can not employ Technology Y." is a readable and clear expression. No: The Premise/Conclusion is an <i>unreadable expression</i> or has an <i>unclear meaning</i>. For example, "Technology Y is deelrmined in Region Z." is not a readable and clear expression. No: The Premise/Conclusion is an <i>unreadable expression</i> or has an <i>unclear meaning</i>. For example, "Technology Y is deelrmined in Region Z." is not a readable and clear expression. Type II (Logically Correct): Is the statement. Instead, "Technology Y is deployed/invented in Region Z." is a readable and clear expression. Yype II (Logically Correct): Is the statement "If the Premise happens, then the Conclusion will happen as well." logically correct, with very high probability? Yes: If the Premise happens, then the Conclusion is <i>very likely</i> to happen. No: The Premise will be <i>unlikely</i> to lead to the Conclusion. The given Premise is insufficient or <i>irrelevant</i> or contradictory to determine the Conclusion. 	clusion will happen premise to conclusi tement "If Person X ally correct, since " n whether Person X
 ur job is to answer Yes or No to THREE questions about the provided Premise d Conclusion. These three questions can be categorized into TWO types. Type I (Readable Expression): is the Premise/Conclusion a readable and clear expression? Yes: The Premise/Conclusion is a <i>readable expression</i> and has a <i>clear meaning</i>. For example, "Person X can not employ Technology Y." is a readable and clear expression. No: The Premise/Conclusion is an <i>unreadable expression</i> or has an <i>unclear meaning</i>. For example, "Technology Y is determined in Region Z." is not a readable and clear expression. No: The Premise/Conclusion is an <i>unreadable expression</i> or has an <i>unclear meaning</i>. For example, "Technology Y is deployed/invented in Region Z." is not a readable and clear expression. Type II (Logically Correct): Is the statement. Instead, "Technology Y is deployed/invented in Region Z." is a readable and clear expression. Type II (Logically Correct): Is the statement. "If the Premise happens, then the Conclusion will happen as well." logically correct, with very high probability? Yes: If the Premise happens, then the Conclusion is <i>very likely</i> to happen. No: The Premise will be unlikely to lead to the Conclusion. The given Premise is <i>insufficient or irrelevant or contradictory</i> to determine the Conclusion. The given Premise is <i>insufficient or irrelevant or contradictory</i> to determine the Conclusion. If Will Note that we only focus on the direct logical connection from 	clusion will happen premise to conclusi tement "If Person X tally correct, since " n whether Person X
 ur job is to answer Yes or No to THREE questions about the provided Premise d Conclusion. These three questions can be categorized into TWO types. Type I (Readable Expression): Is the Premise/Conclusion a readable and clear expression? Yes: The Premise/Conclusion is a <i>readable expression</i> and has a <i>clear meaning without ambiguity</i>. For example, "Person X can not employ Technology Y." is a readable and clear expression. No: The Premise/Conclusion is an <i>unreadable expression</i> or has an <i>unclear meaning</i>. For example, "Technology Y is determined in Region Z." is not a readable and clear expression. No: The Premise/Conclusion is an <i>unreadable expression</i> or has an <i>unclear meaning</i>. For example, "Technology Y is deployed/invented in Region Z." is a readable and clear expression. Type II (Logically Correct): Is the statement "If the Premise happens, then the Conclusion is <i>ury likely</i> to happen. No: The Premise happens, then the Conclusion is <i>ury likely</i> to happen. No: The Premise happens, then the Conclusion. The given Premise happens, then the Conclusion. Server likely to happen. No: The Premise happens, then the Conclusion. The given Premise happens, then the Conclusion. The given premise happens, then the Conclusion. I!!!!! Note that we only focus on the direct logical connection from premise to conclusion, without considering other potential situations. 	clusion will happen premise to conclusi terment "If Person X tally correct, since " n whether Person X
 ur job is to answer Yes or No to THREE questions about the provided Premise d Conclusion. These three questions can be categorized into TWO types. Type I (Readable Expression): Is the Premise/Conclusion a readable and clear expression? Yes: The Premise/Conclusion is a readable expression and has a clear meaning without ambiguity. For example, "Person X can not employ Technology Y." is a readable and clear expression. No: The Premise/Conclusion is an uncedable expression or has an unclear meaning. For example, "Technology Y is determined in Region Z." is not a readable and clear expression. No: The Premise/Conclusion is an uncedable expression or has an unclear meaning. For example, "Technology Y is determined in Region Z." is not a readable and clear expression. No: The Premise happens, then the Conclusion is very likely to happen. Type II (Logically Correct): Is the statement "If the Premise happens, then the Conclusion is very likely to happen. No: The Premise happens, then the Conclusion is very likely to happen. No: The Premise happens, then the Conclusion. The given Premise is insufficient or inrelevant or contradictory to determine the Conclusion. IIIII Note that we only focus on the direct logical connection from premise to conclusion, without considering other potential situations. For example, the statement "If Person X is over 18 years old, then Person X 	clusion will happen premise to conclus tement "If Person X ally correct, since ' n whether Person)
 Job is to answer Yes or No to THREE questions about the provided Premise Conclusion. These three questions can be categorized into TWO types. Type I (Readable Expression): is the Premise/Conclusion a readable and clear expression? Yes: The Premise/Conclusion is a readable expression and has a clear meaning without ambiguity. For example, "Person X can not employ Technology Y." is a readable and clear expression. No: The Premise/Conclusion is a unreadable expression or has an unclear meaning. For example, "Technology Y is determined in Region Z." is not a readable and clear expression. No: The Premise/Technology Y is determined in Region Z." is not a readable and clear expression. Type II (Logically Correct): Is the statement "If the Premise happens, then the Conclusion is unreadable and clear expression. No: The Premise Happens, then the Conclusion is very likely to happen. No: The Premise will be unlikely to lead to the Conclusion. The given Premise is insufficient or irrelevant or contradictory to determine the Conclusion. IIIII Note that we only focus on the direct logical connection from premise to conclusion, without considering other potential situations. For example, the statement "If Preson X is over 18 years old, then Person X is over 18 years old, then Person X is over 18 years old, then Person X is unclear, if you experienced any issues, or if you have any other feedback for us. 	clusion will happer premise to conclus tement "If Person X ally correct, since n whether Person : irrelevant or contradictory
 If bits to answer Yes or No to THREE questions about the provided Premise Conclusion. These three questions can be categorized into TWO types. Type I (Readable Expression): Is the Premise/Conclusion a readable and clear expression? Yes: The Premise/Conclusion is a readable expression and has a clear meaning without ambiguity. For example, "Person X can not employ Technology Y: is a readable and clear expression or has an unclear meaning. For example, "Technology Y is determined in Region Z." is not a readable and clear expression. No: The Premise/Conclusion is an unreadable expression or has an unclear meaning. For example, "Technology Y is deeloyed/invented in Region Z." is a readable and clear expression. Type II (Logically Correct): Is the statement 'If the Premise happens, then the Conclusion will happen as well." logically correct, with very high probability? Yes: If the Premise happens, then the Conclusion is very likely to happen. No: The Premise happens, then the Conclusion is very likely to happen. No: The Premise happens, then the Conclusion. The given Premise to fundition of the formise to conclusion, without considering other potential situations. For example, the statement "If the Premise to conclusion, without considering other potential situations. For example, the statement Tif years old, then Person X can drive the car." is considered logically correct, can drive the premise to conclusion, without considering other potential situations. For example, the statement "If Person X is over 18 years old, then Person X can drive the car." is considered logically correct, can drive the readule statement. The given Premise to conclusion, without considering other potential situations. For example, the statement "If the premise to conclusion, without considering other potential situations. For example, the statement "If person X is over 18 years old, then Person X can drive the car." is con	clusion will happer premise to conclus tement "If Person 3 ally correct, since n whether Person

Figure 11: AMT template for human verification of primitive rules.

A.6 Human Verification Templates and Rates

851

855

859

Before human verification, we first craft a qualification task to select AMT annotators from all English-speaking countries (US, UK, New Zealand, Australia, Canada). The prospective workers are presented with three representative test cases and need to predict whether the premise and conclusion are clearly readable, and if the premise logically 856 entails the conclusion. Only those workers correctly passing all the test cases are recruited. The detailed template for human verification is shown

as Figure 11. This template is also used for get-860 ting human performance in rule probing analysis, 861 wherein a separate cohort of workers is qualified for 862 manual rule probing. Besides, the overall rates of 863 rule acceptance in different domains during human 864 verification are listed Table 9. 865

866

867

868

869

B **Rule Probing**

Rule Probing Templates B.1

Table 10 lists five different templates for unbiased rule probing.

	Affordance	Accessibility	Interaction	Location	Person's Need
Yield Rate	48.09	37.28	52.81	53.74	49.45

Table 9: The rule yield rates (%) of human verification.

	Template	Label
1	True or False? Please predict whether the input rule is very likely to be true.	True/False
2	Right or Wrong? Please predict whether the input rule is valid and correct.	Right/Wrong
3	Yes or No? Please predict whether the premise entails the conclusion.	Yes/No
4	Premise:, Conclusion: Does premise en- tail conclusion? Please answer Yes or No.	Yes/No
5	Given the observations, can we draw the conclusion? Please answer Yes or No.	Yes/No

Table 10: Five templates for rule probing.

B.2 Dual-side Rule Probing Setting

Table 11 illustrate a concrete example of dual-side rule probing.

If Premise, then Conclusion_original. If Premise, then Conclusion_flipped.	True/Right/Yes False/Wrong/No	
Example		
If Person X is allergic to Substance Z and Food Y contains Substance Z, then Person X cannot eat Food Y.	True/Right/Yes	
If Person X is allergic to Substance Z and Food Y contains Substance Z, then Person X can eat Food Y.	False/Wrong/No	

Table 11: A specific example of dual-side rule probing.

B.3 Rule Depths Probing

The analysis of GPT-series LLMs and human on different compositional depths is presented as Figure 12. "Depth=0" represents primitive rules and "Depth=1,2,3" denote compositional rules involving 1 to 3 backward chaining steps.

B.4 Illustrations of Rule Structures

Figure 13 displays several examples showcasing both symbolic and verbalized rules across different structure types.

B.5 Different CoT Prompts

Table 12 lists different prompts of three CoT strategies for rule probing.



Figure 12: Probing results of varied depths.

CoT strategy	Prompt
Answer- Explain	True or False? Please predict whether the input rule is very likely to be true, and also explain why.
Answer- Explain	True or False? Please predict whether the input rule is very likely to be true. Please first briefly explain your thought process in one sentence, and then give your answer.
Self- Consistency	True or False? Please predict whether the input rule is very likely to be true. Please first gener- ate three different sentences to respectively ex- plain your three thought processes briefly, and then based on the corresponding thought to give your answer. Finally, output the final answer ac- cording to majority voting.

Table 12: Three CoT prompts for rule probing.

886

887

888

890

891

892

893

894

895

896

897

898

899

900

901

902

903

904

B.6 Necessary Bias

As mentioned in Section 3.2, We investigate why GPT-4 significantly underperforms GPT-3.5-Turbo on transitive rules. Transitive rules typically describe a straightforward logical chain from variable X to Y, where GPT-3.5-Turbo and GPT-3.5-Instruct manage with greater ease. In contrast, we find that GPT-4 exhibits a "necessary bias" that tend to consider all necessary conditions reaching a conclusion, which avoids drawing a definite judgement. This conservative response is more pronounced in transitive rules, where GPT-4 more frequently responds with hesitations like "it does not necessarily mean" in its explanations. We present a probing example of a transitive rule by GPT-4 in Table 13, including its generated prediction, explanation and the corresponding label. We hypothesize that this conservative style may come from LLMs' preference alignment during Reinforcement Learning

870

872

- 879
- 88
- 882

383



Figure 13: Example rules of different structures.

905

907

with Human Feedback (Ouyang et al., 2022).

Input	True or False? Please predict whether the input rule is very likely to be true, and also explain why. Rule: If Person X has a job A that requires Skill Z, and Skill Z is required to cook Food Y, then Person X can cook Food Y.
Prediction	False
Explanation	Just because Person X has a job that requires Skill Z, it does not necessarily mean they can cook Food Y. They may have the skill, but cooking also requires other knowledge of recipes, techniques.
Label	True

Table 13: An example probing result of a transitive rules by GPT-4.

C Inference Engine

C.1 Illustration of Instruction Tuning

908 Figure 14 illustrate the pipeline of instruction tuning for rule distillation as an inference engine. Our 909 inference engine is trained for three tasks: conclu-910 sion generation, premise completion and premise 911 generation. The conclusion generation focuses on 912 creating a conclusion from a provided premise. For 913 premise completion, given a conclusion and its 914 partial premise, the inference engine must com-915 plete the remaining premise part to support the 916 conclusion. In premise generation, the engine is 917 918 tasked with creating premises of varying complexity based on a given conclusion, specifically gen-919 erating premises with one, two or even more facts. 920 We also provide an inference engine demo for flexible rule generation as shown in Figure 15. 922



Figure 14: Rule distillation for inference engine.

C.2 Implementation Details

We fine-tune Mistral-7b with our constructed instruction dataset with Quantization LoRA (QLoRA) method (Hu et al., 2021; Dettmers et al., 2023) as our inference engine. We set the learning rate to 7×10^{-5} , batch size to 8, gradient accumulation step to 16, and train the model 2 epochs. We apply QLoRA to all the linear layers of the model, including q_proj, k_proj, v_proj, o_proj, gate_proj, up_proj, down_proj, and lm_head. The α and r of the QLoRA method are both set to 16. 923

924

925

926

927

928

929

930

931

932

933

934

935

C.3 Prompting ChatGPT and GPT-4 for Three Tasks

As Step-2 of Sec. 2.2, we utilize two-shot prompts936to instruct ChatGPT and GPT-4 in simultaneously937generating symbolic and verbalized responses for938three tasks, as shown in Table 14, 15, 16.939

Prompt for Conclusion Generation

Given the premise, please generate its conclusion between X and Y in both Prolog and natural language. The conclusion in Prolog should have the same meaning with the conclusion in natural language. Each conclusion should contain only two variables X and Y without mentioning other variables, like A, B, C, Z. ### Examples: Premise: If Person X is allergic to Material Z and Furniture Y is made from Material Z. Conclusion: [Prolog]: CanNotHold(Person X, Furniture Y); [Natural Language]: Person X cannot hold Furniture Y. Premise: If Substance X has a Density Z1, the density of Substance Y is Density Z2, and Density Z1 is bigger than

Density Z2. Conclusion:

[Prolog]: CanSubmerge(Substance X, Substance Y); [Natural Language]: Substance X can submerge in Substance Y.

Premise: {premise} Conclusion:

Table 14: Prompt ChatGPT and GPT-4 for conclusion generation.

C.4 Evaluation Metrics

941

942

943

945

950

951

952

955

959

960

962

964 965

966

968

We detailed describe the metrics for evaluating our inference engine against ChatGPT and GPT-4 for the premise generation task.

- Accuracy: The premise is logically correct to infer the conclusion and follow the instruction regarding the specific number of facts.
- Diversity: The degree of variation among the three generated rules.
- Complexity: Assessed only for premise generation with more than 2 facts, measuring the fact number and the semantic difficulty.
- Abstractness: The variable types in premises are abstract to generalize to diverse instances. For example, the variable types "Region" and "Event" are abstrct while "New York" and "The FIFA World Cup" are specific entities with low abstractness.

C.5 LLM Evaluation Prompts

We prompt GPT-4 as the evaluator for rating the accuracy of conclusion generation and premise completion tasks, and the accuracy, diversity, complexity and abstractness of the premise generation task. We adopt one-shot prompts which are shown as Table 17 and Table 18 (with demonstrations omitted).

C.6 Human Evaluation Templates

For the human evaluation of premise generation accuracy, we qualify a new cohort of AMT annotators to pairwise compare two sets of generated premises in terms of logical consistency with the provided conclusion, alignment with common sense and the inclusion of an accurate number of facts. The detailed template for human evaluation is shown as Figure 16.

C.7 Downstream Reasoning Datasets

StrategyQA and SOCIAL IQA consist of crowdsourced questions involving reasoning of implicit logic. LINK comprises GPT-4 generated statements instantiated from abstract rules, including two subsets: head distribution statements and longtail knowledge statements. PIQA examines operational commonsense for achieving physical goals and CSQA2.0 features adversarial commonsense examples designed to mislead AI systems.

Inferential Rule Distillation Demo 齡

As an Inference Engine, I can conduct the following inferences on Commonsense Rules 💗

Conclusion Generation	~
Premise Completion	~
Premise Generation	~

Instruction

Please select an inference type	
Given the conclusion, please generate its premise.	~
Please select your preferred fact number in the premise	
2	~

⊘ Input

Premise:	
If Person X demands sleep time A and Person X has sleep time B, and B is longer than A.	
	11
Conclusion:	
Chairman X can not drive Vehicle Y.	
	-11
Submit	

Output

1: Premise: If Chairman X lacks License Z and Vehicle Y requires License Z.

2: Premise: If Chairman X lacks License Z2 and Vehicle Y requires License Z2.

3: Premise: If Chairman X is banned from Region Z and Vehicle Y is registered in Region Z.

Figure 15: Inference Engine Demo.

Prompt for Premise Completion

Given the conclusion and a part of its premise, please complete the remaining portion of the premise in both Prolog and natural language.

The remaining premise in Prolog should have the same meaning with the remaining premise in natural language. Each fact in the remaining premise should contain two variables, like X, Y, Z, Z1, Z2, A, B.

Examples: Conclusion: Person X cannot use Furniture Y. Partial Premise: If Person X is allergic to Material Z, Remaining Premise: [Prolog]: MadeFrom(Furniture Y, Material Z); [Natural Language]: Furniture Y is made from Material Z.

Conclusion: Substance X can submerge in Substance Y. Partial Premise: If Substance X has a Density Z1, the density of Substance Y is Density Z2, Remaining Premise: [Prolog]: BiggerThan(Density Z1, Density Z2); [Natural Language]: Density Z1 is bigger than Density Z2.

Conclusion: {conclusion} Partial Premise: {partial premise} Remaining Premise:

Table 15: Prompt ChatGPT and GPT-4 for premise completion.

Prompt for Premise Generation

Given the conclusion, please generate three different premises in both Prolog and natural language, ensuring that each Prolog premise conveys the same meaning as its natural language counterpart. Each premise should contain a specified number of facts, with each fact comprising only two variables, such as X, Y, Z, Z1, Z2, A, B. ### Examples: Fact number: 1 fact Conclusion: Person X has Skill Y. Three Premises: 1. [Prolog] Learned(Person X, Skill Y); [Natural Language] If Person X learned Skill Y. 2. [Prolog] Inherit(Person X, Skill Y); [Natural Language] If Person X inherits Skill Y. 3. [Prolog] Acquire(Person X, Skill Y); [Natural Language] If Person X acquires Skill Y. Fact number: more than 2 facts Conclusion: Person X cannot attend Event Y. Three Premises: 1. [Prolog] Have(Person X, Age Z1), RequireMinimumAge(Event Y, Age Z2), BiggerThan(Age Z2, Age Z1); [Natural Language] If Person X has Age Z1 and the minimum age requirement for attending Event Y is Age Z2, Age Z2 is bigger than Age Z1. 2. [Prolog] Have(Person X, Height Z1), RequireAbove(Event Y, Height Z2), SmallerThan(Height Z1, Height Z2); [Natural Language] If Person X has a Height Z1, and Event Y requires a Height above Z2, and Height Z1 is smaller than Height Z2. 3. [Prolog] HaveCriminalRecord(Person X, Event Z), ProhibitedBy(Event Z, Legislation A), EnforcedIn(Legislation A, Region B), HeldIn(Event Y, Region B); [Natural Language] If Person X has a criminal record for Event Z and Event Z is prohibited by Legislation A, which is enforced in Region B, and Event Y is held in Region B. Fact number: {fact num} Conclusion: {conclusion} Three Premises:

Table 16: Prompt ChatGPT and GPT-4 for premise generation.

Prompt for Rating the Accuracy of Conclusion Generation

You are a helpful scoring assistant.

Please read the provided premise carefully, and rate the accuracy of the candidate conclusion on a scale of 1 to 3:

- 1 (not accurate): The conclusion is clearly unsupported, irrelevant or contradictory to the provided premise.

- 2 (somewhat accurate): The conclusion, despite being supported by the premise, fails to state the definitive link between X and Y, or contradicts common sense, or lacks clarity.

- 3 (highly accurate): The conclusion correctly states the definitive link between X and Y, and is well-supported by the premise aligning with both established facts and common sense.

Please first output your rating based on your general knowledge and logical reasoning, and then provide a brief explaination with no more than 100 words.

[Provided Premise]: {premise} [Candidate Conclusion]: {conclusion} [Output]:

Prompt for Rating the Accuracy of Premise Completion

You are a helpful scoring assistant.

Please read the provided conclusion and its partial premise carefully, and rate the accuracy of its remaining premise in completing the provided premise to reach the conclusion, using a scale from 1 to 3:

- 1 (not accurate): The remaining premise fails to complete the provided premise for deducing the conclusion. It may be irrelevant or inconsistent with the provided premise or conclusion, or both.

- 2 (somewhat accurate): The remaining premise can somewhat supplement the provided premise but is not entirely sufficient for a conclusion inference. It may require additional information for comprehensive completion, or contradicts common sense, or lacks clarity.

- 3 (highly accurate): The remaining premise, combined with the provided partial premise, can correctly lead to the given conclusion, and also aligns well with common sense.

Please first output your rating based on your general knowledge and logical reasoning, and then provide a brief explaination with no more than 100 words.

[Conclusion]: {conclusion} [Partial Premise]: {partial premise} [Remaining Premise]: {rest premise} [Output]:

Prompt for Rating the Accuracy of Premise Generation

You are a helpful scoring assistant.

Please carefully read the provided conclusion along with the specified number of facts, and rate the accuracy of candidate premise in both reaching the conclusion and containing the correct number of facts, using a scale from 1 to 3:

- 1 (not accurate): The premise is logically incorrect, irrelevant or contradictory for deducing the conclusion, or it contains an incorrect number of facts.

- 2 (somewhat accurate): The premise can partially infer the conclusion but is not entirely sufficient. It may require additional information, or contradicts common sense, or lacks clarity.

- 3 (highly accurate): The premise can correctly lead to the given conclusion and aligns well with common sense, and precisely contains the specified number of facts.

Please first output your rating based on your general knowledge and logical reasoning, and then provide a brief explaination with no more than 100 words.

[Fact Number]: {fact num} [Conclusion]: {conclusion} [Premise]: {premise} [Output]:

Table 17: Prompts for rating the accuracy of three tasks.

Prompt for Rating the Diversity of Premise Generation

You are a helpful scoring assistant.

Please read the provided conclusion and multiple generated premises carefully, and rate the diversity of these premises using a scale from 1 to 3:

- 1 (low diversity): The premises show minimal variation, where all three premises largely repeat same perspectives with slight lexical changes.

- 2 (moderate diversity): The premises exhibit some degree of variation, with two out of the three premises sharing similar perspectives, expressions and fact numbers while the third presents different content.

- 3 (high diversity): The premises display a high level of diversity, where each premise presents distinct perspective from the others, or contains different fact numbers.

Please first output your rating, and then provide a brief explaination with no more than 50 words.

[Conclusion]: {conclusion} [Premise]: {premise₁}, {premise₂}, {premise₃} [Output]:

Prompt for Rating the Complexity of Premise Generation

You are a helpful scoring assistant.

Please carefully read the provided conclusion, and rate the complexity of candidate premise considering both the number of facts it comprises and its semantic difficulty, using a scale from 1 to 3:

- 1 (low complexity): The premise is straightforward, incorporating no more than 3 facts with clear and easy-tounderstand semantics and a simple logical structure.

- 2 (moderate complexity): The premise exhibits moderate complexity, which involves 4 facts and somewhat intricate semantics and a logical structure that require some thought to understand.

- 3 (high complexity): The premise is highly complex with more than 4 facts, which also includes complex semantics and an abstract logical structure, demanding a high level of understanding.

Please first output your rating based on your general knowledge and logical reasoning, and then provide a brief explaination with no more than 50 words.

[Conclusion]: {conclusion} [Premise]: {premise} [Output]:

Prompt for Rating the Abstractness of Premise Generation

You are a helpful scoring assistant.

Please carefully read the provided conclusion, and rate the abstractness of objects in the candidate premise considering how broadly they can generalize to various specific instances, using a scale from 1 to 3:

- 1 (low abstractness): The objects in the premise are concrete and specific, making direct and clear reference to particular instances or examples, which focus on specific people, places, or tangible entities, such as Swimmer, New York, or SUV.

- 2 (moderate abstractness): The objects in the premise are somewhat abstract, representing a balance between specific instances and general concepts. They may pertain to fine-grained categories of people, places, or things, such as Professionals, City, or Car.

- 3 (high abstractness): The objects in the premise are highly abstract, focusing on coarse-grained people, places or things that are far removed from concrete instances, such as Person, Region, or Event, or general properties like Age and Height.

Please first output your rating based on your general knowledge and logical reasoning, and then provide a brief explaination with no more than 50 words.

[Conclusion]: {conclusion} [Premise]: {premise} [Output]:

Table 18: Prompts for rating the diversity, complexity and abstractness of premise generation.

Please read the following Instructions and Examples very carefully, and refer back to them while annotating:

Instructions (click to expand)

In this HIT you will be provided with a conclusion and two groups of its candidate premises, along with the specified number of facts in the premises.

- A conclusion is a statement that typically involves two objects. It usually describes the objects' abilities, locations, or needs.
- For example, "Person X can not employ Technology Y." is a conclusion, where "Person X" and "Technology Y" are two objects.
- A Premise is a statement describing <u>facts about multiple objects</u>, aiming to provide evidence supporting the conclusion.
 - For example, "Person X is situated in Region Z, and Technology Y is prohibited in Region Z." is a plausible premise for above mentioned conclusion.
- The specified number of facts refers the number of facts that <u>each candidate</u> premise should comprise. Each fact should involve two objects

 For example, the above premise "Person X is situated in Region Z, and Technology Y is prohibited in Region Z." contains 2 facts.

Your job is to **compare** two groups of candidate premises, and **determine which** group is more accurate to reach the conclusion with specified number of facts. When assessing accuracy, please consider the following three criteria:

- Logical Consistency: The premises in this group are logically correct to lead to the given conclusion.
- Common Sense Alignment: The premises in this group align well with common sense.
- Fact Count Accuracy: The premises in this group precisely contain the specified number of facts – no more, no less.

Please choose one of the following three options: A, B, or Tie (cannot determine).

Examples (click to expand) Conclusion: Person X can not drive Vehicle Y. Specified Number of Facts: more than 2 facts. Premises: Group A: If Person X has Age Z1 and the minimum age requirement for driving Vehicle Y is Age Z2, and Age Z1 is smaller than Age Z2.If Person X has a height of Height Z1 and the minimum height requirement for driving Vehicle Y is Height Z2, and Height Z1 is smaller than Height Z2. If Person X is under the age of Z1 and Vehicle Y is manufactured by Organization A, which has set the age limit for driving the vehicle at Z2, and Age Z2 is greater than Age Z1. Group B: If Person X is of age Z1 and the minimum driving age for Vehicle Y is Z2, and Z1 is smaller than Z2. If Person X has a license of type Z1 and Vehicle Y requires a license of type Z2, and Z1 does not match Z2. If Person X has a medical condition Z and Vehicle Y is prohibited for individuals with medical condition Z. Question: Overall, which group of premises are more accurate to support the conclusion with correct number of facts and alignment with common sense? Answer: A Why? Because the premises in Group A and Group B can both accurately lead to the conclusion "Person X can not drive Vehicle Y" and make sense logically. The

issue lies with Group B's third premise, which contains only 2 facts inconsistent

with our specification of "more than 2 facts".

Figure 16: AMT template for human evaluation for premise generation accuracy.