

Self-Taught Agentic Long-Context Understanding

Anonymous ACL submission

Abstract

Answering complex, long-context questions remains a major challenge for large language models (LLMs) as it requires effective question clarifications and context retrieval. We propose Agentic Long-Context Understanding (AgenticLU), a framework designed to enhance an LLM’s understanding of such queries by integrating targeted self-clarification with contextual grounding within an agentic workflow. At the core of AgenticLU is Chain-of-Clarifications (CoC), where models refine their understanding through self-generated clarification questions and corresponding contextual groundings. By scaling inference as a tree search where each node represents a CoC step, we achieve 97.8% answer recall on NarrativeQA with a search depth of up to three and a branching factor of eight. To amortize the high cost of this search process to training, we leverage the preference pairs for each step obtained by the CoC workflow and perform two-stage model finetuning: (1) supervised finetuning to learn effective decomposition strategies, and (2) direct preference optimization to enhance reasoning quality. This enables AgenticLU models to generate clarifications and retrieve relevant context effectively and efficiently in a single inference pass. Extensive experiments across seven long-context tasks demonstrate that AgenticLU significantly outperforms state-of-the-art prompting methods and specialized long-context LLMs, achieving robust multi-hop reasoning while sustaining consistent performance as context length grows.

1 Introduction

Large language models have achieved notable milestones in natural language processing, demonstrating exceptional performance in tasks such as mathematical reasoning, code generation, and conversational understanding (OpenAI, 2023; DeepSeek-AI, 2025). However, effectively comprehending and utilizing long-context inputs remains a major

challenge. Complex queries often require models to retrieve multiple relevant pieces of information from extensive contexts and synthesize them coherently. While recent advancements have extended context windows to 128K and even 2M tokens (Dubey et al., 2024; Touvron et al., 2023; Reid et al., 2024), these models still struggle to fully integrate and reason over large-scale contextual information. Recent studies (Liu et al., 2024; Gao et al., 2024) highlight a fundamental challenge in long-context understanding: the disparity between a model’s nominal context size—the theoretical maximum input length—and its effective context window, the portion of the input the model actively utilizes for reasoning. This gap significantly impacts the understanding performance, limiting the model’s ability to fully comprehend and integrate long-context information.

We introduce a novel framework AgenticLU to enhance long-context comprehension in LLMs. As illustrated in fig. 1, the core of AgenticLU is **Chain-of-Clarifications** (CoC), a process where models enhance their understanding by generating clarification questions, retrieving relevant information from the long context and answering their own clarification questions based on the gathered evidence. Rather than relying on a direct response, CoC helps models refine their reasoning iteratively, resolving uncertainties along the way. We structure the framework into the following two stages.

CoC Path Construction. To collect reliable CoC understanding path, we structure data collection as a tree search, where each CoC step represents a node. We leverage extended inference time to determine the effective clarification questions to ask and the relevant evidence to retrieve. With a search depth of three and a branching factor of eight, AgenticLU successfully retrieves 97.8% of the correct answers in NarrativeQA (Kočíský et al., 2018), demonstrating its capability to tackle com-




Figure 1: **Overview of the AgenticLU pipeline:** The model iteratively refines its understanding of long-context inputs through an agentic workflow. At each step, it raises self-clarifications, retrieves relevant context via the pointback mechanism, and updates its reasoning trace. The framework integrates CoC Path Construction to generate diverse reasoning paths, followed by two-stage fine-tuning (SFT and DPO) to enhance long-context understanding.

plex questions that require multi-step reasoning over long-context inputs.

CoC Path Distillation. Once the dataset is collected from the tree-search process, we train the model to generate effective clarifications and contextual groundings in a single pass, eliminating the need for scaling at inference time. This is achieved by distilling these collected paths into LLMs through supervised finetuning (SFT) and direct preference optimization (DPO) (Rafailov et al., 2024), effectively amortizing the computational cost from inference to training.

Our method AgenticLU significantly improves model’s long-context understanding capabilities without relying on laborious human annotations or stronger teacher models for data generation. Instead, the base model’s self-generated CoC paths enables it to teach itself to process long-context inputs more effectively. This approach harnesses the model’s inherent long-context capabilities—previously only accessible through an additional LLM agent—allowing it to independently refine its reasoning and retrieval processes. Empirically, we demonstrate that AgenticLU consistently boosts performance across a set of question-answering tasks up to 128K tokens, outperforming both prompting-based approaches and other long-context-finetuned LLMs. By integrating self-clarification and context grounding in an agentic manner, we take a step further toward enabling LLMs to comprehend long contexts.

2 Related Work

Challenges in Long Context Understanding

LLMs struggle with long contexts despite supporting up to 2M tokens (Dubey et al., 2024; Reid et al., 2024). The “lost-in-the-middle” effect (Liu et al., 2024) and degraded performance on long-range tasks (Li et al., 2023) highlight these issues. To address this, ProLong (Gao et al., 2024) fine-tunes base models on a large, carefully curated long-context corpus. While this approach improves performance on long-range tasks, it comes at a significant cost, requiring training with an additional 40B tokens and long-input sequences.

Inference-time Scaling for Long-Context

The Self-Taught Reasoner (STaR) framework (Zelikman et al., 2022) iteratively generates rationales to refine reasoning, with models evaluating answers and finetuning on correct reasoning paths. Wang et al. (2024b) introduced Model-induced Process Supervision (MiPS), automating verifier training by generating multiple completions and assessing accuracy, boosting PaLM 2’s performance on math and coding tasks. Li et al. (2024) proposed an inference scaling pipeline for long-context tasks using Bayes Risk-based sampling and fine-tuning, though their evaluation is limited to shorter contexts (10K tokens) compared to ours (128K tokens).

Agentic Workflow for Long-Context

Agentic workflows (Yao et al., 2022) enable LLMs to autonomously manage tasks by generating internal plans and refining outputs iteratively. The Lon-

gRAG framework (Zhao et al., 2024b) enables an LLM and an RAG module to collaborate on long-context tasks by breaking down the input into smaller segments, processing them individually, and integrating the results to form a coherent output. Chain-of-Agents (CoA) (Zhang et al., 2024b) tackles long-context tasks through decomposition and multi-agent collaboration. In CoA, the input text is divided into segments, each handled by a worker agent that processes its assigned portion and communicates its findings to the next agent in the sequence. Unlike these, our approach employs a single LLM that orchestrates its own reasoning and retrieval without relying on multiple components. By dynamically structuring its process and iteratively refining long-context information, our model reduces complexity while maintaining efficiency.

3 The Context Size Gap

State-of-the-art LLMs have made strong claims about their context lengths, supporting hundreds of thousands of input tokens. However, recent studies (Gao et al., 2024; Yen et al., 2024; Shang et al., 2024) have shown that the *effective* context size of an LLM (the length over which it can reliably perform tasks such as information retrieval and complex reasoning) often diverges from its claimed, or *nominal*, context length.

To illustrate this gap, we evaluate Llama3.1-8B-Instruct, which supports a 128K-token context, on the HotPotQA dataset to test multi-hop QA performance at various input lengths (8K, 16K, 32K, 64K, and 128K). We artificially expand the input by adding irrelevant context and measure the accuracy of its answers using GPT-4o as a judge. As shown in fig. 2, The model’s performance degrades substantially as increasing context length, demonstrating the discrepancy between nominal and effective context sizes.

While expanding nominal context capacity is undoubtedly important, we argue that it is not sufficient for solving all long-context problems. By analogy with computer memory, simply having more capacity does not guarantee efficient or accurate computation; one must also manage the “loading” of relevant information in and out of this memory. Therefore, we propose an agentic workflow aimed at helping LLMs process and interpret extended contexts more intelligently.




Figure 2: **Effective context size is smaller than nominal context size.** Performance of Llama3.1-8B-Instruct (advertised 128K-token context) on the HotPotQA dataset drops sharply as input length increases (8K, 16K, 32K, 64K, 128K), illustrating the gap between nominal and effective context capacities.

4 Chain-of-Clarifications Workflow

Our approach centers on enhancing long-context comprehension through an iterative, self-refining process that blends inference-time scaling with agentic reasoning. We coin this agentic workflow Chain-of-Clarifications (CoC). In this section, we detail its key components, including the self-clarification process and the pointback mechanism, as illustrated in fig. 1.

Our proposed CoC framework is designed to mitigate the gap between nominal and effective context sizes in large language models. Rather than processing the entire long context and potentially multi-hop questions in a single pass, our methodology decomposes the task into a sequence of targeted sub-tasks. At each CoC step, the model autonomously:

- **Generates clarifying questions** by identifying areas of the long input that require further elaboration or are prone to misinterpretation.
- **Pointbacks to relevant context** by using a pointback mechanism that highlights critical segments of the context by naming the index of relevant paragraphs. In the data collection phase, this is done by iteratively querying the LLM about the relevance of each paragraph with respect to the question. After training, the model is finetuned to generate the related paragraph indexes directly in a single pass.
- **Answers clarifying questions** by integrating highlighted context into consideration to build a more accurate and contextually grounded understanding of the long document.

- **Answers the original question** by combining all newly gathered clarifications, the model attempts to generate a valid answer to the original question.

It is important to note a key distinction between CoC path generation during data collection and the actual task deployment of the agentic workflow. In the data generation phase, we prompt the LLM to iteratively process each chunk of input text along with its self-generated clarifying questions, ensuring accurate retrieval of relevant context. During training, rather than relying on repeated inference calls, we finetune the model to directly generate the indexes of relevant paragraphs using pointback examples, effectively amortizing the computational cost into training. This enables the model to internalize the retrieval process, allowing it to dynamically synthesize relevant clarifications and contextual references at inference time without requiring extensive additional prompting.

5 Data Generation & Model Training

Dataset We use the NarrativeQA (Kočíský et al., 2018) dataset to facilitate long-context QA and generate agentic workflow traces with 14.7K QA pairs in the training set. NarrativeQA is designed for reading comprehension over narrative texts, such as books and movie scripts, where each example includes a full story and a set of corresponding QA pairs. This dataset emphasizes deeper reasoning and long-context understanding, as many questions require synthesizing information from multiple parts of the narrative rather than focusing solely on particular local context. Its relatively long passages make NarrativeQA particularly suitable for testing and refining agentic reasoning in large language models, as the answers often depend on weaving together details spanning the entire text.

Base Model Our base model is *Llama3.1-8B-Instruct* (Dubey et al., 2024), an 8-billion-parameter instruction-tuned Llama model. This model is built on the same transformer architecture as Llama3, but with additional fine-tuning data to improve its performance on multi-turn dialogue and instruction-following tasks.

5.1 CoC Path Construction

We employ a test-time scaling approach to generate CoC paths. For each question, we construct a tree of search paths where each node represents a distinct clarification question posed by the LLM.

Table 1: Statistics of the generated traces dataset used in finetuning derived from NarrativeQA. We left out 11.9K traces for validation.

Data	#
Num of Traces	107,550
Avg Context Length	67,812
Avg Chosen Response Length	165
Avg Rejected Response Length	164
Total Generation Tokens	17M

In our experiments, we use a branching factor of 8 at each depth and select the most promising trace based on an evaluation score that combines:

- **Semantic similarity**, measured by the RougeL (Lin, 2004) score relative to the ground truth.
- **Discrete correctness**, evaluated by a binary verification using GPT4o-mini.

In the data construction process, the relevant context is found by iteratively querying the LLM about the relevance of all chunked passages. Here we use 512 as the chunk size. This process is compute-intensive but only happens in data collection. After the training, the LLM will directly generate the paragraph numbers of the relevant context as shown in the lower right of fig. 1.

For most long-context tasks, a single clarification question suffices because the required reasoning is not highly complex. 92% of the questions in our experiments are resolved correctly with just one round of clarification. More challenging tasks may require multiple rounds of clarification: two rounds resolve 53% of the remaining 8%, and three rounds resolve 35% of the remaining 4%. Because of the exponentially increasing cost—and given that 97.4% of the training questions are already solved—we limit the maximum depth of our inference scaling to 3.

The statistics of the collected dataset are shown in table 1. The total number of conditional generation tokens that the LLM trained on is 17M tokens, with input that has an average length of 67K and a max length of 128K tokens.

5.2 CoC Path Distillation

We employ a two-stage finetuning recipe: Supervised Fine-Tuning (SFT) followed by Direct Preference Optimization (DPO) (Rafailov et al., 2024), to convert our base model into a long-context under-

standing agent. The dataset statistics is described in table 1, with input length up to 128K tokens.

Supervised Fine-Tuning In the first phase, we finetune *Llama3.1-8B-Instruct* using the generated CoC paths. Each training example includes (1) the full context from NarrativeQA, (2) the question, and (3) the step-by-step reasoning trace leading to the final answer. By exposing the model to these traces, we encourage it to internalize multi-step reasoning strategies and context grounding for the long-context inputs. The SFT stage uses a standard cross-entropy loss on the next-token prediction task, ensuring the model learns how to produce consistent and complete reasoning sequences.

Direct Preference Optimization In the second phase, we apply Direct Preference Optimization to further refine the model’s output quality. To create preference pairs, we sample incorrect workflow traces as negative examples with using GPT4o-mini as the judge for answer correctness from the test-time scaling. DPO explicitly optimizes the model to generate higher-ranked responses more frequently, thus aligning the agent’s outputs with desirable characteristics, such as clarity, correctness, and coherence. This stage ensures that even among valid reasoning paths, the model learns to prioritize the most instructive reasoning.

The details for the two-phase training are listed in appendix A.

6 Evaluation

In this section, we assess our method AgenticLU using a suite of evaluation tasks drawn from the HELMET long-context benchmark (Yen et al., 2024). Our experiments focus on testing models’ ability to retain, process, and reason over extended contexts ranging from 8K to 128K tokens.

6.1 Tasks and Metrics

We evaluate our models and baselines on the Helmet (Yen et al., 2024) long-context evaluation benchmark’s retrieval-augmented generation (RAG) and long-range QA (LongQA) tasks ranging from 8K, 16K, 32K, 64K, to 128K.

We use GPT-4o as the judge for answer correctness, with the prompt template shown in appendix E. We report accuracies for all datasets.

The RAG test suite includes: (1) **HotpotQA** (Yang et al., 2018), a multi-hop reasoning dataset over Wikipedia; (2) **Natural Questions** (Kwiatkowski et al., 2019), real user queries

with Wikipedia-based short and long answers; (3) **TriviaQA** (Joshi et al., 2017), a large-scale trivia dataset with question-answer pairs linked to evidence documents; (4) **PopQA** (Mallen et al., 2022), a dataset testing model memorization with fact-based questions from popular culture.

The LongQA test suite includes: (1) **NarrativeQA** (Kočíský et al., 2018), a reading comprehension dataset with Wikipedia summaries and story-based Q&A; (2) **InfiniteBench QA** (Zhang et al., 2024a), a long-range QA benchmark requiring reasoning over extended contexts; (3) **InfiniteBench Multiple-Choice** (Zhang et al., 2024a), a multiple-choice variant of the previous evaluating reading comprehension over long documents.

For the four RAG tasks, each question is put alongside a set of relevant contexts, and the overall input length is increased by appending irrelevant context. Consequently, these tasks become strictly more difficult as the context window expands. In contrast, for the three LongQA tasks, the relevant context may not appear in the truncated input (the first 8K, 16K, or 128K tokens). Hence, performance might improve at longer input lengths simply because the necessary information becomes available only after including more tokens.

6.2 Baselines

We compare AgenticLU against a diverse set of strong baselines representing different approaches for handling long-context tasks. Our comparisons include two main categories.

Under prompting methods we consider techniques that require no additional model training. In particular, we evaluate (a) the chain-of-thought approach (Kojima et al., 2022), which encourages models to decompose complex questions into intermediate reasoning steps; (b) fact-and-reflection prompting (Zhao et al., 2024c), which iteratively verifies and refines factual claims to enhance consistency; (c) plan-and-solve prompting (Wang et al., 2023), where the model first outlines a high-level plan before sequentially executing it to address structured reasoning tasks; and (d) LongRAG (Zhao et al., 2024a) where a hybrid RAG system is used to retrieve relevant context to generate global summaries and local details ¹.

In the fine-tuning category, we focus on models

¹Note that LongRAG provided finetuned models as well. But the SFT-ed Llama3-8B only supports 8K context length. Thus we did not include it in our comparison.

Table 2: Performance difference of AgenticLU and its base, Llama3.1-8B-Instruct (δ =AgenticLU-8B minus Llama3.1-8B), on long context (the 128K tasks) and short-context benchmarks (6 regular tasks including ARC, GSM8K, and MMLU), the details of the short-context performance can be found in appendix B. Scores represent accuracy, with AgenticLU demonstrating significantly improved performance across long-context tasks with minimal effect on regular task performance.

Model	Short Avg	HotpotQA	Natural Questions	TriviaQA	PopQA	NarrativeQA	InfiniQA	InfiniChoice	Long Avg
Llama3.1-8B	62.3	40.0	56.1	80.6	56.1	38.0	48.0	55.0	53.4
AgenticLU (δ)	-0.6	+31.1	+21.7	+7.7	+9.4	+18.0	+2.0	+13.0	+14.7




Figure 3: **Main results on 7 long-context tasks across context lengths from 8K to 128K.** Our AgenticLU-8B (dotted orange) achieves significant improvements on *all* tasks over our base model Llama3.1-8B (solid orange). We also compare with the prompting methods (Step-by-Step, Plan-and-Solve, Fact-and-Reflect, LongRAG) and the state-of-the-art ProLong-8B model. AgenticLU-8B consistently maintains strong performance across most tasks and context lengths.

that have been specifically adapted for extended context data. For a substantial comparison, we employ ProLong-8B-512K (Gao et al., 2024)—a model based on the Llama3 8B architecture that has been further trained on an additional 40B tokens of long-context data.

6.3 Main Results

The performance of AgenticLU and baseline models is shown in fig. 3.

Self-clarification significantly improves multi-hop reasoning. AgenticLU-8B consistently surpasses other methods in HotpotQA. By iteratively refining its understanding, resolving ambigu-

ities, and verifying intermediate steps, the model achieves higher accuracy, particularly as context length increases.

Robust performance across diverse datasets.

Unlike baseline models, AgenticLU-8B maintains consistently strong performance across RAG and LongQA benchmarks, demonstrating its ability to adapt effectively to different long-context tasks.

Reduced performance degradation with longer contexts.

While most models experience significant accuracy drops as context length increases, AgenticLU-8B remains stable. Its self-clarification and pointback mechanisms effectively filter noise from irrelevant information, allowing the model to extract and prioritize essential evidence.

Fine-tuning vs. prompting trade-offs.

While structured prompting techniques like *plan-and-solve* improve short-context reasoning, they struggle with extreme context lengths (e.g., 128K tokens). In contrast, AgenticLU-8B, through targeted finetuning with self-clarification and pointback, maintains robust long-context reasoning without relying on complex prompting strategies. Although ProLong-8B, another finetuned model, achieves strong results, it comes with significantly higher training costs. AgenticLU-8B, by contrast, is more data-efficient and generalizes better to novel tasks, making it a more practical and effective solution for long-context reasoning.

Overall, these results underscore the effectiveness of AgenticLU-8B in tackling long-context understanding challenges. The integration of self-clarification plays a crucial role in improving grounding, reasoning, and comprehension in long-context settings.

6.4 Performance on Short-Context Tasks

To demonstrate that our fine-tuning process preserves the model’s general capabilities while enhancing long-context understanding, we evaluated the finetuned model on a diverse set of standard benchmarks. These include elementary and advanced reasoning tasks ARC Easy and ARC Challenge (Clark et al., 2018), mathematical problem-solving GSM8K (Cobbe et al., 2021), MathQA (Amini et al., 2019), and broad knowledge assessment MMLU (Hendrycks et al., 2021b,a), MMLU-Pro (Wang et al., 2024a).

We report the average performance across short-context tasks in table 2, and each individual task

Table 3: We evaluate the performance of adding additional self-clarification and contextual grounding rounds at inference time. The gain from self-clarification is close to optimal at the initial round.

Model	HotpotQA	NaturalQ	PopQA	TriviaQA	Avg
Llama-3.1-8B	40.0	56.1	56.1	80.6	58.2
AgenticLU-8B	71.1	77.8	65.5	88.3	75.7
(w/ 2 rounds)	71.1	76.7	67.2	91.7	76.7
(w/ 3 rounds)	75.5	78.8	68.3	91.1	78.4

result can be found in appendix B. We find that the short-context performance is well preserved, demonstrating that AgenticLU’s core reasoning and problem-solving abilities remain strong and are not compromised by the significant improvements to its long-context understanding powers.

7 Analyses & Ablation Studies

In this section, we take a closer look at how each part of our approach affects long-context understanding and retrieval. Specifically, we study three main questions: (1) Can the finetuned system benefit from multi-round CoC? (2) Does adding clarifications and pointing back to the original document help the model understand and utilize the context more accurately? (3) How much additional compute overhead does AgenticLU add to the process?

7.1 How many rounds of CoC are needed?

Setup. We add additional rounds of reasoning in the evaluation and see if the LLM can benefit from multi-rounds of reasoning at test-time.

Analysis. The results, presented in Table 3, indicate that additional rounds of agentic reasoning do provide performance improvements.

This suggests that while significant benefits of self-clarification are achieved in the first round, additional rounds still contribute to further improvements. One possible explanation is the nature of our dataset: approximately 92% of the questions are resolved within a single round of clarification. However, for the remaining cases, extended reasoning allows the model to refine its understanding, leading to measurable gains in performance with more clarification and reasoning.

7.2 Do Self-Clarifications and Pointback Help in Long-Context Understanding?

Setup. To evaluate the impact of each component in our agentic workflow, we compare the full AgenticLU-8B model against two variants:

Table 4: We test the agentic workflow with AgenticLU-8B when taking out the self-clarification steps and the contextual grounding (pointback) step. The tasks are with 128K context length.

Model	HotpotQA	NaturalQ	PopQA	TriviaQA	Avg
Llama-3.1-8B	40.0	56.1	56.1	80.6	58.2
AgenticLU-8B	71.1	77.8	65.5	88.3	75.7
(w/o Clarification)	57.8	56.7	55.5	78.3	62.1
(w/o Pointback)	53.3	59.4	52.7	83.3	62.2

Table 5: Performance Overhead Comparison between direct answering baseline and AgenticLU.

Metric	Baseline	AgenticLU
Runtime Overhead	100%	101.93%
Avg Tokens Generated in One Round	76.28	1205.38

one without the self-clarification step and another without the contextual grounding (*pointback*) step. We use the four RAG datasets with 128K context length as the evaluation benchmark, and compare the performance alongside the original model.

Analysis. Table 4 shows the results on four QA benchmarks with a 128K context length. Removing self-clarification leads to an absolute performance drop of at least 10 points across most tasks (e.g., from 71.1% to 57.8% on HotpotQA), confirming that the model benefits from clarifying its own uncertainties when the context is long. Meanwhile, omitting pointback yields degenerate results, indicating that pinpointing relevant information at each stage is crucial for long-context QA. Overall, these findings highlight the importance of both clarifications and context-grounding to maximize retrieval accuracy and robustness in lengthy documents.

7.3 How much additional compute cost does AgenticLU impose in generation?

Since additional generation steps are introduced in the QA process, we assess the overhead in inference time. Naïvely, long-context inference and multi-round conversations could significantly amplify compute costs. However, by leveraging prefix caching to store computed KV caches, the additional cost scales linearly with the number of newly generated tokens rather than exponentially.

To quantify this overhead, we conduct a runtime evaluation on 100 queries with a 128K context size. The results, summarized in table 5, demonstrate that the additional computational overhead remains minimal when using prefix caching.

8 Conclusion

In this work, we introduce Agentic Long-Context Understanding (AgenticLU), a framework designed to enhance large language models’ ability to process and reason over long-context inputs with self-generated data. By incorporating an agentic workflow (CoC) that dynamically refines model reasoning through self-clarifications and contextual grounding, AgenticLU significantly improves LLM’s long context understanding capabilities.

Through a combination of trace data collection and two-stage post-training, our approach enables models to autonomously explore multiple reasoning paths, distill the most effective clarification strategies, and improve their understanding of lengthy documents. Extensive evaluations on long-context benchmarks demonstrate that AgenticLU outperforms existing prompting techniques and finetuned baselines, maintaining strong performance across context lengths up to 128K tokens. Additionally, ablation studies confirm that self-clarification and pointback mechanisms play a crucial role in improving retrieval and reasoning over long-contexts.

Limitations

Despite its effectiveness in long-context reasoning, AgenticLU has notable limitations. One key drawback is its inability to autonomously determine when to stop multi-round reasoning. While additional rounds of self-clarification can improve performance, the model follows a fixed number of reasoning steps rather than dynamically assessing when further refinement is necessary. This can lead to inefficiencies, where the model either stops too early, missing potential improvements, or continues reasoning unnecessarily, expending computational resources without significant gains.

Developing a fully agentic mechanism remains an open challenge. Ideally, the model should assess its confidence in an intermediate response and decide whether further clarification is needed. Future work should explore approaches that enable AgenticLU to regulate its reasoning depth dynamically, optimizing both efficiency and performance.

References

Aida Amini, Saadia Gabriel, Peter Lin, Rik Koncel-Kedziorski, Yejin Choi, and Hannaneh Hajishirzi. 2019. [Mathqa: Towards interpretable math word](#)

591	problem solving with operation-based formalisms.	Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yu-	643
592	<i>Preprint</i> , arXiv:1905.13319.	taka Matsuo, and Yusuke Iwasawa. 2022. Large lan-	644
593	Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot,	guage models are zero-shot reasoners. <i>Advances in</i>	645
594	Ashish Sabharwal, Carissa Schoenick, and Oyvind	<i>neural information processing systems</i> , 35:22199–	646
595	Tafford. 2018. Think you have solved question an-	22213.	647
596	swering? try arc, the ai2 reasoning challenge. <i>ArXiv</i> ,	Tom Kwiatkowski, Jennimaria Palomaki, Olivia Red-	648
597	abs/1803.05457.	field, Michael Collins, Ankur Parikh, Chris Alberti,	649
598	Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian,	Danielle Epstein, Illia Polosukhin, Jacob Devlin, Ken-	650
599	Jacob Hilton, Reiichiro Nakano, Christopher Hesse,	ton Lee, et al. 2019. Natural questions: a benchmark	651
600	and John Schulman. 2021. Training verifiers to solve	for question answering research. <i>Transactions of the</i>	652
601	math word problems . <i>Preprint</i> , arXiv:2110.14168.	<i>Association for Computational Linguistics</i> , 7:453–	653
602	Tri Dao. 2023. Flashattention-2: Faster attention with	466.	654
603	better parallelism and work partitioning. <i>arXiv</i>	Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying	655
604	<i>preprint arXiv:2307.08691</i> .	Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E.	656
605	DeepSeek-AI. 2025. Deepseek-r1: Incentivizing rea-	Gonzalez, Hao Zhang, and Ion Stoica. 2023. Effi-	657
606	soning capability in llms via reinforcement learning .	cient memory management for large language model	658
607	<i>Preprint</i> , arXiv:2501.12948.	serving with pagedattention. In <i>Proceedings of the</i>	659
608	Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey,	<i>ACM SIGOPS 29th Symposium on Operating Systems</i>	660
609	Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman,	<i>Principles</i> .	661
610	Akhil Mathur, Alan Schelten, Amy Yang, Angela	Jiaqi Li, Mengmeng Wang, Zilong Zheng, and Muhan	662
611	Fan, et al. 2024. The llama 3 herd of models. <i>arXiv</i>	Zhang. 2023. Loogle: Can long-context language	663
612	<i>preprint arXiv:2407.21783</i> .	models understand long contexts? <i>arXiv preprint</i>	664
613	Tianyu Gao, Alexander Wettig, Howard Yen, and	<i>arXiv:2311.04939</i> .	665
614	Danqi Chen. 2024. How to train long-context	Siheng Li, Cheng Yang, Zesen Cheng, Lemao Liu,	666
615	language models (effectively). <i>arXiv preprint</i>	Mo Yu, Yujiu Yang, and Wai Lam. 2024. Large	667
616	<i>arXiv:2410.02660</i> .	language models can self-improve in long-context	668
617	Dan Hendrycks, Collin Burns, Steven Basart, Andrew	reasoning. <i>arXiv preprint arXiv:2411.08147</i> .	669
618	Critch, Jerry Li, Dawn Song, and Jacob Steinhardt.	Chin-Yew Lin. 2004. ROUGE: A package for auto-	670
619	2021a. Aligning ai with shared human values. <i>Pro-</i>	matic evaluation of summaries . In <i>Text Summariza-</i>	671
620	<i>ceedings of the International Conference on Learning</i>	<i>tation Branches Out</i> , pages 74–81, Barcelona, Spain.	672
621	<i>Representations (ICLR)</i> .	Association for Computational Linguistics.	673
622	Dan Hendrycks, Collin Burns, Steven Basart, Andy	Hao Liu, Matei Zaharia, and Pieter Abbeel. 2023.	674
623	Zou, Mantas Mazeika, Dawn Song, and Jacob Stein-	Ring attention with blockwise transformers for near-	675
624	hardt. 2021b. Measuring massive multitask language	infinite context. <i>arXiv preprint arXiv:2310.01889</i> .	676
625	understanding. <i>Proceedings of the International Con-</i>	Nelson F Liu, Kevin Lin, John Hewitt, Ashwin Paranjape,	677
626	<i>ference on Learning Representations (ICLR)</i> .	Michele Bevilacqua, Fabio Petroni, and Percy Liang. 2024. Lost in the middle: How language mod-	678
627	Jian Hu, Xibin Wu, Weixun Wang, Dehao Zhang,	els use long contexts. <i>Transactions of the Association</i>	679
628	Yu Cao, et al. 2024. Openrlhf: An easy-to-use, scal-	<i>for Computational Linguistics</i> , 12:157–173.	680
629	able and high-performance rlhf framework. <i>arXiv</i>	Alex Mallen, Akari Asai, Victor Zhong, Rajarshi Das,	681
630	<i>preprint arXiv:2405.11143</i> .	Hannaneh Hajishirzi, and Daniel Khashabi. 2022.	682
631	Mandar Joshi, Eunsol Choi, Daniel S. Weld, and Luke	When not to trust language models: Investigating	683
632	Zettlemoyer. 2017. Triviaqa: A large scale distantl-	effectiveness and limitations of parametric and non-	684
633	supervised challenge dataset for reading comprehen-	parametric memories. <i>arXiv preprint</i> .	685
634	sion. In <i>Proceedings of the 55th Annual Meeting of</i>	OpenAI. 2023. GPT-4 technical report . <i>Preprint</i> ,	686
635	<i>the Association for Computational Linguistics</i> , Van-	arXiv:2303.08774.	687
636	couver, Canada. Association for Computational Lin-	Rafael Rafailov, Archit Sharma, Eric Mitchell, Christo-	688
637	guistics.	pher D Manning, Stefano Ermon, and Chelsea Finn.	689
638	Tomáš Kočiský, Jonathan Schwarz, Phil Blunsom, Chris	2024. Direct preference optimization: Your language	690
639	Dyer, Karl Moritz Hermann, Gábor Melis, and Ed-	model is secretly a reward model. <i>Advances in Neu-</i>	691
640	ward Grefenstette. 2018. The NarrativeQA reading	<i>ral Information Processing Systems</i> , 36.	692
641	comprehension challenge . <i>Transactions of the Asso-</i>	Jeff Rasley, Samyam Rajbhandari, Olatunji Ruwase, and	693
642	<i>ciation for Computational Linguistics</i> , 6:317–328.	Yuxiong He. 2020. Deepspeed: System optimiza-	694
		tions enable training deep learning models with over	695
		100 billion parameters. In <i>Proceedings of the 26th</i>	696
			697

698	<i>ACM SIGKDD International Conference on Knowledge Discovery & Data Mining</i> , pages 3505–3506.	
699		
700	Machel Reid, Nikolay Savinov, Denis Teplyashin,	
701	Dmitry Lepikhin, Timothy Lillicrap, Jean-baptiste	
702	Alayrac, Radu Soricut, Angeliki Lazaridou, Orhan Fir-	
703	rat, Julian Schrittwieser, et al. 2024. Gemini 1.5: Un-	
704	locking multimodal understanding across millions of	
705	tokens of context. <i>arXiv preprint arXiv:2403.05530</i> .	
706	Jingbo Shang, Zai Zheng, Jiale Wei, Xiang Ying, Felix	
707	Tao, and Mindverse Team. 2024. Ai-native memory:	
708	A pathway from llms towards agi. <i>arXiv preprint</i>	
709	<i>arXiv:2406.18312</i> .	
710	Hugo Touvron, Louis Martin, Kevin Stone, Peter Al-	
711	bert, Amjad Almahairi, Yasmine Babaei, Nikolay	
712	Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti	
713	Bhosale, et al. 2023. Llama 2: Open founda-	
714	tion and fine-tuned chat models. <i>arXiv preprint</i>	
715	<i>arXiv:2307.09288</i> .	
716	Lei Wang, Wanyu Xu, Yihuai Lan, Zhiqiang Hu, Yunshi	
717	Lan, Roy Ka-Wei Lee, and Ee-Peng Lim. 2023. Plan-	
718	and-solve prompting: Improving zero-shot chain-of-	
719	thought reasoning by large language models. <i>arXiv</i>	
720	<i>preprint arXiv:2305.04091</i> .	
721	Yubo Wang, Xueguang Ma, Ge Zhang, Yuansheng Ni,	
722	Abhranil Chandra, Shiguang Guo, Weiming Ren,	
723	Aaran Arulraj, Xuan He, Ziyang Jiang, Tianle Li, Max	
724	Ku, Kai Wang, Alex Zhuang, Rongqi Fan, Xiang Yue,	
725	and Wenhui Chen. 2024a. <i>Mmlu-pro: A more robust</i>	
726	<i>and challenging multi-task language understanding</i>	
727	<i>benchmark</i> . <i>Preprint</i> , arXiv:2406.01574.	
728	Zihan Wang, Yunxuan Li, Yuexin Wu, Liangchen Luo,	
729	Le Hou, Hongkun Yu, and Jingbo Shang. 2024b.	
730	Multi-step problem solving through a verifier: An	
731	empirical analysis on model-induced process super-	
732	vision. <i>arXiv preprint arXiv:2402.02658</i> .	
733	Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio,	
734	William Cohen, Ruslan Salakhutdinov, and Christo-	
735	pher D. Manning. 2018. <i>HotpotQA: A dataset for</i>	
736	<i>diverse, explainable multi-hop question answering</i> .	
737	In <i>Proceedings of the 2018 Conference on Empirical</i>	
738	<i>Methods in Natural Language Processing</i> , pages	
739	2369–2380, Brussels, Belgium. Association for Com-	
740	putational Linguistics.	
741	Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak	
742	Shafraan, Karthik Narasimhan, and Yuan Cao. 2022.	
743	React: Synergizing reasoning and acting in language	
744	models. <i>arXiv preprint arXiv:2210.03629</i> .	
745	Howard Yen, Tianyu Gao, Minmin Hou, Ke Ding,	
746	Daniel Fleischer, Peter Izsak, Moshe Wasserblat, and	
747	Danqi Chen. 2024. Helmet: How to evaluate long-	
748	context language models effectively and thoroughly.	
749	<i>arXiv preprint arXiv:2410.02694</i> .	
750	Eric Zelikman, Yuhuai Wu, Jesse Mu, and Noah Good-	
751	man. 2022. Star: Bootstrapping reasoning with rea-	
752	soning. <i>Advances in Neural Information Processing</i>	
753	<i>Systems</i> , 35:15476–15488.	
	Xinrong Zhang, Yingfa Chen, Shengding Hu, Zihang	754
	Xu, Junhao Chen, Moo Hao, Xu Han, Zhen Thai,	755
	Shuo Wang, Zhiyuan Liu, and Maosong Sun. 2024a.	756
	<i>∞Bench: Extending long context evaluation beyond</i>	757
	<i>100K tokens</i> . In <i>Proceedings of the 62nd Annual</i>	758
	<i>Meeting of the Association for Computational Lin-</i>	759
	<i>guistics (Volume 1: Long Papers)</i> , pages 15262–	760
	15277, Bangkok, Thailand. Association for Compu-	761
	tational Linguistics.	762
	Yusen Zhang, Ruoxi Sun, Yanfei Chen, Tomas Pfister,	763
	Rui Zhang, and Serkan Ö Arik. 2024b. Chain of	764
	agents: Large language models collaborating on long-	765
	context tasks. <i>arXiv preprint arXiv:2406.02818</i> .	766
	Qingfei Zhao, Ruobing Wang, Yukuo Cen, Daren Zha,	767
	Shicheng Tan, Yuxiao Dong, and Jie Tang. 2024a.	768
	<i>LongRAG: A dual-perspective retrieval-augmented</i>	769
	<i>generation paradigm for long-context question an-</i>	770
	<i>swering</i> . In <i>Proceedings of the 2024 Conference on</i>	771
	<i>Empirical Methods in Natural Language Processing</i> ,	772
	pages 22600–22632, Miami, Florida, USA. Associa-	773
	tion for Computational Linguistics.	774
	Xiaowei Zhao, Yong Zhou, and Xiujuan Xu. 2024b.	775
	<i>Dual encoder: Exploiting the potential of syntac-</i>	776
	<i>tic and semantic for aspect sentiment triplet extrac-</i>	777
	<i>tion</i> . In <i>Proceedings of the 2024 Joint International</i>	778
	<i>Conference on Computational Linguistics, Language</i>	779
	<i>Resources and Evaluation (LREC-COLING 2024)</i> ,	780
	pages 5401–5413, Torino, Italia. ELRA and ICCL.	781
	Xinran Zhao, Hongming Zhang, Xiaoman Pan, Wenlin	782
	Yao, Dong Yu, Tongshuang Wu, and Jianshu Chen.	783
	2024c. <i>Fact-and-reflection (FaR) improves confi-</i>	784
	<i>dence calibration of large language models</i> . In <i>Find-</i>	785
	<i>ings of the Association for Computational Linguistics:</i>	786
	<i>ACL 2024</i> , pages 8702–8718, Bangkok, Thailand. As-	787
	sociation for Computational Linguistics.	788
	A Training Configurations	789
	We employed the DeepSpeed (Rasley et al., 2020)	790
	framework for distributed training across four GPU	791
	nodes, each equipped with four AMD MI250 GPUs.	792
	We used vLLM (Kwon et al., 2023) for inference.	793
	Our implementation builds upon OpenRLHF (Hu	794
	et al., 2024) for both SFT and DPO. Given the input	795
	sequence length of up to 128K tokens, we lever-	796
	aged FlashAttention-2 (Dao, 2023) alongside Ring	797
	Attention (Liu et al., 2023) to efficiently process	798
	extremely long sequences. The detailed hyperpa-	799
	rameters for SFT and DPO are provided in table 6	800
	and table 7.	801
	B Short Context Performance	802
	As shown in table 8, we evaluate the short-	803
	context performance across six tasks: ARC Easy,	804
	ARC Challenge, GSM8K, MathQA, MMLU, and	805
	MMLU Pro. AgenticLU performs on par with	806

Table 6: Hyperparameters for SFT.

Hyperparameter	Value
Learning Rate	5e-7
Learning Rate Schedule	Cosine Annealing
Optimizer	Adam
β_1	0.9
β_2	0.95
Training dtype	bf16
Batch Size	128
Max Length	131,072

Table 7: Hyperparameters for DPO.

Hyperparameter	Value
Learning Rate	5e-7
Learning Rate Schedule	Cosine Annealing
Optimizer	Adam
β_1	0.9
β_2	0.95
Training dtype	bf16
Batch Size	128
β	0.1
Max Length	131,072

the base model Llama3.1-8B-Instruct on short-context benchmarks, demonstrating that AgenticLU preserves the original short-context ability while greatly enhancing long-context performance.

C Detailed Results on Seven Benchmark Tasks

As shown in table 9, table 10, table 11, table 12, table 13, table 14 and table 15, we evaluate the long-context performance across seven tasks: HotpotQA, Natural Questions, TriviaQA, PopQA, NarrativeQA, InfiniteBench QA and InfiniteBench Multiple-Choice. AgenticLU provides significant improvement for all tasks, especially for those that require multi-hop reasoning such as HotPotQA.

D Chain-of-Clarifications Workflow

The input was first processed into chunks and grouped with paragraph tags. We list the example prompts used in AgenticLU workflow below. In training, we sampled 100 variations of the same prompt text and use them randomly to avoid training collapse.

Chain-of-Clarifications Workflow Prompts

[System Prompt]

You are an AI assistant specialized in long context reasoning. Analyze information thoroughly while maintaining clarity and focus. Track the full context of conversations, building connections between concepts and flagging when context review is needed. Break down complex problems into components, showing your reasoning steps and stating key assumptions. Structure your responses with clear headers and periodic summaries. Present evidence for your conclusions, acknowledge uncertainties, and request clarification when needed. Keep your analysis organized, explicit, and focused on addressing the core question.

[Long-Context Input]

<para 1> [chunk 1] </para 1> <para 2> [chunk 2] </para 2> ... {Question}

[Self Clarification - Raise Question]

In order to answer this question, ask one question about what you want to know in order to better answer it.

[Contextual Grounding - Pointback]

Help me find relevant context to answer the previous clarifying question.

[Self Clarification - Answer Question]

Based on the relevant context, answer the previous clarifying question.

[Answer the Original Question]

Now, let's answer the final question. Be concise in your answer.

E Evaluation Template

We use GPT-4o (OpenAI, 2023) to judge if the model's answer is correct. The specific prompt template with the structured output class is shown below.

```
...
Please verify the following answer:

Question: {question}
Ground Truth Answers: {ground_truth}
Predicted Answer: {answer}

Your task is to determine whether the predicted
↪ answer correctly matches the ground truth.
↪ Focus on overall correctness and provide a
↪ detailed explanation in the following
↪ format:
...

class VerificationResult:
    explanation: str # Justification
    confidence: float # Confidence score in
    ↪ the range [0,1]
    correct_answer: bool # True if the
    ↪ prediction is correct, otherwise False
```

Table 8: Performance comparison of AgenticLU and Llama3.1-8B-Instruct on short-context benchmarks. Scores represent accuracy percentages, with AgenticLU demonstrating matching results across tasks.

Model	ARC Easy	ARC Challenge	GSM8k	MathQA	MMLU	MMLU Pro	Avg
Llama3.1-8B	84.80	59.64	80.13	42.88	68.72	37.71	62.31
AgenticLU-8B	83.96	58.36	80.51	41.74	68.38	37.51	61.74

Model	HotpotQA				
	8K	16K	32K	64K	128K
Llama3.1-8B	63.3	56.7	61.1	47.8	40.0
Llama3.1-8B+step-by-step	60.0	66.7	56.7	58.9	56.7
Llama3.1-8B+plan&solve	71.1	66.7	72.2	62.2	50.0
Llama3.1-8B+fact&reflect	58.9	58.9	62.2	61.1	48.9
ProLong-8B	62.2	65.6	57.8	53.3	58.9
Llama3.1-8B+LongRAG	61.1	58.9	73.3	56.7	57.8
AgenticLU-8B	81.1	75.6	78.9	75.6	71.1

Table 9: Long-context performance on HotpotQA.

Model	Nature Questions				
	8K	16K	32K	64K	128K
Llama3.1-8B	71.7	69.4	70.6	73.9	56.1
Llama3.1-8B+step-by-step	66.7	66.1	58.9	55.6	38.9
Llama3.1-8B+plan&solve	67.8	71.7	66.7	62.2	50.6
Llama3.1-8B+fact&reflect	63.3	63.3	61.7	59.4	40.0
ProLong-8B	83.3	82.2	83.9	90.0	77.8
Llama3.1-8B+LongRAG	65.6	76.1	79.4	77.2	73.9
AgenticLU-8B	91.7	91.1	85.0	85.0	77.8

Table 10: Long-context performance on Nature Questions.

Model	TriviaQA				
	8K	16K	32K	64K	128K
Llama3.1-8B	82.8	86.7	85.6	81.1	80.6
Llama3.1-8B+step-by-step	84.4	86.1	90.0	82.2	57.2
Llama3.1-8B+plan&solve	78.9	88.3	89.4	87.2	86.7
Llama3.1-8B+fact&reflect	87.8	83.9	84.4	86.7	84.4
ProLong-8B	71.1	88.3	78.9	82.8	78.3
Llama3.1-8B+LongRAG	77.2	79.4	83.9	83.9	83.3
AgenticLU-8B	88.3	92.2	91.1	93.3	88.3

Table 11: Long-context performance on TriviaQA.

Model	PopQA				
	8K	16K	32K	64K	128K
Llama3.1-8B	61.1	62.8	57.2	58.3	56.1
Llama3.1-8B+step-by-step	61.7	58.9	55.0	58.9	60.6
Llama3.1-8B+plan&solve	62.2	63.4	58.9	55.0	61.1
Llama3.1-8B+fact&reflect	65.0	64.4	58.9	53.3	65.0
ProLong-8B	67.8	68.3	70.0	64.4	65.6
Llama3.1-8B+LongRAG	47.8	54.4	54.4	57.2	50.6
AgenticLU-8B	82.2	82.2	78.3	76.7	65.6

Table 12: Long-context performance on PopQA.

Model	NarrativeQA				
	8K	16K	32K	64K	128K
Llama3.1-8B	15.0	19.0	27.0	35.0	38.0
Llama3.1-8B+step-by-step	23.0	30.0	36.0	51.0	43.0
Llama3.1-8B+plan&solve	22.0	25.0	38.0	41.0	39.0
Llama3.1-8B+fact&reflect	18.0	35.0	37.0	42.0	46.0
ProLong-8B	18.0	27.0	28.0	38.0	42.0
Llama3.1-8B+LongRAG	23.3	23.3	50.0	50.0	46.7
AgenticLU-8B	27.0	35.0	41.0	49.0	56.0

Table 13: Long-context performance on NarrativeQA.

Model	InfbenchQA				
	8K	16K	32K	64K	128K
Llama3.1-8B	17.0	31.0	36.0	40.0	48.0
Llama3.1-8B+step-by-step	21.0	36.0	36.0	45.0	43.0
Llama3.1-8B+plan&solve	17.0	26.0	32.0	41.0	40.0
Llama3.1-8B+fact&reflect	19.0	30.0	40.0	42.0	37.0
ProLong-8B	16.0	31.0	29.0	31.0	45.0
Llama3.1-8B+LongRAG	16.7	23.3	36.7	43.3	36.7
AgenticLU-8B	25.0	39.0	42.0	47.0	50.0

Table 14: Long-context performance on InfbenchQA.

Model	InfbenchChoice				
	8K	16K	32K	64K	128K
Llama3.1-8B	9.0	12.0	24.0	39.0	55.0
Llama3.1-8B+step-by-step	15.0	13.0	41.0	41.0	44.0
Llama3.1-8B+plan&solve	27.0	15.0	48.0	55.0	58.0
Llama3.1-8B+fact&reflect	20.0	14.0	38.0	51.0	56.0
ProLong-8B	22.0	27.0	37.0	48.0	58.0
Llama3.1-8B+LongRAG	16.7	30.0	43.3	53.3	63.3
AgenticLU-8B	45.0	46.0	47.0	64.0	68.0

Table 15: Long-context performance on InfbenchChoice.