Neutralizing Bias in LLM Reasoning using Entailment Graphs

Anonymous ACL submission

Abstract

LLMs are often claimed to be capable of Natural Language Inference (NLI), which is widely regarded as a cornerstone of more complex forms of reasoning. However, recent works show that LLMs still suffer from hallucinations in NLI due to attestation bias, where LLMs overly rely on propositional memory to build shortcuts. To solve the issue, we design an unsupervised framework to construct counterfactual reasoning data and fine-tune LLMs to reduce attestation bias. To measure bias reduction, we build bias-adversarial variants of NLI 012 datasets with randomly replaced predicates in premises while keeping hypotheses unchanged. Extensive evaluations show that our framework can significantly reduce hallucinations from attestation bias. Then, we further evalu-017 ate LLMs fine-tuned with our framework on original NLI datasets and their bias-neutralized versions, where original entities are replaced 021 with randomly sampled ones. Extensive results show that our framework consistently improves inferential performance on both original and bias-neutralized NLI datasets. 024

1 Introduction

026

027

034

040

Natural Language Inference (NLI) has long been recognized as a foundational understanding task in language understanding with various downstream applications (Cheng et al., 2023; Deng et al., 2023; Gao et al., 2023). It assesses the understanding ability of models by requiring them to determine if a given premise logically entails a hypothesis. Recently, with the rise of LLMs, the field of NLI has witnessed significant advancements (Brown et al., 2020; He et al., 2023; Liu et al., 2024b). These models, pre-trained on vast amounts of text data, have been claimed to capture inferential relations between statements enabling reasoning, positioning them as state-of-the-art tools for NLI.

However, despite the apparent success of LLMs on natural NLI tasks, they continue to embody re-



Figure 1: An example of attestation bias. LLMs tend to evaluate entailment with their memorized knowledge rather than given premise.

sponse biases, leading to the phenomenon of hallucination (Huang and Chang, 2023; Ji et al., 2023; Gallegos et al., 2024). In NLI, this issue arises because models rely more on memorization from their training corpus rather than inference from the given premises, causing false positive entailment judgments when the hypothesis is *attested* in the training data (Poliak et al., 2018; Rawte et al., 2023), the phenomenon known as **attestation bias** (Mckenna et al., 2023). The attestation bias leads to brittleness in bias-adversarial cases, and poses challenges in accurately assess the bias-free reasoning capabilities of LLMs (Mckenna et al., 2023).

In this study, we explore the method of finetuning LLMs to improve their robustness against the attestation bias. We propose an *unsupervised* approach to construct counterfactual but logically consistent datasets for training LLMs. Our approach begin with unsupervised extraction of textual entailment relations between predicates from large-scale open-domain corpora using semantic parsing. The extracted data is then formatted into Entailment Graphs (EGs) (Hosseini et al., 2018, 2021), which consist of typed predicate pairs. Finally, we generate counterfactual samples by randomly selecting named entities and other arguments to instantiate these types.

We evaluate the effectiveness of our method along two dimensions: bias reduction and general

042

043

044

045

047



Figure 2: The pipeline of our approach: **Step 1:** Build EGs in unsupervised manner. **Step 2:** Instantiate predicates using random entities with matching types, then wrap instantiated predicates into prompts to generate training corpus.

inferential performance improvement.

First, to measure how well our training has reduced the attestation bias, we compare LLMs before and after our training on *bias-adversarial* variants of NLI datasets. Specifically, we randomly alter the predicates in the premises while keeping the hypothesis fixed. The newly generated premises are non-entailing, so any positive judgments by the LLM are false positives, arising from attestation bias relating to the hypothesis. The results demonstrate that training LLMs with our method can significantly reduce attestation bias, ensuring a more reliable evaluation of their reasoning capabilities.

Second, to evaluate the effectiveness of our training in improving inferential performance on the original NLI tasks, we conduct experiments on both the *standard* and a further *bias-neutralized* NLI datasets, where entities in the original dataset are replaced with randomly selected entities of the same type. In both cases, our approach outperforms baseline models, demonstrating its robustness and effectiveness in enhancing inferential capability.

The main contributions of this paper are summarized as follows:

(a) To reduce attestation bias while enhancing inferential capabilities, we propose an unsupervised approach using EGs to generate a logically sound inference dataset, free of the artefacts that plague human-constructed NLI datasets, for fine-tuning LLMs.

(b) We show that for 4 different LLMs, our approach reduce attestation bias and improves performance in NLI tasks.

(c) We introduce a bias-neutralized method for a more accurate evaluation of LLMs' true inferential capabilities. This approach generates biasneutralized test sets, where our EG-enhanced models consistently achieve superior reasoning performance on both standard and these bias-neutralized inference datasets.

2 Related Work

Hallucination in Inference: Hallucination in LLMs has emerged as a significant area of concern in NLP, as these models often generate content that is either factually inaccurate or contextually inappropriate. Talman and Chatzikyriakidis (2019) report that many models struggle to generalize across different NLI datasets, even when the task format remains the same. In smaller language models, Li et al. (2022) observed a reliance on dataset artifacts when performing directional NLI on predicates. Furthermore, Poliak et al. (2018) found a range of NLI datasets containing artifacts that are memorized by supervised models trained on only sample hypotheses, causing overestimation of their inference performance. Gulati et al. (2024) proves that SOTA LLMs rely on memorized data to answer math questions, and their performance drops significantly once variable names are altered. Carlini et al. (2023) found that LLMs are capable of memorizing significantly more data compared to smaller models, raising doubts on whether their performance gains stem from advanced inferential capabilities or more memorization.

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

Attestation Bias: The attestation bias occurs when LLMs show a significantly higher probability of predicting Entail when the hypothesis is *attested*, indicating that the inference process of LLMs is heavily influenced by their reliance on memorization about hypotheses. As a result, LLMs are inherently prone to disregarding the premise and responding incorrectly by relying on memorized information about hypothesis from their training corpus, as illustrated in Figure 1.

Mckenna et al. (2023) conducted a hypothesisonly test on LLMs, revealing that when labels contradict attestation bias, LLMs can be poor or even near-random classifier. Their research demonstrates that the attestation bias is the primary source

109

110

of hallucination in LLMs on inference tasks. 150

Entailment Graphs: EGs are symbolic graphs used to preserve entailment relations between pred-152 icates (Berant et al., 2010, 2011; Hosseini et al., 2018, 2021). Unlike sentence-level inference data, EGs are formatted as sets of triples, with each triple 155 consisting of predicate pairs and typed arguments. For example, "(*Person.X*, *visited*, *Location.Y*) \models (Person.X, went to, Location.Y)". EGs have been utilized in open-domain question answering and knowledge inference (Cheng et al., 2023; Wang et al., 2024).

Methodology 3

151

153

154

156

157

158

159

160

161

162

163

164

165

168

169

170

171

172

173

174

175

176

177

178

179

181

187

190

191

192

194

We propose an *unsupervised* approach for constructing counterfactual reasoning datasets to finetune LLMs, enabling them to generalize beyond memorized knowledge and enhance inferential capabilities.

3.1 Constructing Counterfactual Reasoning **Datasets**

As demonstrated in Figure 2, our counterfactual reasoning dataset is built in two key steps: unsupervised extraction of EGs $(\S3.1.1)$ and instantiating EG rules into NLI training sets ($\S3.1.2$).

3.1.1 Extracting Entailment Graph

We adopt the approach proposed by Hosseini et al. (2018) for constructing EGs, which involves following main steps:

First, we employ a combinatory categorial grammar (CCG) parser (Steedman, 2000), GraphParser (Reddy et al., 2014), to extract binary relations between a predicate and its arguments from sentences. Each argument, typically a noun, is then linked to its corresponding FreeBase IDs and entity type using the Named Entity Linking tool Aidalight (Nguyen et al., 2014), formatting the extracted triple as predicates with typed arguments. Then, we compute the distributional similarity score¹ by calculating the co-occurrence of predicates associated with entities of the same types, assuming that predicates linked to the same entities refer to the same event or episode. We generate negative examples by replacing predicates with the same typed arguments. Notably, the entire process is unsupervised.

Corpus: Following Hosseini et al. (2021), we use the multiple-source NewsSpike (Zhang and Weld, 2013) corpus to extract the EGs. NewsSpike was deliberately built to include different articles from different sources describing identical news events. From this dataset, we extract 5,500 positive and 5,500 negative samples.

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

227

230

231

232

233

235

236

237

238

239

240

241

242

243

3.1.2 Instantiating Premise-Hypothesis Pairs

Entailment graphs consist of entailment rules, each rule in an EG involves a pair of predicates expecting two typed arguments. To instantiate EG rules into NLI data entries, we first replace the type arguments with specific named entities. To ensure consistent entity replacements, we categorize entities from the open-domain corpus into 48 FIGER types (Ling and Weld, 2012), such as "person" or "location", aligning them with the types in Freebase (Bollacker et al., 2008). We assign a default type "thing" in failure cases. Using the entity-to-type mapping, we randomly select entities that match the corresponding types to instantiate typed EGs into premise-hypothesis pairs.

EG rules are predicate focused and applies to any context, so the instantiation process preserves the entailment relationships within typed EGs. Figure 2 illustrates this process with an example, where the entailment "(Person X, was assassinated in, Location Y) \models (Person X, died in, Location Y)" is formatted into the following NLI format: "[Premise]: Steve Jobs was assassinated in London. [Hypothesis]: Steve Jobs died in London". Our constructed premise-hypothesis pairs preserve the logical inferential relationship but are counterfactual.

We adopt the prompt templates from previous studies (Schmitt and Schütze, 2021; Mckenna et al., 2023), formatting the premise-hypothesis pairs as a two-way answer choice: A) True, B) False. These generated natural questions are then used to query the models. The full list of concrete prompts can be found in Appendix E.1.

3.2 Training LLMs with Instantiated EGs

We use the counterfactual reasoning data generated from EGs to fine-tune DeepSeek-R1-Distill-Llama-8B (DeepSeek-AI et al., 2025), Mistral-7B, LLaMA-3-8B-instruct, and LLaMA-3-70Binstruct models. These models are widely recognized for their strong reasoning capabilities and have drawn significant interest from researchers.

Following the *llama-recipes* tools published by

We use the Weeds similarity score (Weeds and Weir, 2003) as the entailment score in our construction.

337

289

Meta², we fine-tune LLMs using LoRA (Hu et al., 2022) within the PEFT (Parameter-Efficient Fine-Tuning) (Ding et al., 2023) framework. During fine-tuning, we set a fixed learning rate of $1e^{-4}$ and train for 12 epochs. The LoRA rank is set to 8, with LoRA dropout rate of 0.05.

4 Experimental Setup

245

246

247

248

251

252

260

263

264

269

271

272

273

274

275

277

278

281

283

287

To evaluate the effectiveness of our EG-enhanced models, we conduct two experiments: (1) examining whether EG-enhanced models reduce attestation bias in §5, and (2) assessing their inferential performance in NLI benchmarks in §6. Both evaluation experiments follow the same settings, including the evaluation datasets and baselines, as detailed in the following sections³.

4.1 Evaluation Datasets

Levy/Holt (Levy and Dagan, 2016; Holt, 2019) dataset is a widely used for NLI, which comprises premise-hypothesis pairs structured in a specific task format: "Given [premise P], is it true that [hypothesis H]?". Each P- and H-statement has the property of containing one predicate with two named entity arguments, where the same entities appear in both P and H. The Levy/Holt dataset contains inverse of all entailment pairs. Following Mckenna et al. (2023), we study the challenging directional subset, where the entailments hold in one direction but not both.

SNLI (Bowman et al., 2015) is another widely used datasets for NLI. It consists of humangenerated premise-hypothesis pairs with manually assigned labels. Unlike Levy/Holt, which contains named-entity artifacts, SNLI is composed of general sentences in both premises and hypotheses, typically without named entities.

Fomatting as two-choice questions: For evaluation, premise-hypothesis pairs in Levy/Holt and SNLI are formatted as two-choice natural questions using prompts, where choice A corresponds to Entail and choice B to No-Entail, ensuring alignment with the Levy/Holt and SNLI annotations⁴. These prompts are crafted by human experts (Schmitt and Schütze, 2021; Mckenna et al., 2023), as shown in Appendix §E.3. During evaluation, all models successfully selected either A or B for every development set question, indicating compatibility with the QA format.

4.2 Baselines

Standard LLMs with Few-Shot Setting: To evaluate the performance of EG-enhanced LLMs, we compare them against the original LLMs as baseline models. During inference, we adopt a few-shot approach, hand-annotating a minimal set of 4 examples in the style of the template. These examples are prepended before the query (see Appendix E.3 for an example). Our goal is to analyze model behavior as conditions change, rather than maximize the score on a specific dataset. Therefore, we maintain a minimal 4-example setup to evoke positive responses across LLMs.

Chain-of-Thought Reasoning: In our experiments, we incorporate manually written explanations in few-shot examples, providing step-bystep reasoning before each answer to guide LLMs. Specifically, we utilize a three-step analytical process for guidance: analyzing the premise, analyzing the hypothesis and clarifying the relationship between premise and hypothesis. These explanations, detailed in Appendix E.4, serve as Chain-of-Thought (CoT) prompts, establishing a baseline for evaluating LLM performance under CoT guidance.

5 Experiment 1: Attestation Bias Reduction

To evaluate the effectiveness of our method in reducing attestation bias, we measure attestation bias by comparing estimated probabilities of predicting Entail conditioned on whether the hypothesis is predicted Attested or not.

However, in original NLI dataset entailments may coincidentally refer to attested facts, which could lead to spurious correlation between inference and attestation scores, making it difficult to determine whether LLMs rely on memory or reasoning to generate predictions. To address this issue, we adopt the **Random Premise Inference Task** proposed by Mckenna et al. (2023), which serves as a *bias-adversarial* benchmark for accurately quantifying attestation bias.

The Random Premise Task (*RPI*) modifies the original NLI dataset by replacing the original premise predicate with a randomly selected predicate while keeping the hypothesis fixed and maintaining the same entity arguments. As a result, this process create non-entailing premise-hypothesis

²https://github.com/meta-llama/llama-recipes

³Our code and used data will be released upon publication. ⁴In SNLI, contradiction and neutral labels are categorized as No-Entail.

| Task | Sample Query: [premise] \Rightarrow [hypothesis] | Dataset Label |
|------|--|---------------|
| Ι | George Bush was the governor of Texas \Rightarrow George Bush is a politician from Texas | Entail |
| RPI | George Bush lives in Texas \Rightarrow George Bush is a politician from Texas | No-Entail |

| Table 1: A sample of generate <i>RPI</i> from original inferent | ice task I | ٠. |
|---|------------|----|
|---|------------|----|

pairs, as the example illustrated in Table 1. This transformation produces a dataset in which all samples are labeled as negatives (No-Entail), as two randomly paired predicates are highly unlikely to form entailment relations⁵. We determine whether LLMs can correctly identify these samples as negatives or if they rely solely on attested hypotheses to make false positive predictions. An ideal model should predict zero Entail. The *RPI* task effectively tests the model's reliance on propositional memory, as it prevents true entailments while maintaining the attestedness of the conclusions (hypotheses).

338

339

341

344

347

348

351

357

361

362

363

370

372

373

374

375

376

To calculate attestation biases, we first determine the attestedness of each hypothesis by prompting the LLM to classify it as true, false, or unknown, following the same prompts⁶ used in prior studies (Poliak et al., 2018; Mckenna et al., 2023). Then, we categorize all samples into two groups: *attested* and *non-attested*, depending on whether the LLM identifies the hypothesis as true. We calculate the proportion of Entail predictions in the *attested* set and compare it to the *non-attested* set, providing an effective measure of attestation bias by highlighting differences in prediction behavior between the two sets.

We adopt the Levy/Holt dataset for this attestation bias measurement experiment because this dataset includes artifacts containing named entities, allowing us to assess whether these artifacts in hypothesis are attested by LLMs.

5.1 Scoring Attestation Bias

Attestation bias reflects a significantly higher likelihood of predicting Entail for *attested* hypotheses compared to *non-attested* hypotheses. To quantify this bias, we define the **Attestation Bias score** as follows:

$$AttBias = P(tok = \texttt{Entail}|Att(hypo))$$
$$-P(tok = \texttt{Entail}|\neg Att(hypo))$$

| Model | AttBias | $\Delta_{AttBias}$ |
|-------------------------------------|---------|--------------------|
| DeepSeek-R1-Llama-8B | 26.04 | - |
| DeepSeek-R1-Llama-8B _{CoT} | 15.10 | -10.94 |
| $DeepSeek-R1-Llama-8B_{EG}$ | 7.58 | -18.46 |
| Mistral-7B | 32.98 | - |
| Mistral-7 B_{CoT} | 22.64 | -10.34 |
| Mistral-7 B_{EG} | 13.0 | -19.98 |
| Llama-3-8B | 23.12 | - |
| Llama-3-8 B_{CoT} | 13.94 | -9.18 |
| Llama-3-8 B_{EG} | 5.99 | -17.13 |
| Llama-3-70B | 19.20 | - |
| Llama-3-70 B_{CoT} | 15.96 | -3.24 |
| Llama-3-70 B_{EG} | 8.34 | -10.86 |

Table 2: AttBias scores on the *RPI* Levy/Holt dataset across various models (lower is better). The subscript *EG* denotes LLMs trained on our constructed EGs, while *CoT* refers to models employing chain-of-thought reasoning.

where P(tok = Entail | Att(hypo)) represents the estimated conditional probability of predicting Entail when the hypothesis is attested. When the models achieve the same accuracy rate⁷, we calculate the proportion of Entail predictions that fall within the *attested* hypothesis set compared to *non-attested* set.

Lower AttBias scores representing reduced influence from attested memorization, indicating less impact of attestation bias.

5.2 Results of Experiment I: Degree of Bias Reduction

Table 2 presents the Attestation Bias scores for the *RPI* task. The results demonstrate that our EGenhanced LLMs significantly reduce attestation bias, addressing the challenges of hallucination in NLI. Additionally, we report the reduction of false positives on *attested* hypotheses in Appendix C, indicating reduced reliance on the model's memorization of the training corpus.

We observe that the reduction in attestation bias is more pronounced in smaller models, compared to larger models, such as LLaMA-3-70B. This suggests that the fine-tuning with our EGs is more effective for smaller-sized models, as larger mod394

395

396

397

399

400

401

377

⁵Mckenna et al. (2023) manually inspect the generated random premise entries for the Levy/Holt dataset and found only 9.6% to be true entailment.

⁶The attestation prompt is provided in Appendix E.2.

⁷In our experiments, accuracy rate is set to 0.5.



Figure 3: The Attestation Bias scores for the original Levy/Holt, demonstrating a consistent attestation bias reduction after fine-tuning with EGs.

els require more extensive EGs data for fine-tuning. To validate this, we fine-tune LLMs with increasing amounts of training data generated from EGs. Our results indicate that attestation bias in LLaMA-3-70B continues to decline as training data increases, reaching levels comparable to those observed in smaller LLMs (detailed in Appendix D).

In addition to the *RPI* task, which is explicitly designed to be bias-adversarial, we also present the AttBias scores on the original Levy/Holt dataset in Figure 3, which demonstrate a consistent reduction in attestation bias following fine-tuning with EGs.

The significant reduction in attestation bias can be attributed to the counterfactual nature of our EG-based training corpus. During fine-tuning, the LLMs learn entailment between predicates while incorporating counterfactual knowledge, thereby reducing their reliance on memorized artifacts for inference. Our method minimizes hallucinations from attestation bias and enhances overall robustness.

6 Experiment 2: Evaluate Capability of Inference

EG-enhanced LLMs exhibit a notable reduction in attestation bias. To further investigate how this attestation bias reduction affects their capability of inference, we evaluate their general inferential performance on original NLI tasks.

However, attestation biases and reported data leakage (Gururangan et al., 2020; Balloccu et al., 2024; Ravaut et al., 2024) often lead to an overestimation of LLMs performance on original NLI dataset, where LLMs rely on memorization to form reasoning shortcuts rather than genuinely reasoning, making it challenging to accurately evaluating their true inference capabilities.

To address these challenges, we introduce a method to generate bias-neutralized dataset from original NLI datasets for evaluation. We neutralize biases by replacing the original entities with others of the same type, generating new inference data that includes counterfactual statements while preserving original entailment labels. We then evaluate our EG-enhanced LLMs on both *original* and *bias-neutralized* NLI test sets, enabling a more accurate assessment of their *true* inferential capabilities.

437

438

439

440

441

442

443

444

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

477

478

479

480

481

482

483

484

485

6.1 Neutralizing Biases

To neutralize the biases arising from memorization, we generate counterfactual premise-hypothesis pairs from the original dataset by randomly replacing the original entities with other entities of the same type. Since the entities are randomly selected, the newly generated pairs are logically sound but are likely not to exist in original training corpora. This method generates novel statements without changing their entailment labels, enabling an unbiased assessment of the model's true inferential capability without interference of memorization.

We use entity type constraints here to ensure polysemous predicates maintain the same sense. For instance, the verb "run" has different meanings in "[person] runs [organization]" versus "[person] runs [software]", but when substituting entities of the same type, the sense remains consistent. Therefore, the specific entity names do not affect the entailment labels (Yarowsky, 1993). Notably, this approach ensures that the dataset remains distinct from the original inference data and can allow for building new datasets for every experiment, thereby reducing potential overestimation caused by evaluation data leakage.

6.2 Bias-neutralized Test Sets

We apply this method to construct bias-neutralized test sets from the original NLI datasets.

Replaced Argument LevyHolt (LH_{rpArg}) : All original entities in Levy/Holt are named entities. We replace them with other real entities of the same type, which are extracted using the named entity linking tool Aidalight (Nguyen et al., 2014) from NewsCrawl (Barrault et al., 2019), a decade-long span of multi-source news text, in which entities are typed into FIGER types (Ling and Weld, 2012).

Pre-trained LLMs are likely to contain more memorized knowledge about high-frequent named

427

428

429

430

431

432

433

434

435

436

| Task | Sample Query: [premise] \Rightarrow [hypothesis] | |
|------------------------|--|--------|
| LH | George Bush was the Governor of Texas \Rightarrow George Bush is a politician from Texas | Entail |
| $LH_{rpArg\downarrow}$ | Jan Hus was the Governor of Svaneti \Rightarrow Jan Hus is a politician from Svaneti | Entail |
| $LH_{rpArg\uparrow}$ | Elon Musk was the Governor of $Paris \Rightarrow Elon Musk$ is a politician from Paris | Entail |

Table 3: An example of generating $LH_{rpArg\downarrow}$ and $LH_{rpArg\uparrow}$ from original Levy/Holt data (LH).

entities. Thus these generated counterfactual sam-486 ples involving high-frequency entities have higher 487 probability to conflict with the model's memorized 488 knowledge, exacerbating attestation biases. To fur-489 ther analyze the effect of entities frequency, we 490 sample new entities uniform randomly from the 5% 491 least common entities in NewsCrawl ($LH_{rpArg\downarrow}$), 492 and the 5% most common $(LH_{rpArq\uparrow})$, separately. 493 We insert the sampled entities while preserving the 494 rest of each statement. Examples are shown in 495 Table 3. 496

497

498

499 500

501

504 505

510

511

512

513

514

515

516

517

518

519

520

521

523

524

526

528

Replaced Argument SNLI (*SNLI*_{rpArg}): Sincethe SNLI dataset typically consists of general sentences without named entities, making it impractical to directly extract real named entities fromNewsCrawl to replace these general entities.</sub>

To address this, we adopt the approach proposed by Liu et al. (2024a), using ChatGPT to identify entities with their types that co-occur in both the hypothesis and premise (these are general entities, not limited to named entities) and then generate new entities that match the specified types to replace them. For instance, an original SNLI sample such as "John gives Mary an <u>apple</u> \Rightarrow Mary receives an <u>apple from John</u>", will be modified to "John gives Mary a <u>book</u> \Rightarrow Mary receives a <u>book from John</u>".

We manually check 50 samples from LH_{rpArg} and $SNLI_{rpArg}$ separately, confirming that all of them are logically sound. Additionally, we also examine the attestedness of hypotheses in LH_{rpArg} and $SNLI_{rpArg}$ and find only 0.89% are attested, ensuring that these bias-neutralized test sets are logically consistent and bias-free.

6.3 Scoring Inferential Capability

Following Mckenna et al. (2023), we analyze model performance across varying confidence thresholds by converting letter choices into probabilities using the following mapping:

$$S_{\text{ent}} = 0.5 + 0.5 * \mathbb{I}[\text{tok} = \mathbf{A}] * S_{\text{tok}}$$
$$- 0.5 * \mathbb{I}[\text{tok} = \mathbf{B}] * S_{\text{tok}}$$

Where I is the indicator function, and S_{ent} estimates the probability of Entail from a textual output ($0 \le S_{ent} \le 1$) with token probability S_{tok} .

| Models | Levy/Holt | SNLI |
|-------------------------------------|-----------|-------|
| DeepSeek-R1-Llama-8B | 69.25 | 85.06 |
| DeepSeek-R1-Llama-8B _{CoT} | 65.65 | 85.26 |
| $DeepSeek-R1-Llama-8B_{EG}$ | 71.49 | 85.80 |
| Mistral-7B | 69.78 | 85.47 |
| Mistral-7 B_{CoT} | 65.14 | 83.63 |
| Mistral-7 B_{EG} | 72.82 | 85.64 |
| LLaMA-3-8B | 66.87 | 87.49 |
| LLaMA-3-8 B_{CoT} | 62.40 | 85.63 |
| LLaMA-3-8 B_{EG} | 73.69 | 86.62 |
| LLaMA-3-70B | 77.40 | 90.01 |
| LLaMA-3-70 B_{CoT} | 76.53 | 89.03 |
| $LLaMA-3-70B_{EG}$ | 77.46 | 89.85 |

Table 4: AUC scores of original, EG-enhanced ($_{EG}$) and with chain-of-thought prompts ($_{CoT}$) LLMs versions on original Levy/Holt and SNLI.

The linear transformation preserves the ordering of model confidences, which is sufficient for calculating a precision-recall curve and **Area Under the Curve (AUC)** score.

6.4 Results of Experiment II: Performance in Inference Tasks

Table 4 presents the AUC scores for original NLI datasets, demonstrating that EG-enhanced LLMs consistently outperform original LLMs across various model families on the Levy/Holt dataset. Notably, smaller models exhibit significant performance gains from EGs tuning, surpassing the improvements observed in larger models. On the original SNLI dataset, our EG-enhanced models yield only modest improvements. One possible explanation for this limited improvement is data leakage (Balloccu et al., 2024), as the original SNLI dataset may contain more memorized instances from pretrained LLMs, leading to an overestimation of inferential capacities.

To assess the true capability of inference, we evaluate bias-neutralized inference test sets and present the AUC scores in Table 5. The results highlight consistent improvements achieved by our EG-enhanced models across all bias-neutralized datasets. Additionally, the Precision-Recall curve in Appendix B further illustrates that EG-enhanced LLMs outperform the original models, with particularly notable gains in smaller LLMs. Notably, 549

550

551

552

553

554

555

556

557

| Models | | | Ta | isks | | |
|-------------------------------------|--------|------------------|-----------------|----------------|-------|----------------|
| | LH_r | $pArg\downarrow$ | LH _r | $pArg\uparrow$ | SNL | I_{rpArg} |
| | AUC | Δ_{AUC} | AUC | Δ_{AUC} | AUC | Δ_{AUC} |
| DeepSeek-R1-Llama-8B | 66.17 | - | 61.04 | - | 76.13 | - |
| DeepSeek-R1-Llama-8B _{CoT} | 59.57 | -6.6 | 56.65 | -4.39 | 69.66 | -6.47 |
| DeepSeek-R1-Llama-8B _{EG} | 67.37 | +1.2 | 68.92 | +7.87 | 77.87 | +1.74 |
| LLaMA-3-8B | 61.80 | - | 59.05 | - | 78.31 | - |
| LLaMA-3-8 B_{CoT} | 53.69 | -8.11 | 54.95 | -4.1 | 70.11 | -8.20 |
| LLaMA-3-8 B_{EG} | 71.27 | +9.47 | 70.96 | +11.91 | 80.03 | +1.72 |
| Mistral-7B | 61.27 | - | 59.96 | - | 78.17 | - |
| Mistral-7 B_{CoT} | 59.78 | -1.49 | 57.52 | -2.44 | 75.62 | -2.55 |
| Mistral-7 B_{EG} | 71.20 | +9.93 | 72.27 | +12.31 | 80.43 | +2.26 |
| LLaMA-3-70B | 71.99 | - | 69.55 | - | 80.26 | - |
| LLaMA-3-70 B_{CoT} | 70.65 | -1.34 | 67.34 | -2.21 | 80.10 | -0.16 |
| LLaMA-3-70 B_{EG} | 76.14 | +4.15 | 76.71 | +7.16 | 83.29 | +3.03 |

Table 5: AUC scores of LLMs, LLMs with chain-of-thought prompt $(_{CoT})$ and their EG-enhanced versions $(_{EG})$ on bias-neutralized inference datasets.

across all bias-neutralized inference datasets, the EG-enhanced smaller models (DeepSeek- $8B_{EG}$, LLaMA-3- $8B_{EG}$ and Mistral- $7B_{EG}$) achieve performance on the same level of LLaMA-3-70B. These results suggest that after training on our EGs, smaller LLMs achieve inferential capabilities comparable to the standard extreme large models. We further examine the impact of prompt templates in Appendix A, proving that LLMs are genuinely learning textual entailment during finetuning rather than merely memorizing the prompts.

559

562

563

564

565

567

568

569

571

573

574

575

576

577

578

582

585

587

588

589

591

In Table 5, we also observe that standard LLMs are limited in $LH_{rpArg\uparrow}$ and the improvement achieved by our method on $LH_{rpArg\uparrow}$ is more pronounced compared to $LH_{rpArg\downarrow}$. This suggests that standard LLMs face greater challenges when processing counterfactual information involving highfrequency entities. The observation indicates that LLMs overly rely on memorization to build reasoning shortcuts, ultimately undermining their reasoning performance on high-frequent counterfactual tasks, which have higher probability to conflict with the model's memorized knowledge. On the other hand, the improvement of our EG-enhanced models on $LH_{rpArq\uparrow}$ highlights their enhanced inferential capability and robustness, particularly in handling conflicts between given premise and memorization.

Figure 4 presents that EG-enhanced model exhibit a more pronounced improvement on biasneutralized test set compared to original test sets. The reduction of attestation bias explains theses findings, as EG-enhanced models increasingly rely on their enhanced inferential capabilities to process NLI tasks rather than retrieving memorized



Figure 4: AUC scores of baseline (outline) and EGtrained (solid) LLMs on original (orange) and our biasneutralized (blue) Levy/Holt.

592

593

594

595

596

598

599

600

601

602

603

604

605

606

607

608

609

610

information from training corpus.

7 Conclusion

In NLI tasks, attestation bias in LLMs leads to false positives, as models rely on memorization rather than reasoning from the given premise, ultimately undermining their robustness and accuracy in inference. To address this, we propose an unsupervised method for constructing logically consistent counterfactual EGs to fine-tune LLMs, enhancing their robustness against attestation bias. Experimental results show that our method reduces attestation bias and enhances inference by learning counterfactual EGs, enabling models to learn predicate entailment while without introducing artifacts, thereby minimizing dependency on memorized patterns. Our method improves robustness and effectiveness of models in practical applications while providing a more objective evaluation of inference capability across LLMs.

8 Limitation

611

In this paper, we propose an unsupervised approach
to construct counterfactual reasoning data by instantiating entailment graphs and demonstrate its
effectiveness in reducing hallucinations, enhancing
the reasoning capabilities of LLMs.

A limitation of our current work is that the coun-617 terfactual reasoning data is used to fine-tune large 618 LLMs for a specific task, natural language infer-619 ence, rather than across a broader range of tasks. 620 Although inference is foundational to many NLP 621 tasks, it remains uncertain whether our approach 622 will generalize effectively to other tasks. In future 623 work, we plan to integrate counterfactual reasoning 624 data into instruction-tuning frameworks to evalu-625 ate its performance across a wider variety of NLP 626 tasks. 627

References

628

629

631

632

633

634

637

643

645

647

648

651

653

659

661

665

672

673

674

675

676

677

678

679

682

- Simone Balloccu, Patrícia Schmidtová, Mateusz Lango, and Ondřej Dušek. 2024. Leak, cheat, repeat: Data contamination and evaluation malpractices in closedsource llms. *arXiv preprint arXiv:2402.03927*.
 - Loïc Barrault, Ondřej Bojar, Marta R. Costa-jussà, Christian Federmann, Mark Fishel, Yvette Graham, Barry Haddow, Matthias Huck, Philipp Koehn, Shervin Malmasi, Christof Monz, Mathias Müller, Santanu Pal, Matt Post, and Marcos Zampieri. 2019. Findings of the 2019 Conference on Machine Translation (WMT19). In Proceedings of the Fourth Conference on Machine Translation (Volume 2: Shared Task Papers, Day 1), pages 1–61, Florence, Italy. Association for Computational Linguistics.
 - Jonathan Berant, Ido Dagan, and Jacob Goldberger. 2010. Global Learning of Focused Entailment Graphs. In *Proceedings of the 48th Annual Meeting of the Association for Computational Linguistics*, pages 1220–1229.
 - Jonathan Berant, Ido Dagan, and Jacob Goldberger. 2011. Global Learning of Typed Entailment Rules. In Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies, pages 610–619.
 - Kurt Bollacker, Colin Evans, Praveen Paritosh, Tim Sturge, and Jamie Taylor. 2008. Freebase: A collaboratively created graph database for structuring human knowledge. In Proceedings of the 2008 ACM SIGMOD International Conference on Management of Data, SIGMOD '08, page 1247–1250, New York, NY, USA. Association for Computing Machinery.
 - Samuel R. Bowman, Gabor Angeli, Christopher Potts, and Christopher D. Manning. 2015. A large annotated corpus for learning natural language inference. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pages 632–642, Lisbon, Portugal. Association for Computational Linguistics.
 - Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language Models are Few-Shot Learners. Advances in neural information processing systems, 33:1877–1901.
 - Nicholas Carlini, Daphne Ippolito, Matthew Jagielski, Katherine Lee, Florian Tramer, and Chiyuan Zhang. 2023. Quantifying memorization across neural language models. In *The Eleventh International Conference on Learning Representations*.
 - Liang Cheng, Mohammad Javad Hosseini, and Mark Steedman. 2023. Complementary roles of inference and language models in QA. *EMNLP 2023*, 550(2023):75.
 - DeepSeek-AI, Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu,

Shirong Ma, Peiyi Wang, Xiao Bi, Xiaokang Zhang, Xingkai Yu, Yu Wu, Z. F. Wu, Zhibin Gou, Zhihong Shao, Zhuoshu Li, Ziyi Gao, Aixin Liu, Bing Xue, Bingxuan Wang, Bochao Wu, Bei Feng, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, Damai Dai, Deli Chen, Dongjie Ji, Erhang Li, Fangyun Lin, Fucong Dai, Fuli Luo, Guangbo Hao, Guanting Chen, Guowei Li, H. Zhang, Han Bao, Hanwei Xu, Haocheng Wang, Honghui Ding, Huajian Xin, Huazuo Gao, Hui Qu, Hui Li, Jianzhong Guo, Jiashi Li, Jiawei Wang, Jingchang Chen, Jingyang Yuan, Junjie Qiu, Junlong Li, J. L. Cai, Jiaqi Ni, Jian Liang, Jin Chen, Kai Dong, Kai Hu, Kaige Gao, Kang Guan, Kexin Huang, Kuai Yu, Lean Wang, Lecong Zhang, Liang Zhao, Litong Wang, Liyue Zhang, Lei Xu, Leyi Xia, Mingchuan Zhang, Minghua Zhang, Minghui Tang, Meng Li, Miaojun Wang, Mingming Li, Ning Tian, Panpan Huang, Peng Zhang, Qiancheng Wang, Qinyu Chen, Qiushi Du, Ruiqi Ge, Ruisong Zhang, Ruizhe Pan, Runji Wang, R. J. Chen, R. L. Jin, Ruyi Chen, Shanghao Lu, Shangyan Zhou, Shanhuang Chen, Shengfeng Ye, Shiyu Wang, Shuiping Yu, Shunfeng Zhou, Shuting Pan, S. S. Li, Shuang Zhou, Shaoqing Wu, Shengfeng Ye, Tao Yun, Tian Pei, Tianyu Sun, T. Wang, Wangding Zeng, Wanjia Zhao, Wen Liu, Wenfeng Liang, Wenjun Gao, Wenqin Yu, Wentao Zhang, W. L. Xiao, Wei An, Xiaodong Liu, Xiaohan Wang, Xiaokang Chen, Xiaotao Nie, Xin Cheng, Xin Liu, Xin Xie, Xingchao Liu, Xinyu Yang, Xinyuan Li, Xuecheng Su, Xuheng Lin, X. Q. Li, Xiangyue Jin, Xiaojin Shen, Xiaosha Chen, Xiaowen Sun, Xiaoxiang Wang, Xinnan Song, Xinyi Zhou, Xianzu Wang, Xinxia Shan, Y. K. Li, Y. Q. Wang, Y. X. Wei, Yang Zhang, Yanhong Xu, Yao Li, Yao Zhao, Yaofeng Sun, Yaohui Wang, Yi Yu, Yichao Zhang, Yifan Shi, Yiliang Xiong, Ying He, Yishi Piao, Yisong Wang, Yixuan Tan, Yiyang Ma, Yiyuan Liu, Yongqiang Guo, Yuan Ou, Yuduan Wang, Yue Gong, Yuheng Zou, Yujia He, Yunfan Xiong, Yuxiang Luo, Yuxiang You, Yuxuan Liu, Yuyang Zhou, Y. X. Zhu, Yanhong Xu, Yanping Huang, Yaohui Li, Yi Zheng, Yuchen Zhu, Yunxian Ma, Ying Tang, Yukun Zha, Yuting Yan, Z. Z. Ren, Zehui Ren, Zhangli Sha, Zhe Fu, Zhean Xu, Zhenda Xie, Zhengyan Zhang, Zhewen Hao, Zhicheng Ma, Zhigang Yan, Zhiyu Wu, Zihui Gu, Zijia Zhu, Zijun Liu, Zilin Li, Ziwei Xie, Ziyang Song, Zizheng Pan, Zhen Huang, Zhipeng Xu, Zhongyu Zhang, and Zhen Zhang. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning.

684

685

687

688

689

690

691

692

693

694

695

696

697

698

699

702

704

705

706

709

710

711

712

713

714

715

716

717

718

719

720

721

722

723

724

725

726

727

728

729

730

731

732

733

734

735

736

737

738

739

740

741

742

743

744

- Yang Deng, Wenxuan Zhang, Weiwen Xu, Ying Shen, and Wai Lam. 2023. Nonfactoid question answering as query-focused summarization with graphenhanced multihop inference. *IEEE Transactions on Neural Networks and Learning Systems*.
- Ning Ding, Yujia Qin, Guang Yang, Fuchao Wei, Zonghan Yang, Yusheng Su, Shengding Hu, Yulin Chen, Chi-Min Chan, Weize Chen, et al. 2023. Parameter-efficient fine-tuning of large-scale pretrained language models. *Nature Machine Intelligence*, 5(3):220–235.

837

838

839

840

841

842

843

844

845

846

847

848

849

850

851

852

853

854

Isabel O Gallegos, Ryan A Rossi, Joe Barrow, Md Mehrab Tanjim, Sungchul Kim, Franck Dernoncourt, Tong Yu, Ruiyi Zhang, and Nesreen K Ahmed. 2024. Bias and fairness in large language models: A survey. *Computational Linguistics*, pages 1–79.

746

747

750

751

752

755

756

757

760

762

770

774

775

776

778

779

784

789

790

791

793

794

795

796

799

- Yunfan Gao, Yun Xiong, Xinyu Gao, Kangxiang Jia, Jinliu Pan, Yuxi Bi, Yi Dai, Jiawei Sun, and Haofen Wang. 2023. Retrieval-augmented generation for large language models: A survey. arXiv preprint arXiv:2312.10997.
- Aryan Gulati, Brando Miranda, Eric Chen, Emily Xia, Kai Fronsdal, Bruno de Moraes Dumont, and Sanmi Koyejo. 2024. Putnam-AXIOM: A functional and static benchmark for measuring higher level mathematical reasoning. In *The 4th Workshop on Mathematical Reasoning and AI at NeurIPS'24*.
 - Suchin Gururangan, Ana Marasović, Swabha Swayamdipta, Kyle Lo, Iz Beltagy, Doug Downey, and Noah A. Smith. 2020. Don't stop pretraining: Adapt language models to domains and tasks. In Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, pages 8342–8360, Online. Association for Computational Linguistics.
- Xuanli He, Yuxiang Wu, Oana-Maria Camburu, Pasquale Minervini, and Pontus Stenetorp. 2023. Using natural language explanations to improve robustness of in-context learning for natural language inference. *arXiv preprint arXiv:2311.07556*.
- Xavier Holt. 2019. Probabilistic Models of Relational Implication. *arXiv:1907.12048 [cs, stat]*. ArXiv: 1907.12048.
- Mohammad Javad Hosseini, Nathanael Chambers, Siva Reddy, Xavier R Holt, Shay B Cohen, Mark Johnson, and Mark Steedman. 2018. Learning Typed Entailment Graphs with Global Soft Constraints. *Transactions of the Association for Computational Linguistics*, 6:703–717.
- Mohammad Javad Hosseini, Shay B Cohen, Mark Johnson, and Mark Steedman. 2021. Open-Domain Contextual Link Prediction and its Complementarity with Entailment Graphs. In *Findings of the Association for Computational Linguistics: EMNLP 2021*, pages 2790–2802.
- Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. LoRA: Low-rank adaptation of large language models. In *International Conference* on Learning Representations.
- Jie Huang and Kevin Chen-Chuan Chang. 2023. Towards reasoning in large language models: A survey. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 1049–1065.
- Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Ye Jin Bang, Andrea

Madotto, and Pascale Fung. 2023. Survey of hallucination in natural language generation. *ACM Computing Surveys*, 55(12):1–38.

- Omer Levy and Ido Dagan. 2016. Annotating Relation Inference in Context via Question Answering. In Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers), pages 249–255, Berlin, Germany. Association for Computational Linguistics.
- Tianyi Li, Mohammad Javad Hosseini, Sabine Weber, and Mark Steedman. 2022. Language Models Are Poor Learners of Directional Inference. In *Findings* of the Association for Computational Linguistics: *EMNLP 2022*, pages 903–921, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.
- Xiao Ling and Daniel S. Weld. 2012. Fine-grained entity recognition. In *Proceedings of the Twenty-Sixth AAAI Conference on Artificial Intelligence*, AAAI'12, page 94–100. AAAI Press.
- Tianyang Liu, Tianyi Li, Liang Cheng, and Mark Steedman. 2024a. Explicit inductive inference using large language models. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 15779–15786.
- Xiaoyu Liu, Paiheng Xu, Junda Wu, Jiaxin Yuan, Yifan Yang, Yuhang Zhou, Fuxiao Liu, Tianrui Guan, Haoliang Wang, Tong Yu, et al. 2024b. Large language models and causal inference in collaboration: A comprehensive survey. *arXiv preprint arXiv:2403.09606*.
- Nick Mckenna, Tianyi Li, Liang Cheng, Mohammad Hosseini, Mark Johnson, and Mark Steedman. 2023. Sources of Hallucination by Large Language Models on Inference Tasks. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 2758–2774.
- Dat Ba Nguyen, Johannes Hoffart, Martin Theobald, and Gerhard Weikum. 2014. AIDA-light: Highthroughput Named-entity Disambiguation. In *Workshop on Linked Data on the Web 2014*, pages 1–10. CEUR-WS. org.
- Adam Poliak, Jason Naradowsky, Aparajita Haldar, Rachel Rudinger, and Benjamin Van Durme. 2018.
 Hypothesis only baselines in natural language inference. *NAACL HLT 2018*, page 180.
- Mathieu Ravaut, Bosheng Ding, Fangkai Jiao, Hailin Chen, Xingxuan Li, Ruochen Zhao, Chengwei Qin, Caiming Xiong, and Shafiq Joty. 2024. How much are llms contaminated? a comprehensive survey and the llmsanitize library. *arXiv preprint arXiv:2404.00699*.
- Vipula Rawte, A. Sheth, and Amitava Das. 2023. A survey of hallucination in large foundation models. *ArXiv*, abs/2309.05922.

Siva Reddy, Mirella Lapata, and Mark Steedman. 2014. Large-scale Semantic Parsing without Question-Answer Pairs. *Transactions of the Association for Computational Linguistics*, 2:377–392.

855

858

860

861

870

871 872

873

874

875

876

877 878

879

880

887

894

- Martin Schmitt and Hinrich Schütze. 2021. Language Models for Lexical Inference in Context. In Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume, pages 1267–1280, Online. Association for Computational Linguistics.
- Mark Steedman. 2000. *The Syntactic Process*. MIT Press, Cambridge, MA.
- Aarne Talman and Stergios Chatzikyriakidis. 2019. Testing the Generalization Power of Neural Network Models across NLI Benchmarks. In Proceedings of the 2019 ACL Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP, pages 85– 94, Florence, Italy. Association for Computational Linguistics.
- Zhaowei Wang, Wei Fan, Qing Zong, Hongming Zhang, Sehyun Choi, Tianqing Fang, Xin Liu, Yangqiu Song, Ginny Y Wong, and Simon See. 2024. Absinstruct: Eliciting abstraction ability from llms through explanation tuning with plausibility estimation. arXiv preprint arXiv:2402.10646.
- Julie Weeds and David Weir. 2003. A general framework for distributional similarity. In *Proceedings of the 2003 conference on Empirical methods in natural language processing*, pages 81–88.
- Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, brian ichter, Fei Xia, Ed Chi, Quoc V Le, and Denny Zhou. 2022. Chain-of-thought prompting elicits reasoning in large language models. In Advances in Neural Information Processing Systems, volume 35, pages 24824–24837. Curran Associates, Inc.
- David Yarowsky. 1993. One sense per collocation. In Human Language Technology: Proceedings of a Workshop Held at Plainsboro, New Jersey, March 21-24, 1993.
- Congle Zhang and Daniel S Weld. 2013. Harvesting Parallel News Streams to Generate Paraphrases of Event Relations. In *Proceedings of the 2013 Conference on Empirical Methods in Natural Language Processing*, pages 1776–1786.

921

922

923

924

925

927

928

929

931

A Analyzing the effects of prompt templates

One concern is whether the observed improve-902 ments in LLMs performance stem from learning 903 the predicate entailment in EGs or simply memorizing the structure of query prompt templates. 905 906 To determine this, we conducted a series of controlled experiments where the predicates in the EGs 907 were randomly shuffled while preserving the orig-908 inal prompt structure during fine-tuning. These 909 controlled datasets contain incorrect entailment re-910 lations between predicates but maintain the same 911 prompt template. For instance, a shuffled example 913 might present: "If Steve Jobs was assassinated in London, then Steve Jobs was born in London. Is 914 that true or false?". As shown in Table 6, the re-915 sults show a significant performance drop (almost random predict) after fine-tuning on the randomly 917 shuffled EGs. This confirms that the LLMs are in-918 919 deed learning textual entailment during fine-tuning, rather than simply memorizing prompt templates.

| Models | Levy/Holt | SNLI |
|--|-----------|-------|
| DeepSeek-R1-Llama-8B | 69.25 | 85.06 |
| DeepSeek-R1-Llama- $8B_{EG}$ | 71.49 | 85.80 |
| DeepSeek-R1-Llama-8B _{randEG} | 52.0 | 51.76 |
| Mistral-7B | 69.78 | 85.47 |
| Mistral-7B $_{EG}$ | 72.82 | 85.64 |
| Mistral-7 \mathbf{B}_{randEG} | 52.77 | 50.34 |
| LLaMA-3-8B | 66.87 | 87.49 |
| LLaMA-3-8 B_{EG} | 73.69 | 86.62 |
| LLaMA-3-8 B_{randEG} | 51.03 | 49.07 |
| LLaMA-3-70B | 77.40 | 90.01 |
| LLaMA-3-70 B_{EG} | 77.46 | 89.85 |
| LLaMA-3-70B _{randEG} | 56.25 | 52.91 |

Table 6: The AUC score of original, EG-enhanced ($_{EG}$), with chain-of-thought prompts ($_{CoT}$) and the random-shuffled-EG-enhanced ($_{randEG}$) LLMs versions on original Levy/Holt and SNLI dataset.

B Precision-Recall curve

To reduce biases arising from memorization, we evaluate bias-neutralized inference dataset and present the Precision-Recall curve for LH_{rpArg} in Figure 6. The results show that our EG-enhanced LLMs outperform original models, with particularly significant improvements observed in smaller LLMs. Additionally, Figure 7 shows the Precision-Recall curve for the original LH dataset, further demonstrating the consistent benefits of fine-tuning with EGs.



Figure 5: The probability of predicting Entail for *RPI* LevyHolt, conditioned on the LLMs' attestation of the hypothesis. Since predicting Entail in this context represents a false positive hallucination, a lower probability is better. The image clearly shows that hallucination decrease significantly after fine-tuning with EGs.

| Sizes of EGs | Model | |
|--------------|--------------------|---------------------|
| | LLaMA-3-8 B_{EG} | LLaMA-3-70 B_{EG} |
| 0 samples | 23.12 | 19.20 |
| 2k samples | 14.03 | 18.63 |
| 5k samples | 12.30 | 11.93 |
| 11k samples | 5.99 | 8.34 |
| 18k samples | 4.87 | 5.81 |

Table 7: The AttBias scores of various LLMs fine-tuned with different sizes of EG datasets.

932

933

934

935

936

937

938

939

940

941

942

943

944

945

946

947

948

949

950

951

952

C Proportion of False Positives on PRI

Figure 5 presents the estimated probability of predicting *Entail* when the hypothesis is attested, highlighting a consistent decrease after fine-tuning with EGs across all LLMs. This decrease presents fewer false positives on *attested* hypotheses, indicating reduced reliance on the model's memorization of the training corpus.

D Fine-tuning LLMs with different sizes EGs

To evaluate the performance of LLMs trained on varying sizes of generated counterfactual data, we present the attestation bias scores in Table 7. The results indicate that smaller LLMs are more sensitive to fine-tuning, while extremely large LLMs require larger amounts of generated data during the fine-tuning process.

E Prompt Format Selection

Prompt templates are widely acknowledged for their significant and sometimes decisive impact on the behavior of LLMs. In our experiments, we



Figure 6: The Precision-Recall curve of our method compared to standard LLMs on $LH_{rpArg\downarrow}$ and $LH_{rpArg\uparrow}$ datasets.



Figure 7: The Precision-Recall Curve of Levy/Holt across LLMs and the EG-tuned version.

categorize the prompt templates into three distinct types based on their usage: (a) prompt templates for fine-tuning LLMs, (b) prompt templates for hypothesis attestation, and (c) prompt templates used during inference.

E.1 prompt template for fine-tuning

955

956

957

959

960

961

962

963

964

965

We adopt the manually crafted prompts utilized in prior inference studies (Schmitt and Schütze, 2021; Mckenna et al., 2023), which follow the format outlined below:

If [PREMISE], then [HYPOTHESIS].

To make LLMs better understanding the task, we format it as Boolean questions and include indicator words such as "Question:" and "Answer:". For each choice, we automatically provide explanations for every answer by adding affirmation or negation to the propositions. As a result, the data in our counterfactual reasoning training corpus will be structured as Table 8 shown. We fine-tune our method on these templates.

967

968

969

970

971

972

973

974

975

976

977

978

979

980

981

982

983

984

985

986

987

988

989

990

991

992

E.2 prompt template for attesting hypothesis

In attesting hypothesis process, we using the same prompt discussed in §E.1, but mask the premise. Since the model may not be able to definitively determine whether the hypothesis is true or false, we use a question with three choices to evaluate the hypothesis, as (A) True, (B) Unknown, and (C) False.

In-context examples have been widely used for interacting with LLMs since Brown et al. (2020). Moreover, Wei et al. (2022) demonstrated that incorporating chain-of-thought reasoning, step-bystep explanations, into in-context examples enhances LLMs' understanding of tasks. To improve the model's comprehension of the attestation task, we include a minimal set of three examples with explanations in few-shot settings, ensuring that each choice is represented by a corresponding example. We present the manual-crafted examples in Table 9.

995

996

997

998

999

1000

1001

1002

1003 1004

1005

1006

1007

1008

1009

E.3 prompt template for inference

Similar to the hypothesis attestation experiments (§E.2), we employ the few-shot settings in our prompts for inference tasks. Specifically, we manually created four examples for the inference tasks, consisting of two positive and two negative instances. These examples are presented in Table 9.

E.4 Chain-of-Thought Prompts

Similar to the prompts used for inference (§E.3), we employ the few-shot settings in our prompts for inference tasks. Consistently, we manually created four examples for the inference tasks, each with step-by-step explanations to guide LLMs through reasoning. These examples are presented in Table 10.

F Computing Costs

In our experiments, the extraction and learning of 1010 entailment graphs from the NewsSpike corpus re-1011 1012 quired approximately 220G of CPU resources over a span of 20 hours. For the fine-tuning process, 1013 we employed four NVIDIA RTX A6000 GPUs to 1014 fine-tune the LLaMA-3-70B models, a process that 1015 took 21 hours to complete. This setup ensured effi-1016 1017 cient resource utilization while achieving optimal performance for our large-scale model fine-tuning. 1018

| | Question: If [PREMISE], then [HYPOTHESIS]. Is that true or false? |
|---------------------|---|
| | (A) True; (B) false |
| labol_True | (A) True. |
| label=1/ue | Yes, it is true. [PREMISE] entails [HYPOTHESIS]. |
| lobal-Ealas | (B) False. |
| label= <i>Fulse</i> | No, it is false. [PREMISE] does not entail [HYPOTHESIS]. |

Table 8: The table present the prompt template using in our training steps.

| A. Few-shot Examples Instantiated Prompt for Inference Task |
|---|
| If Google bought Youtube, then Google owns Youtube. Is that true or false? |
| A) True |
| B) False |
| Answer: A) True. Owning is a consequence of buying. |
| If Google owns Youtube, then Google bought Youtube. Is that true or false? |
| A) True |
| B) False |
| Answer: B) False. Owning does not imply buying, the ownership may come from other means. |
| If John went to the mall, then John drove to the mall. Is that true or false? |
| A) True |
| B) False |
| Answer: B) False. John may have gone to the mall by other means. |
| If John drove to the mall, then John went to the mall. Is that true or false? |
| A) True |
| B) False |
| Answer: A) true. Driving is a means of going to the mall. |
| If John F. Kennedy was killed in Dallas, then John F. Kennedy died in Dallas. Is that true or |
| false? |
| A) True |
| B) False |
| Answer: |
| B. Few-shot Examples Instantiated Prompt for Attesting Hypothesis |
| Google bought Youtube. Is that true or false? |
| A) True |
| B) Unknown |
| C) False |
| Answer: A) True. |
| Yoshua Bengio likes oak trees. Is that true or false? |
| A) True |
| B) Unknown |
| C) False |
| Answer: B) Unknown. |
| The sun rises from the west. Is that true or false? |
| A) True |
| B) Unknown |
| C) False |
| Answer: C) False. |
| Answer: |

Table 9: Example instantiated prompts in Few-shot settings, for the sample "PREMISE: [Google bought Youtube], HYPOTHESIS: [Google owns Youtube]". The few-shot prompts in part B are used throughout the main experiments in this paper. We also present an example of the prompts we use for the hypothesis-only measure as described in §E.2.

C. Few-shot Chain-of-Thought Prompts

If Google bought YouTube, then Google owns YouTube. Is that true or false?

A) True

B) False

Explanation:

1. Analyze Premise: the premise describe Google bought YouTube.

2. Analyze Hypothesis: the hypothesis state that Google owns the YouTube.

- 3. Reasoning: company A bought company B, it means that the company B belongs to company
- A now. So the premise entails hypothesis.

Answer: A) True.

If Google owns YouTube, then Google bought YouTube. Is that true or false?

A) True

B) False

Explanation:

1. Analyze Premise: the premise state that Google owns the YouTube now.

- 2. Analyze Hypothesis: the hypothesis describe Google bought YouTube.
- 3. Reasoning: owning does not imply buying, the ownership may come from other means. So the premise does not entail hypothesis.

Answer: B) False.

If John went to the mall, then John drove to the mall. Is that true or false?

A) True

B) False Explanation:

1. Analyze Premise: the premise state that a person go to someplace.

- 2. Analyze Hypothesis: the hypothesis describe a person went to someplace by driving car.
- 3. Reasoning: A person may have gone to the place by other ways, so the premise does not entail

hypothesis.

Answer: B) False.

If John drove to the mall, then John went to the mall. Is that true or false?

A) True

B) False

Explanation:

1. Analyze Premise: the premise describe a person went to someplace by driving car.

2. Analyze Hypothesis: the hypothesis state that a person go to someplace.

3. Reasoning: Driving present the way to went to the place, so the premise entails hypothesis. Answer: A) true.

If John F. Kennedy was killed in Dallas, then John F. Kennedy died in Dallas. Is that true or false?

A) True

B) False

Answer:

Table 10: Examples of CoT prompts, contains 3 steps: (1) analyze premise. (2) analyze hypothesis. (3) finding the relation between hypothesis and premise.